archive.today
webpage capture
Saved from https://www.linkedin.com/posts/google-ai-studio-fakes-data-deletion-vrp-shar search
no other snapshots from this url
13 Oct 2026 23:47:26 UTC
All snapshots from host www.linkedin.com
Webpage Screenshot
share download .zip report bug or abuse Buy me a coffee

Google Cloud Data Deletion Flaw Exposes User Data

Emagin Technology
61 followers
3w

The claim in this Medium post that stuck with me: you hit delete in Google AI Studio, the UI confirms it's gone, and the data is still there. Then the researcher who reported it got auto-banned from the Vulnerability Reward Program in 60 seconds.

I have no way to verify the technical claim from a blog post. But the pattern is familiar to anyone who's done a real data migration.

"Delete" almost never means delete. It means a soft-delete flag. The row stays, an `is_deleted` column flips to true, and the record lives in the table until some purge job runs — if one exists. I've pulled "deleted" customer PII out of SAP staging tables months after the business swore it was gone. NetSuite keeps deleted records in the system for exactly this reason.

For internal ops that's a rounding error. For a consumer AI product where users paste contracts, health notes, and half their company's roadmap into a prompt, the gap between the UI confirmation and the actual retention policy is the whole ballgame under GDPR Article 17.

MAGINTECHN
ECTED FO
61 followers
View Profile + Connect

Explore related topics
How to Ensure Data Integrity in AI Deployments
How Data Integrity Affects AI Performance
Tips for Understanding GDPR Compliance

The auto-ban is the part that should worry Google. If your triage bot punishes the person telling you your delete is fake, you've built a system that optimizes for silence.

When you built your last data-retention flow, did "delete" actually delete — or just flip a flag?

#DataPrivacy #GDPR #GoogleCloud #DataGovernance

Google AI Studio fakes data deletion. VRP auto-banned me in 60s for reporting it
medium.com

Like Comment Share

To view or add a comment, sign in

More Relevant Posts

Explore content categories

Career
Productivity
Finance
Soft Skills & Emotional Intelligence
Project Management
Education
Technology
Leadership
Ecommerce
User Experience
Recruitment & HR
Customer Experience
Real Estate
Marketing
Sales
Retail & Merchandising
Science
Supply Chain Management
Future Of Work
Consulting
Writing
Economics

Emagin Technology
61 followers
3mo

The detail in this writeup that stopped me: invisible Unicode characters reportedly embedded in AI coding tool prompts, potentially acting as a fingerprint on requests. Not metadata in a header you can inspect. Characters that don't render but travel with the text.

Most enterprise teams I work with treat their AI tooling like a black box they happen to pay for. The contract says your data is yours. Nobody checks whether the tool is quietly tagging the payloads it sends.

Here's where this gets real for anyone running this in a regulated shop. We spend weeks in vendor reviews arguing about data residency, PII handling, model training opt-outs. Then we copy AI-generated code into a repo and never ask what's actually in those strings. If steganographic markers were present in committed code, you could be carrying a vendor's fingerprint into your codebase without a single line of your DLP catching it, because it scans for patterns it can read.


I've sat through SAP audits where the dispute was over named-user counts. Imagine the next-gen version: a vendor proving you used their tool by pointing at invisible characters in your commits.

If you run Claude Code or Copilot at scale, has anyone on your team actually byte-inspected the output before it lands in source control?

#AIGovernance #DevSecOps #ClaudeCode #EnterpriseAI

Artificial Intelligence
Employee Experience
Workplace Trends
Fundraising
Networking
Corporate Social Responsibility
Negotiation
Communication
Engineering
Hospitality & Tourism
Business Strategy
Change Management
Organizational Culture
Design
Innovation
Event Planning
Training & Development

Show less



Claude Code Is Steganographically Marking Requests
thereallo.dev

Like Comment Share

To view or add a comment, **sign in**

Virentiq.ai
8 followers
3w

The claim in this Medium post that stuck with me: you hit delete in Google AI Studio, the UI confirms it's gone, and the data is still there. Then the researcher who reported it got auto-banned from the Vulnerability Reward Program in 60 seconds.

I have no way to verify the technical claim from a blog post. But the pattern is familiar to anyone who's done a real data migration.

"Delete" almost never means delete. It means a soft-delete flag. The row stays, an

`is_deleted` column flips to true, and the record lives in the table until some purge job runs — if one exists. I've pulled "deleted" customer PII out of SAP staging tables months after the business swore it was gone. NetSuite keeps deleted records in the system for exactly this reason.

For internal ops that's a rounding error. For a consumer AI product where users paste contracts, health notes, and half their company's roadmap into a prompt, the gap between the UI confirmation and the actual retention policy is the whole ballgame under GDPR Article 17.

The auto-ban is the part that should worry Google. If your triage bot punishes the person telling you your delete is fake, you've built a system that optimizes for silence.

When you built your last data-retention flow, did "delete" actually delete — or just flip a flag?

#DataPrivacy #GDPR #GoogleCloud #DataGovernance

Google AI Studio fakes data deletion. VRP auto-banned me in 60s for reporting it
medium.com

Like Comment Share

To view or add a comment, sign in

Emagin Technology
61 followers
2mo

The headline framing in a recent security piece stuck with me: exploit brokers paying large sums for a WordPress RCE, and the idea that someone could find a real one using a frontier AI model and only a small amount of API credits.

I don't work in offensive security. I do data and ERP integrations. But the cost curve is the same story I keep watching in my own world.

For years the moat was expertise. You needed someone who understood the SAP FICO posting logic, or the way a legacy IBM i core actually handled batch cutoffs, before you could break anything or build anything. That knowledge took years and cost real money. It gated who could even attempt the work.

That gate is thinning. When a model can chew through a codebase and surface an exploitable path for the price of a coffee, the constraint moves from "can you find it" to "how fast can everyone else find it too."

The uncomfortable part for enterprise teams: the same WordPress plugins, the same abandoned middleware, the same forgotten integration endpoints from a 2016 migration are still sitting in production. Nobody budgeted to look at them. Now the cost of looking dropped to near zero — for attackers.

What's your team actually doing to inventory the old, unglamorous code paths before someone with $25 does it for you?

#WordPressSecurity #ApplicationSecurity #AIsecurity #VulnerabilityManagement



Exploit brokers pay $500k for WordPress RCEs. I found one with GPT5.6 and $25
https://slcyber.io

Like Comment Share

To view or add a comment, sign in

Ebrahim Abdulsattar
3w

The claim in this Medium post that stuck with me: you hit delete in Google AI Studio, the UI confirms it's gone, and the data is still there. Then the researcher who reported it got auto-banned from the Vulnerability Reward Program in 60 seconds.

I have no way to verify the technical claim from a blog post. But the pattern is familiar

to anyone who's done a real data migration.

"Delete" almost never means delete. It means a soft-delete flag. The row stays, an `is_deleted` column flips to true, and the record lives in the table until some purge job runs — if one exists. I've pulled "deleted" customer PII out of SAP staging tables months after the business swore it was gone. NetSuite keeps deleted records in the system for exactly this reason.

For internal ops that's a rounding error. For a consumer AI product where users paste contracts, health notes, and half their company's roadmap into a prompt, the gap between the UI confirmation and the actual retention policy is the whole ballgame under GDPR Article 17.

The auto-ban is the part that should worry Google. If your triage bot punishes the person telling you your delete is fake, you've built a system that optimizes for silence.

When you built your last data-retention flow, did "delete" actually delete — or just flip a flag?

#DataPrivacy #GDPR #GoogleCloud #DataGovernance

Google AI Studio fakes data deletion. VRP auto-banned me in 60s for reporting it
medium.com

Like Comment Share

To view or add a comment, sign in

Emagin Technology
61 followers
5mo

Mozilla's security team crediting Anthropic's Mythos for finding high-severity Firefox bugs is interesting, but I'm more curious about what happens next.

Finding bugs is the easy part. The hard part is what every enterprise security team already knows: triage, prioritization, and actually fixing things without breaking production.

I've sat through enough vulnerability review meetings to know that a tool surfacing 200 high-severity findings doesn't make you more secure. It makes you busier. The real question is whether Mythos can differentiate between a theoretical exploit and something actually reachable in your deployed environment.

The Firefox use case is relatively clean — they control the codebase, the build pipeline, the release cycle. Try running this against a 15-year-old financial services application with custom COBOL bridges and three different middleware layers. The signal-to-noise ratio changes fast.

What I'd want to know: how much human review time did Mozilla's team spend validating Mythos findings versus their previous tooling? That's the metric that matters for enterprise adoption. Not bugs found — hours saved on false positive investigation.

If the answer is "about the same," this is incremental. If it's "we cut review time by 60%," that's a different conversation entirely.

Anyone running AI-assisted security scanning in regulated environments — what's your false positive rate looking like?

#Anthropic #Mozilla #CyberSecurity #AppSec #AIinSecurity



How Anthropic's Mythos has rewritten Firefox's approach to cybersecurity
https://techcrunch.com

Like Comment Share

To view or add a comment, sign in

Virentiq Ventures
13 followers
3w

The claim in this Medium post that stuck with me: you hit delete in Google AI Studio, the UI confirms it's gone, and the data is still there. Then the researcher who reported it got auto-banned from the Vulnerability Reward Program in 60 seconds.

I have no way to verify the technical claim from a blog post. But the pattern is familiar to anyone who's done a real data migration.

"Delete" almost never means delete. It means a soft-delete flag. The row stays, an `is_deleted` column flips to true, and the record lives in the table until some purge job runs — if one exists. I've pulled "deleted" customer PII out of SAP staging tables months after the business swore it was gone. NetSuite keeps deleted records in the system for exactly this reason.

For internal ops that's a rounding error. For a consumer AI product where users paste contracts, health notes, and half their company's roadmap into a prompt, the gap between the UI confirmation and the actual retention policy is the whole ballgame under GDPR Article 17.

The auto-ban is the part that should worry Google. If your triage bot punishes the person telling you your delete is fake, you've built a system that optimizes for silence.

When you built your last data-retention flow, did "delete" actually delete — or just flip a flag?

#DataPrivacy #GDPR #GoogleCloud #DataGovernance

Google AI Studio fakes data deletion. VRP auto-banned me in 60s for reporting it
medium.com

Like Comment Share

To view or add a comment, sign in

Emagin Technology
61 followers
2mo

Google has publicly highlighted how AI is helping surface more Chrome security bugs than ever before. Impressive number. Also the exact kind of stat that makes me nervous when I see it land in a board deck.

Here's what happens next in the enterprise. Someone reads that headline, walks into the security steering committee, and asks why our vulnerability remediation isn't running at Google speed. The answer nobody wants to hear: Chrome is one codebase with world-class telemetry and a dedicated team. Your ERP estate is SAP

FICO bolted to a 15-year-old custom IBM i billing system with integration middleware nobody fully understands anymore.


AI finding bugs is genuinely useful. Fuzzing at scale, pattern-matching against known CVE classes, triaging noise. That's real work getting faster. But "found" and "fixed and deployed to production" are separated by change control, regression testing, and a regional team in three time zones who need a maintenance window.

I've watched a single Workday patch cycle take six weeks because one downstream integration broke payroll calc for one country. AI didn't shorten that. Governance did the opposite of shortening it.

The finding gets automated. The fixing still runs at the speed of your slowest change board.

For those running patch cycles on core systems — has AI actually moved your remediation timeline, or just your detection volume?

#ApplicationSecurity #VulnerabilityManagement #ChangeManagement #EnterpriseIT



Google fixed more Chrome bugs in June than over the past two years, thanks to AI
blog.google

Like Comment Share

To view or add a comment, **sign in**

Tioga AI
1 follower
2w

On September 25, TechCrunch reported that OpenAI had disclosed an incident: its agents posted 53 user-provided images to image-hosting sites, as links that weren't publicly listed.

The part worth pausing on came next. OpenAI said it could not notify the affected users, because its technical approach and privacy policy prevent it from linking the images back to the people who provided them.

Credit where due: OpenAI disclosed the incident publicly, and says it will keep publishing anonymized accounts of incidents like this.

The disclosure could describe what happened. It could not connect the exposed data to the people it belonged to.

That raises a related question for business systems. If an agent changes or exposes data in your ERP or CRM, can you identify the affected records, the authority the agent acted under, and the customers or vendors who need to be told?

Two things to settle before agents touch those systems:

1. "Unlisted" does not, by itself, mean access-controlled. Check who can actually retrieve the data, not just whether a link is published.
2. Design for traceability before the agent acts: which records, which actions, whose authority. Decide up front how that evidence will support notification while still respecting privacy and retention limits.

If an agent exposed or changed business data tomorrow, could your systems show what it touched and on whose authority?

Source: TechCrunch, "Unsecured OpenAI agents posted 53 user images on the internet without the lab's knowledge," Sept. 25, 2026.

Tioga AI builds and reviews governed write paths for ERP and CRM systems.


Like Comment Share

To view or add a comment, **sign in**



Krishna Shukla
1w · Edited

Most tools built for AI agents return everything and let the agent sort out what matters. For LinkedIn research specifically, that means walls of raw, unstructured data an agent has to parse before it can even start being useful. So Pratyush Kum ...more



26 · 4 Comments

Like Comment Share

To view or add a comment, sign in



Katerina Zhittsova
2w

🙋‍♀️ Have you ever asked an AI assistant:
“Give me the next steps for this lead.”

Suppose the salesperson or account manager has permissions to open the lead record, but a pricing field and another team’s notes are restricted. The assistant retrieves through a broader data platform integration account. Then whose permissions will its summary actually reflect?

Yesterday, I shared a SaaS product team case working with consumer data and the GDPR limitations around retrieval: **https://lnkd.in/p/eVRDRgY3**.

This Salesforce case focuses the access question on individual records and fields. At first, it looks like a summarisation task, until we follow the data under the infra connector’s identity. With the fast pace of AI adoption across businesses, this is an aspect often overlooked.

The infra connector’s broad access must not become the user requester’s effective permissions.

An AI agent skill can include a script that performs scoped retrieval. But instructions asking the model to use it can't enforce that boundary. The host must enforce access controls and prevent the agent from changing the policy or widening credentials. So the permission check has to belong in the trusted application layer.

The requester’s identity needs to be established, and their permissions to access the relevant objects, records and fields checked - before the model’s context is assembled. Each service receiving the data must also be approved for it, including embedding services. Being allowed to read a record in Salesforce doesn’t automatically authorise sending it to a model provider.

Then the answer still needs evidence. A recorded next step is different from an invented discount promise. If retrieval is denied, the agent response must not pretend it succeeded. An extra layer of answer verification should check claims against permitted evidence. An instruction somewhere in a note, not necessarily

intended as a prompt injection, must not modify assistant's permissions.

My course-assistant project separates request checks, scoped retrieval and answer verification, with evidence kept alongside the decision. Salesforce would be a new connector and evaluation set. Access tests would cover restricted fields, revoked permissions and cached summaries, alongside useful answers for permitted users.


That's a business application I'd like to build with a CRM or product team.

The next post returns to my implemented AI assistant: where its rails checks sit, and what happened when I evaluated its four response decisions on the calibration set. All eight disposition errors had something in common.

For teams building around CRM data 🙋‍♀️: would your first failing test be a restricted field, a cached summary or a permission revoked between requests? I'd be interested in the particular constraint behind your answer.

The project behind this approach:
https://lnkd.in/eS5KEuq4

#AIEngineering #RAG #Salesforce #DataSecurity



GitHub - zhittsova/llm-rag-guardrails-ai-course-assistant: An AI course assistant that checks requests, retrieved evidence, and answers before responding. Configurable LLM/RAG guardrails, inspectable evaluation, and OpenAI-compatible APIs.
github.com

1

Like Comment Share

To view or add a comment, **sign in**

The Year of the Graph
11,831 followers
5d · Edited

A Governed Graph for Agents and Apps

Agents need enterprise context to do meaningful work. Without it, they are off-the-shelf LLMs with a thin wrapper.

That context sits behind APIs, because APIs run the business. And APIs were not built for agents:

- Responses mix sensitive data like PII with innocuous material
- Shorthand field names obscure what a field means and how to use it
- How one API relates to another is opaque, so handing an agent all of them becomes a guessing exercise

What is missing is a domain model: a governed map of a company's systems and APIs, how they relate, and who or what is allowed to see and act on them.

The case study here is Apollo's answer: extend the graph companies already use to govern access for people, and use it to govern access for agents.

GraphOS Agent Services sits between agents and enterprise systems. The graph supplies context for every interaction: the services and entities in the business, how they connect, and the policies that apply. Each agent request is translated into the right API calls, with credentials brokered for each one.

Four capabilities operate on the graph:
- Search: agents find the right data and tools
- Identity: credentials for agents acting autonomously or on behalf of a person
- Policy: field-level control over what each agent can see and do
- Audit: a log of everything that happened

Because policy applies per field, sensitive data stays out of an agent's context entirely. The policy engine makes each decision, not the model.

In practice, Intuit runs GraphOS in production and is piloting Agent Services in preview. Its marketing agents analyze spend against results and propose changes in real time, a cycle that previously took weeks, with access limited to what they need and an audit trail of every action.

The graph is also built with agents. GraphOS Factory turns REST APIs into Apollo Connectors from an OpenAPI spec, recording decisions in Git so the domain model grows as APIs change. The GraphOS MCP Server lets an agent read a live graph and answer "Is my graph healthy?" from launch history, composition errors, lint and metrics.

By **Kaitlyn Barnard**. Link in comments

#AIAgents #AgentOrchestration #GraphQL #DomainModel #MCP

--


📩 The Year of the Graph Autumn 2026 newsletter issue is out!

Meaning, Traversal, Reasoning, Action: The Graph Stack for Agentic AI. 👇

https://lnkd.in/d42aBdCP

All things **#KnowledgeGraph**, **#GraphDB**, Graph **#Analytics** / **#DataScience** / **#AI** and **#SemTech**.

Subscribe and follow to be in the know. Reach out if you'd like to be featured



5 · 1 Comment

Like Comment Share

To view or add a comment, sign in



Piyush Saluja
2w

🔐 Put policy at the tool boundary
Don't just prompt an AI agent to behave.
Enforce the policy where the action actually happens.
A model may decide:
“Call delete_customer().”
A system prompt can tell it not to.
But a production agent needs a deterministic control point that can say:

ALLOW / DENY
before the tool executes.
A particularly useful recent development is the addition of lifecycle hooks around agent execution. Amazon Bedrock AgentCore's September 2026 updates expose hooks at before_invocation, before_tool_call, after_tool_call, and after_invocation. A synchronous Lambda decision can allow or deny a tool call, while SNS/EventBridge can capture non-blocking telemetry.
AWS Documentation +1
Microsoft's Agent Framework guidance similarly treats LLM-generated tool arguments as untrusted input and recommends allow-list validation, resource limits and explicit trust boundaries.
Microsoft Learn
The architecture shift
Instead of:
User → Agent → Tool → Result
build:
User → Agent → Policy Gate → Tool → Result Validation → Agent
The policy layer can enforce:

- Tool allowlists

Which tools can this agent/user/role call?

- Argument validation

Are the model-generated parameters valid and within permitted ranges?

- Authorization

Does this user/agent actually have permission?

- Approval gates

Should a human approve this high-impact action?

- Destination restrictions

Which APIs, domains, databases or resources can be accessed?

- Rate/time/token budgets


Can the agent keep retrying indefinitely?

- Result validation

Did the tool return something unexpected, sensitive or policy-violating?
Example
The model generates:

tool = delete_database
db = customer_production
Don't rely on the model remembering:
“Never delete production data.”
Instead:
before_tool_call
→ check tool allowlist
→ validate arguments
→ check identity
→ check environment
→ require approval
→ DENY
The dangerous operation never happens.
Why this matters
Prompt-level guardrails are behavioral instructions.
Boundary enforcement is system control.
That distinction becomes increasingly important as agents gain access to MCP servers, APIs, databases, code execution and enterprise systems.
Practical implementation checklist
✅ Treat model-generated tool arguments as untrusted
✅ Validate server-side
✅ Prefer allowlists over blocklists
✅ Default high-impact tools to deny
✅ Separate read vs write permissions
✅ Require approval for irreversible actions
✅ Enforce resource/time/rate limits
✅ Validate tool outputs
✅ Log every policy decision
✅ Correlate tool calls with user/session/run IDs
✅ Test jailbreak and prompt-injection attempts in CI
The model decides what it wants to do.
Your control plane decides what it is allowed to do.
That's the architecture I would use for serious production agents.

#AIEngineering #AIAgents #AgenticAI #LLM #GenerativeAI #MCP #AIArchitecture #LLMOps #AI安全 #GenAI #Python #MachineLearning



1 · 2 Comments

Like Comment Share

To view or add a comment, **sign in**

LinkedIn © 2026 About Accessibility User Agreement Privacy Policy Cookie Policy Copyright Policy Brand Policy Guest Controls Community Guidelines

Language