

Database creation

```
CREATE DATABASE EcommerceDB;
GO
USE EcommerceDB;
GO
```

Create core tables with constraints

```
CREATE TABLE ProductPrice (
    PriceID INT PRIMARY KEY IDENTITY(1,1),
    ProductID INT NOT NULL,
    CurrentPrice DECIMAL(10,2) NOT NULL,
    EffectiveDate DATE,
    SysStartTime DATETIME2 GENERATED ALWAYS AS ROW START HIDDEN,
    SysEndTime DATETIME2 GENERATED ALWAYS AS ROW END HIDDEN,
    PERIOD FOR SYSTEM_TIME (SysStartTime, SysEndTime),
    FOREIGN KEY (ProductID) REFERENCES Product(ProductID)
) WITH (SYSTEM_VERSIONING = ON);
GO
```

```
SELECT ProductID, CurrentPrice, SysStartTime, SysEndTime
FROM ProductPrice
FOR SYSTEM_TIME ALL
WHERE ProductID = 1;
```

	ProductID	CurrentPrice	SysStartTime	SysEndTime
1	1	109.99	2026-09-21 08:23:49.1639895	9999-12-31 23:59:59.9999999
2	1	99.99	2026-09-21 08:23:49.1626793	2026-09-21 08:23:49.1639895

Add JSON columns for metadata

```
USE EcommerceDB;
GO
ALTER TABLE Product ADD Metadata JSON;
GO
ALTER TABLE Product ADD MetadataColor AS JSON_VALUE(Metadata, '$.color');
GO
CREATE NONCLUSTERED INDEX IX_Product_Metadata_Color
    ON Product (MetadataColor);
GO
UPDATE Product SET Metadata = N'{"color":"blue","size":"large","material":"cotton"}'
WHERE ProductID = 1;
UPDATE Product SET Metadata = N'{"color":"red","size":"small","material":"silk"}'
WHERE ProductID = 2;
GO

SELECT
    ProductID,
    ProductName,
    JSON_VALUE(Metadata, '$.color') AS Color,
    JSON_VALUE(Metadata, '$.size') AS Size,
    JSON_VALUE(Metadata, '$.material') AS Material
FROM Product
WHERE JSON_VALUE(Metadata, '$.color') = 'blue';
```

Resultados		Mensajes			
	ProductID	ProductName	Color	Size	Material
1	1	Wireless Mouse	blue	large	cotton

Create a partitioned order table

```
USE EcommerceDB;
GO

SELECT
    $PARTITION.PF_OrderDate(OrderDate) AS PartitionNumber,
    COUNT(*) AS OrdersInPartition,
    MIN(OrderDate) AS MinDate,
    MAX(OrderDate) AS MaxDate
FROM [Order]
GROUP BY $PARTITION.PF_OrderDate(OrderDate);
```

Resultados		Mensajes		
	PartitionNumber	OrdersInPartition	MinDate	MaxDate
1	2	2	2025-01-15	2025-02-20
2	3	1	2025-06-10	2025-06-10

Creación de detalles de orden con SEQUENCE

```
USE EcommerceDB;
GO
CREATE SEQUENCE OrderLineSequence
  START WITH 1
  INCREMENT BY 1;
CREATE TABLE OrderDetail (
  OrderLineID INT PRIMARY KEY,
  OrderID BIGINT NOT NULL,
  OrderDate DATE NOT NULL,
  ProductID INT NOT NULL,
  Quantity INT NOT NULL,
  UnitPrice DECIMAL(10,2) NOT NULL,
  LineTotal AS (Quantity * UnitPrice),
  CHECK (Quantity > 0),
  CHECK (UnitPrice > 0),
  FOREIGN KEY (OrderID, OrderDate) REFERENCES [Order](OrderID, OrderDate),
  FOREIGN KEY (ProductID) REFERENCES Product(ProductID)
);
GO
INSERT INTO OrderDetail (OrderLineID, OrderID, OrderDate, ProductID, Quantity, UnitPrice)
VALUES
  (NEXT VALUE FOR OrderLineSequence, 1, '2025-01-15', 1, 2, 99.99),
  (NEXT VALUE FOR OrderLineSequence, 1, '2025-01-15', 2, 1, 149.99),
  (NEXT VALUE FOR OrderLineSequence, 2, '2025-02-20', 1, 3, 99.99);
GO

SELECT * FROM OrderDetail;
```

	OrderLineID	OrderID	OrderDate	ProductID	Quantity	UnitPrice	LineTotal
1	1	1	2025-01-15	1	2	99.99	199.98
2	2	1	2025-01-15	2	1	149.99	149.99
3	3	2	2025-02-20	1	3	99.99	299.97

Verificar objetos de la base de datos

```
USE EcommerceDB;
GO

INSERT INTO Product (ProductName, CategoryID, SupplierID, BasePrice, StockQuantity)
VALUES ('Invalid', 1, 1, -50, 10);

INSERT INTO OrderDetail (OrderLineID, OrderID, OrderDate, ProductID, Quantity, UnitPrice)
VALUES
  (NEXT VALUE FOR OrderLineSequence, 1, '2025-01-15', 1, 2, 99.99),
  (NEXT VALUE FOR OrderLineSequence, 1, '2025-01-15', 2, 1, 149.99),
  (NEXT VALUE FOR OrderLineSequence, 2, '2025-02-20', 1, 3, 99.99);
GO
```

Mensajes

Mens. 547, Nivel 16, Estado 0, Línea 6

Instrucción INSERT en conflicto con la restricción CHECK 'CK_Product_BasePri_534D60F1'.
Se terminó la instrucción.

(3 filas afectadas)

Hora de finalización: 2026-09-21T10:42:01.7211011+02:00

