

# SymPy: Symbolic Computing in Python

Aaron Meurer<sup>1</sup>, Christopher P. Smith<sup>2</sup>, Mateusz Paprocki<sup>3</sup>, Ondřej Čertík<sup>4</sup>, Sergey B. Kirpichev<sup>5</sup>, Matthew Rocklin<sup>6</sup>, AMiT Kumar<sup>7</sup>, Sergiu Ivanov<sup>8</sup>, Jason K. Moore<sup>9</sup>, Sartaj Singh<sup>10</sup>, Thilina Rathnayake<sup>11</sup>, Sean Vig<sup>12</sup>, Brian E. Granger<sup>13</sup>, Richard P. Muller<sup>14</sup>, Francesco Bonazzi<sup>15</sup>, Harsh Gupta<sup>16</sup>, Shivam Vats<sup>17</sup>, Fredrik Johansson<sup>18</sup>, Fabian Pedregosa<sup>19</sup>, Matthew J. Curry<sup>20</sup>, Andy R. Terrel<sup>21</sup>, Štěpán Roučka<sup>22</sup>, Ashutosh Saboo<sup>23</sup>, Isuru Fernando<sup>24</sup>, Sumith Kulal<sup>25</sup>, Robert Cimrman<sup>26</sup>, and Anthony Scopatz<sup>27</sup>

<sup>1</sup>University of South Carolina, Columbia, SC 29201 (asmeurer@gmail.com).

<sup>2</sup>Polar Semiconductor, Inc., Bloomington, MN 55425 (smichr@gmail.com).

<sup>3</sup>Continuum Analytics, Inc., Austin, TX 78701 (mattpap@gmail.com).

<sup>4</sup>Los Alamos National Laboratory, Los Alamos, NM 87545 (certik@lanl.gov). The Los Alamos National Laboratory is operated by Los Alamos National Security, LLC, for the National Nuclear Security Administration of the U.S. Department of Energy under Contract No. DE-AC52-06NA25396.

<sup>5</sup>Moscow State University, Faculty of Physics, Leninskie Gory, Moscow, 119991, Russia (skirpichev@gmail.com).

<sup>6</sup>Continuum Analytics, Inc., Austin, TX 78701 (mrocklin@gmail.com).

<sup>7</sup>Delhi Technological University, Shahbad Daultpur, Bawana Road, New Delhi 110042, India (dtu.amit@gmail.com).

<sup>8</sup>Université Paris Est Créteil, 61 av. Général de Gaulle, 94010 Créteil, France (sergiu.ivanov@u-pec.fr).

<sup>9</sup>University of California, Davis, Davis, CA 95616 (jkm@ucdavis.edu).

<sup>10</sup>Indian Institute of Technology (BHU), Varanasi, Uttar Pradesh 221005, India (singhsartaj94@gmail.com).

<sup>11</sup>University of Moratuwa, Bandaranayake Mawatha, Katubedda, Moratuwa 10400, Sri Lanka (thilinarmtb.10@cse.mrt.ac.lk).

<sup>12</sup>University of Illinois at Urbana-Champaign, Urbana, IL 61801 (sean.v.775@gmail.com).

<sup>13</sup>California Polytechnic State University, San Luis Obispo, CA 93407 (ellisonbg@gmail.com).

<sup>14</sup>Center for Computing Research, Sandia National Laboratories, Albuquerque, NM 87185 (rmuller@sandia.gov). Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy's National Nuclear Security Administration under Contract DE-AC04-94AL85000.

<sup>15</sup>Max Planck Institute of Colloids and Interfaces, Department of Theory and Bio-Systems, Science Park Golm, 14424 Potsdam, Germany (francesco.bonazzi@mpikg.mpg.de).

<sup>16</sup>Indian Institute of Technology Kharagpur, Kharagpur, West Bengal 721302, India (hargup@protonmail.com).

<sup>17</sup>Indian Institute of Technology Kharagpur, Kharagpur, West Bengal 721302, India (shivamvats.iitkgp@gmail.com).

<sup>18</sup>INRIA Bordeaux-Sud-Ouest – LFANT project-team, 200 Avenue de la Vieille Tour, 33405 Talence, France (fredrik.johansson@gmail.com).

<sup>19</sup>INRIA – SIERRA project-team, 2 Rue Simone IFF, 75012 Paris, France (f@bianp.net).

<sup>20</sup>Department of Physics and Astronomy, University of New Mexico, Albuquerque, NM 87131 (mattjcurry@gmail.com).

<sup>21</sup>Fashion Metric, Inc, Austin, TX 78681 (andy.terrel@gmail.com).

<sup>22</sup>Faculty of Mathematics and Physics, Charles University in Prague, V Holešovičkách 2, 180 00 Praha, Czech Republic (stepan.roucka@mff.cuni.cz).

<sup>23</sup>Birla Institute of Technology and Science, Pilani, K.K. Birla Goa Campus, NH 17B Bypass Road, Zuarinagar, Sancoale, Goa 403726, India (ashutosh.saboo96@gmail.com).

<sup>24</sup>University of Moratuwa, Bandaranayake Mawatha, Katubedda, Moratuwa 10400, Sri Lanka (isuru.11@cse.mrt.ac.lk).  
<sup>25</sup>Indian Institute of Technology Bombay, Powai, Mumbai, Maharashtra 400076, India (sumith@cse.iitb.ac.in).  
<sup>26</sup>New Technologies – Research Centre, University of West Bohemia, Univerzitní 8, 306 14 Plzeň, Czech Republic (cimirman3@ntc.zcu.cz).  
<sup>27</sup>University of South Carolina, Columbia, SC 29201 (scopatz@cec.sc.edu).

## ABSTRACT

SymPy is an open source computer algebra system written in pure Python. It is built with a focus on extensibility and ease of use, through both interactive and programmatic applications. These characteristics have led SymPy to become a popular symbolic library for the scientific Python ecosystem. This paper presents the architecture of SymPy, a description of its features, and a discussion of select domain specific submodules. The supplementary materials provide additional examples and further outline details of the architecture and features of SymPy.

Keywords: symbolic, Python, computer algebra system

## 1 INTRODUCTION

SymPy is a full featured computer algebra system (CAS) written in the Python [30] programming language. It is free and open source software, licensed under the 3-clause BSD license [45]. The SymPy project was started by Ondřej Čertík in 2005, and it has since grown to over 500 contributors. Currently, SymPy is developed on GitHub using a bazaar community model [41]. The accessibility of the codebase and the open community model allow SymPy to rapidly respond to the needs of users and developers.

Python is a dynamically typed programming language that has a focus on ease of use and readability.<sup>1</sup> Due in part to this focus, it has become a popular language for scientific computing and data science, with a broad ecosystem of libraries [35]. SymPy is itself used by many libraries and tools to support research within a variety of domains, such as SageMath [54] (pure and applied mathematics), yt [59] (astronomy and astrophysics), PyDy [18] (multibody dynamics), and SfePy [10] (finite elements).

Unlike many CAS's, SymPy does not invent its own programming language. Python itself is used both for the internal implementation and end user interaction. By using the operator overloading functionality of Python, SymPy follows the embedded domain specific language paradigm proposed by Hudak [23]. The exclusive usage of a single programming language makes it easier for people already familiar with that language to use or develop SymPy. Simultaneously, it enables developers to focus on mathematics, rather than language design. SymPy officially supports Python 2.6, 2.7 and 3.2–3.5.

SymPy is designed with a strong focus on usability as a library. Extensibility is important in its application program interface (API) design. Thus, SymPy makes no attempt to extend the Python language itself. The goal is for users of SymPy to be able to include SymPy alongside other Python libraries in their workflow, whether that be in an interactive environment or as a programmatic part in a larger system.

As a library, SymPy does not have a built-in graphical user interface (GUI). However, SymPy exposes a rich interactive display system, and supports registering display formatters with Jupyter [27] frontends, including the Notebook and Qt Console, which will render SymPy expressions using MathJax [9] or L<sup>A</sup>T<sub>E</sub>X.

The remainder of this paper discusses key components of the SymPy library. Section 2 enumerates the features of SymPy and takes a closer look at some of the important ones. The section 3 looks at the numerical features of SymPy and its dependency library, mpmath.

---

<sup>1</sup>This paper assumes a moderate familiarity with the Python programming language.

100 Section 4 looks at the domain specific physics submodules for performing symbolic and numerical  
101 calculations in classical mechanics and quantum mechanics. Section 5 discusses the architecture  
102 of SymPy. Conclusions and future directions for SymPy are given in section 7. All examples in  
103 this paper use SymPy version 1.0 and mpmath version 0.19.

104 The following statement imports all SymPy functions into the global Python namespace.<sup>2</sup>  
105 From here on, all examples in this paper assume that this statement has been executed:<sup>3</sup>

```
106 >>> from sympy import *
```

107 All examples could be tested on the SymPy Live instance, that is an online Python shell,  
108 which uses the Google App Engine to execute SymPy code. The SymPy Live is integrated in the  
109 SymPy documentation system at <http://docs.sympy.org>.

## 110 2 OVERVIEW OF CAPABILITIES

111 This section gives a basic introduction of SymPy, and lists its features. A few features—  
112 assumptions, simplification, calculus, polynomials, printers, solvers, and matrices—are core  
113 components of SymPy and are discussed in depth. Many other features are discussed in depth in  
114 the supplementary material.

### 115 2.1 Basic Usage

116 Symbolic variables, called symbols, must be defined and assigned to Python variables before they  
117 can be used. This is typically done through the `symbols` function, which may create multiple  
118 symbols in a single function call. For instance,

```
119 >>> x, y, z = symbols('x y z')
```

120 creates three symbols representing variables named  $x$ ,  $y$ , and  $z$ . In this particular instance, these  
121 symbols are all assigned to Python variables of the same name. However, the user is free to  
122 assign them to different Python variables, while representing the same symbol, such as `a`, `b`,  
123 `c = symbols('x y z')`. In order to minimize potential confusion, though, all examples in this  
124 paper will assume that the symbols  $x$ ,  $y$ , and  $z$  have been assigned to Python variables identical  
125 to their symbolic names.

126 Expressions are created from symbols using Python's mathematical syntax. For instance, the  
127 following Python code creates the expression  $(x^2 - 2x + 3)/y$ . Note that the expression remains  
128 unevaluated: it is represented symbolically.

```
129 >>> (x**2 - 2*x + 3)/y  
130 (x**2 - 2*x + 3)/y
```

131 Importantly, SymPy expressions are immutable. This simplifies the design of SymPy by  
132 allowing expression interning. It also enables expressions to be hashed, that is used to implement  
133 caching in SymPy.

### 134 2.2 List of Features

135 Although SymPy's extensive feature set cannot be covered in-depth in this paper, calculus and  
136 other bedrock areas are discussed in their own subsections. Additionally, Table 1 gives a compact  
137 listing of all major capabilities present in the SymPy codebase. This grants a sampling from the  
138 breadth of topics and application domains that SymPy services. Unless stated otherwise, all  
139 features noted in Table 1 are symbolic in nature. Numeric features are discussed in Section 3.

---

<sup>2</sup>`import *` has been used here to aid the readability of the paper, but is best to avoid such wildcard import statements in production code, as they make it unclear which names are present in the namespace. Furthermore, imported names could clash with already existing imports from another package. For example, SymPy, the standard Python `math` library, and NumPy all define the `exp` function, but only the SymPy one will work with SymPy symbolic expressions.

<sup>3</sup> The three greater-than signs denote the user input for the Python interactive session, with the result, if there is one, shown on the next line.

**Table 1.** SymPy Features and Descriptions

Feature (submodules)	Description
Calculus ( <code>sympy.core</code> , <code>sympy.series</code> , <code>sympy.integrals</code> )	Algorithms for computing derivatives, integrals, and limits.
Category Theory ( <code>sympy.categories</code> )	Representation of objects, morphisms, and diagrams. Tools for drawing diagrams with Xy-pic.
Code Generation ( <code>sympy.printing</code> , <code>sympy.codegen</code> )	Generation of compilable and executable code in a variety of different programming languages from expressions directly. Target languages include C, Fortran, Julia, JavaScript, Mathematica, MATLAB and Octave, Python, and Theano.
Combinatorics & Group Theory ( <code>sympy.combinatorics</code> )	Permutations, combinations, partitions, subsets, various permutation groups (such as polyhedral, Rubik, symmetric, and others), Gray codes [34], and Prufer sequences [4].
Concrete Math ( <code>sympy.concrete</code> )	Summation, products, tools for determining whether summation and product expressions are convergent, absolutely convergent, hypergeometric, and for determining other properties; computation of Gosper's normal form [40] for two univariate polynomials.
Cryptography ( <code>sympy.crypto</code> )	Block and stream ciphers, including shift, Affine, substitution, Vigenère's, Hill's, bifid, RSA, Kid RSA, linear-feedback shift registers, and Elgamal encryption.
Differential Geometry ( <code>sympy.diffgeom</code> )	Representations of manifolds, metrics, tensor products, and coordinate systems in Riemannian and pseudo-Riemannian geometries [48].
Geometry ( <code>sympy.geometry</code> )	Representations of 2D geometrical entities, such as lines and circles. Enables queries on these entities, such as asking the area of an ellipse, checking for collinearity of a set of points, or finding the intersection between objects.
Lie Algebras ( <code>sympy.liealgebras</code> )	Representations of Lie algebras and root systems.
Logic ( <code>sympy.logic</code> )	Boolean expressions, equivalence testing, satisfiability, and normal forms.
Matrices ( <code>sympy.matrices</code> )	Tools for creating matrices of symbols and expressions. Both sparse and dense representations, as well as symbolic linear algebraic operations (e.g., inversion and factorization), are supported.
Matrix Expressions ( <code>sympy.matrices.expressions</code> )	Matrices with symbolic dimensions (unspecified entries). Block matrices.
Number Theory ( <code>sympy.ntheory</code> )	Prime number generation, primality testing, integer factorization, continued fractions, Egyptian fractions, modular arithmetic, quadratic residues, partitions, binomial and multinomial coefficients, prime number tools, hexadecimal digits of $\pi$ , and integer factorization.
Plotting ( <code>sympy.plotting</code> )	Hooks for visualizing expressions via matplotlib [24] or as text drawings when lacking a graphical back-end. 2D function plotting, 3D function plotting, and 2D implicit function plotting are supported.
Polynomials ( <code>sympy.polys</code> )	Polynomial algebras over various coefficient domains. Functionality ranges from simple operations (e.g., polynomial division) to advanced computations (e.g., Gröbner bases [1] and multivariate factorization over algebraic number domains).

Printing ( <code>sympy.printing</code> )	Functions for printing SymPy expressions in the terminal with ASCII or Unicode characters and converting SymPy expressions to $\text{\LaTeX}$ and MathML.
Quantum Mechanics ( <code>sympy.physics.quantum</code> )	Quantum states, bra-ket notation, operators, basis sets, representations, tensor products, inner products, outer products, commutators, anticommutators, and specific quantum system implementations.
Series ( <code>sympy.series</code> )	Series expansion, sequences, and limits of sequences. This includes Taylor, Laurent, and Puiseux series as well as special series, such as Fourier and formal power series.
Sets ( <code>sympy.sets</code> )	Representations of empty, finite, and infinite sets (including special sets such as the natural, integer, and complex numbers). Operations on sets such as union, intersection, Cartesian product, and building sets from other sets are supported.
Simplification ( <code>sympy.simplify</code> )	Functions for manipulating and simplifying expressions. Includes algorithms for simplifying hypergeometric functions, trigonometric expressions, rational functions, combinatorial functions, square root denesting, and common subexpression elimination.
Solvers ( <code>sympy.solvers</code> )	Functions for symbolically solving equations, systems of equations, both linear and non-linear, inequalities, ordinary differential equations, partial differential equations, Diophantine equations, and recurrence relations.
Special Functions ( <code>sympy.functions</code> )	Implementations of a number of well known special functions, including Dirac delta, Gamma, Beta, Gauss error functions, Fresnel integrals, Exponential integrals, Logarithmic integrals, Trigonometric integrals, Bessel, Hankel, Airy, B-spline, Riemann Zeta, Dirichlet eta, polylogarithm, Lerch transcendent, hypergeometric, elliptic integrals, Mathieu, Jacobi polynomials, Gegenbauer polynomial, Chebyshev polynomial, Legendre polynomial, Hermite polynomial, Laguerre polynomial, and spherical harmonic functions.
Statistics ( <code>sympy.stats</code> )	Support for a random variable type as well as the ability to declare this variable from prebuilt distribution functions such as Normal, Exponential, Coin, Die, and other custom distributions [44].
Tensors ( <code>sympy.tensor</code> )	Symbolic manipulation of indexed objects.
Vectors ( <code>sympy.vector</code> )	Basic operations on vectors and differential calculus with respect to 3D Cartesian coordinate systems.

## 2.3 Assumptions

The assumptions system allows users to specify that symbols have certain common mathematical properties, such as being positive, imaginary, or integral. SymPy is careful to never perform simplifications on an expression unless the assumptions allow them. For instance, the identity  $\sqrt{t^2} = t$  holds if  $t$  is nonnegative ( $t \geq 0$ ). However, for general complex  $t$ , no such identity holds.

By default, SymPy performs all calculations assuming that symbols are complex valued. This assumption makes it easier to treat mathematical problems in full generality.

```
>>> t = Symbol('t')
>>> sqrt(t**2)
sqrt(t**2)
```

By assuming the most general case, that  $t$  is complex by default, SymPy avoids performing mathematically invalid operations. However, in many cases users will wish to simplify expressions containing terms like  $\sqrt{t^2}$ .

Assumptions are set on `Symbol` objects when they are created. For instance `Symbol('t', positive=True)` will create a symbol named `t` that is assumed to be positive.

```
>>> t = Symbol('t', positive=True)
>>> sqrt(t**2)
t
```

Some of the common assumptions that SymPy allows are `positive`, `negative`, `real`, `nonpositive`, `integer`, `prime` and `commutative`.<sup>4</sup> Assumptions on any object can be checked with the `is_assumption` attributes, like `t.is_positive`.

Assumptions are only needed to restrict a domain so that certain simplifications can be performed. They are not required to make the domain match the input of a function. For instance, one can create the object  $\sum_{n=0}^m f(n)$  as `Sum(f(n), (n, 0, m))` without setting `integer=True` when creating the `Symbol` object `n`.

The assumptions system additionally has deductive capabilities. The assumptions use a three-valued logic using the Python built in objects `True`, `False`, and `None`. Note that `False` is returned if the SymPy object doesn't or can't have the assumption. For example, both `I.is_real` and `I.is_prime` return `False` for the imaginary unit `I`.

`None` represents the “unknown” case. This could mean that given assumptions do not unambiguously specify the truth of an attribute. For instance, `Symbol('x', real=True).is_positive` will give `None` because a real symbol might be positive or negative. The `None` could also mean that not enough is known or implemented to compute the given fact. For instance, `(pi + E).is_irrational` gives `None`—indeed, the rationality of  $\pi + e$  is an open problem in mathematics [29].

Basic implications between the facts are used to deduce assumptions. Deductions are made using the Rete algorithm [12].<sup>5</sup> For instance, the assumptions system knows that being an integer implies being rational.

```
>>> i = Symbol('i', integer=True)
>>> i.is_rational
True
```

Furthermore, expressions compute the assumptions on themselves based on the assumptions of their arguments. For instance, if `x` and `y` are both created with `positive=True`, then `(x + y).is_positive` will be `True` whereas `(x - y).is_positive` will be `None`.

## 2.4 Simplification

The generic way to simplify an expression is by calling the `simplify` function. It must be emphasized that simplification is not a rigorously defined mathematical operation [32]. The `simplify` function applies several simplification routines along with heuristics to make the output expression “simple”.<sup>6</sup>

It is often preferable to apply more directed simplification functions. These apply very specific rules to the input expression and are typically able to make guarantees about the output. For instance, the `factor` function, given a polynomial with rational coefficients in several variables, is guaranteed to produce a factorization into irreducible factors. Table 2 lists common simplification functions.

**Table 2.** Some SymPy Simplification Functions

<sup>4</sup>SymPy assumes that two expressions  $A$  and  $B$  commute with each other multiplicatively, that is,  $A \cdot B = B \cdot A$ , unless they both have `commutative=False`. Many algorithms in SymPy require special consideration to work correctly with noncommutative products.

<sup>5</sup>For historical reasons, this algorithm is distinct from the `sympy.logic` submodule, which is discussed in the supplementary material. SymPy has an experimental assumptions system which stores facts separate from objects, and uses `sympy.logic` and a SAT solver for deduction. We will not discuss this system here.

<sup>6</sup>The `measure` parameter of the `simplify` function lets the user specify the Python function used to determine how complex an expression is. The default measure function returns the total number of operations in the expression.

<code>expand</code>	expand the expression
<code>factor</code>	factor a polynomial into irreducibles
<code>collect</code>	collect polynomial coefficients
<code>cancel</code>	rewrite a rational function as $p/q$ with common factors canceled
<code>apart</code>	compute the partial fraction decomposition of a rational function
<code>trigsimp</code>	simplify trigonometric expressions [17]
<code>hyperexpand</code>	expand hypergeometric functions [42, 43]

---

## 2.5 Calculus

SymPy provides all the basic operations of calculus, such as calculating limits, derivatives, integrals, or summations.

Limits are computed with the `limit` function, using the Gruntz algorithm [21] for computing symbolic limits and heuristics (a description of the Gruntz algorithm may be found in the supplement). For example, the following computes  $\lim_{x \rightarrow \infty} x \sin(\frac{1}{x}) = 1$ . Note that SymPy denotes  $\infty$  as `oo`.

```
>>> limit(x*sin(1/x), x, oo)
1
```

As a more complex example, SymPy computes

$$\lim_{x \rightarrow 0} \left( 2e^{\frac{1 - \cos(x)}{\sin(x)}} - 1 \right)^{\frac{\sinh(x)}{\operatorname{atan}^2(x)}} = e.$$

```
>>> limit((2*E**((1-cos(x))/sin(x))-1)**(sinh(x)/atan(x)**2), x, 0)
E
```

Derivatives are computed with the `diff` function, which recursively uses the various differentiation rules.

```
>>> diff(sin(x)*exp(x), x)
exp(x)*sin(x) + exp(x)*cos(x)
```

Integrals are calculated with the `integrate` function. SymPy implements a combination of the Risch algorithm [7], table lookups, a reimplementation of Manuel Bronstein’s “Poor Man’s Integrator” [6], and an algorithm for computing integrals based on Meijer G-functions [42, 43]. These allow SymPy to compute a wide variety of indefinite and definite integrals. The Meijer G-function algorithm and the Risch algorithm are respectively demonstrated below by the computation of

$$\int_0^\infty e^{-st} \log(t) dt = -\frac{\log(s) + \gamma}{s}$$

and

$$\int \frac{-2x^2(\log(x) + 1)e^{x^2} + (e^{x^2} + 1)^2}{x(e^{x^2} + 1)^2(\log(x) + 1)} dx = \log(\log(x) + 1) + \frac{1}{e^{x^2} + 1}.$$

```
>>> s, t = symbols('s t', positive=True)
>>> integrate(exp(-s*t)*log(t), (t, 0, oo)).simplify()
-(log(s) + EulerGamma)/s
>>> integrate((-2*x**2*(log(x) + 1)*exp(x**2) +
... (exp(x**2) + 1)**2)/(x*(exp(x**2) + 1)**2*(log(x) + 1)), x)
log(log(x) + 1) + 1/(exp(x**2) + 1)
```

Summations are computed with `summation` using a combination of Gosper’s algorithm [20], an algorithm that uses Meijer G-functions [42, 43], and heuristics. Products are computed with `product` function via a suite of heuristics.

```

218 >>> i, n = symbols('i n')
219 >>> summation(2**i, (i, 0, n - 1))
220 2**n - 1
221 >>> summation(i*factorial(i), (i, 1, n))
222 n*factorial(n) + factorial(n) - 1

```

Series expansions are computed with the `series` function. This example computes the power series of  $\sin(x)$  around  $x = 0$  up to  $x^6$ .

```

225 >>> series(sin(x), x, 0, 6)
226 x - x**3/6 + x**5/120 + O(x**6)

```

The supplementary material discusses series expansions methods in more depth.

Integrals, derivatives, summations, products, and limits that cannot be computed return unevaluated objects. These can also be created directly if the user chooses.

```

230 >>> integrate(x**x, x)
231 Integral(x**x, x)
232 >>> Sum(2**i, (i, 0, n - 1))
233 Sum(2**i, (i, 0, n - 1))

```

## 2.6 Polynomials

SymPy implements a suite of algorithms for polynomial manipulation, which ranges from relatively simple algorithms for doing arithmetic of polynomials, to advanced methods for factoring multivariate polynomials into irreducibles, symbolically determining real and complex root isolation intervals, or computing Gröbner bases.

Polynomial manipulation is useful in its own right. Within SymPy, though, it is mostly used indirectly as a tool in other areas of the library. In fact, many mathematical problems in symbolic computing are first expressed using entities from the symbolic core, preprocessed, and then transformed into a problem in the polynomial algebra, where generic and efficient algorithms are used to solve the problem. The solutions to the original problem are subsequently recovered from the results. This is a common scheme in symbolic integration or summation algorithms.

SymPy implements dense and sparse polynomial representations.<sup>7</sup> Both are used in the univariate and multivariate cases. The dense representation is the default for univariate polynomials. For multivariate polynomials, the choice of representation is based on the application. The most common case for the sparse representation is algorithms for computing Gröbner bases (Buchberger, F4, and F5) [8, 13, 14]. This is because different monomial orderings can be expressed easily in this representation. However, algorithms for computing multivariate GCDs or factorizations, at least those currently implemented in SymPy [36], are better expressed when the representation is dense. The dense multivariate representation is specifically a recursively-dense representation, where polynomials in  $K[x_0, x_1, \dots, x_n]$  are viewed as a polynomials in  $K[x_0][x_1] \dots [x_n]$ . Note that despite this, the coefficient domain  $K$ , can be a multivariate polynomial domain as well. The dense recursive representation in Python gets inefficient as the number of variables increases.

Some examples for the `sympy.polys` submodule can be found in the supplement.

## 2.7 Printers

SymPy has a rich collection of expression printers. By default, an interactive Python session will render the `str` form of an expression, which has been used in all the examples in this paper so far. The `str` form of an expression is valid Python and roughly matches what a user would type to enter the expression.<sup>8</sup>

<sup>7</sup>In a dense representation, the coefficients for all terms up to the degree of each variable are stored in memory. In a sparse representation, only the nonzero coefficients are stored.

<sup>8</sup>Many Python libraries distinguish the `str` form of an object, which is meant to be human-readable, and the `repr` form, which is meant to be valid Python that recreates the object. In SymPy, `str(expr) == repr(expr)`. In other words, the string representation of an expression is designed to be compact, human-readable, and valid Python code that could be used to recreate the expression. As it was noted in section 5.1, the `srepr` function prints the exact, verbose form of an expression.



```

263 >>> phi0 = Symbol('phi0')
264 >>> str(Integral(sqrt(phi0), phi0))
265 'Integral(sqrt(phi0), phi0)'

```

A two-dimensional (2D) textual representation of the expression can be printed with monospace fonts via `pprint`. Unicode characters are used for rendering mathematical symbols such as integral signs, square roots, and parentheses. Greek letters and subscripts in symbol names that have Unicode code points associated are also rendered automatically.

```

266 >>> pprint(Integral(sqrt(phi0 + 1), phi0))
267
268
269

```

$$\int \sqrt{\varphi_0 + 1} \, d(\varphi_0)$$

Alternately, the `use_unicode=False` flag can be set, which causes the expression to be printed using only ASCII characters.

```

273 >>> pprint(Integral(sqrt(phi0 + 1), phi0), use_unicode=False)
274 /
275 |
276 | _____
277 | \ /  phi0 + 1  d(phi0)
278 |
279 /

```

The function `latex` returns a L<sup>A</sup>T<sub>E</sub>X representation of an expression.

```

281 >>> print(latex(Integral(sqrt(phi0 + 1), phi0)))
282 \int \sqrt{\phi_{0} + 1}\, d\phi_{0}

```

Users are encouraged to run the `init_printing` function at the beginning of interactive sessions, which automatically enables the best pretty printing supported by their environment. In the Jupyter Notebook or Qt Console [38], the L<sup>A</sup>T<sub>E</sub>X printer is used to render expressions using MathJax or L<sup>A</sup>T<sub>E</sub>X, if it is installed on the system. The 2D text representation is used otherwise.

Other printers such as MathML are also available. SymPy uses an extensible printer subsystem for customizing any given printer, and allows custom objects to define their printing behavior for any printer. The code generation functionality of SymPy relies on this subsystem to convert expressions into code in various target programming languages.

## 2.8 Solvers

SymPy has equation solvers that can handle ordinary differential equations, recurrence relationships, Diophantine equations<sup>9</sup>, and algebraic equations. There is also rudimentary support for simple partial differential equations.

There are two functions for solving algebraic equations in SymPy: `solve` and `solveset`. `solveset` has several design changes with respect to the older `solve` function. This distinction is present in order to resolve the usability issues with the previous `solve` function API while maintaining backward compatibility with earlier versions of SymPy. `solveset` only requires essential input information from the user. The function signatures of `solve` and `solveset` are

```

301 solve(f, *symbols, **flags)
302 solveset(f, symbol, domain=S.Complexes)

```

The `domain` parameter can be any set from the `sympy.sets` module (see the supplementary material for details on `sympy.sets`), but is typically either `S.Complexes` (the default) or `S.Reals`; the latter causes `solveset` to only return real solutions.

<sup>9</sup>See the supplementary material for an in depth discussion on the Diophantine submodule.

An important difference between the two functions is that the output API of `solve` varies with input (sometimes returning a Python list and sometimes a Python dictionary) whereas `solveset` always returns a SymPy set object.

Both functions implicitly assume that expressions are equal to 0. For instance, `solveset(x - 1, x)` solves  $x - 1 = 0$  for  $x$ .

`solveset` is under active development as a planned replacement for `solve`. There are certain features which are implemented in `solve` that are not yet implemented in `solveset`, including multivariate systems, and some transcendental equations.

More examples of `solveset` and `solve` can be found in the supplement.

## 2.9 Matrices

Besides being an important feature in its own right, computations on matrices with symbolic entries are important for many algorithms within SymPy. The following code shows some basic usage of the `Matrix` class.

```
>>> A = Matrix([[x, x + y], [y, x]])
>>> A
Matrix([
[x, x + y],
[y,      x]])
```

SymPy matrices support common symbolic linear algebra manipulations, including matrix addition, multiplication, exponentiation, computing determinants, solving linear systems, and computing inverses using LU decomposition, LDL decomposition, Gauss-Jordan elimination, Cholesky decomposition, Moore-Penrose pseudoinverse, singular values, and adjugate matrix.

All operations are performed symbolically. For instance, eigenvalues are computed by generating the characteristic polynomial using the Berkowitz algorithm and then solving it using polynomial routines.

```
>>> A.eigenvals()
{x - sqrt(y*(x + y)): 1, x + sqrt(y*(x + y)): 1}
```

Internally these matrices store the elements as Lists of Lists (LIL), meaning the matrix is stored as a list of lists of entries (effectively, the input format used to create the matrix `A` above), making it a dense representation.<sup>10</sup> For storing sparse matrices, the `SparseMatrix` class can be used. Sparse matrices store their elements in Dictionary of Keys (DOK) format, meaning entries are stored as (row, column) pairs mapping to the elements.

SymPy also supports matrices with symbolic dimension values. `MatrixSymbol` represents a matrix with dimensions  $m \times n$ , where  $m$  and  $n$  can be symbolic. Matrix addition and multiplication, scalar operations, matrix inverse, and transpose are stored symbolically as matrix expressions.

Block matrices are also implemented in SymPy. `BlockMatrix` elements can be any matrix expression, including explicit matrices, matrix symbols, and other block matrices. All functionalities of matrix expressions are also present in `BlockMatrix`.

When symbolic matrices are combined with the assumptions submodule for logical inference, they provide powerful reasoning over invertibility, semi-definiteness, orthogonality, etc., which are valuable in the construction of numerical linear algebra systems.

More examples for `Matrix` and `BlockMatrix` may be found in the supplement.

## 3 NUMERICS

While SymPy primarily focuses on symbolics, it is impossible to have a complete symbolic system without the ability to numerically evaluate expressions. Many operations directly use numerical evaluation, such as plotting a function, or solving an equation numerically. Beyond this, certain purely symbolic operations require numerical evaluation to effectively compute. For instance,

<sup>10</sup>Similar to the polynomials submodule, dense here means that all entries are stored in memory, contrasted with a sparse representation where only nonzero entries are stored.

determining the truth value of  $e + 1 > \pi$  is most conveniently done by numerically evaluating both sides of the inequality and checking which is larger.

### 3.1 Floating-Point Numbers

Floating-point numbers in SymPy are implemented by the `Float` class, which represents an arbitrary-precision binary floating-point number by storing its value and precision (in bits). This representation is distinct from the Python built-in `float` type, which is a wrapper around machine `double` types and uses a fixed precision (53-bit).

Because Python `float` literals are limited in precision, strings should be used to input precise decimal values:

```
>>> Float(1.1)
1.1000000000000000
>>> Float(1.1, 30) # precision equivalent to 30 digits
1.100000000000000008881784197001
>>> Float("1.1", 30)
1.10000000000000000000000000000000
```

The `evalf` method converts a constant symbolic expression to a `Float` with the specified precision, here 25 digits:

```
>>> (pi + 1).evalf(25)
4.141592653589793238462643
```

`Float` numbers do not track their accuracy, and should be used with caution within symbolic expressions since familiar dangers of floating-point arithmetic apply [19]. A notorious case is that of catastrophic cancellation:

```
>>> cos(exp(-100)).evalf(25) - 1
0
```

Applying the `evalf` method to the whole expression solves this problem. Internally, `evalf` estimates the number of accurate bits of the floating-point approximation for each sub-expression, and adaptively increases the working precision until the estimated accuracy of the final result matches the sought number of decimal digits:

```
>>> (cos(exp(-100)) - 1).evalf(25)
-6.919482633683687653243407e-88
```

The `evalf` method works with complex numbers and supports more complicated expressions, such as special functions, infinite series, and integrals. The internal error tracking does not provide rigorous error bounds (in the sense of interval arithmetic) and cannot be used to accurately track uncertainty in measurement data; the sole purpose is to mitigate loss of accuracy that typically occurs when converting symbolic expressions to numerical values.

### 3.2 The mpmath Library

The implementation of arbitrary-precision floating-point arithmetic is supplied by the `mpmath` library [25]. Originally, it was developed as a SymPy submodule but has subsequently been moved to a standalone pure-Python package. The basic datatypes in `mpmath` are `mpf` and `mpc`, which respectively act as multiprecision substitutes for Python's `float` and `complex`. The floating-point precision is controlled by a global context:

```
>>> import mpmath
>>> mpmath.mp.dps = 30 # 30 digits of precision
>>> mpmath.mpf("0.1") + mpmath.exp(-50)
mpf('0.10000000000000000000000000000000192874984794')
>>> print(_) # pretty-printed
0.10000000000000000000000000000000192874985
```

Like SymPy, mpmath is a pure Python library. A design decision of SymPy is to keep it and its required dependencies pure Python. This is a primary advantage of mpmath over other multiple precision libraries such as GNU MPFR [16], which is much more feature-rich and fast. Like SymPy, mpmath is also BSD licensed (GNU MPFR is licensed under the GNU Lesser General Public License [45]).

Internally, mpmath represents a floating-point number  $(-1)^s x \cdot 2^y$  by a tuple  $(s, x, y, b)$  where  $x$  and  $y$  are arbitrary-size Python integers and the redundant integer  $b$  stores the bit length of  $x$  for quick access. If GMPY [22] is installed, mpmath automatically uses the `gmpy.mpz` type for  $x$ , and GMPY methods for rounding-related operations, improving performance.

Most mpmath and SymPy functions use the same naming scheme, although this is not true in every case. For example, the symbolic SymPy summation expression `Sum(f(x), (x, a, b))` representing  $\sum_{x=a}^b f(x)$  is represented in mpmath as `nsum(f, (a, b))`, where `f` is a numeric Python function.

The mpmath library supports special functions, root-finding, linear algebra, polynomial approximation, and numerical computation of limits, derivatives, integrals, infinite series, and solving ODEs. All features work in arbitrary precision and use algorithms that allow computing hundreds of digits rapidly (except in degenerate cases).

The double exponential (tanh-sinh) quadrature is used for numerical integration by default. For smooth integrands, this algorithm usually converges extremely rapidly, even when the integration interval is infinite or singularities are present at the endpoints [50, 2]. However, for good performance, singularities in the middle of the interval must be specified by the user. To evaluate slowly converging limits and infinite series, mpmath automatically tries Richardson extrapolation and the Shanks transformation (Euler-Maclaurin summation can also be used) [3]. A function to evaluate oscillatory integrals by means of convergence acceleration is also available.

A wide array of higher mathematical functions is implemented with full support for complex values of all parameters and arguments, including complete and incomplete gamma functions, Bessel functions, orthogonal polynomials, elliptic functions and integrals, zeta and polylogarithm functions, the generalized hypergeometric function, and the Meijer G-function. The Meijer G-function instance  $G_{1,3}^{3,0}(0; \frac{1}{2}, -1, -\frac{3}{2}|x)$  is a good test case [58]; past versions of both Maple and Mathematica produced incorrect numerical values for large  $x > 0$ . Here, mpmath automatically removes an internal singularity and compensates for cancellations (amounting to 656 bits of precision when  $x = 10000$ ), giving correct values:

```
>>> mpmath.mp.dps = 15
>>> mpmath.meijerg([[],[0]], [[-0.5,-1,-1.5],[]], 10000)
mpf('2.4392576907199564e-94')
```

Equivalently, with SymPy's interface this function can be evaluated as:

```
>>> meijerg([[],[0]], [[-S(1)/2,-1,-S(3)/2],[]], 10000).evalf()
2.43925769071996e-94
```

Symbolic integration and summation often produce hypergeometric and Meijer G-function closed forms (see Subsection 2.5); numerical evaluation of such special functions is a useful complement to direct numerical integration and summation.

## 4 PHYSICS SUBMODULE

SymPy includes several submodules that allow users to solve domain specific problems. For example, a comprehensive physics submodule is included that is useful for solving problems in mechanics, optics, and quantum mechanics along with support for manipulating physical quantities with units.

### 4.1 Classical Mechanics

One of the core domains that SymPy supports is the physics of classical mechanics. This is in turn separated into two distinct components: vector algebra and mechanics.

#### 4.1.1 Vector Algebra

The `sympy.physics.vector` submodule provides reference frame-, time-, and space-aware vector and dyadic objects that allow for three-dimensional operations such as addition, subtraction, scalar multiplication, inner and outer products, and cross products. The vector and dyadic objects can both be written in very compact notation that make it easy to express the vectors and dyadics in terms of multiple reference frames with arbitrarily defined relative orientations. The vectors are used to specify the positions, velocities, and accelerations of points; orientations, angular velocities, and angular accelerations of reference frames; and forces and torques. The dyadics are essentially reference frame-aware  $3 \times 3$  tensors [49]. The vector and dyadic objects can be used for any one-, two-, or three-dimensional vector algebra, and they provide a strong framework for building physics and engineering tools.

The following Python code demonstrates how a vector is created using the orthogonal unit vectors of three reference frames that are oriented with respect to each other, and the result of expressing the vector in the  $A$  frame. The  $B$  frame is oriented with respect to the  $A$  frame using Z-X-Z Euler Angles of magnitude  $\pi$ ,  $\frac{\pi}{2}$ , and  $\frac{\pi}{3}$ , respectively, whereas the  $C$  frame is oriented with respect to the  $B$  frame through a simple rotation about the  $B$  frame's  $X$  unit vector through  $\frac{\pi}{2}$ .

```
>>> from sympy.physics.vector import ReferenceFrame
>>> A, B, C = symbols('A B C', cls=ReferenceFrame)
>>> B.orient(A, 'body', (pi, pi/3, pi/4), 'zxz')
>>> C.orient(B, 'axis', (pi/2, B.x))
>>> v = 1*A.x + 2*B.z + 3*C.y
>>> v
A.x + 2*B.z + 3*C.y
>>> v.express(A)
A.x + 5*sqrt(3)/2*A.y + 5/2*A.z
```

#### 4.1.2 Mechanics

The `sympy.physics.mechanics` submodule utilizes the `sympy.physics.vector` submodule to populate time-aware particle and rigid-body objects to fully describe the kinematics and kinetics of a rigid multi-body system. These objects store all of the information needed to derive the ordinary differential or differential algebraic equations that govern the motion of the system, i.e., the equations of motion. These equations of motion abide by Newton's laws of motion and can handle arbitrary kinematic constraints or complex loads. The submodule offers two automated methods for formulating the equations of motion based on Lagrangian Dynamics [28] and Kane's Method [26]. Lastly, there are automated linearization routines for constrained dynamical systems [39].

## 4.2 Quantum Mechanics

The `sympy.physics.quantum` submodule has extensive capabilities to solve problems in quantum mechanics, using Python objects to represent the different mathematical objects relevant in quantum theory [46]: states (bras and kets), operators (unitary, Hermitian, etc.), and basis sets, as well as operations on these objects such as representations, tensor products, inner products, outer products, commutators, and anticommutators. The base objects are designed in the most general way possible to enable any particular quantum system to be implemented by subclassing the base operators and defining the relevant class methods to provide system-specific logic.

Symbolic quantum operators and states may be defined, and one can perform a full range of operations with them.

```
>>> from sympy.physics.quantum import Commutator, Dagger, Operator
>>> from sympy.physics.quantum import Ket, qapply
>>> A, B, C, D = symbols('A B C D', cls=Operator)
>>> a = Ket('a')
>>> comm = Commutator(A, B)
>>> comm
[A,B]
>>> qapply(Dagger(comm*a)).doit()
```

```
503 -<a|*(Dagger(A)*Dagger(B) - Dagger(B)*Dagger(A))
```

504 Commutators can be expanded using common commutator identities:

```
505 >>> Commutator(C+B, A*D).expand(commutator=True)
506 -[A,B]*D - [A,C]*D + A*[B,D] + A*[C,D]
```

507 On top of this set of base objects, a number of specific quantum systems have been implemented  
508 in a fully symbolic framework. These include:

- 509 • Many of the exactly solvable quantum systems, including simple harmonic oscillator states  
510 and raising/lowering operators, infinite square well states, and 3D position and momentum  
511 operators and states.
- 512 • Second quantized formalism of non-relativistic many-body quantum mechanics [15].
- 513 • Quantum angular momentum [60]. Spin operators and their eigenstates can be represented  
514 in any basis and for any quantum numbers. A rotation operator representing the Wigner-D  
515 matrix, which may be defined symbolically or numerically, is also implemented to rotate  
516 spin eigenstates. Functionality for coupling and uncoupling of arbitrary spin eigenstates is  
517 provided, including symbolic representations of Clebsch-Gordon coefficients and Wigner  
518 symbols.
- 519 • Quantum information and computing [33]. Multidimensional qubit states, and a full  
520 set of one- and two-qubit gates are provided and can be represented symbolically or as  
521 matrices/vectors. With these building blocks, it is possible to implement a number of basic  
522 quantum algorithms including the quantum Fourier transform, quantum error correction,  
523 quantum teleportation, Grover's algorithm, dense coding, etc. In addition, any quantum  
524 circuit may be plotted using the `circuit_plot` function (Figure 1).

525 Here are a few short examples of the quantum information and computing capabilities in  
526 `sympy.physics.quantum`. Start with a simple four-qubit state and flip the second qubit from the  
527 right using a Pauli-X gate:

```
528 >>> from sympy.physics.quantum.qubit import Qubit
529 >>> from sympy.physics.quantum.gate import XGate
530 >>> q = Qubit('0101')
531 >>> q
532 |0101>
533 >>> X = XGate(1)
534 >>> qapply(X*q)
535 |0111>
```

536 Qubit states can also be used in adjoint operations, tensor products, inner/outer products:

```
537 >>> Dagger(q)
538 <0101|
539 >>> ip = Dagger(q)*q
540 >>> ip
541 <0101|0101>
542 >>> ip.doit()
543 1
```

544 Quantum gates (unitary operators) can be applied to transform these states and then classical  
545 measurements can be performed on the results:

```
546 >>> from sympy.physics.quantum.qubit import measure_all
547 >>> from sympy.physics.quantum.gate import H, X, Y, Z
548 >>> c = H(0)*H(1)*Qubit('00')
549 >>> c
```

```

550 H(0)*H(1)*|00>
551 >>> q = qapply(c)
552 >>> measure_all(q)
553 [(|00>, 1/4), (|01>, 1/4), (|10>, 1/4), (|11>, 1/4)]

```



**Figure 1.** The circuit diagram for a three-qubit quantum Fourier transform generated by SymPy.

554 Lastly, the following example demonstrates creating a three-qubit quantum Fourier transform,  
 555 decomposing it into one- and two-qubit gates, and then generating a circuit plot for the sequence  
 556 of gates (see Figure 1).

```

557 >>> from sympy.physics.quantum.qft import QFT
558 >>> from sympy.physics.quantum.circuitplot import circuit_plot
559 >>> fourier = QFT(0,3).decompose()
560 >>> fourier
561 SWAP(0,2)*H(0)*C((0),S(1))*H(1)*C((0),T(2))*C((1),S(2))*H(2)
562 >>> c = circuit_plot(fourier, nqubits=3)

```

## 563 5 ARCHITECTURE

564 Software architecture is of central importance in any large software project because it establishes  
 565 predictable patterns of usage and development [47]. This section describes the essential structural  
 566 components of SymPy, provides justifications for the design decisions that have been made, and  
 567 gives example user-facing code as appropriate.

### 568 5.1 The Core

569 A computer algebra system stores mathematical expressions as data structures. For example,  
 570 the mathematical expression  $x + y$  is represented as a tree with three nodes,  $+$ ,  $x$ , and  $y$ ,  
 571 where  $x$  and  $y$  are ordered children of  $+$ . As users manipulate mathematical expressions  
 572 with traditional mathematical syntax, the CAS manipulates the underlying data structures.  
 573 Automated optimizations and computations such as integration, simplification, etc. are all  
 574 functions that consume and produce expression trees.

575 In SymPy every symbolic expression is an instance of a Python `Basic` class,<sup>11</sup> a superclass  
 576 of all SymPy types providing common methods to all SymPy tree-elements, such as traversals.  
 577 The children of a node in the tree are held in the `args` attribute. A terminal or leaf node in the  
 578 expression tree has empty `args`.

579 For example, consider the expression  $xy + 2$ :

```

580 >>> x, y = symbols('x y')
581 >>> expr = x*y + 2

```

<sup>11</sup>Some internal classes, such as those used in the polynomial submodule, do not follow this rule for efficiency reasons.

582 By order of operations, the parent of the expression tree for `expr` is an addition, so it is of type  
583 `Add`. The child nodes of `expr` are 2 and `x*y`.

```
584 >>> type(expr)
585 <class 'sympy.core.add.Add'>
586 >>> expr.args
587 (2, x*y)
```

588 Descending further down into the expression tree yields the full expression. For example,  
589 the next child node (given by `expr.args[0]`) is 2. Its class is `Integer`, and it has an empty `args`  
590 tuple, indicating that it is a leaf node.

```
591 >>> expr.args[0]
592 2
593 >>> type(expr.args[0])
594 <class 'sympy.core.numbers.Integer'>
595 >>> expr.args[0].args
596 ()
```

597 Symbols or symbolic constants, like  $e$  or  $\pi$ , are examples of leaf nodes.

```
598 >>> exp(1)
599 E
600 >>> exp(1).args
601 ()
602 >>> x.args
603 ()
```

604 A useful way to view an expression tree is using the `srepr` function, which returns a string  
605 representation of an expression as valid Python code<sup>12</sup> with all the nested class constructor calls  
606 to create the given expression.

```
607 >>> srepr(expr)
608 "Add(Mul(Symbol('x'), Symbol('y')), Integer(2))"
```

609 Every SymPy expression satisfies a key identity invariant:

```
610 expr.func(*expr.args) == expr
```

611 This means that expressions are rebuildable from their `args`.<sup>13</sup> Note that in SymPy the `==`  
612 operator represents exact structural equality, not mathematical equality. This allows testing if  
613 any two expressions are equal to one another as expression trees. For example, even though  
614  $(x+1)^2$  and  $x^2+2x+1$  are equal mathematically, SymPy gives

```
615 >>> (x + 1)**2 == x**2 + 2*x + 1
616 False
```

617 because they are different as expression trees (the former is a `Pow` object and the latter is an `Add`  
618 object).

619 Python allows classes to override mathematical operators. The Python interpreter translates  
620 the above `x*y + 2` to, roughly, `(x.__mul__(y)).__add__(2)`. Both `x` and `y`, returned from the  
621 `symbols` function, are `Symbol` instances. The 2 in the expression is processed by Python as a  
622 literal, and is stored as Python's built in `int` type. When 2 is passed to the `__add__` method  
623 of `Symbol`, it is converted to the SymPy type `Integer(2)` before being stored in the resulting  
624 expression tree. In this way, SymPy expressions can be built in the natural way using Python  
625 operators and numeric literals.

---

<sup>12</sup> The `dotprint` function from the `sympy.printing.dot` submodule prints output to dot format, which can be rendered with `Graphviz` to visualize expression trees graphically.

<sup>13</sup> `expr.func` is used instead of `type(expr)` to allow the function of an expression to be distinct from its actual Python class. In most cases the two are the same.



## 5.2 Extensibility

While the core of SymPy is relatively small, it has been extended to a wide variety of domains by a broad range of contributors. This is due, in part, to the fact that the same language, Python, is used both for the internal implementation and the external usage by users. All of the extensibility capabilities available to users are also utilized by SymPy itself. This eases the transition pathway from SymPy user to SymPy developer.

The typical way to create a custom SymPy object is to subclass an existing SymPy class, usually `Basic`, `Expr`, or `Function`. As it was stated before, all SymPy classes used for expression trees should be subclasses of the base class `Basic`. `Expr` is the `Basic` subclass for mathematical that can be added and multiplied together. The most commonly seen classes in SymPy are subclasses of `Expr`, including `Add`, `Mul`, and `Symbol`. Instances of `Expr` typically represent complex numbers, but may also include other “rings”, like matrix expressions. Not all SymPy classes are subclasses of `Expr`. For instance, logic expressions, such as `And(x, y)`, are subclasses of `Basic` but not of `Expr`.

The `Function` class is a subclass of `Expr` which makes it easier to define mathematical functions called with arguments. This includes named functions like  $\sin(x)$  and  $\log(x)$  as well as undefined functions like  $f(x)$ . Subclasses of `Function` should define a class method `eval`, which returns a canonical form of the function application (usually an instance of some other class, i.e., a `Number`) or `None`, if for given arguments that function should not be automatically evaluated.

Many SymPy functions perform various evaluations down the expression tree. Classes define their behavior in such functions by defining a relevant `_eval_*` method. For instance, an object can indicate to the `diff` function how to take the derivative of itself by defining the `_eval_derivative(self, x)` method, which may in turn call `diff` on its args. (Subclasses of `Function` should implement `fdiff` method instead, it returns the derivative of the function without considering the chain rule.) The most common `_eval_*` methods relate to the assumptions: `_eval_is_assumption` is used to deduce *assumption* on the object.

As an example of the notions presented in this section, Listing 1 presents a minimal version of the gamma function  $\Gamma(x)$  from SymPy, which evaluates itself on positive integer arguments, has the real assumption defined, can be rewritten in terms of factorial with `gamma(x).rewrite(factorial)`, and can be differentiated. `self.func` is used throughout instead of referencing `gamma` explicitly so that potential subclasses of `gamma` can reuse the methods.

**Listing 1.** A minimal implementation of `sympy.gamma`.

```
from sympy import Integer, Function, floor, factorial, polygamma

class gamma(Function)
    @classmethod
    def eval(cls, arg):
        if isinstance(arg, Integer) and arg.is_positive:
            return factorial(arg - 1)

    def _eval_is_real(self):
        x = self.args[0]
        # noninteger means real and not integer
        if x.is_positive or x.is_noninteger:
            return True

    def _eval_rewrite_as_factorial(self, z):
        return factorial(z - 1)

    def fdiff(self, argindex=1):
        from sympy.core.function import ArgumentIndexError
        if argindex == 1:
            return self.func(self.args[0])*polygamma(0, self.args[0])
        else:
```

679                   raise IndexError(self, argindex)

680 The gamma function implemented in SymPy has many more capabilities than the above listing,  
681 such as evaluation at rational points and series expansion.

### 682 **5.3 Speed**

683 Due to being written in pure Python, SymPy’s speed is generally slower compared with its  
684 commercial competitors. For many applications and uses of SymPy, that is not a problem, as  
685 SymPy is able to return the answer quickly enough, but for some applications that require  
686 handling of very long expressions and/or lots of small expressions, the speed becomes a problem.

687 For this reason, a new library called SymEngine [56] was started. It is a pure C++ library  
688 with thin wrappers to other languages (Python, Ruby, Julia, ...) whose aim is to be the fastest  
689 manipulation library. Preliminary benchmarks suggest that SymEngine is as fast or faster than  
690 the commercial or open source competitors.

691 The development branch of SymPy recently started to use SymEngine as an optional backend,  
692 initially in `sympy.physics.mechanics` only. The plan is to allow more algorithms in SymPy to  
693 take advantage of the speed of SymEngine.

## 694 **6 PROJECTS THAT DEPEND ON SYMPY**

695 There are several projects that depend on SymPy as a library for implementing a part of their  
696 functionality. A selection of these projects are listed in Table 3.

**Table 3.** Selected projects that depend on SymPy.

Project name	Description
<b>SymPy Gamma</b>	An open source analog of the Wolfram Alpha. See more in the supplementary material.
<b>Cadabra</b> [37]	CAS designed specifically for the resolution of problems encountered in field theory.
<b>GNU Octave Symbolic Package</b> [55]	An implementation of a symbolic toolbox for Octave using SymPy.
<b>SymPy.jl</b> [57]	Provides a Julia interface to SymPy using PyCall.
<b>Mathics</b> [52]	A free, online CAS featuring Mathematica compatible syntax and functions.
<b>Mathpix</b> [31]	An iOS App, that detects handwritten math as input, and uses SymPy Gamma to evaluate the math input and generate the relevant steps to solve the problem.
<b>IKFast</b> [11]	IKFast is a robot kinematics compiler provided by OpenRAVE.
<b>SageMath</b> [54]	A free open-source mathematics software system, builds on top of many existing open-source packages, including SymPy.
<b>PyDy</b> [18]	Multibody Dynamics with Python.
<b>galgebra</b> [5]	A module for geometric algebra (previously <code>sympy.galgebra</code> ).
<b>yt</b> [59]	Python package for analyzing and visualizing volumetric data.
<b>SfePy</b> [10]	A Python package for solving partial differential equations (PDEs) in 1D, 2D and 3D by the finite element (FE) method [61].
<b>Quameon</b> [53]	Quantum Monte Carlo in Python.
<b>Lcapy</b> [51]	Experimental Python package for teaching linear circuit analysis.

## 697 **7 CONCLUSION AND FUTURE WORK**

698 SymPy is a robust computer algebra system that provides a wide spectrum of features both in  
699 traditional computer algebra and in a plethora of scientific disciplines. This allows SymPy to be  
700 used in a first-class way with other Python projects, including the scientific Python stack. Unlike  
701 many other CAS’s, SymPy is designed to be used in an extensible way: both as an end-user  
702 application and as a library.

SymPy expressions are immutable trees of Python objects. SymPy uses Python both as the internal language and the user language. This permits users to access to the same methods that the library implements in order to extend it for their needs. Additionally, SymPy has a powerful assumptions system for declaring and deducing mathematical properties of expressions.

SymPy supports a wide array of mathematical facilities. This includes functions for simplifying expressions, performing common calculus operations, pretty printing expressions, solving equations, and representing symbolic matrices. Other supported facilities include discrete math, concrete math, plotting, geometry, statistics, polynomials, sets, series, vectors, combinatorics, group theory, code generation, tensors, Lie algebras, cryptography, and special functions. Additionally, SymPy contains submodules targeting certain specific domains, such as classical mechanics and quantum mechanics. This breadth of domains has been engendered by a strong and vibrant user community. Anecdotaly, these users likely chose SymPy because of its ease of access.

Some of the planned future work for SymPy includes work on improving code generation, improvements to the speed of SymPy using SymEngine, improving the assumptions system, and improving the solvers submodule.

## REFERENCES

- [1] Adams, W. W. and Loustaunau, P. (1994). *An introduction to Gröbner bases*. Number 3. American Mathematical Society.
- [2] Bailey, D. H., Jeyabalan, K., and Li, X. S. (2005). A comparison of three high-precision quadrature schemes. *Experimental Mathematics*, 14(3):317–329.
- [3] Bender, C. M. and Orszag, S. A. (1999). *Advanced Mathematical Methods for Scientists and Engineers*. Springer, 1st edition.
- [4] Biggs, N., Lloyd, E. K., and Wilson, R. J. (1976). *Graph Theory, 1736-1936*. Oxford University Press.
- [5] Bromborsky, A. (2016). *geometric algebra/calculus modules for SymPy*. <https://github.com/brombo/galgebra>.
- [6] Bronstein, M. (2005a). pmint—The Poor Man’s Integrator. <http://www-sop.inria.fr/cafe/Manuel.Bronstein/pmint>.
- [7] Bronstein, M. (2005b). *Symbolic Integration I: Transcendental Functions*. Springer–Verlag, New York, NY, USA.
- [8] Buchberger, B. (1965). *Ein Algorithmus zum Auffinden der Basis Elemente des Restklassenrings nach einem nulldimensionalen Polynomideal*. PhD thesis, University of Innsbruck, Innsbruck, Austria.
- [9] Cervone, D. (2012). Mathjax: a platform for mathematics on the web. *Notices of the AMS*, 59(2):312–316.
- [10] Cimrman, R. (2014). SfePy - write your own FE application. In de Buyl, P. and Varoquaux, N., editors, *Proceedings of the 6th European Conference on Python in Science (EuroSciPy 2013)*, pages 65–70. <http://arxiv.org/abs/1404.6391>.
- [11] Diankov, R. (2010). Ikfast: The robot kinematics compiler. [http://openrave.org/docs/latest\\_stable/openravepy/ikfast/](http://openrave.org/docs/latest_stable/openravepy/ikfast/).
- [12] Doorenbos, R. B. (1995). *Production matching for large learning systems*. PhD thesis, University of Southern California.
- [13] Faugère, J. C. (1999). A New Efficient Algorithm for Computing Gröbner Bases (F4). *Journal of Pure and Applied Algebra*, 139(1-3):61–88.
- [14] Faugère, J. C. (2002). A New Efficient Algorithm for Computing Gröbner Bases Without Reduction To Zero (F5). In *ISSAC ’02: Proceedings of the 2002 International Symposium on Symbolic and Algebraic Computation*, pages 75–83, New York, NY, USA. ACM Press.
- [15] Fetter, A. and Walecka, J. (2003). *Quantum Theory of Many-Particle Systems*. Dover Publications.
- [16] Fousse, L., Hanrot, G., Lefèvre, V., Pélissier, P., and Zimmermann, P. (2007). Mpf: A multiple-precision binary floating-point library with correct rounding. *ACM Trans. Math. Softw.*, 33(2).

- [17] Fu, H., Zhong, X., and Zeng, Z. (2006). Automated and Readable Simplification of Trigonometric Expressions. *Mathematical and Computer Modelling*, 55(11-12):1169–1177.
- [18] Gede, G., Peterson, D. L., Nanjangud, A. S., Moore, J. K., and Hubbard, M. (2013). Constrained multibody dynamics with Python: From symbolic equation generation to publication. In *ASME 2013 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*, pages V07BT10A051–V07BT10A051. American Society of Mechanical Engineers.
- [19] Goldberg, D. (1991). What every computer scientist should know about floating-point arithmetic. *ACM Computing Surveys (CSUR)*, 23(1):5–48.
- [20] Gosper, R. W. (1978). Decision procedure for indefinite hypergeometric summation. *Proceedings of the National Academy of Sciences*, 75(1):40–42.
- [21] Gruntz, D. (1996). *On Computing Limits in a Symbolic Manipulation System*. PhD thesis, Swiss Federal Institute of Technology, Zürich, Switzerland.
- [22] Horsen, C. V. (2015). GMPY. <https://pypi.python.org/pypi/gmpy2>.
- [23] Hudak, P. (1998). Domain specific languages. In Salas, P. H., editor, *Handbook of Programming Languages, Vol. III: Little Languages and Tools*, chapter 3, pages 39–60. MacMillan, Indianapolis.
- [24] Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing In Science & Engineering*, 9(3):90–95.
- [25] Johansson, F. et al. (2014). mpmath: a Python library for arbitrary-precision floating-point arithmetic (version 0.19). <http://mpmath.org/>.
- [26] Kane, T. R. and Levinson, D. A. (1985). *Dynamics, Theory and Applications*. McGraw Hill.
- [27] Kluyver, T., Ragan-Kelley, B., Pérez, F., Granger, B., Bussonnier, M., Frederic, J., Kelley, K., Hamrick, J., Grout, J., Corlay, S., et al. (2016). Jupyter notebooks—a publishing format for reproducible computational workflows. In *Positioning and Power in Academic Publishing: Players, Agents and Agendas: Proceedings of the 20th International Conference on Electronic Publishing*, page 87. IOS Press.
- [28] Lagrange, J. (1811). *Mécanique analytique*. Number v. 1 in *Mécanique analytique*. Ve Courcier.
- [29] Lang, S. (1966). Introduction to transcendental numbers. *Reading, Mass.*
- [30] Lutz, M. (2013). *Learning Python*. O’Reilly Media, Inc.
- [31] Mathpix, Inc. (2016). *Mathpix — Solve and graph math using pictures*. <http://mathpix.com/>.
- [32] Moses, J. (1971). Algebraic Simplification: A Guide for the Perplexed. In *SYMSAC ’71: Proceedings of the second ACM Symposium on Symbolic and Algebraic Computation*, pages 282–304, New York, NY, USA. ACM Press.
- [33] Nielsen, M. and Chuang, I. (2011). *Quantum Computation and Quantum Information*. Cambridge University Press.
- [34] Nijenhuis, A. and Wilf, H. S. (1978). *Combinatorial Algorithms: For Computers and Calculators*. Academic Press, New York, NY, USA, second edition.
- [35] Oliphant, T. E. (2007). Python for scientific computing. *Computing in Science & Engineering*, 9(3):10–20.
- [36] Paprocki, M. (2010). Design and implementation issues of a computer algebra system in an interpreted, dynamically typed programming language. Master’s thesis, University of Technology of Wrocław, Poland.
- [37] Peeters, K. (2007). Cadabra: a field-theory motivated symbolic computer algebra system. *Computer Physics Communications*.
- [38] Pérez, F. and Granger, B. E. (2007). IPython: a system for interactive scientific computing. *Computing in Science & Engineering*, 9(3):21–29.
- [39] Peterson, D. L., Gede, G., and Hubbard, M. (2014). Symbolic linearization of equations of motion of constrained multibody systems. *Multibody System Dynamics*, 33(2):143–161.
- [40] Petkovšek, M., Wilf, H. S., and Zeilberger, D. (1996). *A=BAK peters*. Wellesley, MA.
- [41] Raymond, E. (1999). The cathedral and the bazaar. *Knowledge, Technology & Policy*, 12(3):23–49.
- [42] Roach, K. (1996). Hypergeometric function representations. In *ISSAC ’96: Proceedings of the 1996 International Symposium on Symbolic and Algebraic Computation*, pages 301–308,

- New York, NY, USA. ACM Press.
- [43] Roach, K. (1997). Meijer G function representations. In *ISSAC '97: Proceedings of the 1997 international symposium on Symbolic and algebraic computation*, pages 205–211, New York, NY, USA. ACM.
- [44] Rocklin, M. and Terrel, A. R. (2012). Symbolic statistics with SymPy. *Computing in Science and Engineering*, 14.
- [45] Rosen, L. (2005). *Open source licensing*, volume 692. Prentice Hall.
- [46] Sakurai, J. and Napolitano, J. (2010). *Modern Quantum Mechanics*. Addison-Wesley.
- [47] Shaw, M. and Garlan, D. (1996). *Software Architecture: Perspectives on an Emerging Discipline*. Prentice Hall. Prentice Hall Ordering Information.
- [48] Sussman, G. J. and Wisdom, J. (2013). *Functional Differential Geometry*. Massachusetts Institute of Technology Press.
- [49] Tai, C.-T. (1997). *Generalized vector and dyadic analysis: applied mathematics in field theory*, volume 9. Wiley-IEEE Press.
- [50] Takahasi, H. and Mori, M. (1974). Double exponential formulas for numerical integration. *Publications of the Research Institute for Mathematical Sciences*, 9(3):721–741.
- [51] The Lcapy Developers (2016). *Lcapy, a Python package for linear circuit analysis*. <http://lcapy.elec.canterbury.ac.nz/>.
- [52] The Mathics Developers (2016). *Mathics, a free, general-purpose online computer algebra system featuring Mathematica-compatible syntax and functions*. <https://mathics.github.io/>.
- [53] The Quameon Developers (2016). *Quameon, Quantum Monte Carlo in Python*. <http://quameon.sourceforge.net/>.
- [54] The Sage Developers (2016). *SageMath, the Sage Mathematics Software System*. <http://www.sagemath.org>.
- [55] The Symbolic Package Developers (2016). *The Symbolic Package for GNU Octave*.
- [56] The SymPy Developers (2016). *SymEngine, a fast symbolic manipulation library, written in C++*. <https://github.com/symengine/symengine>.
- [57] The SymPy.jl Developers (2016). *SymPy.jl, a package to bring Python’s SymPy functionality into Julia via PyCall*. <https://github.com/JuliaPy/SymPy.jl>.
- [58] Toth, V. T. (2007). Maple and Meijer’s G-function: a numerical instability and a cure. <http://www.vttoth.com/CMS/index.php/technical-notes/67>.
- [59] Turk, M. J., Smith, B. D., Oishi, J. S., Skory, S., Skillman, S. W., Abel, T., and Norman, M. L. (2011). yt: A Multi-code Analysis Toolkit for Astrophysical Simulation Data. *The Astrophysical Journal Supplement Series*, 192:9–+.
- [60] Zare, R. (1991). *Angular Momentum: Understanding Spatial Aspects in Chemistry and Physics*. Wiley.
- [61] Zienkiewicz, O., Taylor, R., and Zhu, J. (2013). *The Finite Element Method: Its Basis and Fundamentals*. Butterworth-Heinemann, seventh edition edition.