

# Scan2Serve Django Backend Changes Report

Generated for local development / deployment alignment with the Flutter client. Changes were applied under multiple repository copies in Downloads; mirror these into your canonical backend repository if you use a different path.

## 1. Scope

Edits target Django projects located at:

- QR-Based-Smart-Restaurant-System-test\...\Backend\scan2serve (primary test clone)
- QR-Based-Smart-Restaurant-System-main\...\Backend\scan2serve
- QR-test\_dunura computer\...\Backend\scan2serve

The Flutter app workspace (scan2serve flutter1) does not contain the Django project; this report documents backend file changes only.

## 2. Summary of modified files

scan2serve/settings.py (per clone):

- INSTALLED\_APPS: added chatbot, analytics (where URL includes those routes).
- ALLOWED\_HOSTS / SECURE\_SSL\_REDIRECT: local dev and LAN / emulator fixes.

users/views.py (test clone):

- New CustomerMeView for GET /users/customer/me/.

users/urls.py (test clone):

- Registered route customer/me/.

## 3. scan2serve/settings.py - QR-Based-Smart-Restaurant-System-test

### 3.1 SECURE\_SSL\_REDIRECT (DEBUG)

When DEBUG is True, SECURE\_SSL\_REDIRECT is forced to False so manage.py runserver (HTTP only) does not redirect clients to https:// on port 8000, which caused TLS handshake errors on the dev server.

### 3.2 ALLOWED\_HOSTS

When DEBUG is True, ALLOWED\_HOSTS = ['\*'] so requests from phones on the LAN (Host header = PC IP) are accepted. When DEBUG is False, an explicit list is used (localhost, 127.0.0.1, LAN IPs, 10.0.2.2 for Android emulator).

### 3.3 INSTALLED\_APPS

Added: 'chatbot', 'analytics' to match urlpatterns entries path('chat/', ...) and path('analytics/', ...), avoiding import errors on deploy.

## 4. scan2serve/settings.py - QR-Based-Smart-Restaurant-System-main

### 4.1 INSTALLED\_APPS

Added: "chatbot", "analytics" after "favourites".

### 4.2 SECURE\_SSL\_REDIRECT

Replaced a single SECURE\_SSL\_REDIRECT = not DEBUG assignment with logic that respects environment variable DISABLE\_SECURE\_SSL\_REDIRECT (true/1/yes) to force redirect off. Useful when DEBUG defaults to False locally but you still use HTTP runserver.

## 5. scan2serve/settings.py - QR-test\_dunura computer

Added 'chatbot' and 'analytics' to INSTALLED\_APPS (same rationale as other clones). Note: this copy may not include all other test-branch settings (e.g. ALLOWED\_HOSTS wildcard); align with your chosen source of truth.

## 6. users/views.py and users/urls.py (test clone)

### 6.1 CustomerMeView

New APIView: GET only, isAuthenticated, role must be 'customer'. Returns UserSerializer data (id, email, name, role, phone\_no). Non-customers receive 403.

### 6.2 URL

path('customer/me/', views.CustomerMeView.as\_view(), name='customer-me')

Full path: GET /users/customer/me/ (project includes users/ under 'users/').

## 7. Operational notes

- Run server on all interfaces for phone testing: python manage.py runserver 0.0.0.0:8000
- After INSTALLED\_APPS changes: run migrations if chatbot/analytics define models.
- Favourites app was not added to the test clone urls.py in these edits; add if the Flutter client calls /favourites/.

## 8. Related client-side change (not in this PDF repo)

Login request body uses 'email' (not 'username') to match LoginSerializer on the backend. That change is in Flutter lib/api/users\_api.dart, not in Django.