

Introduction to terminal

Iván Andrés Trujillo

ivantrujillo1229

ai-page.readthedocs.io

Different flavors of an operating system. Ubuntu is one of the most popular distro in the data science ecosystem.

Testing on Colab

```
1 cat /etc/os-release
```

or you can try:

```
1 clear
2 lsb_release -a
```

Is a program that interpret the commands! **bash** is the most common in linux.

```
1 echo $SHELL
```

to see the currently installed version of **bash**

```
1 bash --version
```

Where am i?

```
1 pwd
```

Show folders and files

```
1 ls
2 ls -a
3 ls -al
```

Create a folder

```
1 mkdir data
```

go to the folder

```
1 cd data  
2 pwd
```


Create a file

```
1 echo '10,20,30,50' > data.txt
```


we can alter or modify the document content:

```
1 vim data.txt
```

to exit of vim:

```
1 :wq!
```

Relative and Absolute path



if we want to go to folderB we must use an absolute path:

```
1 cd /home/user/folderRoot
```

if we want to change to folderA we can use a relative path using

```
1 cd ../folderA
```

to come back to folderRoot we only need

```
1 cd ..
```

is very used in linux, and means or is equal to

```
/home/USER_NAME
```

```
cd ~
```

root directory system

```
1 cd /
```

go to Documents

```
1 cd ~/Documents
```

establish your working directory and create two files:

```
1  pwd
2  mkdir testing
3  mkdir deploy
4  cd testing
5  echo 'the only line in my new file' > program.txt
6  cd ..
```

moving or rename files

First check that you are in **testing** folder rename the **program.txt** by **main.txt**

```
1 mv program.txt main.txt
```

move to **deploy** folder

```
1 mv main.txt ../deploy/
```

```
1 cd ../deploy/  
2 ls
```


copy a file

```
1 cp main.txt main_copy.txt
2 vim main.txt
3 :wq!
```

delete files and folder

```
1 rm main_copy.txt
```

delete a folder and all that is contained uses -r (recursive)

```
1 rm -r deploy
```

hint: there is no come back! after rm is used! Another command that could be useful is

```
1 rmdir EMPTY_FOLDER
```

only delete empty folders else shows errors.

```
1 find ~ -type f -name program.txt
```

- . in paths the current (this) directory
- ./program.py

variables

```
1 pi=3.14 #good
2 pi = 3.14 #no work!
```

```
1 echo $pi
```

operations

```
1 a=1
2 b=2
3 suma=$((a + b))
4 resta=$((a - b))
5 multi=$((a * b))
6 divi=$((a / b))
```

if you uses `(( ))` then:

```
1 (( variable = operation ))
```

if uses `$(( ))` then:

```
1 variable=$((operacin))
```

```
1 income=10
2 cost=3
3 ((profit = income - cost))
4 echo $profit
5 profit=$((income-cost))
```