❌ Filter operators - GraphQL API

Overview

Each filterable field supports a specific set of filter operations depending on its data type. All filter parameters are optional — only specify the ones you need. Multiple parameters within a single filter are combined with AND logic.

Example

Get all QAP products having indications with `IndicationNumber` 1 and 2.

```
products(
  where: {
    filter: {
      isQAP: { eq: true }
      indications: { containsAll: [1, 2] }
    }
  }
) {
  totalCount
}
```

Boolean Fields

Used for yes/no fields such as `IsQAP` or `IsOriginal`.

Operation	Description	Example
`eq`	Matches the exact value.	`eq: true` — only QAP products

Single-Value String Fields

Used for fields that hold a single text value, such as `TradeStatus`, `DispensingCategory`, or `GalenicForm`.

Operation	Description	Example
`in`	Matches any of the provided values.	`in: ["InTrade", "OutOfTrade"]` — products with either status

`nIn`	Excludes all of the provided values.	`nIn: ["OutOfTrade"]` — products that are not out of trade

String Collection Fields

Used for fields that hold multiple text values, such as `Publications`, `ReimbursementCategories`, or `NutritionalInformationDietaryAdvice`.

Operation	Description	Example
`containsAll`	Must contain **every** specified value.	`containsAll: ["Compendium", "RefData"]` — listed in both publications
`containsSome`	Must contain **at least one** of the specified values.	`containsSome: ["SL", "MiGeL"]` — reimbursed in at least one category
`notContainsAny`	Must **not** contain **any** of the specified values.	`notContainsAny: ["LACTOSE_FREE"]` — no lactose-free dietary advice
`notContainsAll`	Must **not** contain **all** of the specified values simultaneously.	`notContainsAll: ["SL", "HM"]` — not reimbursed in both SL and HM

> **Note:** An empty array behaves as follows:
> - `containsAll` / `notContainsAny` / `notContainsAll` → always true
> - `containsSome` → always false

Single-Value Number Fields

Used for numeric fields such as `ProductNumber`.

Operation	Description	Example

`eq`	Equal to the value.	`eq: 6956` — exact product number
`nEq`	Not equal to the value.	`nEq: 0` — exclude a specific value
`gt`	Greater than the value.	`gt: 10000` — product numbers above 10 000
`lt`	Less than the value.	`lt: 5000` — product numbers below 5 000
`ge`	Greater than or equal to the value.	`ge: 1` — score is at least 1
`le`	Less than or equal to the value.	`le: 100` — product numbers up to 100
`in`	Matches any of the provided values.	`in: [6956, 10104, 10730]` — specific product numbers
`nIn`	Excludes all of the provided values.	`nIn: [0]` — exclude score 0
`range`	Within a range (inclusive). Specify `min` and `max`.	`range: { min: 1000, max: 5000 }` — products in range

Number Collection Fields

Used for fields that hold multiple numeric values.

Operation	Description	Example
`containsAll`	Must contain **every** specified value.	`containsAll: [1, 2]`
`containsSome`	Must contain **at least one** of the specified values.	`containsSome: [1, 3]`
`notContainsAny`	Must **not** contain **any** of the specified values.	`notContainsAny: [0]`

`notContainsAll`	Must **not** contain **all** of the specified values simultaneously.	`notContainsAll: [1, 2]`

> **Note:** An empty array behaves as follows:
>
> - `containsAll` / `notContainsAny` / `notContainsAll` → always true
> - `containsSome` → always false