

Information Technologies for Industrial Engineers

เทคโนโลยีสารสนเทศสำหรับวิศวกรอุตสาหกรรม

Data Fetching

Get external data

- Let say we want to display this data on our app.
 - <https://jsonplaceholder.typicode.com/todos>
- You can use `fetch`.

fetch API

- The Fetch API is a modern interface that allows you to make HTTP requests to servers from web browsers.
- The `fetch()` method is available in the global scope that instructs the web browsers to send a request to a URL.
- Let's `fetch` information from [Star Wars API](#)

fetch

```
fetch("https://jsonplaceholder.typicode.com/todos");
```

- The `fetch()` method returns a `Promise`.
- But what is a **Promise**?

Promise

- A `Promise` is an object that represents an intermediate state of an operation.
- `Promise` tells you that a result of some kind will be returned at some point in the future.
- You have to write code that will be executed in order to do something else with a successful result, or to gracefully handle a failure case.

C

Responding to Promise

```
fetch("https://jsonplaceholder.typicode.com/todos")
  .then((res) => {
    return res.json();
  })
  .then((todos) => {
    return console.log(todos);
  });
```

Shorter syntax

```
fetch("https://jsonplaceholder.typicode.com/todos")  
  .then((res) => res.json())  
  .then((todos) => console.log(todos));
```


Fetching data in react app

- **Do not** fetch data in the main section of the function.
 - Infinite re-render.
- use `useEffect` function.

useEffect

- Lets you synchronize a component with an external system.

```
useEffect(() => {  
  // Fetching data here  
}, []);
```

Code

<https://gist.github.com/nnnpoooh/7d0fb6e6f798782e945211c92d781626#file-app1-tsx>

Send data

- Let's send message to a Line group.

Get Line access token

- <https://notify-bot.line.me>

Environment variable

```
./.env
```

```
VITE_LINE_TOKEN="....."  
VITE_CORS_PROXY="https://web-production-5af8.up.railway.app"
```

Code

<https://gist.github.com/nnnpoooh/7d0fb6e6f798782e945211c92d781626#file-app2-tsx>

```
fetch(`${CORS_PROXY}/https://notify-api.line.me/api/notify`, {  
  method: "POST",  
  headers: {  
    Authorization: `Bearer ${LINE_TOKEN}`,  
    "Content-Type": "application/x-www-form-urlencoded",  
  },  
  body: new URLSearchParams({  
    message: message,  
  } ),  
});
```


Note

- `POST` request
- Use a proxy to send message.
 - `CORS errors`
- Use `headers`
- Send content (body) as a URL search parameters.

```
const usp = new URLSearchParams({ message: "Hello", name: "Tom" });  
console.log(usp.toString());
```