

Information Technologies for Industrial Engineers

Deployment

Goal

- We will containerize the backend and frontend applications using `Docker` and deploy them to a server.
- The cool things about using docker is that we can test all the steps in our local machine before deploying to the server.

Requirements

- On the server we will use Linux without GUI.
 - No Dbeaver, no Docker Desktop, no mouse.
- Terminal
 - Windows - Git Bash
 - Mac - Terminal
- Tips: to paste commands in Git Bash
 - Right click to paste
 - Shift + Insert to paste

Variable in Bash

- Define a variable

```
MY_VARIABLE='Hello World'
```

- Inspect the variable

```
echo ${MY_VARIABLE}
```

- Interpolate the variable in a command

```
echo "The message is: ${MY_VARIABLE}"
```

Notice the single quote `'` and double quote `"` difference. Single quote will not interpolate the variable.

Dockerhub

- We will push the backend/frontend images to Dockerhub so that we can pull it from the server.
- Create an account at <https://hub.docker.com>.
- Create two repositories called `gXX_backend_image` and `gXX_frontend_image`.
- Login to your account in terminal
 - `docker login`

Step 1

| Preparing Docker Environment

```
DOCKER_VOLUME_NAME='gXX_volume'  
DOCKER_NETWORK_NAME='gXX_network'
```

- Create volume

```
docker volume create ${DOCKER_VOLUME_NAME}
```

- List the volume

```
docker volume ls
```

- Create network

```
docker network create ${DOCKER_NETWORK_NAME}
```

- List the network

```
docker network ls
```

Why Network?

- The backend container needs to connect to the database container.
 - The url is no longer `localhost` because the backend container is running in a different container than the database container.
 - This is like a separate computer connecting to a database server.
- Without a network
 - We need the **IP address** of the database container.
 - Unstable -> IP changes every time we restart the container.
- With a network
 - We use the **container name** as the hostname
 - Stable

Step 2

| Database

Create Database

```
DB_IMAGE_NAME='postgres:latest'  
DB_CONTAINER_NAME='gXX_db'  
DB_PASSWORD='6&zi9!%BYCUZo6B'  
DB_PORT='40XX'
```

- Create a container

```
docker run -d --name ${DB_CONTAINER_NAME} -e POSTGRES_PASSWORD=${DB_PASSWORD} -v  
${DOCKER_VOLUME_NAME}:/var/lib/postgresql --network ${DOCKER_NETWORK_NAME} -p  
${DB_PORT}:5432 ${DB_IMAGE_NAME}
```

Explanation for the command

Option	Description
<code>-d</code>	Run the container in detached mode
<code>--name</code>	Assign a name to the container
<code>-e</code>	Set environment variables in the container
<code>-v</code>	Mount a volume to the container
<code>--network</code>	Connect the container to a network
<code>-p</code>	Publish a container's port to the host
<code>\${DB_IMAGE_NAME}</code>	The name of the image to use for the container

DB Container Management

- Inspect the list of container

```
docker ps -a
```

- Inspect the container

```
docker inspect ${DB_CONTAINER_NAME}
```

- Delete the container, volume, and network if you want to start over

```
docker rm -f ${DB_CONTAINER_NAME}
```

```
docker volume rm ${DOCKER_VOLUME_NAME}
```

```
docker network rm ${DOCKER_NETWORK_NAME}
```

Connection to Database

We will use `psql` to create a database and a table. Think about `psql` as Dbeaver.

- Go into the container

```
docker exec -it ${DB_CONTAINER_NAME} bash
```

- Connect to the database

```
psql -U postgres
```

Create Database

- Create a database

```
CREATE DATABASE app_db;
```

- Check the database

```
\1
```

- Connect to the database

```
\c app_db
```

- Check connection

```
\conninfo
```

Create Table

- Create table

```
CREATE TABLE IF NOT EXISTS
todos (
  id serial PRIMARY KEY,
  title VARCHAR(50) NOT NULL,
  completed BOOLEAN NOT NULL DEFAULT FALSE,
  created_at TIMESTAMPTZ NOT NULL DEFAULT NOW()
);
```

- Check the table

```
\dt or SELECT * FROM todos;
```

Exit

- Exit `psql`
`\q`
- Exit the container
`exit`

Common Mistakes in `psql`

- Forget `;` at the end of the command.
 -  `CREATE DATABASE app_db`
 -  `CREATE DATABASE app_db;`
- Use `/` instead of `\` for commands.
 -  `/1`
 -  `\1`
- Forget to connect to the database before creating a table.
 -  `CREATE TABLE todos ...`
 -  `\c app_db then CREATE TABLE todos ...`

Step 3:

| Backend Application

Backend Starter

- `git clone -b starter https://github.com/it-for-ie-69/backend-deploy.git`
- Open VSCode and open the folder `backend-deploy`.
- Create `.env` file from `.env.example` and set the database password to your own password.
- `pnpm i`
- `pnpm run dev`
- `pnpm run build`

Visit `http://localhost:3000/todos` to see the backend is running and can connect to the database.

Prepare Backend for Docker Build

- Create `Dockerfile` ([Link](#))
 - This is the recipe to build the backend image.
- Create `.dockerignore` ([Link](#))
 - This is the list of files and folders that we don't want to include in the image.

Build Backend Image

```
BACKEND_IMAGE_NAME="gXX_backend_image"
```

- Build the image

```
docker build --platform linux/amd64 -t ${BACKEND_IMAGE_NAME} .
```

- Check the image

```
docker images
```

- Remove the image if you want to start over

```
docker rmi ${BACKEND_IMAGE_NAME}
```

Test Run Backend Container

```
BACKEND_CONTAINER_NAME='gXX_backend'  
BACKEND_PORT=50XX
```

```
# These are the env from the .env file that we need to pass to the container  
PGUSER=postgres  
PGHOST=${DB_CONTAINER_NAME}  
PGDATABASE=app_db  
PGPASSWORD=${DB_PASSWORD}  
PGPORT=5432
```

```
docker run -d --name ${BACKEND_CONTAINER_NAME} -p ${BACKEND_PORT}:3000 --network  
${DOCKER_NETWORK_NAME} -e PGUSER=${PGUSER} -e PGHOST=${PGHOST} -e  
PGDATABASE=${PGDATABASE} -e PGPASSWORD=${PGPASSWORD} -e PGPORT=${PGPORT}  
${BACKEND_IMAGE_NAME}
```

DB Connection Confusion

Consider this setup

```
PGHOST=${DB_CONTAINER_NAME} # i.e. gXX_db  
PGPORT=5432
```

- The host is no longer `localhost` because the backend container is running in a different container than the database container.
- The port is no longer `40XX` because the backend container is connecting to the database container directly, not through the host machine.

Push Backend Image to Dockerhub

```
BACKEND_IMAGE_NAME_TAG = 'dockerhub_username/gXX_backend_image:latest'
```

- Tag the image

```
docker tag ${BACKEND_IMAGE_NAME} ${BACKEND_IMAGE_NAME_TAG}
```

- Push command

```
docker push ${BACKEND_IMAGE_NAME_TAG}
```

Test Running Container

- `docker rm -f ${BACKEND_CONTAINER_NAME}`
- `docker image rm ${BACKEND_IMAGE_NAME}`
- `docker run -d --name ${BACKEND_CONTAINER_NAME} -p ${BACKEND_PORT}:3000 --network ${DOCKER_NETWORK_NAME} -e PGUSER=${PGUSER} -e PGHOST=${PGHOST} -e PGDATABASE=${PGDATABASE} -e PGPASSWORD=${PGPASSWORD} -e PGPORT=${PGPORT} ${BACKEND_IMAGE_NAME}`

You should see the image being pulled from Dockerhub and the container running successfully.

Step 4:

| Frontend Application

Starter

- `git clone -b starter https://github.com/it-for-ie-69/frontend-deploy.git`
- Open VSCode and open the folder `frontend-deploy`.
- Create `.env` file from `.env.example` and set the backend url to your own backend url.
- `pnpm i`
- `pnpm run dev`
- `pnpm run build`

Build Error

- You will see error from TypeScript compiler when you run `pnpm run build`.
- Change the `package.json` file

```
"build": "vue-tsc -b && vite build",
```

to

```
"build": "vite build",
```

Problem with Current Frontend Build

- Right now if you inspect `./dist/assets/index-*.js` you will see that the `baseUrl` is hardcoded to `http://localhost:3000` or similar.
- This does not work when we build the frontend container and run it in a different machine.
- We need to make the `baseUrl` configurable so that we can set it to the backend container url when we run the frontend container.

Solution

- Make proxy server by modifying `vite.config.ts` ([Link](#))
 - This config is used to forward the request to the backend container.
- Change `App.vue` to use the configurable `baseUrl`.

```
const baseUrl = "/api";
```

- Check if your apps runs/build correctly
 - `pnpm run dev`
 - `pnpm run build`

In production, we will use `Nginx` instead of the development proxy server to forward the request to the backend container.

Prepare Frontend for Docker Build

- Create `Dockerfile` ([Link](#))
- Create `.dockerignore` ([Link](#))
- Create `nginx.conf.template` ([Link](#))
 - This is the Nginx configuration file that will be used to forward the request to the backend container.
 - The `${NGINX_PROXY_PASS}` will be replaced with the backend container url when we run the frontend container.

Insert Diagram Here

Build Frontend Image

```
FRONTEND_IMAGE_NAME="gXX_frontend_image"
```

- Build the image

```
docker build --platform linux/amd64 -t ${FRONTEND_IMAGE_NAME} .
```

- Check the image

```
docker images
```

- Remove the image if you want to start over

```
docker rmi ${FRONTEND_IMAGE_NAME}
```

Test Run Frontend Container

```
FRONTEND_CONTAINER_NAME='gXX_frontend'  
FRONTEND_PORT=60XX  
BACKEND_URL=http://${BACKEND_CONTAINER_NAME}:3000
```

```
docker run -d --name ${FRONTEND_CONTAINER_NAME} -p ${FRONTEND_PORT}:81 --network  
${DOCKER_NETWORK_NAME} -e NGINX_PROXY_PASS=${BACKEND_URL} ${FRONTEND_IMAGE_NAME}
```

`NGINX_PROXY_PASS` is the how we tell the frontend container where to forward the request to the backend container.

What is port 81 and 3000?

- Port 81 is the port that the frontend container is listening to.

```
server {  
    listen 81;  
    listen [::]:81;  
    server_name localhost;  
}
```

- Port 3000 is the port that the backend container is listening to.

Push Frontend Image to Dockerhub

```
FRONTEND_IMAGE_NAME_TAG = 'dockerhub_username/gXX_frontend_image:latest'
```

- Tag the image

```
docker tag ${FRONTEND_IMAGE_NAME} ${FRONTEND_IMAGE_NAME_TAG}
```

- Push the image

```
docker push ${FRONTEND_IMAGE_NAME_TAG}
```

Test Frontend Container

- `docker rm -f ${FRONTEND_CONTAINER_NAME}`
- `docker image rm ${FRONTEND_IMAGE_NAME}`
- `docker run -d --name ${FRONTEND_CONTAINER_NAME} -p ${FRONTEND_PORT}:81 --network ${DOCKER_NETWORK_NAME} -e NGINX_PROXY_PASS=${BACKEND_URL} ${FRONTEND_IMAGE_NAME}`

You should see the image being pulled from Dockerhub and the container running successfully.