

Grease Pump Kit

TMK-GP3H


Trolley mounted kits are ideal for use in workshops, garages, shop floors providing complete portability for everyday lubrication needs

KIT INCLUDES

A	50:1 Air Operated Grease Pump
B	Grease Control Valve With Z swivel for trouble free dispensing
C	Grease Hose Reel - Heavy Duty Dual Arm Steel Reel Hose I.D.: 1/4" (6.35 mm) Maximum Pressure: 5800 PSI (400 BAR)
D	Steel Drum Cover 24-1/2" (612 mm) Prevents contamination of grease and keeps pump in vertical position
E	Rubber Lined Follower Plate O.D. Steel End: 21-5/8" (550 mm) O.D. Plate: 23-11/16" (602 mm) I.D. Grommet: 1-3/16" (29.5 mm)
F	Drum Trolley - Heavy Duty Manufactured from 4 mm thick steel sheet in powder coated finish Front Wheels: 6" (150 mm) polyurethane with nylon rim Rear castors with toe lock
G	Filter-Regulator Combination with Pressure Gauge (FRC) Port Size: 1/4" Type: Miniature Filter: 40 micron
H	Feeder Hose Connects pump outlet to the hose reel inlet Length: 1.5m (5')



WETTED COMPONENTS

Steel, Brass, Aluminium, Polyurethane & Nitrile Rubber

RECOMMENDED USE

With light and self collapsing grease up to NLGI No. 2

ORDERING INFORMATION

CAT NR.	ORD NR.	HOSE LENGTH		THREADS	BOX QTY.
		(M)	(FEET)		
TMK/GP3H-10/A/BSP	45824	10	32	1/8" BSPT	1
TMK/GP3H-10/A/N	45829	10	32	1/8" NPT	1
TMK/GP3H/A/BSP	45822	15	50	1/8" BSPT	1
TMK/GP3H/A/N	45826	15	50	1/8" NPT	1

SPECIFICATIONS

WORKING PRESSURE	30-150 PSI	2-10 BAR
MAX. AIR PRESSURE	150 PSI	10 BAR
MAX. OUTLET PRESSURE	7,500 PSI	500 BAR
AIR INLET CONNECTION	1/4" (F)	
PUMP OUTLET	1/4" (F)	
AIR CONSUMPTION	72 GPM	270 LPM
NOISE LEVEL	85 db	
GREASE OUTPUT (MAX.)	2.42 LBS./MIN.	1.1 KG/MIN.
FOR USE WITH	400 LBS. DRUMS	180 KG DRUMS