



BSc (Hons) in **Computer Science**
SE3062 : Intelligent Systems

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 02

Objective & Lecture Mapping: In Lecture 03, we learned that a mathematically perfect "Table-Driven Agent" is impossible to build due to combinatorial explosion. Instead, we must write Agent Programs. Today, you will implement a **Simple Reflex Agent** using Condition-Action rules, observe its fatal flaws in a partially observable environment, and then upgrade it to a **Model-Based Agent** that maintains an internal memory state.

Part 1: Practical Implementation — Coding the Architectures

Step 1.1: Setting the Trap (Partial Observability)

To see why Simple Reflex agents fail, we must handicap your agent's sensors. We are moving from a Fully Observable world to a Partially Observable one.

1. Open your `visual_grid_game.py` from Lab 01.
2. Locate the `get_percept(self)` method.
3. Modify it so it **no longer returns** the exact global coordinates (`agent_pos`). Instead, it should only return local booleans, e.g., `{'wall_ahead': True/False, 'food_here': True/False}` based on checking the adjacent cell in its current facing direction.

Step 1.2: The Simple Reflex Agent (Implementation & Failure)

1. Create a new class called `SimpleReflexAgent` .
2. Implement a `sense_and_act(self, percept)` method that uses strictly IF-THEN logic (Condition-Action rules). *Do not use an `__init__` method to store history.*

Example Logic: IF food_here THEN suck; IF wall_ahead THEN turn_left; ELSE move_forward

3. Run the simulation. **Observe:** Watch the agent get trapped in a corner or a U-shaped wall, infinitely repeating a cycle (e.g., turn left, step forward, hit wall, turn left...).

Step 1.3: The Model-Based Agent (Memory & State)

1. Create a new class called `ModelBasedAgent`.
2. Implement an `__init__(self)` method to initialize an internal memory state (e.g., `self.visited_cells = set()` or a relative movement tracker).
3. In `sense_and_act(self, percept)`, first **update the state** (Transition & Sensor Model) by recording the current percept and the last action taken.
4. Update your IF-THEN rules to query the memory.
Example Logic: IF wall_ahead AND left_is_visited THEN turn_right
5. Run the simulation. **Observe:** The agent should now remember where it has been, realize it is in a loop, and choose an alternate path to escape.

Part 2: Theoretical Evaluation & Lecture Mapping

Based on your practical observations above, answer the following questions to map your code directly to the architectural theories covered in Lecture 02.

1. (Remember) According to Lecture 02, why is it impossible to program a mathematically perfect "Table-Driven Agent" for complex environments like Chess? What happens as the agent's lifetime increases?

A mathematically perfect Table-Driven Agent is impossible because the percept sequence P^* grows infinitely as the agent's lifetime increases. This causes a combinatorial explosion — storing every possible percept history is infeasible. In complex domains like Chess, the number of possible percept sequences is astronomical, so a perfect table cannot be implemented. Instead, we use agent programs to approximate the agent function.

2. (Understand) Look at the code you wrote for your `SimpleReflexAgent` . Identify and explain the specific lines of code that represent the "Condition-Action Rules" discussed in the lecture.

```
if percept['food_here']:
    return 'suck'
elif percept['wall_ahead']:
    return 'turn_left'
else:
    return 'move_forward'
```

These IF-THEN statements in `sense_and_act()` are the condition-action rules. For example, if food is present → suck, if a wall is ahead → turn left, else → move forward. They directly implement the Simple Reflex Agent architecture discussed in the lecture, where actions depend only on the current percept and not on memory.

3. (Analyze) Your `SimpleReflexAgent` likely got stuck in an infinite loop during Step 1.2. Based on the lecture, analyze exactly why this happened. How did the combination of "Partial Observability" and a lack of "Percept History" cause this failure?

The `SimpleReflexAgent` loops because it only reacts to the current percept without memory. In a partially observable grid, it cannot see the full environment. When trapped in a corner, it keeps repeating the same rules (wall ahead → turn left, else → move forward). Without percept history, it cannot recognize that it is stuck. This is the fatal flaw of reflex agents in partially observable environments.

4. (Evaluate) In Step 1.3, you added an internal state to your `ModelBasedAgent` . Evaluate how your specific code handles the "Transition Model" (how the world evolves) and the "Sensor Model" (how the agent's actions affect the world).

In Step 1.3, the `ModelBasedAgent` applies a Transition Model by updating its internal position and facing whenever it executes an action, keeping its belief state consistent with the environment. It applies a Sensor Model by recording percepts like `wall_ahead` and `food_here` into memory, marking blocked directions and deciding when to suck food. Together, these updates refresh the agent's internal state before selecting a new rule, allowing it to escape loops and act rationally in a partially observable environment.

Finalize and Lock Lab 02 Documentation



FACULTY OF COMPUTING