



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 01

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation

Task 0 : Setting up and getting the starter Code

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" branch of the repo.

Task 1.1: The Environment State (`__init__`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

E – Environment
A – Actuators
S – Sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

The environment state is represented by variables such as:

`self.agent_pos`

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

Answer: Multi-Agent

Reason: The variable `self.opponents` shows that other agents exist in the environment besides the main agent.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

A percept sequence is the complete history of all percepts (sensor inputs) received by an agent from the beginning until the current time.

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Answer: Sensors (S)

It collects information from the environment and sends it to the agent.

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Answer: Partially Observable

Reason: The agent only receives the information returned by `get_percept()`. It cannot directly observe the entire environment.

Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Answer: Performance Measure (P)

The score changes according to the agent's action.

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

Because the performance measure should evaluate the results of the agent's actions, not how much computation the agent performs.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

The environment becomes more partially observable because the agent cannot directly see where the toxic traps are.

Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

The sensor gives the agent information about nearby danger.

This allows the agent to avoid toxic traps and choose safer actions, helping it

Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The vacuum repeatedly made the floor dirty and cleaned it to increase its score (Vacuum World Exploit).

Finalize and Lock Lab 01 Analytical Evaluation

Lab 01 code analysis and theoretical evaluation complete and verified!



FACULTY OF COMPUTING

