Prinect API - Current Version

- 1 Introduction
- 2 General principles
  - 2.1 Request structure
  - 2.2 Response structure
  - 2.3 Internationalization
  - 2.4 Authentification
  - 2.5 Usage restrictions
  - 2.6 Date / Time format
  - 2.7 Paging
- 3 Available REST APIs
  - 3.1 Job API
    - 3.1.1 /rest/job (GET)
    - 3.1.2 /rest/job/[jobId] (GET)
    - 3.1.3 /rest/job/[jobId]/workstep (GET)
    - 3.1.4 /rest/job/[jobId]/milestone/[milestoneId] (POST)
    - 3.1.5 /rest/job/[jobId]/workstep/[workstepId] (GET)
    - 3.1.6 /rest/job/[jobId]/workstep/[workstepId]/quality (GET)
    - 3.1.7 /rest/job/[jobId]/workstep/[workstepId]/activity (GET)
    - 3.1.8 /rest/job/[jobId]/workstep/[workstepId]/preview (GET)
    - 3.1.9 /rest/job/[jobId]/workstep/[workstepId]/inkConsumption (GET)
    - 3.1.10 /rest/job/[jobId]/element (GET)
    - 3.1.11 /rest/job/[jobId]/workstep/[workstepId]/element (GET)
    - 3.1.12 /rest/job/[jobId]/element/page (POST)
    - 3.1.13 /rest/job/[jobId]/element/sheet (POST)
    - 3.1.14 /rest/job/[jobId]/element/plate (POST)
    - 3.1.15 /rest/job/action/subscription (POST)
    - 3.1.16 /rest/job/[jobid]/ticket (GET)
    - 3.1.17 /rest/job/[jobId]/workstep/[workstepId]/output (GET)
  - 3.2 Device API
    - 3.2.1 /rest/device (GET)
    - 3.2.2 /rest/device/[deviceId] (GET)
    - 3.2.3 /rest/device/[deviceId]/activity (GET)
    - 3.2.4 /rest/device/[deviceId]/consumption (GET)
    - 3.2.5 /rest/device/action/subscription (POST) NEW IN 2021
    - 3.2.6 /rest/devicegroup (GET)
    - 3.2.7 /rest/device/[deviceId]/output (GET)
  - 3.3 Employee API
    - 3.3.1 /rest/employee (GET)
    - 3.3.2 /rest/employee/[employeeId] (GET)
    - 3.3.3 /rest/employee/[employeeId]/activity (GET)
  - 3.4 Masterdata API
    - 3.4.1 /rest/masterdata/milestone (GET)
  - 3.5 Service API
    - 3.5.1 /rest/service/startGanging (POST)
    - 3.5.2 /rest/service/gangResult (GET)
  - 3.6 Product API
    - 3.6.1 /rest/product (GET)
    - 3.6.2 /rest/product/[productid] (GET)
  - 3.7 Quote API
    - 3.7.1 /rest/quote (GET)
    - 3.7.2 /rest/quote/[quoteid] (GET)
  - 3.8 Customer API
    - 3.8.1. /rest/customer (get)
    - 3.8.2. /rest/customer/[customerid] (get)
  - 3.9 Product Type API
    - 3.9.1. /rest/producttype (get)
    - 3.9.2. /rest/producttype/[producttypeid] (get)
  - 3.10 Plate API
    - 3.10.1 /rest/plate/[plateID] (GET)
    - 3.10.2 /rest/plate/[plateID] (POST)
  - 3.11 Common
    - 3.11.1 /rest/version (GET)
    - 3.11.2 /rest/content/file (GET)

1 Introduction

This document describes the structure and use of the Prinect API. The Prinect API is based on the principles of REST and offers in the form of individual HTTP interface access to the resources of Prinect. It will provide the possibility of connecting specific in-house IT solutions to the customers to Prinect. The implementation is provided as an open API for the general availability within the Internet depending on the installation at customer site.

2 General principles

2.1 Request structure

The Prinect services can be accessed by request in the following form, the URL depends on the way the system has been set up :

Integrated installer in the INTMAN setup

http://[**PRINECT**_SRV_HOSTNAME]:15011/PrinectAPILocal/rest/[resource]?parameter

Dedicated Portal installation (separate setup), Portal runs on an extra host normally

http://[**PORTAL**_SRV_HOSTNAME]:15011/PrinectAPI/rest/[resource]?parameter

2.2 Response structure

Every request returns a specific response object. A response object always contains an error object. If the error object is null, the request was handled without any error.

Name	Type	Valid values	Description	Example
error	object		Error object provided with any resonse. Null if no error occured.	
error.code	Enum	RUNTIME_ERROR, NO_LICENSE	Error code	
error. message	String			

Currently only the JSON format is support for responses and for the payload of a POST request

2.3 Internationalization

Some request have a locale parameter, to specify the language for translatable attributes. The locale must be specified in ISO 3166 2-letter locale.

2.4 Authentification

Each installation Prinect offers the option to use the API with Prinect if the corresponding license option is available. PrinectAPI supports authentification based on HTTP Basic authentication . The credentials will be checked against the Prinect user management. Additional, the administrator has to give a specific access right to the user for data Access via Prinect API. If the username / password is unknown, the Systems returns HTTP 401. If the username / password is right, bute the Access right has not been set to the user, the Systems returns HTTP 403. A specific JSON response is not provided in that cases.

If Prinect Business Manager is installed, a similar user with PrinectAPI access rights has to be created there.

2.5 Usage restrictions

Access to the Prinect API is limited to the simultaneous processing of a request. Parallel incoming requests are buffered and processed in sequence. The Prinect API will slow down incoming requests to 2 requests per second.

2.6 Date / Time format

All times are based on local time, according to ISO8601 in the following form: [yyyy]-[mm]-[dd]T[hh]:[mm]:[ss][Offset UTC].

Sample for a parameter: ...?start=2014-02-27T16:36:45%2B01:00.... Remember to url encode the '+' sign (%2B).

2.7 Paging

For some resources paging is possible or even mandatory. Paging can be defined by 2 parameters

- page (starting point, multiplied with pagesize)
- pagesize (number of entities to get)

If paging is mandatory, pagesize has a default of 100 (DEFAULTPAGESIZE) entities.

For some ressources there is a maximum pagesize (MAXPAGESIZE) which is the same as DEFAULTPAGESIZE .

If paging is possible, the response structure contains a pageinfo object

Name	Type	Description	Example
pageInfo	object	pageiInfo object provided with the pageable calls. Null if the result is null.	
pageInfo.offset	Long	index in the complete content, is calculated by page*pagesize	
pageInfo.pagesize	Long	equivalent to the pagesize parameter, or DEFAULTPAGESIZE	

3 Available REST APIs

3.1 Job API

3.1.1 /rest/job (GET)

This call returns information about all the jobs contained in the system, matching a given filter. It does not include information about deleted or finished jobs, even if reports for such jobs are still available in AnalyzePoint.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	search	String	no	If given, the request returns jobs where the string is contained in either JobID, JobName, CustomerID or CustomerName.		14-05
Parameter	milestoneId1	String	no	Allows filtering by Milestonestatus. ID of the milestone for check. For access to the ID of the milestones of the system, see /rest/masterdata/milestone. Must always be used together with milestoneStatus1. Maybe future versions will have additional milestone filtering like milestoneId2, milestoneId3, .. .		ID4467330a169d4882a063c5cdb5f8634d
Parameter	milestoneStatus1	String	no	Allows filtering by Milestonestatus. Status of the specified milestone. Must always be used together with milestoneid.	IGNORE, NOT_COMPLETED, COMPLETED	IGNORE
Parameter	modifiedSince	Date	no	If given, the request returns jobs that have been modified since the given date. The Date must obey ISO8601 as described in 2.6.		2014-12-17T16:36:45%2B01:00
Parameter	globalStatus	String[]	no	If given, the request returns all job which matches one of the given globalStates (OR)	SETUP, ACTIVE, FINISHED, CANCELLED, OFFLINE	?globalStatus=SETUP&globalStatus=ACTIVE

Return value:

Name	Type	Description	Valid values	Sample
jobs	List	List of all known jobs		
jobs[].dueDate	String	Delivery data of the job		2013-04-10T08:04:54+02:00
jobs[].id	String	ID of the job		20130408-0803
jobs[].name	String	Name of the job		Brochure
jobs[].deliveryAmount	Int	Delivery amount		2500
jobs[].customerOrderId	String	The internal order number in the system of the customer		XYZ123
jobs[].jobCustomer	Object	Customer information		
jobs[].jobCustomer.id	String	Customer ID		1234
jobs[].jobCustomer.name	String	Customer name		CentralPrintshop
jobs[].jobStatus	Object	Status information		
jobs[].jobStatus.globalStatus	Enum	Status of the job.	UNDEFINED, SETUP, ACTIVE, RUNNING, STOPPED, FINISHED, OFFLINE, MODIFIED, CANCELLED	RUNNING
jobs[].jobStatus.milestones	List	List of production status information based on milestones		
jobs[].jobStatus.milestones[].calculatedProgress	Int	Progress to finish a milestone in % calculated by Prinect for automatic milestones.		0

jobs[].jobStatus.milestones[].milestoneDefId	String	Internal ID of the milestone. Please refer to /rest/masterdata/milestone		ID0c2e19bf1efc40c6bc09b9eaaac67100
jobs[].jobStatus.milestones[].status	String	Status of the milestone.	UNKNOWN, NORMAL, USER_FINISHED, PROGRESS_FINISHED, NOT_PLANNED	NORMAL
jobs[].jobStatus.milestones[].comment	String	Comment for manually checked milestones		

3.1.2 /rest/job/[jobId] (GET)

This provides basic information for JobID specified as part of the URL.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where information are requested for.		140512-1429

Return value:

Name	Type	Description	Valid values	Sample
job	Object	Single job.		
job.dueDate	String	Delivery date of the job.		2013-04-10T08:04:54+02:00
job.creationDate	String	Creation date of the job		2015-01-05T08:20:33+02:00
job.lastModified	String	Date of the last modification		2014-12-12T13:14:46+01:00
job.id	String	ID of the job.		20130408-0803
job.name	String	Name of the job.		Brochure
job.deliveryAmount	Int	Delivery amount		2500
job.numberPlannedPages	Int	Number of planned pages		36
job.priority	Int	Priority of the job between 0 (min priority) and 100 (max priority)		50
job.customerOrderId	String	The internal order number in the system of the customer		XYZ123
job.description	String	Long description of the job		Brochure 4 Pages Cover + 2x16 Pages Body
job.sourceJobIds	List<String>	For gang jobs: IDs of the jobs, wich are produced in the job.		[J-A , J-B]
job.projectId	String	For web to print jobs: shopping cart number in web shop		cart123
job.shopId	String	For web to print jobs: ID of the web shop		shopXYZ
job.author	String	Author		employee123
job.jobCustomer	Object	Customer information		
job.jobCustomer.id	String	Customer ID		1234
job.jobCustomer.name	String	Customer name		CentralPrintshop
job.jobStatus	Object	Status information		
job.jobStatus.globalStatus	Enum	Status of the job.	UNDEFINED, SETUP, ACTIVE, RUNNING, STOPPED, FINISHED, OFFLINE, MODIFIED, CANCELLED	RUNNING
job.jobStatus.milestones	List	List of production status information based on milestones		
job.jobStatus.milestones[].calculatedProgress	Int	Progress to finish a milestone in % calculated by Prinect for automatic milestones.		0
job.jobStatus.milestones[].milestoneDefId	String	Internal ID of the milestone. Please refer to /rest/masterdata/milestone		ID0c2e19bf1efc40c6bc09b9eaaac67100
job.jobStatus.milestones[].status	String	Status of the milestone.	UNKNOWN, NORMAL, USER_FINISHED, PROGRESS_FINISHED, NOT_PLANNED	NORMAL
job.jobStatus.milestones[].comment	String	Comment for manually checked milestones		

job.productionMonitorUrl	String	URL for a detailed status panel may be shown in a browser window		
job.gangJobs	List	Information about gang jobs in wich parts of the Job are produced		
job.gangJobs[]. gangJobId	String	ID of the gang job		J-AB
job.gangJobs[]. sheetName	List<String>	Names of the Sheets from the gang job on wich pages from the job are placed		[FB 001 , FB 002]
job.sequences	List			
job.sequences[].name	String	Name of the sequence		QualifyLowRes
job.sequences[].type	String	Type of the sequence		Qualify

3.1.3 /rest/job/[jobId]/workstep (GET)

Provides workstep information of the job by the given JobID.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where information are requested for.		140512-1429

Return value:

Name	Type	Description	Valid values	Sample
worksteps	List	List of all worksteps belonging to the jobid specified.		
worksteps[].job	Object	Job information		
worksteps[].job.id	String	ID of the job.		140512-1531
worksteps[].job.name	String	Name of the job.		Brochure
worksteps[].id	String	ID of the workstep (system internal)		_140512_153037680_003138
worksteps[].name	String	Name of the workstep.		Sheet1 5/0
worksteps[].status	Enum	Status of the workstep	UNKNOWN, WAITING, RUNNING, SUSPENDED, COMPLETED, ABORTED	COMPLETED
worksteps[].amountPlanned	Long	Planned amount.		
worksteps[].wastePlanned	Long	Planned waste.		
worksteps[].amountProduced	Long	Done amount.(Cycles)		
worksteps[].wasteProduced	Long	Done waste.(Cycles)		
worksteps[].deviceId	String	DeviceID of the devices on which the workstep ist o be / was produced.		
worksteps[].types[]	List<String>	List of type information for the workstep.		ConventionalPrinting
worksteps[].sequenceType	String	Type of the corresponding sequence.		SheetfedPrinting
worksteps[].startPlanned	Datetime	Time at which the workstep should be started. Normally filled, if the workstep is scheduled.		2013-04-10T08:04:54+02:00
worksteps[].endPlanned	Datetime	Time at which the workstep should be finished. Normally filled, if the workstep is scheduled.		2013-04-10T09:04:54+02:00
worksteps[].start	Datetime	Time at which the workstep has been started.		2013-04-10T08:04:54+02:00
worksteps[].end	Datetime	Time at which the workstep has been finished.		2013-04-10T09:04:54+02:00
worksteps[]. setuptimePlanned	Long	Time (duration) planned for setup in seconds		1500
worksteps[].prodtimePlanned	Long	Time (duration) planned for production in seconds (setup time is not included)		800
worksteps[].actualTimes	List			
worksteps[].actualTimes[]. timeTypeGroupName	String	Name of the time type category		Auxilliary time

worksteps[].actualTimes[].timeTypeName	String	Name of the time type		Waiting
worksteps[].actualTimes[].duration	Long	actual Time (duration) for timeTypeName in seconds		400

3.1.4 /rest/job/[jobId]/milestone/[milestoneId] (POST)

Sets / resets the milestone status of a specified milestone for a job.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where the milestone has to be set.		140512-1429
Path	milestoneId	String	yes	Internal ID of the milestone. Please refer to /rest/masterdata/milestone		IDec5a4efee0dc41db831c277d32968984
Parameter	completed	String	yes	New status for the specified milestone.	true, false	true
Parameter	comment	String	no	Comment for the new milestone status		done by Jack

Return value:

Name	Type	Description	Valid values	Sample
jobs	List	List of all known jobs.		
jobs[].dueDate	String	Delivery data of the job.		2013-04-10T08:04:54+02:00
jobs[].id	String	ID of the job.		20130408-0803
jobs[].name	String	Name of the job.		Brochure
jobs[].jobCustomer	Object	Customer information		
jobs[].jobCustomer.id	String	Customer ID		1234
jobs[].jobCustomer.name	String	Customer name		CentralPrintshop
jobs[].jobStatus	Object	Status information		
jobs[].jobStatus.globalStatus	Enum	Status of the job.	UNDEFINED, SETUP, ACTIVE, RUNNING, STOPPED, FINISHED, OFFLINE, MODIFIED	RUNNING
jobs[].jobStatus.milestones	List	List of production status information based on milestones		
jobs[].jobStatus.milestones[].calculatedProgress	Int	Progress to finish a milestone in % calculated by Prinect for automatic milestones.		0
jobs[].jobStatus.milestones[].milestoneDefId	String	Internal ID of the milestone. Please refer to /rest/masterdata/milestone		ID0c2e19bf1efc40c6bc09b9eaaac67100
jobs[].jobStatus.milestones[].status	String	Status of the milestone.	UNKNOWN, NORMAL, USER_FINISHED, PROGRESS_FINISHED, NOT_PLANNED	NORMAL
jobs[].jobStatus.milestones[].comment	String	Comment for manually checked milestones		
jobs[].productionMonitorUrl	String	URL for a detailed status panel may be shown in a browser window		

3.1.5 /rest/job/[jobId]/workstep/[workstepId] (GET)

Provides workstep information of the workstep by the given JobId and WorkstepId.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where information are requested for.		140512-1429
Path	workstepId	String	yes	The WorkstepId of the workstep, where information is requested for		123456

Return value:

Name	Type	Description	Valid values	Sample

workstep	List	List of all worksteps belonging to the jobid specified.		
workstep[].job	Object	Job information		
workstep[].job.id	String	ID of the job.		140512-1531
workstep[].job.name	String	Name of the job.		Brochure
workstep[].id	String	ID of the workstep (system internal)		_140512_153037680_003138
workstep[].name	String	Name of the workstep.		Sheet1 5/0
workstep[].status	Enum	Status of the workstep	UNKNOWN, WAITING, RUNNING, SUSPENDED, COMPLETED, ABORTED	COMPLETED
workstep[].amountPlanned	Long	Planned amount.		
workstep[].wastePlanned	Long	Planned waste.		
workstep[].amountProduced	Long	Done amount.(Cycles)		
workstep[].wasteProduced	Long	Done waste.(Cycles)		
workstep[].deviceId	String	DeviceID of the devices on which the workstep ist o be / was produced.		
workstep[].types[]	List<String>	List of type information for the workstep.		ConventionalPrinting
workstep[].sequenceType	String	Type of the corresponding sequence.		SheetfedPrinting
workstep[].startPlanned	Datetime	Time at which the workstep should be started. Normally filled, if the workstep is scheduled.		2013-04-10T08:04:54+02:00
workstep[].endPlanned	Datetime	Time at which the workstep should be finished. Normally filled, if the workstep is scheduled.		2013-04-10T09:04:54+02:00
workstep[].start	Datetime	Time at which the workstep has been started.		2013-04-10T08:04:54+02:00
workstep[].end	Datetime	Time at which the workstep has been finished.		2013-04-10T09:04:54+02:00
workstep[].setuptimePlanned	Long	Time (duration) planned for setup in seconds		1500
workstep[].prodtimePlanned	Long	Time (duration) planned for production in seconds (setup time is not included)		800
workstep[].actualTimes	List			
workstep[].actualTimes[].timeTypeGroupName	String	Name of the time type category		Auxilliary time
workstep[].actualTimes[].timeTypeName	String	Name of the time type		Waiting
workstep[].actualTimes[].duration	Long	actual Time (duration) for timeTypeName in seconds		400

3.1.6 /rest/job/[jobId]/workstep/[workstepId]/quality (GET)

Provides the quality measurement data of a workstep. The request /quality will provide data if the following versions are installed at the color measurement devices used for measurement:

- Image Control: >= I13
- Inpress Control / AxisControl: S10A.018, >= S12B.00

Please note: The Prinect API does not provide quality data measured by Prinect Inpress Control by default. To get access for this data, please contact your Heidelberg sales representative.

paging : the paging behaviour did not change and is different to the common description, this will be changed in the next version!

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where the milestone has to be set.		140512-1429

Path	workstepId	String	yes	Internal Workstep ID of a (sheetfed printing) workstep where the quality data are requested for.		_140512_153037680_003138
Parameter	page	Long	no	In case of a large amount of data, a paging may be necessary. To get the first data set, request without the page parameter or by page=0. Request the next pages by page=1 until the result will be empty.	0, 1, 2, ...	0
Parameter	pagesize	Long	no	the number of entities to get		
Parameter	zoneValues	String	no	If "false" (default), no ink zone color measurement values will be included in the response. These values will be provided if the parameter is set to "true". Please be aware: Including the ink zone measurement values will decrease response time significantly.	false, true	false

Return value:

Name	Type	Description	Valid values	Sample
quality	Object			
quality.workstep	Object	Workstep information.		
quality.workstep.job	Object	Job information		
quality.workstep.job.id	String	ID of the job		140512-1531
quality.workstep.job.name	String	Name ofthe job.		Brochure
quality.workstep.id	String	ID of the workstep (system internal)		_140512_153037680_003138
quality.workstep.name	String	Name of the workstep.		Sheet1 5/0
quality.printQuality	Object	Container for quality information		
quality.printQuality.colorMeasurements	List	List of measurements captured for the workstep.		
quality.printQuality.colorMeasurements[].colorMeasurementDevice	Object	Measurement device information.		
quality.printQuality.colorMeasurements[].colorMeasurementDevice.colorMeasurementDeviceType	Enum	Type of the measurement device	Unknown, AxisControl, ImageControl, InpressControl	InpressControl
quality.printQuality.colorMeasurements[].colorMeasurementNumber	Long	Measurement no. Inctemented by any measurement recorded, starting from 1.		1
quality.printQuality.colorMeasurements[].front	Bool	true: front side measurement, false: back side	true, false	true
quality.printQuality.colorMeasurements[].grade	Enum		Unknown, GlossCoatedPaper, GlossCoatedWebPaper, MattCoatedPaper, UncoatedWhitePaper, UncoatedYellowishPaper	GlossCoatedPaper
quality.printQuality.colorMeasurements[].illumination	Enum		Unknown, D50, D65	D50
quality.printQuality.colorMeasurements[].measurementFilter	Enum	Optical filter used during color measurement.	Unknown, None, Pol, UV	Pol
quality.printQuality.colorMeasurements[].observer	Long	Observer in degree.		2
quality.printQuality.colorMeasurements[].printControlStrip	String	Name of Print control strip.		Micro-6
quality.printQuality.colorMeasurements[].whiteBase	Enum		Unknown, Absolute, Paper	
quality.printQuality.colorMeasurements[].timestamp	Date	Time of the color measurement.		2014-05-12T16:30:16+02:00
quality.printQuality.colorMeasurements[].totalProductionCounter	String	The current press total production counter assigned to the measurement.		123456789
quality.printQuality.colorMeasurements[].paperWhite	Object	Value of the measured paper whiteness using the L*a*b* color space.		
quality.printQuality.colorMeasurements[].paperWhite.l	Double			92.1100
quality.printQuality.colorMeasurements[].paperWhite.a	Double			0.08799

quality.printQuality.colorMeasurements[].paperWhite.b	Double			-0.8399
quality.printQuality.colorMeasurements[].unitColorMeasurements	List	List of measurement information for each print unit		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].id	Long	Print unit numer, starting from 0		0
quality.printQuality.colorMeasurements[].unitColorMeasurements[].ColorReference	Object			
quality.printQuality.colorMeasurements[].unitColorMeasurements[].ColorReference.ColorName	String			Cyan
quality.printQuality.colorMeasurements[].unitColorMeasurements[].density	Double			1.3999
quality.printQuality.colorMeasurements[].unitColorMeasurements[].measuredColor	Object			
quality.printQuality.colorMeasurements[].unitColorMeasurements[].measuredColor.l	Double			85.0699
quality.printQuality.colorMeasurements[].unitColorMeasurements[].measuredColor.a	Double			-4.1630
quality.printQuality.colorMeasurements[].unitColorMeasurements[].measuredColor.b	Double			95.0599
quality.printQuality.colorMeasurements[].unitColorMeasurements[].unitDotGainMeasurements	List	List of avail. dotgain measurements.		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].unitDotGainMeasurements[].dotGain	Double	Dot gain in %		14
quality.printQuality.colorMeasurements[].unitColorMeasurements[].unitDotGainMeasurements[].tonalValue	Long	Tonal value in %		40
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[]	List	The measured color values of all ink zones of a printing unit. The size of this list is zero until the parameter "zoneValues" is set to "true".		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].zoneID	Long	Number of the ink zone.	1...64	1
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].measuredColor.l	Double	L* value of the measured color using the L*a*b* color space.		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].measuredColor.a	Double	a* value of the measured color using the L*a*b* color space.		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].measuredColor.b	Double	b* value of the measured color using the L*a*b* color space.		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].density	Double	Solid ink density.		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].zoneDotGainMeasurements	List	The measured dot gains .		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].zoneDotGainMeasurements[].dotGain	Double	Dot gain in %		
quality.printQuality.colorMeasurements[].unitColorMeasurements[].zoneColorMeasurements[].zoneDotGainMeasurements[].tonalValue	Long	Tonal value in %		

3.1.7 /rest/job/[jobId]/workstep/[workstepId]/activity (GET)

The request provides a log of finished activities (operations) describing the production of the workstep, sorted by time descending.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where the milestone has to be set.		140512-1429
Path	workstep Id	String	yes	Internal Workstep ID of a (sheetfed printing) workstep where the quality data are requested for.		_140512_153037680 _003138
Parameter	locale	String	no	Indicates the locale for the Activity Name (if Prinect standard configuration is used).		en

Return value:

Name	Type	Description	Valid values	Sample
activities	Object			
activities[].startTime	Date	Start time of the activity.		2014-05-12T16:32:41+02:00
activities[].endTime	Date	End time of the activity.		2014-05-12T16:40:28+02:00
activities[].id	String	ID of the activity		4100
activities[].name	String	Name of the activity		Good production
activities[].goodCycles	Long	Good amount produced in interval.		1000
activities[].wasteCycles	Long	Waste amount produced in interval.		0
activities[].timeTypeName	String	Name of the TimeType assigned to the activity.		Execution time
activities[].timeTypeGroupName	String	Name of the TimeTypeGroup where the TimeType is assigned to.		Production time
activities[].device	Object	Device Information		
activities[].device.id	String	ID of the device		1234
activities[].device.name	String	Name of the device.		XL105-4
activities[].workstep	Object	Information about the active workstep in interval.		
activities[].workstep.id	String	ID of the workstep (system internal)		_140512_153037680_003138
activities[].workstep.name	String	Name of the workstep		Sheet1 5/0
activities[].workstep.job	Object	Job information		
activities[].workstep.job.id	String	ID of the Job.		140512-1531
activities[].workstep.job.name	String	Name of the Job		Brochure
activities[].costCenter	String	Identification of the Cost Center		CC-SF-4C
activities[].comment	String	Comment entered by the user at start of the activity		"any comment"
employees	List	List of all user information		
employees[].name	String			Marcipane
employees[].firstName	String			Antonio
employees[].id	String	Staff ID of the employee		4759

3.1.8 /rest/job/[jobId]/workstep/[workstepId]/preview (GET)

The request provides the related previews of a workstep.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where the milestone has to be set.		140512-1429
Path	workstep Id	String	yes	Internal Workstep ID of a (sheetfed printing) workstep where the quality data are requested for.		_140512_153037680 _003138

Return value:

Name	Type	Description	Valid values	Sample
previews	Object	The list of previews.		

previews[].previewType	Enum	The type of a preview.	sheet_front: Frontside of a sheet sheet_back: Backside of a sheet page: preview of PDF page	sheet_front
previews[].mimeType	String	The MIME Type of the preview.		`image/png`
previews[].data	String	Base64 encoded String of the preview data.		

3.1.9 /rest/job/[jobId]/workstep/[workstepId]/inkConsumption (GET)

The request provides the related ink consumptions of a workstep.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where the milestone has to be set.		140512-1429
Path	workstep Id	String	yes	Internal Workstep ID of a (sheetfed printing) workstep where the ink consumption data are requested for.		_140512_153037680_003138

Return value:

Name	Type	Description	Valid values	Sample
inkConsumption	Object	The list of estimated amount of ink for each color in the workstep.		
inkConsumption[].color	String	The separation name.		Magenta
inkConsumption[]. estimatedConsumption	double	The estimated ink quantity in kg / 1000 Impressions of the workstep (calculated always at 100% Paper ink consumption factor)		`0.0635`

3.1.10 /rest/job/[jobId]/element (GET)

Provides Information about plates, press Sheets and pages of the job by the given JobID.

The deprecated fields colorFront and colorBack in elements.pressSheets[] have been removed.

ParamType	Name	DataType	Required	Description	Valid values	Sample	
Path	jobid	String	yes	ID of the job where information are requested for.		140512-1429	
Parameter	query	Enum	no	Specifies the scope of the response.	PAGES, SHEETS, PLATES, ALL	ALL	

Return value:

Name	Type	Description	Valid values	Sample
elements	Object			
elements.pressSheets	List			
elements.pressSheets[]. layoutName	String	Name of the Layout		SN25723
elements.pressSheets[]. layoutId	String	Prinect internal Layout ID (required i.e. for approval via Prinect API)		
elements.pressSheets[]. sheetName	String	Name of the sheet		SN25723
elements.pressSheets[]. variantID	String	ID of the variant.		
elements.pressSheets[]. brand	String	Brand Name of the paper		Prinect Special Cover 74
elements.pressSheets[]. quality	Long	Grade of the paper ISO 12647		1
elements.pressSheets[]. width	Double	Width of the paper (point)		2040.94488189
elements.pressSheets[]. height	Double	Height of the paper (point)		1502.36220472

elements.pressSheets[]. weight	Double	Weight of the paper (g/m^2)		200
elements.pressSheets[]. surfaces[]	List			
elements.pressSheets[]. surfaces[].name	Enum		Front, Back	Front
elements.pressSheets[]. surfaces[].colors	List<String>	Names of the colors on the surface of the sheet		[Black , Cyan , Magenta ,Yellow]
elements.pressSheets[]. surfaces[].inkConsumption	List	the estimated ink consumption		
elements.pressSheets[]. surfaces[].inkConsumption[]. color	String			black
elements.pressSheets[]. surfaces[].inkConsumption[]. estimatedConsumption	Double	The estimated ink quantity in kg / 1000 Sheets (calculated always at 100% Paper ink consumption factor)		0.129366
elements.pressSheets[]. surfaces[].thumbnail	String	encoded URL, to be used in the content/file rest call		
elements.pressSheets[]. surfaces[].statusCA	Enum	Status customer approval	APPROVED, REJECTED, UNCHECKED	
elements.pressSheets[]. surfaces[]. statusCAComment	String	Last customer approval comment.		
elements.pressSheets[]. surfaces[].statusPA	Enum	Status production approval		
elements.pressSheets[]. surfaces[]. statusPAComment	String	Last production approval comment.		
elements.pressSheets[]. articles	List	List of placed articles at the press sheet. **DEPRECATED**		
elements.pressSheets[]. articles[].name	String	Name of the article.		
elements.pressSheets[]. articles[].repeats	Int	Number of repeats of the article at the sheet.		
elements.pressSheets[]. foldingSheets	List	foldingSheets on PressSheet		
elements.pressSheets[]. foldingSheets[].id	String	folding sheet Id (system-wide unique)		
elements.pressSheets[]. foldingSheets[]. foldingScheme	String	Folding scheme (CIP4)		F16-6
elements.pressSheets[]. foldingSheets[].assemblyId	String	identification of the product part		
elements.pressSheets[]. foldingSheets[].name	String	Name of folding sheet (including name of the folding scheme)		F16-06_dd_4x2
elements.pressSheets[]. foldingSheets[].height	Double	Folding Sheet height (points)		
elements.pressSheets[]. foldingSheets[].width	Double	Folding Sheet width (points)		
elements.pressSheets[]. foldingSheets[].position	String	Folding sheet position regarding the final product and identification of the layout (first 2 positions)		
elements.pressSheets[]. foldingSheets[].copies	Int	number of identical folding Sheets		4
elements.pages	List			
elements.pages[].pageID	Long	Internal Page ID for approval reference		0
elements.pages[]. numberinpagefile	Int	Index of the page in the original document.		1
elements.pages[]. pagelistName	String	Name of the pagelist **DEPRECATED**		PL_HDcityLayout102

elements.pages[].pagelists	List	List of all pagelists the page is assigned to		
elements.pages[].pagelists[].pagelistName	String	Name of the pagelist		PL_HDcityLayout102
elements.pages[].pagelists[].positions	List<String>	The positions the page is assigned to		[2 , 7]
elements.pages[].name	String	Name of the page		Pages_1-36_6C - 01
elements.pages[].width	Double	Width of the page (point)		595.27603
elements.pages[].height	Double	Height of the page (point)		841.88998
elements.pages[].colors	List<String>	Names of the colors on the page		[Cyan , Magenta , Yellow , Black , HD Gray , PANTONE 281 C]
elements.pages[].preflightStatus	Enum	Result of page preflight.	UNKNOWN, OK, WARNING, ERROR	
elements.pages[].preflightReport	String	encoded URL, to be used in the content/file rest call		
elements.pages[].preview	String	encoded URL, to be used in the content/file rest call		
elements.pages[].statusCA	Enum	Status customer approval	APPROVED, REJECTED, UNCHECKED	
elements.pages[].statusCAComment	String	Last customer approval comment		
elements.pages[].statusPA	Enum	Status production approval		
elements.pages[].statusPAComment	String	Last production approval comment	production approval comment	
elements.plates	List			
elements.plates[].layoutName	String	Name of the Layout		SN25723
elements.plates[].layoutID	String	ID of the Layout		
elements.plates[].sheetName	String	Name of the sheet		SN25723
elements.plates[].variantID	String	ID of the variant		
elements.plates[].separationName	String	name of the separation		Black
elements.plates[].id	String	ID of the plate		7487400001000
elements.plates[].width	Double	Width of the plate (point)		1488.18897638
elements.plates[].height	Double	Height of the plate (point)		1301.1023622
elements.plates[].color	String	Name of the color of the plate		Magenta
elements.plates[].surfaceName	Enum		Front, Back	
elements.plates[].plateStatus	Enum	Status plate availibility	UNAVAILABLE, TO_BE_APPROVED, AVAILABLE, REJECTED, APPROVED, IMAGED PENDING status "PENDING" : plate data are calculated and waiting to be imaged by a plate setter status "IMAGED" : plate is imaged, this status can only appear in a scenario with an external plate handling system status "AVAILABLE" : in a scenario with an external plate handling system the meaning is : the plate is on a plate trolley, otherwise it means the plate is imaged	

3.1.11 /rest/job/[jobId]/workstep/[worksteplId]/element (GET)

Provides Information about plates, press Sheets and pages of a workstep if these elements are assigned to the workstep.

The deprecated fields colorFront and colorBack in elements.pressSheets[] have been removed.

ParamType	Name	DataType	Required	Description	Valid values	Sample	

Path	jobid	String	yes	ID of the job where the milestone has to be set.		140512-1429	
Path	workstepId	String	yes	Internal Workstep ID of a (sheetfed printing) workstep where the quality data are requested for.		_140512_153037680_003138	
Parameter	query	Enum	no	Specifies the scope of the response.	PAGES, SHEETS, PLATES, ALL	ALL	

Return value :

Name	Type	Description	Valid values	Sample
elements	Object			
elements.pressSheets	List			
elements.pressSheets[].layoutName	String	Name of the Layout		SN25723
elements.pressSheets[].layoutId	String	Prinect internal Layout ID (required i.e. for approval via Prinect API)		
elements.pressSheets[].sheetName	String	Name of the sheet		SN25723
elements.pressSheets[].variantID	String	ID of the variant.		
elements.pressSheets[].brand	String	Brand Name of the paper		Prinect Special Cover 74
elements.pressSheets[].quality	Long	Grade of the paper ISO 12647		1
elements.pressSheets[].width	Double	Width of the paper (point)		2040.94488189
elements.pressSheets[].height	Double	Height of the paper (point)		1502.36220472
elements.pressSheets[].weight	Double	Weight of the paper (g/m^2)		200
elements.pressSheets[].surfaces[]	List			
elements.pressSheets[].surfaces[].name	Enum		Front, Back	Front
elements.pressSheets[].surfaces[].colors	List<String>	Names of the colors on the surface of the sheet		[Black , Cyan , Magenta ,Yellow]
elements.pressSheets[].surfaces[].inkConsumption	List	the estimated ink consumption		
elements.pressSheets[].surfaces[].inkConsumption[].color	String			black
elements.pressSheets[].surfaces[].inkConsumption[].estimatedConsumption	Double	The estimated ink quantity in kg / 1000 Sheets (calculated always at 100% Paper ink consumption factor)		0.129366
elements.pressSheets[].surfaces[].thumbnail	String	encoded URL, to be used in the content/file rest call		
elements.pressSheets[].surfaces[].statusCA	Enum	Status customer approval	APPROVED, REJECTED, UNCHECKED	
elements.pressSheets[].surfaces[].statusCAComment	String	Last customer approval comment.		
elements.pressSheets[].surfaces[].statusPA	Enum	Status production approval		
elements.pressSheets[].surfaces[].statusPAComment	String	Last production approval comment.		
elements.pressSheets[].articles	List	List of placed articles at the press sheet. **DEPRECATED**		
elements.pressSheets[].articles[].name	String	Name of the article.		

elements.pressSheets[].articles[].repeats	Int	Number of repeats of the article at the sheet.		
elements.pressSheets[].foldingSheets	List	foldingSheets on PressSheet **Not yet implemented for /workstep. To get this information, use /job /element**		
elements.pressSheets[].foldingSheets[].id	String	folding sheet Id (system-wide unique)		
elements.pressSheets[].foldingSheets[].foldingScheme	String	Folding scheme (CIP4)		F16-6
elements.pressSheets[].foldingSheets[].assemblyId	String	identification of the product part		
elements.pressSheets[].foldingSheets[].name	String	Name of folding sheet (including name of the folding scheme)		F16-06_dd_4x2
elements.pressSheets[].foldingSheets[].height	Double	Folding Sheet height (points)		
elements.pressSheets[].foldingSheets[].width	Double	Folding Sheet width (points)		
elements.pressSheets[].foldingSheets[].position	String	Folding sheet position regarding the final product and identification of the layout (first 2 positions)		
elements.pressSheets[].foldingSheets[].copies	Int	number of identical folding Sheets		4
elements.pages	List			
elements.pages[].pagelistName	String	Name of the pagelist		PL_HDcityLayout102
elements.pages[].name	String	Name of the page		Pages_1-36_6C - 01
elements.pages[].width	Double	Width of the page (point)		595.27603
elements.pages[].height	Double	Height of the page (point)		841.88998
elements.pages[].colors	List<String>	Names of the colors on the page		[Cyan , Magenta , Yellow , Black , HD Gray , PANTONE 281 C]
elements.pages[].preflightStatus	Enum	Result of page preflight.	UNKNOWN, OK, WARNING, ERROR	
elements.pages[].preflightReport	String	encoded URL, to be used in the content/file rest call		
elements.pages[].preview	String	encoded URL, to be used in the content/file rest call		
elements.pages[].statusCA	Enum	Status customer approval	APPROVED, REJECTED, UNCHECKED	
elements.pages[].statusCAComment	String	Last customer approval comment		
elements.pages[].statusPA	Enum	Status production approval		
elements.pages[].statusPAComment	String	Last production approval comment	production approval comment	
elements.plates	List			
elements.plates[].layoutName	String	Name of the Layout		SN25723
elements.plates[].layoutID	String	ID of the Layout		
elements.plates[].sheetName	String	Name of the sheet		SN25723
elements.plates[].variantID	String	ID of the variant		
elements.plates[].separationName	String	name of the separation		Black
elements.plates[].id	String	ID of the plate		7487400001000
elements.plates[].width	Double	Width of the plate (point)		1488.18897638
elements.plates[].height	Double	Height of the plate (point)		1301.1023622

elements.plates[].color	String	Name of the color of the plate		Magenta
elements.plates[]. surfaceName	Enum		Front, Back	
elements.plates[].plateStatus	Enum	Status plate availibility	UNAVAILABLE, TO_BE_APPROVED, AVAILABLE, REJECTED, APPROVED, IMAGED PENDING status "PENDING" : plate data are calculated and waiting to be imaged by a plate setter status "IMAGED" : plate is imaged, this status can only appear in a scenario with an external plate handling system status "AVAILABLE" : in a scenario with an external plate handling system the meaning is : the plate is on a plate trolley, otherwise it means the plate is imaged	

3.1.12 /rest/job/[jobId]/element/page (POST)

Sets the approval status and approval comment for an existing page.

ParamType	Name	DataType	Required	Description	Valid values	Sample	Default
Path	jobid	String	yes	ID of the job to set elements approval.		140512-1429	

Request data:

Name	Type	Description	Valid values	Sample
pages	List			
pages[].pagelistName	String	Name of the pagelist		????
pages[].name	String	Name of the page		Pages_1-36_6C - 01
pages[].pageID	Long	Internal ID of the page		
pages[].numberinpagefile	String	number of the page in the pagefile		
pages[].customerapprovalStatus	Enum	Status customer approval	APPROVED,REJECTED, UNCHECKED	
pages[].customerapprovalComment	String	comment for the customer approval		
pages[].productionapprovalStatus	Enum	Status production approval	APPROVED,REJECTED, UNCHECKED	
pages[].productionapprovalComment	String	comment for the production approval		

Return value:

error.code OK, RUNTIME_ERROR.

The return data provides the status of the elements specified in the request. If requested element doen't exist in the System it will be not included in the response.

Name	Type	Description	Valid values	Sample
elements	Object			
elements.pages	List			
elements.pages[]. pagelistName	String	Name of the pagelist		????
elements.pages[].name	String	Name of the page		Pages_1-36_6C - 01
elements.pages[].width	Double	Width of the page (point)		595.27603
elements.pages[].height	Double	Height of the page (point)		841.88998
elements.pages[].colors	List<String>	Names of the colors on the page		[Cyan , Magenta , Yellow , Black , HD Gray , PANTONE 281 C]
elements.pages[]. preflightStatus	Enum		UNKNOWN, OK, WARNING, ERROR	

elements.pages[]. preflightReport	String			
elements.pages[].preview	String			
elements.pages[].statusCA	Enum	Status customer approval	APPROVED,REJECTED, UNCHECKED	
elements.pages[].statusPA	Enum	Status production approval	APPROVED,REJECTED, UNCHECKED	

3.1.13 /rest/job/[jobId]/element/sheet (POST)

This sets the approval status and approval comment for an existing sheet.

ParamType	Name	DataType	Required	Description	Valid values	Sample	Default
Path	jobid	String	yes	ID of the job to set elements approval.		140512-1429	

Request data:

Name	Type	Description	Valid values	Sample
pressSheets	List			
pressSheets[].layoutID	String	ID of the Layout		SN25723
pressSheets[].sheetName	String	Name of the sheet		SN25723
pressSheets[].variantID	String	ID of the variant		
pressSheets[].surfaces[]	List			
pressSheets[].surfaces[].name	Enum		FRONT, BACK	FRONT
pressSheets[].surfaces[].customerapprovalStatus	Enum	Status customer approval	APPROVED,REJECTED, UNCHECKED	
pressSheets[].surfaces[].customerapprovalComment	String	comment for the customer approval		
pressSheets[].surfaces[].productionapprovalStatus	Enum	Status production approval	APPROVED,REJECTED, UNCHECKED	
pressSheets[].surfaces[].productionapprovalComment	String	comment for the production approval		

Return value:

error.code OK, RUNTIME_ERROR.

The return data provides the status of the elements specified in the request. If requested element doen't exist in the system it will be not included in the response.

Name	Type	Description	Valid values	Sample
elements	Object			
elements.pressSheets	List			
elements.pressSheets[].layoutName	String	Name of the Layout		SN25723
elements.pressSheets[].layoutId	String	Prinect internal Layout ID (required i.e. for approval via Prinect API)		
elements.pressSheets[].sheetName	String	Name of the sheet		SN25723
elements.pressSheets[].variantID	String	ID of the variant.		
elements.pressSheets[].brand	String	Brand Name of the paper		Prinect Special Cover 74
elements.pressSheets[].quality	Long	Grade of the paper ISO 12647		1
elements.pressSheets[].width	Double	Width of the paper (point)		2040.94488189
elements.pressSheets[].height	Double	Height of the paper (point)		1502.36220472
elements.pressSheets[].weight	Double	Weight of the paper (g/m^2)		200

elements.pressSheets[].colorsFront	List<String>	Names of the colors on the front surface of the sheet **DEPRECATED**		[Black , Cyan , Magenta ,Yellow]
elements.pressSheets[].colorsBack	List<String>	Names of the colors on the back surface of the sheet **DEPRECATED**		[Black , Cyan , Magenta ,Yellow]
elements.pressSheets[].surfaces[]	List			
elements.pressSheets[].surfaces[].name	Enum		Front, Back	Front
elements.pressSheets[].surfaces[].colors	List<String>	Names of the colors on the surface of the sheet		[Black , Cyan , Magenta ,Yellow]
elements.pressSheets[].surfaces[].thumbnail	String			
elements.pressSheets[].surfaces[].statusCA	Enum	Status customer approval	APPROVED, REJECTED, UNCHECKED	
elements.pressSheets[].surfaces[].statusCAComment	String	customer approval comment		
elements.pressSheets[].surfaces[].statusPA	Enum	Status production approval		
elements.pressSheets[].surfaces[].statusPAComment	String	production approval comment		
elements.pressSheets[].articles	List	List of placed articles at the press sheet. **DEPRECATED**		
elements.pressSheets[].articles[].name	String	Name of the article.		
elements.pressSheets[].articles[].repeats	Int	Number of repeats of the article at the sheet.		
elements.pressSheets[].foldingSheets	List	foldingSheets on PressSheet		
elements.pressSheets[].foldingSheets[].id	String	folding sheet Id (system-wide unique)		
elements.pressSheets[].foldingSheets[].foldingScheme	String	Folding scheme (CIP4)		F16-6
elements.pressSheets[].foldingSheets[].assemblyId	String	identification of the product part		
elements.pressSheets[].foldingSheets[].name	String	Name of folding sheet (including name of the folding scheme)		F16-06_dd_4x2
elements.pressSheets[].foldingSheets[].height	Double	Folding Sheet height (points)		
elements.pressSheets[].foldingSheets[].width	Double	Folding Sheet width (points)		
elements.pressSheets[].foldingSheets[].position	String	Folding sheet position regarding the final product and identification of the layout (first 2 positions)		
elements.pressSheets[].foldingSheets[].copies	Int	number of identical folding Sheets		4

3.1.14 /rest/job/[jobId]/element/plate (POST)

This sets the approval status and approval comment for an existing plate.

This kind of approval will only work if the approval feature has been activated in the sequences for **plate making** and **printing** in this job!

ParamType	Name	DataType	Required	Description	Valid values	Sample	Default
Path	jobid	String	yes	ID of the job to set elements approval.		140512-1429	

Request data:

Name	Type	Description	Valid values	Sample
plates	List			
plates[].layoutID	String	ID of the Layout		SN25723
plates[].sheetName	String	Name of the sheet		SN25723
plates[].variantID	String	ID of the variant		
plates[].color	String	Name of the color of the plate		Magenta
plates[].surfaceName	Enum		Front, Back	
plates[].separationName	String		Front, Back	
plates[].approvalStatus	Enum	Status of the plate approval	APPROVED,REJECETD, UNCHECKED	
plates[].approvalComment	String	production approval comment		

Return value:

error.code OK, RUNTIME_ERROR.

The return data provides the status of the elements specified in the request. If requested element doen't exist in the system it will be not included in the response.

Name	Type	Description	Valid values	Sample
elements	Object			
elements.plates	List			
elements.plates[].layoutName	String	Name of the Layout		SN25723
elements.plates[].layoutID	String	ID of the Layout		
elements.plates[].sheetName	String	Name of the sheet		SN25723
elements.plates[].variantID	String	ID of the variant		
elements.plates[].separationName	String	name of the separation		Black
elements.plates[].id	String	ID of the plate		7487400001000
elements.plates[].width	Double	Width of the plate (point)		1488.18897638
elements.plates[].height	Double	Height of the plate (point)		1301.1023622
elements.plates[].color	String	Name of the color of the plate		Magenta
elements.plates[].surfaceName	Enum		Front, Back	
elements.plates[].plateStatus	Enum	Status plate availibility	UNAVAILABLE, TO_BE_APPROVED, AVAILABLE, REJECTED, APPROVED, IMAGED PENDING status "PENDING" : plate data are calculated and waiting to be imaged by a plate setter status "IMAGED" : plate is imaged, this status can only appear in a scenario with an external plate handling system status "AVAILABLE" : in a scenario with an external plate handling system the meaning is : the plate is on a plate trolley, otherwise it means the plate is imaged	

3.1.15 /rest/job/action/subscription (POST)

This call sets a subscription for notification messages.

After the subscription is created, messages according to those subscription type will be sent to the receiver URL via http POST.

If the receiver service is not available, the messages will be queued and sent immediately after the receiver service is available again. The subscription will be deleted finally a after a number of days of receiver inactivity (42 in Prinect 2018).

Valid receiver URI schemes are : http and https

See also /rest/device/action/subscription.

ParamType	Name	DataType	Required	Description	Valid values	Sample
PARAMETER	action	Enum	yes	command to create or remove a subscription	create, delete	delete
PARAMETER	url	String	yes	receiver url, where the messages will be sent to		http://targethost:8888

This section describes the messages structure of the messages according to the subscription type. Only an extract will be documented, there are other information for internal use.

Notification Message

This message will be sent when a job reaches a certain processing state/milestone,

Name	Type	Description	Valid values	Sample
XJMF	object			
XJMF.SignalNotification[]	List			
XJMF.SignalNotification[].Notification[]	List			
XJMF.SignalNotification[].Notification[].ID	String			a.753733701. _160718_100928674_013824
XJMF.SignalNotification[].Notification[].Milestone[]	List			
XJMF.SignalNotification[].Notification[].Milestone[]. MilestoneType	String	defined in JDF Spec or user defined		
XJMF.SignalNotification[].Notification[].JobID	String	job ticket id		testBDE
XJMF.SignalNotification[].Notification[].TimeStamp	String	notification timestamp		2016-07-14T10:26:49+02:00

3.1.16 /rest/job/[jobid]/ticket (GET)

This call provides the Prinect native jobticket for a given job.

PLEASE NOTE: The structure of the jobticket is subject of change without notification. Content and structure may vary in dependence of Prinect version. It is highly recommended to use PrinectAPI calls returning a defined JSON structure instead of any direct access to the jobticket given here.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	jobid	String	yes	ID of the job where information are requested for.		140512-1429

Return value: Jobticket file is returned as stream, in case of an exception the return structure looks like

<xml><errortext>"the errortext" </errortext></xml>

The current prinect system version in the resulting JDF is located in the JDF element as an attribute HDM:PrinectVersion . Below is an example :

<JDF Activation="Active" DescriptiveName="J09-0031" HDM:FormatVersion="1.4" HDM:GlobalJobStatus="Active" HDM:HasPPF="true" HDM: KeepMISColorantControl="true" HDM:PrinectVersion="18.0" ....

3.1.17 /rest/job/[jobId]/workstep/[workstepId]/output (GET)

Reports the detailled output of a given device, in detail about the sheets that had been printed. Supported for Sheetfed Press only. Data are kept for max. 15 days.

ParamType	Name	DataType	Required	Description	Valid values	Sample

PATH	jobId	String	yes	job id		
PATH	workstepId	String	yes	id of the printing workstep		
PARAMETER	page	Long	no	limit the output to page (page * pagesize)		
PARAMETER	pagesize	Long	no	number of entries to be fetched		

Return value:

Name	Type	Description	Valid values	Sample
output	object			
outputElements	List	List of print intervals, limited by start- and endcounter		
output.outputElements[].timestamp	String	Date (UTC time) when the interval is been tracked		2019-10-30T13:10:15+00:00
output.outputElements[].sheetCounterStart	Int	SheetID of the first sheet tracked in this bunch		12350
output.outputElements[].sheetCounterEnd	Int	SheetID of the last sheet tracked in this bunch		
output.outputElements[].sheetType	Enum	type of the sheet	AdvanceSheet, CleaningSheet, MissingSheet, NonStopPileChangeSheet, PrintedSheet, SampleSheet, StartupSheet, UnprintedSheet	MissingSheet
output.outputElements[].classification	Enum	sheet classification	Good, Waste, Unprinted	Unprinted
output.outputElements[].destination	Enum	Target destination after printing	DeliveryPile, SampleSheetTable, WasteCollector	WasteCollector
output.outputElements[].errorDetails	Enum	Details about an eventual error	BadSheetDetection, NotAvailable, PullError	Okay
output.outputElements[].inspectionState	Enum	State reported by the inspection system : NotAvailable : Inspection system not available. NotRequired : Inspection not required for the sheets in the bunch. Okay : Inspection has been done successfully. UnknownError : Inpection required but not done due to an unknown error.	NotAvailable, NotRequired, Okay, UnknownError	NotRequired
output.outputElements[].codeInspectionState	Enum	state reported by the code inspection system NotAvailable : Code inspection system not available.	NotAvailable, NotRequired, Okay, UnknownError	Warning
output.outputElements[].qualityDeviation	Enum	state reported by the Color measurement system NotAvailable : Color measurement system not available / licenced or switched off. Okay : Target color distance within OK range. Large : Large target color distance detected. Medium : Medium target color distance detected. | Small | Small target color distance detected.|	NotAvailable, Okay, Large, Medium, Small, NotRequired, UnkownError	Small
output.outputElements[].sheetInfos	List	Provides sheet based details information		
output.outputElements[].sheetInfos[].sheetCounter	Int	index between sheetCounter1 and sheetCounter2		567133
output.outputElements[].sheetInfos[].customSheetCode	String	customer defined sheet id		Q7DB6Z
output.outputElements[].sheetInfos[].errorsCode	Int	stores the number of erroneous codes detected by the code inspection on the sheet (e.g., bar codes, etc.).		3
output.outputElements[].sheetInfos[].errorsLarge	Int	stores the number of large errors detected by the inspection system on the sheet, the associated error size can be individually configured.		2
output.outputElements[].sheetInfos[].errorsMedium	Int	stores the number of medium errors detected by the inspection system on the sheet, the associated error size can be individually configured.		4
output.outputElements[].sheetInfos[].errorsSmall	Int	stores the number of small errors detected by the inspection system on the sheet, the associated error size can be individually configured.		0

3.2 Device API

3.2.1 /rest/device (GET)

Gets a list of all configured devices.

Return value:

Name	Type	Description	Valid values	Sample
devices	List<Device Object>	List of device objects. Each device contains the structure which is described in the return value of /rest/device/[deviceId].		

3.2.2 /rest/device/[deviceId] (GET)

Privides information about a specific device.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	deviceId	String	yes	ID of the device where information are requested for.		

Return value:

Name	Type	Description	Valid values	Sample
device	Object			
device.id	String	ID of the device.		
device.name	String	Name of the device.		
device.classId	String	Device category information.		ID_SheetfedPress
device.deviceStatus.status	Enum	Status of the device	Unknown,Cleanup,Down, Idle, Running,Setup	Idle
device.deviceStatus.speed	Long	Speed of the machine		3000
device.deviceStatus.activity	String	The current activity of the device.		Setup
device.deviceStatus.totalizer	Long	The total machine counter		12346845648
device.deviceStatus.employees[].firstName	String	First name of an employee at the machine		John
device.deviceStatus.employees[].name	String	Last name of an employee at the machine		Doe
device.deviceStatus.employees[].id	String	Employee Id of an employee at the machine		4711
device.deviceStatus.workstep	Object	If a workstep is active at the machine the workstep object is filled with workstep information according to /rest/job/[jobId]/workstep/[workstepId] extended by job information.		
device.deviceStatus.workstep.job	Object	Job information		
device.deviceStatus.workstep.job.id	String	ID of the job.		140512-1531
device.deviceStatus.workstep.job.name	String	Name of the job.		Brochure
device.deviceStatus.workstep.job.customerOderId	String	The id of the order from customer side.		
device.deviceStatus.workstep.job.jobCustomer	Object	Customer information		
device.deviceStatus.workstep.job.jobCustomer.id	String	Customer ID		1234
device.deviceStatus.workstep.job.jobCustomer.name	String	Customer name		CentralPrintshop

3.2.3 /rest/device/[deviceId]/activity (GET)

The request provides a log of finished activities (operations) on a machine in the polling period, sorted by timestamp desc.

paging : the paging behaviour did not change and is different to the common description, this will be changed in the next version!

ParamType	Name	DataType	Required	Description	Valid values	Sample
PATH	deviceId	String	yes	ID of the device for which the activities are requested.		XL105-6
PARAMETER	start	Date	no	Begin of the interval requested.		2014-04-24T18:16:36+02:00
PARAMETER	end	Date	no	End of the interval requested.		2014-05-05T18:42:54+02:00
PARAMETER	page	Long	no	In case of a large amount of data, a paging may be necessary. To get the first data set, request without the page parameter or by page=0. Request the next pages by page=1 until the result will be empty.	0, 1, 2, ...	0
PARAMETER	pagesize	Long	no	The number of entities to get	1...	10

Return value:

Name	Type	Description	Valid values	Sample
activities	Object			
activities[].startTime	String	Start time of the activity.		2014-05-12T16:32:41+02:00
activities[].endTime	String	End time of the activity.		2014-05-12T16:40:28+02:00
activities[].id	String	ID of the activity		4100
activities[].name	String	Name of the activity		Good production
activities[].goodCycles	Long	Good amount produced in interval.		1000
activities[].wasteCycles	Long	Waste amount produced in interval.		0
activities[].timeTypeName	String	Name of the TimeType assigned to the activity.		Execution time
activities[].timeTypeGroupName	String	Name of the TimeTypeGroup where the TimeType is assigned to.		Production time
activities[].device	Object	Device Information		
activities[].device.id	String	ID of the device		1234
activities[].device.name	String	Name of the device.		XL105-4
activities[].workstep	Object	Information about the active workstep in interval.		
activities[].workstep.id	String	ID of the workstep (system internal)		_140512_153037680_003138
activities[].workstep.name	String	Name of the workstep		Sheet1 5/0
activities[].workstep.job	Object	Job information		
activities[].workstep.job.id	String	ID of the Job.		140512-1531
activities[].workstep.job.name	String	Name of the Job		Brochure
activities[].costCenter	String	Identification of the Cost Center		CC-SF-4C
activities[].comment	String	Comment entered by the user at start of the activity		"any comment"
activities[].employees	List	List of all user information		
activities[].employees[].name	String			Marcipane
activities[].employees[].firstName	String			Antonio
activities[].employees[].id	String	Staff ID of the employee		4759

3.2.4 /rest/device/[deviceId]/consumption (GET)

This call provides various consumption information for a device.

- Energy consumption information, if a meter had been installed at the device.
- Amount of plate changes for all printing units

For the energy consumption in the requested period, the energy consumption messages of the machine are added up in the period. The machine usually sends these messages every 60 seconds. Therefore, for short periods of time, the result does not exactly reflect the energy consumption during this period.

ParamType	Name	DataType	Required	Description	Valid values	Sample
PATH	deviceId	String	yes	ID of the device for which the activities are requested.		XL105-6
PARAMETER	start	Date	no	Begin of the interval requested.		2016-01-24T18:00:00+02:00
PARAMETER	end	Date	no	End of the interval requested.		2016-02-05T18:00:0+02:00

Return value:

Name	Type	Description	Valid values	Sample
consumption	object			
consumption.energy[]	List	List of energy consumption information splitted by energy consumption meters.		
consumption.energy[].meterName	String	Name of the energy consumption meter installed at the device.		CutStar
consumption.energy[].energyConsumption	Double	Energy consumption in kWh.		12350
plateChanges	Long	Amount of plate changes for all printing units NEW IN 2021		120

3.2.5 /rest/device/action/subscription (POST) NEW IN 2021

This request sets a subscription for status and resource signaling. Any status / resource information will be send automatically to the subscription target given by the request at the same time as generated by any sender in Prinect. This feature is compareable to the JMF integration included in Level3 MIS integration. This enables a message processing outside of Prinect for status or data processing applications.

In addition to subscribe for status/resource messages it is possible to subscribe for "color measurement files". Color measurement files will be generated from a HEIDELBERG color measurement device attached to a certain press and includes spectral measurement data. This function is avaliable from PressCenter version S20b. Another requirement is that the path to the color measurement files is a UNC path.

ParamType	Name	DataType	Required	Description	Valid values	Sample
PARAMETER	action	Enum	yes	command to create or remove a subscription	create, delete	delete
PARAMETER	url	String	yes	receiver url, where the messages will be sent to		http://targethost:8888
PARAMETER	type	Enum	No	the kind of description	StatusSignal, ResourceSignal, ColorMeasurement	ColorMeasurement

If "type" is not given, the subscription will be set for StatusSignal and ResourceSignal due to backward compatibility.

3.2.5.1 Status Signal

This signal will be sent after a device status change

	Type	Description	Valid values	Sample
XJMF	object			
XJMF.SignalStatus[]	List			
XJMF.SignalStatus[].DeviceID	String	Prinect Service which issues the message		ICSPortal
XJMF.SignalStatus[].Time	String	timestamp of device status change		2016-07-14T10:26:49+02:00
XJMF.SignalStatus[].DeviceInfo[]	List			
XJMF.SignalStatus[].DeviceInfo[].Status	Enum	Current device status information.	Idle, NonProductive, Offline, Production, Stopped	Idle
XJMF.SignalStatus[].DeviceInfo[].StatusDetails	Enum	Current device status detail information.		WashUp
XJMF.SignalStatus[].DeviceInfo[].Speed	Long	Speed of the machine		
XJMF.SignalStatus[].DeviceInfo[].TotalProductionCounter	String	press total production counter		

XJMF.SignalStatus[].DeviceInfo[].ProductionCounter	String	production counter which can be used by the printer		
XJMF.SignalStatus[].DeviceInfo[].EventID	String	Event which caused the status change, see list provided below.		@95
XJMF.SignalStatus[].DeviceInfo[].Activity[]	List			
XJMF.SignalStatus[].DeviceInfo[].Activity[].PersonalID	String	User who is logged on		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[]	List	Provides information about the job if a job is processed at the device.		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Status	Enum	Job Status	Aborted, Cleanup, Completed, InProgress, Setup, Stopped, Suspended, Waiting	Setup
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Amount	Long	Done amount (Good)		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].StartTime	Date	job start time		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].TotalAmount	Long	Amount planned		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Waste	Long	Done amount (Waste)		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].PercentCompleted	Int			
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].CostCenterID	String			
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].JobID	String	ID of the job.		Job125
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].WorkstepID	String	ID of the workstep (system internal)		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Part	List			
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Part[].Side	Enum		Front, Back	Front
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Part[].SheetName	String		Print sheet 1	
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Activity	List			
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Activity[].PersonalID	String			
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Activity[].StartTime	Date	start time of the activity		
XJMF.SignalStatus[].DeviceInfo[].JobPhase[].Activity[].ActivityID	String			2016-07-14T10:26:49+02:00
XJMF.SignalStatus[].DeviceInfo[].ModuleIDs	String		Module IDs affected	

For Heidelberg Sheetfed presses, a signal is fired in case of the following events. This variies depending on the PressCenter version and installed equipment:

EventID	Meaning	From Press Center version
8000 / 8001	Start / stop machine run	-
8002 / 8003	Start / stop ready to run	-
@47 / @48	Start / stop blanket washup	V47 upwards
@45 / @46	Start / stop washup impression cylinder	V47 upwards
@49 / @50	Start/ stop washup ink rollers	V47 upwards
8004 / 8005	Start / stop feeder active	-
8006 / 8007	Start / stop paper run	-
8008 / 8009	Start / stop printing	-

8010 / 8011	Start / stop dampening rollers	-
8012 / 8013	Start / stop dampening	-
8014 / 8015	Start / stop ink roller activity	-
8016 / 8017	Start / stop ink ductor	-
8018 / 8019	On / off good production counter	only V47 ⚠️
@53/ @54	Start / stop plate washing	V47 upwards
@51 / @52	Start / stop washup ink fountain roller	V47 upwards
@57 / @58	Start / stop missing sheet	S10a upwards
@59 / @60	Start / stop early sheet	V47 upwards
@61 / @62	Start / stop misaligned sheet	V47 upwards
@63 / @64	Start / stop double sheet	V47 upwards
@67 / @68	Start / stop side guide warning	V47 upwards
@69 / @70	Start / stop sheet infeed error	V47 upwards
@118 / @119	Start / stop printing interval	V47 upwards
8023	New machine speed	S15b upwards
8024	Current counts	- (implicitely in signals)
@41 / @42	Start / stop plate mounting	V47 upwards
@110 / @1	Power on / off	all (by CDM)
8029 / 8030	Start / stop good production	V47 upwards
@201 / @202	Start / stop lost sheet	S12b upwards
@203 / @204	Start / stop multiple sheet	S12b upwards
@221	Tab inserter	S14a upwards
@205 / @206	Start / stop overrunning sheet feeder	S12b upwards
@207 / @208	Start / stop overrunning sheet delivery	S15b upwards
@220	Palette change	S14a upwards
@17	Cyclic status update message	V47 upwards
@95	Start Job	V47 upwards
@96	Interrupt Job	V47 upwards
@97	End Job	V47 upwards
@112	Login Assistant	V47 upwards
@113	Logout Assistant	V47 upwards
@114	Login Operator	V47 upwards
@115	Logout Operator	V47 upwards
(any)	Manual input according configuration	V47 upwards

3.2.5.2 Ressource Signals

This signal will be sent after consuming material,

Name	Type	Description	Valid values	Sample
XJMF	object			
XJMF.SignalRessource[]	List			

XJMF.SignalRessource[].PersonalID	String	employee number		
XJMF.SignalRessource[].deviceID	String	Device which consumed the material		4202
XJMF.SignalRessource[].Time	String	consumption time		2016-07-14T10:26:49+02:00
XJMF.SignalRessource[].RessourceInfo[]	List			
XJMF.SignalRessource[].RessourceInfo[].Status	Enum	Ressource status	Incomplete, Rejected, Unavailable, InUse, Draft, Complete, Available	
XJMF.SignalRessource[].RessourceInfo[].ModuleID	String	the Module that the Resource is consumed or produced by		
XJMF.SignalRessource[].RessourceInfo[].Comment	List			
XJMF.SignalRessource[].RessourceInfo[].Comment[].Name	Enum	defines the usage of a comment	Description, DeviceText, Instruction, JobDescription, OperatorText, Orientation, TemplateDescription,	OperatorText
XJMF.SignalRessource[].RessourceInfo[].Comment[].#text	String	comment text	needed additional sheets	
XJMF.SignalRessource[].RessourceInfo[].ActualAmount	Long	Amount of material consumed		100
XJMF.SignalRessource[].RessourceInfo[].Unit	String	Unit of the amount		
XJMF.SignalRessource[].RessourceInfo[].JobID	String			
XJMF.SignalRessource[].RessourceInfo[].ExternalID	String	Material ID from external system		
XJMF.SignalRessource[].RessourceInfo[].ProductID	String	Material ID		100002
XJMF.SignalRessource[].RessourceInfo[].ResourceSet	List			
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].ModuleID	String	the Module that the Resource is consumed or produced by		
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].ResourceName	String	Name of the ressource		
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Level	Enum	Level of consumable resources in the device.	Empty, Low, Ok	
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Unit	String	Unit of the amount		kwH
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Name	String			
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Resource	List			
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Resource[].DescriptiveName	String			
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Resource[].AmountPool	List			
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Ressource[].AmountPool[].ActualAmount	Double	Amount of material produced		
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Resource[].AmountPool[].Amount	Double	Amount needed		
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Resource[].MiscConsumable	List	MiscConsumable Resource is intended for cost accounting, inventory control and availability scheduling		
XJMF.SignalRessource[].RessourceInfo[].ResourceSet[].Resource[].MiscConsumable[].ConsumableType	String	type of the MiscConsumable Resource	Developer, Electricity, FuserOil, Gas, Glue, Headband, RegistrationRibbon, Paperclips, Staples, WasteContainer, Wire	

3.2.5.3 Color Measurement Data

If there is a HEIDELBERG color measurement device configured at a press results of color measurements can be get as pure spectral data using this API method. In addition processed color measurement information can be get using /rest/job/[jobId]/workstep/[workstepId]/quality (see chapter 3.1.6).

Spectral data will be transferred as ISO 28178 compatible file and have to be processed accordingly.

Additional information about spectral data file:
- Measurement condition is described in attribute “FILTER” as M2 or M3
- JobID and WorkstepID are include in file. Using this information in API additional information about job can be get.
- Information about ink zone is included to each measurement patch

An API user can subscribe to these files.

One precondition is to activate and setup the color measurement file location at the press device configuration (Important : use UNC naming e.g. \\server\share...).

The PrinectAPI sends then a notification message for every new color measurement file to the specified receiver URL.

The server which receives the message has to confirm the receipt with HTTP OK .

The format of the notification message is a json structure :

Name	Type	Description	Valid values	Sample
deviceID	String	deviceID on which the measurement was made		1200
fileName	String	the original name of the color measurement file		
SpectralData	String	encrypted content file locator		content/file?r=66696c653a2f4....7874&t=t.txt

To get the file content, a subsequent API call "rest/content/file" has to be performed with the value of "SpectralData".

Constraints of this kind of subscription :

The SpectralData files are available for 24 hours.

The SpectralData files collection will not be saved if the system shuts down.

If the receiver is not available, the messages will be queued and sent in a bunch if the receiver is available again at a later time.

The subscription will be deleted automatically by Prinect if the receiver is not available for 48 hours.

A maximum of 2 subscriptions is possible.

3.2.6 /rest/devicegroup (GET)

The request provides the group configuration in analyze point for the authenticated user. If no group definition is done or no user is given in the query, Prinect provides an automatic group definition based on the device class ("Prepress", "Press", "Postpress"). The locale parameter has only effect if the user did not create an individual devicegroup configuration.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	locale	String	no	Indicates the locale for the devicegroup name (if Prinect standard configuration is used).		en

Return value:

Name	Type	Description	Valid values	Sample
devicegroups	List			
devicegroups[].name	String	Group name		MyPresses
devicegroups[].devices	List			
devicegroups[].devices[].id	String	ID of the device.		4711
devicegroups[].devices[].name	String	Name of the device		XL105-5
devicegroups[].devices[].classid	String	Device category information		SheetfedPress

3.2.7 /rest/device/[deviceId]/output (GET)

Reports the detailled output of a given device, in detail about the sheets that had been printed. Supported for Sheetfed Press only. Data are kept for max. 15 days.

ParamType	Name	DataType	Required	Description	Valid values	Sample
PATH	jobId	String	yes	job id		
PATH	workstepId	String	yes	id of the printing workstep		
PARAMETER	page	Long	no	limit the output to page (page * pagesize)		2
PARAMETER	pagesize	Long	no	number of entries to be fetched		1000
PARAMETER	start	String	no	start of the query period. If not given, the 100 first entries will be fetched	date acc. to ISO 8601 format	2019-10-29T13%3A10%3A15%2B01%3A00
PARAMETER	end	String	no	end of the query period. If not given, the 100 first entries will be fetched	date acc. to ISO 8601 format	2019-10-30T13%3A10%3A15%2B01%3A00

Return value:

Name	Type	Description	Valid values	Sample
output	object			
outputElements	List	List of print intervals, limited by start- and endcounter		
output.outputElements[].timestamp	String	Date (UTC time) when the interval is been tracked		2019-10-30T13:10:15+00:00
output.outputElements[].sheetCounterStart	Int	SheetID of the first sheet tracked in this bunch		12350
output.outputElements[].sheetCounterEnd	Int	SheetID of the last sheet tracked in this bunch		
output.outputElements[].sheetType	Enum	type of the sheet	AdvanceSheet, CleaningSheet, MissingSheet, NonStopPileChangeSheet, PrintedSheet, SampleSheet, StartupSheet, UnprintedSheet	MissingSheet
output.outputElements[].classification	Enum	sheet classification	Good, Waste, Unprinted	Unprinted
output.outputElements[].destination	Enum	Target destination after printing	DeliveryPile, SampleSheetTable, WasteCollector	WasteCollector
output.outputElements[].errorDetails	Enum	Details about an eventual error	BadSheetDetection, NotAvailable, PullError	Okay
output.outputElements[].inspectionState	Enum	State reported by the inspection system : NotAvailable : Inspection system not available. NotRequired : Inspection not required for the sheets in the bunch. Okay : Inspection has been done successfully. UnknownError : Inpection required but not done due to an unknown error.	NotAvailable, NotRequired, Okay, UnknownError	NotRequired
output.outputElements[].codeInspectionState	Enum	state reported by the code inspection system NotAvailable : Code inspection system not available.	NotAvailable, NotRequired, Okay, UnknownError	Warning
output.outputElements[].qualityDeviation	Enum	state reported by the Color measurement system NotAvailable : Color measurement system not available / licenced or switched off. Okay : Target color distance within OK range. Large : Large target color distance detected. Medium : Medium target color distance detected. | Small | Small target color distance detected.|	NotAvailable, Okay, Large, Medium, Small, NotRequired, UnkownError	Small
output.outputElements[].sheetInfos	List	Provides sheet based details information		
output.outputElements[].sheetInfos[].sheetCounter	Int	index between sheetCounter1 and sheetCounter2		567133
output.outputElements[].sheetInfos[].customSheetCode	String	customer defined sheet id		Q7DB6Z
output.outputElements[].sheetInfos[].errorsCode	Int	stores the number of erroneous codes detected by the code inspection on the sheet (e.g., bar codes, etc.).		3

output.outputElements[].sheetInfos[].errorsLarge	Int	stores the number of large errors detected by the inspection system on the sheet, the associated error size can be individually configured.		2
output.outputElements[].sheetInfos[].errorsMedium	Int	stores the number of medium errors detected by the inspection system on the sheet, the associated error size can be individually configured.		4
output.outputElements[].sheetInfos[].errorsSmall	Int	stores the number of small errors detected by the inspection system on the sheet, the associated error size can be individually configured.		0

3.3 Employee API

3.3.1 /rest/employee (GET)

Provides information about the known employees (all Prinect users with qualified Staff-ID).

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	page	Integer	no	In case of a large amount of data, a paging may be necessary. To get the first data set, request without the page parameter or by page=0. Request the next pages by page=1 until the result will be empty.	0, 1, 2, ...	0
Parameter	pagesize	Integer	no	the number of entities to get		

Regionaler Naturpark Lothringen

Return value:

Name	Type	Description	Valid values	Sample
employees	List	List of all user information		
employees[].name	String			Marcipane
employees[].firstName	String			Antonio
employees[].id	String	Staff ID of the employee		4759

3.3.2 /rest/employee/[employeeId] (GET)

Provides information about a specific employee.

ParamType	Name	DataType	Required	Description	Valid values	Sample
PATH	employeeId	String	yes	Staff ID of the employee		4759

Return value:

Name	Type	Description	Valid values	Sample
employee	Object	Single user information		
employee.name	String			Marcipane
employee.firstName	String			Antonio
employee.id	String	Staff ID of the employee		4759

3.3.3 /rest/employee/[employeeId]/activity (GET)

The request provides a log of finished activities (operations) on a user in the polling period, sorted by timestamp desc (time sheet).

paging : the paging behaviour did not change and is different to the common description, this will be changed in the next version!

ParamType	Name	DataType	Required	Description	Valid values	Sample
PATH	employeeId	String	yes	Staff ID of the employee		4759
PARAMETER	start	Date	no	Begin of the interval requested.		2015-04-24T18:16:36+02:00
PARAMETER	end	Date	no	End of the interval requested.		2015-05-05T18:42:54+02:00
PARAMETER	page	Long	no	In case of a large amount of data, a paging may be necessary. To get the first data set, request without the page parameter or by page=0. Request the next pages by page=1 until the result will be empty.	0, 1, 2, ...	0
PARAMETER	pagesize	Long	no	The number of entities to get	1,2...	1

Return value:

Name	Type	Description	Valid values	Sample
activities	Object			
activities[].startTime	String	Start time of the activity.		2015-05-12T16:32:41+02:00
activities[].endTime	String	End time of the activity.		2015-05-12T16:40:28+02:00
activities[].id	String	ID of the activity		4100
activities[].name	String	Name of the activity		Good production
activities[].goodCycles	Long	Good amount produced in interval.		1000
activities[].wasteCycles	Long	Waste amount produced in interval.		0
activities[].timeTypeName	String	Name of the TimeType assigned to the activity.		Execution time
activities[].timeTypeGroupName	String	Name of the TimeTypeGroup where the TimeType is assigned to.		Production time
activities[].workType	Enum	Definition of the WorkType: Original – Standard work that was originally planned for the Job. Alteration – Work done to accommodate change made to the Job at the request of the customer. Rework – Work done due to unforeseen problem with original work (bad plate, Resource damaged, etc.)	Original, Alteration, Rework	Original
activities[].costCenter	String	Identification of the Cost Center		CC-SF-4C
activities[].comment	String	Comment entered by the user at start of the activity		"any comment"
activities[].device	Object	Device Information		
activities[].device.id	String	ID of the device		1234
activities[].device.name	String	Name of the device.		XL105-4
activities[].workstep	Object	Information about the active workstep in interval.		
activities[].workstep.id	String	ID of the workstep (system internal)		_140512_153037680_003138
activities[].workstep.name	String	Name of the workstep		Sheet1 5/0
activities[].workstep.job	Object	Job information		
activities[].workstep.job.id	String	ID of the Job.		140512-1531
activities[].workstep.job.name	String	Name of the Job		Brochure
activities[].employees	List	List of all user information		

activities[].employees[]. name	String			Marcipane
activities[].employees[]. firstName	String			Antonio
activities[].employees[].id	String	Staff ID of the employee		4759

3.4 Masterdata API

3.4.1 /rest/masterdata/milestone (GET)

ParamType	Name	DataType	Required	Description	Valid values	Sample
PARAMETER	locale	String	no	Locale for milestoneDefs[].name (for standard milestones only)		en

Return value:

Name	Type	Description	Valid values	Sample
milestoneD efs	List			
milestoneD efs[].id	String	Internal ID of the milestone		ID0c2e19bf1efc40 c6bc09b9eaaac67 100
milestoneD efs[].name	String	Name of the milestone		Printing
milestoneD efs[].type	Enum	Type of the milestone in respect of the section where the milestone belongs to. "Custom" for all userdefined milestones.	Document, Page, Layout, LayoutProof, PlateOutput, DigitalPrint, Print, SheetFinishing, ProductFinishing, CAD, PreCutting, Custom	Print
milestoneD efs[]. actionTag	String	Action tag assigned to the milestone.		PressCompleted

3.5 Service API

3.5.1 /rest/service/startGanging (POST)

This request triggers the SignaGangServer to produce a gang layout from the request data. The result is a gangID wich can be used as parameter in the request /rest/service/gangResult to view the status and result of the ganging process.

RequestData:

Name	Type	Description	Valid values	Sample
gangJobID	String	The gangJobID is used for example in the name of the resulting layout.		AutoGanging001
gangJobName	String	The gangJobName is used for example in the name of the resulting layout.		AutoGanging
gangJobTemplate	String	The product part template.		AutoGanging /BMGanging-XL106-SM74
jobData	List			
jobData[].jobID	String	ID of the job.		
jobData[]. jobName	String	Name of the job.		
jobData[].amount	Integer	The required print amount.		5000
jobData[]. contentData	List			

jobData[]. contentData[]. fileURI	String	Path to the PDF-file in the form file://processorname/path or C://path.		*C:\path\path\file.pdf*
jobData[]. contentData[]. pages	String	Comma seperated list of pagenumbers. This parameter is optional, if it is not used all pages from the content file will be taken.		*1,2,27,28*
jobData[]. customerName	String	The customer name.		
jobData[]. mediaName	String	The paper name.		
jobData[].weight	Double	The paper weight [g/m²] .		
jobData[]. productCode	String	The product code is used to choose a product part template.		
jobData[].dueDate	String	Delivery data of the job.		
jobData[]. colorsFront	List<String>	The front colors.		[C , M , Y , K , Gold]
jobData[]. colorsBack	List<String>	The back colors.		[K]
jobData[]. overproduction	Integer	Paid overproduction in percent.		
jobData[]. grainRestriction	Enum	Machine direction of the paper. This parameter is optional, the default value is: Unique	Normal, Rotated, Unique, None, FromLayout	
jobData[].nPages	Integer	If there is no content, the number of pages is provided by the template and can be multiplied by nPages.		
jobData[]. sourceLayout	String	The layout (file URL) in wich the contentData is emposed.		
jobData[]. assemblyIDs	String	The IDs of the folding sheets in the sourceLayout, that shall be taken over to the gang layout. Not optional if a sourceLayout is used.		
jobData[]. foldingMode	String	The proportions of the folding sheets.		F4-1:X40X60Y100
media	List	The list entries address specific plate templates in the gangJobTemplate and media data.		
media[]. plateTemplateName	String	Name of the plate template.		SM 74
media[].mediaID	String	ID of the media in the plate template.		100006
media[]. mediaCost	Double	Cost of the media.		50
media[]. grainDirection	Enum	Grain direction of the media.	ShortEdge, LongEdge	ShortEdge
media[].weight	Double	Weight of the media.		135
media[].quality	String	Quality of the media.		glossy
media[].height	Double	Height of the media..		700
media[].width	Double	Width of the media.		500
media[].unit	Enum	The unit for height and width.	mm, cm, m, point, inch, pica, cicero	mm

Return value:

Name	Type	Description	Valid values	Sample
gangID	String	ID of this ganging process. The ID can be used as parameter in the request /rest/service/gangResult to view the status and result of the ganging process.		bc205165-f43b-4c68-8cb5-e7e46f3c564b

3.5.2 /rest/service/gangResult (GET)

The request returns the status and result of the ganging process adressed by the gangID.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	gangID	String	yes	ID of the ganging process		bc205165-f43b-4c68-8cb5-e7e46f3c564b

Return value:

Name	Type	Description	Valid values	Sample
gangResult				
gangResult.gangingFinished	Booelan	true if the ganging process is finished. If the process is not finished all other attributes in this result are empty.		
gangResult.resultCode	Integer	The result code is "0" if the ganging succeded. Other entries indicate errors.		0
gangResult.resultMessage	String	Description of the result code.		Success
gangResult.autogangingJDF	String	Encoded URL, to be used in the content/file rest call.		
gangResult. autogangingReport	String	Encoded URL, to be used in the content/file rest call.		
gangResult. autogangingPDFReport	String	Encoded URL, to be used in the content/file rest call.		
gangResult.media		Information about the resulting plate template an media.		
gangResult.media. plateTemplateName	String	Name of the plate template.		SM 74
gangResult.media.mediaID	String	ID of the media.		100006
gangResult.media.mediaCost	Double	Cost of the media.		50
gangResult.media. grainDirection	Enum	Grain direction of the media.	ShortEdge, LongEdge	ShortEdge
gangResult.media.weight	Double	Weight of the media.		135
gangResult.media.quality	String	Quality of the media.		glossy
gangResult.media.height	Double	Height of the media.		700
gangResult.media.width	Double	Width of the media.		500
gangResult.media.unit	Enum	The unit for height and width.	mm, cm, m, point, inch, pica, cicero	mm

3.6 Product API

3.6.1 /rest/product (GET)

get the products (BMStockItemsByUserIDRequest)

This call returns information about all the products in the system, matching a given filter.

To get the product in the list, enter the product in Prinect Business Manager, enter "properties" and navigate to "internet". Check "ok to order over internet" in the "ok to order"-section there.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	search	String	no	If given, the request returns products where the string is contained in either ProductID, Description or Ref at customer	Blank = %20	ness%20card%20Mr%20x
Parameter	customerid	String	no	shows the products and specific prices for this customer		
Parameter	page	Integer	no	In case of a large amount of data, a paging may be necessary. To get the first data set, request without the page parameter or by page=0. Request the next pages by page=1 until the result will be empty.	0,1,2..	1
Parameter	pagesize	Integer	no	indicates the number of entities per page, restricted to MAXPAGESIZE	1,2..	120
Parameter	locale	String	no	Locale		en

Return value:

Name	Type	Description	Valid values	Sample
products	List	List of all products		
products[].id	String	Product ID		101197
products[].name	String	Product description		Business%20card%20Mr%20xyz
products[].refAtCustomer	String	Product ID in customers system		SAP1234
products[].image	String	Base64 encoded String representing an URL to the product image		
products[].stock	Object	Stock information		
products[].stock.available	Double	Available stock (Available Amount)		12000
products[].measureUnit	String	Unit for stock taking/ording...		cps.
products[].basePriceQuantity	Double	base price quantity		
products[].minOrderQuantity	Double	minimum order amount		1000
products[].maxOrderQuantity	Double	maximum order amount		50000
products[].orderBy	Double	multiples of quantites which can be ordered		100
products[].comment	String	Comment		
products[].productGroup	Object	Product group the product belongs to		
products[].productGroup.id	String	Product group id		000
products[].productGroup.name	String	Product group name		Sheets

3.6.2 /rest/product/[productid] (GET)

get the specific product details of the selected product id (optional per customer) (BMStockItemsByStockIDRequest)

With parameter "customerid" prices and RefAtCustomer for this customer will be retrieved.

If this parameter is not specified or there is no match in the system, the products common data will be retrieved.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	productId	String	yes	product id		100001
Parameter	customerId	String	no	customer id		100035
Parameter	locale	String	no	Locale		en

Return value:

Name	Type	Description	Valid values	Sample
product	Object	List of all products		
product.id	String	Product ID		101197
product.name	String	Product description		Business%20card%20Mr%20xyz
product.refAtCustomer	String	common id for all customers		
product.image	String	Base64 encoded URL referring to the product image		
product.stock	Object	Stock information		
product.stock.available	Double	Available stock		12000
product.measureUnit	String	Unit for stock taking/ording...		cps.
product.basePriceQuantity	Double	base price quantity		/1000
product.minOrderQuantity	Double	minimum order amount		1000
product.maxOrderQuantity	Double	maximum order amount		50000
product.orderBy	Double	quantity intervals which can be ordered		100
product.comment	String	Comment		
product.productGroup	Object	Product group the product belongs to		
product.productGroup.id	String	Product group id		000

product.productGroup.name	String	Product group name		Sheets
product.graduation	Object	either the common graduation table or the customer specific one		
product.graduation.Customer	Object			
product.graduation.Customer.id	String	Customer id		
product.graduation.Customer.name	String	Customer name		
product.graduation.prices[]	List	all graduations		
product.graduation.prices[].quantity	Long	price is valid from this quantity upwards		2000
product.graduation.prices[].priceUnit	Int	price is per Peace, sheet, reel		Sheet
product.graduation.prices[].price	Double	Price		200.21
product.graduation.prices[].isAbovePrice	Boolean	indicates the price for quantities above all graduations	true, false	

3.7 Quote API

3.7.1 /rest/quote (GET)

get a list of all known quotes,

To get a quote in the result list it has to be enabled in Prinect Business Manager .

to enable it enter the quote in PBM, open the variant, navigate to the internet tab and set "publish on internet" to "will be published on customer portal" in the customer portal section.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	search	String	no	if given, the request returns quotes where the string is contained in quote name or quote keyword description	Blank = %20	company %20xy
Parameter	locale	String	no			DE
Parameter	page	Long	no	In case of a large amount of data, a paging may be necessary. To get the first data set, request without the page parameter or by page=0. Request the next pages by page=1 until the result will be empty.	0,1,2.. 0,1,2..	2
Parameter	pagesize	Integer	no	indicates the number of entities per page, restricted to MAXPAGESIZE	1,2	7
Parameter	createdFrom	Date	no	first creation date		
Parameter	created Until	Date	no	last creation date		
Parameter	validFrom	Date	no	first validation date		
Parameter	validUntil	Date	no	last validation date		
Parameter	internalStatus	String	no	one of the user defined Status values (calculation parameters-estimate status)		0800
Parameter	orderOverInternet	Boolean	no	quotes that can be ordered via internet (Portal, Web4Labels)	true, false	false
Parameter	customerid	String	no	quotes for this customer		

Return value

Name	Type	Description	Valid values	Sample
quotes	List	List of all quotes		
quotes[].id	String	quote id		123456
quotes[].name	String	quote title		company xy
quotes[].created	Date	creation date		2016-07-14T10:26:49+02:00
quotes[].valid	Date	date until the quote is valid		2016-07-28T10:26:49+02:00

quotes[].deliveryDate	Date	quoted delivery date		2016-07-20T10:26:49+02:00
quotes[].customer	Object			
quotes[].customer.id	String	customer id		100001
quotes[].customer.name	String	customer name		Company.xy
quotes[].customerContact	Object			
quotes[].customerContact.id	String	customer contact id		000
quotes[].customerContact.name	String	customer contact name		Cook
quotes[].quoteLetterFile	String	Base64 encoded string containing a URL to the quote letter (e.g. PDF)	to be used as URL completition to http://...rest/content	
quotes[].refAtCustomer	String	id in customers system		SAP12.45
quotes[].status	Object			
quotes[].status.name	String	user defined status name		ORDERED
quotes[].status.id	Enum	user defined status id		9000
quotes[].creator	String	Name who created the quote		user1

3.7.2 /rest/quote/[quoteid] (GET)

get details of the defined quote

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	quoteid	String	yes	gets the specific quote		101273
Parameter	locale	String	no			DE

Return value

Name	Type	Description	Valid values	Sample
quote	Object	List of all quotes		
quote.id	String	quote id		123456
quote.name	String	quote title		company xy
quote.created	Date	creation date		2016-07-14T10:26:49+02:00
quote.valid	Date	date until the quote is valid		2016-07-28T10:26:49+02:00
quote.deliveryDate	Date	quoted delivery date		2016-07-20T10:26:49+02:00
quote.customer	Object			
quote.customer.id	String	customer id		000
quote.customer.name	String	customer name		Company.xy
quote.customerContact	Object			
quote.customerContact.id	String	customer contact id		000
quote.customerContact.name	String	customer contact name		Cook
quote.quoteLetterFile	String	link to the quote letter (e.g. PDF)		
quote.refAtCustomer	String		id in print buyers system	
quote.status	Object			
quote.status.id	String	user defined status id		
quote.status.name	String	user defined status name		
quote.creator	String			
quote.quoteItems[]	List			
quote.quoteItems[].variants[]	List			

quote.quoteItems[].variants[].id	String	variant id		
quote.quoteItems[].variants[].name	String	name of the variant		
quote.quoteItems[].variants[].quoteletter[]	List	key-value pairs containing the quote attributes		
quote.quoteItems[].variants[].quoteletter[].id	String	key		
quote.quoteItems[].variants[].quoteletter[].name	String	value		
quote.quoteItems[].variants[].graduation	Object			
quote.quoteItems[].variants[].graduation. customerCurrency	String	currency assigned to the customer /output on the quote		
quote.quoteItems[].variants[].graduation. systemCurrency	String	internal system currency		
quote.quoteItems[].variants[].graduation. currencyExchangeRate	Double			
quote.quoteItems[].variants[].graduation.prices[]	List			
quote.quoteItems[].variants[].graduation.prices[]. quantity	Double	the quantity		
quote.quoteItems[].variants[].graduation.prices[]. additionalQuantity	Double	the additional quantity		10000
quote.quoteItems[].variants[].graduation.prices[]. priceUnit	String	price unit		pcs.
quote.quoteItems[].variants[].graduation.prices[]. price	Double	the price		2100.23
quote.quoteItems[].variants[].graduation.prices[]. additionalPrice	Double	price for additional quantity		
quote.quoteItems[].variants[].refAtCustomer	String	ID in print buyers system		
quote.quoteItems[].variants[].deliveryAddress	Object			
quote.quoteItems[].variants[].deliveryAddress.id	String	delivery address id		000
quote.quoteItems[].variants[].deliveryAddress. name	String	delivery address name		Cook
quote.quoteIntents[]	List	RFQ content		
quote.quoteIntents[].productTypeid	String	product type on which quote is based		
quote.quoteIntents[].firstQuantity	Double	quantity		
quote.quoteIntents[].secondQuantity	Double	quantity		
quote.quoteIntents[].thirdQuantity	Double	quantity		
quote.quoteIntents[].comment	String	comment		
quote.quoteIntents[].width	Double	finished format		
quote.quoteIntents[].height	Double	finished format		
quote.quoteIntents[].dimensionUnit	String	Unit for width/height		mm
quote.quoteIntents[].description	String	RFQ description		
quote.quoteIntents[].parts[]	List	product parts		
quote.quoteIntents[].parts[].id	String	Part id		000
quote.quoteIntents[].parts[].name	String	Part name		Cover
quote.quoteIntents[].parts[].pages	Long	Number of pages		
quote.quoteIntents[].parts[].colorFront	String	color frontside		
quote.quoteIntents[].parts[].colorBack	String	color backside		
quote.quoteIntents[].parts[].plateChangesFront	String	number of plate changes front		
quote.quoteIntents[].parts[].plateChangesBack	String	number plate change back		
quote.quoteIntents[].parts[].width	Double	width		1502.36220472
quote.quoteIntents[].parts[].height	Double	height		2040.94488189
quote.quoteIntents[].parts[].dimensionUnit	String	Unit for width/height		mm
quote.quoteIntents[].parts[].paper				
quote.quoteIntents[].parts[].paper.id	String	paper id		UNCO-0

quote.quoteIntents[].parts[].paper.name	String	paper name		uncoated
quote.quoteIntents[].parts[].paper.grammage	Double	grammage value		135
quote.quoteIntents[].parts[].paper.grammageUnit	String	grammage unit		g/m2
quote.quoteIntents[].parts[].finishings[]	List	finishing worksteps		
quote.quoteIntents[].parts[].finishings[]. finishingSide	Enum	finishing side/kind	GENERAL, FRONT, BACK, FRONTANDBACK, OFF	FRONT
quote.quoteIntents[].parts[].finishings[].sequence	Int	finishing sequence		
quote.quoteIntents[].parts[].flaps[]	List	flaps		
quote.quoteIntents[].parts[].flaps[].length	Double			
quote.quoteIntents[].parts[].flaps[].flapUnit	String	measure unit		mm
quote.quoteIntents[].parts[].flaps[].type	Enum		FRONT, BACK, LEFT, RIGHT, UPPER, LOWER, SPINE	LEFT
quote.quoteIntents[].parts[].flaps[].version	Int			

3.8 Customer API

3.8.1. /rest/customer (get)

to get a customer list

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	search	String	no	if given, the request returns customers where the string is contained in name or keyword description		customer1
Parameter	page	Long	no	the offset in the result query	0,1,2	2
Parameter	pagesize	Long	no	the number of objects calculated from "page", restricted to MAXPAGESIZE	1,2	2

return value

Name	Type	Description	Valid values	Sample
customers	List	List of all customers		
customers[].id	String	customer id		100001
customers[].name	String	customer name		companyX

3.8.2. /rest/customer/[customerid] (get)

to get a specific customer

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	quoteid	String	yes	gets the specific customer		100001
Parameter	locale	String	no			DE

return value

Name	Type	Description	Valid values	Sample
customer	Object			
customer.id	String	customer id		100001
customer.name	String	customer name		CompanyX
customer.keyword	String			COMPANYX

customer.currency	String	currency	Iso codes according to ISO-4217	CompanyX
customer.salesRepresentative	Object	sales representative (user)		
customer.salesRepresentative.id	String	id of this user		100001
customer.salesRepresentative.name	String	user name		John
customer.contacts	List	List of customer contacts like delivery addresses, contact persons,..		
customer.contacts[].id	String	contact ID (generic)		MAIN100004_
customer.contacts[].name	String	contact name		CompanyX
customer.contacts[].contactType	Enum	indicates the contact type, either an other address, another customer, a person	MAIN, CONTACT, DELIVERY, INVOICE, NOTRANSPORT, FAVORITEDELIVERY	MAIN100004_
customer.contacts[].language	String	language symbol (2 digits)	ISO codes according ISO-639-1	DE
customer.contacts[].approver	Boolean	indicates if this contact (person) is an approver (remote access workflow)		False
customer.contacts[].prefix	String	salutation of this contact (person)		Mr
customer.contacts[].standard	Boolean	indicates if this contact is a standard contact according to its contactType		False
customer.contacts[].user	Object	User (login)		
customer.contacts[].user.id	String	userid of this contact (person)		100011
customer.contacts[].user.name	String	user name of this contact (person)		contact1
customer.contacts[].address	Object	postal address		
customer.contacts[].address.name	String	Name		delivery1
customer.contacts[].address.street	String	Street		main street 1
customer.contacts[].address.zipcode	String	Zip code		69115
customer.contacts[].address.city	String	city		Heidelberg
customer.contacts[].address.country	String	country name		Germany
customer.contacts[].address.department	String	department		sales
customer.contacts[].address.state	String	State (US)		NY
customer.contacts[].address.county	String	County (US)		
customer.contacts[].address.district	String	District (IR)		
customer.contacts[].address. transportZone	Object	Transport zone		
customer.contacts[].address. transportZone.id	String			000
customer.contacts[].address. transportZone.name	String			our Warehouse
customer.contacts[].address. transportZone.rate	List	Rates of this transport zone		
customer.contacts[].address. transportZone.rate[].id	String	Id of this rate		001
customer.contacts[].address. transportZone.rate[].name	String	name of this rate		Standard
customer.contacts[].address. transportZone.rate[].keyword	String	keyword of this rate		STANDARD
customer.contacts[].address. transportZone.rate[].daysDeliveryTime	String	days to calculate for delivery		1
customer.contacts[].address. transportZone.rate[].timeForDeliveryTime	String	duration to calculate for delivery		2
customer.contacts[].commChannels	List	communication channels		
customer.contacts[].commChannels[].type	String	Phone,Email, Fax..		Phone
customer.contacts[].commChannels[]. value	String	The phone number, email address...		1234
customer.status	Object	Statistics about this customer		
customer.status.openOrders	Object	active orders		100

customer.status.openQuotes	Object	active quotes		10
customer.lastOrderDate	String	last order date		2017-01-18T12:00:00+01:00

3.9 Product Type API

3.9.1. /rest/producttype (get)

to get a list of product types

To retrieve a product type in the list it has to be enabled for customer portal (enter product type, navigate to the internet tab and check "Customer Portal" checkbox in the "Customer Portal" section

If no customer id is specified, only the common product types which are not assigned to a specific customer are displayed.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Parameter	search	String	no	if given, the request returns product types where the string is contained in name or keyword description		brochure 123
Parameter	customer id	String	no	customer id (PBM)		100002
Parameter	locale	String	no	to address translated content		DE

return value

Name	Type	Description	Valid values	Sample
productTypes	List	List of all product types		
productTypes[].id	String	product type id		100001
productTypes[].name	String	product type name		brochures.xy

3.9.2. /rest/producttype/[producttypeid] (get)

gets a specific product type

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	producttypeid	String	yes	the productid to show		100002
Parameter	locale	String	no	to address translated content		DE

return value

Name	Type	Description	Valid values	Sample
productType	Object	List of all product types		
productType.id	String	product type id		100001
productType.name	String	product type name		brochures.xy
productType.directOrderAllowed	Boolean	product type can be direct ordered	true, false	false
productType.speedEstimatorAllowed	Boolean	speed estimator will be used for this product type	true, false	true
productType.versioningAllowed	Boolean	versioning can be used for this product type	true, false	true
productType.finalFormats	List	final formats		

productType.finalFormats[].finalFixedFormats	List	selection from a list of fixed final formats		
productType.finalFormats[].finalFixedFormats[].id	String	format entry id		030000
productType.finalFormats[].finalFixedFormats[]. name	String	format entry name		A3
productType.finalFormats[].finalFixedFormats[]. isDefault	Boolean	indicates whether this format entry is default	true, false	true
productType.finalFormats[].finalFixedFormats[].x	Double	x dimension		297.0
productType.finalFormats[].finalFixedFormats[].y	Double	y dimension		420.0
productType.finalFormats[].finalFixedFormats[]. unit	String	dimension unit		mm
productType.finalFormats[].finalCustomFormat	Object	one custom format is possible per product type		
productType.finalFormats[].finalCustomFormat. maxHeight	Double	maximum height		450.0
productType.finalFormats[].finalCustomFormat. maxWidth	Double	maximum width		300.0
productType.finalFormats[].finalCustomFormat. minHeight	Double	minimum height		100.0
productType.finalFormats[].finalCustomFormat. minWidth	Double	minimum width		100.0
productType.finalFormats[].finalCustomFormat. unit	String	dimension unit		mm
productType.image	String	encoded URL, to be used in the content /file rest call		
productType.productTypeParts	List			
productType.productTypeParts[].id	String	part id		100006_000
productType.productTypeParts[].name	String	part name		Cover
productType.productTypeParts[].constraint	Enum		REQUIRED, OPTIONAL	REQUIRED
productType.productTypeParts[].pages	Object			
productType.productTypeParts[].pages. defaultCount	Integer	default number of pages		4
productType.productTypeParts[].pages.minCount	Integer	minimum number of pages		4
productType.productTypeParts[].pages.maxCount	Integer	maximum number of pages		8
productType.productTypeParts[].finishings	List			
productType.productTypeParts[].finishings[].id	String			000001
productType.productTypeParts[].finishings[].name	String	Name of the finishing		Laminating
productType.productTypeParts[].finishings[]. defaultValue	Enum		GENERAL, FRONT, BACK, FRONTANDBACK, OFF	ON
productType.productTypeParts[].finishings[]. sequence	Integer	sequence of this workstep		2
productType.productTypeParts[].finishings[].sides	Enum		GENERAL, FRONT, BACK, FRONTANDBACK, OFF	OFF, BACK
productType.productTypeParts[].colors	List			
productType.productTypeParts[].colors[].id	String	color id		4_B
productType.productTypeParts[].colors[].name	String	Color name		CMYK / Black
productType.productTypeParts[].colors[]. frontColor	Object			
productType.productTypeParts[].colors[].frontColor.id	String	front Color id		4
productType.productTypeParts[].colors[].frontColor.name	String	front Color name		CMYK
productType.productTypeParts[].colors[]. frontColor.colorCount	Integer	number of front colors		4
productType.productTypeParts[].colors[].backColor.id	String	back Color id		B

productType.productTypeParts[].colors[].backColor.name	String	back Color name		Black
productType.productTypeParts[].colors[].backColor.colorCount	Integer	number of back colors		1
productType.productTypeParts[].colors[].isDefault	Boolean	default color	true, false	false
productType.productTypeParts[].papers	List			
productType.productTypeParts[].papers[].id	String	paper id		100006_001_MATT-0
productType.productTypeParts[].papers[].name	String	paper name		matt coated paper
productType.productTypeParts[].papers[].isDefault	Boolean	default paper	true, false	false
productType.productTypeParts[].papers[].weights	List			
productType.productTypeParts[].papers[].weights[].id	String			90
productType.productTypeParts[].papers[].weights[].name	String			90 g/m3
productType.productTypeParts[].papers[].weights[].isDefault	Boolean		true, false	true
productType.productTypeParts[].flaps	List			
productType.productTypeParts[].flaps[].id	String			
productType.productTypeParts[].flaps[].name	String			
productType.productTypeParts[].flaps[].flapLength	Double			
productType.productTypeParts[].flaps[].flapUnit	String			mm
productType.productTypeParts[].flaps[].flapType	Enum		FRONT, BACK, LEFT, RIGHT, UPPER, LOWER, SPINE	

3.10 Plate API

PD-161489 - Abrufen der Vorgangsdetails... STATUS

3.10.1 /rest/plate/[plateID] (GET)

The request provides information regarding a given plate.

ParamType	Name	DataType	Required	Description	Valid values	Sample
Path	plateID	String	yes	ID of the plate where information are requested for.		123456789

Return value:

Name	Type	Description	Valid values	Sample
plate	Object	Covers the information given for a plate		
plate.layoutName	String	Name of the Layout		SN25723
plate.layoutID	String	ID of the Layout		
plate.sheetName	String	Name of the sheet		SN25723
plate.variantID	String	ID of the variant		
plate.separationName	String	name of the separation		Black

plate.id	String	The plate number of the plate (not PlateId!)		7487400001000
plate.width	Double	Width of the plate (point)		1488.18897638
plate.height	Double	Height of the plate (point)		1301.1023622
plate.color	String	Name of the color of the plate		Magenta
plate.surfaceName	Enum		Front, Back	
plate.plateStatus	Enum	Status plate availibility	UNAVAILABLE, TO_BE_APPROVED, AVAILABLE, REJECTED, APPROVED, IMAGED PENDING status "PENDING" : plate data are calculated and waiting to be imaged by a plate setter status "IMAGED" : plate is imaged, this status can only appear in a scenario with an external plate handling system status "AVAILABLE" : in a scenario with an external plate handling system the meaning is :the plate is on a plate trolley, otherwise it means the plate is imaged	
plate.plateStackID	String	Name of the plate stack where the plate belongs to (if Plate Pilot had been used).		42
plate.plateStackSize	Integer	Number of plates in PlateStack (0 if unknown)		12
plate.plateTrolleyName	String	Name of the plate trolley (if available).		Trolley A
plate.worksteps[]	List	Information about the workstep (print) where the plate is assigned to.		
plate.worksteps[].id	String	ID of the workstep (system internal)		_140512_153037680_003138
plate.worksteps[].name	String	Name of the workstep		Sheet1 5/0
plate.worksteps[].job	Object	Job information		
plate.worksteps[].job.id	String	ID of the Job.		140512-1531
plate.worksteps[].job.name	String	Name of the Job		Brochure

3.10.2 /rest/plate/[plateID] (POST)

This allows to set information regarding a given plate.

The following plate availibility state transitions are allowed/implemented :

- from state "Imaged" to "Available" (plate is imaged and available for printing)
- from state "Imaged" to "Pending" (re-imaging requested - the plate is not ok)
- from state "Pending" to "Imaged" (external plate automation system reports plate as imaged, but not yet available for printing)
- from state "Pending" to "Pending" (re-imaging requested - the plate is not ok)

The status network depends on the existence of an external plate automation system.

If the target status is set to "Pending", the imaged plate is not ok. A more detailled description about the reason can be defined in the comment field.

ParamType	Name	DataType	Required	Description	Valid values	Sample	Default
Path	plateID	String	yes	plate number of the plate		140512-1429	

Request data:

Name	Type	Description	Valid values	Sample

plate	Object	Covers the information given for a plate. Any additional information into that object not mentioned below will be ignored.		
plate. plateStatus	Enum	Status plate availibility. Any other status is not supported yet. If empty, the plate status remains unchanged.	AVAILABLE, IMAGED, PENDING	
plate. plateTrolleyName	String	Name of the plate trolley. The value given here will be set (incl. empty value). Leave that attribute of the plate trolley name should remain unchanged!		Trolley A
plate.comment	String	in case of resetting the status to a previous state, for instance in case of a plate defect, a comment about the reason can be defined		plate spoiled

Example

```
{
  "plate":
  {
   "plateStatus": "AVAILABLE",
   "plateTrolleyName": "max",
   "comment" : "Plate spoiled"
  }
}
```

Return value:

error.code OK, RUNTIME_ERROR.

The return data provides the status of the elements specified in the request. If requested element doen't exist in the system it will be not included in the response.

Name	Type	Description	Valid values	Sample
plate	Object	Covers the information given for a plate		
plate. layoutName	String	Name of the Layout		SN25723
plate. layoutID	String	ID of the Layout		
plate. sheetName	String	Name of the sheet		SN25723
plate. variantID	String	ID of the variant		
plate. separationName	String	name of the separation		Black
plate.id	String	The plate number of the plate (not PlateId)		7487400001000
plate.width	Double	Width of the plate (point)		1488.18897638
plate.height	Double	Height of the plate (point)		1301.1023622
plate.color	String	Name of the color of the plate		Magenta
plate. surfaceName	Enum		Front, Back	

plate.plateStatus	Enum	Status plate availibility	UNAVAILABLE, TO_BE_APPROVED, AVAILABLE, REJECTED, APPROVED, IMAGED PENDING status "PENDING" : plate data are calculated and waiting to be imaged by a plate setter status "IMAGED" : plate is imaged, this status can only appear in a scenario with an external plate handling system status "AVAILABLE" : in a scenario with an external plate handling system the meaning is : the plate is on a plate trolley, otherwise it means the plate is imaged	
plate.plateStackID	String	Name of the plate stack where the plate belongs to (if Plate Pilot had been used).		42
plate.plateStackSize	Integer	Number of plates in PlateStack (0 if unknown)		12
plate.plateTrolleyName	String	Name of the plate trolley (if available).		Trolley A
plate.worksteps[]	List	Information about the workstep (print) where the plate is assigned to.		
plate.worksteps[].id	String	ID of the workstep (system internal)		_140512_153037680_003138
plate.worksteps[].name	String	Name of the workstep		Sheet1 5/0
plate.worksteps[].job	Object	Job information		
plate.worksteps[].job.id	String	ID of the Job.		140512-1531
plate.worksteps[].job.name	String	Name of the Job		Brochure

3.11 Common

3.11.1 /rest/version (GET)

Returns the complete version number of the installed Prinect System. No parameters for this call.

Return value:

Name	Type	Description	Valid values	Sample
version	String	Prinect Build Number		18.00.100.501

3.11.2 /rest/content/file (GET)

Returns a relative URL to the content of a file,

ParamType	Name	DataType	Required	Description	Valid values	Sample
PARAMETER	r	String	yes	the encoded URL retrieved by the job/element or workstep/element rest call		"content/file?r=66696c653a2f2f484549504339353031305 62f50544a6f62732f4a6f62732f323031362d30322d30332f4131322d303031322f53797374656d2f5061676556696577732f484 4636974795f312d31305f36432f70312e70646623706167653d32&t=t.pdf#page=2"

Return value: relative URL to a file content, for example from a preview or a thumbnail (pdf or png file)

This relative URL has to be prefixed with the base URL determined by the Reverse Proxy like

http://reverseProxyHostname/PrinectAPI/rest/content/file?=r=66696c653a2f2f484549504339353303130562f50544a6f62732f4a6f62732f323031362d30322d30332f4131322d303031322f53797374656d2f5061676556696577732f484

4636974795f312d31305f36432f70312e70646623706167653d32&t=t.pdf#page=2"