BSc (Hons) in **Information Technology Specialized in AI**

Faculty of Computing

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Practical 03

> **Objective & Lecture Mapping:** In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

> Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

> You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

> The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

> Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

The State Space is the complete set of every possible configuration in the environment along with the actions that connect them together. In terms of a standard graph , it is like every node and edge. The Search Tree is the actual map of all the visited states and paths used to visit them , that gets built during a search to keep track of the current search.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

In graph search theory it solves the problem of checking nodes that have already been checked and getting stuck in a loop of checking the same set of nodes. In DFS specifically it would make the agent visit only the exact same path it just finished over and over again as there would be no logic to tell it that that path has been fully explored

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

BFS is guaranteed to be optimal as by exploring each neighbor of a specific distance first before moving onto neighbors that are further away, it can always find the shortest path as it will have popped all the neighbors relating to other paths once it finds the goal, meaning it has nothing else to explore. DFS produces winding suboptimal routes as it goes in whatever path it tries first until it reaches the goal, meaning it can be the longest , windiest path to the goal but if it happened to be the first path tried that reached the goal , DFS will consider it the correct path.

4. (Evaluate) If we scaled `visual_grid_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

BFS would reach a memory bottleneck fast as in a larger grid the number of neighbors for each previously visited state would all have to be held until the search completes that level . The number of neighbors per level grows

exponentially as for every new neighbor there will likely be more than one neighbor for it meaning the bigger the grid, the bigger the number of neighbors , the search has to keep track of.
DFS compared to this is far more memory efficient with a larger grid as it ever only keeps track of one path. It can only reach a memory bottleneck only of the grid is extremely large that the total number of spaces before getting to the goal added with each spaces immediate neighbors exceeds the memory bounds which is very unlikely in a practical grid size.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation



FACULTY OF COMPUTING