

Machine Learning 机器学习

Lecture 11 : Dimension reduction & Feature selection 降维和特征选择

李洁

nijanice@163.com

维度灾难问题

Curse of dimensionality

- Many explored domains have hundreds to tens of thousands of **variables/features** with many **irrelevant** and **redundant** ones!
- In domains with many features the underlying probability distribution can be very complex and very hard to estimate (e.g. dependencies between variables) !
- Irrelevant and redundant features can confuse learners!
- Limited training data!
- Limited computational resources!
- **Curse of dimensionality!**

维度灾难问题

Curse of dimensionality


- Spatial sampling

4 units for each dimension, 10 samples per unit




total sample :

1-D:



2-D:




10-D:

维度灾难问题

Curse of dimensionality

- Spatial sampling


4 units for each dimension, 10 samples per unit



total sample :


1-D: 4

~40



2-D: $4 \times 4 = 16$

~160



10-D: $4^{10} = 1048576$

~10M

维度灾难问题

Curse of dimensionality

- Spatial sampling


4 units for each dimension, 10 samples per unit



total sample :


1-D: 4

~40



2-D: $4 \times 4 = 16$

~160



10-D: $4^{10} = 1048576$

~10M

- Sample sparsity

total sample: 1000

partition of each dimension: 4


Samples per unit:

维度灾难问题

Curse of dimensionality

- Spatial sampling


4 units for each dimension, 10 samples per unit



total sample :


1-D: 4

~40



2-D: $4 \times 4 = 16$

~160



10-D: $4^{10} = 1048576$

~10M

- Sample sparsity

total sample: 1000

partition of each dimension : 4

Samples per unit :

1D: $1000/4 = 250$

2D: $1000/(4 \times 4) = 62.5$

10D: $1000/(4^{10}) = 0.001$

噪声影响


Noise influence

- Feature space : 101D
- The distance between the positive and negative samples at the first dimension: 1
- The noise of the sample in its residual dimension : 10%
- “Noise distance” : $\sqrt{100 \times 0.1^2} = 1$
- Even if the noise is only 10%, the noise distance in high dimensional space is enough to mask the essential difference between positive and negative samples.


低维嵌入

Low dimensional embedding

Looks like 3-D,
Actually, 2-D




28x28 D,
Actually, 1-D



降维与特征选择


Dimensionality reduction & Feature selection

Dimensionality reduction: creating a subset of new features by combinations of the existing features



$$\{f_1, \dots, f_i, \dots, f_n\} \xrightarrow{f.\text{extraction}} \{g_1(f_1, \dots, f_n), \dots, g_j(f_1, \dots, f_n), \dots, g_m(f_1, \dots, f_n)\}$$

Feature Selection: choosing a subset of all the features



$$\{f_1, \dots, f_i, \dots, f_n\} \xrightarrow{f.\text{selection}} \{f_{i_1}, \dots, f_{i_j}, \dots, f_{i_m}\}$$

$$i_j \in \{1, \dots, n\}; j = 1, \dots, m$$

$$i_a = i_b \Rightarrow a = b; a, b \in \{1, \dots, m\}$$

Machine Learning Problems

	<i>Supervised Learning</i>	<i>Unsupervised Learning</i>
<i>Discrete</i>	classification or categorization	clustering
<i>Continuous</i>	regression	<div>dimensionality reduction</div>

降维方法

Dimensionality reduction Method

- Principal Component Analysis (PCA)
- Multidimensional Scaling (MDS)
- Locally Linear Embedding (LLE)
- Laplacian Eigenmaps (LE)
- Isometric Mapping(Isomap)
- T-distributed Stochastic Neighbor Embedding (t-SNE)
- Auto-encoders
- Non-negative Matrix Factorization(NMF)
- Canonical Correlation Analysis(CCA)
- Independent Component Analysis (ICA)
- Probabilistic PCA
- Kernel PCA
- (Linear Discriminant Analysis(LDA)-supervised)
- ...

举例

Dimensionality Reduction Example

- Given 53 blood and urine samples (features) from 65 people.
- How can we visualize the measurements?

Matrix format (65x53)

	H-WBC	H-RBC	H-Hgb	H-Hct	H-MCV	H-MCH	H-MCHC
A1	8.0000	4.8200	14.1000	41.0000	85.0000	29.0000	34.0000
A2	7.3000	5.0200	14.7000	43.0000	86.0000	29.0000	34.0000
A3	4.3000	4.4800	14.1000	41.0000	91.0000	32.0000	35.0000
A4	7.5000	4.4700	14.9000	45.0000	101.0000	33.0000	33.0000
A5	7.3000	5.5200	15.4000	46.0000	84.0000	28.0000	33.0000
A6	6.9000	4.8600	16.0000	47.0000	97.0000	33.0000	34.0000
A7	7.8000	4.6800	14.7000	43.0000	92.0000	31.0000	34.0000
A8	8.6000	4.8200	15.8000	42.0000	88.0000	33.0000	37.0000
A9	5.1000	4.7100	14.0000	43.0000	92.0000	30.0000	32.0000


Difficult to see the correlations between the features...

举例

Dimensionality Reduction Example

- Given 53 blood and urine samples (features) from 65 people.
- How can we visualize the measurements?

Matrix format (65x53)




Difficult to compare the different patients...


举例

Dimensionality Reduction Example

Bi-variate



Tri-variate



How can we visualize the other variables???

... difficult to see in 4 or higher dimensional spaces...

举例

Dimensionality Reduction Example

- Is there a representation better than the coordinate axes?
- Is it really necessary to show all the 53 dimensions?

举例


Dimensionality Reduction Example

- Is there a representation better than the coordinate axes?
- Is it really necessary to show all the 53 dimensions?
 - discard low significance dimensions
 - Get compact description (what if there are strong correlations between the features?)

举例

Dimensionality Reduction Example

- Spectral format (65 pictures, one for each person)



Difficult to compare the different subjects...

举例

Dimensionality Reduction Example

- Is there a representation better than the coordinate axes?
- Is it really necessary to show all the 53 dimensions?
 - discard low significance dimensions
 - Get compact description (what if there are strong correlations between the features?)
- How could we find
the *smallest subspace* of the 53-D space that
keeps the *most information* about the original data?

举例


Dimensionality Reduction Example

- Is there a representation better than the coordinate axes?
- Is it really necessary to show all the 53 dimensions?
 - discard low significance dimensions
 - Get compact description (what if there are strong correlations between the features?)
- How could we find
the *smallest subspace* of the 53-D space that
keeps the *most information about the original data*?
- A solution: Principal Component Analysis

举例

Dimensionality Reduction Example


- Spectral format (65 pictures, one for each person)



Difficult to compare the different subjects...

主成分分析

Principle Component Analysis



PCA:

Orthogonal projection of data onto lower-dimension linear space that...

- maximizes variance of projected data (purple line)
- minimizes mean squared distance between data point and projections (sum of blue lines)

主成分分析

Principle Component Analysis


- **Data Preparation:**
 - Standardize the data if the features have different units or scales. (centering, scaling)
- **Compute and Select Principal Components:**
 - Iterative Algorithms (For very large datasets, can find the main components without computing the full covariance matrix)
 - Covariance Matrix (data dimensions are not excessively high)
 - Singular Value Decomposition (can handle matrices of any size)
- **Transform the Original Dataset:**
 - Project the original dataset into the new space formed by the selected principal components to obtain the reduced-dimensionality data representation.

主成分分析算法一（顺序求解）


PCA algorithm I (sequential)

- **Vectors** originating from the center of mass
- Principal component #1 points in the direction of the **largest variance**.
- Each subsequent principal component...
 - is **orthogonal** to the previous ones, and
 - points in the directions of the **largest variance of the residual subspace**

1st PCA axis



2nd PCA axis



主成分分析算法一（顺序求解）

PCA algorithm I (sequential)

Given the **centered** data $\{\mathbf{x}_1, \dots, \mathbf{x}_m\}$, compute the principal vectors:


$$\mathbf{w}_1 = \arg \max_{\|\mathbf{w}\|=1} \frac{1}{m} \sum_{i=1}^m \{(\mathbf{w}^T \mathbf{x}_i)^2\} \quad \text{1st PCA vector}$$

can be obtained
by gradient
ascent

$$\mathbf{w}_k = \arg \max_{\|\mathbf{w}\|=1} \frac{1}{m} \sum_{i=1}^m \{[\mathbf{w}^T (\mathbf{x}_i - \underbrace{\sum_{j=1}^{k-1} \mathbf{w}_j \mathbf{w}_j^T \mathbf{x}_i}_{\mathbf{x}'})]^2\} \quad k^{\text{th}} \text{ PCA vector}$$

\mathbf{x}' PCA reconstruction

We maximize the variance
of the projection in the
residual subspace



主成分分析算法二（特征值分解）

PCA algorithm II(sample covariance matrix)

- Given data $\{\mathbf{x}_1, \dots, \mathbf{x}_m\}$, compute covariance matrix Σ

$$\Sigma = \frac{1}{m} \sum_{i=1}^m (\mathbf{x}_i - \bar{\mathbf{x}})(\mathbf{x}_i - \bar{\mathbf{x}})^T \quad \text{where} \quad \bar{\mathbf{x}} = \frac{1}{m} \sum_{i=1}^m \mathbf{x}_i \quad \begin{array}{l} \text{(Optional)} \\ \text{Standardization} \end{array}$$

- Eigenvalue decomposition $\Sigma = U \Lambda U^T$
- PCA basis vectors = the eigenvectors of Σ
- Larger eigenvalues \Rightarrow more important eigenvectors

主成分分析算法二（特征值分解）

PCA algorithm II(sample covariance matrix)

PCA algorithm(\mathbf{X} , k): top k eigenvalues/eigenvectors

% $\mathbf{X} = N \times m$ data matrix, each data point \mathbf{x}_i = column vector, $i=1..m$

- $\mathbf{X} \leftarrow$ subtract mean \bar{X} from each column vector \mathbf{x}_i in \mathbf{X}
- $\Sigma \leftarrow \mathbf{X}\mathbf{X}^T$...compute covariance matrix of \mathbf{X}
- $\{ \lambda_i, \mathbf{u}_i \}_{i=1..N}$ = eigenvectors/eigenvalues of Σ
... Sort the eigenvalues in descending order $\lambda_1 \geq \lambda_2 \geq \dots \geq \lambda_N$
- Return $\{ \lambda_i, \mathbf{u}_i \}_{i=1..k}$
% top k principle components

主成分分析算法三（奇异值分解）





PCA algorithm III (SVD of the data matrix)

Singular Value Decomposition of the **centered** data matrix **X**.

$$\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_m] \in \mathbb{R}^{N \times m}, \quad \begin{array}{l} m: \text{number of instances,} \\ N: \text{dimension} \end{array}$$

$$\mathbf{X}_{N \times m} = \mathbf{U}_{N \times N} \mathbf{S}_{N \times m} \mathbf{V}_{m \times m}^T \approx \mathbf{U}_{N \times k} \mathbf{S}_{k \times k} \mathbf{V}_{k \times m}^T$$

$$\mathbf{X} = \mathbf{U} \mathbf{S} \mathbf{V}^T$$



主成分分析算法三（奇异值分解）

PCA algorithm III (SVD of the data matrix)

- **Columns of U**

- the principal vectors, $\{ \mathbf{u}^{(1)}, \dots, \mathbf{u}^{(k)} \}$
- orthogonal and has unit norm – so $U^T U = I$
- Can reconstruct the data using linear combinations of $\{ \mathbf{u}^{(1)}, \dots, \mathbf{u}^{(k)} \}$

- **Matrix S**

- Diagonal
- Shows importance of each eigenvector

- **Columns of V^T**

- The coefficients for reconstructing the samples

主成分个数

How many PCA components

Problem: How many to keep?

Many criteria.


e.g. % total data variance:

$$\max(m) \ni \frac{\sum_{i=(m+1):n} \lambda_i}{\sum_{i=1:n} \lambda_i} < \varepsilon$$

	λ_1	λ_2	λ_3	λ_4	λ_5	λ_6
ratio	0.45	0.18	0.13	0.12	0.07	0.04

Using 4 components is good enough

L_2 error and PCA dim



主成分分析用于图像压缩

PCA application: Image Compression

Original Image




- Divide the original 372x492 image into patches:
 - Each patch is an instance that contains 12x12 pixels on a grid
- View each as a 144-D vector

主成分分析用于图像压缩

PCA application: Image Compression

60 most important eigenvectors:



Looks like the discrete cosine bases of JPEG!...

主成分分析用于图像压缩

PCA application: Image Compression


PCA compression: 144D \rightarrow 60D



主成分分析用于图像压缩

PCA application: Image Compression

16 most important eigenvectors:



主成分分析用于图像压缩

PCA application: Image Compression


PCA compression: 144D \rightarrow 16D



主成分分析用于图像压缩

PCA application: Image Compression

6 most important eigenvectors:



主成分分析用于图像压缩

PCA application: Image Compression




PCA compression: 144D \rightarrow 6D



主成分分析用于图像压缩

PCA application: Image Compression

3 most important eigenvectors:



主成分分析用于图像压缩

PCA application: Image Compression


PCA compression: 144D \rightarrow 3D



主成分分析用于图像压缩

PCA application: Image Compression

PCA compression: 144D \rightarrow 1D



主成分分析用于滤除噪声

PCA application: Noise Filtering



Noisy image

主成分分析用于滤除噪声

PCA application: Noise Filtering




Denoised image using 15 PCA components

主成分分析弱点 Weaknesses of PCA




Unsupervised

Linear:

PCA






LDA




流形学习

Manifold Learning



Intrinsic Space



t-分布领域嵌入算法(t-SNE)

T-distributed Stochastic Neighbor Embedding

$x \longrightarrow z$

Compute similarity between all pairs of x : $S(x^i, x^j)$

$$P(x^j | x^i) = \frac{S(x^i, x^j)}{\sum_{k \neq i} S(x^i, x^k)}$$

Compute similarity between all pairs of z : $S'(z^i, z^j)$

$$Q(z^j | z^i) = \frac{S'(z^i, z^j)}{\sum_{k \neq i} S'(z^i, z^k)}$$

Find a set of z making the two distributions as close as possible

$$\begin{aligned} L &= \sum_i KL(P(* | x^i) || Q(* | z^i)) \\ &= \sum_i \sum_j P(x^j | x^i) \log \frac{P(x^j | x^i)}{Q(z^j | z^i)} \end{aligned}$$

t-分布领域嵌入算法(t-SNE)

T-distributed Stochastic Neighbor Embedding

$x \longrightarrow z$

SNE:


$$S(x^i, x^j)$$

$$S'(z^i, z^j) = \exp(-\|z^i - z^j\|_2)$$

$$= \exp(-\|x^i - x^j\|_2)$$

t-SNE:


$$S'(z^i, z^j) = 1 / (1 + \|z^i - z^j\|_2)$$



t-分布领域嵌入算法(t-SNE)

T-distributed Stochastic Neighbor Embedding

- Good at visualization




t-SNE on MNIST



t-SNE on COIL-20

自编码器 Auto-encoder


- Greedy Layer-wise Pre-training again



Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

自编码器 Auto-encoder


- Greedy Layer-wise Pre-training again



Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

自编码器 Auto-encoder

- Greedy Layer-wise Pre-training again




Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

自编码器 Auto-encoder

– Greedy Layer-wise Pre-training again

Find-tune by
backpropagation




Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

自编码器

Auto-encoder

- An auto-encoder is an artificial neural net used for unsupervised learning of efficient codings.
- Greedy Layer-wise Pre-training again




use neural networks to recover the data

Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

学习自编码器

Learning Auto-encoder




Compact
representation of
the input object

Can reconstruct
the original object

学习PCA


Learning PCA



Output of the hidden layer is the code

深度自编码器 Deep Auto-encoder


The auto-encoder can be deep



use neural networks to recover the data


Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

深度自编码器 Deep Auto-encoder



深度自编码器


Deep Auto-encoder



深度自编码器用于文本检索

Auto-encoder for Text Retrieval

Vector Space Model



Bag-of-words

	this	1
	is	1
word string:	a	0
"This is an apple"	an	1
	apple	1
	pen	0
	⋮	


Semantics are not considered

深度自编码器用于文本检索

Auto-encoder for Text Retrieval



Latent semantic analysis
based on PCA




A 2000- 500-250-125-2 autoencoder
Trained by DBN

Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *science* 313.5786 (2006): 504-507.

深度自编码器用于去噪声

Denoising Auto-Encoder Examples



Vincent, Pascal, et al. "Extracting and composing robust features with denoising autoencoders." *ICML*, 2008.

深度自编码器用于去噪声

Denoising Auto-Encoder Examples

Original

Corrupted

Reconstructed




PCA人臉分析

PCA on Face

$$\mathbf{q} = a_1 \mathbf{w}^1 + a_2 \mathbf{w}^2 + \dots$$

images

30 components:



Eigen-digits

PCA人臉分析

PCA on Face

30 components:



<http://www.cs.unc.edu/~lazechnik/research/spring08/assignment3.html>

Eigen-face

PCA结果

What happens to PCA




$$= \underline{a_1} w^1 + \underline{a_2} w^2 + \dots$$

Can be any real number

- PCA involves adding up and subtracting some components (images)
 - Then the components may not be “parts of digits”
- Non-negative matrix factorization (NMF)
 - Forcing a_1, a_2, \dots be non-negative
 - additive combination
 - Forcing w^1, w^2, \dots be non-negative
 - More like “parts of digits”
- Ref: Daniel D. Lee and H. Sebastian Seung. "Algorithms for non-negative matrix factorization." *Advances in neural information processing systems*. 2001.

非负矩阵分解 (NMF)

Non-negative Matrix Factorization




Non-negativity constraint offers physical and real-world interpretability!

$$\operatorname{argmin} \frac{1}{2} \|X - WH\|^2 = \frac{1}{2} \sum_{ij} (X_{ij} - WH_{ij})^2$$

$$\operatorname{argmin} J(W, H) = \sum_{ij} \left(X_{ij} \ln \frac{X_{ij}}{WH_{ij}} - X_{ij} + WH_{ij} \right)$$

非负矩阵分解应用

NMF on MNIST




非负矩阵分解应用

NMF on Face



鸡尾酒会问题

Cocktail-party problem



鸡尾酒会问题

Cocktail-party problem

Model

$$\begin{aligned}x_1(t) &= a_{11}s_1(t) + a_{12}s_2(t) \\x_2(t) &= a_{21}s_1(t) + a_{22}s_2(t)\end{aligned}$$

We observe

$$\begin{pmatrix} x_1(1) \\ x_2(1) \end{pmatrix}, \begin{pmatrix} x_1(2) \\ x_2(2) \end{pmatrix}, \dots, \begin{pmatrix} x_1(t) \\ x_2(t) \end{pmatrix}$$

We want

$$\begin{pmatrix} s_1(1) \\ s_2(1) \end{pmatrix}, \begin{pmatrix} s_1(2) \\ s_2(2) \end{pmatrix}, \dots, \begin{pmatrix} s_1(t) \\ s_2(t) \end{pmatrix}$$


But we don't know $\{a_{ij}\}$, nor $\{s_i(t)\}$

Goal: Estimate $\{s_i(t)\}$, (and also $\{a_{ij}\}$)

中心极限定理


Central Limit Theorem

The sum of independent variables converges to the normal distribution



ICA 假设

ICA Assumptions



1. s_1, \dots, s_K statistical Independence
2. Nongaussianity
(at most one component is Gaussian)
3. \mathbf{A} is column full-rank

ICA 原则

ICA Principal (Non-Gaussian is Independent)

$$y = w^T x = w^T A s = z^T s$$

- Key to estimating A is non-gaussianity
- y is a linear combination of s_i , with weights given by z_i .
- $z^T s$ is more gaussian than either of s_i . AND becomes least gaussian when its equal to one of s_i .
- So we could take w as a vector which maximizes the non-gaussianity of $w^T x$.
- Such a w would correspond to a z with only one non zero comp. So we get back the s_i .

非高斯性衡量

Measures of Non-Gaussianity

- Kurtosis : gauss=0 (sensitive to outliers)

$$kurt(y) = E\{y^4\} - 3(E\{y^2\})^2$$

Subgaussian: negative

- Entropy : gauss=largest

Supergaussian: positive

$$H(y) = -\int f(y) \log f(y) dy$$

- Neg-entropy : gauss = 0 (difficult to estimate)

$$J(y) = H(y_{\text{gauss}}) - H(y)$$

- Approximations

$$J(y) = \frac{1}{12} E\{y^2\}^2 + \frac{1}{48} kurt(y)^2$$

$$J(y) \approx [E\{G(y)\} - E\{G(v)\}]^2$$

where v is a standard gaussian random variable and :

$$G(y) = \frac{1}{a} \log \cosh(a \cdot y)$$

$$G(y) = -\exp(-a \cdot y^2 / 2)$$

FastICA算法

FastICA Algorithm

- Based on: w
- Basic form: $J(y) \approx [E\{G(y)\} - E\{G(v)\}]^2$
 - Choose an initial (e.g. Random) weight vector
 - Let $w = w^+ / \|w^+\|$
 - Let $w^+ = E\{xg(w^T x)\} - E\{g'(w^T x)\}w$
 - If not converged, go back to step 2
- For several units: decorrelation
 - Let $w_{p+1} = w_{p+1} - \sum_{j=1}^p w_{p+1}^T w_j w_j$
 - Let $w_{p+1} = w_{p+1} / \sqrt{w_{p+1}^T w_{p+1}}$

鸡尾酒会问题 ICA 求解

The Cocktail Party Problem Solving with ICA

Sources

Mixing

Observation



ICA Estimation



$\mathbf{s}(t)$

$$\mathbf{A} \in \mathbb{R}^{M \times M}$$

$$\mathbf{x}(t) = \mathbf{A}\mathbf{s}(t)$$



$$\mathbf{y}(t) = \mathbf{W}\mathbf{x}(t)$$

鸡尾酒会问题 ICA 求解

The Cocktail Party Problem Solving with PCA

Sources

Mixing

Observation


PCA Estimation



$\mathbf{s}(t)$

$$\mathbf{A} \in \mathbb{R}^{M \times M}$$




$$\mathbf{x}(t) = \mathbf{A}\mathbf{s}(t)$$



$$\mathbf{y}(t) = \mathbf{W}\mathbf{x}(t)$$



图像问题ICA求解

ICA Application on image




图像问题ICA求解

ICA Application on image



图像问题ICA求解

ICA Application on image



图像问题ICA求解

ICA Application on image

Original
image



Noisy
image



Wiener
filtering



ICA
filtering



视频问题 ICA 求解

ICA Application on Video



Source images

视频问题ICA求解

ICA Application on Video




ICs

EEG问题ICA求解

ICA Application on EEG


- EEG ~ *Neural cocktail party*
- Severe **contamination** of EEG activity by
 - eye movements
 - blinks
 - muscle
 - heart, ECG artifact
 - vessel pulse
 - electrode noise
 - line noise, alternating current (60 Hz)
- ICA can improve signal
 - effectively **detect, separate and remove** activity in EEG records from a wide variety of artifactual sources.
(Jung, Makeig, Bell, and Sejnowski)
- ICA weights help find **location** of sources



EEG问题 ICA求解

ICA Application on EEG


ICA decomposition



EEG问题ICA求解


ICA Application on EEG

Summed Projection of Selected Components



EEG问题 ICA求解


ICA Application on EEG



降维与特征选择


Dimensionality reduction& Feature selection

Dimensionality reduction: creating a subset of new features by combinations of the existing features



$$\{f_1, \dots, f_i, \dots, f_n\} \xrightarrow{f.\text{extraction}} \{g_1(f_1, \dots, f_n), \dots, g_j(f_1, \dots, f_n), \dots, g_m(f_1, \dots, f_n)\}$$

Feature Selection: choosing a subset of all the features



$$\{f_1, \dots, f_i, \dots, f_n\} \xrightarrow{f.\text{selection}} \{f_{i_1}, \dots, f_{i_j}, \dots, f_{i_m}\}$$


$$i_j \in \{1, \dots, n\}; j = 1, \dots, m$$

$$i_a = i_b \Rightarrow a = b; a, b \in \{1, \dots, m\}$$

特征选择

Feature selection

- Find the optimal feature subset.




- Filter Methods
- Wrapper Methods
- Embedded Methods

过滤法

Filter Methods

Select subsets of variables as a pre-processing step,
independently of the used classifier!!



Features could be evaluated by

- Distance
- Information
- dependency(correlation)
- ...

过滤法

Filter Methods

- Relief (Relevant Features)

$$\delta^j = \sum_i -\text{diff}(x_i^j, x_{i,\text{nh}}^j)^2 + \text{diff}(x_i^j, x_{i,\text{nm}}^j)^2$$

- Fischer's ratio. $\frac{|S_b|}{|S_w|} = \frac{(\mu_1 - \mu_2)^2}{\sigma_1^2 + \sigma_2^2}$

- information gain $\text{Gain}(A) = \text{Ent}(D) - \sum_{v=1}^V \frac{|D^v|}{|D|} \text{Ent}(D^v)$
- coefficient scores $\Re(i) = \frac{\text{cov}(X_i, Y)}{\sigma(X_i) \times \sigma(Y)}$
- ...


过滤法

Filter Methods

- usually fast
- provide generic selection of features
- feature set not optimized for used classifier
- sometimes used as a preprocessing step for other methods

包裹法

Wrapper Methods



Features could be evaluated by **classifier error rate** (the classifier themselves).

包裹法

Wrapper Methods

- The problem of finding the optimal subset is NP-hard!
- A wide range of heuristic search strategies can be used.
Two different classes:
 - **Forward selection**
(start with empty feature set and add features at each step)
 - **Backward elimination**
(start with full feature set and discard features at each step)
- predictive power is usually measured on a validation set or by cross-validation
- By using the learner as a black box wrappers are universal and simple!
- Criticism: a large amount of computation is required.

嵌入法

Embedded Methods

- Specific to a given learning machine!
- Performs feature selection (implicitly) in the process of training
- E.g. LASSO [Tibshirani, 1996]

$$\min_{\mathbf{w}} \sum_{i=1}^m (y_i - \mathbf{w}^\top \mathbf{x}_i)^2 + \lambda \|\mathbf{w}\|_1$$

- Random Forest and Gradient Boosting

问题：简述你所了解到的特征降维的几种方法及其特点