

In order to numerically solve the minimization problem (??), we follow the general lines of the discretized problem presented in [?gjthesis].

Given $m \in \mathbb{N}_+$, divide the interval $[0, 1]$ to m subintervals $I_{m,k} := (\frac{k}{m}, \frac{k+1}{m})$, $k = 0, \dots, m-1$, of length $\frac{1}{m}$, and consider only H^1 -functions that are linear on each subinterval,

$$(1) \quad W_m := \left\{ u \in H^1([0, 1], \mathbb{R}^{2n}) \mid \dot{u}|_{I_{m,k}} \text{ is constant, } \int_0^1 u(t) dt = 0, \int_0^1 \langle -J\dot{u}, u \rangle = 1 \right\},$$

where $J \in \text{Mat}(2n, \mathbb{R})$ is the standard complex structure on \mathbb{R}^{2n} ,

$$J = \begin{pmatrix} 0 & I_n \\ -I_n & 0 \end{pmatrix}.$$

Let $u \in W_m$, then \dot{u} is piece-wise constant, and can be represented by a vector $\dot{\mathbf{x}} = (\dot{x}_1, \dots, \dot{x}_m) \in \mathbb{R}^{2n \cdot m}$. In this case, the functional to minimize (??) takes the form

$$(2) \quad F(\dot{\mathbf{x}}) = \frac{1}{m} \sum_{j=1}^m G(-J\dot{x}_j),$$

and its gradient is

$$(3) \quad \nabla F(\dot{\mathbf{x}}) = \frac{1}{m} (J\nabla G(-J\dot{x}_1), \dots, J\nabla G(-J\dot{x}_m)).$$

The constraints are given by

$$(4) \quad 0 = \ell(\dot{\mathbf{x}}) = \sum_{j=0}^{m-1} \dot{x}_j,$$

$$(5) \quad 0 = q(\dot{\mathbf{x}}) = \frac{1}{m^2} \sum_{k=1}^{m-1} \sum_{j=0}^{k-1} \langle -J\dot{x}_k, \dot{x}_j \rangle - 1 = \frac{1}{m^2} \dot{\mathbf{x}}^T A \dot{\mathbf{x}} - 1,$$

where

$$A := \begin{pmatrix} 0_{2n} & -J_{2n} & \cdots & -J_{2n} \\ \vdots & \ddots & & \vdots \\ \vdots & & \ddots & -J_{2n} \\ 0_{2n} & \cdots & \cdots & 0_{2n} \end{pmatrix} \in \text{Mat}(\mathbb{R}, 2n \cdot m),$$

and the gradient of the quadratic constraint is

$$\nabla q(\dot{\mathbf{x}}) = \frac{1}{m^2} (A + A^T) \dot{\mathbf{x}}.$$

To minimize the functional F under the constraints ℓ, q we use the Matlab library function named "fmincon". This function recives as input the functional, its gradient, the constraints and their gradients, together with a starting point in $\mathbb{R}^{2n \cdot m}$ and iteratively searches for a local minimum. The function "fmincon" enables to choose a minimization algorithm out of a given list. After numerically experimenting the possible algorithms, we chose "active-set" as it produced the best results in terms of accuracy and run-time. To choose a starting vector, we randomly pick a vector in $\mathbb{R}^{2n \cdot m}$, then shift and rescale it to satisfy conditions (4), (5).