

Task 1: HADOOP, HDFS, PIG and HIVE

1. Import RStudio Log Files from one week in February 2019 into HDFS

Step-1

Download one week Logs from <http://cran-logs.rstudio.com/>

Step-2

Create a new folder to store downloaded logs files.

```
mkdir RStudioLogs
```

Step-3 Verify files in RStudioLogs folder

```
ls
```

Step-3 Unzip all *.zip files

```
gunzip *.csv.gz
```


Step-4 Put on HDFS and verify

```
hdfs dfs -mkdir /user/master
```

```
hdfs dfs -mkdir /user/master/RLogFiles
```

```
hdfs dfs -put *.csv /user/master/RLogFiles
```

```
hdfs dfs -ls /user/master/RLogFiles
```



```
charan@quickstart:~/RLogFiles
File Edit View Search Terminal Help
[charan@quickstart RLogFiles]$ ls
2019-02-01.csv 2019-02-03.csv 2019-02-05.csv 2019-02-07.csv
2019-02-02.csv 2019-02-04.csv 2019-02-06.csv
[charan@quickstart RLogFiles]$ hdfs dfs -mkdir /user/master/RLogFiles
[charan@quickstart RLogFiles]$ hdfs dfs -put *.csv /user/master/RLogFiles
[charan@quickstart RLogFiles]$ hdfs dfs -ls /user/master/RLogFiles
Found 7 items
-rw-r--r-- 1 charan supergroup 230459165 2019-03-19 20:47 /user/master/RLogFiles/2019-02-01.csv
-rw-r--r-- 1 charan supergroup 117303794 2019-03-19 20:47 /user/master/RLogFiles/2019-02-02.csv
-rw-r--r-- 1 charan supergroup 119279156 2019-03-19 20:47 /user/master/RLogFiles/2019-02-03.csv
-rw-r--r-- 1 charan supergroup 247621719 2019-03-19 20:48 /user/master/RLogFiles/2019-02-04.csv
-rw-r--r-- 1 charan supergroup 261986660 2019-03-19 20:48 /user/master/RLogFiles/2019-02-05.csv
-rw-r--r-- 1 charan supergroup 268666730 2019-03-19 20:48 /user/master/RLogFiles/2019-02-06.csv
-rw-r--r-- 1 charan supergroup 266936135 2019-03-19 20:48 /user/master/RLogFiles/2019-02-07.csv
[charan@quickstart RLogFiles]$
```

2. Pig Latin: Top-100-packages (by operating system)


a. Load log-file of one day (e.g., 1st of February 2019)

```
logfile = LOAD '/user/master/RLogFiles/2019-02-07.csv' USING PigStorage(',') AS
```

```
(date:chararray,time : chararray,size: int,r_version: float,r_arch: int,r_os: chararray, package : chararray,
version : float, country : chararray, ip_id : int);
```

b. Dump the first 10 entries on screen (attach a screen shot into your report) to check if it works or not

```
grunt> FIRST_10 = LIMIT logfile 10;  
grunt> DUMP FIRST_10;
```



```
charan@quickstart:~/RLogFiles  
File Edit View Search Terminal Help  
2019-03-19 21:35:12,465 [main] INFO org.apache.pig.backend.hadoop.executionengi  
ne.mapReduceLayer.MapReduceLauncher - Success!  
2019-03-19 21:35:12,469 [main] INFO org.apache.hadoop.conf.Configuration.deprec  
ation - fs.default.name is deprecated. Instead, use fs.defaultFS  
2019-03-19 21:35:12,469 [main] INFO org.apache.hadoop.conf.Configuration.deprec  
ation - mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.addr  
ess  
2019-03-19 21:35:12,470 [main] INFO org.apache.pig.data.SchemaTupleBackend - Ke  
y [pig.schematuple] was not set... will not generate code.  
2019-03-19 21:35:12,476 [main] INFO org.apache.hadoop.mapreduce.lib.input.FileI  
nputFormat - Total input paths to process : 1  
2019-03-19 21:35:12,476 [main] INFO org.apache.pig.backend.hadoop.executionengi  
ne.util.MapRedUtil - Total input paths to process : 1  
( "date", "time", , , , "r_os", "package", , "country", )  
( "2019-02-07", "02:25:20", 2085103, , , "mingw32", "dendextend", , "BR", 54840 )  
( "2019-02-07", "02:25:23", 657276, , , "mingw32", "gplots", , "BR", 54840 )  
( "2019-02-07", "02:25:23", 22245685, , , NA, "rcdklibs", , "US", 1822 )  
( "2019-02-07", "02:25:24", 40033, , , "linux-gnu", "quadprog", , "US", 23793 )  
( "2019-02-07", "02:25:24", 208092, , , "mingw32", "registry", , "BR", 54840 )  
( "2019-02-07", "02:25:25", 496454, , , "darwin15.6.0", "httr", , "BR", 54840 )  
( "2019-02-07", "02:25:27", 513, , , "darwin15.6.0", "ordinal", , "KR", 54914 )  
( "2019-02-07", "02:25:28", 252954, , , "darwin15.6.0", "getPass", , "US", 2242 )  
( "2019-02-07", "02:25:31", 2660018, , , "darwin15.6.0", "kernlab", , "BR", 6972 )  
grunt>
```

c. Count the number of occurrences of different packages;

```
pack_R = FOREACH logfile GENERATE $6 as pack_R;  
grouped = GROUP pack_R BY $0;  
count = FOREACH grouped GENERATE group, COUNT(pack_R);  
STORE count INTO '/user/master/result_new1';
```




/ user / master / result_new1 / part-r-00000	
"rbounds"	25
"rcanvec"	5
"rcarbon"	9
"rccmisc"	6
"rcoreoa"	20
"rdmulti"	19
"rdpower"	15
"rdtLite"	4
"read.gb"	5

d. Count the number of occurrences of different packages by operating system;

```
FEB07= LOAD '/user/master/RLogFiles/2019-02-07.csv' USING PigStorage(',') AS (date:chararray,
time:chararray, size:int, rversion:chararray, arch:chararray, os:chararray, pkg:chararray,
version:chararray, country:chararray, ipid:int);
```

```
pack_R_OS = FOREACH FEB07 GENERATE REPLACE(os, '[{""]}', ''), REPLACE(pkg,'[{""]}', '');
```

```
grouped_os = GROUP pack_R_OS BY ($0,$1);
count = FOREACH grouped_os GENERATE group, COUNT(pack_R_OS);
STORE count INTO '/user/master/result_new2';
```



/ user / master / result_new2 / part-r-00000	
(mingw32,lcc)	1
(mingw32,lda)	55
(mingw32,ldr)	1
(mingw32,lfe)	107
(mingw32,lfl)	3
(mingw32,lga)	1
(mingw32,lhs)	169
(mingw32,ljr)	2
(mingw32,lle)	14
(mingw32,lmf)	6

e. Store the results of both operations in HDFS;

```
a = LOAD '/user/master/result_new2/part-r-00000' using PigStorage('\t') AS
```

```
(os_pkg:chararray,count:chararray);
```

```
b = FOREACH a GENERATE REPLACE(os_pkg, '[{""]}', ''), REPLACE(count,'[{""]}', '');
STORE b INTO '/user/master/result_new3';
```

3. sqoop, MySQL and R/Python:

a. Export the results of both operations (package frequencies and package frequencies by operating systems) via sqoop into MySQL;

Step-1 Create new database in mysql or use existing one, we are using 'retail_db' with required permissions. Create tables 'package_count' and 'package_count_os'.

```
use retail_db;
```

```
create table package_count(package_r varchar(50), counting long);
```

```
create table package_count_os(package_r varchar(50), counting long);
```

Step-2 Use sqoop for exporting data from HDFS to MySQL tables package_count and package_count_os respectively.

```
sqoop export --connect "jdbc:mysql://quickstart.cloudera:3306/retail_db" --username root --password
cloudera --table package_count --export-dir /user/master/result_new1/part-r-00000 --input-fields-
terminated-by '\t' --input-lines-terminated-by '\n' --num-mappers 2 --batch --outdir java_files
```

```
sqoop export --connect "jdbc:mysql://quickstart.cloudera:3306/retail_db" --username root --password cloudera --table package_count_os --export-dir /user/master/result_new3/part-m-00000 --input-fields-terminated-by '\t' --input-lines-terminated-by '\n' --num-mappers 2 --batch --outdir java_files
```


b. Access the tables by R/RStudio or Python and display the results (Top-10-results in bar charts)

Step-1 Install required R packages.

```
install.packages("https://cloud.r-project.org/src/contrib/DBI_1.0.0.tar.gz")
install.packages("http://cloud.r-project.org/src/contrib/RMySQL_0.10.16.tar.gz")
install.packages("http://cloud.r-project.org/src/contrib/Rcpp_1.0.0.tar.gz")
install.packages("http://cloud.r-project.org/src/contrib/plyr_1.8.4.tar.gz")
```

Step-2 Create Script

```
library("RMySQL")
library("plyr")
drv <- dbDriver("MySQL")
con <- dbConnect(drv, user='root', password='cloudera',
host='quickstart.cloudera',dbname="retail_db", port=3306)
dbListConnections(MySQL())
res <- dbGetQuery(con, "SELECT package_r, counting from package_count order by CAST(counting
AS DECIMAL) desc limit 10")
t1 <- unlist(res[1], use.names = FALSE)
c2 <- res[2]
c3 <- as.numeric(unlist(c2))
barplot(c3, names.arg = t1, xlab = "package name", ylab = "counts",
main = "Top 10 packages download")
```




```

library("RMySQL")
library("plyr")
drv <- dbDriver("MySQL")
con <- dbConnect(drv, user='root', password='cloudera',
host='quickstart.cloudera',dbname="retail_db", port=3306)
dbListConnections(MySQL())
res <- dbGetQuery(con, "SELECT package_r, counting from package_count_os order by
CAST(counting AS DECIMAL) desc limit 10")
t1 <- unlist(res[1], use.names = FALSE)
c2 <- res[2]
c3 <- as.numeric(unlist(c2))

barplot(c3, names.arg = t1, xlab = "package name", ylab = "counts",
main = "Top 10 packages download")

```



4. Pig Latin and HIVE: Number of individual users each day

a. Load the log-files into HDFS

As per 1 solution, data is already present into HDFS.

b. Count the number of distinct users each day(with one week data)

```


week_logfile = LOAD '/user/master/RLogFiles/*.csv' USING PigStorage(',') AS (date:chararray,time :
chararray,size: int,r_version: float,r_arch: int,r_os: chararray, package : chararray, version : float,
country : chararray, ip_id : int);

```

```

user_ip = FOREACH week_logfile GENERATE $0,$9 as user_ip;
grouped = GROUP user_ip BY $0;
count = FOREACH grouped GENERATE group, COUNT(user_ip);
STORE count INTO '/user/master/result_new6';

```



```

charan@quickstart:~/RLogFiles
File Edit View Search Terminal Help
ne.mapReduceLayer.MapReduceLauncher - Encountered Warning FIELD_DISCARDED_TYPE_C
ONVERSION_FAILED 7 time(s).
2019-03-19 21:55:01,767 [main] INFO  org.apache.pig.backend.hadoop.executionengi
ne.mapReduceLayer.MapReduceLauncher - Success!
2019-03-19 21:55:01,767 [main] INFO  org.apache.hadoop.conf.Configuration.deprec
ation - fs.default.name is deprecated. Instead, use fs.defaultFS
2019-03-19 21:55:01,768 [main] INFO  org.apache.hadoop.conf.Configuration.deprec
ation - mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.addr
ess
2019-03-19 21:55:01,768 [main] INFO  org.apache.pig.data.SchemaTupleBackend - Ke
y [pig.schematuple] was not set... will not generate code.
2019-03-19 21:55:01,792 [main] INFO  org.apache.hadoop.mapreduce.lib.input.FileI
nputFormat - Total input paths to process : 2
2019-03-19 21:55:01,792 [main] INFO  org.apache.pig.backend.hadoop.executionengi
ne.util.MapRedUtil - Total input paths to process : 2
("2019-02-01",2665973)
("2019-02-03",1389895)
("2019-02-05",3026029)
("2019-02-07",3079783)
("date",7)
("2019-02-02",1364597)
("2019-02-04",2864816)
("2019-02-06",3126076)
grunt>

```

5. Pig Latin and HIVE: Machine Learning Frameworks

a. There are two important machine learning frameworks in R available: caret and mlr.

Caret is widely used and mlr provides a second approach (please check the official CRAN webpage)

b. We are interested how frequent both frameworks are used: count the number of package caret and package mlr downloads each day)

```

register '/usr/lib/pig/piggybank.jar' ;
define CSVLoader org.apache.pig.piggybank.storage.CSVLoader();
logsAll= LOAD '/user/master/RLogFiles/2019-02*.csv' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE', 'NOCHANGE') AS
(date:chararray, time:chararray, size:long, r_version:chararray, r_arch:chararray, r_os:chararray,
package:chararray, version: chararray, country:chararray, ip_id : int);
mlrpkg = FILTER logsAll BY NOT(($6 != 'mlr'));
mlrgrp = GROUP mlrpkg BY date;
count = FOREACH mlrgrp GENERATE group as date, COUNT(mlrpkg) as cnt;
STORE count INTO '/user/master/result_new17' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE',
'UNIX', 'WRITE_OUTPUT_HEADER');

```



```
charan@quickstart:~/RLogFiles
2019-03-20 07:24:40,019 [main] WARN org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Encountered Warning FIELD_DISCARDED_TYPE_CONVERSION_FA
ILED 14 time(s).
2019-03-20 07:24:40,019 [main] INFO org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Success!
2019-03-20 07:24:40,020 [main] INFO org.apache.hadoop.conf.Configuration.deprecation
- fs.default.name is deprecated. Instead, use fs.defaultFS
2019-03-20 07:24:40,020 [main] INFO org.apache.hadoop.conf.Configuration.deprecation
- mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.address
2019-03-20 07:24:40,020 [main] INFO org.apache.pig.data.SchemaTupleBackend - Key [pig
.schematuple] was not set... will not generate code.
2019-03-20 07:24:40,027 [main] INFO org.apache.hadoop.mapreduce.lib.input.FileInputFo
rmat - Total input paths to process : 2
2019-03-20 07:24:40,027 [main] INFO org.apache.pig.backend.hadoop.executionengine.uti
l.MapRedUtil - Total input paths to process : 2
(2019-02-01,536)
(2019-02-03,265)
(2019-02-05,476)
(2019-02-07,439)
(2019-02-02,228)
(2019-02-04,538)
(2019-02-06,597)
grunt>
```

```
register '/usr/lib/pig/piggybank.jar' ;
define CSVLoader org.apache.pig.piggybank.storage.CSVLoader();
logsAll= LOAD '/user/master/RLogFiles/2019-02*.csv' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE', 'NOCHANGE') AS
(date:chararray, time:chararray, size:long, r_version:chararray, r_arch:chararray, r_os:chararray,
package:chararray, version: chararray, country:chararray, ip_id : int);
mlrpkg = FILTER logsAll BY NOT(($6 != 'caret'));
mlrgrp = GROUP mlrpkg BY date;
count = FOREACH mlrgrp GENERATE group as date, COUNT(mlrpkg) as cnt;
STORE count INTO '/user/master/result_new18' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE',
'UNIX', 'WRITE_OUTPUT_HEADER');
```

```
charan@quickstart:~/RLogFiles
2019-03-20 07:47:45,598 [main] WARN org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Encountered Warning FIELD_DISCARDED_TYPE_CONVERSION_FA
ILED 14 time(s).
2019-03-20 07:47:45,598 [main] INFO org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Success!
2019-03-20 07:47:45,605 [main] INFO org.apache.hadoop.conf.Configuration.deprecation
- fs.default.name is deprecated. Instead, use fs.defaultFS
2019-03-20 07:47:45,605 [main] INFO org.apache.hadoop.conf.Configuration.deprecation
- mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.address
2019-03-20 07:47:45,607 [main] INFO org.apache.pig.data.SchemaTupleBackend - Key [pig
.schematuple] was not set... will not generate code.
2019-03-20 07:47:45,659 [main] INFO org.apache.hadoop.mapreduce.lib.input.FileInputFo
rmat - Total input paths to process : 2
2019-03-20 07:47:45,659 [main] INFO org.apache.pig.backend.hadoop.executionengine.uti
l.MapRedUtil - Total input paths to process : 2
(2019-02-01,4107)
(2019-02-03,2021)
(2019-02-05,4397)
(2019-02-07,4345)
(2019-02-02,2646)
(2019-02-04,3929)
(2019-02-06,4710)
grunt> █
```


c. Visualize the results in R (line chart) (follow the step in No. 3 or import the results directly into R)

```
install.packages("https://cloud.r-project.org/src/contrib/csvread_1.2.1.tar.gz")
install.packages("https://cloud.r-project.org/src/contrib/zoo_1.8-4.tar.gz")
```


```
library('csvread')
library('zoo')
z<- read.zoo("mlr_count.csv", sep = ',', header=TRUE)
plot(z, xaxt="n", type = "l", xlab = "Date", ylab = "Num of download" )
title(main = "Count of ctv download each day")
```

```
library('csvread')
library('zoo')
z<- read.zoo("caret_count.csv", sep = ',', header=TRUE)
plot(z, xaxt="n", type = "l", xlab = "Date", ylab = "Num of download" )
title(main = "Count of ctv download each day")
```


Count of mlr download each day



Count of caret download each day



6. Pig Latin and HIVE: Download volume (in MB) of caret and mlr packages

a. Use CRAN to find out the package size of the caret and mlr packages (use Windows-Package file size) in MB. Round to 1 decimal place.

```
charan@quickstart:~/RLogFiles
2019-03-20 17:32:01,982 [main] WARN  org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Encountered Warning FIELD_DISCARDED_TYPE_CONVERSION_FA
ILED 14 time(s).
2019-03-20 17:32:01,983 [main] INFO  org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Success!
2019-03-20 17:32:02,019 [main] INFO  org.apache.hadoop.conf.Configuration.deprecation
- fs.default.name is deprecated. Instead, use fs.defaultFS
2019-03-20 17:32:02,019 [main] INFO  org.apache.hadoop.conf.Configuration.deprecation
- mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.address
2019-03-20 17:32:02,020 [main] INFO  org.apache.pig.data.SchemaTupleBackend - Key [pig
.schematuple] was not set... will not generate code.
2019-03-20 17:32:02,060 [main] INFO  org.apache.hadoop.mapreduce.lib.input.FileInputFo
rmat - Total input paths to process : 2
2019-03-20 17:32:02,060 [main] INFO  org.apache.pig.backend.hadoop.executionengine.uti
l.MapRedUtil - Total input paths to process : 2
(2019-02-01,22020)
(2019-02-03,11095)
(2019-02-05,24048)
(2019-02-07,23749)
(2019-02-02,14783)
(2019-02-04,21560)
(2019-02-06,24844)
grunt>
```

b. Enter this information into a text file together with the name (should be the same as in log-files)

c. Import this file into HDFS

d. Load the file in Pig (I assume that the RStudio CRAN Log Files are available already)

```
charan@quickstart:~/RLogFiles
2019-03-20 17:42:45,401 [main] WARN  org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Encountered Warning FIELD_DISCARDED_TYPE_CONVERSION_FA
ILED 14 time(s).
2019-03-20 17:42:45,401 [main] INFO  org.apache.pig.backend.hadoop.executionengine.map
ReduceLayer.MapReduceLauncher - Success!
2019-03-20 17:42:45,401 [main] INFO  org.apache.hadoop.conf.Configuration.deprecation
- fs.default.name is deprecated. Instead, use fs.defaultFS
2019-03-20 17:42:45,401 [main] INFO  org.apache.hadoop.conf.Configuration.deprecation
- mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.address
2019-03-20 17:42:45,404 [main] INFO  org.apache.pig.data.SchemaTupleBackend - Key [pig
.schematuple] was not set... will not generate code.
2019-03-20 17:42:45,412 [main] INFO  org.apache.hadoop.mapreduce.lib.input.FileInputFo
rmat - Total input paths to process : 2
2019-03-20 17:42:45,413 [main] INFO  org.apache.pig.backend.hadoop.executionengine.uti
l.MapRedUtil - Total input paths to process : 2
(2019-02-01,1661)
(2019-02-03,948)
(2019-02-05,1446)
(2019-02-07,1361)
(2019-02-02,760)
(2019-02-04,1595)
(2019-02-06,1781)
grunt>
```

e. Filter out the caret and mlr packages in Pig

f. Add the size information

- g. Calculate the download volume of caret and mlr packages by day**
- h. Export the results and display the results in R or Python**

```
register '/usr/lib/pig/piggybank.jar' ;
define CSVLoader org.apache.pig.piggybank.storage.CSVLoader();
logsAll= LOAD '/user/master/RLogFiles/2019-02*.csv' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE', 'NOCHANGE') AS
(date:chararray, time:chararray, size:long, r_version:chararray, r_arch:chararray, r_os:chararray,
package:chararray, version: chararray, country:chararray, ip_id : int);
crtpkg = FILTER logsAll BY NOT(($6 != 'caret'));
crtgrp = GROUP crtpkg BY date;
volume = FOREACH crtgrp GENERATE group as date, ROUND(SUM(crtpkg.$2)*0.000001) as sum;
STORE volume INTO '/user/master/result_new19' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE',
'UNIX', 'WRITE_OUTPUT_HEADER');
```


```
register '/usr/lib/pig/piggybank.jar' ;
define CSVLoader org.apache.pig.piggybank.storage.CSVLoader();
logsAll= LOAD '/user/master/RLogFiles/2019-02*.csv' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE', 'NOCHANGE') AS
(date:chararray, time:chararray, size:long, r_version:chararray, r_arch:chararray, r_os:chararray,
package:chararray, version: chararray, country:chararray, ip_id : int);
mlrpkg = FILTER logsAll BY NOT(($6 != 'mlr'));
mlrgrp = GROUP mlrpkg BY date;
volume = FOREACH mlrgrp GENERATE group as date, ROUND(SUM(mlrpkg.$2)*0.000001) as sum;
STORE volume INTO '/user/master/result_new20' USING
org.apache.pig.piggybank.storage.CSVExcelStorage(',', 'NO_MULTILINE',
'UNIX', 'WRITE_OUTPUT_HEADER');
```

f. Add the size information

g. Calculate the download volume of each of the 10 packages by day


h. Export the results and display the results in R or Python
create table package_size(package_r
varchar(50), counting long);

Count of caret download each day



Date

Volume(in MB) of mlr download each day



Date