

被控机要放入 cmdb 所在环境运行用户的 id_rsa.pub

keepalived 网络查看

architecture/views/keepnet.py # 主业务逻辑所在源码文件
配置

```
def create_conf(request):
```

```
    hostip = '192.168.181.133'    # nginx 的主机
```

```
    conf_dir = '/usr/local/src/'    # nginx 子 conf 的目录
```

```
---
```

onlineconfig/views/nginx.py

```
class GetKeepIpaddr():
```

```
    def setUp(self):
```

```
        host_data = [        # 这个数组以字典结构内放入所以 keepalived 待机的 host 信息
```

```
        {
```

```
            "hostname": "keepalived1",    # 这个一定不能重名
```

```
            "ip": "172.20.100.68",
```

```
            "port": 22,
```

```
            "username": "root",    # 不一定要 root 用户，只要是能执行  
systemctl status keepalived 的用户都行
```

```
            "groups": ["keepalived"],
```

```
            # "password": "stu@python",    # 由于有 id_rsa.pub 免密码  
登录
```

```
        },
```

```
        {
```

```
            "hostname": "keepalived2",
```

```
"ip": "172.20.100.71",  
"port": 22,  
"username": "root",  
"groups": ["keepalived"],  
#"password": "stu@python",
```

```
},
```

```
]
```

```
---
```