

被控机要放入 cmdb 所在环境运行用户的 id\_rsa.pud

### 在线配置 nginx

apps/onlineconfig/views/nginx.py

```
def create_conf(request):
    hostip = '192.168.181.133'    # nginx 的主机
    conf_dir = '/usr/local/src/'  # nginx 子 conf 的目录
```

---

### keepalived 网络查看

apps/architecture/views/keepnet.py # 主业务逻辑所在源码文件

```
class GetKeepIpaddr():
    def setUp(self):
        host_data = [          # 这个数组以字典结构内放入所以 keepalived 待机的 host
信息
            {
                "hostname": "keepalived1",    # 这个一定不能重名
                "ip": "172.20.100.68",
                "port": 22,
                "username": "root",    # 不一定要 root 用户，只要是能执行
systemctl status keepalived 的用户都行
                "groups": ["keepalived"],
                #"password": "stu@python",      # 由于有 id_rsa.pub 免密码登
录
            },
            {
                "hostname": "keepalived2",
                "ip": "172.20.100.71",
                "port": 22,
                "username": "root",
                "groups": ["keepalived"],
                #"password": "stu@python",
            },
        ]
    ---
```

### 在线配置 nginx - api 接口

运营后台对接 cmdb api 接口生成代理站相关配置文件及资源所在目录

apps/onlineconfig/api/nginx.py # 主业务逻辑所在源码文件

...

```
# nginx 所在主机
host_data = [
    {
        "hostname": "nginx_1",
        "ip": "172.20.100.104",
        "port": 22,
        "username": "root",
        "groups": ["nginx"],
        #"password": "stu@python",
    }
]
```

```

example = 'example.com'          # nginx conf 文件模板域名

vhost_dir = '/usr/local/nginx/conf/vhost/'          # nginx conf 子配置文件所在目录
master_nginx_conf = "/usr/local/nginx/conf/nginx.conf"  # nginx 主配置文件
nginx_reload = '/usr/local/nginx/sbin/nginx -s reload'  # 重载命令
www_dir = "/usr/local/nginx/html/"                  # 主机资源存放主目录
old_www_dir = "/home/wwwroot/"                      # nginx conf 文件模板原资源存放主目录
'''

```

nginx conf 文件模板 在 cmdb/ 根目录有

生产实际环境的 nginx 主配置文件 nginx.conf 中引入 子配置目录的后面要加上

```

#headinclude
include vhost/*.conf; #headinclude

```

----

### 阿里云 oss 同步

```

apps/cloud/views/aliyu/oss.py          # 主业务逻辑所在源码文件

package_dir = "/storage/dadir"          # 你需要同步的文件或目录
synclog = "/storage/www/ly-cmdb/sync.log"  # 记录 sync.log 状态的文件, 在项目源码第一级目录里有
exec_sync_bucket = "/storage/www/ly-cmdb/sync_bucket.py"  # 执行同步行为的程序文件, 在项目源码第一级目录里有

apps/sync_bucket.py                    # 主业务逻辑所在源码文件 之 执行同步行为的程序文件

synclog = "/storage/www/ly-cmdb/sync.log"  # 记录 sync.log 状态的文件, 在项目源码第一级目录里有
bucket_name = ['regengxin-yfb', 'regengxin-yfb-tmp']  # 存储桶的设置
localdir = "/storage/dadir"              # 你需要同步的文件或目录
auth = oss2.Auth('AccessKeyId', 'AccessKeySecret')  # 阿里云的 auth id 和 key

```

---