

BusBuddy

Generated by Doxygen 1.8.3.1

Fri Apr 26 2013 21:31:26



# Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Namespace Index</b>                   | <b>1</b>  |
| 1.1      | Packages . . . . .                       | 1         |
| <b>2</b> | <b>Hierarchical Index</b>                | <b>3</b>  |
| 2.1      | Class Hierarchy . . . . .                | 3         |
| <b>3</b> | <b>Class Index</b>                       | <b>7</b>  |
| 3.1      | Class List . . . . .                     | 7         |
| <b>4</b> | <b>Namespace Documentation</b>           | <b>13</b> |
| 4.1      | Package alert.client . . . . .           | 13        |
| 4.1.1    | Detailed Description . . . . .           | 13        |
| 4.2      | Package alert.client.model . . . . .     | 13        |
| 4.2.1    | Detailed Description . . . . .           | 13        |
| 4.3      | Package alert.controller . . . . .       | 14        |
| 4.3.1    | Detailed Description . . . . .           | 14        |
| 4.4      | Package alert.controller.model . . . . . | 14        |
| 4.4.1    | Detailed Description . . . . .           | 15        |
| 4.5      | Package alert.domain . . . . .           | 15        |
| 4.5.1    | Detailed Description . . . . .           | 15        |
| 4.6      | Package alert.domain.model . . . . .     | 15        |
| 4.6.1    | Detailed Description . . . . .           | 16        |
| 4.7      | Package alert.enums . . . . .            | 16        |
| 4.7.1    | Detailed Description . . . . .           | 16        |
| 4.8      | Package alert.service . . . . .          | 16        |
| 4.8.1    | Detailed Description . . . . .           | 17        |
| 4.9      | Package common . . . . .                 | 17        |
| 4.9.1    | Detailed Description . . . . .           | 17        |
| 4.10     | Package tracking . . . . .               | 18        |
| 4.10.1   | Detailed Description . . . . .           | 19        |
| 4.11     | Package transit . . . . .                | 19        |
| 4.11.1   | Detailed Description . . . . .           | 20        |

|          |   |           |
|----------|---|-----------|
| 4.12     | Package user                                | 20        |
| 4.12.1   | Detailed Description                        | 21        |
| <b>5</b> | <b>Class Documentation</b>                  | <b>23</b> |
| 5.1      | AbstractFeedParserTemplate Class Reference  | 23        |
| 5.1.1    | Detailed Description                        | 24        |
| 5.1.2    | Member Function Documentation               | 24        |
| 5.1.2.1  | loadFeed                                    | 24        |
| 5.1.2.2  | parseFeed                                   | 24        |
| 5.1.2.3  | saveRoutes                                  | 25        |
| 5.1.2.4  | start                                       | 25        |
| 5.1.2.5  | validate                                    | 25        |
| 5.2      | Alert Class Reference                       | 25        |
| 5.2.1    | Detailed Description                        | 27        |
| 5.2.2    | Member Data Documentation                   | 27        |
| 5.2.2.1  | alertInitiator                              | 27        |
| 5.2.2.2  | alertRunType                                | 27        |
| 5.2.2.3  | alertType                                   | 27        |
| 5.2.2.4  | Status                                      | 27        |
| 5.2.2.5  | userInformation                             | 27        |
| 5.3      | AlertExecuteStrategyFactory Class Reference | 27        |
| 5.3.1    | Detailed Description                        | 28        |
| 5.3.2    | Member Function Documentation               | 28        |
| 5.3.2.1  | getAlertExecuteStrategy                     | 28        |
| 5.4      | AlertExecutionScheduler Class Reference     | 28        |
| 5.4.1    | Detailed Description                        | 28        |
| 5.4.2    | Member Function Documentation               | 28        |
| 5.4.2.1  | getAlertServices                            | 28        |
| 5.4.2.2  | runAlert                                    | 29        |
| 5.5      | AlertFactory Class Reference                | 29        |
| 5.5.1    | Detailed Description                        | 29        |
| 5.5.2    | Member Function Documentation               | 29        |
| 5.5.2.1  | createAlert                                 | 29        |
| 5.5.2.2  | createAlert                                 | 29        |
| 5.6      | AlertInitiator Enum Reference               | 30        |
| 5.6.1    | Detailed Description                        | 30        |
| 5.7      | AlertNotificationType Enum Reference        | 30        |
| 5.7.1    | Detailed Description                        | 30        |
| 5.7.2    | Member Data Documentation                   | 30        |
| 5.7.2.1  | PlannedDisruption                           | 30        |

|          |  |    |
|----------|--|----|
| 5.7.2.2  | ScheduleInformation                    | 30 |
| 5.7.2.3  | UnplannedDisruption                    | 31 |
| 5.8      | AlertRangeLogic Class Reference        | 31 |
| 5.8.1    | Detailed Description                   | 31 |
| 5.9      | AlertRecurringType Enum Reference      | 31 |
| 5.9.1    | Detailed Description                   | 31 |
| 5.10     | AlertRepository Class Reference        | 32 |
| 5.10.1   | Detailed Description                   | 32 |
| 5.10.2   | Member Function Documentation          | 32 |
| 5.10.2.1 | deleteAlert                            | 32 |
| 5.10.2.2 | getAlertByDateTime                     | 32 |
| 5.10.2.3 | getAlertByRoute                        | 33 |
| 5.10.2.4 | getAlertByUserId                       | 33 |
| 5.10.2.5 | saveAlert                              | 33 |
| 5.10.2.6 | updateAlert                            | 33 |
| 5.11     | AlertRequestController Class Reference | 34 |
| 5.11.1   | Detailed Description                   | 34 |
| 5.11.2   | Member Function Documentation          | 35 |
| 5.11.2.1 | processTrackingAlertRequest            | 35 |
| 5.11.2.2 | processTransitAlertRequest             | 35 |
| 5.11.2.3 | processUserAlertRequest                | 35 |
| 5.11.2.4 | verifySession                          | 36 |
| 5.12     | AlertRequestModel Class Reference      | 36 |
| 5.12.1   | Detailed Description                   | 36 |
| 5.12.2   | Member Data Documentation              | 37 |
| 5.12.2.1 | alertInitiator                         | 37 |
| 5.13     | AlertResponseModel Class Reference     | 37 |
| 5.13.1   | Detailed Description                   | 37 |
| 5.14     | AlertRunType Enum Reference            | 37 |
| 5.14.1   | Detailed Description                   | 37 |
| 5.15     | AlertService Class Reference           | 37 |
| 5.15.1   | Detailed Description                   | 38 |
| 5.15.2   | Member Function Documentation          | 38 |
| 5.15.2.1 | createAlert                            | 38 |
| 5.15.2.2 | deleteAlert                            | 39 |
| 5.15.2.3 | saveAlert                              | 39 |
| 5.15.2.4 | sendAlert                              | 39 |
| 5.15.2.5 | updateAlert                            | 39 |
| 5.15.3   | Member Data Documentation              | 40 |
| 5.15.3.1 | alertExecuteStrategyFactory            | 40 |

|          |   |    |
|----------|---|----|
| 5.15.3.2 | alertFactory                                | 40 |
| 5.15.3.3 | alertRepository                             | 40 |
| 5.16     | AlertServiceFactory Class Reference         | 40 |
| 5.16.1   | Detailed Description                        | 41 |
| 5.16.2   | Member Function Documentation               | 41 |
| 5.16.2.1 | getAlertService                             | 41 |
| 5.16.3   | Member Data Documentation                   | 41 |
| 5.16.3.1 | trackingAlertService                        | 41 |
| 5.16.3.2 | transitAlertService                         | 41 |
| 5.16.3.3 | userAlertService                            | 41 |
| 5.17     | AlertSpecification Interface Reference      | 41 |
| 5.17.1   | Detailed Description                        | 42 |
| 5.17.2   | Member Function Documentation               | 42 |
| 5.17.2.1 | inAlertRange                                | 42 |
| 5.18     | AlertStatus Enum Reference                  | 42 |
| 5.18.1   | Detailed Description                        | 43 |
| 5.18.2   | Member Data Documentation                   | 43 |
| 5.18.2.1 | Deactive                                    | 43 |
| 5.18.2.2 | Error                                       | 43 |
| 5.18.2.3 | Expired                                     | 43 |
| 5.19     | AlertType Enum Reference                    | 43 |
| 5.19.1   | Detailed Description                        | 43 |
| 5.20     | AlertUserClient Class Reference             | 43 |
| 5.20.1   | Detailed Description                        | 44 |
| 5.20.2   | Member Function Documentation               | 44 |
| 5.20.2.1 | getUserInformation                          | 44 |
| 5.20.2.2 | verifySessionToken                          | 44 |
| 5.21     | BaseController Class Reference              | 44 |
| 5.21.1   | Detailed Description                        | 45 |
| 5.21.2   | Member Function Documentation               | 45 |
| 5.21.2.1 | handleBusBuddyException                     | 45 |
| 5.21.2.2 | handleGenericException                      | 45 |
| 5.22     | BusBuddyBadRequestException Class Reference | 46 |
| 5.22.1   | Detailed Description                        | 46 |
| 5.22.2   | Member Function Documentation               | 46 |
| 5.22.2.1 | getHttpCode                                 | 46 |
| 5.23     | BusBuddyConflictException Class Reference   | 46 |
| 5.23.1   | Detailed Description                        | 47 |
| 5.23.2   | Member Function Documentation               | 47 |
| 5.23.2.1 | getHttpCode                                 | 47 |

|          |   |    |
|----------|---|----|
| 5.24     | BusBuddyException Class Reference . . . . .                           | 47 |
| 5.24.1   | Detailed Description . . . . .  | 48 |
| 5.24.2   | Member Function Documentation . . . . .                               | 48 |
| 5.24.2.1 | getHttpCode . . . . .   | 48 |
| 5.25     | BusBuddyForbiddenException Class Reference . . . . .                  | 48 |
| 5.25.1   | Detailed Description . . . . .  | 49 |
| 5.25.2   | Member Function Documentation . . . . .                               | 49 |
| 5.25.2.1 | getHttpCode . . . . .   | 49 |
| 5.26     | BusBuddyInternalException Class Reference . . . . .                   | 49 |
| 5.26.1   | Detailed Description . . . . .  | 50 |
| 5.26.2   | Member Function Documentation . . . . .                               | 50 |
| 5.26.2.1 | getHttpCode . . . . .   | 50 |
| 5.27     | BusBuddyNotFoundException Class Reference . . . . .                   | 50 |
| 5.27.1   | Detailed Description . . . . .  | 50 |
| 5.27.2   | Member Function Documentation . . . . .                               | 51 |
| 5.27.2.1 | getHttpCode . . . . .   | 51 |
| 5.28     | BusVehicle Class Reference . . . . .                                  | 51 |
| 5.28.1   | Detailed Description . . . . .  | 51 |
| 5.28.2   | Member Data Documentation . . . . .                                   | 51 |
| 5.28.2.1 | alertList . . . . .   | 51 |
| 5.29     | CertificateHandler Class Reference . . . . .                          | 52 |
| 5.29.1   | Detailed Description . . . . .  | 52 |
| 5.29.2   | Member Function Documentation . . . . .                               | 52 |
| 5.29.2.1 | verifySessionToken . . . . .  | 52 |
| 5.30     | CommercialTracking Class Reference . . . . .                          | 52 |
| 5.30.1   | Detailed Description . . . . .  | 53 |
| 5.30.2   | Constructor & Destructor Documentation . . . . .                      | 53 |
| 5.30.2.1 | CommercialTracking . . . . .  | 53 |
| 5.30.3   | Member Function Documentation . . . . .                               | 53 |
| 5.30.3.1 | getInstance . . . . .   | 53 |
| 5.31     | CommercialTracking.CommercialTrackingHolder Class Reference . . . . . | 54 |
| 5.31.1   | Detailed Description . . . . .  | 54 |
| 5.32     | DelayAlertLogic Class Reference . . . . .                             | 54 |
| 5.32.1   | Detailed Description . . . . .  | 54 |
| 5.33     | Detour Class Reference . . . . .                                      | 54 |
| 5.33.1   | Detailed Description . . . . .  | 55 |
| 5.33.2   | Constructor & Destructor Documentation . . . . .                      | 55 |
| 5.33.2.1 | Detour . . . . .  | 55 |
| 5.33.3   | Member Data Documentation . . . . .                                   | 55 |
| 5.33.3.1 | cause . . . . .   | 55 |

|          |   |    |
|----------|---|----|
| 5.33.3.2 | detourId                                    | 55 |
| 5.33.3.3 | estimatedDelay                              | 56 |
| 5.34     | Fare Class Reference                        | 56 |
| 5.34.1   | Detailed Description                        | 56 |
| 5.34.2   | Constructor & Destructor Documentation      | 56 |
| 5.34.2.1 | Fare  | 56 |
| 5.34.2.2 | Fare  | 57 |
| 5.34.3   | Member Function Documentation               | 57 |
| 5.34.3.1 | setDiscountedFare                           | 57 |
| 5.34.3.2 | setRegularFare                              | 57 |
| 5.34.4   | Member Data Documentation                   | 57 |
| 5.34.4.1 | discountedFare                              | 57 |
| 5.35     | FavoriteTransitService Class Reference      | 57 |
| 5.35.1   | Detailed Description                        | 58 |
| 5.35.2   | Constructor & Destructor Documentation      | 58 |
| 5.35.2.1 | FavoriteTransitService                      | 58 |
| 5.35.3   | Member Function Documentation               | 58 |
| 5.35.3.1 | getFavoriteRouteIds                         | 58 |
| 5.35.3.2 | getTransitServiceUrl                        | 58 |
| 5.35.3.3 | isFavoriteTransitService                    | 58 |
| 5.35.3.4 | setFavoriteRouteIds                         | 59 |
| 5.35.3.5 | setFavoriteTransitService                   | 59 |
| 5.36     | GoogleTransitServiceAdapter Class Reference | 59 |
| 5.36.1   | Detailed Description                        | 59 |
| 5.36.2   | Constructor & Destructor Documentation      | 60 |
| 5.36.2.1 | GoogleTransitServiceAdapter                 | 60 |
| 5.36.3   | Member Function Documentation               | 60 |
| 5.36.3.1 | getRoute                                    | 60 |
| 5.36.3.2 | getRoutes                                   | 60 |
| 5.37     | GoogleTransitServiceAPI Interface Reference | 61 |
| 5.37.1   | Detailed Description                        | 61 |
| 5.38     | GPSLocationObject Class Reference           | 61 |
| 5.38.1   | Detailed Description                        | 61 |
| 5.39     | GPSLocationObserver Class Reference         | 61 |
| 5.39.1   | Detailed Description                        | 62 |
| 5.39.2   | Member Function Documentation               | 62 |
| 5.39.2.1 | getGPSLocation                              | 62 |
| 5.39.2.2 | gpsUpdate                                   | 62 |
| 5.39.2.3 | setGPSLocation                              | 63 |
| 5.40     | GPSLocationTracking Class Reference         | 63 |



|   |    |
|---|----|
| 5.40.1 Detailed Description . . . . .                     | 63 |
| 5.40.2 Member Function Documentation . . . . .            | 63 |
| 5.40.2.1 registerGPSDevice . . . . .                      | 63 |
| 5.40.2.2 unregisterGPSDevice . . . . .                    | 64 |
| 5.41 GPSPuller Class Reference . . . . .                  | 64 |
| 5.41.1 Detailed Description . . . . .                     | 65 |
| 5.41.2 Constructor & Destructor Documentation . . . . .   | 65 |
| 5.41.2.1 GPSPuller . . . . .                              | 65 |
| 5.42 GPSPuller.GPSPullerHolder Class Reference . . . . .  | 65 |
| 5.42.1 Detailed Description . . . . .                     | 65 |
| 5.43 GPSPusher Class Reference . . . . .                  | 65 |
| 5.43.1 Detailed Description . . . . .                     | 66 |
| 5.43.2 Constructor & Destructor Documentation . . . . .   | 66 |
| 5.43.2.1 GPSPusher . . . . .                              | 66 |
| 5.43.3 Member Function Documentation . . . . .            | 66 |
| 5.43.3.1 getInstance . . . . .                            | 66 |
| 5.44 GPSPusher.GPSPusherHolder Class Reference . . . . .  | 67 |
| 5.44.1 Detailed Description . . . . .                     | 67 |
| 5.45 GPSVehicleTracker Class Reference . . . . .          | 67 |
| 5.45.1 Detailed Description . . . . .                     | 67 |
| 5.45.2 Constructor & Destructor Documentation . . . . .   | 68 |
| 5.45.2.1 GPSVehicleTracker . . . . .                      | 68 |
| 5.46 GTFSFeedParser Class Reference . . . . .             | 68 |
| 5.46.1 Detailed Description . . . . .                     | 68 |
| 5.46.2 Member Function Documentation . . . . .            | 68 |
| 5.46.2.1 parseFeed . . . . .                              | 68 |
| 5.47 HashUtility Class Reference . . . . .                | 68 |
| 5.47.1 Detailed Description . . . . .                     | 69 |
| 5.47.2 Member Function Documentation . . . . .            | 69 |
| 5.47.2.1 hash . . . . .                                   | 69 |
| 5.48 IAlertExecuteStrategy Interface Reference . . . . .  | 69 |
| 5.48.1 Detailed Description . . . . .                     | 69 |
| 5.48.2 Member Function Documentation . . . . .            | 69 |
| 5.48.2.1 execute . . . . .                                | 70 |
| 5.49 InvalidRouteParseException Class Reference . . . . . | 70 |
| 5.49.1 Detailed Description . . . . .                     | 70 |
| 5.49.2 Constructor & Destructor Documentation . . . . .   | 71 |
| 5.49.2.1 InvalidRouteParseException . . . . .             | 71 |
| 5.49.3 Member Data Documentation . . . . .                | 71 |
| 5.49.3.1 routeBatch . . . . .                             | 71 |

|          |   |    |
|----------|---|----|
| 5.49.3.2 | serialVersionUID                              | 71 |
| 5.50     | ISessionHandler Interface Reference           | 71 |
| 5.50.1   | Detailed Description                          | 71 |
| 5.50.2   | Member Function Documentation                 | 71 |
| 5.50.2.1 | verifySessionToken                            | 71 |
| 5.51     | ITeamTransitServiceController Class Reference | 72 |
| 5.51.1   | Detailed Description                          | 73 |
| 5.51.2   | Member Function Documentation                 | 73 |
| 5.51.2.1 | getRoute                                      | 73 |
| 5.51.2.2 | getRoutes                                     | 73 |
| 5.51.2.3 | getServiceURL                                 | 74 |
| 5.51.2.4 | getTransitInfo                                | 74 |
| 5.51.2.5 | handleRouteDisruptionEvent                    | 74 |
| 5.51.3   | Member Data Documentation                     | 74 |
| 5.51.3.1 | alertRequestController                        | 74 |
| 5.51.3.2 | transitFeed                                   | 75 |
| 5.52     | ITeamTripServiceController Class Reference    | 75 |
| 5.52.1   | Detailed Description                          | 75 |
| 5.52.2   | Member Function Documentation                 | 75 |
| 5.52.2.1 | calculateTrip                                 | 75 |
| 5.53     | ITeamUserFavoritesService Class Reference     | 76 |
| 5.53.1   | Detailed Description                          | 76 |
| 5.53.2   | Member Function Documentation                 | 76 |
| 5.53.2.1 | readFavorites                                 | 76 |
| 5.53.2.2 | saveFavorites                                 | 76 |
| 5.54     | ITeamUserLoginService Class Reference         | 77 |
| 5.54.1   | Detailed Description                          | 77 |
| 5.54.2   | Member Function Documentation                 | 77 |
| 5.54.2.1 | checkPermissions                              | 77 |
| 5.54.2.2 | createAlertSession                            | 78 |
| 5.54.2.3 | getUser                                       | 78 |
| 5.54.2.4 | login   | 78 |
| 5.54.2.5 | logout  | 78 |
| 5.54.2.6 | resetPassword                                 | 78 |
| 5.54.2.7 | resetPassword                                 | 79 |
| 5.54.2.8 | sendUsername                                  | 79 |
| 5.54.2.9 | sendUsername                                  | 79 |
| 5.55     | ITeamUserManagementService Class Reference    | 79 |
| 5.55.1   | Detailed Description                          | 79 |
| 5.55.2   | Member Function Documentation                 | 80 |

|          |  |    |
|----------|--|----|
| 5.55.2.1 | <a href="#">createUser</a>                                 | 80 |
| 5.55.2.2 | <a href="#">deleteUser</a>                                 | 80 |
| 5.55.2.3 | <a href="#">findUserByEmail</a>                            | 80 |
| 5.55.2.4 | <a href="#">findUserByMobile</a>                           | 80 |
| 5.55.2.5 | <a href="#">findUserByUsername</a>                         | 80 |
| 5.55.2.6 | <a href="#">updateUser</a>                                 | 80 |
| 5.56     | <a href="#">ITrackingService Interface Reference</a>       | 80 |
| 5.56.1   | <a href="#">Detailed Description</a>                       | 81 |
| 5.56.2   | <a href="#">Member Function Documentation</a>              | 81 |
| 5.56.2.1 | <a href="#">addUserTrackingAlert</a>                       | 81 |
| 5.56.2.2 | <a href="#">getTransitVehicleLocation</a>                  | 81 |
| 5.56.2.3 | <a href="#">registerVehicleOnRoute</a>                     | 82 |
| 5.56.2.4 | <a href="#">startTrackingController</a>                    | 82 |
| 5.56.2.5 | <a href="#">unregisterVehicleFromRoute</a>                 | 82 |
| 5.57     | <a href="#">Location Class Reference</a>                   | 82 |
| 5.57.1   | <a href="#">Detailed Description</a>                       | 82 |
| 5.57.2   | <a href="#">Constructor &amp; Destructor Documentation</a> | 83 |
| 5.57.2.1 | <a href="#">Location</a>                                   | 83 |
| 5.58     | <a href="#">MessageDeliveryUtility Class Reference</a>     | 83 |
| 5.58.1   | <a href="#">Detailed Description</a>                       | 83 |
| 5.58.2   | <a href="#">Member Function Documentation</a>              | 83 |
| 5.58.2.1 | <a href="#">sendEmail</a>                                  | 83 |
| 5.58.2.2 | <a href="#">sendSms</a>                                    | 83 |
| 5.59     | <a href="#">OneTimeAlert Class Reference</a>               | 84 |
| 5.59.1   | <a href="#">Detailed Description</a>                       | 84 |
| 5.59.2   | <a href="#">Member Data Documentation</a>                  | 84 |
| 5.59.2.1 | <a href="#">dateExecuted</a>                               | 84 |
| 5.60     | <a href="#">PersistedTransitFeed Class Reference</a>       | 85 |
| 5.60.1   | <a href="#">Detailed Description</a>                       | 85 |
| 5.60.2   | <a href="#">Member Function Documentation</a>              | 85 |
| 5.60.2.1 | <a href="#">getRoute</a>                                   | 85 |
| 5.60.2.2 | <a href="#">getRoutes</a>                                  | 86 |
| 5.61     | <a href="#">RecurringAlert Class Reference</a>             | 86 |
| 5.61.1   | <a href="#">Detailed Description</a>                       | 87 |
| 5.61.2   | <a href="#">Member Data Documentation</a>                  | 87 |
| 5.61.2.1 | <a href="#">alertRecurringType</a>                         | 87 |
| 5.61.2.2 | <a href="#">repeatEvery</a>                                | 87 |
| 5.62     | <a href="#">RecurringData Class Reference</a>              | 87 |
| 5.62.1   | <a href="#">Detailed Description</a>                       | 88 |
| 5.62.2   | <a href="#">Member Data Documentation</a>                  | 88 |

|          |   |    |
|----------|---|----|
| 5.62.2.1 | dayOfMonth                                | 88 |
| 5.62.2.2 | dayOfWeek                                 | 88 |
| 5.62.2.3 | dayOfYear                                 | 88 |
| 5.62.2.4 | startHour                                 | 89 |
| 5.62.2.5 | startMinute                               | 89 |
| 5.63     | Route Class Reference                     | 89 |
| 5.63.1   | Detailed Description                      | 89 |
| 5.63.2   | Constructor & Destructor Documentation    | 90 |
| 5.63.2.1 | Route                                     | 90 |
| 5.63.3   | Member Function Documentation             | 90 |
| 5.63.3.1 | setStops                                  | 90 |
| 5.63.4   | Member Data Documentation                 | 90 |
| 5.63.4.1 | detours                                   | 90 |
| 5.63.4.2 | routeName                                 | 90 |
| 5.63.4.3 | stops                                     | 90 |
| 5.64     | RouteAlertExecuteStrategy Class Reference | 90 |
| 5.64.1   | Detailed Description                      | 91 |
| 5.64.2   | Member Function Documentation             | 91 |
| 5.64.2.1 | execute                                   | 91 |
| 5.64.3   | Member Data Documentation                 | 91 |
| 5.64.3.1 | alertRepository                           | 91 |
| 5.64.3.2 | userClient                                | 91 |
| 5.65     | RouteDisruptionAlert Class Reference      | 92 |
| 5.65.1   | Detailed Description                      | 92 |
| 5.65.2   | Member Data Documentation                 | 92 |
| 5.65.2.1 | routeld                                   | 92 |
| 5.65.2.2 | transitServiceUrl                         | 92 |
| 5.66     | RouteDisruptionEvent Class Reference      | 92 |
| 5.66.1   | Detailed Description                      | 93 |
| 5.66.2   | Constructor & Destructor Documentation    | 93 |
| 5.66.2.1 | RouteDisruptionEvent                      | 93 |
| 5.67     | RouteRepository Interface Reference       | 93 |
| 5.67.1   | Detailed Description                      | 93 |
| 5.67.2   | Member Function Documentation             | 94 |
| 5.67.2.1 | delete                                    | 94 |
| 5.67.2.2 | getAll                                    | 94 |
| 5.67.2.3 | read                                      | 94 |
| 5.67.2.4 | save                                      | 94 |
| 5.67.2.5 | save                                      | 95 |
| 5.68     | RouteSpecification Class Reference        | 95 |

|   |     |
|---|-----|
| 5.68.1 Detailed Description . . . . .                       | 95  |
| 5.68.2 Member Function Documentation . . . . .              | 96  |
| 5.68.2.1 isSatisfiedBy . . . . .                            | 96  |
| 5.69 ScheduleAlertExecuteStrategy Class Reference . . . . . | 96  |
| 5.69.1 Detailed Description . . . . .                       | 97  |
| 5.69.2 Member Data Documentation . . . . .                  | 97  |
| 5.69.2.1 alertRepository . . . . .                          | 97  |
| 5.69.2.2 userClient . . . . .                               | 97  |
| 5.70 Session Class Reference . . . . .                      | 97  |
| 5.70.1 Detailed Description . . . . .                       | 98  |
| 5.70.2 Constructor & Destructor Documentation . . . . .     | 98  |
| 5.70.2.1 Session . . . . .                                  | 98  |
| 5.70.3 Member Function Documentation . . . . .              | 98  |
| 5.70.3.1 getCreationTime . . . . .                          | 98  |
| 5.70.3.2 getExpirationTime . . . . .                        | 98  |
| 5.70.3.3 getSessionToken . . . . .                          | 98  |
| 5.70.3.4 getUserId . . . . .                                | 99  |
| 5.70.3.5 isAlertSession . . . . .                           | 99  |
| 5.70.3.6 isValid . . . . .                                  | 99  |
| 5.70.3.7 setExpirationTime . . . . .                        | 99  |
| 5.70.3.8 setValid . . . . .                                 | 99  |
| 5.71 SessionRepository Class Reference . . . . .            | 99  |
| 5.71.1 Detailed Description . . . . .                       | 100 |
| 5.71.2 Member Function Documentation . . . . .              | 100 |
| 5.71.2.1 createSession . . . . .                            | 100 |
| 5.71.2.2 getSession . . . . .                               | 100 |
| 5.71.2.3 killSession . . . . .                              | 101 |
| 5.72 SessionTokenHandler Class Reference . . . . .          | 101 |
| 5.72.1 Detailed Description . . . . .                       | 102 |
| 5.72.2 Member Function Documentation . . . . .              | 102 |
| 5.72.2.1 verifySessionToken . . . . .                       | 102 |
| 5.72.3 Member Data Documentation . . . . .                  | 102 |
| 5.72.3.1 userClient . . . . .                               | 102 |
| 5.73 SessionVerificationFactory Class Reference . . . . .   | 102 |
| 5.73.1 Detailed Description . . . . .                       | 103 |
| 5.73.2 Member Function Documentation . . . . .              | 103 |
| 5.73.2.1 getSessionTokenVerificationStrategy . . . . .      | 103 |
| 5.74 Specification< T > Interface Reference . . . . .       | 103 |
| 5.74.1 Detailed Description . . . . .                       | 103 |
| 5.74.2 Member Function Documentation . . . . .              | 103 |

|          |   |     |
|----------|---|-----|
| 5.74.2.1 | and                                       | 103 |
| 5.74.2.2 | isSatisfiedBy                             | 104 |
| 5.74.2.3 | not                                       | 104 |
| 5.74.2.4 | or  | 104 |
| 5.75     | Stop Class Reference                      | 104 |
| 5.75.1   | Detailed Description                      | 105 |
| 5.75.2   | Constructor & Destructor Documentation    | 105 |
| 5.75.2.1 | Stop                                      | 105 |
| 5.75.3   | Member Function Documentation             | 105 |
| 5.75.3.1 | getStopTimes                              | 105 |
| 5.75.4   | Member Data Documentation                 | 106 |
| 5.75.4.1 | covered                                   | 106 |
| 5.75.4.2 | description                               | 106 |
| 5.75.4.3 | stopId                                    | 106 |
| 5.76     | TrackingAlertFactory Class Reference      | 106 |
| 5.76.1   | Detailed Description                      | 106 |
| 5.76.2   | Member Function Documentation             | 107 |
| 5.76.2.1 | createAlertObserver                       | 107 |
| 5.77     | TrackingAlertObserver Class Reference     | 107 |
| 5.77.1   | Detailed Description                      | 107 |
| 5.77.2   | Member Function Documentation             | 108 |
| 5.77.2.1 | getSpec                                   | 108 |
| 5.77.2.2 | setSpec                                   | 108 |
| 5.77.2.3 | updateAlert                               | 108 |
| 5.78     | TrackingAlertRequestModel Class Reference | 108 |
| 5.78.1   | Detailed Description                      | 108 |
| 5.79     | TrackingAlertService Class Reference      | 109 |
| 5.79.1   | Detailed Description                      | 109 |
| 5.79.2   | Member Function Documentation             | 109 |
| 5.79.2.1 | createAlert                               | 109 |
| 5.79.2.2 | sendAlert                                 | 109 |
| 5.79.2.3 | updateAlert                               | 110 |
| 5.80     | TrackingDelayAlert Class Reference        | 110 |
| 5.80.1   | Detailed Description                      | 110 |
| 5.80.2   | Member Function Documentation             | 110 |
| 5.80.2.1 | updateAlert                               | 110 |
| 5.81     | TrackingLocationAlert Class Reference     | 111 |
| 5.81.1   | Detailed Description                      | 111 |
| 5.81.2   | Constructor & Destructor Documentation    | 111 |
| 5.81.2.1 | TrackingLocationAlert                     | 111 |

|  |     |
|--|-----|
| 5.82 TrackingResponseModel Class Reference . . . . .     | 111 |
| 5.82.1 Detailed Description . . . . .                    | 112 |
| 5.82.2 Member Function Documentation . . . . .           | 112 |
| 5.82.2.1 convertJSONAlertInput . . . . .                 | 112 |
| 5.82.2.2 convertJSONVehicleInput . . . . .               | 112 |
| 5.82.2.3 formatJSONResponse . . . . .                    | 112 |
| 5.83 TrackingServiceController Class Reference . . . . . | 112 |
| 5.83.1 Detailed Description . . . . .                    | 113 |
| 5.83.2 Member Function Documentation . . . . .           | 113 |
| 5.83.2.1 addUserTrackingAlert . . . . .                  | 113 |
| 5.83.2.2 registerVehicleOnRoute . . . . .                | 113 |
| 5.83.2.3 unregisterVehicleFromRoute . . . . .            | 114 |
| 5.84 TransitAlertRequestModel Class Reference . . . . .  | 114 |
| 5.84.1 Detailed Description . . . . .                    | 114 |
| 5.85 TransitAlertService Class Reference . . . . .       | 114 |
| 5.85.1 Detailed Description . . . . .                    | 115 |
| 5.85.2 Member Function Documentation . . . . .           | 115 |
| 5.85.2.1 createAlert . . . . .                           | 115 |
| 5.85.2.2 sendAlert . . . . .                             | 115 |
| 5.85.2.3 updateAlert . . . . .                           | 115 |
| 5.86 TransitFeed Interface Reference . . . . .           | 115 |
| 5.86.1 Detailed Description . . . . .                    | 116 |
| 5.86.2 Member Function Documentation . . . . .           | 116 |
| 5.86.2.1 getRoute . . . . .                              | 116 |
| 5.86.2.2 getRoutes . . . . .                             | 116 |
| 5.87 TransitInfo Class Reference . . . . .               | 117 |
| 5.87.1 Detailed Description . . . . .                    | 117 |
| 5.87.2 Member Data Documentation . . . . .               | 117 |
| 5.87.2.1 logo . . . . .                                  | 117 |
| 5.87.2.2 transitAuthorityName . . . . .                  | 118 |
| 5.87.2.3 website . . . . .                               | 118 |
| 5.88 TransitProvider Class Reference . . . . .           | 118 |
| 5.88.1 Detailed Description . . . . .                    | 118 |
| 5.88.2 Member Function Documentation . . . . .           | 118 |
| 5.88.2.1 fireRouteDisruptionEvent . . . . .              | 118 |
| 5.88.2.2 registerObserver . . . . .                      | 119 |
| 5.88.2.3 unregisterObserver . . . . .                    | 119 |
| 5.88.3 Member Data Documentation . . . . .               | 119 |
| 5.88.3.1 name . . . . .                                  | 119 |
| 5.88.3.2 providerId . . . . .                            | 119 |

|          |   |     |
|----------|---|-----|
| 5.89     | TransitProviderObserver Interface Reference | 119 |
| 5.89.1   | Detailed Description                        | 120 |
| 5.89.2   | Member Function Documentation               | 120 |
| 5.89.2.1 | handleRouteDisruptionEvent                  | 120 |
| 5.90     | TransitService Interface Reference          | 120 |
| 5.90.1   | Detailed Description                        | 120 |
| 5.90.2   | Member Function Documentation               | 120 |
| 5.90.2.1 | getRoute                                    | 120 |
| 5.90.2.2 | getRoutes                                   | 121 |
| 5.90.2.3 | getServiceURL                               | 121 |
| 5.90.2.4 | getTransitInfo                              | 122 |
| 5.91     | TransitVehicle Class Reference              | 122 |
| 5.91.1   | Detailed Description                        | 122 |
| 5.91.2   | Member Function Documentation               | 123 |
| 5.91.2.1 | addAlertSpecification                       | 123 |
| 5.91.2.2 | checkForAlerts                              | 123 |
| 5.92     | TransitVehicleFactory Class Reference       | 123 |
| 5.92.1   | Detailed Description                        | 123 |
| 5.92.2   | Member Function Documentation               | 123 |
| 5.92.2.1 | createTransitVehicle                        | 123 |
| 5.92.2.2 | getGPSTypeFromURL                           | 124 |
| 5.92.2.3 | getVehicleGPSDeviceID                       | 124 |
| 5.93     | Trip Class Reference                        | 124 |
| 5.93.1   | Detailed Description                        | 124 |
| 5.93.2   | Constructor & Destructor Documentation      | 125 |
| 5.93.2.1 | Trip  | 125 |
| 5.94     | TripInformation Class Reference             | 125 |
| 5.94.1   | Detailed Description                        | 125 |
| 5.94.2   | Member Function Documentation               | 125 |
| 5.94.2.1 | getRouteIds                                 | 125 |
| 5.94.3   | Member Data Documentation                   | 126 |
| 5.94.3.1 | tripData                                    | 126 |
| 5.95     | TripService Interface Reference             | 126 |
| 5.95.1   | Detailed Description                        | 126 |
| 5.95.2   | Member Function Documentation               | 126 |
| 5.95.2.1 | calculateTrip                               | 126 |
| 5.96     | User Class Reference                        | 127 |
| 5.96.1   | Detailed Description                        | 128 |
| 5.96.2   | Constructor & Destructor Documentation      | 128 |
| 5.96.2.1 | User  | 128 |



|  |     |
|--|-----|
| 5.96.3 Member Function Documentation . . . . .           | 128 |
| 5.96.3.1 getCountryCode . . . . .                        | 128 |
| 5.96.3.2 getEmail . . . . .                              | 128 |
| 5.96.3.3 getFirstName . . . . .                          | 128 |
| 5.96.3.4 getMobile . . . . .                             | 129 |
| 5.96.3.5 getPasswordHash . . . . .                       | 129 |
| 5.96.3.6 getUserId . . . . .                             | 129 |
| 5.96.3.7 getUsername . . . . .                           | 129 |
| 5.96.3.8 getUserType . . . . .                           | 129 |
| 5.96.3.9 isForcePasswordChange . . . . .                 | 130 |
| 5.96.3.10 setCountryCode . . . . .                       | 130 |
| 5.96.3.11 setEmail . . . . .                             | 130 |
| 5.96.3.12 setFirstName . . . . .                         | 130 |
| 5.96.3.13 setForcePasswordChange . . . . .               | 130 |
| 5.96.3.14 setMobile . . . . .                            | 130 |
| 5.96.3.15 setPasswordHash . . . . .                      | 131 |
| 5.96.3.16 setUserType . . . . .                          | 131 |
| 5.97 UserAlertRequestModel Class Reference . . . . .     | 131 |
| 5.97.1 Detailed Description . . . . .                    | 131 |
| 5.98 UserAlertService Class Reference . . . . .          | 131 |
| 5.98.1 Detailed Description . . . . .                    | 132 |
| 5.98.2 Member Function Documentation . . . . .           | 132 |
| 5.98.2.1 createAlert . . . . .                           | 132 |
| 5.98.2.2 sendAlert . . . . .                             | 132 |
| 5.98.2.3 updateAlert . . . . .                           | 132 |
| 5.99 UserFavoritesList Class Reference . . . . .         | 133 |
| 5.99.1 Detailed Description . . . . .                    | 133 |
| 5.99.2 Constructor & Destructor Documentation . . . . .  | 133 |
| 5.99.2.1 UserFavoritesList . . . . .                     | 133 |
| 5.99.3 Member Function Documentation . . . . .           | 133 |
| 5.99.3.1 getFavoriteTransitServices . . . . .            | 133 |
| 5.99.3.2 getUserId . . . . .                             | 133 |
| 5.99.3.3 setFavoriteTransitServices . . . . .            | 134 |
| 5.100 UserFavoritesRepository Class Reference . . . . .  | 134 |
| 5.100.1 Detailed Description . . . . .                   | 134 |
| 5.100.2 Member Function Documentation . . . . .          | 134 |
| 5.100.2.1 getFavorites . . . . .                         | 134 |
| 5.100.2.2 updateFavorites . . . . .                      | 135 |
| 5.101 UserFavoritesService Interface Reference . . . . . | 135 |
| 5.101.1 Detailed Description . . . . .                   | 135 |

|   |     |
|---|-----|
| 5.101.2 Member Function Documentation . . . . .           | 135 |
| 5.101.2.1 readFavorites . . . . .                         | 136 |
| 5.101.2.2 saveFavorites . . . . .                         | 136 |
| 5.102 UserInformation Class Reference . . . . .           | 136 |
| 5.102.1 Detailed Description . . . . .                    | 137 |
| 5.103 UserLoginService Interface Reference . . . . .      | 137 |
| 5.103.1 Detailed Description . . . . .                    | 138 |
| 5.103.2 Member Function Documentation . . . . .           | 138 |
| 5.103.2.1 createAlertSession . . . . .                    | 138 |
| 5.103.2.2 getUser . . . . .                               | 139 |
| 5.103.2.3 login . . . . .                                 | 139 |
| 5.103.2.4 logout . . . . .                                | 140 |
| 5.103.2.5 resetPassword . . . . .                         | 140 |
| 5.103.2.6 resetPassword . . . . .                         | 141 |
| 5.103.2.7 sendUsername . . . . .                          | 141 |
| 5.103.2.8 sendUsername . . . . .                          | 142 |
| 5.104 UserManagementService Interface Reference . . . . . | 142 |
| 5.104.1 Detailed Description . . . . .                    | 143 |
| 5.104.2 Member Function Documentation . . . . .           | 143 |
| 5.104.2.1 createUser . . . . .                            | 143 |
| 5.104.2.2 deleteUser . . . . .                            | 144 |
| 5.104.2.3 findUserByEmail . . . . .                       | 144 |
| 5.104.2.4 findUserByMobile . . . . .                      | 145 |
| 5.104.2.5 findUserByUsername . . . . .                    | 146 |
| 5.104.2.6 updateUser . . . . .                            | 146 |
| 5.105 UserRepository Class Reference . . . . .            | 147 |
| 5.105.1 Detailed Description . . . . .                    | 147 |
| 5.105.2 Member Function Documentation . . . . .           | 147 |
| 5.105.2.1 createUser . . . . .                            | 147 |
| 5.105.2.2 deleteUser . . . . .                            | 148 |
| 5.105.2.3 getUserByEmail . . . . .                        | 148 |
| 5.105.2.4 getUserById . . . . .                           | 149 |
| 5.105.2.5 getUserByMobile . . . . .                       | 149 |
| 5.105.2.6 getUserByUsername . . . . .                     | 150 |
| 5.105.2.7 updateUser . . . . .                            | 151 |
| 5.106 UserSessionInformation Class Reference . . . . .    | 151 |
| 5.106.1 Detailed Description . . . . .                    | 151 |
| 5.106.2 Member Data Documentation . . . . .               | 152 |
| 5.106.2.1 userSessionToken . . . . .                      | 152 |
| 5.107 UserTrackingAlertObject Class Reference . . . . .   | 152 |

|   |     |
|---|-----|
| 5.107.1 Detailed Description . . . . .            | 152 |
| 5.107.2 Member Data Documentation . . . . .       | 152 |
| 5.107.2.1 alertTime . . . . .                     | 152 |
| 5.107.2.2 routeID . . . . .                       | 152 |
| 5.107.2.3 scheduledTime . . . . .                 | 153 |
| 5.107.2.4 stopLocation . . . . .                  | 153 |
| 5.107.2.5 transitCoInfo . . . . .                 | 153 |
| 5.107.2.6 type . . . . .                          | 153 |
| 5.107.2.7 userContactInfo . . . . .               | 153 |
| 5.108 UserType Enum Reference . . . . .           | 153 |
| 5.108.1 Detailed Description . . . . .            | 153 |
| 5.109 VehicleObject Class Reference . . . . .     | 154 |
| 5.109.1 Detailed Description . . . . .            | 154 |
| 5.109.2 Member Data Documentation . . . . .       | 154 |
| 5.109.2.1 currentRoute . . . . .                  | 154 |
| 5.109.2.2 gpsDeviceID . . . . .                   | 154 |
| 5.109.2.3 gpsDeviceInfo . . . . .                 | 154 |
| 5.109.2.4 transitCoURL . . . . .                  | 154 |
| 5.110 VehicleRepository Class Reference . . . . . | 155 |
| 5.110.1 Detailed Description . . . . .            | 155 |
| 5.110.2 Member Function Documentation . . . . .   | 155 |
| 5.110.2.1 findVehicle . . . . .                   | 155 |
| 5.110.2.2 findVehiclesByRoute . . . . .           | 155 |
| 5.110.2.3 removeVehicle . . . . .                 | 156 |
| 5.110.2.4 updateVehicle . . . . .                 | 156 |



# Chapter 1

## Namespace Index

### 1.1 Packages

Here are the packages with brief descriptions (if available):

|  |   |    |
|--|---|----|
| <a href="#">alert.client</a>           | This package contains client layer classes that facilitates the call to other modules. We use client layer to communicate and gather information from external system . . . . . | 13 |
| <a href="#">alert.client.model</a>     | This package contains model needed for client layer classes . . . . .   | 13 |
| <a href="#">alert.controller</a>       | This package contains controller layer classes for Alert module which takes in REST request from external sources . . . . .   | 14 |
| <a href="#">alert.controller.model</a> | This package contains model needed for controller layer . . . . .   | 14 |
| <a href="#">alert.domain</a>           | This package contains domain layer classes for Alert Module . . . . .   | 15 |
| <a href="#">alert.domain.model</a>     | This package contains entity and aggregate needed for domain layer in <a href="#">Alert</a> Module . . . . .  | 15 |
| <a href="#">alert.enums</a>            | This package contains enums needed for Alert module . . . . .   | 16 |
| <a href="#">alert.service</a>          | This package contains service layer classes needed for Alert Module . . . . .   | 16 |
| <a href="#">common</a>                 | This package contains common BusBuddy objects and utilities to be used by all modules . . . . .   | 17 |
| <a href="#">tracking</a>               | Tracking Module manages GPS vehicle tracking and alerting subscribed users based on vehicle location . . . . .  | 18 |
| <a href="#">transit</a>                | The Transit Module is an interface to get <a href="#">Route/Fare/Detour</a> information from a <a href="#">TransitProvider</a> . . . . .  | 19 |
| <a href="#">user</a>                   | This package contains the objects used by the <a href="#">User</a> Module of the BusBuddy application . . . . .   | 20 |



## Chapter 2

# Hierarchical Index

### 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

|   |     |
|---|-----|
| AbstractFeedParserTemplate . . . . .                  | 23  |
| GTFSFeedParser . . . . .                              | 68  |
| AlertExecuteStrategyFactory . . . . .                 | 27  |
| AlertExecutionScheduler . . . . .                     | 28  |
| AlertFactory . . . . .                                | 29  |
| AlertInitiator . . . . .                              | 30  |
| AlertNotificationType . . . . .                       | 30  |
| AlertRecurringType . . . . .                          | 31  |
| AlertRepository . . . . .                             | 32  |
| AlertRequestController . . . . .                      | 34  |
| AlertRequestModel . . . . .                           | 36  |
| TrackingAlertRequestModel . . . . .                   | 108 |
| TransitAlertRequestModel . . . . .                    | 114 |
| UserAlertRequestModel . . . . .                       | 131 |
| AlertResponseModel . . . . .                          | 37  |
| AlertRunType . . . . .                                | 37  |
| AlertService . . . . .                                | 37  |
| TrackingAlertService . . . . .                        | 109 |
| TransitAlertService . . . . .                         | 114 |
| UserAlertService . . . . .                            | 131 |
| AlertServiceFactory . . . . .                         | 40  |
| AlertSpecification . . . . .                          | 41  |
| AlertRangeLogic . . . . .                             | 31  |
| DelayAlertLogic . . . . .                             | 54  |
| AlertStatus . . . . .                                 | 42  |
| AlertType . . . . .                                   | 43  |
| AlertUserClient . . . . .                             | 43  |
| BaseController . . . . .                              | 44  |
| ITeamTransitServiceController . . . . .               | 72  |
| ITeamTripServiceController . . . . .                  | 75  |
| CommercialTracking.CommercialTrackingHolder . . . . . | 54  |
| Detour . . . . .                                      | 54  |
| Exception   |     |
| BusBuddyException . . . . .                           | 47  |
| BusBuddyBadRequestException . . . . .                 | 46  |
| BusBuddyConflictException . . . . .                   | 46  |

|   |     |
|---|-----|
| BusBuddyForbiddenException . . . . .    | 48  |
| BusBuddyInternalException . . . . .     | 49  |
| BusBuddyNotFoundException . . . . .     | 50  |
| InvalidRouteParseException . . . . .    | 70  |
| Fare . . . . .                          | 56  |
| FavoriteTransitService . . . . .        | 57  |
| GoogleTransitServiceAPI . . . . .       | 61  |
| GPSLocationObject . . . . .             | 61  |
| GPSLocationObserver . . . . .           | 61  |
| GPSVehicleTracker . . . . .             | 67  |
| GPSLocationTracking . . . . .           | 63  |
| CommercialTracking . . . . .            | 52  |
| GPSPuller . . . . .                     | 64  |
| GPSPusher . . . . .                     | 65  |
| GPSPuller.GPSPullerHolder . . . . .     | 65  |
| GPSPusher.GPSPusherHolder . . . . .     | 67  |
| HashUtility . . . . .                   | 68  |
| IAAlertExecuteStrategy . . . . .        | 69  |
| RouteAlertExecuteStrategy . . . . .     | 90  |
| ScheduleAlertExecuteStrategy . . . . .  | 96  |
| ISessionHandler . . . . .               | 71  |
| CertificateHandler . . . . .            | 52  |
| SessionTokenHandler . . . . .           | 101 |
| ITrackingService . . . . .              | 80  |
| TrackingServiceController . . . . .     | 112 |
| Location . . . . .                      | 82  |
| MessageDeliveryUtility . . . . .        | 83  |
| RecurringData . . . . .                 | 87  |
| Route . . . . .                         | 89  |
| RouteDisruptionAlert . . . . .          | 92  |
| RouteDisruptionEvent . . . . .          | 92  |
| RouteRepository . . . . .               | 93  |
| Session . . . . .                       | 97  |
| SessionRepository . . . . .             | 99  |
| SessionVerificationFactory . . . . .    | 102 |
| Specification< T > . . . . .            | 103 |
| Stop . . . . .                          | 104 |
| TrackingAlertFactory . . . . .          | 106 |
| TrackingAlertObserver . . . . .         | 107 |
| TrackingDelayAlert . . . . .            | 110 |
| TrackingLocationAlert . . . . .         | 111 |
| TrackingResponseModel . . . . .         | 111 |
| TransitFeed . . . . .                   | 115 |
| GoogleTransitServiceAdapter . . . . .   | 59  |
| PersistedTransitFeed . . . . .          | 85  |
| TransitInfo . . . . .                   | 117 |
| TransitProvider . . . . .               | 118 |
| TransitProviderObserver . . . . .       | 119 |
| ITeamTransitServiceController . . . . . | 72  |
| TransitService . . . . .                | 120 |
| ITeamTransitServiceController . . . . . | 72  |
| TransitVehicle . . . . .                | 122 |
| BusVehicle . . . . .                    | 51  |
| TransitVehicleFactory . . . . .         | 123 |
| Trip . . . . .                          | 124 |



|                                      |     |
|--------------------------------------|-----|
| TripInformation . . . . .            | 125 |
| TripService . . . . .                | 126 |
| ITeamTripServiceController . . . . . | 75  |
| User . . . . .                       | 127 |
| UserFavoritesList . . . . .          | 133 |
| UserFavoritesRepository . . . . .    | 134 |
| UserFavoritesService . . . . .       | 135 |
| ITeamUserFavoritesService . . . . .  | 76  |
| UserInfo . . . . .                   | 136 |
| UserLoginService . . . . .           | 137 |
| ITeamUserLoginService . . . . .      | 77  |
| UserManagementService . . . . .      | 142 |
| ITeamUserManagementService . . . . . | 79  |
| UserRepository . . . . .             | 147 |
| UserSessionInformation . . . . .     | 151 |
| UserTrackingAlertObject . . . . .    | 152 |
| UserType . . . . .                   | 153 |
| VehicleObject . . . . .              | 154 |
| VehicleRepository . . . . .          | 155 |
| Serializable                         |     |
| Alert . . . . .                      | 25  |
| OneTimeAlert . . . . .               | 84  |
| RecurringAlert . . . . .             | 86  |
| Specification                        |     |
| RouteSpecification . . . . .         | 95  |



## Chapter 3

# Class Index

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

|   |  |    |
|---|--|----|
| <a href="#">AbstractFeedParserTemplate</a>  | A Template Method pattern to allow for the import of data from different <a href="#">TransitProviders</a> in potentially different formats . . . . .                                   | 23 |
| <a href="#">Alert</a>                       | This is a base <a href="#">Alert</a> Model that has most of the common information about an <a href="#">Alert</a> . . . . .  | 25 |
| <a href="#">AlertExecuteStrategyFactory</a> | This factory is going to pick the best available strategy to execute the alert so that the user can be notified . . . . .  | 27 |
| <a href="#">AlertExecutionScheduler</a>     | This is a background service that runs all the time . . . . .  | 28 |
| <a href="#">AlertFactory</a>                | An alert factory that can create different types of semi-populated alert models depending upon the information . . . . .   | 29 |
| <a href="#">AlertInitiator</a>              | A list of enums corresponding with modules that initiates the call . . . . .   | 30 |
| <a href="#">AlertNotificationType</a>       | Notification type of alert, . . . . .  | 30 |
| <a href="#">AlertRangeLogic</a>             | Alert Range Logic implements the business logic to determine if a vehicle is within a range where an alert needs to be sent to a user who has registered for tracking alerts . . . . . | 31 |
| <a href="#">AlertRecurringType</a>          | Represents different recurring type of alert i.e., Yearly, Monthly, Weekly or Daily . . . . .  | 31 |
| <a href="#">AlertRepository</a>             | A Repository that handles the persistent behavior of the <a href="#">Alert</a> aggregate . . . . .   | 32 |
| <a href="#">AlertRequestController</a>      | This is a front facing controller that takes in request from other module via REST call and returns a JSON representation data . . . . .   | 34 |
| <a href="#">AlertRequestModel</a>           | A base model that contains bare minimum information about the alert request . . . . .  | 36 |
| <a href="#">AlertResponseModel</a>          | This is a basic alert response model that is returned for every alert related requested . . . . .  | 37 |
| <a href="#">AlertRunType</a>                | Represents the type of alert depending upon the run type whether to run once or to run in a fixed recurring manner . . . . .   | 37 |
| <a href="#">AlertService</a>                | Alert Service is a base class that is extended by other module specific services . . . . .   | 37 |

|  |    |
|--|----|
| <a href="#">AlertServiceFactory</a>  |    |
| <a href="#">AlertServiceFactory</a> initializes appropriate alert service depending upon the parameter being passed . . . . .  | 40 |
| <a href="#">AlertSpecification</a>   |    |
| Interface for Alert Specifications which contain the business logic used to determine if an alert should be triggered for a vehicle . . . . .  | 41 |
| <a href="#">AlertStatus</a>  |    |
| Represents the status of an alert depending upon its state in its life cycle . . . . .   | 42 |
| <a href="#">AlertType</a>  |    |
| Enumeration of the alert types recognized by bus buddy . . . . .   | 43 |
| <a href="#">AlertUserClient</a>  |    |
| Client layer will handle all the responsibility of sending request to other modules or external sources . . . . .  | 43 |
| <a href="#">BaseController</a>   |    |
| This is a base class to be extended by each of the controller classes . . . . .  | 44 |
| <a href="#">BusBuddyBadRequestException</a>  |    |
| This exception object represents internal errors which may occur as a result of an error in the client's request . . . . .   | 46 |
| <a href="#">BusBuddyConflictException</a>  |    |
| This exception object is thrown when a request would create a conflict which violates constraints set within the system . . . . .  | 46 |
| <a href="#">BusBuddyException</a>  |    |
| This exception object is an abstract base class . . . . .  | 47 |
| <a href="#">BusBuddyForbiddenException</a>   |    |
| This exception object represents internal errors which may occur as a result of attempts to access a resource without authorization . . . . .  | 48 |
| <a href="#">BusBuddyInternalException</a>  |    |
| This exception object represents internal errors which may occur, which are generally not due to the specifics of what appears to be a valid request . . . . .   | 49 |
| <a href="#">BusBuddyNotFoundException</a>  |    |
| This exception object represents the error that occurs when a resource cannot be found . . . . .   | 50 |
| <a href="#">BusVehicle</a>   |    |
| Bus Vehicle is a concrete implementation of the abstract Transit Vehicle . . . . .   | 51 |
| <a href="#">CertificateHandler</a>   |    |
| A concrete strategy implementation of <a href="#">ISessionHandler</a> that can verify the certificate token being passed . . . . .   | 52 |
| <a href="#">CommercialTracking</a>   |    |
| Implements Subject <a href="#">GPSLocationTracking</a> for retrieving GPS location updates from outside commercial tracking services . . . . .   | 52 |
| <a href="#">CommercialTracking.CommercialTrackingHolder</a>  |    |
| Commercial Tracking Holder is loaded on the first execution of <a href="#">CommercialTracking.getInstance()</a> or the first access to <a href="#">CommercialTracking.INSTANCE</a> , not before (lazy instantiation) . . . . . | 54 |
| <a href="#">DelayAlertLogic</a>  |    |
| Implements the business logic to determine if the vehicle is behind schedule or not reporting GPS updates and send a notification to the transit company . . . . .   | 54 |
| <a href="#">Detour</a>   |    |
| A disruption in service due to an unexpected event . . . . .   | 54 |
| <a href="#">Fare</a>   |    |
| An immutable Value Object representing the cost, or 'fare,' required to ride a <a href="#">TransitVehicle</a> on a particular <a href="#">Route</a> . . . . .  | 56 |
| <a href="#">FavoriteTransitService</a>   |    |
| This class is a single transit service in a user's list of favorites . . . . .   | 57 |
| <a href="#">GoogleTransitServiceAdapter</a>  |    |
| An Adapter Class to allow a <a href="#">GoogleTransitServiceAPI</a> service to appear as a <a href="#">TransitService</a> . . . . .  | 59 |
| <a href="#">GoogleTransitServiceAPI</a>  |    |
| A client to Google's <a href="#">Maps API</a> . . . . .  | 61 |
| <a href="#">GPSLocationObject</a>  |    |
| GPS Location is a value object used for GPS coordinates and the time of the last update . . . . .  | 61 |

|  |    |
|--|----|
| <a href="#">GPSLocationObserver</a>  |    |
| Observer Pattern - Observer interface for GPS location tracking . . . . .  | 61 |
| <a href="#">GPSLocationTracking</a>  |    |
| <a href="#">GPSLocationTracking</a> - interface Subject of the Observer Pattern Defines methods for an observer GPS Device to register and receive updates on vehicle location . . . . .                             | 63 |
| <a href="#">GPSPuller</a>  |    |
| GPS Puller is a concrete implementation of <a href="#">GPSLocationTracking</a> for obtaining coordinates directly from a GPS device installed in a registered vehicle . . . . .                                      | 64 |
| <a href="#">GPSPuller.GPSPullerHolder</a>  |    |
| GPS Puller Holder is loaded on the first execution of <a href="#">GPSPuller.getInstance()</a> or the first access to <a href="#">GPSPuller.INSTANCE</a> , not before (lazy instantiation) . . . . .                  | 65 |
| <a href="#">GPSPusher</a>  |    |
| Implements Subject <a href="#">GPSLocationTracking</a> for retrieving GPS location updates from registered vehicles . . . . .  | 65 |
| <a href="#">GPSPusher.GPSPusherHolder</a>  |    |
| GPS Pusher Holder is loaded on the first execution of <a href="#">GPSPusher.getInstance()</a> or the first access to <a href="#">GPSPusher.INSTANCE</a> , not before (lazy instantiation) . . . . .                  | 67 |
| <a href="#">GPSVehicleTracker</a>  |    |
| Implementation of the Observer, update transit vehicle GPS location and time GPS Vehicle Tracker gets the state as new GPS coordinates and time from GPS Location Tracking and updates the transit vehicle . . . . . | 67 |
| <a href="#">GTFSFeedParser</a>   |    |
| A <a href="#">AbstractFeedParserTemplate</a> implementation designed to parse <a href="#">GTFS</a> format ZIP files into <a href="#">Routes</a> . . . . .  | 68 |
| <a href="#">HashUtility</a>  |    |
| This is a utility class to handle secure hashes . . . . .  | 68 |
| <a href="#">IAlertExecuteStrategy</a>  |    |
| An interface for executing different type of alert based on alert type . . . . .   | 69 |
| <a href="#">InvalidRouteParseException</a>   |    |
| An <a href="#">InvalidRouteParseException</a> indicates an invalid batch of parsed <a href="#">Routes</a> has been detected . . . . .  | 70 |
| <a href="#">ISessionHandler</a>  |    |
| An interface to verify the validity of encrypted token being passed . . . . .  | 71 |
| <a href="#">ITeamTransitServiceController</a>  |    |
| The iTeam implementation of the <a href="#">TransitService</a> that exposes Transit data via a REST Service . . . . .  | 72 |
| <a href="#">ITeamTripServiceController</a>   |    |
| An iTeam implementation of the <a href="#">TripService</a> that exposes <a href="#">Trip</a> data via a REST Service . . . . .   | 75 |
| <a href="#">ITeamUserFavoritesService</a>  |    |
| This is the iTeam's implementation of <a href="#">UserFavoritesService</a> . . . . .   | 76 |
| <a href="#">ITeamUserLoginService</a>  |    |
| This is the iTeam's implementation of <a href="#">UserLoginService</a> . . . . .   | 77 |
| <a href="#">ITeamUserManagementService</a>   |    |
| This is the iTeam's implementation of <a href="#">UserManagementService</a> . . . . .  | 79 |
| <a href="#">ITrackingService</a>   |    |
| Interface for the Tracking Service Controller . . . . .  | 80 |
| <a href="#">Location</a>   |    |
| An immutable Value Object representing a physical point on the geographic coordinate system . . . . .  | 82 |
| <a href="#">MessageDeliveryUtility</a>   |    |
| This is a utility class to handle message delivery, such as through email or SMS . . . . .   | 83 |
| <a href="#">OneTimeAlert</a>   |    |
| This is a model of alert that is to be run one time only . . . . .   | 84 |
| <a href="#">PersistedTransitFeed</a>   |    |
| An implementation of the <a href="#">TransitFeed</a> interface that communicates with a <a href="#">RouteRepository</a> to retrieve its data . . . . .   | 85 |
| <a href="#">RecurringAlert</a>   |    |
| This is a model of alert that is to be run multiple times . . . . .  | 86 |
| <a href="#">RecurringData</a>  |    |
| This model holds the information about the date and time the alert needs to run . . . . .  | 87 |

|   |     |
|---|-----|
| <a href="#">Route</a>   |     |
| A <a href="#">Route</a> is a <a href="#">TransitVehicle</a> path of travel, or a "Line," as referred to by a <a href="#">TransitProvider</a>  | 89  |
| <a href="#">RouteAlertExecuteStrategy</a>   |     |
| A concrete implementation of <a href="#">IAlertExecuteStrategy</a> that handles executing alert related to route changes  | 90  |
| <a href="#">RouteDisruptionAlert</a>  |     |
| An Alert indicating a disruption of normal <a href="#">Route</a> availability or scheduling   | 92  |
| <a href="#">RouteDisruptionEvent</a>  |     |
| An event indicating a disruption in normal <a href="#">Route</a> scheduling or service  | 92  |
| <a href="#">RouteRepository</a>   |     |
| A Repository Pattern supporting lifecycle operations of <a href="#">Routes</a> , such as Read, Save, Delete, and Query functionality  | 93  |
| <a href="#">RouteSpecification</a>  |     |
| A Specification Pattern class for validating a <a href="#">Route</a>  | 95  |
| <a href="#">ScheduleAlertExecuteStrategy</a>  |     |
| A concrete implementation of <a href="#">IAlertExecuteStrategy</a> that handles executing alert related to user's regular schedule  | 96  |
| <a href="#">Session</a>   |     |
| This class represents a single session for a user of the system, and all of the state data associated with that session   | 97  |
| <a href="#">SessionRepository</a>   |     |
| This class is responsible for handling database access for Sessions, and to construct, persist, and retrieve <a href="#">Session</a> objects  | 99  |
| <a href="#">SessionTokenHandler</a>   |     |
| A concrete strategy implementation of <a href="#">ISessionHandler</a> that can verify the session token being passed  | 101 |
| <a href="#">SessionVerificationFactory</a>  |     |
| A factory that picks the appropriate strategy <a href="#">ISessionHandler</a> to verify the encrypted token   | 102 |
| <a href="#">Specification&lt; T &gt;</a>  |     |
| A Generic Specification to be used for chaining business validation rules together  | 103 |
| <a href="#">Stop</a>  |     |
| A point on a <a href="#">Route</a> in which a <a href="#">TransitVehicle</a> will stop to pick up and drop off passengers   | 104 |
| <a href="#">TrackingAlertFactory</a>  |     |
| The Alert Factory handles the creation of a user alert  | 106 |
| <a href="#">TrackingAlertObserver</a>   |     |
| Abstract class defining the methods for the tracking alert observer   | 107 |
| <a href="#">TrackingAlertRequestModel</a>   |     |
| This model is a JSON representation of the request from Tracking module   | 108 |
| <a href="#">TrackingAlertService</a>  |     |
| Extends <a href="#">AlertService</a> and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy   | 109 |
| <a href="#">TrackingDelayAlert</a>  |     |
| Tracking Alert Observer implements the abstract tracking alert observer and provides the method to actually send an alert to a registered user that their bus is approaching their stop | 110 |
| <a href="#">TrackingLocationAlert</a>   |     |
| Concrete implementation of the tracking alert observer  | 111 |
| <a href="#">TrackingResponseModel</a>   |     |
| This is a basic tracking response model that is returned for every tracking related request   | 111 |
| <a href="#">TrackingServiceController</a>   |     |
| Tracking service controller is the concrete implementation of the tracking service interface  | 112 |
| <a href="#">TransitAlertRequestModel</a>  |     |
| This model is a JSON representation of the request from Transit module  | 114 |
| <a href="#">TransitAlertService</a>   |     |
| Extends <a href="#">AlertService</a> and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy   | 114 |
| <a href="#">TransitFeed</a>   |     |
| A <a href="#">TransitFeed</a> is an abstraction over a service or set of services that provide information about <a href="#">Routes</a>   | 115 |

|   |   |     |
|---|---|-----|
| <a href="#">TransitInfo</a>             | An immutable Value Object describing metadata about a <a href="#">TransitService</a> . . . . .  | 117 |
| <a href="#">TransitProvider</a>         | A <a href="#">TransitProvider</a> is a description of a company or organization that is the producer of public transportation services . . . . .  | 118 |
| <a href="#">TransitProviderObserver</a> | An asynchronous update interface for receiving notifications about <a href="#">TransitProvider Route</a> disruptions . . . . .  | 119 |
| <a href="#">TransitService</a>          | The <a href="#">TransitService</a> is an interface to get <a href="#">Route/Fare/Detour</a> information from a <a href="#">TransitProvider</a> .  | 120 |
| <a href="#">TransitVehicle</a>          | Abstract transit vehicle class contains the common data for all types of vehicles and the Subject GPS Tracking and the GPS observer to receive GPS location updates . . . . .   | 122 |
| <a href="#">TransitVehicleFactory</a>   | Transit Vehicle Factory encapsulates the complexity of creating a new vehicle . . . . .   | 123 |
| <a href="#">Trip</a>                    | A <a href="#">Trip</a> is considered an ordered collection of <a href="#">Routes</a> going from a starting point to an ending point   | 124 |
| <a href="#">TripInformation</a>         | This model stores the information about a trip as a value object . . . . .  | 125 |
| <a href="#">TripService</a>             | A Service to calculate a collection of <a href="#">Routes</a> , or a <a href="#">Trip</a> , allowing for a continuous transit path from a start <a href="#">Location</a> to an end <a href="#">Location</a> . . . . . | 126 |
| <a href="#">User</a>                    | This class represents a single user of the system, and all of the state data associated with that user . . . . .  | 127 |
| <a href="#">UserAlertRequestModel</a>   | This model is a JSON representation of the request from User module . . . . .   | 131 |
| <a href="#">UserAlertService</a>        | Extends <a href="#">AlertService</a> and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy . . . . .   | 131 |
| <a href="#">UserFavoritesList</a>       | This class ties a userId to that user's ordered list of favorites . . . . .   | 133 |
| <a href="#">UserFavoritesRepository</a> | This class is responsible for handling database access for favorites, and to persist and retrieve <a href="#">UserFavoritesList</a> objects . . . . .   | 134 |
| <a href="#">UserFavoritesService</a>    | This is the generic BusBuddy <a href="#">UserFavoritesService</a> interface . . . . .   | 135 |
| <a href="#">UserInformation</a>         | <a href="#">UserInformation</a> contains the user related data that we get from User Module . . . . .   | 136 |
| <a href="#">UserLoginService</a>        | This is the generic BusBuddy <a href="#">UserLoginService</a> interface . . . . .   | 137 |
| <a href="#">UserManagementService</a>   | This is the generic BusBuddy <a href="#">UserManagementService</a> interface . . . . .  | 142 |
| <a href="#">UserRepository</a>          | This class is responsible for handling database access for <a href="#">User</a> objects, and to construct, persist, and retrieve <a href="#">User</a> objects . . . . .   | 147 |
| <a href="#">UserSessionInformation</a>  | A model that stores all the information needed to call user module about user information . . .   | 151 |
| <a href="#">UserTrackingAlertObject</a> | User tracking alert information obtained from the user interface when the user registers for an alert . . . . .   | 152 |
| <a href="#">UserType</a>                | This is an enumeration of the different statuses that a user can be assigned . . . . .  | 153 |
| <a href="#">VehicleObject</a>           | Value Object containing vehicle information obtained when the user registers a vehicle using the user interface . . . . .   | 154 |
| <a href="#">VehicleRepository</a>       | Repository for information on vehicles registered on a route . . . . .  | 155 |





## Chapter 4

# Namespace Documentation

### 4.1 Package alert.client

This package contains client layer classes that facilitates the call to other modules. We use client layer to communicate and gather information from external system.

#### Packages

- package [model](#)  
*This package contains model needed for client layer classes.*

#### Classes

- class [AlertUserClient](#)  
*Client layer will handle all the responsibility of sending request to other modules or external sources.*

#### 4.1.1 Detailed Description

This package contains client layer classes that facilitates the call to other modules. We use client layer to communicate and gather information from external system. This layer contains method that can make REST call to other modules and get back appropriate response. Currently, it is only making REST calls, but we can add new classes to make SOAP or any other type of external request. Hence, it abstracts the interaction with outer system and separates that concern to itself.

### 4.2 Package alert.client.model

This package contains model needed for client layer classes.

#### Classes

- class [UserInformation](#)  
*[UserInformation](#) contains the user related data that we get from User Module.*

#### 4.2.1 Detailed Description

This package contains model needed for client layer classes.

## 4.3 Package alert.controller

This package contains controller layer classes for Alert module which takes in REST request from external sources.

### Packages

- package [model](#)

*This package contains model needed for controller layer.*

### Classes

- class [AlertRequestController](#)

*This is a front facing controller that takes in request from other module via REST call and returns a JSON representation data.*

- class [CertificateHandler](#)

*A concrete strategy implementation of [ISessionHandler](#) that can verify the certificate token being passed.*

- interface [ISessionHandler](#)

*An interface to verify the validity of encrypted token being passed.*

- class [SessionTokenHandler](#)

*A concrete strategy implementation of [ISessionHandler](#) that can verify the session token being passed.*

- class [SessionVerificationFactory](#)

*A factory that picks the appropriate strategy [ISessionHandler](#) to verify the encrypted token.*

### 4.3.1 Detailed Description

This package contains controller layer classes for Alert module which takes in REST request from external sources. Controller acts like a facade to most of the modules as the methods are mapped to a certain URI. Other modules can call the REST interface and controller will handle the request. Also, controller handles the session verification depending upon type of encrypted token passed and provides the authorization and authentication. This is achieved by using factory and strategy pattern.

## 4.4 Package alert.controller.model

This package contains model needed for controller layer.

### Classes

- class [AlertRequestModel](#)

*A base model that contains bare minimum information about the alert request.*

- class [AlertResponseModel](#)

*This is a basic alert response model that is returned for every alert related requested.*

- class [TrackingAlertRequestModel](#)

*This model is a JSON representation of the request from Tracking module.*

- class [TransitAlertRequestModel](#)

*This model is a JSON representation of the request from Transit module.*

- class [UserAlertRequestModel](#)

*This model is a JSON representation of the request from User module.*

#### 4.4.1 Detailed Description

This package contains model needed for controller layer.

### 4.5 Package alert.domain

This package contains domain layer classes for Alert Module.

#### Packages

- package [model](#)

*This package contains entity and aggregate needed for domain layer in [Alert](#) Module.*

#### Classes

- class [AlertFactory](#)

*An alert factory that can create different types of semi-populated alert models depending upon the information.*

- class [AlertRepository](#)

*A Repository that handles the persistent behavior of the [Alert](#) aggregate.*

#### 4.5.1 Detailed Description

This package contains domain layer classes for Alert Module. Domain layer classes contains factory and repository that are responsible for handling the models lifecycle. Factory pattern is used to create different types of alert depending upon the parameter.

### 4.6 Package alert.domain.model

This package contains entity and aggregate needed for domain layer in [Alert](#) Module.

#### Classes

- class [Alert](#)

*This is a base [Alert](#) Model that has most of the common information about an [Alert](#).*

- class [OneTimeAlert](#)

*This is a model of alert that is to be run one time only.*

- class [RecurringAlert](#)

*This is a model of alert that is to be run multiple times.*

- class [RecurringData](#)

*This model holds the information about the date and time the alert needs to run.*

- class [TripInformation](#)

*This model stores the information about a trip as a value object.*

- class [UserSessionInformation](#)

*A model that stores all the information needed to call user module about user information.*

### 4.6.1 Detailed Description

This package contains entity and aggregate needed for domain layer in [Alert](#) Module. Domain layer models are database representation of the alert model. It contains a root aggregate through which we can enforce business rules and get access to information about its child objects. In the future, if we have to add more fields for alert we can probably implement bridge pattern to provide more flexible structure.

## 4.7 Package alert.enums

This package contains enums needed for Alert module.

### Classes

- enum [AlertInitiator](#)  
*A list of enums corresponding with modules that initiates the call.*
- enum [AlertNotificationType](#)  
*Notification type of alert,.*
- enum [AlertRecurringType](#)  
*Represents different recurring type of alert i.e., Yearly, Monthly, Weekly or Daily.*
- enum [AlertRunType](#)  
*Represents the type of alert depending upon the run type whether to run once or to run in a fixed recurring manner.*
- enum [AlertStatus](#)  
*Represents the status of an alert depending upon its state in its life cycle.*

### 4.7.1 Detailed Description

This package contains enums needed for Alert module.

## 4.8 Package alert.service

This package contains service layer classes needed for Alert Module.

### Classes

- class [AlertExecuteStrategyFactory](#)  
*This factory is going to pick the best available strategy to execute the alert so that the user can be notified.*
- class [AlertExecutionScheduler](#)  
*This is a background service that runs all the time.*
- class [AlertService](#)  
*Alert Service is a base class that is extended by other module specific services.*
- class [AlertServiceFactory](#)  
*[AlertServiceFactory](#) initializes appropriate alert service depending upon the parameter being passed.*
- interface [IAlertExecuteStrategy](#)  
*An interface for executing different type of alert based on alert type.*
- class [RouteAlertExecuteStrategy](#)  
*A concrete implementation of [IAlertExecuteStrategy](#) that handles executing alert related to route changes.*
- class [ScheduleAlertExecuteStrategy](#)  
*A concrete implementation of [IAlertExecuteStrategy](#) that handles executing alert related to user's regular schedule.*
- class [TrackingAlertService](#)

*Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.*

- class [TransitAlertService](#)

*Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.*

- class [UserAlertService](#)

*Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.*

#### 4.8.1 Detailed Description

This package contains service layer classes needed for Alert Module. Service layer handles the workflow and orchestrates the calls to process the request. Depending upon the modules initiating the call, service implementation can invoke factory method in domain layer to create alert and can manipulate its properties. Also service layer can execute the alert using different strategy. Service layer uses factory and strategy patterns to select appropriate service implementation and strategy type.

## 4.9 Package common

This package contains common BusBuddy objects and utilities to be used by all modules.

### Classes

- class [BaseController](#)

*This is a base class to be extended by each of the controller classes.*

- class [BusBuddyBadRequestException](#)

*This exception object represents internal errors which may occur as a result of an error in the client's request.*

- class [BusBuddyConflictException](#)

*This exception object is thrown when a request would create a conflict which violates constraints set within the system.*

- class [BusBuddyException](#)

*This exception object is an abstract base class.*

- class [BusBuddyForbiddenException](#)

*This exception object represents internal errors which may occur as a result of attempts to access a resource without authorization.*

- class [BusBuddyInternalException](#)

*This exception object represents internal errors which may occur, which are generally not due to the specifics of what appears to be a valid request.*

- class [BusBuddyNotFoundException](#)

*This exception object represents the error that occurs when a resource cannot be found.*

- class [HashUtility](#)

*This is a utility class to handle secure hashes.*

- class [MessageDeliveryUtility](#)

*This is a utility class to handle message delivery, such as through email or SMS.*

- interface [Specification< T >](#)

*A Generic Specification to be used for chaining business validation rules together.*

#### 4.9.1 Detailed Description

This package contains common BusBuddy objects and utilities to be used by all modules.

## 4.10 Package tracking

Tracking Module manages GPS vehicle tracking and alerting subscribed users based on vehicle location.

### Classes

- class [AlertRangeLogic](#)  
*Alert Range Logic implements the business logic to determine if a vehicle is within a range where an alert needs to be sent to a user who has registered for tracking alerts.*
- interface [AlertSpecification](#)  
*Interface for Alert Specifications which contain the business logic used to determine if an alert should be triggered for a vehicle.*
- enum [AlertType](#)  
*Enumeration of the alert types recognized by bus buddy.*
- class [BusVehicle](#)  
*Bus Vehicle is a concrete implementation of the abstract Transit Vehicle.*
- class [CommercialTracking](#)  
*Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from outside commercial tracking services.*
- class [DelayAlertLogic](#)  
*Implements the business logic to determine if the vehicle is behind schedule or not reporting GPS updates and send a notification to the transit company.*
- class [GPSLocationObject](#)  
*GPS Location is a value object used for GPS coordinates and the time of the last update.*
- class [GPSLocationObserver](#)  
*Observer Pattern - Observer interface for GPS location tracking.*
- class [GPSLocationTracking](#)  
*[GPSLocationTracking](#) - interface Subject of the Observer Pattern Defines methods for an observer GPS Device to register and receive updates on vehicle location.*
- class [GPSPuller](#)  
*GPS Puller is a concrete implementation of [GPSLocationTracking](#) for obtaining coordinates directly from a GPS device installed in a registered vehicle.*
- class [GPSPusher](#)  
*Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from registered vehicles.*
- class [GPSVehicleTracker](#)  
*Implementation of the Observer, update transit vehicle GPS location and time GPS Vehicle Tracker gets the state as new GPS coordinates and time from GPS Location Tracking and updates the transit vehicle.*
- interface [ITrackingService](#)  
*Interface for the Tracking Service Controller.*
- class [TrackingAlertFactory](#)  
*The Alert Factory handles the creation of a user alert.*
- class [TrackingAlertObserver](#)  
*Abstract class defining the methods for the tracking alert observer.*
- class [TrackingDelayAlert](#)  
*Tracking Alert Observer implements the abstract tracking alert observer and provides the method to actually send an alert to a registered user that their bus is approaching their stop.*
- class [TrackingLocationAlert](#)  
*Concrete implementation of the tracking alert observer.*
- class [TrackingResponseModel](#)  
*This is a basic tracking response model that is returned for every tracking related request.*
- class [TrackingServiceController](#)  
*Tracking service controller is the concrete implementation of the tracking service interface.*

- class [TransitVehicle](#)  
*Abstract transit vehicle class contains the common data for all types of vehicles and the Subject GPS Tracking and the GPS observer to receive GPS location updates.*
- class [TransitVehicleFactory](#)  
*Transit Vehicle Factory encapsulates the complexity of creating a new vehicle.*
- class [UserTrackingAlertObject](#)  
*User tracking alert information obtained from the user interface when the user registers for an alert.*
- class [VehicleObject](#)  
*Value Object containing vehicle information obtained when the user registers a vehicle using the user interface.*
- class [VehicleRepository](#)  
*Repository for information on vehicles registered on a route.*

#### 4.10.1 Detailed Description

Tracking Module manages GPS vehicle tracking and alerting subscribed users based on vehicle location. The Tracking Module handles the tracking GPS data from the transit vehicles and initiating alerts to users subscribed to route based messages and triggers transit vehicle delay alerts. The transit vehicle location data is also available to the Maps Module to place the bus icon at the correct position on maps.

## 4.11 Package transit

The Transit Module is an interface to get [Route/Fare/Detour](#) information from a [TransitProvider](#).

### Classes

- class [AbstractFeedParserTemplate](#)  
*A Template Method pattern to allow for the import of data from different [TransitProviders](#) in potentially different formats.*
- class [Detour](#)  
*A disruption in service due to an unexpected event.*
- class [Fare](#)  
*An immutable Value Object representing the cost, or 'fare,' required to ride a [TransitVehicle](#) on a particular [Route](#).*
- class [GoogleTransitServiceAdapter](#)  
*An Adapter Class to allow a [GoogleTransitServiceAPI](#) service to appear as a [TransitService](#).*
- interface [GoogleTransitServiceAPI](#)  
*A client to Google's [Maps API](#).*
- class [GTFSFeedParser](#)  
*A [AbstractFeedParserTemplate](#) implementation designed to parse [GTFS](#) format ZIP files into [Routes](#).*
- class [InvalidRouteParseException](#)  
*An [InvalidRouteParseException](#) indicates an invalid batch of parsed [Routes](#) has been detected.*
- class [ITeamTransitServiceController](#)  
*The iTeam implementation of the [TransitService](#) that exposes Transit data via a REST Service.*
- class [ITeamTripServiceController](#)  
*An iTeam implementation of the [TripService](#) that exposes [Trip](#) data via a REST Service.*
- class [Location](#)  
*An immutable Value Object representing a physical point on the geographic coordinate system.*
- class [PersistedTransitFeed](#)  
*An implementation of the [TransitFeed](#) interface that communicates with a [RouteRepository](#) to retrieve its data.*
- class [Route](#)  
*A [Route](#) is a [TransitVehicle](#) path of travel, or a "Line," as referred to by a [TransitProvider](#).*
- class [RouteDisruptionAlert](#)

- An Alert indicating a disruption of normal [Route](#) availability or scheduling.*

  - class [RouteDisruptionEvent](#)

*An event indicating a disruption in normal [Route](#) scheduling or service.*
  - interface [RouteRepository](#)

*A Repository Pattern supporting lifecycle operations of [Routes](#), such as Read, Save, Delete, and Query functionality.*
  - class [RouteSpecification](#)

*A Specification Pattern class for validating a [Route](#).*
  - class [Stop](#)

*A point on a [Route](#) in which a [TransitVehicle](#) will stop to pick up and drop off passengers.*
  - interface [TransitFeed](#)

*A [TransitFeed](#) is an abstraction over a service or set of services that provide information about [Routes](#).*
  - class [TransitInfo](#)

*An immutable Value Object describing metadata about a [TransitService](#).*
  - class [TransitProvider](#)

*A [TransitProvider](#) is a description of a company or organization that is the producer of public transportation services.*
  - interface [TransitProviderObserver](#)

*An asynchronous update interface for receiving notifications about [TransitProvider](#) [Route](#) disruptions.*
  - interface [TransitService](#)

*The [TransitService](#) is an interface to get [Route/Fare/Detour](#) information from a [TransitProvider](#).*
  - class [Trip](#)

*A [Trip](#) is considered an ordered collection of [Routes](#) going from a starting point to an ending point.*
  - interface [TripService](#)

*A Service to calculate a collection of [Routes](#), or a [Trip](#), allowing for a continuous transit path from a start [Location](#) to an end [Location](#).*

#### 4.11.1 Detailed Description

The Transit Module is an interface to get [Route/Fare/Detour](#) information from a [TransitProvider](#). The main module interface, the [TransitService](#), provides a consistent interface for the application logic to query for this information.

From a design perspective, there are two main tasks performed by the Transit Module: Consuming Transit Information from a [TransitProvider](#), and Providing Transit Information to [Users](#).

## 4.12 Package user

This package contains the objects used by the [User](#) Module of the BusBuddy application.

### Classes

- class [FavoriteTransitService](#)

*This class is a single transit service in a user's list of favorites.*
- class [ITeamUserFavoritesService](#)

*This is the iTeam's implementation of [UserFavoritesService](#).*
- class [ITeamUserLoginService](#)

*This is the iTeam's implementation of [UserLoginService](#).*
- class [ITeamUserManagementService](#)

*This is the iTeam's implementation of [UserManagementService](#).*
- class [Session](#)

*This class represents a single session for a user of the system, and all of the state data associated with that session.*
- class [SessionRepository](#)



*This class is responsible for handling database access for Sessions, and to construct, persist, and retrieve [Session](#) objects.*

- class [User](#)

*This class represents a single user of the system, and all of the state data associated with that user.*

- class [UserFavoritesList](#)

*This class ties a [userId](#) to that user's ordered list of favorites.*

- class [UserFavoritesRepository](#)

*This class is responsible for handling database access for favorites, and to persist and retrieve [UserFavoritesList](#) objects.*

- interface [UserFavoritesService](#)

*This is the generic BusBuddy [UserFavoritesService](#) interface.*

- interface [UserLoginService](#)

*This is the generic BusBuddy [UserLoginService](#) interface.*

- interface [UserManagementService](#)

*This is the generic BusBuddy [UserManagementService](#) interface.*

- class [UserRepository](#)

*This class is responsible for handling database access for [User](#) objects, and to construct, persist, and retrieve [User](#) objects.*

- enum [UserType](#)

*This is an enumeration of the different statuses that a user can be assigned.*

#### 4.12.1 Detailed Description

This package contains the objects used by the [User](#) Module of the BusBuddy application.




## Chapter 5

# Class Documentation

### 5.1 AbstractFeedParserTemplate Class Reference

A Template Method pattern to allow for the import of data from different [TransitProviders](#) in potentially different formats.

Inheritance diagram for AbstractFeedParserTemplate:



#### Public Member Functions

- [RouteRepository](#) **getRouteRepository** ()
- void **setRouteRepository** ([RouteRepository](#) routeRepository)
- Specification< [Route](#) > **getRouteSpecification** ()
- void **setRouteSpecification** (Specification< [Route](#) > routeSpecification)

#### Protected Member Functions

- void [start](#) (URL location) throws InvalidRouteParseException  
*The start method initiates the process and calls the appropriate methods in the appropriate order.*
- InputStream [loadFeed](#) (URL location)  
*Converts the resource URL into an InputStream for further processing.*
- abstract Set< [Route](#) > [parseFeed](#) (InputStream feed)  
*Parses the feed InputStream into a Set of Routes.*
- boolean [validate](#) ([Route](#) route)  
*Allow subclasses to validate Routes as they are parsed.*
- void [saveRoutes](#) (Set< [Route](#) > routes)  
*Save the Routes to the RouteRepository.*

#### Private Attributes

- [RouteRepository](#) routeRepository  
*The RouteRepository dependency allows for the persistence of the parsed Routes.*

- Specification< [Route](#) > [routeSpecification](#)

*This [Specification](#) allows subclasses to validate [Routes](#) as they are parsed.*

### 5.1.1 Detailed Description

A Template Method pattern to allow for the import of data from different [TransitProviders](#) in potentially different formats.

The algorithm sequence is as follows:

1. A [URL](#) of a resource location is passed into the [start](#) method. This method initiates the parsing/transformation process.
2. The [start](#) method calls the method [loadFeed](#) to establish the `InputStream`.
3. The `InputStream` returned by [loadFeed](#) is passed into the abstract [parseFeed](#) method. Subclasses will implement this as necessary to produce the resulting [Routes](#)
4. The newly created [Routes](#) are saved to the [RouteRepository](#) via the [saveRoutes](#) method.

### 5.1.2 Member Function Documentation

#### 5.1.2.1 `InputStream loadFeed ( URL location )` `[protected]`

Converts the resource URL into an `InputStream` for further processing.

##### Precondition

**location** exists and has been validated.

##### Parameters

|                 |                       |
|-----------------|-----------------------|
| <i>location</i> | The resource location |
|-----------------|-----------------------|

##### Returns

The resulting `InputStream`

#### 5.1.2.2 `abstract Set<Route> parseFeed ( InputStream feed )` `[protected]`, `[pure virtual]`

Parses the feed `InputStream` into a Set of [Routes](#).

Subclasses will implement this abstract method with the appropriate parsing logic for the particular input format.

##### Parameters

|             |                                       |
|-------------|---------------------------------------|
| <i>feed</i> | The resource <code>InputStream</code> |
|-------------|---------------------------------------|

##### Returns

The resulting Set of [Routes](#)

Implemented in [GTFSFeedParser](#).

### 5.1.2.3 void saveRoutes ( Set< Route > routes ) [protected]

Save the [Routes](#) to the [RouteRepository](#).

#### Precondition

**routes** may be an empty Set, but must not be null.

#### Parameters

|               |   |
|---------------|---|
| <i>routes</i> | The Set of <a href="#">Routes</a> to persist. |
|---------------|---|

### 5.1.2.4 void start ( URL location ) throws InvalidRouteParseException [protected]

The start method initiates the process and calls the appropriate methods in the appropriate order.

#### Exceptions

|  |   |
|--|---|
| <a href="#">InvalidRouteParseException</a> | if any of the parsed <a href="#">Routes</a> fail to validate via the given <a href="#">routeSpecification</a> . |
|--|---|

#### Parameters

|                 |  |
|-----------------|--|
| <i>location</i> | The input data resource location. This may be a local file or a remote resource. |
|-----------------|--|

### 5.1.2.5 boolean validate ( Route route ) [protected]

Allow subclasses to validate [Routes](#) as they are parsed.

Subclasses are encouraged to use this method

#### Parameters

|              |           |
|--------------|-----------|
| <i>route</i> | the route |
|--------------|-----------|


#### Returns

true, if successful

## 5.2 Alert Class Reference

This is a base [Alert](#) Model that has most of the common information about an [Alert](#).

Inheritance diagram for Alert:



## Public Member Functions

- String **getAlertGuid** ()
- void **setAlertGuid** (String [alertGuid](#))
- String **getDescription** ()
- void **setDescription** (String [description](#))
- Date **getCreatedDateTime** ()
- void **setCreatedDateTime** (Date [createdDateTime](#))
- Date **getStartDateTime** ()
- void **setStartDateTime** (Date [startDateTime](#))
- Date **getExpireDateTime** ()
- void **setExpireDateTime** (Date [expireDateTime](#))
- [AlertStatus](#) **getStatus** ()
- void **setStatus** ([AlertStatus](#) status)
- int **getErrorCount** ()
- void **setErrorCount** (int [errorCount](#))
- [AlertNotificationType](#) **getAlertType** ()
- void **setAlertType** ([AlertNotificationType](#) [alertType](#))
- [AlertRunType](#) **getAlertRunType** ()
- void **setAlertRunType** ([AlertRunType](#) [alertRunType](#))
- [UserInformation](#) **getUserInformation** ()
- void **setUserInformation** ([UserInformation](#) [userInformation](#))
- [TripInformation](#) **getTripInformation** ()
- void **setTripInformation** ([TripInformation](#) [tripInformation](#))
- [AlertInitiator](#) **getAlertInitiator** ()
- void **setAlertInitiator** ([AlertInitiator](#) [alertInitiator](#))

## Private Attributes

- String [alertGuid](#)  
*A unique identifier for [Alert](#).*
- String [description](#)  
*A text description about the alert that the user or other modules want to remember.*
- Date [createdDateTime](#)  
*DateTime that the alert was created.*
- Date [startDateTime](#)  
*DateTime that the alert should start running.*
- Date [expireDateTime](#)  
*DateTime that the alert would expire.*
- [AlertStatus](#) [Status](#)  
*current status of the alert.*
- int [errorCount](#)  
*Count of error occurrence when the alert was ran.*
- [AlertNotificationType](#) [alertType](#)  
*Notification type of alert.*
- [AlertRunType](#) [alertRunType](#)  
*Run type of alert e.g., one time or recurring.*
- [AlertInitiator](#) [alertInitiator](#)  
*Module that initiated or created this alert.*
- [UserInformation](#) [userInformation](#)  
*Information about the user if the alert is created by a dedicated user.*
- [TripInformation](#) [tripInformation](#)  
*A HashMap of.*

## Static Private Attributes

- static final long **serialVersionUID** = -5671884600600864426L

### 5.2.1 Detailed Description

This is a base [Alert](#) Model that has most of the common information about an [Alert](#).

[OneTimeAlert](#) and [RecurringAlert](#) extends this [Alert](#) Model. [Alert](#) can only be created from [AlertFactory](#) and then manipulated from [AlertRepository](#).

### 5.2.2 Member Data Documentation

#### 5.2.2.1 **AlertInitiator** alertInitiator [private]

Module that initiated or created this alert.

[AlertInitiator](#)

#### 5.2.2.2 **AlertRunType** alertRunType [private]

Run type of alert e.g., one time or recurring.

Value is defined by [AlertRunType](#)

#### 5.2.2.3 **AlertNotificationType** alertType [private]

Notification type of alert.

Depends upon the value as specified in [AlertNotificationType](#)

#### 5.2.2.4 **AlertStatus** status [private]

current status of the alert.

The value depends upon [AlertStatus](#) enum.

#### 5.2.2.5 **UserInfo** userInfo [private]

Information about the user if the alert is created by a dedicated user.

For any alerts generated by Transit or Tracking module, the user can either be admin of that module or the admin of the bus service provider. [UserInfo](#)

## 5.3 AlertExecuteStrategyFactory Class Reference

This factory is going to pick the best available strategy to execute the alert so that the user can be notified.

### Static Public Member Functions

- static [IAlertExecuteStrategy](#) **getAlertExecuteStrategy** ([Alert](#) alertModel)

*Based on the alertModel information, this method is going to pick the best strategy to send the alert.*

### 5.3.1 Detailed Description

This factory is going to pick the best available strategy to execute the alert so that the user can be notified.

### 5.3.2 Member Function Documentation

#### 5.3.2.1 `static IAlertExecuteStrategy getAlertExecuteStrategy ( Alert alertModel ) [static]`

Based on the alertModel information, this method is going to pick the best strategy to send the alert.

#### Parameters

|                   |  |
|-------------------|--|
| <i>alertModel</i> | <a href="#">Alert</a> model which is used to pick the best strategy. |
|-------------------|--|

#### Returns

An implementation of [IAlertExecuteStrategy](#) that can send the notification message for given alert.

## 5.4 AlertExecutionScheduler Class Reference

This is a background service that runs all the time.

### Public Member Functions

- void [runAlert](#) ()

*This method runs in fixed time interval indefinitely as long as program is alive.*

### Private Member Functions

- List< [AlertService](#) > [getAlertServices](#) ()

*Gets all the classes that extends the [AlertService](#) via reflection.*

### 5.4.1 Detailed Description

This is a background service that runs all the time.

The [runAlert\(\)](#) method is invoked in a fixed time interval which actually calls other methods and services to process the alert.

### 5.4.2 Member Function Documentation

#### 5.4.2.1 `List<AlertService> getAlertServices ( ) [private]`

Gets all the classes that extends the [AlertService](#) via reflection.

#### Returns

A list of classes extending [AlertService](#).



#### 5.4.2.2 void runAlert ( )

This method runs in fixed time interval indefinitely as long as program is alive.

It calls [getAlertServices\(\)](#) to get a list of classes that extend [AlertService](#). It then loops through those services to call [AlertService#sendAlert\(\)](#) to push notification to users preferred mode of communication.

## 5.5 AlertFactory Class Reference

An alert factory that can create different types of semi-populated alert models depending upon the information.

### Public Member Functions

- [Alert createAlert \(AlertRunType runType\)](#)  
*Creates an alert model depending upon the run Type.*
- [Alert createAlert \(AlertRecurringType recurringType\)](#)  
*Created alert model depending upon the recurringType.*

#### 5.5.1 Detailed Description

An alert factory that can create different types of semi-populated alert models depending upon the information.

Any additional create method can be created during implementation phase.

#### 5.5.2 Member Function Documentation

##### 5.5.2.1 Alert createAlert ( AlertRunType runType )

Creates an alert model depending upon the run Type.

###### Parameters

|                |                                    |
|----------------|------------------------------------|
| <i>runType</i> | <a href="#">AlertRunType</a> enum. |
|----------------|------------------------------------|

###### Returns

Either a Onetime or Recurring alert Model.

##### 5.5.2.2 Alert createAlert ( AlertRecurringType recurringType )

Created alert model depending upon the recurringType.

###### Parameters

|                      |   |
|----------------------|---|
| <i>recurringType</i> | <a href="#">AlertRecurringType</a> enum |
|----------------------|---|

#### Returns

A recurring alert Model

## 5.6 AlertInitiator Enum Reference

A list of enums corresponding with modules that initiates the call.

### Public Attributes

- [UserModule](#)  
*User module initiates the call.*
- [TrackingModule](#)  
*Tracking module initiates the call.*
- [TransitModule](#)  
*Transit module initiates the call.*

### 5.6.1 Detailed Description

A list of enums corresponding with modules that initiates the call.

## 5.7 AlertNotificationType Enum Reference

Notification type of alert,.

### Public Attributes

- [PlannedDisruption](#)  
*A planned alert that is to be run in the future.*
- [UnplannedDisruption](#)  
*A sudden change in route or plan can trigger this alert.*
- [ScheduleInformation](#)  
*A general type of alert where a user is to be notified of their schedule in a timely fashion.*

### 5.7.1 Detailed Description

Notification type of alert,.

### 5.7.2 Member Data Documentation

#### 5.7.2.1 PlannedDisruption

A planned alert that is to be run in the future.

Usually this is provided by Transit Module when the bus route is going to be changed in near future.

#### 5.7.2.2 ScheduleInformation

A general type of alert where a user is to be notified of their schedule in a timely fashion.

Generally, user module creates this type of alert.

### 5.7.2.3 UnplannedDisruption


A sudden change in route or plan can trigger this alert.

Usually this type of alert is executed right away. This type of alert is provided by either Transit or Tracking module.

## 5.8 AlertRangeLogic Class Reference

Alert Range Logic implements the business logic to determine if a vehicle is within a range where an alert needs to be sent to a user who has registered for tracking alerts.

Inheritance diagram for AlertRangeLogic:



### Public Member Functions

- boolean `inAlertRange` (`GPSLocationObject` vehicleLocation)

*Provides the logic necessary to determine from the GPS coordinates if the registered user should be alerted.*

### 5.8.1 Detailed Description

Alert Range Logic implements the business logic to determine if a vehicle is within a range where an alert needs to be sent to a user who has registered for tracking alerts.

This logic is designed to guarantee that an alert will be sent to the user before the vehicle has passes the desired stop. GPS coordinates are regularly updated, but not necessarily in real-time. BusBuddy needs to notify the user before the bus reaches the stop. An alert range is a distance range before the stop when the user should be notified.

## 5.9 AlertRecurringType Enum Reference

Represents different recurring type of alert i.e., Yearly, Monthly, Weekly or Daily.

### Public Attributes

- **Yearly**
- **Monthly**
- **Weekly**
- **Daily**

### 5.9.1 Detailed Description

Represents different recurring type of alert i.e., Yearly, Monthly, Weekly or Daily.

## 5.10 AlertRepository Class Reference

A Repository that handles the persistent behavior of the [Alert](#) aggregate.

### Public Member Functions

- [Alert](#) **saveAlert** ([Alert](#) alertModel)  
*This methods take an Alert and saves it to the database.*
- boolean **deleteAlert** ([Alert](#) alertModel)  
*This method deletes the alert that is being passed.*
- [Alert](#) **updateAlert** ([Alert](#) alertModel)  
*This method is used to update the alert with new information.*
- List< [Alert](#) > **getAlertByDateTime** (Date dateTimeToFetch, int offsetMinute)  
*This method fetches all the alerts that is to be run in next couple of minutes of given date and time.*
- List< [Alert](#) > **getAlertByRoute** (String routeld)  
*This method fetches all the alerts that is linked to the routeld.*
- List< [Alert](#) > **getAlertByUserId** (String userId)  
*This method fetches all the alerts that is tied to a user.*

### 5.10.1 Detailed Description

A Repository that handles the persistent behavior of the [Alert](#) aggregate.

It has methods that can alter the lifecycle of the aggregate.

### 5.10.2 Member Function Documentation

#### 5.10.2.1 boolean deleteAlert ( [Alert](#) alertModel )

This method deletes the alert that is being passed.

##### Precondition

the alertModel being passed at least needs to have an ID defined.

##### Postcondition

the alert will be removed from the system and can no longer be accessed.

##### Parameters

|                   |  |
|-------------------|--|
| <i>alertModel</i> | The <a href="#">Alert</a> model that is to be deleted. |
|-------------------|--|

##### Returns

A boolean to indicate whether the delete was success or not.

#### 5.10.2.2 List<[Alert](#)> getAlertByDateTime ( Date dateTimeToFetch, int offsetMinute )

This method fetches all the alerts that is to be run in next couple of minutes of given date and time.

e.g., if DateTime is NOW and offset is 5 minutes. Then it fetches all the alerts that is to be run in next 5 minutes.

## Parameters

|                        |   |
|------------------------|---|
| <i>dateTimeToFetch</i> | DateTime when the alert is supposed to run.                             |
| <i>offsetMinute</i>    | An int value that is used to fetch alerts within that minute in future. |

## Returns

Returns a list of [Alert](#) models that is to be run in next couple of minutes (offsetMinute) of given date time.

**5.10.2.3 List<Alert> getAlertByRoute ( String routeId )**

This method fetches all the alerts that is linked to the routeId.

## Parameters

|                |                                      |
|----------------|--------------------------------------|
| <i>routeId</i> | The route ID that is being affected. |
|----------------|--------------------------------------|

## Returns

A list of [Alert](#) models.

**5.10.2.4 List<Alert> getAlertByUserId ( String userId )**

This method fetches all the alerts that is tied to a user.

## Parameters

|               |                               |
|---------------|-------------------------------|
| <i>userId</i> | userId that is being affected |
|---------------|-------------------------------|

## Returns

A list of [Alert](#) models.

**5.10.2.5 Alert saveAlert ( Alert alertModel )**

This methods take an Alert and saves it to the database.

## Parameters

|                   |   |
|-------------------|---|
| <i>alertModel</i> | <a href="#">Alert</a> model to be saved |
|-------------------|---|

## Returns

The saved object with updated property.

Save the alert via Hibernate.

**5.10.2.6 Alert updateAlert ( Alert alertModel )**

This method is used to update the alert with new information.

**Precondition**

the alert must exist in the system.

**Parameters**

|                   |  |
|-------------------|--|
| <i>alertModel</i> | A <a href="#">Alert</a> model that needs to be updated |
|-------------------|--|

**Returns**

Returns the updated [Alert](#) model back to the method that is calling.

## 5.11 AlertRequestController Class Reference

This is a front facing controller that takes in request from other module via REST call and returns a JSON representation data.

**Public Member Functions**

- [AlertResponseModel](#) [processUserAlertRequest](#) ([UserAlertRequestModel](#) userAlertRequest, String encryptedToken)  
*Processes Alert manipulation request from User module.*
- [AlertResponseModel](#) [processTransitAlertRequest](#) ([TransitAlertRequestModel](#) transitAlertRequest, String encryptedToken)  
*Processes Alert manipulation request from Transit module.*
- [AlertResponseModel](#) [processTrackingAlertRequest](#) ([TrackingAlertRequestModel](#) trackingAlertRequest, String encryptedToken)  
*Processes Alert manipulation request from Tracking module.*

**Private Member Functions**

- void [verifySession](#) ([AlertRequestModel](#) requestModel, String encryptedToken)  
*Method to verify the validity of session token being passed.*

**Private Attributes**

- [SessionVerificationFactory](#) [sessionVerificationFactory](#)  
*Session Verification Factory picks the appropriate type of session verification strategy depending upon which module is initiating the call.*

### 5.11.1 Detailed Description

This is a front facing controller that takes in request from other module via REST call and returns a JSON representation data.

User module calls the alert module to create new alert, delete alert, update alert or to get a list of alert for a user. Transit module can call alert module to create, delete and update a new alert. Tracking module can call alert module to create a new alert. As far as public facing end points go, we have implemented one endpoint for each module. During implementation there might be different GET, POST, PUT and DELETE methods. But for now, we are putting only one method per module as a placeholder assuming that it can take different actions depending upon the information in the [AlertRequestModel](#).

## 5.11.2 Member Function Documentation

### 5.11.2.1 **AlertResponseModel** processTrackingAlertRequest ( **TrackingAlertRequestModel** *trackingAlertRequest*, **String** *encryptedToken* )

Processes Alert manipulation request from Tracking module.

#### Parameters

|                              |   |
|------------------------------|---|
| <i>trackingAlert-Request</i> | { |
|------------------------------|---|

#### See Also

TrackingAlertRequestModel}

#### Parameters

|                       |   |
|-----------------------|---|
| <i>encryptedToken</i> | An encrypted token that can be validated. |
|-----------------------|---|

#### Returns

An [AlertResponseModel](#) that has the success/error information.

### 5.11.2.2 **AlertResponseModel** processTransitAlertRequest ( **TransitAlertRequestModel** *transitAlertRequest*, **String** *encryptedToken* )

Processes Alert manipulation request from Transit module.

#### Parameters

|                             |   |
|-----------------------------|---|
| <i>transitAlert-Request</i> | { |
|-----------------------------|---|

#### See Also

TransitAlertRequestModel}

#### Parameters

|                       |   |
|-----------------------|---|
| <i>encryptedToken</i> | <ul style="list-style-type: none"><li>• An encrypted token that can be validated.</li></ul> |
|-----------------------|---|

#### Returns

An [AlertResponseModel](#) that has the success/error information.

### 5.11.2.3 **AlertResponseModel** processUserAlertRequest ( **UserAlertRequestModel** *userAlertRequest*, **String** *encryptedToken* )

Processes Alert manipulation request from User module.

## Parameters

|                          |   |
|--------------------------|---|
| <i>userAlert-Request</i> | An alertRequestModel that has the necessary information regarding creation of an alert. { |
|--------------------------|---|

## See Also

UserAlertRequestModel}

## Parameters

|                       |   |
|-----------------------|---|
| <i>encryptedToken</i> | An encrypted token that can be validated. |
|-----------------------|---|

## Returns

An [AlertResponseModel](#) that has the success/error information.

5.11.2.4 void verifySession ( [AlertRequestModel](#) requestModel, String encryptedToken ) [private]

Method to verify the validity of session token being passed.

If token verification fails, it automatically throws an error the request is terminated.


## Parameters

|                       |  |
|-----------------------|--|
| <i>requestModel</i>   | An object representation of JSON that has the request. |
| <i>encryptedToken</i> | An encrypted token that can be validated.              |

## 5.12 AlertRequestModel Class Reference

A base model that contains bare minimum information about the alert request.

Inheritance diagram for AlertRequestModel:



### Public Member Functions

- [AlertInitiator](#) **getAlertInitiator** ()
- void **setAlertInitiator** ([AlertInitiator](#) alertInitiator)

### Private Attributes

- [AlertInitiator](#) alertInitiator  
Alert Initiator {.

#### 5.12.1 Detailed Description

A base model that contains bare minimum information about the alert request.



Any model that extends this class can add additional data that is needed.

### 5.12.2 Member Data Documentation

#### 5.12.2.1 AlertInitiator alertInitiator [private]

Alert Initiator {.

See Also

AlertInitiator}.

## 5.13 AlertResponseModel Class Reference

This is a basic alert response model that is returned for every alert related requested.

### Private Attributes

- String [status](#)  
*Status message for the alert process job.*
- String [errorMessage](#)  
*Any error message if the alert request fails.*

### 5.13.1 Detailed Description

This is a basic alert response model that is returned for every alert related requested.

Additional fields can be added as needed during implementation phase.

## 5.14 AlertRunType Enum Reference

Represents the type of alert depending upon the run type whether to run once or to run in a fixed recurring manner.

### Public Attributes

- **Onetime**
- **Recurring**

### 5.14.1 Detailed Description


Represents the type of alert depending upon the run type whether to run once or to run in a fixed recurring manner.

OneTime Alert runs only once and is then deactivated. Recurring Alert runs in every certain amount of time depending upon the parameter defined.

## 5.15 AlertService Class Reference

Alert Service is a base class that is extended by other module specific services.

Inheritance diagram for AlertService:



## Public Member Functions

- [AlertResponseModel saveAlert](#) ([Alert](#) alertModel)  
*Takes in an [Alert](#) model to persist it into db.*
- [AlertResponseModel deleteAlert](#) ([Alert](#) alertModel)  
*Takes in an [Alert](#) Model for deletion.*
- abstract boolean [sendAlert](#) ()  
*Finds all the alerts that are initiated by this service and calls [AlertExecuteStrategyFactory](#) to find appropriate strategy to send each type of alert.*

## Protected Member Functions

- abstract [AlertResponseModel createAlert](#) ([AlertRequestModel](#) requestModel)  
*An abstract class that must be implemented by derived classes to create a new alert model.*
- abstract [AlertResponseModel updateAlert](#) ([Alert](#) alertModel)  
*Takes in a final [Alert](#) Model that needs to be updated in db.*

## Protected Attributes

- [AlertExecuteStrategyFactory](#) alertExecuteStrategyFactory  
{
- [AlertRepository](#) alertRepository  
{
- [AlertFactory](#) alertFactory  
{

### 5.15.1 Detailed Description

Alert Service is a base class that is extended by other module specific services.

This abstract class defines signature for basic CRUD operation.

### 5.15.2 Member Function Documentation

#### 5.15.2.1 abstract [AlertResponseModel createAlert](#) ( [AlertRequestModel](#) *requestModel* ) [protected], [pure virtual]

An abstract class that must be implemented by derived classes to create a new alert model.

#### Precondition

An [AlertRequest](#) model must be supplied that must have necessary information to create an alert

#### Parameters

|                     |  |
|---------------------|--|
| <i>requestModel</i> | A <a href="#">AlertResponseModel</a> that has necessary information to create a new alert model. |
|---------------------|--|

**Returns**

Returns an [AlertReponseModel](#) that contains information needed by the caller.

Implemented in [TrackingAlertService](#), [TransitAlertService](#), and [UserAlertService](#).

**5.15.2.2 AlertResponseModel deleteAlert ( Alert *alertModel* )**

Takes in an Alert Model for deletion.

**Parameters**

|                   |                                     |
|-------------------|-------------------------------------|
| <i>alertModel</i> | A valid <a href="#">Alert</a> model |
|-------------------|-------------------------------------|

**Returns**

An [AlertResponseModel](#) that has the success or error message.

**5.15.2.3 AlertResponseModel saveAlert ( Alert *alertModel* )**

Takes in an [Alert](#) model to persist it into db.

**Parameters**

|                   |                                     |
|-------------------|-------------------------------------|
| <i>alertModel</i> | A valid <a href="#">Alert</a> model |
|-------------------|-------------------------------------|

**Returns**

An [AlertResponseModel](#) that has the success or error message.

**5.15.2.4 abstract boolean sendAlert ( ) [pure virtual]**

Finds all the alerts that are initiated by this service and calls [AlertExecuteStrategyFactory](#) to find appropriate strategy to send each type of alert.

1. Get all the alerts created by this service/module.
2. Loop through each one of them and call appropriate strategy via StrategyFactory
3. Use execute method in strategy to push notification

**Returns**

Implemented in [TrackingAlertService](#), [TransitAlertService](#), and [UserAlertService](#).

**5.15.2.5 abstract AlertResponseModel updateAlert ( Alert *alertModel* ) [protected],[pure virtual]**

Takes in a final Alert Model that needs to be updated in db.

**Parameters**

|                   |                                     |
|-------------------|-------------------------------------|
| <i>alertModel</i> | A valid <a href="#">Alert</a> model |
|-------------------|-------------------------------------|

#### Returns

An [AlertResponseModel](#) that has the success or error message.

Implemented in [TrackingAlertService](#), [TransitAlertService](#), and [UserAlertService](#).

### 5.15.3 Member Data Documentation

#### 5.15.3.1 [AlertExecuteStrategyFactory](#) `alertExecuteStrategyFactory` [protected]

{

#### See Also

[AlertExecuteStrategyFactory](#). This is autowired via Spring Framework.

#### 5.15.3.2 [AlertFactory](#) `alertFactory` [protected]

{

#### See Also

[AlertFactory](#). This is autowired via Spring framework.

#### 5.15.3.3 [AlertRepository](#) `alertRepository` [protected]

{

#### See Also

[AlertRepository](#). This is autowired via Spring Framework.

## 5.16 [AlertServiceFactory](#) Class Reference

[AlertServiceFactory](#) initializes appropriate alert service depending upon the parameter being passed.

### Public Member Functions

- [AlertService](#) `getAlertService` ([AlertRequestModel](#) requestModel)  
*This method returns a concrete implementation of the alert service.*

### Private Attributes

- [UserAlertService](#) `userAlertService`  
{
- [TrackingAlertService](#) `trackingAlertService`  
{
- [TransitAlertService](#) `transitAlertService`  
{

### 5.16.1 Detailed Description

[AlertServiceFactory](#) initializes appropriate alert service depending upon the parameter being passed.

Currently, each module is aligned to each service but in the future it could change such that 2 module can use same service.

### 5.16.2 Member Function Documentation

#### 5.16.2.1 `AlertService` `getAlertService ( AlertRequestModel requestModel )`

This method returns a concrete implementation of the alert service.

##### Parameters

|                           |   |
|---------------------------|---|
| <code>requestModel</code> | A JSON representation of the request from controller. |
|---------------------------|---|

##### Returns

An extension of [AlertService](#).

thrown an error if applicable.

### 5.16.3 Member Data Documentation

#### 5.16.3.1 `TrackingAlertService` `trackingAlertService` [private]

{

##### See Also

[TrackingAlertService](#)}. This is autowired via Spring Framework.

#### 5.16.3.2 `TransitAlertService` `transitAlertService` [private]

{

##### See Also

[TransitAlertService](#)}. This is autowired via Spring Framework.

#### 5.16.3.3 `UserAlertService` `userAlertService` [private]

{


##### See Also

[UserAlertService](#)}. This is autowired via Spring Framework.

## 5.17 AlertSpecification Interface Reference

Interface for Alert Specifications which contain the business logic used to determine if an alert should be triggered for a vehicle.

Inheritance diagram for AlertSpecification:



## Public Member Functions

- boolean [inAlertRange](#) ([GPSLocationObject](#) vehicleLocation)  
*Compare GPS location and time with alert information to determine if vehicle is within range of a stop and user(s) need to be notified.*

### 5.17.1 Detailed Description

Interface for Alert Specifications which contain the business logic used to determine if an alert should be triggered for a vehicle.

Alert specifications are referenced in the vehicle tracking observer and used by the subject to determine when to send an alert. This is to reduce the number of false positive alerts.

### 5.17.2 Member Function Documentation

#### 5.17.2.1 boolean inAlertRange ( [GPSLocationObject](#) *vehicleLocation* )

Compare GPS location and time with alert information to determine if vehicle is within range of a stop and user(s) need to be notified.

#### Parameters

|                        |  |
|------------------------|--|
| <i>lastUpdateTime</i>  | - Time GPS information was last updated          |
| <i>vehicleLocation</i> | - Latest GPS coordinates obtained from a vehicle |

#### Returns

true if vehicle is in alert range, false if vehicle is not in alert range

Implemented in [AlertRangeLogic](#), and [DelayAlertLogic](#).

## 5.18 AlertStatus Enum Reference

Represents the status of an alert depending upon its state in its life cycle.

### Public Attributes

- [Active](#)  
*Represents an alert that is active and is ready to be run when time comes.*
- [Deactive](#)  
*Represents an alert that is in dormant state and wont run even if its time parameter is valid.*
- [Running](#)  
*Represents an alert that is in running state.*

- [Expired](#)

*Represents an alert that is expired.*

- [Error](#)

*Represents an alert that is in error state due to technical difficulties.*

### 5.18.1 Detailed Description

Represents the status of an alert depending upon its state in its life cycle.

### 5.18.2 Member Data Documentation

#### 5.18.2.1 Deactive

Represents an alert that is in dormant state and wont run even if its time parameter is valid.

Usually alert canbe in this status if it is paused.

#### 5.18.2.2 Error

Represents an alert that is in error state due to technical difficulties.

This alert will be run 3 times before it is permanently paused until further action from user or admin.

#### 5.18.2.3 Expired

Represents an alert that is expired.

This type of alert are deleted periodically.

## 5.19 AlertType Enum Reference

Enumeration of the alert types recognized by bus buddy.

### Public Attributes

- **LOCATION**
- **DELAY**

### 5.19.1 Detailed Description

Enumeration of the alert types recognized by bus buddy.

Bus Buddy can then use a configuration file to tie the alert type to the [AlertSpecification](#) to determine the logic necessary to determine if users registered to a vehicle should be sent alerts.

## 5.20 AlertUserClient Class Reference

Client layer will handle all the responsibility of sending request to other modules or external sources.

## Public Member Functions

- [UserInformation getUserInformation](#) (String *userId*, String *sessionToken*)  
*Calls User module to get User information for a particular user such as their contact preference via a REST call.*
- boolean [verifySessionToken](#) (String *sessionToken*)  
*Calls the user module to verify the authenticity of session token being passed.*

## Package Attributes

- String [userModuleURL](#)  
*A user module url that is used to make a REST call to get users information This information is saved in a config file that is retrieved via Spring's Resource annotation.*

### 5.20.1 Detailed Description

Client layer will handle all the responsibility of sending request to other modules or external sources.

This particular client class will handle request to User module to get necessary user information.

### 5.20.2 Member Function Documentation

#### 5.20.2.1 [UserInformation getUserInformation](#) ( String *userId*, String *sessionToken* )

Calls User module to get User information for a particular user such as their contact preference via a REST call.

##### Parameters

|                     |   |
|---------------------|---|
| <i>userId</i>       | User ID of the user that should receive the alert.  |
| <i>sessionToken</i> | Valid long lived session token that can be used to get information about a particular user. |

##### Returns

A [UserInformation](#) that contains user data.

gets the user information from the user module via REST call

#### 5.20.2.2 boolean [verifySessionToken](#) ( String *sessionToken* )

Calls the user module to verify the authenticity of session token being passed.

##### Parameters

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | An encrypted token that needs to be validated. |
|---------------------|--|

##### Returns


A boolean flag indicating the authenticity of the session token.

## 5.21 BaseController Class Reference

This is a base class to be extended by each of the controller classes.

Inheritance diagram for BaseController:





## Public Member Functions

- `ResponseEntity<String> handleBusBuddyException (BusBuddyException e)`  
*This method handles cases where [BusBuddyException](#) is thrown from controller methods.*
- `ResponseEntity<String> handleGenericException (BusBuddyException e)`  
*This method handles cases where a generic Exception is thrown from controller methods (other than [BusBuddyException](#)).*

### 5.21.1 Detailed Description

This is a base class to be extended by each of the controller classes.

This provides a means to handle exceptions that need to be thrown back up to the user. It could be modified to add other common logic that apply to multiple controllers.

### 5.21.2 Member Function Documentation

#### 5.21.2.1 `ResponseEntity<String> handleBusBuddyException ( BusBuddyException e )`

This method handles cases where [BusBuddyException](#) is thrown from controller methods.

It will format the exception for the user, and return the correct HTTP status code, based on the code stored within the exception.

##### Parameters

|                |                            |
|----------------|----------------------------|
| <code>e</code> | exception which was thrown |
|----------------|----------------------------|

##### Returns

ResponseEntity object

#### 5.21.2.2 `ResponseEntity<String> handleGenericException ( BusBuddyException e )`

This method handles cases where a generic Exception is thrown from controller methods (other than [BusBuddyException](#)).

It will format the exception for the user, and return a generic HTTP 500. Since handled exceptions should result in a [BusBuddyException](#), if this happens, it is unexpected behavior and should be treated as an internal error.

##### Parameters

|                |                            |
|----------------|----------------------------|
| <code>e</code> | exception which was thrown |
|----------------|----------------------------|


##### Returns

ResponseEntity object

## 5.22 BusBuddyBadRequestException Class Reference

This exception object represents internal errors which may occur as a result of an error in the client's request.

Inheritance diagram for BusBuddyBadRequestException:



### Public Member Functions

- **BusBuddyBadRequestException** (String message)
- **BusBuddyBadRequestException** (Throwable cause)
- **BusBuddyBadRequestException** (String message, Throwable cause)
- HttpStatus [getHttpCode](#) ()

*This method returns the HTTP status code associated with this exception.*

### Static Private Attributes

- static final long **serialVersionUID** = -597422588227245539L

### Additional Inherited Members

#### 5.22.1 Detailed Description

This exception object represents internal errors which may occur as a result of an error in the client's request.

#### 5.22.2 Member Function Documentation

##### 5.22.2.1 HttpStatus [getHttpCode](#) ( ) [virtual]

This method returns the HTTP status code associated with this exception.

#### Returns


HTTP 400 Bad Request

Implements [BusBuddyException](#).

## 5.23 BusBuddyConflictException Class Reference

This exception object is thrown when a request would create a conflict which violates constraints set within the system.

Inheritance diagram for BusBuddyConflictException:



## Public Member Functions

- **BusBuddyConflictException** (String message)
- **BusBuddyConflictException** (Throwable cause)
- **BusBuddyConflictException** (String message, Throwable cause)
- HttpStatus [getHttpCode](#) ()

*This method returns the HTTP status code associated with this exception.*

## Static Private Attributes

- static final long **serialVersionUID** = -2044397352042431762L

## Additional Inherited Members

### 5.23.1 Detailed Description

This exception object is thrown when a request would create a conflict which violates constraints set within the system.

### 5.23.2 Member Function Documentation

#### 5.23.2.1 HttpStatus [getHttpCode](#) ( ) [virtual]

This method returns the HTTP status code associated with this exception.

#### Returns


HTTP 409 Conflict

Implements [BusBuddyException](#).

## 5.24 BusBuddyException Class Reference

This exception object is an abstract base class.

Inheritance diagram for BusBuddyException:



## Protected Member Functions

- **BusBuddyException** (String message)
- **BusBuddyException** (Throwable cause)
- **BusBuddyException** (String message, Throwable cause)
- abstract HttpStatus [getHttpCode](#) ()

*This method returns a Spring HTTP status code object representing the HTTP status code tied to this exception.*

## Static Private Attributes

- static final long **serialVersionUID** = 5906063726935813830L

### 5.24.1 Detailed Description

This exception object is an abstract base class.

Other exceptions within the BusBuddy application will extend this class. This provides a common base for all application exceptions.

### 5.24.2 Member Function Documentation

#### 5.24.2.1 abstract HttpStatus [getHttpCode](#) ( ) [protected], [pure virtual]

This method returns a Spring HTTP status code object representing the HTTP status code tied to this exception.

#### Returns


HTTP Status Code object

Implemented in [BusBuddyConflictException](#), [BusBuddyForbiddenException](#), [BusBuddyInternalException](#), [BusBuddyBadRequestException](#), and [BusBuddyNotFoundException](#).

## 5.25 BusBuddyForbiddenException Class Reference

This exception object represents internal errors which may occur as a result of attempts to access a resource without authorization.

Inheritance diagram for BusBuddyForbiddenException:



## Public Member Functions

- **BusBuddyForbiddenException** (String message)
- **BusBuddyForbiddenException** (Throwable cause)
- **BusBuddyForbiddenException** (String message, Throwable cause)
- HttpStatus [getHttpCode](#) ()

*This method returns the HTTP status code associated with this exception.*

## Static Private Attributes

- static final long **serialVersionUID** = -4463973248172436949L

## Additional Inherited Members

### 5.25.1 Detailed Description

This exception object represents internal errors which may occur as a result of attempts to access a resource without authorization.

### 5.25.2 Member Function Documentation

#### 5.25.2.1 HttpStatus getHttpCode ( ) [virtual]

This method returns the HTTP status code associated with this exception.

#### Returns


HTTP 403 Forbidden

Implements [BusBuddyException](#).

## 5.26 BusBuddyInternalException Class Reference

This exception object represents internal errors which may occur, which are generally not due to the specifics of what appears to be a valid request.

Inheritance diagram for BusBuddyInternalException:



## Public Member Functions

- **BusBuddyInternalException** (String message)
- **BusBuddyInternalException** (Throwable cause)
- **BusBuddyInternalException** (String message, Throwable cause)
- HttpStatus [getHttpCode](#) ( )

*This method returns the HTTP status code associated with this exception.*

## Static Private Attributes

- static final long **serialVersionUID** = 4549592428602851924L

## Additional Inherited Members

### 5.26.1 Detailed Description

This exception object represents internal errors which may occur, which are generally not due to the specifics of what appears to be a valid request.

### 5.26.2 Member Function Documentation

#### 5.26.2.1 `HttpStatus getHttpCode ( )` [virtual]

This method returns the HTTP status code associated with this exception.

#### Returns


HTTP 500 Internal Server Error

Implements [BusBuddyException](#).

## 5.27 BusBuddyNotFoundException Class Reference

This exception object represents the error that occurs when a resource cannot be found.

Inheritance diagram for BusBuddyNotFoundException:



## Public Member Functions

- **BusBuddyNotFoundException** (String message)
- **BusBuddyNotFoundException** (Throwable cause)
- **BusBuddyNotFoundException** (String message, Throwable cause)
- HttpStatus [getHttpCode](#) ( )

*This method returns the HTTP status code associated with this exception.*

## Static Private Attributes

- static final long **serialVersionUID** = -5490492502661128777L

## Additional Inherited Members

### 5.27.1 Detailed Description

This exception object represents the error that occurs when a resource cannot be found.

## 5.27.2 Member Function Documentation

### 5.27.2.1 HttpStatus getHttpCode ( ) [virtual]

This method returns the HTTP status code associated with this exception.

#### Returns


HTTP 404 Not Found

Implements [BusBuddyException](#).

## 5.28 BusVehicle Class Reference

Bus Vehicle is a concrete implementation of the abstract Transit Vehicle.

Inheritance diagram for BusVehicle:



### Public Member Functions

- [BusVehicle](#) ()  
*Constructor for bus type vehicles, perform any initializations unique to buses.*
- void [registerTrackingAlert](#) ([TrackingAlertObserver](#) ao)  
*Register any user alerts for this vehicle.*
- void [unregisterTrackingAlert](#) ([TrackingAlertObserver](#) ao)  
*Unregister any user alert currently tracking this bus.*
- void [checkForAlerts](#) ()  
*When the bus GPS position is updated, determine if any user alerts need to be sent.*

### Private Attributes

- `ArrayList< TrackingAlertObserver > alertList`  
*List of alerts registered for this vehicle.*

## 5.28.1 Detailed Description

Bus Vehicle is a concrete implementation of the abstract Transit Vehicle.

Contains data and functionality specific to buses.

## 5.28.2 Member Data Documentation

### 5.28.2.1 ArrayList<TrackingAlertObserver> alertList [private]


List of alerts registered for this vehicle.

Note alerts may be tracking or delay alerts

## 5.29 CertificateHandler Class Reference

A concrete strategy implementation of [ISessionHandler](#) that can verify the certificate token being passed.

Inheritance diagram for CertificateHandler:



### Public Member Functions

- boolean [verifySessionToken](#) (String sessionToken) throws **BusBuddyForbiddenException**  
*This method takes in an encrypted certificate from Tracking and Transit module in a form of string and then validates for its authenticity.*

#### 5.29.1 Detailed Description

A concrete strategy implementation of [ISessionHandler](#) that can verify the certificate token being passed.

#### 5.29.2 Member Function Documentation

##### 5.29.2.1 boolean verifySessionToken ( String sessionToken ) throws **BusBuddyForbiddenException**

This method takes in an encrypted certificate from Tracking and Transit module in a form of string and then validates for its authenticity.

#### Exceptions


|                                   |  |
|-----------------------------------|--|
| <i>BusBuddyForbiddenException</i> | Throws an exception when the token is not valid. |
|-----------------------------------|--|

Implements [ISessionHandler](#).

## 5.30 CommercialTracking Class Reference

Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from outside commercial tracking services.

Inheritance diagram for CommercialTracking:



### Classes

- class [CommercialTrackingHolder](#)



*Commercial Tracking Holder is loaded on the first execution of [CommercialTracking.getInstance\(\)](#) or the first access to `CommercialTracking.INSTANCE`, not before (lazy instantiation).*

### Protected Member Functions

- void [registerGPSDevice](#) ([GPSLocationObserver](#) gpsObs)  
*Register a GPS Device to the list to poll for updates.*
- void [unregisterGPSDevice](#) ([GPSLocationObserver](#) gpsObs)  
*Remove a GPS device from the list currently being polled for updates.*
- void [pollGPSDevice](#) ()  
*Continuously poll the registered GPS devices for location updates.*

### Static Protected Member Functions

- static [CommercialTracking](#) [getInstance](#) ()  
*Instantiates a single Commercial Tracking service to the caller.*

### Private Member Functions

- [CommercialTracking](#) ()  
*Only need one Commercial Tracking Service running to track by polling all registered GPS devices.*

### Private Attributes

- ArrayList< [GPSLocationObserver](#) > [gpsObserver](#)  
*Array list of GPS devices registered for updates.*

#### 5.30.1 Detailed Description

Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from outside commercial tracking services.

#### Postcondition

New GPS commercial tracker created or existing one returned.

#### 5.30.2 Constructor & Destructor Documentation

##### 5.30.2.1 [CommercialTracking](#) ( ) [private]

Only need one Commercial Tracking Service running to track by polling all registered GPS devices.

Constructor, creates ArrayList<[GPSLocationObserver](#)> to hold registered observers.

#### 5.30.3 Member Function Documentation

##### 5.30.3.1 static [CommercialTracking](#) [getInstance](#) ( ) [static], [protected]

Instantiates a single Commercial Tracking service to the caller.

#### Returns

- [CommercialTracking](#) instance

## 5.31 CommercialTracking.CommercialTrackingHolder Class Reference

Commercial Tracking Holder is loaded on the first execution of [CommercialTracking.getInstance\(\)](#) or the first access to `CommercialTracking.INSTANCE`, not before (lazy instantiation).

### Static Public Attributes

- static final [CommercialTracking](#) **INSTANCE** = new [CommercialTracking](#)()


#### 5.31.1 Detailed Description

Commercial Tracking Holder is loaded on the first execution of [CommercialTracking.getInstance\(\)](#) or the first access to `CommercialTracking.INSTANCE`, not before (lazy instantiation).

## 5.32 DelayAlertLogic Class Reference

Implements the business logic to determine if the vehicle is behind schedule or not reporting GPS updates and send a notification to the transit company.

Inheritance diagram for DelayAlertLogic:



### Public Member Functions

- boolean [inAlertRange](#) ([GPSLocationObject](#) vehicleLocation)  
*Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from outside commercial tracking services.*

#### 5.32.1 Detailed Description

Implements the business logic to determine if the vehicle is behind schedule or not reporting GPS updates and send a notification to the transit company.

## 5.33 Detour Class Reference

A disruption in service due to an unexpected event.

### Public Member Functions

- [Detour](#) (String [detourId](#), String [cause](#), int [estimatedDelay](#), Set< [Stop](#) > [affectedStops](#))  
*Instantiates a new [Detour](#) with all required fields.*
- String [getCause](#) ()
- void [setCause](#) (String [cause](#))
- int [getEstimatedDelay](#) ()

- void **setEstimatedDelay** (int [estimatedDelay](#))
- Set< [Stop](#) > **getAffectedStops** ()
- void **setAffectedStops** (Set< [Stop](#) > [affectedStops](#))
- String **getDetourId** ()
- void **setDetourId** (String [detourId](#))

### Private Attributes

- String [detourId](#)  
*A unique identifier for this [Detour](#).*
- String [cause](#)  
*A text-based description of the cause of the [Detour](#), intended to be displayed to customers.*
- int [estimatedDelay](#)  
*The estimated time (in minutes) that each of the [Stops](#) in the.*
- Set< [Stop](#) > [affectedStops](#)  
*All [Stops](#) that are subject to the noted [estimatedDelay](#).*

### 5.33.1 Detailed Description

A disruption in service due to an unexpected event.

A [Detour](#) may not affect all [Stops](#) in a [Route](#), as a [Detour](#) may only alter portions of the [Route](#). Any affected [Stop](#) will be listed in the [affectedStops](#) attribute.

### 5.33.2 Constructor & Destructor Documentation

#### 5.33.2.1 [Detour](#) ( String [detourId](#), String [cause](#), int [estimatedDelay](#), Set< [Stop](#) > [affectedStops](#) )

Instantiates a new [Detour](#) with all required fields.

#### Precondition

**estimatedDelay** >= 0  
**affectedStops.size()** > 0

#### Parameters

|                                       |  |
|---------------------------------------|--|
| <i><a href="#">detourId</a></i>       | The <a href="#">Detour</a> id  |
| <i><a href="#">cause</a></i>          | The cause (a short, informative description) of the reason for the disruption. |
| <i><a href="#">estimatedDelay</a></i> | The estimated delay (in minutes)   |
| <i><a href="#">affectedStops</a></i>  | The affected <a href="#">Stops</a>   |

### 5.33.3 Member Data Documentation

#### 5.33.3.1 String [cause](#) [private]

A text-based description of the cause of the [Detour](#), intended to be displayed to customers.

If null or blank, the cause is considered Unspecified or Unknown.

#### 5.33.3.2 String [detourId](#) [private]

A unique identifier for this [Detour](#).

This is not intended to be human-readable and can be generated.

As a [Detour](#) is part of the [Route](#) Aggregate, this identifier needs only be unique within the context of a [Route](#).

#### 5.33.3.3 `int estimatedDelay` [`private`]

The estimated time (in minutes) that each of the [Stops](#) in the [affectedStops](#) will be delayed.

## 5.34 Fare Class Reference

An immutable Value Object representing the cost, or 'fare,' required to ride a [TransitVehicle](#) on a particular [Route](#).

### Public Member Functions

- [Fare](#) (BigDecimal [regularFare](#))  
*Instantiates a new [Fare](#) with a regular fare and no discounted fair.*
- [Fare](#) (BigDecimal [regularFare](#), BigDecimal [discountedFare](#))  
*Instantiates a new [Fare](#) with both a regular fare and a discounted fare.*
- BigDecimal **getRegularFare** ()
- void **setRegularFare** (BigDecimal [regularFare](#))
- BigDecimal **getDiscountedFare** ()
- void **setDiscountedFare** (BigDecimal [discountedFare](#))

### Private Attributes

- BigDecimal [regularFare](#)  
*The normally applied fare.*
- BigDecimal [discountedFare](#)  
*A discounted fare for children, elderly, holidays, or other adjustment criteria as supplied by the [TransitProvider](#).*

#### 5.34.1 Detailed Description

An immutable Value Object representing the cost, or 'fare,' required to ride a [TransitVehicle](#) on a particular [Route](#).

Although BusBuddy does not specify explicit rules governing the [regularFare](#) and the [discountedFare](#), each [Transit-Provider](#) must publicly state its [Fare](#) policies on a website or other public forum.

#### Invariant

if [discountedFare](#) exists, [discountedFare](#) <= [regularFare](#)

#### 5.34.2 Constructor & Destructor Documentation

##### 5.34.2.1 `Fare` ( BigDecimal *regularFare* )

Instantiates a new [Fare](#) with a regular fare and no discounted fair.

#### Precondition

**regularFare** >= 0

## Parameters

|                    |                                  |
|--------------------|----------------------------------|
| <i>regularFare</i> | The Regular <a href="#">Fare</a> |
|--------------------|----------------------------------|

5.34.2.2 Fare ( BigDecimal *regularFare*, BigDecimal *discountedFare* )

Instantiates a new [Fare](#) with both a regular fare and a discounted fare.

## Precondition

**regularFare** >= 0  
**discountedFare** >= 0  
**discountedFare** <= **discountedFare**

## Parameters

|                       |                                     |
|-----------------------|-------------------------------------|
| <i>regularFare</i>    | The Regular <a href="#">Fare</a>    |
| <i>discountedFare</i> | The Discounted <a href="#">Fare</a> |

## 5.34.3 Member Function Documentation

5.34.3.1 void setDiscountedFare ( BigDecimal *discountedFare* )

## Precondition

**discountedFare** >= 0 AND **discountedFare** <= [regularFare](#) if [regularFare](#) exists.

5.34.3.2 void setRegularFare ( BigDecimal *regularFare* )

## Precondition

**regularFare** >= 0

## 5.34.4 Member Data Documentation

5.34.4.1 BigDecimal *discountedFare* [private]

A discounted fare for children, elderly, holidays, or other adjustment criteria as supplied by the [TransitProvider](#).

This is optional. [TransitProviders](#) are not required to provide discounted Fares for any reason.

## 5.35 FavoriteTransitService Class Reference

This class is a single transit service in a user's list of favorites.

## Public Member Functions

- [FavoriteTransitService](#) (String *transitServiceUrl*)  
*This creates a new favorites entry.*
- String [getTransitServiceUrl](#) ()  
*This retrieves the transit service URL associated with the transit service represented by this object.*
- boolean [isFavoriteTransitService](#) ()  
*This retrieves whether this transit service itself is a favorite.*

- void [setFavoriteTransitService](#) (boolean favoriteTransitService)  
*This sets whether this transit service itself is a favorite.*
- List< String > [getFavoriteRoutelds](#) ()  
*This retrieves the ordered list of favorite routes for this transit service.*
- void [setFavoriteRoutelds](#) (List< String > favoriteRoutelds)  
*This sets the ordered list of favorite routes for this transit service.*

## Private Attributes

- final String **transitServiceUrl**
- boolean **favoriteTransitService**
- List< String > **favoriteRoutelds**

### 5.35.1 Detailed Description

This class is a single transit service in a user's list of favorites.

If just the routes are favorites, and not the service, then the favoriteTransitService boolean can be set to false. Likewise, if just the transit service is a favorite, and there are no favorite routes, the list of favorite routes can be empty.

### 5.35.2 Constructor & Destructor Documentation

#### 5.35.2.1 FavoriteTransitService ( String transitServiceUrl )

This creates a new favorites entry.

Once created, the service URL cannot be changed.

#### Parameters

|                          |   |
|--------------------------|---|
| <i>transitServiceUrl</i> | URL to the transit service represented by this object |
|--------------------------|---|

### 5.35.3 Member Function Documentation

#### 5.35.3.1 List<String> getFavoriteRoutelds ( )

This retrieves the ordered list of favorite routes for this transit service.

#### Returns

ordered list of favorite route IDs

#### 5.35.3.2 String getTransitServiceUrl ( )

This retrieves the transit service URL associated with the transit service represented by this object.

#### Returns

transit service URL

#### 5.35.3.3 boolean isFavoriteTransitService ( )

This retrieves whether this transit service itself is a favorite.

## Returns

true if it is, false if it is just a container object for favorite routes

## 5.35.3.4 void setFavoriteRouteIds ( List&lt; String &gt; favoriteRouteIds )

This sets the ordered list of favorite routes for this transit service.

## Parameters

|                         |                                    |
|-------------------------|------------------------------------|
| <i>favoriteRouteIds</i> | ordered list of favorite route IDs |
|-------------------------|------------------------------------|

## 5.35.3.5 void setFavoriteTransitService ( boolean favoriteTransitService )

This sets whether this transit service itself is a favorite.


## Parameters

|                                |   |
|--------------------------------|---|
| <i>favoriteTransit-Service</i> | true if it is, false if it is just a container object for favorite routes |
|--------------------------------|---|

## 5.36 GoogleTransitServiceAdapter Class Reference

An Adapter Class to allow a [GoogleTransitServiceAPI](#) service to appear as a [TransitService](#).

Inheritance diagram for GoogleTransitServiceAdapter:



### Public Member Functions

- [GoogleTransitServiceAdapter](#) ([GoogleTransitServiceAPI](#) googleTransitServiceAPI)  
*Instantiates a new [GoogleTransitServiceAdapter](#) with a [GoogleTransitServiceAPI](#) to delegate calls to.*
- [Route](#) getRoute (String routeId)  
*Gets a [Route](#) by its unique identifier.*
- Set< [Route](#) > getRoutes ([Location](#) pickup, [Location](#) dropoff, int distance)  
*Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.*
- [GoogleTransitServiceAPI](#) getGoogleTransitServiceAPI ()
- void setGoogleTransitServiceAPI ([GoogleTransitServiceAPI](#) googleTransitServiceAPI)

### Private Attributes

- [GoogleTransitServiceAPI](#) googleTransitServiceAPI  
*The [GoogleTransitServiceAPI](#) to adapt as a [TransitService](#).*

#### 5.36.1 Detailed Description

An Adapter Class to allow a [GoogleTransitServiceAPI](#) service to appear as a [TransitService](#).

## 5.36.2 Constructor & Destructor Documentation

### 5.36.2.1 GoogleTransitServiceAdapter ( GoogleTransitServiceAPI *googleTransitServiceAPI* )

Instantiates a new [GoogleTransitServiceAdapter](#) with a [GoogleTransitServiceAPI](#) to delegate calls to.

#### Parameters

|                                |   |
|--------------------------------|---|
| <i>googleTransitServiceAPI</i> | The <a href="#">GoogleTransitServiceAPI</a> to adapt. |
|--------------------------------|---|

## 5.36.3 Member Function Documentation

### 5.36.3.1 Route getRoute ( String *routeId* )

Gets a [Route](#) by its unique identifier.

#### Precondition

**routeId** is not null or blank.

#### Postcondition

The [Route](#) is returned if the **routeId** is found, else null.

#### Parameters

|                |  |
|----------------|--|
| <i>routeId</i> | The unique identifier of the <a href="#">Route</a> |
|----------------|--|

#### Returns

The matching [Route](#), or null if not found

Implements [TransitFeed](#).

### 5.36.3.2 Set<Route> getRoutes ( Location *pickup*, Location *dropoff*, int *distance* )

Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.

#### Precondition

**pickup** is not null or blank.

**dropoff** is not null or blank.

**distance** is non-negative.

#### Parameters

|                 |  |
|-----------------|--|
| <i>pickup</i>   | The requested pickup <a href="#">Location</a>  |
| <i>dropoff</i>  | The requested dropoff <a href="#">Location</a>   |
| <i>distance</i> | The distance (in miles) that each <a href="#">Route</a> can deviate from the requested <b>pickup</b> or <b>dropoff</b> <a href="#">Location</a> . For each <a href="#">Route</a> returned, neither its start or end <a href="#">Location</a> can differ from the requested <b>pickup</b> or <b>dropoff</b> <a href="#">Location</a> by more than the value of the <b>distance</b> parameter. |



**Returns**

The matching [Routes](#)

Implements [TransitFeed](#).

## 5.37 GoogleTransitServiceAPI Interface Reference

A client to Google's [Maps API](#).

### 5.37.1 Detailed Description

A client to Google's [Maps API](#).

Note: Actual design of the appropriate interfaces in this class are deferred to implementation teams or a further phase of design.

## 5.38 GPSLocationObject Class Reference

GPS Location is a value object used for GPS coordinates and the time of the last update.

### Public Member Functions

- double **getLatitude** ()
- void **setLatitude** (double [latitude](#))
- double **getLongitude** ()
- void **setLongitude** (double [longitude](#))
- Date **getLastUpdateTime** ()
- void **setLastUpdateTime** (Date [lastUpdateTime](#))

### Private Attributes

- double [latitude](#)  
*current GPS latitude*
- double [longitude](#)  
*current GPS longitude*
- Date [lastUpdateTime](#)  
*time of last GPS update from device*


### 5.38.1 Detailed Description

GPS Location is a value object used for GPS coordinates and the time of the last update.

## 5.39 GPSLocationObserver Class Reference

Observer Pattern - Observer interface for GPS location tracking.

Inheritance diagram for GPSLocationObserver:



## Protected Member Functions

- void [setGPSLocation](#) ([GPSLocationObject](#) gpsLocation)  
*Set the current GPS location of a vehicle (state).*

## Protected Attributes

- [GPSLocationTracking](#) gpsDevice  
*Observer Pattern Subject.*
- int [gpsID](#)  
*GPS Device ID being tracked.*
- [GPSLocationObject](#) gpsLocation  
*Current GPS latitude and longitude from GPS tracker.*

## Package Functions

- abstract void [gpsUpdate](#) (int [gpsID](#), [GPSLocationObject](#) newLocation)  
*Observer Pattern update method to update transit vehicle GPS location.*
- [GPSLocationObject](#) [getGPSLocation](#) ()  
*Return current GPS location received from a vehicle.*

### 5.39.1 Detailed Description

Observer Pattern - Observer interface for GPS location tracking.

### 5.39.2 Member Function Documentation

#### 5.39.2.1 [GPSLocationObject](#) [getGPSLocation](#) ( ) [package]

Return current GPS location received from a vehicle.

This is the state of the observer pattern.

#### Returns

- Location

#### 5.39.2.2 abstract void [gpsUpdate](#) ( int [gpsID](#), [GPSLocationObject](#) *newLocation* ) [package],[pure virtual]

Observer Pattern update method to update transit vehicle GPS location.

#### Parameters

|                  |   |
|------------------|---|
| <i>gpsID</i>     | - integer device ID from the GPS unit being tracked |
| <i>latitude</i>  | - double new latitude from GPS device               |
| <i>longitude</i> | - double new longitude from GPS device              |

Implemented in [GPSVehicleTracker](#).

5.39.2.3 `void setGPSLocation ( GPSTrackingObject gpsLocation )` [protected]

Set the current GPS location of a vehicle (state).


#### Parameters

|                    |   |
|--------------------|---|
| <i>gpsLocation</i> | - Location latest latitude and longitude of vehicle |
|--------------------|---|

## 5.40 GPSTracking Class Reference

[GPSTracking](#) - interface Subject of the Observer Pattern Defines methods for an observer GPS Device to register and receive updates on vehicle location.

Inheritance diagram for GPSTracking:



### Package Functions

- abstract void [registerGPSDevice](#) ([GPSTrackingObserver](#) gpsObs)  
*registerGPSDevice* - register a GPS device with the Location Tracking Service
- abstract void [unregisterGPSDevice](#) ([GPSTrackingObserver](#) gpsObs)  
*unregisterGPSDevice* - remove a vehicle from list.
- abstract void [pollGPSDevice](#) ()  
*pollGPSDevice* - continuously poll registered GPS Devices for location updates

### 5.40.1 Detailed Description

[GPSTracking](#) - interface Subject of the Observer Pattern Defines methods for an observer GPS Device to register and receive updates on vehicle location.

### 5.40.2 Member Function Documentation

5.40.2.1 `abstract void registerGPSDevice ( GPSTrackingObserver gpsObs )` [package], [pure virtual]

`registerGPSDevice` - register a GPS device with the Location Tracking Service

#### Parameters

|                                     |  |
|-------------------------------------|--|
| <a href="#">GPSTrackingObserver</a> | - Vehicle location to notify when new vehicle GPS location is received |
|-------------------------------------|--|

Implemented in [GPSPusher](#), [CommercialTracking](#), and [GPSPuller](#).

5.40.2.2 **abstract void unregisterGPSDevice ( [GPSLocationObserver](#) *gpsObs* )** [package],[pure virtual]

unregisterGPSDevice - remove a vehicle from list.

Stop updating vehicle location.

#### Parameters


|               |  |
|---------------|--|
| <i>gpsObs</i> | <a href="#">GPSLocationObserver</a> - vehicle to remove from notification list |
|---------------|--|

Implemented in [GPSPusher](#), [CommercialTracking](#), and [GPSPuller](#).

## 5.41 GPSPuller Class Reference

GPS Puller is a concrete implementation of [GPSLocationTracking](#) for obtaining coordinates directly from a GPS device installed in a registered vehicle.

Inheritance diagram for GPSPuller:



### Classes

- class [GPSPullerHolder](#)  
*GPS Puller Holder is loaded on the first execution of GPSPuller.getInstance() or the first access to GPSPuller.INSTANCE, not before (lazy instantiation).*

### Package Functions

- void [registerGPSDevice](#) ([GPSLocationObserver](#) *gpsObs*)  
*Register a GPS Device to the list to poll for updates.*
- void [unregisterGPSDevice](#) ([GPSLocationObserver](#) *gpsObs*)  
*Remove a GPS device from the list currently being polled for updates.*
- void [pollGPSDevice](#) ()  
*Continuously poll the registered GPS devices for location updates.*

### Static Package Functions

- static [GPSPuller](#) **getInstance** ()

### Private Member Functions

- [GPSPuller](#) ()  
*Only need one GPS Puller Service running to track by polling all registered GPS devices.*

### Private Attributes

- ArrayList< [GPSLocationObserver](#) > *gpsObserver*  
*Array list of GPS devices registered for updates.*

### 5.41.1 Detailed Description

GPS Puller is a concrete implementation of [GPSLocationTracking](#) for obtaining coordinates directly from a GPS device installed in a registered vehicle.

GPS Puller is implemented as a singleton to limit the number of system resources consumed. GPS Puller uses the system infrastructure to establish a wireless network connection to the physical GPS device and retrieve update coordinates. The necessary information to contact the device is provided through the user interface when a vehicle is registered to a route.

#### Postcondition

New GPS Puller created if one did not previously exist.

### 5.41.2 Constructor & Destructor Documentation

#### 5.41.2.1 GPSPuller ( ) [private]

Only need one GPS Puller Service running to track by polling all registered GPS devices.

Constructor, creates ArrayList<[GPSLocationObserver](#)> to hold registered observers.

## 5.42 GPSPuller.GPSPullerHolder Class Reference

GPS Puller Holder is loaded on the first execution of [GPSPuller.getInstance\(\)](#) or the first access to [GPSPuller.INSTANCE](#), not before (lazy instantiation).

#### Static Public Attributes

- static final [GPSPuller](#) **INSTANCE** = new [GPSPuller](#)()


### 5.42.1 Detailed Description

GPS Puller Holder is loaded on the first execution of [GPSPuller.getInstance\(\)](#) or the first access to [GPSPuller.INSTANCE](#), not before (lazy instantiation).

## 5.43 GPSPusher Class Reference

Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from registered vehicles.

Inheritance diagram for GPSPusher:



#### Classes

- class [GPSPusherHolder](#)

*GPS Pusher Holder is loaded on the first execution of [GPSPusher.getInstance\(\)](#) or the first access to [GPSPusher.INSTANCE](#), not before (lazy instantiation).*

## Public Member Functions

- void [registerGPSDevice](#) ([GPSLocationObserver](#) gpsObs)  
*Register a GPS Device to the list to poll for updates.*
- void [unregisterGPSDevice](#) ([GPSLocationObserver](#) gpsObs)  
*Remove a GPS device from the list currently being polled for updates.*
- void [pollGPSDevice](#) ()  
*Continuously poll the registered GPS devices for location updates.*

## Static Public Member Functions

- static [GPSPusher](#) [getInstance](#) ()  
*Create a single instance of the GPS Listener for receiving GPS updates from devices that periodically push updated directly from the device.*

## Private Member Functions

- [GPSPusher](#) ()  
*Only need one GPS Pusher Service running to track by polling all registered GPS devices.*

## Private Attributes

- ArrayList< [GPSLocationObserver](#) > [gpsObserver](#)  
*Array list of GPS devices registered for updates.*

### 5.43.1 Detailed Description

Implements Subject [GPSLocationTracking](#) for retrieving GPS location updates from registered vehicles.

[GPSPusher](#) uses system infrastructure resources to set up a network listener to receive updates directly from the GPS device. GPS Pusher is implemented as a singleton to limit the number of system resources consumed. GPS Pusher receives the necessary configuration information (e.g. port) from the user interface when the GPS device is registered.

#### Postcondition

New GPS Listener created if none existed previously.

### 5.43.2 Constructor & Destructor Documentation

#### 5.43.2.1 [GPSPusher](#) ( ) [private]

Only need one GPS Pusher Service running to track by polling all registered GPS devices.

Constructor, creates ArrayList<[GPSLocationObserver](#)> to hold registered observers. < List of GPS devices currently registered and waiting for updates

### 5.43.3 Member Function Documentation

#### 5.43.3.1 static [GPSPusher](#) [getInstance](#) ( ) [static]

Create a single instance of the GPS Listener for receiving GPS updates from devices that periodically push updated directly from the device.

**Returns**

[GPSPusher](#) reference to the listener for incoming GPS updates from registered devices.

**5.44 GPSPusher.GPSPusherHolder Class Reference**

GPS Pusher Holder is loaded on the first execution of [GPSPusher.getInstance\(\)](#) or the first access to GPSPusher.-INSTANCE, not before (lazy instantiation).

**Static Public Attributes**

- static final [GPSPusher](#) **INSTANCE** = new [GPSPusher](#)()


**5.44.1 Detailed Description**

GPS Pusher Holder is loaded on the first execution of [GPSPusher.getInstance\(\)](#) or the first access to GPSPusher.-INSTANCE, not before (lazy instantiation).

**5.45 GPSVehicleTracker Class Reference**

Implementation of the Observer, update transit vehicle GPS location and time GPS Vehicle Tracker gets the state as new GPS coordinates and time from GPS Location Tracking and updates the transit vehicle.

Inheritance diagram for GPSVehicleTracker:

**Public Member Functions**

- [GPSVehicleTracker](#) ([GPSLocationTracking](#) gpsDevice)  
*Register the Transit Vehicle GPS device with GPS location tracking.*
- void [gpsUpdate](#) (int [gpsID](#), [GPSLocationObject](#) newLocation)  
*Notify method to get the new GPS coordinates from GPS location tracking.*

**Additional Inherited Members****5.45.1 Detailed Description**

Implementation of the Observer, update transit vehicle GPS location and time GPS Vehicle Tracker gets the state as new GPS coordinates and time from GPS Location Tracking and updates the transit vehicle.

**Postcondition**

Transit Vehicle GPS location updated.

## 5.45.2 Constructor & Destructor Documentation

### 5.45.2.1 GPSVehicleTracker ( GPSLocationTracking *gpsDevice* )

Register the Transit Vehicle GPS device with GPS location tracking.


#### Parameters

|                  |  |
|------------------|--|
| <i>gpsDevice</i> | - <a href="#">GPSLocationTracking</a> Subject being observed |
|------------------|--|

## 5.46 GTFSFeedParser Class Reference

A [AbstractFeedParserTemplate](#) implementation designed to parse [GTFS](#) format ZIP files into [Routes](#).

Inheritance diagram for GTFSFeedParser:



### Protected Member Functions

- Set< [Route](#) > [parseFeed](#) (InputStream feed)  
*Parse the [GTFS](#) format ZIP files into [Routes](#).*

### Additional Inherited Members

#### 5.46.1 Detailed Description

A [AbstractFeedParserTemplate](#) implementation designed to parse [GTFS](#) format ZIP files into [Routes](#).

#### 5.46.2 Member Function Documentation

##### 5.46.2.1 Set<Route> parseFeed ( InputStream *feed* ) [protected],[virtual]

Parse the [GTFS](#) format ZIP files into [Routes](#).

#### See Also

[AbstractFeedParserTemplate::parseFeed](#)

Implements [AbstractFeedParserTemplate](#).

## 5.47 HashUtility Class Reference

This is a utility class to handle secure hashes.



## Static Public Member Functions

- static String [hash](#) (String input)

*This is a method that will take an input string, securely hash it, and return the hashed String using the SHA-512 algorithm.*

### 5.47.1 Detailed Description

This is a utility class to handle secure hashes.

### 5.47.2 Member Function Documentation

#### 5.47.2.1 static String hash ( String input ) [static]

This is a method that will take an input string, securely hash it, and return the hashed String using the SHA-512 algorithm.

#### Parameters


|              |  |
|--------------|--|
| <i>input</i> |  |
|--------------|--|

#### Returns

## 5.48 IAlertExecuteStrategy Interface Reference

An interface for executing different type of alert based on alert type.

Inheritance diagram for IAlertExecuteStrategy:



## Public Member Functions

- boolean [execute](#) ([Alert](#) alertModel)

*A method that executes alert passed in based on the type of alert.*

### 5.48.1 Detailed Description

An interface for executing different type of alert based on alert type.

Each implementation of this interface will apply their own execute method that can send alert based on user, route etc.

### 5.48.2 Member Function Documentation

#### 5.48.2.1 boolean execute ( [Alert](#) *alertModel* )

A method that executes alert passed in based on the type of alert.

##### Parameters

|                   |   |
|-------------------|---|
| <i>alertModel</i> | An <a href="#">Alert</a> model fetched from database. |
|-------------------|---|

##### Returns


A boolean indicating if overall process complete successfully.

Implemented in [RouteAlertExecuteStrategy](#), and [ScheduleAlertExecuteStrategy](#).

## 5.49 InvalidRouteParseException Class Reference

An [InvalidRouteParseException](#) indicates an invalid batch of parsed [Routes](#) has been detected.

Inheritance diagram for InvalidRouteParseException:



### Public Member Functions

- Set< [Route](#) > **getRouteBatch** ()
- void **setRouteBatch** (Set< [Route](#) > *routeBatch*)

### Protected Member Functions

- [InvalidRouteParseException](#) (Set< [Route](#) > *routeBatch*)  
*Instantiates a new invalid route parse exception.*

### Private Attributes

- Set< [Route](#) > *routeBatch*  
*The failed [Route](#) batch.*

### Static Private Attributes

- static final long [serialVersionUID](#) = -4399874766965916500L  
*The Constant serialVersionUID.*

#### 5.49.1 Detailed Description

An [InvalidRouteParseException](#) indicates an invalid batch of parsed [Routes](#) has been detected.

Note that one or more of the referenced [Routes](#) are invalid, but not necessarily all of them are invalid.

## 5.49.2 Constructor & Destructor Documentation

### 5.49.2.1 InvalidRouteParseException ( Set< Route > routeBatch ) [protected]

Instantiates a new invalid route parse exception.

#### Parameters

|                   |                 |
|-------------------|-----------------|
| <i>routeBatch</i> | the route batch |
|-------------------|-----------------|

## 5.49.3 Member Data Documentation

### 5.49.3.1 Set<Route> routeBatch [private]

The failed [Route](#) batch.

Handlers of this Exception may choose to re-validate, fix, and/or retry the operation with an adjusted batch.


### 5.49.3.2 final long serialVersionUID = -4399874766965916500L [static], [private]

The Constant serialVersionUID.

## 5.50 ISessionHandler Interface Reference

An interface to verify the validity of encrypted token being passed.

Inheritance diagram for ISessionHandler:



## Public Member Functions

- boolean [verifySessionToken](#) (String encryptedToken) throws BusBuddyForbiddenException  
*This method takes in an encrypted token in a form of string and then validates for its authenticity.*

## 5.50.1 Detailed Description

An interface to verify the validity of encrypted token being passed.

The implementation of this interface must decrypt the session token or certificate and then verify it.

## 5.50.2 Member Function Documentation

### 5.50.2.1 boolean verifySessionToken ( String encryptedToken ) throws BusBuddyForbiddenException

This method takes in an encrypted token in a form of string and then validates for its authenticity.

## Parameters

|                       |  |
|-----------------------|--|
| <i>encryptedToken</i> | <ul style="list-style-type: none"> <li>An encrypted string.</li> </ul> |
|-----------------------|--|

## Returns

A boolean indicating whether the token was valid or not.

## Exceptions


|                                   |  |
|-----------------------------------|--|
| <i>BusBuddyForbiddenException</i> | <ul style="list-style-type: none"> <li>Throws an exception when the token is not valid.</li> </ul> |
|-----------------------------------|--|

Implemented in [SessionTokenHandler](#), and [CertificateHandler](#).

## 5.51 ITeamTransitServiceController Class Reference

The iTeam implementation of the [TransitService](#) that exposes Transit data via a REST Service.

Inheritance diagram for ITeamTransitServiceController:



### Public Member Functions

- void [handleRouteDisruptionEvent](#) ([RouteDisruptionEvent](#) routeDisruptionEvent)  
After a [RouteDisruptionEvent](#) is received, this class will perform the following:
- [Route](#) [getRoute](#) (String routeId)  
Gets a [Route](#) by its unique identifier.
- Set< [Route](#) > [getRoutes](#) ([Location](#) pickup, [Location](#) dropoff, int distance)  
Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.
- [TransitInfo](#) [getTransitInfo](#) ()  
Gets metadata about the Transit Authority providing the information retrieved from this service.
- URL [getServiceURL](#) ()  
The URL that uniquely identifies this [TransitService](#).
- [TransitFeed](#) [getTransitFeed](#) ()
- void [setTransitFeed](#) ([TransitFeed](#) transitFeed)
- [AlertRequestController](#) [getAlertRequestController](#) ()
- void [setAlertRequestController](#) ([AlertRequestController](#) alertRequestController)

### Private Attributes

- [TransitFeed](#) transitFeed  
The [TransitFeed](#) used to provide data to this [TransitService](#) implementation.
- [AlertRequestController](#) alertRequestController  
The inter-module dependency to the Alert Module.

### 5.51.1 Detailed Description

The iTeam implementation of the [TransitService](#) that exposes Transit data via a REST Service.

Note that this is intended to receive and respond to HTTP requests via JSON. The actual Object -> JSON transformation, as well as the specification of HTTP REST URLs is left to the development phase and is not specified here.

Errors should be communicated via standard HTTP error codes. The [BaseController](#) will be responsible for mapping Exception types to HTTP error codes, so actual error codes are not specified explicitly here.

### 5.51.2 Member Function Documentation

#### 5.51.2.1 Route `getRoute ( String routeId )`

Gets a [Route](#) by its unique identifier.

##### Parameters

|                |  |
|----------------|--|
| <i>routeId</i> | The unique identifier of the <a href="#">Route</a> |
|----------------|--|

##### Returns

The matching [Route](#)

##### Precondition

**routeId** is not null or blank.

##### Postcondition

The [Route](#) is returned if the **routeId** is found, else null.

##### Exceptions

|                                   |   |
|-----------------------------------|---|
| <i>BusBuddyNotFound-Exception</i> | Thrown if the <a href="#">Route</a> with the given <b>routeId</b> is not found. |
|-----------------------------------|---|

Implements [TransitService](#).

#### 5.51.2.2 Set<[Route](#)> `getRoutes ( Location pickup, Location dropoff, int distance )`

Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.

##### Parameters

|                 |  |
|-----------------|--|
| <i>pickup</i>   | The requested dropoff <a href="#">Location</a>   |
| <i>dropoff</i>  | the dropoff  |
| <i>distance</i> | The distance (in miles) that each <a href="#">Route</a> can deviate from the requested <b>pickup</b> or <b>dropoff</b> |

##### Returns

The matching [Routes](#)

**Precondition**

**pickup** is not null or blank.

**dropoff** is not null or blank.

**distance** is non-negative. [Location](#). For each [Route](#) returned, neither its start or end [Location](#) can differ from the requested **pickup** or **dropoff** [Location](#) by more than the value of the **distance** parameter.

Implements [TransitService](#).

**5.51.2.3 URL `getServiceURL ( )`**

The URL that uniquely identifies this [TransitService](#).

In a REST environment, this might be the root of the REST API path.

**Returns**

The URL of this service

Implements [TransitService](#).

**5.51.2.4 TransitInfo `getTransitInfo ( )`**

Gets metadata about the Transit Authority providing the information retrieved from this service.

**Returns**

The [TransitInfo](#) of the Transit Authority of this service.

Implements [TransitService](#).

**5.51.2.5 void `handleRouteDisruptionEvent ( RouteDisruptionEvent routeDisruptionEvent )`**

After a [RouteDisruptionEvent](#) is received, this class will perform the following:

- Internally register the [RouteDisruptionEvent](#) so that any subsequent requests for affected [Routes](#) will include appropriate [Detour](#) information.
- Notify the Alert module via the [AlertRequestController](#) of the disruption with the updated [Route](#). This updated [Route](#) should include all necessary [Detour](#) information.

Implements [TransitProviderObserver](#).

**5.51.3 Member Data Documentation****5.51.3.1 AlertRequestController `alertRequestController` [private]**

The inter-module dependency to the Alert Module.

The [AlertRequestController](#) accepts requests from this class to inform the Alert Module of a [RouteDisruptionAlert](#).

NOTE: This represents a conceptual dependency to the [AlertRequestController](#). During implementation phase, actual communication with the [AlertRequestController](#) will happen via some client object or service. Implementation of the actual client and its link to the [AlertRequestController](#) (to include REST URLs and JSON structure) will be left to the next phase, or as design details for the development team.

### 5.51.3.2 TransitFeed transitFeed [private]


The [TransitFeed](#) used to provide data to this [TransitService](#) implementation.

Note that this [TransitFeed](#) implementation may be aggregate of many [TransitFeeds](#), an Adapter to another API, or other implementation.

## 5.52 ITeamTripServiceController Class Reference

An iTeam implementation of the [TripService](#) that exposes [Trip](#) data via a REST Service.

Inheritance diagram for ITeamTripServiceController:



### Public Member Functions

- [Trip](#) **calculateTrip** ([Location](#) start, [Location](#) end)  
Calculate an optimal [Trip](#) given a **start** [Location](#) and an **end** [Location](#).
- [TransitService](#) **getTransitService** ()
- void **setTransitService** ([TransitService](#) transitService)

### Private Attributes

- [TransitService](#) transitService  
The [TransitService](#) used to provide the [Route](#) data used in the [Trip](#) calculations.

### 5.52.1 Detailed Description

An iTeam implementation of the [TripService](#) that exposes [Trip](#) data via a REST Service.

Note: The actual [Trip](#) calculation algorithm is not specified here and is beyond the scope of this project.

Errors should be communicated via standard HTTP error codes. The [BaseController](#) will be responsible for mapping Exception types to HTTP error codes, so actual error codes are not specified explicitly here.

### 5.52.2 Member Function Documentation

#### 5.52.2.1 Trip calculateTrip ( Location start, Location end )

Calculate an optimal [Trip](#) given a **start** [Location](#) and an **end** [Location](#).

#### Parameters

|              |  |
|--------------|--|
| <i>start</i> | The requested start <a href="#">Location</a> of the <a href="#">Trip</a> . |
| <i>end</i>   | The requested end <a href="#">Location</a> of the <a href="#">Trip</a> .   |

**Returns**


The calculated [Trip](#)

Implements [TripService](#).

## 5.53 ITeamUserFavoritesService Class Reference

This is the iTeam's implementation of [UserFavoritesService](#).

Inheritance diagram for ITeamUserFavoritesService:

**Public Member Functions**

- [UserFavoritesList](#) `readFavorites` (String `sessionToken`) throws `BusBuddyException`
- void [saveFavorites](#) (String `sessionToken`, [UserFavoritesList](#) `favorites`) throws `BusBuddyException`

**Protected Attributes**

- [ITeamUserLoginService](#) `userLoginService`
- [UserFavoritesRepository](#) `userFavoritesRepository`

### 5.53.1 Detailed Description

This is the iTeam's implementation of [UserFavoritesService](#).

### 5.53.2 Member Function Documentation

#### 5.53.2.1 `UserFavoritesList readFavorites ( String sessionToken )` throws `BusBuddyException`

**See Also**

[UserFavoritesService.readFavorites](#)

Implements [UserFavoritesService](#).

#### 5.53.2.2 `void saveFavorites ( String sessionToken, UserFavoritesList favorites )` throws `BusBuddyException`

**See Also**

[UserFavoritesService.saveFavorites](#)


Implements [UserFavoritesService](#).



## 5.54 ITeamUserLoginService Class Reference

This is the iTeam's implementation of [UserLoginService](#).

Inheritance diagram for ITeamUserLoginService:



### Public Member Functions

- String [login](#) (String username, String password) throws BusBuddyException
- void [logout](#) (String sessionToken) throws BusBuddyException
- [User](#) [getUser](#) (String sessionToken) throws BusBuddyException
- String [createAlertSession](#) (String sessionToken) throws BusBuddyException
- void [sendUsername](#) (String email) throws BusBuddyException
- void [sendUsername](#) (short countryCode, String mobile) throws BusBuddyException
- void [resetPassword](#) (String username, String email) throws BusBuddyException
- void [resetPassword](#) (String username, short countryCode, String mobile) throws BusBuddyException

### Protected Member Functions

- boolean [checkPermissions](#) (String sessionToken, [User](#) user) throws BusBuddyException  
*This method checks to see if the currently logged in user has permissions to modify another given user object.*

### Protected Attributes

- [SessionRepository](#) [sessionRepository](#)
- [UserRepository](#) [userRepository](#)

#### 5.54.1 Detailed Description

This is the iTeam's implementation of [UserLoginService](#).

#### 5.54.2 Member Function Documentation

##### 5.54.2.1 boolean [checkPermissions](#) ( String *sessionToken*, [User](#) *user* ) throws **BusBuddyException** [protected]

This method checks to see if the currently logged in user has permissions to modify another given user object.

A session can modify a user if it is the currently logged in user that is being modified, or if the currently logged in user is a system administrator.

#### Precondition

The session token must be linked to an active and valid session, which must be linked to an active account.

#### Postcondition

The expiration time will be advanced based on this activity against the session.

## Parameters

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | The session token identifying the session of the currently logged in user. |
| <i>user</i>         | The user we are checking to see if the session has permission to modify.   |

## Returns

true if the currently signed in user has permission to modify the user specified in the user parameter, false otherwise

## Exceptions

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the session token is blank.   |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the session token is invalid, linked to an expired session, or the user does not have permission to be signed in. |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.   |

## 5.54.2.2 String createAlertSession ( String sessionToken ) throws BusBuddyException

## See Also

[UserLoginService.createAlertSession](#)

Implements [UserLoginService](#).

## 5.54.2.3 User getUser ( String sessionToken ) throws BusBuddyException

## See Also

[UserLoginService.getUser](#)

Implements [UserLoginService](#).

## 5.54.2.4 String login ( String username, String password ) throws BusBuddyException

## See Also

[UserLoginService.login](#)

Implements [UserLoginService](#).

## 5.54.2.5 void logout ( String sessionToken ) throws BusBuddyException

## See Also

[UserLoginService.logout](#)

Implements [UserLoginService](#).

## 5.54.2.6 void resetPassword ( String username, String email ) throws BusBuddyException

## See Also

[UserLoginService.resetPassword\(String, String\)](#)

Implements [UserLoginService](#).

5.54.2.7 void resetPassword ( String *username*, short *countryCode*, String *mobile* ) throws **BusBuddyException**

See Also

[UserLoginService.resetPassword\(String, short, String\)](#)

Implements [UserLoginService](#).

5.54.2.8 void setUsername ( String *email* ) throws **BusBuddyException**

See Also

[UserLoginService.setUsername\(String\)](#)

Implements [UserLoginService](#).

5.54.2.9 void setUsername ( short *countryCode*, String *mobile* ) throws **BusBuddyException**

See Also


[UserLoginService.setUsername\(short, String\)](#)

Implements [UserLoginService](#).

## 5.55 ITeamUserManagementService Class Reference

This is the iTeam's implementation of [UserManagementService](#).

Inheritance diagram for ITeamUserManagementService:



### Public Member Functions

- [User createUser](#) (User userToCreate, String password) throws **BusBuddyException**
- [User findUserByUsername](#) (String sessionToken, String username) throws **BusBuddyException**
- [User findUserByEmail](#) (String sessionToken, String email) throws **BusBuddyException**
- [User findUserByMobile](#) (String sessionToken, short countryCode, String mobile) throws **BusBuddyException**
- void [updateUser](#) (String sessionToken, User newUserData, String password) throws **BusBuddyException**
- void [deleteUser](#) (String sessionToken, User userToDelete) throws **BusBuddyException**

### Protected Attributes

- [ITeamUserLoginService](#) **userLoginService**
- [UserRepository](#) **userRepository**

### 5.55.1 Detailed Description

This is the iTeam's implementation of [UserManagementService](#).

## 5.55.2 Member Function Documentation

5.55.2.1 **User** createUser ( *User userToCreate*, *String password* ) throws **BusBuddyException**

See Also

[UserManagementService.createUser](#)

Implements [UserManagementService](#).

5.55.2.2 **void** deleteUser ( *String sessionToken*, *User userToDelete* ) throws **BusBuddyException**

See Also

[UserManagementService.delete](#)

Implements [UserManagementService](#).

5.55.2.3 **User** findUserByEmail ( *String sessionToken*, *String email* ) throws **BusBuddyException**

See Also

[UserManagementService.findUserByEmail](#)

Implements [UserManagementService](#).

5.55.2.4 **User** findUserByMobile ( *String sessionToken*, *short countryCode*, *String mobile* ) throws **BusBuddyException**

See Also

[UserManagementService.findUserByMobile](#)

Implements [UserManagementService](#).

5.55.2.5 **User** findUserByUsername ( *String sessionToken*, *String username* ) throws **BusBuddyException**

See Also

[UserManagementService.findUserByUsername](#)

Implements [UserManagementService](#).

5.55.2.6 **void** updateUser ( *String sessionToken*, *User newUserData*, *String password* ) throws **BusBuddyException**

See Also


[UserManagementService.updateUser](#)

Implements [UserManagementService](#).

## 5.56 ITrackingService Interface Reference

Interface for the Tracking Service Controller.

Inheritance diagram for ITrackingService:



## Public Member Functions

- void [registerVehicleOnRoute](#) (URL url, int gpsDeviceID)  
*Interface for registering vehicles on a route from the user interface.*
- void [unregisterVehicleFromRoute](#) (String url, int gpsDeviceID)  
*Interface for removing a registered vehicle from a route when the vehicle goes out of service.*
- void [addUserTrackingAlert](#) ([UserTrackingAlertObject](#) utao)  
*Add a user tracking alert from the user interface.*
- void [startTrackingController](#) ()  
*Logic necessary when the tracking controller is cold started.*
- [GPSLocationObject](#) [getTransitVehicleLocation](#) (int gpsDeviceID)  
*Allows users and modules outside of the tracking package to query for the current location of a registered vehicle.*

### 5.56.1 Detailed Description

Interface for the Tracking Service Controller.

The tracking service purpose is to allow vehicles to register on routes and to establish a connection with the GPS device installed in the vehicle to provide regular vehicle location updates. The tracking service uses the current GPS coordinates to determine when to send alerts to registered users.

### 5.56.2 Member Function Documentation

#### 5.56.2.1 void [addUserTrackingAlert](#) ( [UserTrackingAlertObject](#) utao )

Add a user tracking alert from the user interface.

##### Parameters

|             |  |
|-------------|--|
| <i>utao</i> | - <a href="#">UserTrackingAlertObject</a> information from user interface necessary to create alert. |
|-------------|--|

Implemented in [TrackingServiceController](#).

#### 5.56.2.2 [GPSLocationObject](#) [getTransitVehicleLocation](#) ( int *gpsDeviceID* )

Allows users and modules outside of the tracking package to query for the current location of a registered vehicle.

##### Parameters

|                    |                              |
|--------------------|------------------------------|
| <i>gpsDeviceID</i> | - unique hardware GPS device |
|--------------------|------------------------------|

##### Returns

- Location current latitude and longitude of vehicle

Implemented in [TrackingServiceController](#).

### 5.56.2.3 void registerVehicleOnRoute ( URL url, int gpsDeviceID )

Interface for registering vehicles on a route from the user interface.

#### Parameters

|                    |                                 |
|--------------------|---------------------------------|
| <i>url</i>         | - Transit company URL           |
| <i>gpsDeviceID</i> | - unique hardware GPS device ID |

Implemented in [TrackingServiceController](#).

### 5.56.2.4 void startTrackingController ( )

Logic necessary when the tracking controller is cold started.

Retrieves the saved user alerts from the [IAlertService](#)

Implemented in [TrackingServiceController](#).

### 5.56.2.5 void unregisterVehicleFromRoute ( String url, int gpsDeviceID )

Interface for removing a registered vehicle from a route when the vehicle goes out of service.

#### Parameters

|                    |   |
|--------------------|---|
| <i>url</i>         | - URL uniquely identifying a transit company.                 |
| <i>gpsDeviceID</i> | - unique hardware GPS id being unregistered on user interface |

Implemented in [TrackingServiceController](#).

## 5.57 Location Class Reference

An immutable Value Object representing a physical point on the geographic coordinate system.

### Public Member Functions

- [Location](#) (double [latitude](#), double [longitude](#))  
*Instantiates a new immutable [Location](#) with the given latitude and longitude.*
- double **getLatitude** ()
- double **getLongitude** ()

### Private Attributes

- double [latitude](#)  
*The latitude of the geographic point.*
- double [longitude](#)  
*The longitude of the geographic point.*

### 5.57.1 Detailed Description

An immutable Value Object representing a physical point on the geographic coordinate system.

## 5.57.2 Constructor & Destructor Documentation

### 5.57.2.1 Location ( double *latitude*, double *longitude* )

Instantiates a new immutable [Location](#) with the given latitude and longitude.

#### Parameters

|                  |                     |
|------------------|---------------------|
| <i>latitude</i>  | The point latitude  |
| <i>longitude</i> | The point longitude |

## 5.58 MessageDeliveryUtility Class Reference

This is a utility class to handle message delivery, such as through email or SMS.

### Static Public Member Functions

- static void [sendEmail](#) (String *to*, String *from*, String *subject*, String *htmlBody*) throws [BusBuddyInternalException](#)  
*This method sends an HTML e-mail.*
- static void [sendSms](#) (short *countryCode*, String *mobileNumber*, String *message*)  
*This method sends an SMS text message.*

### 5.58.1 Detailed Description

This is a utility class to handle message delivery, such as through email or SMS.

### 5.58.2 Member Function Documentation

#### 5.58.2.1 static void sendEmail ( String *to*, String *from*, String *subject*, String *htmlBody* ) throws [BusBuddyInternalException](#) [static]

This method sends an HTML e-mail.

#### Parameters

|                 |                          |
|-----------------|--------------------------|
| <i>to</i>       | recipient address        |
| <i>from</i>     | sender address           |
| <i>subject</i>  | subject line             |
| <i>htmlBody</i> | HTML body of the message |

#### Exceptions

|   |   |
|---|---|
| <a href="#">BusBuddyInternalException</a> | This exception is thrown if there is an error sending the e-mail. |
|---|---|

#### 5.58.2.2 static void sendSms ( short *countryCode*, String *mobileNumber*, String *message* ) [static]

This method sends an SMS text message.

#### Precondition

The mobile number must be a String consisting entirely of digits.

## Parameters

|                     |                                |
|---------------------|--------------------------------|
| <i>countryCode</i>  | country code for the recipient |
| <i>mobileNumber</i> | mobile number to send to       |
| <i>message</i>      | body of the message to send    |


## Exceptions

|   |  |
|---|--|
| <a href="#">BusBuddyInternalException</a> | This exception is thrown if there is an error sending the message. |
|---|--|

## 5.59 OneTimeAlert Class Reference

This is a model of alert that is to be run one time only.

Inheritance diagram for OneTimeAlert:



### Public Member Functions

- Date **getDateExecuted** ()
- void **setDateExecuted** (Date [dateExecuted](#))

### Private Attributes

- Date [dateExecuted](#)  
*Date when it was executed.*

### Static Private Attributes

- static final long **serialVersionUID** = 8851691556082123516L

#### 5.59.1 Detailed Description

This is a model of alert that is to be run one time only.

This can be configure by User (e.g., catch bus to Boston at 9am on MM/DD/YYYY) or by any other module (e.g., Route to MSP downtown on MM/DD/YYYY is going to be rerouted). This class extends the [Alert](#).

#### 5.59.2 Member Data Documentation

##### 5.59.2.1 Date `dateExecuted` [private]

Date when it was executed.


If absent, then the alert hasn't been executed.



## 5.60 PersistedTransitFeed Class Reference

An implementation of the [TransitFeed](#) interface that communicates with a [RouteRepository](#) to retrieve its data.

Inheritance diagram for PersistedTransitFeed:



### Public Member Functions

- [Route](#) **getRoute** (String routeld)  
*Gets a [Route](#) by its unique identifier.*
- Set< [Route](#) > **getRoutes** ([Location](#) pickup, [Location](#) dropoff, int distance)  
*Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.*
- [RouteRepository](#) **getRouteRepository** ()
- void **setRouteRepository** ([RouteRepository](#) routeRepository)

### Private Attributes

- [RouteRepository](#) routeRepository  
*The [RouteRepository](#) responsible for providing data.*

#### 5.60.1 Detailed Description

An implementation of the [TransitFeed](#) interface that communicates with a [RouteRepository](#) to retrieve its data.

This implementation is appropriate when a retrieving data from a [TransitProvider](#) that does not already supply an external API that can be used at runtime. If the data needs to be parsed and imported into a [RouteRepository](#), this implementation will expose that persisted data as a [TransitFeed](#).

#### 5.60.2 Member Function Documentation

##### 5.60.2.1 [Route](#) getRoute ( String routeld )

Gets a [Route](#) by its unique identifier.

##### Precondition

**routeld** is not null or blank.

##### Postcondition

The [Route](#) is returned if the **routeld** is found, else null.

##### Parameters

|                |  |
|----------------|--|
| <i>routeld</i> | The unique identifier of the <a href="#">Route</a> |
|----------------|--|

**Returns**

The matching [Route](#), or null if not found

Implements [TransitFeed](#).

**5.60.2.2 Set<Route> getRoutes ( Location pickup, Location dropoff, int distance )**

Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.

**Precondition**

**pickup** is not null or blank.  
**dropoff** is not null or blank.  
**distance** is non-negative.

**Parameters**

|                 |  |
|-----------------|--|
| <i>pickup</i>   | The requested pickup <a href="#">Location</a>  |
| <i>dropoff</i>  | The requested dropoff <a href="#">Location</a>   |
| <i>distance</i> | The distance (in miles) that each <a href="#">Route</a> can deviate from the requested <b>pickup</b> or <b>dropoff</b> <a href="#">Location</a> . For each <a href="#">Route</a> returned, neither its start or end <a href="#">Location</a> can differ from the requested <b>pickup</b> or <b>dropoff</b> <a href="#">Location</a> by more than the value of the <b>distance</b> parameter. |

**Returns**


The matching [Routes](#)

Implements [TransitFeed](#).

**5.61 RecurringAlert Class Reference**

This is a model of alert that is to be run multiple times.

Inheritance diagram for RecurringAlert:

**Public Member Functions**

- Date **getSuspendDateTime** ()
- void **setSuspendDateTime** (Date [suspendDateTime](#))
- Date **getResumeDateTime** ()
- void **setResumeDateTime** (Date [resumeDateTime](#))
- Date **getLastSuccessfullyRanOnDateTime** ()
- void **setLastSuccessfullyRanOnDateTime** (Date [lastSuccessfullyRanOnDateTime](#))
- List< [RecurringData](#) > **getRecurringData** ()
- void **setRecurringData** (List< [RecurringData](#) > [recurringData](#))

- int **getRepeatEvery** ()
- void **setRepeatEvery** (int [repeatEvery](#))
- [AlertRecurringType](#) **getAlertRecurringType** ()
- void **setAlertRecurringType** ([AlertRecurringType](#) [alertRecurringType](#))

### Private Attributes

- Date [suspendDateTime](#)  
*DateTime when the alert is to be suspended temporarily.*
- Date [resumeDateTime](#)  
*DateTime when the alert is to be resumed.*
- Date [lastSuccessfullyRanOnDateTime](#)  
*DateTime of last successful run.*
- List< [RecurringData](#) > [recurringData](#)  
*List of [RecurringData](#) that holds the information about when the alert should actually run.*
- int [repeatEvery](#)  
*Parameter to signify the skip count.*
- [AlertRecurringType](#) [alertRecurringType](#)  
*Type of recurring alert.*

### Static Private Attributes

- static final long **serialVersionUID** = -475174398668611743L

#### 5.61.1 Detailed Description

This is a model of alert that is to be run multiple times.

Depending on User or other modules, the alert will run yearly, monthly, daily in specified hour and minute.

#### 5.61.2 Member Data Documentation

##### 5.61.2.1 [AlertRecurringType](#) [alertRecurringType](#) [private]

Type of recurring alert.

Value is as defined in [AlertRecurringType](#)

##### 5.61.2.2 int [repeatEvery](#) [private]

Parameter to signify the skip count.

Valid value is >0 If alert is to occur every Monday and the repeatEvery is set to 2, then it will repeat once every 2 week.

## 5.62 RecurringData Class Reference

This model holds the information about the date and time the alert needs to run.

## Public Member Functions

- int **getDayOfYear** ()
- void **setDayOfYear** (int [dayOfYear](#))
- int **getDayOfMonth** ()
- void **setDayOfMonth** (int [dayOfMonth](#))
- int **getDayOfWeek** ()
- void **setDayOfWeek** (int [dayOfWeek](#))
- int **getStartHour** ()
- void **setStartHour** (int [startHour](#))
- int **getStartMinute** ()
- void **setStartMinute** (int [startMinute](#))

## Private Attributes

- int [dayOfYear](#)  
*Day of year that the alert should run.*
- int [dayOfMonth](#)  
*Day of month that the alert should run.*
- int [dayOfWeek](#)  
*Day of week that the alert should run.*
- int [startHour](#)  
*The exact hour when the alert should run.*
- int [startMinute](#)  
*The exact minute when the alert should run.*

### 5.62.1 Detailed Description

This model holds the information about the date and time the alert needs to run.

### 5.62.2 Member Data Documentation

#### 5.62.2.1 int [dayOfMonth](#) [private]

Day of month that the alert should run.

Valid value is from 1-28.

#### 5.62.2.2 int [dayOfWeek](#) [private]

Day of week that the alert should run.

e.g., 1 = Sunday and 7 = Saturday.

#### 5.62.2.3 int [dayOfYear](#) [private]

Day of year that the alert should run.

Valid value = 1-365

5.62.2.4 `int startHour` `[private]`

The exact hour when the alert should run.

Valid value is from 0 - 23

5.62.2.5 `int startMinute` `[private]`

The exact minute when the alert should run.

Valid value is from 0-59.

## 5.63 Route Class Reference

A [Route](#) is a [TransitVehicle](#) path of travel, or a "Line," as referred to by a [TransitProvider](#).

### Public Member Functions

- List< [Stop](#) > **getStops** ()
- void **setStops** (List< [Stop](#) > stops)  
*Sets the [Stops](#) of this [Route](#).*
- String **getRouteId** ()
- void **setRouteId** (String routeId)
- String **getRouteName** ()
- void **setRouteName** (String routeName)
- Set< [Detour](#) > **getDetours** ()
- void **setDetours** (Set< [Detour](#) > detours)

### Protected Member Functions

- [Route](#) (String routeId, String routeName, List< [Stop](#) > stops)  
*Instantiates a new [Route](#) with all required fields.*

### Private Attributes

- String routeId  
*A unique identifier for this [Route](#).*
- String routeName  
*Text to display in maps and other literature to denote this [Route](#).*
- List< [Stop](#) > stops  
*And ordered list of [Stops](#) to be visited in this [Route](#).*
- Set< [Detour](#) > detours  
*A set of [Detours](#), or disruptions in [Route](#) availability and/or [Stop](#) schedule.*

### 5.63.1 Detailed Description

A [Route](#) is a [TransitVehicle](#) path of travel, or a "Line," as referred to by a [TransitProvider](#).

A [Route](#) can be thought of as an ordered list of [Stops](#).

Note that Routes may add/remove stops, change [Stop](#) times, or be disrupted by [Detours](#), while still remaining the same [Route](#).

[Route](#) is also the AggregateRoot of the RouteAggregate, which implies that the `routeId` parameter is globally unique.

## Invariant

`stops.size() >= 2`

### 5.63.2 Constructor & Destructor Documentation

#### 5.63.2.1 `Route ( String routeId, String routeName, List< Stop > stops )` [protected]

Instantiates a new [Route](#) with all required fields.

## Precondition

`stops.size() >= 2`

## Parameters

|                  |   |
|------------------|---|
| <i>routeId</i>   | The <a href="#">Route</a> id                              |
| <i>routeName</i> | The <a href="#">Route</a> name                            |
| <i>stops</i>     | The <a href="#">Stops</a> in this <a href="#">Route</a> . |

### 5.63.3 Member Function Documentation

#### 5.63.3.1 `void setStops ( List< Stop > stops )`

Sets the [Stops](#) of this [Route](#).

Note that there must be 2 or more [Stops](#) in a [Route](#).

## Precondition

`stops.size() >= 2`

### 5.63.4 Member Data Documentation

#### 5.63.4.1 `Set<Detour> detours` [private]

A set of [Detours](#), or disruptions in [Route](#) availability and/or [Stop](#) schedule.

These [Detours](#) represent disruptions that are current at the time of retrieval of this [Route](#).

#### 5.63.4.2 `String routeName` [private]

Text to display in maps and other literature to denote this [Route](#).

Uniqueness is not enforced, but this name should provide enough context to allow users to distinguish this [Route](#).

#### 5.63.4.3 `List<Stop> stops` [private]


And ordered list of [Stops](#) to be visited in this [Route](#).

Stops must be visited in order unless there is a disruption in service, in which case clients can expect a [Route-DistruptionAlert](#) and/or an [Detour](#).

## 5.64 RouteAlertExecuteStrategy Class Reference

A concrete implementation of [IAlertExecuteStrategy](#) that handles executing alert related to route changes.

Inheritance diagram for RouteAlertExecuteStrategy:



## Public Member Functions

- boolean `execute` ([Alert](#) alert)

## Package Attributes

- [AlertRepository](#) `alertRepository`  
An instance of [AlertRepository](#) that is used to fetch alerts that are effected by particular route.
- [AlertUserClient](#) `userClient`  
A spring autowired instance of [AlertUserClient](#) that can call the User module to get user information.

### 5.64.1 Detailed Description

A concrete implementation of [IAlertExecuteStrategy](#) that handles executing alert related to route changes.

### 5.64.2 Member Function Documentation

#### 5.64.2.1 boolean `execute` ( [Alert](#) *alert* )

#### See Also

`IAlertExecuteStrategy::execute(List)` Takes in a list of alerts usually provided from Transit or Tracking module where route disruption information is stored. This method finds all the alerts (that users have created) that are associated with a particular route. Hence, each route disruption alert can `execute` multiple other alerts.

Find other alert that is associated with `routeId` in this alert.

call user module for each and every of these alerts and push the notification.

if success

Implements [IAlertExecuteStrategy](#).

### 5.64.3 Member Data Documentation

#### 5.64.3.1 [AlertRepository](#) `alertRepository` [package]

An instance of [AlertRepository](#) that is used to fetch alerts that are effected by particular route.

This is autowired via Spring Framework.

#### 5.64.3.2 [AlertUserClient](#) `userClient` [package]

A spring autowired instance of [AlertUserClient](#) that can call the User module to get user information.

This is autowired via Spring Framework.

## 5.65 RouteDisruptionAlert Class Reference

An Alert indicating a disruption of normal [Route](#) availability or scheduling.

### Public Member Functions

- URL **getTransitServiceUrl** ()
- void **setTransitServiceUrl** (URL [transitServiceUrl](#))
- String **getRouteId** ()
- void **setRouteId** (String [routeId](#))

### Private Attributes

- URL [transitServiceUrl](#)  
*The URL callback of the originating [TransitService](#).*
- String [routeId](#)  
*The unique identifier of the affected [Route](#).*

### 5.65.1 Detailed Description

An Alert indicating a disruption of normal [Route](#) availability or scheduling.

Clients interested in more specific information about the disruption, including cause and affected [Stops](#), should use the `getTransitServiceUrl()` method to establish a link to the appropriate [TransitService](#), and then obtain the affected [Route](#) using the `routeId` from the `getRouteId()` method.

Once retrieved, current [Detour](#) information can be accessed via the [Route](#) `getDetours()` method on the given [Route](#). This method, upon subsequent retrievals of the [Route](#), will return an empty set when all [Detours](#) have cleared.

### 5.65.2 Member Data Documentation

#### 5.65.2.1 String `routeId` [private]

The unique identifier of the affected [Route](#).

This can be used in the [TransitService](#) method `TransitService#getRoute(String)` to retrieve more information about the disruption.

#### 5.65.2.2 URL `transitServiceUrl` [private]

The URL callback of the originating [TransitService](#).

Clients should use this URL to obtain further disruption information, such as [Detours](#) of the affected [Route](#).

## 5.66 RouteDisruptionEvent Class Reference

An event indicating a disruption in normal [Route](#) scheduling or service.

### Public Member Functions

- [RouteDisruptionEvent](#) ([Route](#) `disruptedRoute`)  
*Instantiates a new route disruption event with the affected [Route](#).*



- [Route](#) **getDisruptedRoute** ()
- void **setDisruptedRoute** ([Route](#) *disruptedRoute*)

### Private Attributes

- [Route](#) *disruptedRoute*

The disrupted [Route](#), complete with any [Detour](#) information that is available.

### 5.66.1 Detailed Description

An event indicating a disruption in normal [Route](#) scheduling or service.

This event will be initiated by a [TransitProvider](#) in cases of mechanical failure, scheduled maintenance, infrastructure delays such as construction or road closures, etc.

Note that a [RouteDisruptionEvent](#) can signal that a [Route](#) is returning back to normal service after the disruption has cleared. This is done by sending a [Route](#) with no [Detours](#).

### 5.66.2 Constructor & Destructor Documentation

#### 5.66.2.1 RouteDisruptionEvent ( [Route](#) *disruptedRoute* )

Instantiates a new route disruption event with the affected [Route](#).

#### Parameters

|                       |                                     |
|-----------------------|-------------------------------------|
| <i>disruptedRoute</i> | The Disrupted <a href="#">Route</a> |
|-----------------------|-------------------------------------|

## 5.67 RouteRepository Interface Reference

A Repository Pattern supporting lifecycle operations of [Routes](#), such as Read, Save, Delete, and Query functionality.

### Public Member Functions

- void **delete** (String *routeId*)  
*Deletes the [Route](#) corresponding to the given **routeId**.*
- void **save** ([Route](#) *route*)  
*Saves the [Route](#) to the Repository.*
- void **save** (Set< [Route](#) > *routes*)  
*Saves all of the [Routes](#) to the Repository.*
- [Route](#) **read** (String *routeId*)  
*Read a single [Route](#) from the Repository by its identifier.*
- Collection< [Route](#) > **getAll** ()  
*Retrieves all available [Routes](#) in the Repository.*

### 5.67.1 Detailed Description

A Repository Pattern supporting lifecycle operations of [Routes](#), such as Read, Save, Delete, and Query functionality.

## 5.67.2 Member Function Documentation

### 5.67.2.1 void delete ( String *routeId* )

Deletes the [Route](#) corresponding to the given **routeId**.

#### Precondition

A [Route](#) with the given **routeId** exists in the Repository.

#### Postcondition

A [Route](#) with the given **routeId** is removed from the Repository and is no longer available for retrieval.

#### Parameters

|                |  |
|----------------|--|
| <i>routeId</i> |  |
|----------------|--|

### 5.67.2.2 Collection<[Route](#)> getAll ( )

Retrieves all available [Routes](#) in the Repository.

#### Returns

All available [Routes](#).

### 5.67.2.3 [Route](#) read ( String *routeId* )

Read a single [Route](#) from the Repository by its identifier.

If no [Route](#) is found with the requested **routeId**, a null value is returned.

#### Parameters

|                |   |
|----------------|---|
| <i>routeId</i> | The identifier of the requested <a href="#">Route</a> |
|----------------|---|

#### Returns

The requested [Route](#)

### 5.67.2.4 void save ( [Route](#) *route* )

Saves the [Route](#) to the Repository.

#### Precondition

The [Route](#) has been validated with all appropriate business rules.

#### See Also

[RouteSpecification](#)

**Postcondition**

The [Route](#) is available for retrieval by id and also by appropriate Queries.

**Parameters**

|              |                                    |
|--------------|------------------------------------|
| <i>route</i> | The <a href="#">Route</a> to save. |
|--------------|------------------------------------|

**5.67.2.5 void save ( Set< [Route](#) > routes )**

Saves all of the [Routes](#) to the Repository.

**Precondition**

The [Routes](#) have been validated with all appropriate business rules.

**See Also**

[RouteSpecification](#)

**Postcondition**

The [Routes](#) are available for retrieval by id and also by appropriate Queries.


**Parameters**

|              |                                    |
|--------------|------------------------------------|
| <i>route</i> | The <a href="#">Route</a> to save. |
|--------------|------------------------------------|

**5.68 RouteSpecification Class Reference**

A Specification Pattern class for validating a [Route](#).

Inheritance diagram for RouteSpecification:

**Public Member Functions**

- boolean [isSatisfiedBy](#) ([Route](#) candidate)  
*Validates the given [Route](#) with the appropriate validation rules of this Specification.*
- Specification< [Route](#) > **or** (Specification< [Route](#) > specification)
- Specification< [Route](#) > **and** (Specification< [Route](#) > specification)
- Specification< [Route](#) > **not** (Specification< [Route](#) > specification)

**5.68.1 Detailed Description**

A Specification Pattern class for validating a [Route](#).

Validation can happen in this class, or business rules can be combined using the `and`, `or`, or `not` methods of separate [Specifications](#).

This Specification is necessary because [Routes](#) aren't necessarily created by a controlled Factory, but as a result of parsing of input files via subclasses of the [AbstractFeedParserTemplate](#). Because creation of [Routes](#) isn't centralized, it is necessary to centralize the validation rules so that subclasses of [AbstractFeedParserTemplate](#) have access to it.

This Specification must validate the following conditions:

1. Each [Route](#) has an non-null [routeId](#)
2. Each [Route](#) has an non-blank [routeName](#)
3. Each [Route](#) has two or more [Stops](#)

## 5.68.2 Member Function Documentation

### 5.68.2.1 boolean `isSatisfiedBy ( Route candidate )`

Validates the given [Route](#) with the appropriate validation rules of this Specification.

#### Parameters

|                  |   |
|------------------|---|
| <i>candidate</i> | The <a href="#">Route</a> to be validated |
|------------------|---|


#### Returns

True if a valid [Route](#), False if not

## 5.69 ScheduleAlertExecuteStrategy Class Reference

A concrete implementation of [IAlertExecuteStrategy](#) that handles executing alert related to user's regular schedule.

Inheritance diagram for ScheduleAlertExecuteStrategy:



### Public Member Functions

- boolean `execute (Alert alertModel)`

*For each passed in alert, it pushes notification to the user informing about their upcoming trip and routes (as they have scheduled in the first place)*

### Package Attributes

- [AlertRepository](#) `alertRepository`

*An instance of [AlertRepository](#) that is used to fetch alerts.*

- [AlertUserClient](#) `userClient`

*A spring autowired instance of [AlertUserClient](#) that can call the User module to get user information.*

### 5.69.1 Detailed Description

A concrete implementation of [IAlertExecuteStrategy](#) that handles executing alert related to user's regular schedule.

### 5.69.2 Member Data Documentation

#### 5.69.2.1 [AlertRepository](#) alertRepository [package]

An instance of [AlertRepository](#) that is used to fetch alerts.

This is autowired via Spring Framework.

#### 5.69.2.2 [AlertUserClient](#) userClient [package]

A spring autowired instance of [AlertUserClient](#) that can call the User module to get user information.

This is autowired via Spring Framework.

## 5.70 Session Class Reference

This class represents a single session for a user of the system, and all of the state data associated with that session.

### Protected Member Functions

- String [getSessionToken](#) ()  
*This retrieves the session token.*
- Calendar [getCreationTime](#) ()  
*This retrieves the time that the session was created.*
- Calendar [getExpirationTime](#) ()  
*This retrieves the time that the session is set to expire.*
- void [setExpirationTime](#) (Calendar expirationTime)  
*This sets the time that the session should expire.*
- boolean [isAlertSession](#) ()  
*This checks to see if the session is an alert session.*
- boolean [isValid](#) ()  
*This checks to see if the session is valid.*
- void [setValid](#) (boolean valid)  
*This sets whether the session is valid.*
- int [getUserId](#) ()  
*This gets the ID of the user linked to this session.*

### Package Functions

- [Session](#) (String sessionToken, Calendar creationTime, boolean isAlertSession, int userId)  
*Create a new session object.*

## Private Attributes

- final String **sessionToken**
- final Calendar **creationTime**
- Calendar **expirationTime**
- final boolean **isAlertSession**
- boolean **valid**
- final int **userId**

### 5.70.1 Detailed Description

This class represents a single session for a user of the system, and all of the state data associated with that session.

The session should already exist in the database before instantiating this object. A session grants a user access to the data associated with that user. Sessions expire after a certain point, and can also be invalidated by a user logging out. Some sessions are designed to be longer lasting, for use with alerts. This object is not visible to clients - when they must pass a session reference, they do so by passing around the sessionToken.

### 5.70.2 Constructor & Destructor Documentation

#### 5.70.2.1 Session ( String sessionToken, Calendar creationTime, boolean isAlertSession, int userId ) [package]

Create a new session object.

It is not visible to clients, as [User](#) objects should only be constructed through the [UserRepository](#). The parameters taken by the constructor cannot be changed once the session is created.

#### Parameters

|                       |   |
|-----------------------|---|
| <i>sessionToken</i>   | unique session token                              |
| <i>creationTime</i>   | time that the session was created                 |
| <i>isAlertSession</i> | true if this is an alert session, false otherwise |
| <i>userId</i>         | user ID that the session is linked to             |

### 5.70.3 Member Function Documentation

#### 5.70.3.1 Calendar getCreationTime ( ) [protected]

This retrieves the time that the session was created.

#### Returns

session creation time

#### 5.70.3.2 Calendar getExpirationTime ( ) [protected]

This retrieves the time that the session is set to expire.

#### Returns

session expiration time

#### 5.70.3.3 String getSessionToken ( ) [protected]

This retrieves the session token.

**Returns**

session token

**5.70.3.4 int getUserId ( ) [protected]**

This gets the ID of the user linked to this session.

**Returns**

user's ID number

**5.70.3.5 boolean isAlertSession ( ) [protected]**

This checks to see if the session is an alert session.

**Returns**

true if it is, false otherwise

**5.70.3.6 boolean isValid ( ) [protected]**

This checks to see if the session is valid.

**Returns**

true if it is, false otherwise

**5.70.3.7 void setExpirationTime ( Calendar expirationTime ) [protected]**

This sets the time that the session should expire.

**Parameters**

|                       |                        |
|-----------------------|------------------------|
| <i>expirationTime</i> | expiration time to set |
|-----------------------|------------------------|

**5.70.3.8 void setValid ( boolean valid ) [protected]**

This sets whether the session is valid.

**Parameters**

|              |                                |
|--------------|--------------------------------|
| <i>valid</i> | true if it is, false otherwise |
|--------------|--------------------------------|

## 5.71 SessionRepository Class Reference

This class is responsible for handling database access for Sessions, and to construct, persist, and retrieve [Session](#) objects.

## Package Functions

- [Session](#) `createSession` ([User](#) user, boolean isAlertSession) throws `BusBuddyInternalException`  
*This creates a new session for the given user.*
- [Session](#) `getSession` (String sessionToken) throws `BusBuddyInternalException`, `BusBuddyForbiddenException`  
*This method gets a session from the database.*
- void `killSession` (String sessionToken) throws `BusBuddyInternalException`, `BusBuddyNotFoundException`  
*This method invalidates a session in the database.*

### 5.71.1 Detailed Description

This class is responsible for handling database access for Sessions, and to construct, persist, and retrieve [Session](#) objects.

### 5.71.2 Member Function Documentation

#### 5.71.2.1 `Session createSession ( User user, boolean isAlertSession )` throws `BusBuddyInternalException` [package]

This creates a new session for the given user.

#### Precondition

The [User](#) object parameter must be a valid user retrieved from the database.

#### Postcondition

A session is created in the database, and the object representing that session is returned.

#### Parameters

|                       |   |
|-----------------------|---|
| <i>user</i>           | This is the user to create the session for.   |
| <i>isAlertSession</i> | This is set to true if this should be a long-lived session, for an alert. Otherwise, set to false for a normal session. |

#### Returns

The method returns the newly created [Session](#) object.

#### Exceptions

|  |  |
|--|--|
| <code>BusBuddyInternalException</code> | This exception is thrown when there is a database error. |
|--|--|

#### 5.71.2.2 `Session getSession ( String sessionToken )` throws `BusBuddyInternalException`, `BusBuddyForbiddenException` [package]

This method gets a session from the database.

In addition, since this method is only called when there is an it will update the expiration date on the session.



**Precondition**

The sessionToken parameter must be a valid session identifier in the database.

**Postcondition**

The session's expiration date will have been pushed back due to this activity in the session.

**Parameters**

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | This is the session token that identifies the session. |
|---------------------|--|

**Returns**

[Session](#) object represented by the session token that was passed in.

**Exceptions**

|                                   |   |
|-----------------------------------|---|
| <i>BusBuddyInternalException</i>  | This exception is thrown when there is a database error.                            |
| <i>BusBuddyForbiddenException</i> | This exception is thrown if the session token is invalid or the session is expired. |

**5.71.2.3 void killSession ( String sessionToken ) throws BusBuddyInternalException, BusBuddyNotFoundException [package]**

This method invalidates a session in the database.

**Precondition**

The sessionToken parameter must be a valid session identifier in the database.

**Postcondition**

The session will be invalidated and future calls using that sessionToken will fail.

**Parameters**

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | This is the session token that identifies the session. |
|---------------------|--|


**Exceptions**

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.  |
| <i>BusBuddyNotFoundException</i> | This exception is thrown if the session token is invalid. |

## 5.72 SessionTokenHandler Class Reference

A concrete strategy implementation of [ISessionHandler](#) that can verify the session token being passed.

Inheritance diagram for SessionTokenHandler:



## Public Member Functions

- boolean [verifySessionToken](#) (String sessionToken) throws BusBuddyForbiddenException  
*This method takes in an encrypted session token in a form of string and then validates for its authenticity.*

## Package Attributes

- [AlertUserClient](#) `userClient`  
*A spring autowired instance of [AlertUserClient](#) that can call the User module to verify the session token.*

### 5.72.1 Detailed Description

A concrete strategy implementation of [ISessionHandler](#) that can verify the session token being passed.

### 5.72.2 Member Function Documentation

#### 5.72.2.1 boolean verifySessionToken ( String sessionToken ) throws BusBuddyForbiddenException

This method takes in an encrypted session token in a form of string and then validates for its authenticity.

#### Exceptions

|                                    |  |
|------------------------------------|--|
| <i>BusBuddyForbidden-Exception</i> | <ul style="list-style-type: none"> <li>• Throws an exception when the token is not valid.</li> </ul> |
|------------------------------------|--|

Implements [ISessionHandler](#).

### 5.72.3 Member Data Documentation

#### 5.72.3.1 [AlertUserClient](#) `userClient` [package]

A spring autowired instance of [AlertUserClient](#) that can call the User module to verify the session token.

This is autowired via Spring Framework.

## 5.73 SessionVerificationFactory Class Reference

A factory that picks the appropriate strategy [ISessionHandler](#) to verify the encrypted token.

## Static Public Member Functions

- static [ISessionHandler](#) [getSessionTokenVerificationStrategy](#) ([AlertInitiator](#) alertInitiator)  
*This method takes in an [AlertInitiator](#) and depending upon the value can invoke different strategy to verify the token.*

### 5.73.1 Detailed Description

A factory that picks the appropriate strategy [ISessionHandler](#) to verify the encrypted token.

### 5.73.2 Member Function Documentation

#### 5.73.2.1 static [ISessionHandler](#) getSessionTokenVerificationStrategy ( [AlertInitiator](#) *alertInitiator* ) [static]

This method takes in an [AlertInitiator](#) and depending upon the value can invoke different strategy to verify the token.

##### Parameters

|                       |  |
|-----------------------|--|
| <i>alertInitiator</i> | A valid <a href="#">AlertInitiator</a> |
|-----------------------|--|

##### Returns

A implementation of [ISessionHandler](#)

## 5.74 Specification< T > Interface Reference

A Generic Specification to be used for chaining business validation rules together.

### Public Member Functions

- boolean [isSatisfiedBy](#) (T candidate)  
*Checks if the given candidate satisfies the specification.*
- Specification< T > [or](#) (Specification< T > specification)  
*Returns a Specification representing the 'OR' boolean operation of the Specifications.*
- Specification< T > [and](#) (Specification< T > specification)  
*Returns a Specification representing the 'AND' boolean operation of the Specifications.*
- Specification< T > [not](#) (Specification< T > specification)  
*Returns a Specification representing the 'NOT' boolean operation of the Specifications.*

### 5.74.1 Detailed Description

A Generic Specification to be used for chaining business validation rules together.

##### Parameters

|     |   |
|-----|---|
| <T> | The candidate Type accepted by the Specification. |
|-----|---|

### 5.74.2 Member Function Documentation

#### 5.74.2.1 Specification<T> and ( Specification< T > *specification* )

Returns a Specification representing the 'AND' boolean operation of the Specifications.

##### Parameters

|                      |  |
|----------------------|--|
| <i>specification</i> | The Specification to apply the 'AND' operation to. |
|----------------------|--|

**Returns**

The 'AND' Specification

**5.74.2.2 boolean isSatisfiedBy ( T candidate )**

Checks if the given candidate satisfies the specification.

**Parameters**

|                  |               |
|------------------|---------------|
| <i>candidate</i> | The candidate |
|------------------|---------------|

**Returns**

true, if is satisfied by the candidate

**5.74.2.3 Specification<T> not ( Specification< T > specification )**

Returns a Specification representing the 'NOT' boolean operation of the Specifications.

**Parameters**

|                      |  |
|----------------------|--|
| <i>specification</i> | The Specification to apply the 'NOT' operation to. |
|----------------------|--|

**Returns**

The 'NOT' Specification

**5.74.2.4 Specification<T> or ( Specification< T > specification )**

Returns a Specification representing the 'OR' boolean operation of the Specifications.

**Parameters**

|                      |   |
|----------------------|---|
| <i>specification</i> | The Specification to apply the 'OR' operation to. |
|----------------------|---|

**Returns**

The 'OR' Specification

**5.75 Stop Class Reference**

A point on a [Route](#) in which a [TransitVehicle](#) will stop to pick up and drop off passengers.

**Public Member Functions**

- Set< Date > [getStopTimes](#) (Date begin, Date end)  
*Reports the expected times in which a [TransitVehicle](#) will be at the given [Stop](#) for a given time period.*
- [Location](#) [getLocation](#) ()
- void [setLocation](#) ([Location](#) location)
- String [getDescription](#) ()
- void [setDescription](#) (String [description](#))

- String **getStopId** ()
- void **setStopId** (String [stopId](#))
- boolean **isCovered** ()
- void **setCovered** (boolean [covered](#))

### Protected Member Functions

- [Stop](#) (String [stopId](#), String [description](#), [Location](#) [location](#))  
*Instantiates a new [Stop](#) with all the mandatory fields.*

### Private Attributes

- String [stopId](#)  
*A unique identifier for this [Stop](#).*
- String [description](#)  
*A short text-based description of describing the [Stop](#) and its location.*
- [Location](#) [location](#)  
*The physical location of the [Stop](#).*
- boolean [covered](#)  
*Whether or not this [Stop](#) is protected by some sort of enclosure.*

## 5.75.1 Detailed Description

A point on a [Route](#) in which a [TransitVehicle](#) will stop to pick up and drop off passengers.

A [Stop](#) also is responsible for providing a set of the times in which the [TransitVehicle](#) will be at the [Stop](#).

A [Stop](#) is identified within the context of a single [Route](#). This means that two [Routes](#) may share the same physical [Stop location](#), but maintain different schedules.

## 5.75.2 Constructor & Destructor Documentation

### 5.75.2.1 [Stop](#) ( String [stopId](#), String [description](#), [Location](#) [location](#) ) [protected]

Instantiates a new [Stop](#) with all the mandatory fields.

#### Parameters

|                    |                              |
|--------------------|------------------------------|
| <i>stopId</i>      | The unique identifier        |
| <i>description</i> | The description              |
| <i>location</i>    | The <a href="#">Location</a> |

## 5.75.3 Member Function Documentation

### 5.75.3.1 Set<Date> getStopTimes ( Date *begin*, Date *end* )

Reports the expected times in which a [TransitVehicle](#) will be at the given [Stop](#) for a given time period.

#### Precondition

**begin** < **end**.

## Parameters

|              |  |
|--------------|--|
| <i>begin</i> | The start of the reporting time period. All <a href="#">Stop</a> Times returned will be on (or after) this time. If null, assume to be the current time. |
| <i>end</i>   | The end of the reporting time period. All <a href="#">Stop</a> Times returned will before this time.   |

## Returns

[Stop](#) Times associated with this [Stop](#) that satisfy the begin and end criteria.

## 5.75.4 Member Data Documentation

### 5.75.4.1 boolean covered [private]

Whether or not this [Stop](#) is protected by some sort of enclosure.

The type of enclosure required to constitute 'covered' defined by each [TransitProvider](#), but at a minimum there should be a roof protecting the immediate area before riders board the vehicle.

### 5.75.4.2 String description [private]

A short text-based description of describing the [Stop](#) and its location.

This could be an intersection:

- "18th Ave and 58th St." or a landmark/park/attraction:

"Como Zoo North Entrance" or other identifying text.

This description should be sufficient enough to allow a user to find the given [Stop](#) without necessarily needing the [Location](#) information.

### 5.75.4.3 String stopId [private]

A unique identifier for this [Stop](#).

In some cases, it could be a String representation of the [location](#) - or possibly the [description](#).

As a [Stop](#) is part of the [Route](#) Aggregate, this identifier needs only be unique within the context of a [Route](#).

## 5.76 TrackingAlertFactory Class Reference

The Alert Factory handles the creation of a user alert.

### Public Member Functions

- [TrackingAlertObserver](#) [createAlertObserver](#) ([TransitVehicle](#) vehicle)

### 5.76.1 Detailed Description

The Alert Factory handles the creation of a user alert.

The necessary values for an alert will be entered by a registered user from the BusBuddy User Interface. See [UserTrackingAlertObject](#) for input parameter details.

**Postcondition**

New user alert registered with a transit vehicle in the array list.


**5.76.2 Member Function Documentation****5.76.2.1 TrackingAlertObserver createAlertObserver ( TransitVehicle vehicle )**

1. Determine what type of tracking alert observer to create
1. Determine what rules are needed and add an Alert Specification to this alert. Configuration for alert logic will be obtained based on a configuration file.

**5.77 TrackingAlertObserver Class Reference**

Abstract class defining the methods for the tracking alert observer.

Inheritance diagram for TrackingAlertObserver:

**Package Functions**

- [AlertSpecification getSpec \(\)](#)  
*Return the specification to use to determine if a vehicle is in an alert range.*
- void [setSpec \(AlertSpecification spec\)](#)  
*Set the alert specification.*
- abstract void [updateAlert \(\)](#)  
*The observer pattern update method called from the subject [TransitVehicle](#) when a vehicle is determined to be in an alert range and a user needs to be notified.*

**Private Attributes**

- [UserTrackingAlertObject userAlertTrackingObject](#)  
*Value Object containing the items necessary for an alert.*
- [AlertSpecification specification](#)  
*The business logic specification of how to determine if an alert needs to be sent for a vehicle.*
- [AlertRequestController arc](#) = new [AlertRequestController\(\)](#)  
*Alert Module Controller called via a REST API processUserAlertRequest()*

**5.77.1 Detailed Description**

Abstract class defining the methods for the tracking alert observer.

**Precondition**

Vehicle is determined by [AlertSpecification](#) to within range

**Postcondition**

Alert request is sent to the [AlertService](#) Abstract class defining the methods for the tracking alert observer. This class calls alert module's alert controller via REST call to fetch necessary information.

**5.77.2 Member Function Documentation****5.77.2.1 [AlertSpecification](#) getSpec ( ) [package]**

Return the specification to use to determine if a vehicle is in an alert range.

**Return values**

|                                    |
|------------------------------------|
| <a href="#">AlertSpecification</a> |
|------------------------------------|

**5.77.2.2 void setSpec ( [AlertSpecification spec](#) ) [package]**

Set the alert specification.

**Parameters**

|             |   |
|-------------|---|
| <i>spec</i> | <a href="#">AlertSpecification</a> - the rules used by the subject to determine if an alert is necessary. |
|-------------|---|

**5.77.2.3 abstract void updateAlert ( ) [package], [pure virtual]**

The observer pattern update method called from the subject [TransitVehicle](#) when a vehicle is determined to be in an alert range and a user needs to be notified.


Alert notifications are actually sent using the [IAlertService](#)

Implemented in [TrackingLocationAlert](#), and [TrackingDelayAlert](#).

**5.78 TrackingAlertRequestModel Class Reference**

This model is a JSON representation of the request from Tracking module.

Inheritance diagram for TrackingAlertRequestModel:

**Additional Inherited Members****5.78.1 Detailed Description**

This model is a JSON representation of the request from Tracking module.


During implementation, any additional data that is needed can be added.



## 5.79 TrackingAlertService Class Reference

Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.

Inheritance diagram for TrackingAlertService:



### Public Member Functions

- [AlertResponseModel](#) [createAlert](#) ([AlertRequestModel](#) requestModel)  
{
- [AlertResponseModel](#) [updateAlert](#) ([Alert](#) alertModel)  
{
- boolean [sendAlert](#) ()  
{

### Additional Inherited Members

#### 5.79.1 Detailed Description

Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.

This handles all the alerts initiated by Tracking module.

#### 5.79.2 Member Function Documentation

##### 5.79.2.1 [AlertResponseModel](#) [createAlert](#) ( [AlertRequestModel](#) *requestModel* ) [virtual]

{

See Also

[AlertService::createAlert\(AlertRequestModel\)](#)

Implements [AlertService](#).

##### 5.79.2.2 boolean [sendAlert](#) ( ) [virtual]

{

See Also

[AlertService::sendAlert\(\)](#)

Implements [AlertService](#).

### 5.79.2.3 `AlertResponseModel` `updateAlert ( Alert alertModel )` [virtual]

{

See Also


[AlertService::updateAlert\(Alert\)](#)

Implements [AlertService](#).

## 5.80 TrackingDelayAlert Class Reference

Tracking Alert Observer implements the abstract tracking alert observer and provides the method to actually send an alert to a registered user that their bus is approaching their stop.

Inheritance diagram for TrackingDelayAlert:



### Public Member Functions

- void [updateAlert](#) ()

*Receives the notification indicating that a vehicle is in the alert range.*

### Additional Inherited Members

#### 5.80.1 Detailed Description

Tracking Alert Observer implements the abstract tracking alert observer and provides the method to actually send an alert to a registered user that their bus is approaching their stop.

#### Precondition

Vehicle is determined by [AlertSpecification](#) to within range

#### Postcondition

Alert request is sent to the [AlertService](#)

#### 5.80.2 Member Function Documentation

##### 5.80.2.1 `void updateAlert ( )` [virtual]

Receives the notification indicating that a vehicle is in the alert range.


Use the [AlertService](#) to contact the registered user.

Implements [TrackingAlertObserver](#).

## 5.81 TrackingLocationAlert Class Reference

Concrete implementation of the tracking alert observer.

Inheritance diagram for TrackingLocationAlert:



### Public Member Functions

- [TrackingLocationAlert](#) ([TransitVehicle](#) vehicle)  
*Tracking Location Alert constructor.*
- void [updateAlert](#) ()  
*Vehicle is in vicinity where user registered to be notified, calls Alert Service.*

### Additional Inherited Members

#### 5.81.1 Detailed Description

Concrete implementation of the tracking alert observer.

The subject calls the update alert for registered vehicles.

#### 5.81.2 Constructor & Destructor Documentation

##### 5.81.2.1 TrackingLocationAlert ( [TransitVehicle](#) vehicle )

Tracking Location Alert constructor.

Associates user information with vehicle to monitor.

#### Parameters

|                |  |
|----------------|--|
| <i>vehicle</i> | <a href="#">TransitVehicle</a> Vehicle to add alert monitoring   |
| <i>alert</i>   | - <a href="#">TrackingLocationAlert</a> User contact details and vehicle location indicating when user wants to receive alert. |

## 5.82 TrackingResponseModel Class Reference

This is a basic tracking response model that is returned for every tracking related request.

### Public Member Functions

- String [formatJSONResponse](#) ()  
*Formats output responses and requests from the tracking module.*
- [VehicleObject](#) [convertJSONVehicleInput](#) ()  
*Converts input JSON formatted vehicle registration request to internal vehicle object.*
- [UserTrackingAlertObject](#) [convertJSONAlertInput](#) ()  
*Convert input JSON formatted alert request from user interface to internal user alert object.*

## Private Attributes

- String `status`  
*Status message for the tracking request.*
- String `errorMessage`  
*Any error message if the tracking request fails.*

### 5.82.1 Detailed Description

This is a basic tracking response model that is returned for every tracking related request.

Additional parameters can be added as needed during implementation phase. This model is responsible for verify that all data received is within range before returning local object.

### 5.82.2 Member Function Documentation

#### 5.82.2.1 `UserTrackingAlertObject convertJSONAlertInput ( )`

Convert input JSON formatted alert request from user interface to internal user alert object.

##### Returns

`UserTrackingAlertObject` values

#### 5.82.2.2 `VehicleObject convertJSONVehicleInput ( )`

Converts input JSON formatted vehicle registration request to internal vehicle object.

##### Returns

`VehicleObject` created from user registration.

#### 5.82.2.3 `String formatJSONResponse ( )`

Formats output responses and requests from the tracking module.


##### Returns

String containing response

## 5.83 TrackingServiceController Class Reference

Tracking service controller is the concrete implementation of the tracking service interface.

Inheritance diagram for TrackingServiceController:



## Public Member Functions

- void [registerVehicleOnRoute](#) (URL url, int gpsDeviceID)  
*Create a vehicle when a user registers a vehicle on a route through the user interface.*
- void [unregisterVehicleFromRoute](#) (String url, int gpsDeviceID)  
*Remove a vehicle from the vehicle repository when the vehicle is no longer in service.*
- void [addUserTrackingAlert](#) ([UserTrackingAlertObject](#) utao)  
*Add a new user alert.*
- void [startTrackingController](#) ()  
*Gets a list of saved alerts from the [AlertService](#) and restores them on tracking module startup.*
- [GPSLocationObject](#) [getTransitVehicleLocation](#) (int gpsDeviceID)  
*Find locations of the specified GPS device ID.*

## Package Attributes

- [TransitVehicleFactory](#) [transitFactory](#) = new [TransitVehicleFactory](#)()  
*Logic for creating transit vehicles.*
- [TrackingAlertFactory](#) [alertFactory](#) = new [TrackingAlertFactory](#)()  
*Logic for creating new user alerts.*

### 5.83.1 Detailed Description

Tracking service controller is the concrete implementation of the tracking service interface.

Provides the tracking functionality to other Bus Buddy modules and ties vehicle location to registered user alerts. The tracking service controller accepts REST requests from the User Interface module, the Alert Module

### 5.83.2 Member Function Documentation

#### 5.83.2.1 void addUserTrackingAlert ( [UserTrackingAlertObject](#) utao )

Add a new user alert.

Necessary inputs are entered by the user on the User Interface and made available to the Tracking Controller through [UserTrackingAlertObject](#)

1. Verify that there is a vehicle registered on the route requested by the user.
2. Get a list of vehicles on the route from the vehicle repository
3. Create a new Tracking Alert Observer
4. Add an alert specification containing the business rules to determine if bus is in alert range.
5. Register the user alert observer to the vehicles

Find the vehicles registered on this route

Create an alert for this user request and register this alert with the vehicle(s) the user is watching.

Implements [ITrackingService](#).

#### 5.83.2.2 void registerVehicleOnRoute ( URL url, int gpsDeviceID )

Create a vehicle when a user registers a vehicle on a route through the user interface.

Accepts a [VehicleObject](#) JSON

Implements [ITrackingService](#).

### 5.83.2.3 void unregisterVehicleFromRoute ( String url, int gpsDeviceID )

Remove a vehicle from the vehicle repository when the vehicle is no longer in service.

#### Parameters


|                    |  |
|--------------------|--|
| <i>url</i>         | - URL transit company and route information for this vehicle                                 |
| <i>gpsDeviceID</i> | - integer GPS device ID installed in vehicle, must match the ID the vehicle registered with. |

Implements [ITrackingService](#).

## 5.84 TransitAlertRequestModel Class Reference

This model is a JSON representation of the request from Transit module.

Inheritance diagram for TransitAlertRequestModel:



### Additional Inherited Members

#### 5.84.1 Detailed Description


This model is a JSON representation of the request from Transit module.

During implementation, any additional data that is needed can be added.

## 5.85 TransitAlertService Class Reference

Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.

Inheritance diagram for TransitAlertService:



### Public Member Functions

- [AlertResponseModel](#) [createAlert](#) ([AlertRequestModel](#) requestModel)
- {
- [AlertResponseModel](#) [updateAlert](#) ([Alert](#) alertModel)
- {
- boolean [sendAlert](#) ()
- {

## Additional Inherited Members

### 5.85.1 Detailed Description

Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.

This handles all the alerts initiated by Transit module.

### 5.85.2 Member Function Documentation

#### 5.85.2.1 `AlertResponseModel createAlert ( AlertRequestModel requestModel )` [virtual]

{

See Also

[AlertService::createAlert\(AlertRequestModel\)](#)

Implements [AlertService](#).

#### 5.85.2.2 `boolean sendAlert ( )` [virtual]

{

See Also

[AlertService::sendAlert\(\)](#)

Implements [AlertService](#).

#### 5.85.2.3 `AlertResponseModel updateAlert ( Alert alertModel )` [virtual]

{

See Also


[AlertService::updateAlert\(Alert\)](#)

Implements [AlertService](#).

## 5.86 TransitFeed Interface Reference

A [TransitFeed](#) is an abstraction over a service or set of services that provide information about [Routes](#).

Inheritance diagram for TransitFeed:



## Public Member Functions

- [Route](#) `getRoute` (String *routeId*)  
*Gets a [Route](#) by its unique identifier.*
- Set< [Route](#) > `getRoutes` ([Location](#) *pickup*, [Location](#) *dropoff*, int *distance*)  
*Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.*

### 5.86.1 Detailed Description

A [TransitFeed](#) is an abstraction over a service or set of services that provide information about [Routes](#).

This differs from the [TransitService](#) interface in that a [TransitFeed](#) does not expose provenance information such as the [TransitService#getTransitInfo](#) method.

Because of this, a single [TransitService](#) (or [TransitProvider](#)) could use more than one [TransitFeed](#) to expose their Transit data. For example, a [TransitProvider](#) could utilize two different database storage schemes, each one represented as a separate [TransitFeed](#), and then aggregate the two into one [TransitService](#).

### 5.86.2 Member Function Documentation

#### 5.86.2.1 [Route](#) `getRoute` ( String *routeId* )

Gets a [Route](#) by its unique identifier.

##### Precondition

**routeId** is not null or blank.

##### Postcondition

The [Route](#) is returned if the **routeId** is found, else null.

##### Parameters

|                |  |
|----------------|--|
| <i>routeId</i> | The unique identifier of the <a href="#">Route</a> |
|----------------|--|

##### Returns

The matching [Route](#), or null if not found

Implemented in [GoogleTransitServiceAdapter](#), and [PersistedTransitFeed](#).

#### 5.86.2.2 Set<[Route](#)> `getRoutes` ( [Location](#) *pickup*, [Location](#) *dropoff*, int *distance* )

Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.

##### Precondition

**pickup** is not null or blank.  
**dropoff** is not null or blank.  
**distance** is non-negative.



## Parameters

|                 |  |
|-----------------|--|
| <i>pickup</i>   | The requested pickup <a href="#">Location</a>  |
| <i>pickup</i>   | The requested dropoff <a href="#">Location</a>   |
| <i>distance</i> | The distance (in miles) that each <a href="#">Route</a> can deviate from the requested <b>pickup</b> or <b>dropoff Location</b> . For each <a href="#">Route</a> returned, neither its start or end <a href="#">Location</a> can differ from the requested <b>pickup</b> or <b>dropoff Location</b> by more than the value of the <b>distance</b> parameter. |

## Returns

The matching [Routes](#)

Implemented in [GoogleTransitServiceAdapter](#), and [PersistedTransitFeed](#).

## 5.87 TransitInfo Class Reference

An immutable Value Object describing metadata about a [TransitService](#).

### Public Member Functions

- String **getTransitAuthorityName** ()
- void **setTransitAuthorityName** (String [transitAuthorityName](#))
- URL **getWebsite** ()
- void **setWebsite** (URL [website](#))
- byte[] **getLogo** ()
- void **setLogo** (byte[] [logo](#))

### Private Attributes

- String [transitAuthorityName](#)  
*The name of the governing body of the associated [TransitService](#).*
- URL [website](#)  
*A resolvable URL reference to the official Transit Authority web site.*
- byte[] [logo](#)  
*A byte array of the Transit Authority logo, if any.*

### 5.87.1 Detailed Description

An immutable Value Object describing metadata about a [TransitService](#).

Each [TransitService](#) is required to supply the following information.

### 5.87.2 Member Data Documentation

#### 5.87.2.1 byte [] logo [private]

A byte array of the Transit Authority logo, if any.

Allowed formats are unspecified, as image format parsing/conversion is beyond the scope of this project.

### 5.87.2.2 String transitAuthorityName [private]

The name of the governing body of the associated [TransitService](#).

This can be a Federal, State, or Local governing body responsible for the transit activity associated with the [Transit-Service](#).

### 5.87.2.3 URL website [private]

A resolvable URL reference to the official Transit Authority web site.

Where possible, this site should contain contact info and links to policy, specialized transit requirements, or other information.

## 5.88 TransitProvider Class Reference

A [TransitProvider](#) is a description of a company or organization that is the producer of public transportation services.

### Private Attributes

- String [providerId](#)  
*A unique identifier that globally identifies this [TransitProvider](#).*
- Set< [TransitProviderObserver](#) > [transitProviderObserver](#)  
*An Observer Pattern mechanism to alertlink [TransitProviderObserver](#)s of changes in [Route](#) service;.*
- String [name](#)  
*A text description of the [TransitProvider](#).*
- abstract void [fireRouteDisruptionEvent](#) ()  
*This method is called internally by the [TransitProvider](#) to fire a [RouteDisruptionEvent](#).*
- String [getProviderId](#) ()
- void [setProviderId](#) (String [providerId](#))
- String [getName](#) ()
- void [setName](#) (String [name](#))
- void [registerObserver](#) ([TransitProviderObserver](#) [transitProviderObserver](#))  
*Register the provided [TransitProviderObserver](#) as an observer to this class.*
- void [unregisterObserver](#) ([TransitProviderObserver](#) [transitProviderObserver](#))  
*Unregister the provided [TransitProviderObserver](#) as an observer to this class.*

### 5.88.1 Detailed Description

A [TransitProvider](#) is a description of a company or organization that is the producer of public transportation services.

Observers may subscribe to a [TransitProvider](#) to receive updates on [Route](#) disruptions, such as changes in service availability or schedule.

### 5.88.2 Member Function Documentation

#### 5.88.2.1 abstract void fireRouteDisruptionEvent ( ) [protected],[pure virtual]

This method is called internally by the [TransitProvider](#) to fire a [RouteDisruptionEvent](#).

[TransitProvider](#) subclasses will determine when these Events are fired – for example, if a [TransitProvider](#) has scheduled maintenance days, or known outages due to mechanical breakdown.

After a [RouteDisruptionEvent](#) is fired, this class will perform the following:

- Notify all [TransitProviderObservers](#) of the disruption with the updated [Route](#). This updated [Route](#) should include all necessary [Detour](#) information.

#### 5.88.2.2 void registerObserver ( [TransitProviderObserver](#) *transitProviderObserver* )

Register the provided [TransitProviderObserver](#) as an observer to this class.

##### Parameters

|                                 |  |
|---------------------------------|--|
| <i>transitProvider-Observer</i> | The <a href="#">TransitProviderObserver</a> to unregister. |
|---------------------------------|--|

#### 5.88.2.3 void unregisterObserver ( [TransitProviderObserver](#) *transitProviderObserver* )

Unregister the provided [TransitProviderObserver](#) as an observer to this class.

##### Parameters

|                                 |  |
|---------------------------------|--|
| <i>transitProvider-Observer</i> | The <a href="#">TransitProviderObserver</a> to unregister. |
|---------------------------------|--|

### 5.88.3 Member Data Documentation

#### 5.88.3.1 String name [private]

A text description of the [TransitProvider](#).

This is the text that will be displayed on guides, [Route](#) maps, and advertisements.

#### 5.88.3.2 String providerId [private]


A unique identifier that globally identifies this [TransitProvider](#).

The actual identifier type is unspecified and left to implementations. It may be the same as the [name](#), if that is sufficient to provide uniqueness.

## 5.89 TransitProviderObserver Interface Reference

An asynchronous update interface for receiving notifications about [TransitProvider](#) [Route](#) disruptions.

Inheritance diagram for TransitProviderObserver:



### Public Member Functions

- void [handleRouteDisruptionEvent](#) ([RouteDisruptionEvent](#) routeDisruptionEvent)  
*This method is called when a [TransitProvider](#) fires a [RouteDisruptionEvent](#) indicating a disruption in normal services and/or schedules.*

### 5.89.1 Detailed Description

An asynchronous update interface for receiving notifications about [TransitProvider Route](#) disruptions.

### 5.89.2 Member Function Documentation

#### 5.89.2.1 void handleRouteDisruptionEvent ( [RouteDisruptionEvent](#) *routeDisruptionEvent* )

This method is called when a [TransitProvider](#) fires a [RouteDisruptionEvent](#) indicating a disruption in normal services and/or schedules.

#### Parameters


|                              |  |
|------------------------------|--|
| <i>routeDisruption-Event</i> | The <a href="#">Route</a> Disruption Event |
|------------------------------|--|

Implemented in [ITeamTransitServiceController](#).

## 5.90 TransitService Interface Reference

The [TransitService](#) is an interface to get [Route/Fare/Detour](#) information from a [TransitProvider](#).

Inheritance diagram for TransitService:



### Public Member Functions

- [Route](#) [getRoute](#) (String *routeId*) throws [BusBuddyNotFoundException](#)  
*Gets a [Route](#) by its unique identifier.*
- Set< [Route](#) > [getRoutes](#) ([Location](#) pickup, [Location](#) dropoff, int distance)  
*Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.*
- [TransitInfo](#) [getTransitInfo](#) ()  
*Gets metadata about the Transit Authority providing the information retrieved from this service.*
- URL [getServiceURL](#) ()  
*The URL that uniquely identifies this [TransitService](#).*

### 5.90.1 Detailed Description

The [TransitService](#) is an interface to get [Route/Fare/Detour](#) information from a [TransitProvider](#).

This service will provide a consistent interface for the application logic to query to get this information.

### 5.90.2 Member Function Documentation

#### 5.90.2.1 [Route](#) [getRoute](#) ( String *routeId* ) throws [BusBuddyNotFoundException](#)

Gets a [Route](#) by its unique identifier.

## Parameters

|                |  |
|----------------|--|
| <i>routeId</i> | The unique identifier of the <a href="#">Route</a> |
|----------------|--|

## Returns

The matching [Route](#)

## Precondition

**routeId** is not null or blank.

## Postcondition

The [Route](#) is returned if the **routeId** is found, else null.

## Exceptions

|                                   |   |
|-----------------------------------|---|
| <i>BusBuddyNotFound-Exception</i> | Thrown if the <a href="#">Route</a> with the given <b>routeId</b> is not found. |
|-----------------------------------|---|

Implemented in [ITeamTransitServiceController](#).

#### 5.90.2.2 Set<[Route](#)> getRoutes ( [Location](#) pickup, [Location](#) dropoff, int distance )

Gets all available [Routes](#) that match a **pickup** or **dropoff** [Location](#) by not more than a given **distance**.

## Parameters

|                 |  |
|-----------------|--|
| <i>pickup</i>   | The requested dropoff <a href="#">Location</a>   |
| <i>dropoff</i>  | the dropoff  |
| <i>distance</i> | The distance (in miles) that each <a href="#">Route</a> can deviate from the requested <b>pickup</b> or <b>dropoff</b> |

## Returns

The matching [Routes](#)

## Precondition

**pickup** is not null or blank.

**dropoff** is not null or blank.

**distance** is non-negative. [Location](#). For each [Route](#) returned, neither its start or end [Location](#) can differ from the requested **pickup** or **dropoff** [Location](#) by more than the value of the **distance** parameter.

Implemented in [ITeamTransitServiceController](#).

#### 5.90.2.3 URL getServiceURL ( )

The URL that uniquely identifies this [TransitService](#).

In a REST environment, this might be the root of the REST API path.

## Returns

The URL of this service

Implemented in [ITeamTransitServiceController](#).

#### 5.90.2.4 TransitInfo getTransitInfo ( )

Gets metadata about the Transit Authority providing the information retrieved from this service.

##### Returns


The [TransitInfo](#) of the Transit Authority of this service.

Implemented in [ITeamTransitServiceController](#).

## 5.91 TransitVehicle Class Reference

Abstract transit vehicle class contains the common data for all types of vehicles and the Subject GPS Tracking and the GPS observer to receive GPS location updates.

Inheritance diagram for TransitVehicle:



### Public Member Functions

- abstract void [registerTrackingAlert](#) ([TrackingAlertObserver](#) ao)  
*Transit Vehicle is also the subject for tracking user subscribed alerts.*
- abstract void **unregisterTrackingAlert** ([TrackingAlertObserver](#) ao)
- void [checkForAlerts](#) ()  
*The Observer Pattern Subject notify method extended to limit the number of alerts issued by check conditions prior to actually triggering an alert.*
- void [triggerAlert](#) ([TrackingAlertObserver](#) ao)  
*The conditions in the Alert Specification were met, send update to the observer.*
- void [addAlertSpecification](#) ()  
*Add an alert specification [AlertSpecification](#) to this vehicle.*
- void [removeAlertSpecification](#) ()  
*Remove an alert specification from a transit vehicle.*
- String [toString](#) ()  
*Provide a generic method to output Transit Vehicle information.*

### Private Attributes

- [VehicleObject](#) vehicle  
*Value Object holding vehicle details.*
- [GPSLocationObserver](#) gpsObserver  
*Observer that update the GPS coordinates of the vehicle as they are received.*
- ArrayList< [AlertSpecification](#) > alertSpecification  
*Rules to determine if this vehicle is in an alert range.*

#### 5.91.1 Detailed Description

Abstract transit vehicle class contains the common data for all types of vehicles and the Subject GPS Tracking and the GPS observer to receive GPS location updates.

### 5.91.2 Member Function Documentation

#### 5.91.2.1 void addAlertSpecification ( )

Add an alert specification [AlertSpecification](#) to this vehicle.

A vehicle may have these alerts:

1. one or more users registered for location based alerts
2. transit company registered for delay alerts, or loss of GPS signal alerts

#### 5.91.2.2 void checkForAlerts ( )

The Observer Pattern Subject notify method extended to limit the number of alerts issued by check conditions prior to actually triggering an alert.

The checkForAlerts method uses [AlertSpecification](#) to determine if the observing vehicle should be notified.

## 5.92 TransitVehicleFactory Class Reference

Transit Vehicle Factory encapsulates the complexity of creating a new vehicle.

### Public Member Functions

- [TransitVehicle createTransitVehicle](#) (URL url, int gpsDeviceID)

### Protected Member Functions

- int [getVehicleGPSDeviceID](#) (URL url)  
*Retrieve the GPS Device ID from repository of vehicles registered for route identified by type and URL.*

### Private Member Functions

- int [getGPSTypeFromURL](#) (URL url)  
*Parse the input URL for information about connecting to GPS device in this vehicle.*

### 5.92.1 Detailed Description

Transit Vehicle Factory encapsulates the complexity of creating a new vehicle.

Inputs are obtained from the user interface when a vehicle is registered by a user.

### 5.92.2 Member Function Documentation

#### 5.92.2.1 TransitVehicle createTransitVehicle ( URL url, int gpsDeviceID )

Determine what type of vehicle is needed.

Determine what type of GPS tracking is available on this vehicle and register with the appropriate [GPSLocation-Tracking](#) service.

#### 5.92.2.2 `int getGPSTypeFromURL ( URL url ) [private]`

Parse the input URL for information about connecting to GPS device in this vehicle.

##### Parameters

|                  |   |
|------------------|---|
| <code>url</code> | - URL from User Interface, contains GPS connection information. |
|------------------|---|

##### Returns

integer type of GPS Device Commercial Service, GPS Pusher, or GPS Puller.

#### 5.92.2.3 `int getVehicleGPSDeviceID ( URL url ) [protected]`

Retrieve the GPS Device ID from repository of vehicles registered for route identified by type and URL.

##### Parameters

|                  |                                       |
|------------------|---------------------------------------|
| <code>url</code> | - URL identifying the transit company |
|------------------|---------------------------------------|

##### Returns

integer GPS Device ID

## 5.93 Trip Class Reference

A [Trip](#) is considered an ordered collection of [Routes](#) going from a starting point to an ending point.

### Public Member Functions

- List< [Route](#) > **getRoutes** ()
- void **setRoutes** (List< [Route](#) > routes)

### Protected Member Functions

- [Trip](#) (List< [Route](#) > routes)  
*Instantiates a new [Trip](#) with the appropriate [Routes](#).*

### Private Attributes

- List< [Route](#) > routes  
*The ordered collection of [Routes](#) that when combined make a navigable [Trip](#).*

#### 5.93.1 Detailed Description

A [Trip](#) is considered an ordered collection of [Routes](#) going from a starting point to an ending point.

A [Trip](#) can be thought of as a composition of Routes, and the [TripService](#) is the service that composes them.

##### Invariant

`routes.size() > 0`



### 5.93.2 Constructor & Destructor Documentation

#### 5.93.2.1 Trip ( List< Route > routes ) [protected]

Instantiates a new [Trip](#) with the appropriate [Routes](#).

Precondition

`routes.size() > 0`

Parameters

|                     |   |
|---------------------|---|
| <code>routes</code> | The <a href="#">Routes</a> of this <a href="#">Trip</a> |
|---------------------|---|

## 5.94 TripInformation Class Reference

This model stores the information about a trip as a value object.

### Public Member Functions

- List< String > [getRouteIds](#) ()  
*Provides a list of routeId in the [Trip](#) model.*
- [Trip](#) [getTripData](#) ()
- void [setTripData](#) ([Trip](#) tripData)
- Date [getLastModifiedDate](#) ()
- void [setLastModifiedDate](#) (Date lastModifiedDate)
- Date [getCreatedDate](#) ()
- void [setCreatedDate](#) (Date createdDate)

### Private Attributes

- [Trip](#) tripData  
*Necessary data about a trip.*
- Date [lastModifiedDate](#)  
*Last date when the trip Information was modified or updated.*
- Date [createdDate](#)  
*Date when the actual trip was created.*

### 5.94.1 Detailed Description

This model stores the information about a trip as a value object.

Hence, we have created and last modified date to track the freshness of data. Currently, the [Trip](#) is referring to the model in Trip module. But we expect this to be stored as a value object and during implementation we can create a copy of its model for alert module.

### 5.94.2 Member Function Documentation

#### 5.94.2.1 List<String> getRouteIds ( )

Provides a list of routeId in the [Trip](#) model.

Returns

### 5.94.3 Member Data Documentation

#### 5.94.3.1 Trip tripData [private]

Necessary data about a trip.

This contains a collection of routes. {


See Also

Trip}

## 5.95 TripService Interface Reference

A Service to calculate a collection of [Routes](#), or a [Trip](#), allowing for a continuous transit path from a start [Location](#) to an end [Location](#).

Inheritance diagram for TripService:



### Public Member Functions

- [Trip](#) `calculateTrip` ([Location](#) start, [Location](#) end)  
Calculate an optimal [Trip](#) given a **start** [Location](#) and an **end** [Location](#).

#### 5.95.1 Detailed Description

A Service to calculate a collection of [Routes](#), or a [Trip](#), allowing for a continuous transit path from a start [Location](#) to an end [Location](#).

### 5.95.2 Member Function Documentation

#### 5.95.2.1 Trip calculateTrip ( Location start, Location end )

Calculate an optimal [Trip](#) given a **start** [Location](#) and an **end** [Location](#).

Parameters

|              |  |
|--------------|--|
| <i>start</i> | The requested start <a href="#">Location</a> of the <a href="#">Trip</a> . |
| <i>end</i>   | The requested end <a href="#">Location</a> of the <a href="#">Trip</a> .   |

Returns

The calculated [Trip](#)

Implemented in [ITeamTripServiceController](#).

## 5.96 User Class Reference

This class represents a single user of the system, and all of the state data associated with that user.

### Public Member Functions

- `int getUserId ()`  
*This retrieves the user identifier.*
- `String getUsername ()`  
*This retrieves the user's username.*
- `boolean isForcePasswordChange ()`  
*This checks to see if the password is in a state where it needs to be changed.*
- `String getFirstName ()`  
*This retrieves the user's first name.*
- `void setFirstName (String firstName)`  
*This sets the user's first name.*
- `String getEmail ()`  
*This retrieves the user's e-mail.*
- `void setEmail (String email)`  
*This sets the user's e-mail.*
- `Short getCountryCode ()`  
*This gets the user's country code.*
- `void setCountryCode (Short countryCode)`  
*This sets the user's country code.*
- `String getMobile ()`  
*This gets the user's mobile phone number.*
- `void setMobile (String mobile)`  
*This sets the user's mobile phone number.*
- `UserType getUserType ()`  
*This retrieves the type of the current user.*
- `void setUserType (UserType userType)`  
*This sets the type of the current user.*

### Protected Member Functions

- `User (int userId, String username)`  
*This constructs a new `User` object.*
- `String getPasswordHash ()`  
*This retrieves the password hash for this user.*
- `void setPasswordHash (String passwordHash)`  
*This sets the password hash for this user.*
- `void setForcePasswordChange (boolean forcePasswordChange)`  
*This sets the state indicating if the password is in a state where it needs to be changed.*

## Private Attributes

- final int **userId**
- final String **username**
- String **password**
- String **passwordHash**
- boolean **forcePasswordChange**
- String **firstName**
- String **email**
- Short **countryCode**
- String **mobile**
- [UserType](#) **userType**

### 5.96.1 Detailed Description

This class represents a single user of the system, and all of the state data associated with that user.

The user should already exist in the database before instantiating this object.

### 5.96.2 Constructor & Destructor Documentation

#### 5.96.2.1 `User ( int userId, String username )` [protected]

This constructs a new [User](#) object.

It is not visible to clients, as [User](#) objects should only be constructed through the [UserRepository](#).

#### Parameters

|                 |  |
|-----------------|--|
| <i>userId</i>   | This is the user's unique identifier, which should match the database. |
| <i>username</i> | This is the user's username. It cannot be changed.                     |

### 5.96.3 Member Function Documentation

#### 5.96.3.1 `Short getCountryCode ( )`

This gets the user's country code.

#### Returns

user's country code

#### 5.96.3.2 `String getEmail ( )`

This retrieves the user's e-mail.

#### Returns

user's e-mail

#### 5.96.3.3 `String getFirstName ( )`

This retrieves the user's first name.

**Returns**

user's first name

**5.96.3.4 String getMobile ( )**

This gets the user's mobile phone number.

**Postcondition**

The mobile phone number returned should be a String containing only digits.

**Returns**

user's mobile phone number

**5.96.3.5 String getPasswordHash ( ) [protected]**

This retrieves the password hash for this user.

It has decreased visibility and is ignored when serializing responses, as this data should not be shared beyond this module.

**Returns**

hash of the user's password

**5.96.3.6 int getUserId ( )**

This retrieves the user identifier.

**Returns**

user identifier

**5.96.3.7 String getUsername ( )**

This retrieves the user's username.

**Returns**

username

**5.96.3.8 UserType getUserType ( )**

This retrieves the type of the current user.

**Returns**

user type

#### 5.96.3.9 boolean isForcePasswordChange ( )

This checks to see if the password is in a state where it needs to be changed.

##### Returns

true if it is, false if it is not

#### 5.96.3.10 void setCountryCode ( Short *countryCode* )

This sets the user's country code.

##### Parameters

|                    |                     |
|--------------------|---------------------|
| <i>countryCode</i> | user's country code |
|--------------------|---------------------|

#### 5.96.3.11 void setEmail ( String *email* )

This sets the user's e-mail.

##### Parameters

|              |               |
|--------------|---------------|
| <i>email</i> | user's e-mail |
|--------------|---------------|

#### 5.96.3.12 void setFirstName ( String *firstName* )

This sets the user's first name.

##### Parameters

|                  |                   |
|------------------|-------------------|
| <i>firstName</i> | user's first name |
|------------------|-------------------|

#### 5.96.3.13 void setForcePasswordChange ( boolean *forcePasswordChange* ) [protected]

This sets the state indicating if the password is in a state where it needs to be changed.

This is ignored during deserialization, as it should never be set from outside this module. it is never

##### Parameters

|                             |   |
|-----------------------------|---|
| <i>forcePassword-Change</i> | true if it should be set, false if it should be cleared |
|-----------------------------|---|

#### 5.96.3.14 void setMobile ( String *mobile* )

This sets the user's mobile phone number.

##### Precondition

The mobile parameter should be a String containing only digits.

## Parameters

|               |                            |
|---------------|----------------------------|
| <i>mobile</i> | user's mobile phone number |
|---------------|----------------------------|

5.96.3.15 void setPasswordHash ( String *passwordHash* ) [protected]

This sets the password hash for this user.

It has decreased visibility and is ignored when deserializing requests, as this data should not be set outside this module.

## Parameters

|                     |                             |
|---------------------|-----------------------------|
| <i>passwordHash</i> | hash of the user's password |
|---------------------|-----------------------------|

5.96.3.16 void setUserType ( UserType *userType* )

This sets the type of the current user.


## Parameters

|                 |           |
|-----------------|-----------|
| <i>userType</i> | user type |
|-----------------|-----------|

## 5.97 UserAlertRequestModel Class Reference

This model is a JSON representation of the request from User module.

Inheritance diagram for UserAlertRequestModel:



### Additional Inherited Members

#### 5.97.1 Detailed Description


This model is a JSON representation of the request from User module.

During implementation, any additional data that is needed can be added.

## 5.98 UserAlertService Class Reference

Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.

Inheritance diagram for UserAlertService:



## Public Member Functions

- [AlertResponseModel](#) [createAlert](#) ([AlertRequestModel](#) requestModel)
- {
- [AlertResponseModel](#) [updateAlert](#) ([Alert](#) alertModel)
- {
- boolean [sendAlert](#) ()
- {

## Additional Inherited Members

### 5.98.1 Detailed Description

Extends [AlertService](#) and provides CRUD methods to operate on alerts as well as sends alerts to execute via appropriate strategy.

This handles all the alerts initiated by User module.

### 5.98.2 Member Function Documentation

#### 5.98.2.1 [AlertResponseModel](#) [createAlert](#) ( [AlertRequestModel](#) *requestModel* ) [virtual]

{

See Also

[AlertService::createAlert\(AlertRequestModel\)](#)

Implements [AlertService](#).

#### 5.98.2.2 boolean [sendAlert](#) ( ) [virtual]

{

See Also

[AlertService::sendAlert\(\)](#)

Implements [AlertService](#).

#### 5.98.2.3 [AlertResponseModel](#) [updateAlert](#) ( [Alert](#) *alertModel* ) [virtual]

{

See Also

[AlertService::updateAlert\(Alert\)](#)

Implements [AlertService](#).



## 5.99 UserFavoritesList Class Reference

This class ties a `userId` to that user's ordered list of favorites.

### Public Member Functions

- [UserFavoritesList](#) (int `userId`)  
*This creates a new [UserFavoritesList](#) object.*
- int [getUserId](#) ()  
*This gets the `userId` associated with this favorites list.*
- List< [FavoriteTransitService](#) > [getFavoriteTransitServices](#) ()  
*This retrieves the list of favorite transit services for this user.*
- void [setFavoriteTransitServices](#) (List< [FavoriteTransitService](#) > `favoriteTransitServices`)  
*This sets the ordered list of favorite transit services for this user.*

### Private Attributes

- final int **`userId`**
- List< [FavoriteTransitService](#) > **`favoriteTransitServices`**

#### 5.99.1 Detailed Description

This class ties a `userId` to that user's ordered list of favorites.

#### 5.99.2 Constructor & Destructor Documentation

##### 5.99.2.1 UserFavoritesList ( int `userId` )

This creates a new [UserFavoritesList](#) object.

Once created, the `userId` cannot be modified.

#### Parameters

|                     |  |
|---------------------|--|
| <code>userId</code> | <code>userId</code> to link this favorites object to |
|---------------------|--|

#### 5.99.3 Member Function Documentation

##### 5.99.3.1 List<[FavoriteTransitService](#)> [getFavoriteTransitServices](#) ( )

This retrieves the list of favorite transit services for this user.

#### Returns

list of favorite transit services

##### 5.99.3.2 int [getUserId](#) ( )

This gets the `userId` associated with this favorites list.

#### Returns

`userId`

### 5.99.3.3 void setFavoriteTransitServices ( List< FavoriteTransitService > favoriteTransitServices )

This sets the ordered list of favorite transit services for this user.

#### Parameters

|                                |             |
|--------------------------------|-------------|
| <i>favoriteTransitServices</i> | list to use |
|--------------------------------|-------------|

## 5.100 UserFavoritesRepository Class Reference

This class is responsible for handling database access for favorites, and to persist and retrieve [UserFavoritesList](#) objects.

### Protected Member Functions

- [UserFavoritesList](#) [getFavorites](#) (int *userId*) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method retrieves the [UserFavoritesList](#) object for a given user.*
- void [updateFavorites](#) (int *userId*, [UserFavoritesList](#) *favorites*) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method updates the [UserFavoritesList](#) object for a given user.*

### 5.100.1 Detailed Description

This class is responsible for handling database access for favorites, and to persist and retrieve [UserFavoritesList](#) objects.

### 5.100.2 Member Function Documentation

#### 5.100.2.1 [UserFavoritesList](#) [getFavorites](#) ( int *userId* ) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#) [protected]

This method retrieves the [UserFavoritesList](#) object for a given user.

#### Precondition

The *userId* passed in must have already saved favorites.

#### Parameters

|               |   |
|---------------|---|
| <i>userId</i> | <a href="#">User</a> to retrieve favorites for. |
|---------------|---|

#### Returns

Favorites object for the *userId* that was passed in.

#### Exceptions

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.                        |
| <i>BusBuddyNotFoundException</i> | This exception is thrown if no data has been saved yet, or no such user exists. |

5.100.2.2 void updateFavorites ( int *userId*, UserFavoritesList *favorites* ) throws BusBuddyInternalException, BusBuddyNotFoundException [protected]

This method updates the UserFavoritesList object for a given user.

It creates it if it doesn't exist, and overwrites it if it does.

#### Precondition

The userId must be valid.

#### Parameters

|                  |                            |
|------------------|----------------------------|
| <i>userId</i>    | User to set favorites for. |
| <i>favorites</i> | Favorites to set.          |


#### Exceptions

|                           |  |
|---------------------------|--|
| BusBuddyInternalException | This exception is thrown when there is a database error. |
| BusBuddyNotFoundException | This exception is thrown if no such user exists.         |

## 5.101 UserFavoritesService Interface Reference

This is the generic BusBuddy UserFavoritesService interface.

Inheritance diagram for UserFavoritesService:



#### Public Member Functions

- UserFavoritesList readFavorites (String sessionToken) throws BusBuddyException  
*This method retrieves the UserFavoritesList object for the current user of a given session.*
- void saveFavorites (String sessionToken, UserFavoritesList favorites) throws BusBuddyException  
*This method updates the UserFavoritesList object for a given user.*

### 5.101.1 Detailed Description

This is the generic BusBuddy UserFavoritesService interface.

This interface contains methods dealing with user favorites. It is one of three interfaces that a user module implementation must implement. It can be implemented as a service or as a service client.

Every method call here will (besides createUser) will result in the session's expiration time being updated due to activity on the session.

### 5.101.2 Member Function Documentation

#### 5.101.2.1 `UserFavoritesList readFavorites ( String sessionToken )` throws `BusBuddyException`

This method retrieves the `UserFavoritesList` object for the current user of a given session.

##### Precondition

The `userId` linked to the session must have already saved favorites.

##### Parameters

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | <code>Session</code> whose user favorites will be retrieved for. |
|---------------------|--|

##### Returns

Favorites object for the `userId` that was passed in.

##### Exceptions

|                                    |  |
|------------------------------------|--|
| <i>BusBuddyInternalException</i>   | This exception is thrown when there is an internal error.                      |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown when the current session is invalidated.              |
| <i>BusBuddyNotFoundException</i>   | This exception is thrown if no data has been saved yet.                        |
| <i>BusBuddyBadRequestException</i> | This exception is thrown when the <code>sessionToken</code> is blank or empty. |

Implemented in `ITeamUserFavoritesService`.

#### 5.101.2.2 `void saveFavorites ( String sessionToken, UserFavoritesList favorites )` throws `BusBuddyException`

This method updates the `UserFavoritesList` object for a given user.

It creates it if it doesn't exist, and overwrites it if it does.

##### Parameters

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | <code>Session</code> whose user the favorites will be retrieved for. |
| <i>favorites</i>    | Favorites to set.  |

##### Exceptions

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyInternalException</i>   | This exception is thrown when there is an internal error.   |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown when the current session is invalidated.   |
| <i>BusBuddyBadRequestException</i> | This exception is thrown when the <code>sessionToken</code> is blank or empty, or the <code>userId</code> on the <code>UserFavoritesList</code> object passed in doesn't match the session. |

Implemented in `ITeamUserFavoritesService`.

## 5.102 UserInformation Class Reference

`UserInformation` contains the user related data that we get from User Module.

## Public Member Functions

- int **getUserId** ()
- void **setUserId** (int userId)
- String **getUsername** ()
- void **setUsername** (String username)
- String **getPassword** ()
- void **setPassword** (String password)
- String **getPasswordHash** ()
- void **setPasswordHash** (String passwordHash)
- boolean **isForcePasswordChange** ()
- void **setForcePasswordChange** (boolean forcePasswordChange)
- String **getFirstName** ()
- void **setFirstName** (String firstName)
- String **getEmail** ()
- void **setEmail** (String email)
- Short **getCountryCode** ()
- void **setCountryCode** (Short countryCode)
- String **getMobile** ()
- void **setMobile** (String mobile)
- String **getUserType** ()
- void **setUserType** (String userType)

## Private Attributes

- int **userId**
- String **username**
- String **password**
- String **passwordHash**
- boolean **forcePasswordChange**
- String **firstName**
- String **email**
- Short **countryCode**
- String **mobile**
- String **userType**

### 5.102.1 Detailed Description


[UserInformation](#) contains the user related data that we get from User Module.

This is more or less an exact copy of the [User](#) class.

## 5.103 UserLoginService Interface Reference

This is the generic BusBuddy [UserLoginService](#) interface.

Inheritance diagram for UserLoginService:



## Public Member Functions

- String [login](#) (String username, String password) throws `BusBuddyException`  
*This method handles the login process.*
- void [logout](#) (String sessionToken) throws `BusBuddyException`  
*This method logs a user out, invalidating their session in the database.*
- [User](#) [getUser](#) (String sessionToken) throws `BusBuddyException`  
*This method retrieves the user tied to a supplied session token.*
- String [createAlertSession](#) (String sessionToken) throws `BusBuddyException`  
*This method creates a new session to be used by an alert.*
- void [sendUsername](#) (String email) throws `BusBuddyException`  
*This method sends a user his or her username via e-mail.*
- void [sendUsername](#) (short countryCode, String mobile) throws `BusBuddyException`  
*This method sends a user his or her username via SMS.*
- void [resetPassword](#) (String username, String email) throws `BusBuddyException`  
*This method resets a user's password and sends them their new password via e-mail.*
- void [resetPassword](#) (String username, short countryCode, String mobile) throws `BusBuddyException`  
*This method resets a user's password and sends them their new password via SMS.*

### 5.103.1 Detailed Description

This is the generic BusBuddy [UserLoginService](#) interface.

This interface contains methods dealing with user login and session management. It is one of three interfaces that a user module implementation must implement. It can be implemented as a service or as a service client.

### 5.103.2 Member Function Documentation

#### 5.103.2.1 String [createAlertSession](#) ( String *sessionToken* ) throws `BusBuddyException`

This method creates a new session to be used by an alert.

Since creation of an alert requires an active user session, this takes an active sessionToken as a parameter. It will then create a new alert session for the same user as the active session. This "alert session" will be long-lived, so it won't expire like the main session. This will allow the Alert module to use this sessionToken when the alert executes.

#### Precondition

The session token must be linked to an active and valid session, which must be linked to an active account.

#### Postcondition

The returned session token points to a valid alert session for this user, which will not expire. The base session's expiration time will be advanced based on this activity against the session.

#### Parameters

|                     |   |
|---------------------|---|
| <i>sessionToken</i> | The session token identifying the session that is creating the new alert session. |
|---------------------|---|

#### Returns

[Session](#) token representing the new alert session.

## Exceptions

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the session token is blank.   |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the session token is invalid, linked to an expired session, or the user does not have permission to be signed in. |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.   |

Implemented in [ITeamUserLoginService](#).

**5.103.2.2 User `getUser ( String sessionToken )` throws `BusBuddyException`**

This method retrieves the user tied to a supplied session token.

It will also update the expiration time on the session to keep it valid.

## Precondition

The session token must be linked to an active and valid session, which must be linked to an active account.

## Postcondition

The returned session token points to a valid session for this user. The expiration time will be advanced based on this activity against the session.

## Parameters

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | The session token identifying the session that the user information should be retrieved for. |
|---------------------|--|

## Returns

[User](#) object for the user linked to the session represented by the session token parameter.

## Exceptions

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the session token is blank.   |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the session token is invalid, linked to an expired session, or the user does not have permission to be signed in. |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.   |

Implemented in [ITeamUserLoginService](#).

**5.103.2.3 String `login ( String username, String password )` throws `BusBuddyException`**

This method handles the login process.

A username and password are supplied. A valid session is created for this user.

## Precondition

Login credentials must be valid and linked to an active account, or a [.common.BusBuddyForbiddenException](#) will be thrown.

## Postcondition

The returned session token points to a valid session for this user.

## Parameters

|                 |                                   |
|-----------------|-----------------------------------|
| <i>username</i> | Username of the user to login as. |
| <i>password</i> | Password of the user to login as. |

## Returns

session token of the new session

## Exceptions

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the username or password are blank.   |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the credentials are incorrect, or the user does not have permission to sign in. |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.                           |

Implemented in [ITeamUserLoginService](#).

**5.103.2.4 void logout ( String sessionToken ) throws BusBuddyException**

This method logs a user out, invalidating their session in the database.

## Precondition

The sessionToken parameter must be a valid session identifier in the database.

## Postcondition

The session will be invalidated and future calls using that sessionToken will fail.

## Parameters

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | This is the session token that identifies the session. |
|---------------------|--|

## Exceptions

|                                  |  |
|----------------------------------|--|
| <i>BusBuddyNotFoundException</i> | This exception is thrown if the session token is blank or missing on the request.. |
| <i>BusBuddyNotFoundException</i> | This exception is thrown if the session token is invalid.                          |
| <i>BusBuddyInternalException</i> | This exception is thrown if an internal error prevents processing of the request.  |

Implemented in [ITeamUserLoginService](#).

**5.103.2.5 void resetPassword ( String username, String email ) throws BusBuddyException**

This method resets a user's password and sends them their new password via e-mail.

## Precondition

The username and e-mail address provided both link to the same user in the database.



**Postcondition**

The user's password is reset and sent to the user via e-mail.

**Parameters**

|                 |   |
|-----------------|---|
| <i>username</i> | Username of the <a href="#">User</a> to reset the password for.       |
| <i>email</i>    | E-mail address of the <a href="#">User</a> to reset the password for. |

**Exceptions**

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the username or e-mail address is blank.  |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the username and e-mail address combination don't link to a valid user. Also thrown if the account is suspended or deleted. |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.   |

Implemented in [ITeamUserLoginService](#).

**5.103.2.6 void resetPassword ( String username, short countryCode, String mobile ) throws BusBuddyException**

This method resets a user's password and sends them their new password via SMS.

**Precondition**

The username and mobile information provided both link to the same user in the database.

**Postcondition**

The user's password is reset and sent to the user via SMS.

**Parameters**

|                    |   |
|--------------------|---|
| <i>username</i>    | Username of the <a href="#">User</a> to reset the password for.                               |
| <i>countryCode</i> | country code of the user's mobile phone number  |
| <i>mobile</i>      | String representing the user's mobile phone number (String should consist entirely of digits) |

**Exceptions**

|                                    |   |
|------------------------------------|---|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the username or mobile number is blank (or non numeric).  |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the username and mobile information combination don't link to a valid user. Also thrown if the account is suspended or deleted. |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.   |

Implemented in [ITeamUserLoginService](#).

**5.103.2.7 void sendUsername ( String email ) throws BusBuddyException**

This method sends a user his or her username via e-mail.

**Precondition**

The e-mail address provided must be linked to a valid and active account.

**Postcondition**

An e-mail has been sent to the user, containing the user's username.

**Parameters**

|              |   |
|--------------|---|
| <i>email</i> | E-mail address of the account to send to. |
|--------------|---|

**Exceptions**

|                                    |  |
|------------------------------------|--|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the e-mail address is blank or invalid.                                  |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the e-mail address is linked to an account that is suspended or deleted. |
| <i>BusBuddyNotFoundException</i>   | This exception is thrown if the e-mail address doesn't link to a valid user.                         |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.                    |

Implemented in [ITeamUserLoginService](#).

**5.103.2.8 void setUsername ( short countryCode, String mobile ) throws BusBuddyException**

This method sends a user his or her username via SMS.

**Precondition**

The mobile details provided must be linked to a valid and active account.

**Postcondition**

An SMS has been sent to the user, containing the user's username.

**Parameters**

|              |   |
|--------------|---|
| <i>email</i> | E-mail address of the account to send to. |
|--------------|---|

**Exceptions**


|                                    |  |
|------------------------------------|--|
| <i>BusBuddyBadRequestException</i> | This exception is thrown if the mobile is blank or non-numeric.  |
| <i>BusBuddyForbiddenException</i>  | This exception is thrown if the mobile information is linked to an account that is suspended or deleted. |
| <i>BusBuddyNotFoundException</i>   | This exception is thrown if the mobile information doesn't link to a valid user.                         |
| <i>BusBuddyInternalException</i>   | This exception is thrown if an internal error prevents processing of the request.                        |

Implemented in [ITeamUserLoginService](#).

**5.104 UserManagementService Interface Reference**

This is the generic BusBuddy [UserManagementService](#) interface.

Inheritance diagram for UserManagementService:



## Public Member Functions

- **User createUser** (**User** userToCreate, String password) throws BusBuddyException  
*This method creates a user in the database.*
- **User findUserByUsername** (String sessionToken, String username) throws BusBuddyException  
*This method attempts to retrieve a user by username.*
- **User findUserByEmail** (String sessionToken, String email) throws BusBuddyException  
*This method attempts to retrieve a user by e-mail address.*
- **User findUserByMobile** (String sessionToken, short countryCode, String mobile) throws BusBuddyException  
*This method attempts to retrieve a user by mobile phone number.*
- void **updateUser** (String sessionToken, **User** newUserData, String password) throws BusBuddyException  
*This method updates a user in the database.*
- void **deleteUser** (String sessionToken, **User** userToDelete) throws BusBuddyException  
*This method deletes a user from the database.*

### 5.104.1 Detailed Description

This is the generic BusBuddy **UserManagementService** interface.

This interface contains methods dealing with user account management. It is one of three interfaces that a user module implementation must implement. It can be implemented as a service or as a service client.

Every method call here will (besides createUser) will result in the session's expiration time being updated due to activity on the session.

### 5.104.2 Member Function Documentation

#### 5.104.2.1 **User createUser** ( **User** userToCreate, String password ) throws BusBuddyException

This method creates a user in the database.

##### Precondition

No other user with this username, e-mail address, or mobile phone exists.

##### Postcondition

**User** is created with the given user data.

##### Parameters

|                 |  |
|-----------------|--|
| <i>user</i>     | <b>User</b> data of the user to create (the ID will be ignored). |
| <i>password</i> | Password of the user to create.                                  |

**Returns**

new user object

**Exceptions**

|                                  |  |
|----------------------------------|--|
| <i>BusBuddyInternalException</i> | This exception is thrown when an internal error prevents creation of the user.   |
| <i>BusBuddyConflictException</i> | This exception is thrown when the requested user record would create a duplicate username, e-mail address, or mobile phone data in the database. |

Implemented in [ITeamUserManagementService](#).

**5.104.2.2 void deleteUser ( String sessionToken, User userToDelete ) throws BusBuddyException**

This method deletes a user from the database.

It will delete the user with the same ID as the user passed in as a parameter.

**Precondition**

A user with the specified user ID on the [User](#) object must already exist.

**Postcondition**

[User](#) object in database will be deleted.

**Parameters**

|                     |   |
|---------------------|---|
| <i>sessionToken</i> | session token for the currently logged in user                      |
| <i>userToDelete</i> | This user object should have the same ID as the user to be deleted. |

**Exceptions**

|                                   |   |
|-----------------------------------|---|
| <i>BusBuddyInternalException</i>  | This exception is thrown when there is an internal error preventing execution of the request.   |
| <i>BusBuddyForbiddenException</i> | This exception is thrown if the session token is invalid, linked to an expired session, or the user does not have permission to make this change. |
| <i>BusBuddyNotFoundException</i>  | This exception is thrown if the targeted user is not found in the database.   |

Implemented in [ITeamUserManagementService](#).

**5.104.2.3 User findUserByEmail ( String sessionToken, String email ) throws BusBuddyException**

This method attempts to retrieve a user by e-mail address.

It is not case sensitive. The method will take an e-mail address, read the details from the database, and construct a user object with the given details.

**Precondition**

A user with the supplied e-mail address exists within the database.

**Postcondition**

A user will be returned whose e-mail address matches the supplied e-mail address parameter.

## Parameters

|              |  |
|--------------|--|
| <i>email</i> | This is the e-mail address to look up. |
|--------------|--|

## Returns

The user with the given e-mail address.

## Exceptions

|                                   |  |
|-----------------------------------|--|
| <i>BusBuddyInternalException</i>  | An internal error prevents execution of the request.                                     |
| <i>BusBuddyForbiddenException</i> | The currently logged in user does not have permission to view the result of this search. |
| <i>BusBuddyNotFoundException</i>  | This exception is thrown when the requested user record could not be found.              |

Implemented in [ITeamUserManagementService](#).

**5.104.2.4 User findUserByMobile ( String sessionToken, short countryCode, String mobile ) throws BusBuddyException**

This method attempts to retrieve a user by mobile phone number.

The method will take a mobile phone number, read the details from the database, and construct a user object with the given details.

## Precondition

A user with the supplied mobile phone number exists within the database.

## Postcondition

A user will be returned whose mobile phone details match the supplied parameters.

## Parameters

|                    |   |
|--------------------|---|
| <i>countryCode</i> | This is the country code of the user's mobile phone number.   |
| <i>mobile</i>      | This is the remainder of the user's mobile phone number. This string should consist entirely of digits. |

## Returns

The user with the given mobile phone details.

## Exceptions

|                                   |  |
|-----------------------------------|--|
| <i>BusBuddyInternalException</i>  | An internal error prevents execution of the request.                                     |
| <i>BusBuddyForbiddenException</i> | The currently logged in user does not have permission to view the result of this search. |
| <i>BusBuddyNotFoundException</i>  | This exception is thrown when the requested user record could not be found.              |

Implemented in [ITeamUserManagementService](#).

**5.104.2.5 User findUserByUsername ( String *sessionToken*, String *username* ) throws BusBuddyException**

This method attempts to retrieve a user by username.

It is not case sensitive. The method will take a username, read the details from the database, and construct a user object with the given details.

**Precondition**

A user with the supplied username exists within the database.

**Postcondition**

A user will be returned whose username matches the supplied username parameter.

**Parameters**

|                 |                                  |
|-----------------|----------------------------------|
| <i>username</i> | This is the username to look up. |
|-----------------|----------------------------------|

**Returns**

The user with the given username.

**Exceptions**

|                                   |  |
|-----------------------------------|--|
| <i>BusBuddyInternalException</i>  | An internal error prevents execution of the request.                                     |
| <i>BusBuddyForbiddenException</i> | The currently logged in user does not have permission to view the result of this search. |
| <i>BusBuddyNotFoundException</i>  | This exception is thrown when the requested user record could not be found.              |

Implemented in [ITeamUserManagementService](#).

**5.104.2.6 void updateUser ( String *sessionToken*, User *newUserData*, String *password* ) throws BusBuddyException**

This method updates a user in the database.

It will update the user with the same ID as the user passed in as a parameter. The username will not be updated, but all other fields will be.

**Precondition**

A user with the specified user ID on the [User](#) object must already exist.

**Postcondition**

[User](#) object in database will be updated with the data from the parameter [User](#) object.

**Parameters**

|                     |  |
|---------------------|--|
| <i>sessionToken</i> | session token for the currently logged in user           |
| <i>newUserData</i>  | <a href="#">User</a> object with the new user data on it |
| <i>password</i>     | New password to set on the user.                         |

## Exceptions

|                                   |   |
|-----------------------------------|---|
| <i>BusBuddyInternalException</i>  | This exception is thrown when there is an internal error preventing execution of the request.   |
| <i>BusBuddyForbiddenException</i> | This exception is thrown if the session token is invalid, linked to an expired session, or the user does not have permission to make this change. |
| <i>BusBuddyNotFoundException</i>  | This exception is thrown when the targeted user to receive the update does not exist.   |
| <i>BusBuddyConflictException</i>  | This exception is thrown when the requested change would create a duplicate mobile phone or e-mail address in the database.                       |

Implemented in [ITeamUserManagementService](#).

## 5.105 UserRepository Class Reference

This class is responsible for handling database access for [User](#) objects, and to construct, persist, and retrieve [User](#) objects.

### Package Functions

- [User](#) [createUser](#) ([User](#) user, String password) throws [BusBuddyConflictException](#), [BusBuddyInternalException](#)  
*This method creates a user in the database.*
- [User](#) [getUserById](#) (int userId) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method attempts to retrieve a user by id number.*
- [User](#) [getUserByUsername](#) (String username) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method attempts to retrieve a user by username.*
- [User](#) [getUserByEmail](#) (String email) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method attempts to retrieve a user by e-mail address.*
- [User](#) [getUserByMobile](#) (short countryCode, String mobile) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method attempts to retrieve a user by mobile phone number.*
- void [updateUser](#) ([User](#) newUserData) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#), - [BusBuddyConflictException](#)  
*This method updates a user in the database.*
- void [deleteUser](#) ([User](#) userToDelete) throws [BusBuddyInternalException](#), [BusBuddyNotFoundException](#)  
*This method deletes a user from the database.*

### 5.105.1 Detailed Description

This class is responsible for handling database access for [User](#) objects, and to construct, persist, and retrieve [User](#) objects.

### 5.105.2 Member Function Documentation

#### 5.105.2.1 [User](#) [createUser](#) ( [User](#) user, String password ) throws [BusBuddyConflictException](#), [BusBuddyInternalException](#) [package]

This method creates a user in the database.

**Precondition**

No other user with this username, e-mail address, or mobile phone exists.

**Postcondition**

[User](#) is created with the given user data.

**Parameters**

|                 |   |
|-----------------|---|
| <i>user</i>     | <a href="#">User</a> data of the user to create (the ID will be ignored). |
| <i>password</i> | Password of the user to create.   |

**Returns**

new user object

**Exceptions**

|                                  |  |
|----------------------------------|--|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.   |
| <i>BusBuddyConflictException</i> | This exception is thrown when the requested user record would create a duplicate username, e-mail address, or mobile phone data in the database. |

#### 5.105.2.2 void deleteUser ( [User](#) *userToDelete* ) throws **BusBuddyInternalException**, **BusBuddyNotFoundException** [package]

This method deletes a user from the database.

It will delete the user with the same ID as the user passed in as a parameter.

**Precondition**

A user with the specified user ID on the [User](#) object must already exist.

**Postcondition**

[User](#) object in database will be deleted.

**Exceptions**

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.                    |
| <i>BusBuddyNotFoundException</i> | This exception is thrown when the requested user record could not be found. |

#### 5.105.2.3 [User](#) getUserByEmail ( *String email* ) throws **BusBuddyInternalException**, **BusBuddyNotFoundException** [package]

This method attempts to retrieve a user by e-mail address.

It is not case sensitive. The method will take an e-mail address, read the details from the database, and construct a user object with the given details.

**Precondition**

A user with the supplied e-mail address exists within the database.



**Postcondition**

A user will be returned whose e-mail address matches the supplied e-mail address parameter.

**Parameters**

|              |  |
|--------------|--|
| <i>email</i> | This is the e-mail address to look up. |
|--------------|--|

**Returns**

The user with the given e-mail address.

**Exceptions**

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.                    |
| <i>BusBuddyNotFoundException</i> | This exception is thrown when the requested user record could not be found. |

**5.105.2.4 User getUserById ( int *userId* ) throws BusBuddyInternalException, BusBuddyNotFoundException**  
[package]

This method attempts to retrieve a user by id number.

The method will take a user id, read the details from the database, and construct a user object with the given details.

**Precondition**

A user with the supplied user id exists within the database.

**Postcondition**

A user will be returned whose user id matches the supplied *userId* parameter.

**Parameters**

|               |                                 |
|---------------|---------------------------------|
| <i>userId</i> | This is the user ID to look up. |
|---------------|---------------------------------|

**Returns**

The user with the given ID.

**Exceptions**

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.                    |
| <i>BusBuddyNotFoundException</i> | This exception is thrown when the requested user record could not be found. |

**5.105.2.5 User getUserByMobile ( short *countryCode*, String *mobile* ) throws BusBuddyInternalException, BusBuddyNotFoundException**  
[package]

This method attempts to retrieve a user by mobile phone number.

The method will take a mobile phone number, read the details from the database, and construct a user object with the given details.

**Precondition**

A user with the supplied mobile phone number exists within the database.

**Postcondition**

A user will be returned whose mobile phone details match the supplied parameters.

**Parameters**

|                    |   |
|--------------------|---|
| <i>countryCode</i> | This is the country code of the user's mobile phone number.   |
| <i>mobile</i>      | This is the remainder of the user's mobile phone number. This string should consist entirely of digits. |

**Returns**

The user with the given mobile phone details.

**Exceptions**

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.                    |
| <i>BusBuddyNotFoundException</i> | This exception is thrown when the requested user record could not be found. |

**5.105.2.6 User `getUserByUsername ( String username )` throws `BusBuddyInternalException`, `BusBuddyNotFoundException` [package]**

This method attempts to retrieve a user by username.

It is not case sensitive. The method will take a username, read the details from the database, and construct a user object with the given details.

**Precondition**

A user with the supplied username exists within the database.

**Postcondition**

A user will be returned whose username matches the supplied username parameter.

**Parameters**

|                 |                                  |
|-----------------|----------------------------------|
| <i>username</i> | This is the username to look up. |
|-----------------|----------------------------------|

**Returns**

The user with the given username.

**Exceptions**

|                                  |   |
|----------------------------------|---|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.                    |
| <i>BusBuddyNotFoundException</i> | This exception is thrown when the requested user record could not be found. |

5.105.2.7 void updateUser ( User *newUserData* ) throws BusBuddyInternalException, BusBuddyNotFoundException, BusBuddyConflictException [package]

This method updates a user in the database.

It will update the user with the same ID as the user passed in as a parameter. The username will not be updated, but all other fields will be.

#### Precondition

A user with the specified user ID on the [User](#) object must already exist.

#### Postcondition

[User](#) object in database will be updated with the data from the parameter [User](#) object.

#### Parameters

|                    |  |
|--------------------|--|
| <i>newUserData</i> | <a href="#">User</a> object with the new user data on it |
|--------------------|--|

#### Exceptions

|                                  |  |
|----------------------------------|--|
| <i>BusBuddyInternalException</i> | This exception is thrown when there is a database error.   |
| <i>BusBuddyNotFoundException</i> | This exception is thrown when the requested user record could not be found.  |
| <i>BusBuddyConflictException</i> | This exception is thrown when the requested user record would create a duplicate mobile phone or e-mail address in the database. |

## 5.106 UserSessionInformation Class Reference

A model that stores all the information needed to call user module about user information.

### Public Member Functions

- String **getUserId** ()
- void **setUserId** (String [userId](#))
- String **getUserSessionToken** ()
- void **setUserSessionToken** (String [userSessionToken](#))

### Private Attributes

- String [userId](#)  
*User ID of the user that initiated the alert.*
- String [userSessionToken](#)  
*A long lived session token to validate the authenticity of request to UserModule.*

### 5.106.1 Detailed Description

A model that stores all the information needed to call user module about user information.

### 5.106.2 Member Data Documentation

#### 5.106.2.1 String `userSessionToken` [private]

A long lived session token to validate the authenticity of request to UserModule.

This is required to get the current user information in order to alert the user.

## 5.107 UserTrackingAlertObject Class Reference

User tracking alert information obtained from the user interface when the user registers for an alert.

### Public Member Functions

- URL `getTransitColInfo` ()
- int `getRouteID` ()

### Private Attributes

- URL `transitColInfo`  
*URL uniquely identifies transit company information.*
- int `routeID`  
*Route number user is watching for vehicles.*
- Location `stopLocation`  
*GPS coordinates of vehicle stop closest to user.*
- Date `scheduledTime`  
*Time vehicle is scheduled to be at closest stop.*
- Date `alertTime`  
*Amount of lead time user needs to get to the vehicle stop.*
- String `userContactInfo`  
*How to contact a user with an alert.*
- `AlertType` type  
*Type of alert the user is registered.*

### 5.107.1 Detailed Description

User tracking alert information obtained from the user interface when the user registers for an alert.

Primarily, this meta data will come from the user interface and stored in user module.

### 5.107.2 Member Data Documentation

#### 5.107.2.1 Date `alertTime` [private]

Amount of lead time user needs to get to the vehicle stop.

Obtained from the user interface when the user signs up for an alert.

#### 5.107.2.2 int `routeID` [private]

Route number user is watching for vehicles.

Obtained by translating user interface route description drop down to transit information route id.

**5.107.2.3 Date scheduledTime** [private]

Time vehicle is scheduled to be at closest stop.

Obtained from information uploaded by a transit company. Used for determining delay alerts.

**5.107.2.4 Location stopLocation** [private]

GPS coordinates of vehicle stop closest to user.

Obtained from information uploaded to transit module by a transit company.

**5.107.2.5 URL transitColInfo** [private]

URL uniquely identifies transit company information.

The transit company URL information to distinguish this vehicle from other vehicles in different cities with similar route numbers. Obtained from the user interface when the user registers for an alert, selected from a drop down derived from metadata {}.

**5.107.2.6 AlertType type** [private]

Type of alert the user is registered.

A user may sign up for tracking alerts when a vehicle is approaching their stop. Transit companies may sign up for delay alerts when their vehicle(s) are running behind schedule.

**5.107.2.7 String userContactInfo** [private]

How to contact a user with an alert.

User contact information (phone number or URL) where to send tracking alerts. Obtained from user interface when user signs up for an alert. On Bus Buddy system start, obtained from alert repository.

## 5.108 UserType Enum Reference

This is an enumeration of the different statuses that a user can be assigned.

### Public Attributes

- **NORMAL\_USER**

*This is a standard user.*

- **SYSTEM\_ADMINISTRATOR**

*This is a system administrator, who can read and write to other users' data.*

- **SUSPENDED\_USER**

*A user account marked as suspended cannot create or use sessions.*

### 5.108.1 Detailed Description

This is an enumeration of the different statuses that a user can be assigned.

## 5.109 VehicleObject Class Reference

Value Object containing vehicle information obtained when the user registers a vehicle using the user interface.

### Public Member Functions

- String **getGPSDeviceInfo** ()
- URL **getTransitCoURL** ()
- int **getGPSDeviceID** ()
- int **getCurrentRoute** ()

### Private Attributes

- int [gpsDeviceID](#)  
*GPS hardware device ID.*
- String [gpsDeviceInfo](#)  
*GPS device contact information, commercial web URL, GPS wireless connection or port number.*
- URL [transitCoURL](#)  
*Transit company operating this vehicle.*
- int [currentRoute](#)  
*Current route number.*

### 5.109.1 Detailed Description

Value Object containing vehicle information obtained when the user registers a vehicle using the user interface.

### 5.109.2 Member Data Documentation

#### 5.109.2.1 int currentRoute [private]

Current route number.

Obtain and updated by the user interface.

#### 5.109.2.2 int gpsDeviceID [private]

GPS hardware device ID.

Hardware GPS device ID, uniquely identifies a GPS unit. Obtained from user interface when a vehicle registers for tracking.

#### 5.109.2.3 String gpsDeviceInfo [private]

GPS device contact information, commercial web URL, GPS wireless connection or port number.

Obtained from user interface when a vehicle is registered for tracking.

#### 5.109.2.4 URL transitCoURL [private]

Transit company operating this vehicle.

Obtained from the information uploaded to TransitInfo by the transit company. User selects transit company name from a drop down on the user interface when registering a vehicle.

## 5.110 VehicleRepository Class Reference

Repository for information on vehicles registered on a route.

### Public Member Functions

- [VehicleRepository](#) ()  
*Create the initial repository for saving vehicles registered with the tracking service.*
- void [addVehicle](#) ([TransitVehicle](#) vehicle)  
*Add a vehicle to the repository.*
- void [removeVehicle](#) (int gpsDeviceID)  
*Remove a vehicle from the repository.*
- void [updateVehicle](#) ([TransitVehicle](#) vehicle)  
*A vehicle may switch routes, update an existing vehicle in the repository.*
- [TransitVehicle](#) [findVehicle](#) (int gpsDeviceID)  
*Find a vehicle currently stored in the repository based on the unique GPS device ID.*

### Static Public Member Functions

- static ArrayList< [TransitVehicle](#) > [findVehiclesByRoute](#) (URL transitCoURL, int routeID)  
*Find all vehicles from a transit company registered on a route.*

### Private Attributes

- ArrayList< [TransitVehicle](#) > [vehicleList](#) = null  
*List of vehicles currently registered and available in this repository.*

#### 5.110.1 Detailed Description

Repository for information on vehicles registered on a route.

#### 5.110.2 Member Function Documentation

##### 5.110.2.1 [TransitVehicle](#) [findVehicle](#) ( int *gpsDeviceID* )

Find a vehicle currently stored in the repository based on the unique GPS device ID.

##### Parameters

|                    |                         |
|--------------------|-------------------------|
| <i>gpsDeviceID</i> | - integer GPS device ID |
|--------------------|-------------------------|

##### Returns

[VehicleObject](#) matching vehicle or null if no matching vehicle found.

##### 5.110.2.2 static ArrayList<[TransitVehicle](#)> [findVehiclesByRoute](#) ( URL *transitCoURL*, int *routeID* ) [static]

Find all vehicles from a transit company registered on a route.

## Parameters

|                     |  |
|---------------------|--|
| <i>transitCoURL</i> | URL or the transit company                               |
| <i>routeID</i>      | - integer route that vehicle is currently registered on. |

## Returns

ArrayList<TransitVehicle> of all vehicles for transit company registered on the route or null if no matching vehicles found.

**5.110.2.3 void removeVehicle ( int *gpsDeviceID* )**

Remove a vehicle from the repository.

## Parameters

|                    |  |
|--------------------|--|
| <i>gpsDeviceID</i> | - integer the GPS id if the vehicle to remove. |
|--------------------|--|

**5.110.2.4 void updateVehicle ( TransitVehicle *vehicle* )**

A vehicle may switch routes, update an existing vehicle in the repository.

## Parameters

|                |  |
|----------------|--|
| <i>vehicle</i> | - <a href="#">VehicleObject</a> new vehicle information from driver through UI |
|----------------|--|



# Index

- AbstractFeedParserTemplate, [23](#)
- addAlertSpecification
  - tracking::TransitVehicle, [123](#)
- addUserTrackingAlert
  - tracking::ITrackingService, [81](#)
  - tracking::TrackingServiceController, [113](#)
- Alert, [25](#)
- alert.client, [13](#)
- alert.client.model, [13](#)
- alert.controller, [14](#)
- alert.controller.model, [14](#)
- alert.domain, [15](#)
- alert.domain.model, [15](#)
- alert.enums, [16](#)
- alert.service, [16](#)
- alert::client::AlertUserClient
  - getUserInformation, [44](#)
  - verifySessionToken, [44](#)
- alert::controller::AlertRequestController
  - processTrackingAlertRequest, [35](#)
  - processTransitAlertRequest, [35](#)
  - processUserAlertRequest, [35](#)
  - verifySession, [36](#)
- alert::controller::CertificateHandler
  - verifySessionToken, [52](#)
- alert::controller::ISessionHandler
  - verifySessionToken, [71](#)
- alert::controller::SessionTokenHandler
  - userClient, [102](#)
  - verifySessionToken, [102](#)
- alert::controller::SessionVerificationFactory
  - getSessionTokenVerificationStrategy, [103](#)
- alert::controller::model::AlertRequestModel
  - alertInitiator, [37](#)
- alert::domain::AlertFactory
  - createAlert, [29](#)
- alert::domain::AlertRepository
  - deleteAlert, [32](#)
  - getAlertByDateTime, [32](#)
  - getAlertByRoute, [33](#)
  - getAlertByUserId, [33](#)
  - saveAlert, [33](#)
  - updateAlert, [33](#)
- alert::domain::model::Alert
  - alertInitiator, [27](#)
  - alertRunType, [27](#)
  - alertType, [27](#)
  - Status, [27](#)
  - userInformation, [27](#)
- alert::domain::model::OneTimeAlert
  - dateExecuted, [84](#)
- alert::domain::model::RecurringAlert
  - alertRecurringType, [87](#)
  - repeatEvery, [87](#)
- alert::domain::model::RecurringData
  - dayOfMonth, [88](#)
  - dayOfWeek, [88](#)
  - dayOfYear, [88](#)
  - startHour, [88](#)
  - startMinute, [89](#)
- alert::domain::model::TripInformation
  - getRouteIds, [125](#)
  - tripData, [126](#)
- alert::domain::model::UserSessionInformation
  - userSessionToken, [152](#)
- alert::enums::AlertNotificationType
  - PlannedDisruption, [30](#)
  - ScheduleInformation, [30](#)
  - UnplannedDisruption, [30](#)
- alert::enums::AlertStatus
  - Deactive, [43](#)
  - Error, [43](#)
  - Expired, [43](#)
- alert::service::AlertExecuteStrategyFactory
  - getAlertExecuteStrategy, [28](#)
- alert::service::AlertExecutionScheduler
  - getAlertServices, [28](#)
  - runAlert, [28](#)
- alert::service::AlertService
  - alertExecuteStrategyFactory, [40](#)
  - alertFactory, [40](#)
  - alertRepository, [40](#)
  - createAlert, [38](#)
  - deleteAlert, [39](#)
  - saveAlert, [39](#)
  - sendAlert, [39](#)
  - updateAlert, [39](#)
- alert::service::AlertServiceFactory
  - getAlertService, [41](#)
  - trackingAlertService, [41](#)
  - transitAlertService, [41](#)
  - userAlertService, [41](#)
- alert::service::IAlertExecuteStrategy
  - execute, [69](#)
- alert::service::RouteAlertExecuteStrategy
  - alertRepository, [91](#)
  - execute, [91](#)
  - userClient, [91](#)

- alert::service::ScheduleAlertExecuteStrategy
  - alertRepository, 97
  - userClient, 97
- alert::service::TrackingAlertService
  - createAlert, 109
  - sendAlert, 109
  - updateAlert, 109
- alert::service::TransitAlertService
  - createAlert, 115
  - sendAlert, 115
  - updateAlert, 115
- alert::service::UserAlertService
  - createAlert, 132
  - sendAlert, 132
  - updateAlert, 132
- AlertExecuteStrategyFactory, 27
- alertExecuteStrategyFactory
  - alert::service::AlertService, 40
- AlertExecutionScheduler, 28
- AlertFactory, 29
- alertFactory
  - alert::service::AlertService, 40
- AlertInitiator, 30
- alertInitiator
  - alert::controller::model::AlertRequestModel, 37
  - alert::domain::model::Alert, 27
- alertList
  - tracking::BusVehicle, 51
- AlertNotificationType, 30
- AlertRangeLogic, 31
- AlertRecurringType, 31
- alertRecurringType
  - alert::domain::model::RecurringAlert, 87
- AlertRepository, 32
- alertRepository
  - alert::service::AlertService, 40
  - alert::service::RouteAlertExecuteStrategy, 91
  - alert::service::ScheduleAlertExecuteStrategy, 97
- AlertRequestController, 34
- alertRequestController
  - transit::ITeamTransitServiceController, 74
- AlertRequestModel, 36
- AlertResponseModel, 37
- AlertRunType, 37
- alertRunType
  - alert::domain::model::Alert, 27
- AlertService, 37
- AlertServiceFactory, 40
- AlertSpecification, 41
- AlertStatus, 42
- alertTime
  - tracking::UserTrackingAlertObject, 152
- AlertType, 43
- alertType
  - alert::domain::model::Alert, 27
- AlertUserClient, 43
- and
  - common::Specification< T >, 103
- BaseController, 44
- BusBuddyBadRequestException, 46
- BusBuddyConflictException, 46
- BusBuddyException, 47
- BusBuddyForbiddenException, 48
- BusBuddyInternalException, 49
- BusBuddyNotFoundException, 50
- BusVehicle, 51
- calculateTrip
  - transit::ITeamTripServiceController, 75
  - transit::TripService, 126
- cause
  - transit::Detour, 55
- CertificateHandler, 52
- checkForAlerts
  - tracking::TransitVehicle, 123
- checkPermissions
  - user::ITeamUserLoginService, 77
- CommercialTracking, 52
  - tracking::CommercialTracking, 53
- CommercialTracking.CommercialTrackingHolder, 54
- common, 17
- common::BaseController
  - handleBusBuddyException, 45
  - handleGenericException, 45
- common::BusBuddyBadRequestException
  - getHttpCode, 46
- common::BusBuddyConflictException
  - getHttpCode, 47
- common::BusBuddyException
  - getHttpCode, 48
- common::BusBuddyForbiddenException
  - getHttpCode, 49
- common::BusBuddyInternalException
  - getHttpCode, 50
- common::BusBuddyNotFoundException
  - getHttpCode, 51
- common::HashUtility
  - hash, 69
- common::MessageDeliveryUtility
  - sendEmail, 83
  - sendSms, 83
- common::Specification< T >
  - and, 103
  - isSatisfiedBy, 104
  - not, 104
  - or, 104
- convertJSONAlertInput
  - tracking::TrackingResponseModel, 112
- convertJSONVehicleInput
  - tracking::TrackingResponseModel, 112
- covered
  - transit::Stop, 106
- createAlert
  - alert::domain::AlertFactory, 29
  - alert::service::AlertService, 38
  - alert::service::TrackingAlertService, 109
  - alert::service::TransitAlertService, 115

- alert::service::UserAlertService, 132
- createAlertObserver
  - tracking::TrackingAlertFactory, 107
- createAlertSession
  - user::ITeamUserLoginService, 78
  - user::UserLoginService, 138
- createSession
  - user::SessionRepository, 100
- createTransitVehicle
  - tracking::TransitVehicleFactory, 123
- createUser
  - user::ITeamUserManagementService, 80
  - user::UserManagementService, 143
  - user::UserRepository, 147
- currentRoute
  - tracking::VehicleObject, 154
- dateExecuted
  - alert::domain::model::OneTimeAlert, 84
- dayOfMonth
  - alert::domain::model::RecurringData, 88
- dayOfWeek
  - alert::domain::model::RecurringData, 88
- dayOfYear
  - alert::domain::model::RecurringData, 88
- Deactive
  - alert::enums::AlertStatus, 43
- DelayAlertLogic, 54
- delete
  - transit::RouteRepository, 94
- deleteAlert
  - alert::domain::AlertRepository, 32
  - alert::service::AlertService, 39
- deleteUser
  - user::ITeamUserManagementService, 80
  - user::UserManagementService, 144
  - user::UserRepository, 148
- description
  - transit::Stop, 106
- Detour, 54
  - transit::Detour, 55
- detourId
  - transit::Detour, 55
- detours
  - transit::Route, 90
- discountedFare
  - transit::Fare, 57
- Error
  - alert::enums::AlertStatus, 43
- estimatedDelay
  - transit::Detour, 56
- execute
  - alert::service::IAlertExecuteStrategy, 69
  - alert::service::RouteAlertExecuteStrategy, 91
- Expired
  - alert::enums::AlertStatus, 43
- Fare, 56
  - transit::Fare, 56, 57
- FavoriteTransitService, 57
  - user::FavoriteTransitService, 58
- findUserByEmail
  - user::ITeamUserManagementService, 80
  - user::UserManagementService, 144
- findUserByMobile
  - user::ITeamUserManagementService, 80
  - user::UserManagementService, 145
- findUserByUsername
  - user::ITeamUserManagementService, 80
  - user::UserManagementService, 145
- findVehicle
  - tracking::VehicleRepository, 155
- findVehiclesByRoute
  - tracking::VehicleRepository, 155
- fireRouteDistruptionEvent
  - transit::TransitProvider, 118
- formatJSONResponse
  - tracking::TrackingResponseModel, 112
- GPSLocationObject, 61
- GPSLocationObserver, 61
- GPSLocationTracking, 63
- GPSPuller, 64
  - tracking::GPSPuller, 65
- GPSPuller.GPSPullerHolder, 65
- GPSPusher, 65
  - tracking::GPSPusher, 66
- GPSPusher.GPSPusherHolder, 67
- GPSVehicleTracker, 67
  - tracking::GPSVehicleTracker, 68
- GTFSFeedParser, 68
- getAlertByDateTime
  - alert::domain::AlertRepository, 32
- getAlertByRoute
  - alert::domain::AlertRepository, 33
- getAlertByUserId
  - alert::domain::AlertRepository, 33
- getAlertExecuteStrategy
  - alert::service::AlertExecuteStrategyFactory, 28
- getAlertService
  - alert::service::AlertServiceFactory, 41
- getAlertServices
  - alert::service::AlertExecutionScheduler, 28
- getAll
  - transit::RouteRepository, 94
- getCountryCode
  - user::User, 128
- getCreationTime
  - user::Session, 98
- getEmail
  - user::User, 128
- getExpirationTime
  - user::Session, 98
- getFavoriteRouteIds
  - user::FavoriteTransitService, 58
- getFavoriteTransitServices
  - user::UserFavoritesList, 133

- getFavorites
  - user::UserFavoritesRepository, 134
- getFirstName
  - user::User, 128
- getGPSLocation
  - tracking::GPSLocationObserver, 62
- getGPSTypeFromURL
  - tracking::TransitVehicleFactory, 123
- getHttpCode
  - common::BusBuddyBadRequestException, 46
  - common::BusBuddyConflictException, 47
  - common::BusBuddyException, 48
  - common::BusBuddyForbiddenException, 49
  - common::BusBuddyInternalException, 50
  - common::BusBuddyNotFoundException, 51
- getInstance
  - tracking::CommercialTracking, 53
  - tracking::GPSPusher, 66
- getMobile
  - user::User, 129
- getPasswordHash
  - user::User, 129
- getRoute
  - transit::GoogleTransitServiceAdapter, 60
  - transit::ITeamTransitServiceController, 73
  - transit::PersistedTransitFeed, 85
  - transit::TransitFeed, 116
  - transit::TransitService, 120
- getRouteIds
  - alert::domain::model::TripInformation, 125
- getRoutes
  - transit::GoogleTransitServiceAdapter, 60
  - transit::ITeamTransitServiceController, 73
  - transit::PersistedTransitFeed, 86
  - transit::TransitFeed, 116
  - transit::TransitService, 121
- getServiceURL
  - transit::ITeamTransitServiceController, 74
  - transit::TransitService, 121
- getSession
  - user::SessionRepository, 100
- getSessionToken
  - user::Session, 98
- getSessionTokenVerificationStrategy
  - alert::controller::SessionVerificationFactory, 103
- getSpec
  - tracking::TrackingAlertObserver, 108
- getStopTimes
  - transit::Stop, 105
- getTransitServiceUrl
  - user::FavoriteTransitService, 58
- getTransitVehicleLocation
  - tracking::ITrackingService, 81
- getTransitInfo
  - transit::ITeamTransitServiceController, 74
  - transit::TransitService, 121
- getUser
  - user::ITeamUserLoginService, 78
  - user::UserLoginService, 139
- getUserByEmail
  - user::UserRepository, 148
- getUserById
  - user::UserRepository, 149
- getUserByMobile
  - user::UserRepository, 149
- getUserByUsername
  - user::UserRepository, 150
- getUserId
  - user::Session, 99
  - user::User, 129
  - user::UserFavoritesList, 133
- getUserType
  - user::User, 129
- getUsername
  - user::User, 129
- getVehicleGPSDeviceID
  - tracking::TransitVehicleFactory, 124
- getUserInformation
  - alert::client::AlertUserClient, 44
- GoogleTransitServiceAPI, 61
- GoogleTransitServiceAdapter, 59
  - transit::GoogleTransitServiceAdapter, 60
- gpsDeviceID
  - tracking::VehicleObject, 154
- gpsDeviceInfo
  - tracking::VehicleObject, 154
- gpsUpdate
  - tracking::GPSLocationObserver, 62
- handleBusBuddyException
  - common::BaseController, 45
- handleGenericException
  - common::BaseController, 45
- handleRouteDisruptionEvent
  - transit::ITeamTransitServiceController, 74
  - transit::TransitProviderObserver, 120
- hash
  - common::HashUtility, 69
- HashUtility, 68
- IAAlertExecuteStrategy, 69
- ISessionHandler, 71
- ITeamTransitServiceController, 72
- ITeamTripServiceController, 75
- ITeamUserFavoritesService, 76
- ITeamUserLoginService, 77
- ITeamUserManagementService, 79
- ITrackingService, 80
- inAlertRange
  - tracking::AlertSpecification, 42
- InvalidRouteParseException, 70
  - transit::InvalidRouteParseException, 71
- isAlertSession
  - user::Session, 99
- isFavoriteTransitService
  - user::FavoriteTransitService, 58
- isForcePasswordChange

- user::User, 129
- isSatisfiedBy
  - common::Specification< T >, 104
  - transit::RouteSpecification, 96
- isValid
  - user::Session, 99
- killSession
  - user::SessionRepository, 101
- loadFeed
  - transit::AbstractFeedParserTemplate, 24
- Location, 82
  - transit::Location, 83
- login
  - user::ITeamUserLoginService, 78
  - user::UserLoginService, 139
- logo
  - transit::TransitInfo, 117
- logout
  - user::ITeamUserLoginService, 78
  - user::UserLoginService, 140
- MessageDeliveryUtility, 83
- name
  - transit::TransitProvider, 119
- not
  - common::Specification< T >, 104
- OneTimeAlert, 84
- or
  - common::Specification< T >, 104
- parseFeed
  - transit::AbstractFeedParserTemplate, 24
  - transit::GTFSFeedParser, 68
- PersistedTransitFeed, 85
- PlannedDisruption
  - alert::enums::AlertNotificationType, 30
- processTrackingAlertRequest
  - alert::controller::AlertRequestController, 35
- processTransitAlertRequest
  - alert::controller::AlertRequestController, 35
- processUserAlertRequest
  - alert::controller::AlertRequestController, 35
- providerId
  - transit::TransitProvider, 119
- read
  - transit::RouteRepository, 94
- readFavorites
  - user::ITeamUserFavoritesService, 76
  - user::UserFavoritesService, 135
- RecurringAlert, 86
- RecurringData, 87
- registerGPSDevice
  - tracking::GPSLocationTracking, 63
- registerObserver
  - transit::TransitProvider, 119
- registerVehicleOnRoute
  - tracking::ITrackingService, 81
  - tracking::TrackingServiceController, 113
- removeVehicle
  - tracking::VehicleRepository, 156
- repeatEvery
  - alert::domain::model::RecurringAlert, 87
- resetPassword
  - user::ITeamUserLoginService, 78
  - user::UserLoginService, 140, 141
- Route, 89
  - transit::Route, 90
- RouteAlertExecuteStrategy, 90
- routeBatch
  - transit::InvalidRouteParseException, 71
- RouteDisruptionAlert, 92
- RouteDisruptionEvent, 92
  - transit::RouteDisruptionEvent, 93
- routeId
  - tracking::UserTrackingAlertObject, 152
- routeld
  - transit::RouteDisruptionAlert, 92
- routeName
  - transit::Route, 90
- RouteRepository, 93
- RouteSpecification, 95
- runAlert
  - alert::service::AlertExecutionScheduler, 28
- save
  - transit::RouteRepository, 94, 95
- saveAlert
  - alert::domain::AlertRepository, 33
  - alert::service::AlertService, 39
- saveFavorites
  - user::ITeamUserFavoritesService, 76
  - user::UserFavoritesService, 136
- saveRoutes
  - transit::AbstractFeedParserTemplate, 24
- ScheduleAlertExecuteStrategy, 96
- ScheduleInformation
  - alert::enums::AlertNotificationType, 30
- scheduledTime
  - tracking::UserTrackingAlertObject, 152
- sendAlert
  - alert::service::AlertService, 39
  - alert::service::TrackingAlertService, 109
  - alert::service::TransitAlertService, 115
  - alert::service::UserAlertService, 132
- sendEmail
  - common::MessageDeliveryUtility, 83
- sendSms
  - common::MessageDeliveryUtility, 83
- sendUsername
  - user::ITeamUserLoginService, 79
  - user::UserLoginService, 141, 142
- serialVersionUID
  - transit::InvalidRouteParseException, 71
- Session, 97

- user::Session, 98
- SessionRepository, 99
- SessionTokenHandler, 101
- SessionVerificationFactory, 102
- setCountryCode
  - user::User, 130
- setDiscountedFare
  - transit::Fare, 57
- setEmail
  - user::User, 130
- setExpirationTime
  - user::Session, 99
- setFavoriteRouteIds
  - user::FavoriteTransitService, 59
- setFavoriteTransitService
  - user::FavoriteTransitService, 59
- setFavoriteTransitServices
  - user::UserFavoritesList, 133
- setFirstName
  - user::User, 130
- setForcePasswordChange
  - user::User, 130
- setGPSLocation
  - tracking::GPSLocationObserver, 63
- setMobile
  - user::User, 130
- setPasswordHash
  - user::User, 131
- setRegularFare
  - transit::Fare, 57
- setSpec
  - tracking::TrackingAlertObserver, 108
- setStops
  - transit::Route, 90
- setUserType
  - user::User, 131
- setValid
  - user::Session, 99
- Specification< T >, 103
- start
  - transit::AbstractFeedParserTemplate, 25
- startHour
  - alert::domain::model::RecurringData, 88
- startMinute
  - alert::domain::model::RecurringData, 89
- startTrackingController
  - tracking::ITrackingService, 82
- Status
  - alert::domain::model::Alert, 27
- Stop, 104
  - transit::Stop, 105
- stopId
  - transit::Stop, 106
- stopLocation
  - tracking::UserTrackingAlertObject, 153
- stops
  - transit::Route, 90
- tracking, 18
  - tracking::AlertSpecification
    - inAlertRange, 42
  - tracking::BusVehicle
    - alertList, 51
  - tracking::CommercialTracking
    - CommercialTracking, 53
    - getInstance, 53
  - tracking::GPSLocationObserver
    - getGPSLocation, 62
    - gpsUpdate, 62
    - setGPSLocation, 63
  - tracking::GPSLocationTracking
    - registerGPSDevice, 63
    - unregisterGPSDevice, 63
  - tracking::GPSPuller
    - GPSPuller, 65
  - tracking::GPSPusher
    - GPSPusher, 66
    - getInstance, 66
  - tracking::GPSVehicleTracker
    - GPSVehicleTracker, 68
  - tracking::ITrackingService
    - addUserTrackingAlert, 81
    - getTransitVehicleLocation, 81
    - registerVehicleOnRoute, 81
    - startTrackingController, 82
    - unregisterVehicleFromRoute, 82
  - tracking::TrackingAlertFactory
    - createAlertObserver, 107
  - tracking::TrackingAlertObserver
    - getSpec, 108
    - setSpec, 108
    - updateAlert, 108
  - tracking::TrackingDelayAlert
    - updateAlert, 110
  - tracking::TrackingLocationAlert
    - TrackingLocationAlert, 111
  - tracking::TrackingResponseModel
    - convertJSONAlertInput, 112
    - convertJSONVehicleInput, 112
    - formatJSONResponse, 112
  - tracking::TrackingServiceController
    - addUserTrackingAlert, 113
    - registerVehicleOnRoute, 113
    - unregisterVehicleFromRoute, 113
  - tracking::TransitVehicle
    - addAlertSpecification, 123
    - checkForAlerts, 123
  - tracking::TransitVehicleFactory
    - createTransitVehicle, 123
    - getGPSTypeFromURL, 123
    - getVehicleGPSDeviceID, 124
  - tracking::UserTrackingAlertObject
    - alertTime, 152
    - routeID, 152
    - scheduledTime, 152
    - stopLocation, 153
    - transitColInfo, 153

- type, 153
- userContactInfo, 153
- tracking::VehicleObject
  - currentRoute, 154
  - gpsDeviceID, 154
  - gpsDeviceInfo, 154
  - transitCoURL, 154
- tracking::VehicleRepository
  - findVehicle, 155
  - findVehiclesByRoute, 155
  - removeVehicle, 156
  - updateVehicle, 156
- TrackingAlertFactory, 106
- TrackingAlertObserver, 107
- TrackingAlertRequestModel, 108
- TrackingAlertService, 109
- trackingAlertService
  - alert::service::AlertServiceFactory, 41
- TrackingDelayAlert, 110
- TrackingLocationAlert, 111
  - tracking::TrackingLocationAlert, 111
- TrackingResponseModel, 111
- TrackingServiceController, 112
- transit, 19
- transit::AbstractFeedParserTemplate
  - loadFeed, 24
  - parseFeed, 24
  - saveRoutes, 24
  - start, 25
  - validate, 25
- transit::Detour
  - cause, 55
  - Detour, 55
  - detourId, 55
  - estimatedDelay, 56
- transit::Fare
  - discountedFare, 57
  - Fare, 56, 57
  - setDiscountedFare, 57
  - setRegularFare, 57
- transit::GTFSFeedParser
  - parseFeed, 68
- transit::GoogleTransitServiceAdapter
  - getRoute, 60
  - getRoutes, 60
  - GoogleTransitServiceAdapter, 60
- transit::ITeamTransitServiceController
  - alertRequestController, 74
  - getRoute, 73
  - getRoutes, 73
  - getServiceURL, 74
  - getTransitInfo, 74
  - handleRouteDisruptionEvent, 74
  - transitFeed, 74
- transit::ITeamTripServiceController
  - calculateTrip, 75
- transit::InvalidRouteParseException
  - InvalidRouteParseException, 71
- routeBatch, 71
- serialVersionUID, 71
- transit::Location
  - Location, 83
- transit::PersistedTransitFeed
  - getRoute, 85
  - getRoutes, 86
- transit::Route
  - detours, 90
  - Route, 90
  - routeName, 90
  - setStops, 90
  - stops, 90
- transit::RouteDisruptionAlert
  - routId, 92
  - transitServiceUrl, 92
- transit::RouteDisruptionEvent
  - RouteDisruptionEvent, 93
- transit::RouteRepository
  - delete, 94
  - getAll, 94
  - read, 94
  - save, 94, 95
- transit::RouteSpecification
  - isSatisfiedBy, 96
- transit::Stop
  - covered, 106
  - description, 106
  - getStopTimes, 105
  - Stop, 105
  - stopId, 106
- transit::TransitFeed
  - getRoute, 116
  - getRoutes, 116
- transit::TransitInfo
  - logo, 117
  - transitAuthorityName, 117
  - website, 118
- transit::TransitProvider
  - fireRouteDisruptionEvent, 118
  - name, 119
  - providerId, 119
  - registerObserver, 119
  - unregisterObserver, 119
- transit::TransitProviderObserver
  - handleRouteDisruptionEvent, 120
- transit::TransitService
  - getRoute, 120
  - getRoutes, 121
  - getServiceURL, 121
  - getTransitInfo, 121
- transit::Trip
  - Trip, 125
- transit::TripService
  - calculateTrip, 126
- TransitAlertRequestModel, 114
- TransitAlertService, 114
- transitAlertService



- alert::service::AlertServiceFactory, 41
- transitAuthorityName
  - transit::TransitInfo, 117
- transitColumnInfo
  - tracking::UserTrackingAlertObject, 153
- transitCoURL
  - tracking::VehicleObject, 154
- TransitFeed, 115
- transitFeed
  - transit::ITeamTransitServiceController, 74
- TransitInfo, 117
- TransitProvider, 118
- TransitProviderObserver, 119
- TransitService, 120
- transitServiceUrl
  - transit::RouteDisruptionAlert, 92
- TransitVehicle, 122
- TransitVehicleFactory, 123
- Trip, 124
  - transit::Trip, 125
- tripData
  - alert::domain::model::TripInformation, 126
- TripInformation, 125
- TripService, 126
- type
  - tracking::UserTrackingAlertObject, 153
- UnplannedDisruption
  - alert::enums::AlertNotificationType, 30
- unregisterGPSDevice
  - tracking::GPSLocationTracking, 63
- unregisterObserver
  - transit::TransitProvider, 119
- unregisterVehicleFromRoute
  - tracking::ITrackingService, 82
  - tracking::TrackingServiceController, 113
- updateAlert
  - alert::domain::AlertRepository, 33
  - alert::service::AlertService, 39
  - alert::service::TrackingAlertService, 109
  - alert::service::TransitAlertService, 115
  - alert::service::UserAlertService, 132
  - tracking::TrackingAlertObserver, 108
  - tracking::TrackingDelayAlert, 110
- updateFavorites
  - user::UserFavoritesRepository, 134
- updateUser
  - user::ITeamUserManagementService, 80
  - user::UserManagementService, 146
  - user::UserRepository, 150
- updateVehicle
  - tracking::VehicleRepository, 156
- User, 127
  - user::User, 128
- user, 20
- user::FavoriteTransitService
  - FavoriteTransitService, 58
  - getFavoriteRouteIds, 58
  - getTransitServiceUrl, 58
  - isFavoriteTransitService, 58
  - setFavoriteRouteIds, 59
  - setFavoriteTransitService, 59
- user::ITeamUserFavoritesService
  - readFavorites, 76
  - saveFavorites, 76
- user::ITeamUserLoginService
  - checkPermissions, 77
  - createAlertSession, 78
  - getUser, 78
  - login, 78
  - logout, 78
  - resetPassword, 78
  - sendUsername, 79
- user::ITeamUserManagementService
  - createUser, 80
  - deleteUser, 80
  - findUserByEmail, 80
  - findUserByMobile, 80
  - findUserByUsername, 80
  - updateUser, 80
- user::Session
  - getCreationTime, 98
  - getExpirationTime, 98
  - getSessionToken, 98
  - getUserId, 99
  - isAlertSession, 99
  - isValid, 99
  - Session, 98
  - setExpirationTime, 99
  - setValid, 99
- user::SessionRepository
  - createSession, 100
  - getSession, 100
  - killSession, 101
- user::User
  - getCountryCode, 128
  - getEmail, 128
  - getFirstName, 128
  - getMobile, 129
  - getPasswordHash, 129
  - getUserId, 129
  - getUserType, 129
  - getUsername, 129
  - isForcePasswordChange, 129
  - setCountryCode, 130
  - setEmail, 130
  - setFirstName, 130
  - setForcePasswordChange, 130
  - setMobile, 130
  - setPasswordHash, 131
  - setUserType, 131
  - User, 128
- user::UserFavoritesList
  - getFavoriteTransitServices, 133
  - getUserId, 133
  - setFavoriteTransitServices, 133
  - UserFavoritesList, 133



- user::UserFavoritesRepository
  - getFavorites, [134](#)
  - updateFavorites, [134](#)
- user::UserFavoritesService
  - readFavorites, [135](#)
  - saveFavorites, [136](#)
- user::UserLoginService
  - createAlertSession, [138](#)
  - getUser, [139](#)
  - login, [139](#)
  - logout, [140](#)
  - resetPassword, [140](#), [141](#)
  - sendUsername, [141](#), [142](#)
- user::UserManagementService
  - createUser, [143](#)
  - deleteUser, [144](#)
  - findUserByEmail, [144](#)
  - findUserByMobile, [145](#)
  - findUserByUsername, [145](#)
  - updateUser, [146](#)
- user::UserRepository
  - createUser, [147](#)
  - deleteUser, [148](#)
  - getUserByEmail, [148](#)
  - getUserById, [149](#)
  - getUserByMobile, [149](#)
  - getUserByUsername, [150](#)
  - updateUser, [150](#)
- UserAlertRequestModel, [131](#)
- UserAlertService, [131](#)
- userAlertService
  - alert::service::AlertServiceFactory, [41](#)
- userClient
  - alert::controller::SessionTokenHandler, [102](#)
  - alert::service::RouteAlertExecuteStrategy, [91](#)
  - alert::service::ScheduleAlertExecuteStrategy, [97](#)
- userContactInfo
  - tracking::UserTrackingAlertObject, [153](#)
- UserFavoritesList, [133](#)
  - user::UserFavoritesList, [133](#)
- UserFavoritesRepository, [134](#)
- UserFavoritesService, [135](#)
- UserInformation, [136](#)
- userInformation
  - alert::domain::model::Alert, [27](#)
- UserLoginService, [137](#)
- UserManagementService, [142](#)
- UserRepository, [147](#)
- UserSessionInformation, [151](#)
- userSessionToken
  - alert::domain::model::UserSessionInformation, [152](#)
- UserTrackingAlertObject, [152](#)
- UserType, [153](#)
- validate
  - transit::AbstractFeedParserTemplate, [25](#)
- VehicleObject, [154](#)
- VehicleRepository, [155](#)
- verifySession
  - alert::controller::AlertRequestController, [36](#)
- verifySessionToken
  - alert::client::AlertUserClient, [44](#)
  - alert::controller::CertificateHandler, [52](#)
  - alert::controller::ISessionHandler, [71](#)
  - alert::controller::SessionTokenHandler, [102](#)
- website
  - transit::TransitInfo, [118](#)