

DECLARATION OF PERFORMANCE

THERMAFLEECE COSYWOOL ROLL

- | | |
|--|--|
| 1. Unique identification code of the product-type: | Thermafleece CosyWool Roll. |
| 2. Type , batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): | Thermally bonded non-woven sheep's wool-based insulation. |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Thermal and acoustic insulation for walls, floors and roofs. |
| 4. Name , registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5): | Eden Renewable Innovations Ltd
Soulands Gate, Dacre
Cumbria CA11 0JF |
| 5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | Not applicable |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 4 |
| 7. Notified body (hEN): | Not Applicable |
| 8. Notified body (ETA): | Not Applicable |

9. Declaration of Performance

Essential Characteristic	Performance	Standard	Test Reference	Harmonised Technical Specification
Declared Thermal Conductivity	0.039 WmK ⁻¹	ISO 8302:1991 and BS EN 12667	Report Serial No. 952 / Internal Reference No.: TT11/129	None Available
Reaction to Fire	Class E/E _{FL} /E _L	EN 11925-2 2020 EN 13501-1 2018	Report No. WP431909	
Resistance to Common Clothes Moth (<i>Tineola biselliella</i>)	Pass	ISO 3998	P1KW 1000 CSL SOP EFF/254	
Random Incidence Sound Absorption Coefficient	50mm α_w 0.65(H) 75mm α_w 0.85(H) 100mm α_w 1.00 140mm α_w 1.00	BS EN ISO 354:2003	Report C/21913/C	
Carcinogenic compounds as defined in Annex VI to Regulation (EC) No.1272/2008	n.d. @ 3days n.d. @ 28days	BS EN 16516:2017	Report No. 52696B	
TVOC	9 µg/m ³ @ 3 days n.d. @ 28 days	BS EN 16516:2017	Report No. 52696B	
Formaldehyde	<2 µg/m ³ @ 3 days <2 µg/m ³ @ 28 days	BS ISO 16000-3:2011	Report No. 52696B	

DECLARATION OF PERFORMANCE**THERMAFLEECE COSYWOOL ROLL****10. Declaration**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mark Lynn Managing Director	6th October 2020	
--	------------------------------------	---

Thermafleece CosyWool Roll

Technical Data Sheet



Thermal	
Thermal Conductivity	0.039 Wm ⁻¹ K ⁻¹
Density	18 kg/m ³
Specific Heat Capacity	1800 Jkg ⁻¹ K ⁻¹
Vapour Resistivity	9 MNsg ⁻¹ m ⁻¹

Material Protection	
Mould Resistance CUAP 2002-01-25	Pass
Moth/Beetle Proofing ISO 3998	Pass

Fire	
BS 5803-4, Flammability & Smoulder Resistance	Pass
EN11925-2, Reaction to Fire	Pass
Fire Classification	EuroClass E

Physical	
Recoverability and thickness, EN 823	Pass
Dimensional stability to EN 1604	Pass

Hygrothermal					
Porosity			45.8%		
'Surface' water absorption coefficient (kg/m ² . h ^{0.5})			0.99 (18%)		
'Edge' water absorption coefficient (kg/m ² . h ^{0.5})			0.64 (8.8%)		
Water Vapour Resistance Factor, μ			(-) Dry:1.27 (4.9%) (-) Wet:0.80 (11.8%)		
Vapour sorption:					
Relative Humidity					
Sorption	0%w/w	30%w/w	50%w/w	75%w/w	95%w/w
Moisture Content	0.00%	4.56%	7.21%	10.07%	14.84%
Deviation		(3.3%)	(7.3%)	(7.3%)	(1.9%)
Relative Humidity					
Desorption	95%w/w	75%w/w	50%w/w	30%w/w	0%w/w
Moisture Content	14.84%	11.42%	8.62%	6.09%	0.00%
Deviation	(1.9%)	(3.1%)	(2.7%)	(7.2%)	

Thermafleece CosyWool Roll

Technical Data Sheet



Environmental	
GWP (A1-A3) total	0.05 kgCO ₂ e R1 Functional Unit
GWP (A1-C4) total	0.95 kgCO ₂ e R1 Functional Unit
GWP (A1-D) total	-0.31 kgCO ₂ e R1 Functional Unit
Recycled Content	20%
Recyclable	Yes
EPD registration no	S-P-04468
EPD valid to	31/10/26
Manufactured to ISO 14001	Certificate No: 23/3478

Acoustic							
Sound absorption			NRC 1.05 @ 100mm				
Sound reduction			Rw 40dB @ 75mm				
Can be used to achieve airborne sound reduction of R _w			41dB				
Freq HZ		125	250	500	1000	2000	4000
Cosywool 50mm	Absorption Coefficient	0.2	0.4	0.65	0.75	0.85	0.95
Cosywool 75mm		0.25	0.6	0.85	0.9	0.95	1
Cosywool 100mm		0.45	0.85	1	1	1	1
Cosywool 140mm		0.6	0.9	0.95	1	1	1

Air Quality	
TVOC	9 µg/m ³ @ 3 days, n.d. @ 28 days
Carcinogenic compounds	n.d. @ 3days, n.d. @ 28days
Formaldehyde	<2 µg/m ³ @ 3 days, <2 µg/m ³ @ 28 days

Quality	
Manufactured to ISO 9001	Certificate No: 23/3477

Dimensions	
Thicknesses (+20mm/-0mm)	25, 50, 75, 100, 140, 150 mm
Widths (+20mm/-10mm)	370 & 570 mm
Roll Lengths (+5%/-0%)	12.0 (25mm)13.0 m (50mm), 8.5 m(75mm), 6.5 m (100 mm), 4.6 m (140mm), 4.3 m (150mm)

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland



ecological
BUILDING SYSTEMS

Naturally Better

Discover our solutions online at
ecologicalbuildingsystems.com