

SOLPS-ITER download and installation instructions

Welcome to SOLPS-ITER!

You can generally browse the ITER Git repositories here: <https://git.iter.org> and SOLPS-ITER specifically here: <https://git.iter.org/projects/BND/repos/solps-iter/browse>, but since these repositories are restricted you will first need to authenticate with your ITER username and password – possibly twice, once for the intranet, and once for the Git web front end in the top right-hand corner.

If you upload a copy of your public ssh key here:

<https://git.iter.org/plugins/servlet/ssh/account/keys> (by following links under “Manage Account”), then you should be able to simply clone a copy of SOLPS-ITER to your local machine by doing:

```
> git clone ssh://git@git.iter.org/bnd/solps-iter.git
> cd solps-iter
> git submodule init
> git submodule update
```

If you want to clone SOLPS-ITER into a different directory than the “solps-iter” default name, replace the initial “git clone” command by:

```
> mkdir <my_personal_SOLPS-ITER-directory_name>
> cd <my_personal_SOLPS-ITER-directory_name>
> git clone ssh://git@git.iter.org/bnd/solps-iter.git .
```

Since your userid is immutably encoded into any changes, it's always a good idea to properly configure your local installation of Git on all the systems you plan on making code revisions on with, e.g.:

```
> git config --global user.name "Your Name"
> git config --global user.email your.name@where.you.are
```

You should then position yourself on the master branches in each of the submodules, by doing the following:

```
> git checkout master
> cd modules/B2.5
> git checkout master
> cd ../Eirene
> git checkout master
> cd ../DivGeo
> git checkout master
> cd ../Carre
> git checkout master
> cd ../adas
> git checkout master
```

For later updates, it is recommended you use the script:

> solps-iter_update

If you are planning to do code development, your starting point should be the develop branches, which you can upload by using “solps-iter_update_develop”.

When updating the code in this way, the script will check if you have any local branches where you have done some local work (or if your local work is not yet on a branch), and, if you have not done so already, ask you to commit or stash it first before proceeding. After the update is completed, you will be able to rebase your local work on top of the updated code as necessary. Please check the README file in your \$SOLPSTOP directory for further instructions on how to safeguard your work and update your code version.

The solps-iter_update script automatically recompiles the standard version of the code (no debug, no MPI) but also updates the dependencies lists for all versions. If you wish to recompile others versions of the updated code, you can then do:

> gmake {your favourite target[s] here}

All users have write access to these repositories although not to the develop, master or svn/* branches. This basically means that, for your own development, if any, you should create \$USERNAME/{feature/[topic]|bugfix/[topic]|hotfix/[topic]} branches and raise a Pull Request (<https://git.iter.org/projects/BND/repos/solps-iter/pull-requests>) to have them merged into the develop branch after pushing them back to the ITER repository, where \$USERNAME is your ITER IDM account name. This naming convention is meant to allow the SOLPS-ITER ROs to more easily manage everybody's branches. Please conform to it.

Issues are handled using JIRA (<https://jira.iter.org/browse/IMAS>) and you should feel free to create new issues associated with SOLPS-ITER or any of its submodules (selected from the drop-down list of components) if you have any problems or suggestions. (You can ignore the options associated with resource estimates and sprints.)

For help with Git, we can recommend the documentation here (<http://git-scm.com/>) and the Pro Git book (linked from there) in particular. Another useful resource for novice Git users is the tutorial from Codecademy available at <https://www.codecademy.com/learn/learn-git>.

The documentation specific to SOLPS-ITER can be found at:

<https://portal.iter.org/departments/POP/CM/IMAS/SOLPS-ITER>

and it is visible from here:

<https://imas.iter.org/> (then the “Science Division” tab on the left, and choose “Confinement & Modelling” from the drop-down list, then follow the link to the SOLPS-ITER Folder) and where you will also find a manual on how to raise JIRA issues and pull requests and the like.

In addition, there is an IDM folder, located at <https://user.iter.org/?uid=Q92BAQ>, which contains links to many SOLPS-ITER related documents (those subject to document control procedures and/or presentations about aspects of the code to entities external to the IO, as well as related contract reports).

Once you have cloned the SOLPS-ITER Repository, you may need to modify the configuration files needed so the necessary environment variables are properly defined. Please check the README file and the SOLPS-ITER User Manual (you can use the documentation link above) for details. These

include your domain hostname, defined with the “whereami” script, your preferred compiler, in the “default_compiler” script, the modules you wish to load and your preferred debugger name (given with the DBX=debugger_name command) in SETUP/setup.csh.\$HOST_NAME.\$COMPILER, and the location and linking instructions for the various libraries in SETUP/config.\$HOST_NAME.\$COMPILER. Feel free to look at the examples already present for inspiration. For hosts and compilers on which SOLPS-ITER has already been installed successfully and we know about, we have tried to include these files already in the distribution, but they may be mistaken or incomplete, so please check. In cases where the HOST_NAME is not correctly deduced from the “whereami” script, you can specify your desired HOST_NAME value by means of a SETUP/setup.csh.HOST_NAME.local file, which should contain the line:

```
setenv HOST_NAME <your_desired_HOST_NAME>
```

Once these variables are set, to start a SOLPS-ITER session (every time), from the SOLPS-ITER top directory, you do:

```
> tcsh
> source setup.csh
```

Then, if this is the first installation in your file space, please do:

```
> first_setup
```

This will, if they are not already present in the distribution, create the various config files for each of the SOLPS-ITER submodules. Feel free to modify them afterwards according to your local requirements. We strongly recommend that you do any modifications you may need in local copies of these files, to be named, respectively: SETUP/setup.csh.\$HOST_NAME.\$COMPILER.local and SETUP/config.\$HOST_NAME.\$COMPILER.local. Once you have made the proper modifications, if these are worth sharing with other users on similar platforms, please copy them other into the original files and commit them back to the repository using a pull request.

Then, if all was filled in properly, a simple “gmake” compilation command (and a LOT of patience) will get you a ready-to-run code. You should run the compilation from the SOLPS-ITER top directory, because this is where all the compiler flags are defined and passed down to each of the submodules. The top directory Makefile will also build the SOLPS-ITER Manual, which will be placed in SOLPS-ITER/doc/solps/solps.[pdf|dvi|ps].

For the libraries required at compilation (see the full list in Section 1.2 of the SOLPS-ITER Manual), we recommend these be loaded as modules, which can then be shared across multiple users on a single machine, to make the SOLPS-ITER distribution lighter. With the exception of the GR, MSCL and libsonnet libraries, the libraries are not part of the SOLPS-ITER repository, as the IO does not have distribution rights for them. Libsonnet is built automatically from the SOLPS-ITER Makefile (although you may need to provide a machine architecture environment variable value). GR and MSCL can be obtained from the ITER GIT server at:

<https://git.iter.org/projects/LIB/repos/gr-software/browse>
<https://git.iter.org/projects/LIB/repos/mscl/browse>

When compiling the GR and MSCL libraries, you will need to set two environment variables, in the following way (provided you have already loaded the SOLPS-ITER environment as above):

```
> setenv OBJECTCODE $COMPILER  
> setenv SOLPS_LIB $SOLPSLIB
```

For the others, most are freely available from the Internet, with the exception of the NAG library, for which a pay licence is required. However, the NAG library is not strictly necessary to build SOLPS-ITER. And, if you already have an older version of SOLPS (5.x or 4.x), as distributed by IPP-Garching, you may copy the libraries from it into the SOLPS-ITER/lib/\$HOST_NAME.\$COMPILER directory.

If you have any questions about these instructions or encounter difficulties, feel free to contact the SOLPS-ITER RO at:

xavier.bonnin@iter.org