C++ OOP Header Files Rectangle Tutorial

Contents

1
1
3
6
7

Time required: 60 minutes

Step 1: Single File Rectangle OOP

We will start with a C++ OOP program in a single file.

Enter the following code. This code defines the Rectangle class.

Page 1 of 7 Revised: 2/14/2024

```
* Filename: rectangle oop.cpp
2
     * Written by:
3
4
     * Written on:
5
     * Revised:
      * Calculate the perimeter and area of a rectangle with C++ OOP
6
    L */
7
8
    #include <iostream>
9
    //********************
10
    // Define Rectangle Class
11
    //*********************
12
13
    class Rectangle
14
  □ {
15
        // ----- DEFINE PUBLIC METHODS ----- //
    public:
16
17
        // 2 parameter constructor
18
        Rectangle (double width, double length)
19
20
            this->m width = width;
21
            this->m length = length;
22
23
24
        double get_perimeter()
25
26
            return ((this->m_width * 2) + (this->m_length * 2));
27
28
29
        double get area()
30
31
            this->m area = this->m width * this->m length;
32
            return m_area;
33
        }
34
35
        // ----- DEFINE PRIVATE DATA MEMBERS ----- //
    private:
36
37
        double m_width;
38
        double m length;
39
        double m area;
    L<sub>}</sub>;
40
```

Page 2 of 7 Revised: 2/14/2024

```
//*****************
42
43
        main program entry point
     //*****************
44
45
    int main()
46
   ₽{
47
        double width{2.5};
48
        double length{7.0};
49
        std::cout << "\n -- Rectangle Calculator Single File --\n" << std::endl;
50
        // Create rectangle object with 2 arguments
51
        Rectangle rectanglel (width, length);
52
53
        // Return and display values from object methods
54
        std::cout << " Perimeter: " << rectanglel.get perimeter() << std::endl;
55
        std::cout << " Area: " << rectanglel.get_area() << std::endl;
56
        std::cout << std::endl;
57
58
        // Pause until a key is pressed
59
        system("PAUSE");
60
        return 0;
61
```

Example run:

```
-- Rectangle Calculator Single File --
Perimeter: 19
Area: 17.5
Press any key to continue . . . _
```

Step 2: Rectangle OOP with Multiple Files

As projects become bigger, placing all the code in a single file becomes unmanageable.

rectangle.h defines the public method prototypes and private data members.

Page 3 of 7 Revised: 2/14/2024

```
□/**
2
     * Filename: rectangle.h
3
     * Written by:
     * Written on:
5
     * Revised:
6
    * Header file which defines prototypes for Rectangle class
7
8
   9
    #define RECTANGLE H
10
11
    //*********************
12
13
    // Define Rectangle Class
    //************************
14
15
    class Rectangle
16
   申{
17
        // ----- DEFINE PUBLIC METHOD PROTOTYPES ----- //
    public:
18
19
        // 2 parameter constructor prototype
20
        Rectangle (double width, double length);
21
        double get perimeter();
22
        double get area();
23
        // ----- DEFINE PRIVATE DATA MEMBERS -----
24
25
    private:
26
        double m width;
        double m length;
27
       double m area;
28
29
    - } ;
    #endif
30
```

rectangle.ccp implements the public methods and data members defined in the **rectangle.h** file.

Page 4 of 7 Revised: 2/14/2024

```
* Filename: rectangle.cpp
 2
 3
     * Written by:
     * Written on:
4
     * Revised:
 5
     * Implement Rectangle class constructor and methods
 6
7
8
9
   #include "rectangle.h"
10
11
    // ----- IMPLEMENT PUBLIC METHODS -----//
12
     // Implement 2 parameter constructor
13
   Rectangle::Rectangle(double width, double length)
14 □{
15
        this->m width = width;
16
         this->m_length = length;
17
18
19
   double Rectangle::get perimeter()
20
    ₽ {
21
         return ((this->m width * 2) + (this->m length * 2));
22
23
24
   double Rectangle::get area()
25
   ₽ {
26
         this->m_area = this->m_width * this->m_length;
27
         return m area;
28
```

rectangle_main.cpp is the main program which uses the previous 2 files.

Page 5 of 7 Revised: 2/14/2024

```
* Filename: rectangle_main.cpp
       * Written by:
 3
      * Written on:
 4
 5
       * Revised:
       * Calculate the perimeter and area of a rectangle
 6
 7
       * using header files with OOP
     L */
 8
 9
      #include <iostream>
     #include "rectangle.h"
10
11
12
     int main()
13
    □ 早 {
14
          double width{2.5};
15
          double length {7.0};
16
          std::cout << "\n -- Rectangle Calculator Multiple Files --\n" << std::endl;
17
          // Create rectangle object with 2 arguments
18
          Rectangle rectanglel (width, length);
19
20
          // Return values from object methods
          std::cout << " Perimeter: " << rectanglel.get_perimeter() << std::endl;</pre>
21
          std::cout << " Area: " << rectanglel.get area() << std::endl;
22
23
          std::cout << std::endl;
24
25
          // Pause until a key is pressed
26
          system("PAUSE");
27
          return 0;
28
```

Step 3: Build G++ Multiple File Projects

```
g++ -Wall rectangle.h rectangle_main.cpp rectangle.cpp -o rectangle_main.exe
pause
```

Instead of typing this in every time, let's make a batch file for this.

- 1. In VSCode → create a file named: **compile.bat**
- 2. Copy the above code and paste it into the batch file.
- 3. The pause command on the second line pauses the command line window so you can see if it worked or not.
- 4. In File Explorer → Double Click **compile.bat**

Example run:

Page 6 of 7 Revised: 2/14/2024

```
-- Rectangle Calculator Multiple Files --
Perimeter: 19
Area: 17.5
Press any key to continue . . . _
```

Assignment Submission

- 1. Attach the program files.
- 2. Attach screenshots showing the successful operation of the program.
- 3. Submit in Blackboard.

Page 7 of 7 Revised: 2/14/2024