PythonPing Network Scanner Tutorial

Contents

PythonPing Network Scanner Tutorial 1
Find Network Address 1
Find Your Network IP Address in Windows 1
Tutorial 1: PythonPing 3
Tutorial 2: Scan Your Network from Windows 5
Tutorial 3: Scan Your Network from Linux 8
PythonPing Scanner in Linux 8
Assignment Submission 9

Time required: 60 minutes

Objective: Write a cross platform Python script that uses branching, looping, and pythonping to scan a local network.

Find Network Address

If you are using a VM, set to a bridged adapter.

Find Your Network IP Address in Windows

Use the network address of your local network. Example: 192.168.0.0/24

NOTE: 192.168.56.1 is the VirtualBox adapter address, that is not your network address.

1. Enter the following command at the command prompt: **ipconfig /all**
2. The screenshot below shows my network at home, 192.168.9 Your IP address will probably be different. I have an Ethernet adapter, you may have a wireless adapter.
3. Notice that my IP address information includes a Default Gateway, DHCP Server, and DNS Servers. Those are needed for a functioning network connection.
4. Note that my IPv4 Address for my computer is **192.168.9.101** My subnet Mask is **255.255.255.0** This makes my network a standard Class C network.

5. A typical home network address is **192.168.1.0/24**

If you are not sure about this, please contact me. You will get a 0 for this assignment if you do not provide a screenshot showing a successful scan of your network.

```
C:\Users\Bill.THECOMPUTERGUY>ipconfig /all

Windows IP Configuration

   Host Name . . . . . . . . . . . . : Bill-PC
   Primary Dns Suffix  . . . . . . . : thecomputerguy.local
   Node Type . . . . . . . . . . . . : Hybrid
   IP Routing Enabled. . . . . . . . : No
   WINS Proxy Enabled. . . . . . . . : No
   DNS Suffix Search List. . . . . . : thecomputerguy.local
                                       lan

Ethernet adapter Ethernet:

   Connection-specific DNS Suffix  . : lan
   Description . . . . . . . . . . . : Realtek PCIe GbE Family Controller
   Physical Address. . . . . . . . . : 2C-F0-5D-A2-AC-3E
   DHCP Enabled. . . . . . . . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes
   Link-local IPv6 Address . . . . . : fe80::b08b:b38e:4b9d:3e9b%7(Preferred)
   IPv4 Address. . . . . . . . . . . : 192.168.9.101(Preferred)
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Lease Obtained. . . . . . . . . . : Friday, April 15, 2022 6:32:36 AM
   Lease Expires . . . . . . . . . . : Sunday, April 17, 2022 6:32:37 AM
   Default Gateway . . . . . . . . . : 192.168.9.1
   DHCP Server . . . . . . . . . . . : 192.168.9.1
   DHCPv6 IAID . . . . . . . . . . . : 103608413
   DHCPv6 Client DUID. . . . . . . . : 00-01-00-01-27-89-4B-A4-2C-F0-5D-A2-AC-3E
   DNS Servers . . . . . . . . . . . : 192.168.9.10
                                       8.8.8.8
   NetBIOS over Tcpip. . . . . . . . : Enabled

Ethernet adapter VirtualBox Host-Only Network:

   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : VirtualBox Host-Only Ethernet Adapter
   Physical Address. . . . . . . . . : 0A-00-27-00-00-0F
   DHCP Enabled. . . . . . . . . . . : No
   Autoconfiguration Enabled . . . . : Yes
   Link-local IPv6 Address . . . . . : fe80::b0d1:22cf:dacc:d009%15(Preferred)
   IPv4 Address. . . . . . . . . . . : 192.168.56.1(Preferred)
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . :
   DHCPv6 IAID . . . . . . . . . . . : 168427559
   DHCPv6 Client DUID. . . . . . . . : 00-01-00-01-27-89-4B-A4-2C-F0-5D-A2-AC-3E
   DNS Servers . . . . . . . . . . . : fec0:0:0:ffff::1%1
                                       fec0:0:0:ffff::2%1
                                       fec0:0:0:ffff::3%1
   NetBIOS over Tcpip. . . . . . . . : Enabled
```

Tutorial 1: PythonPing

Security professionals often need to automate or create tools to help them conduct security tests. In this activity, you will write a Python script that uses the ping command and a for loop to ping IP numbers for an entire network.

1. Install the pythonPing library. Enter the following command at a command prompt.

```
# Windows
pip install pythonping
# Linux
sudo pip3 install pythonping
```

2. Create a new file called **pythonping_scanner_1.py**.

3. Enter the following code including the comments.

```python
"""
    Filename: pythonping_scanner_1.py
    This program prompts the user to enter a host address
    Uses the pythonping library to send out ping packets
"""

# Windows: pip install pythonping
# Linux Debian distributions:
#     sudo apt update
#     sudo pip3 install pythonping
#     Use sudo to run script: sudo python3 pythonping_scanner.py
from pythonping import ping


def main():
    # Print program title
    print(48 * "-")
    print("|              Python Network Ping              |")
    print(48 * "-")
    # Get ip address or hostname
    host_address = input(" Enter single IP address or hostname: ")
    # Scan host
    result = scan(host_address)
    print(result)


# ------------------------ PING HOST ADDRESS ----------------------------#
def scan(host_address: str) -> str:
    """Ping the target, return a string response."""
    result = ping(host_address)
    return result


# If a standalone program, call the main function
# Else, use as a module
if __name__ == "__main__":
    main()
```

Example run:

This program pings a single IP address or host name.

```
------------------------------------------------
|         Python Network Ping Scanner          |
------------------------------------------------
 Press CTRL C to exit
IP address or hostname: 1.1.1.1
Reply from 1.1.1.1, 29 bytes in 15.44ms
Reply from 1.1.1.1, 29 bytes in 15.62ms
Reply from 1.1.1.1, 29 bytes in 16.05ms
Reply from 1.1.1.1, 29 bytes in 15.58ms

Round Trip Times min/avg/max is 15.44/15.67/16.05 ms
```

```
-----------------------------------------------
|         Python Network Ping Scanner          |
-----------------------------------------------
 Press CTRL C to exit
IP address or hostname: lab.wncc.net
Reply from 198.206.239.241, 29 bytes in 22.59ms
Reply from 198.206.239.241, 29 bytes in 22.25ms
Reply from 198.206.239.241, 29 bytes in 21.8ms
Reply from 198.206.239.241, 29 bytes in 22.06ms

Round Trip Times min/avg/max is 21.8/22.18/22.59 ms
```

Tutorial 2: Scan Your Network from Windows

Let's scan your entire local network. Only scan networks where you have permission.

```python
#!/usr/bin/env python3
"""
    Filename: pythonping_scanner_2.py
    This program prompts the user to enter a class C network address
    it uses the pythonping library to send out ping packets
"""

# Windows: pip install pythonping
# Linux Debian distributions:
#     sudo apt update
#     sudo pip3 install pythonping
#     Use sudo to run script: sudo python3 pythonping_scanner.py
from pythonping import ping
# https://docs.python.org/3/library/ipaddress.html
# Convert ip/mask to list of hosts
import ipaddress
import sys


def main():
    display_program_title()

    # ------------------------ SET NETWORK ADDRESS -------------------------#
    """Set network address x.x.x.x/x or x.x.x.x/x.x.x.x from user"""
    # Change this to the default value of your network
    default_local_network = "192.168.9.0/24"
    # Prompt the user to input a network address and press Enter
    # If they press enter without an network address, the default is used
    network_address = input(
        "\n Enter your network address (ex. 192.168.9.0/24): "
    ) or default_local_network
    # Create a network address object from user input
    ip_net = ipaddress.ip_network(network_address)

    # Convert all hosts on entered network into a list
    all_hosts = list(ip_net.hosts())
    scan(all_hosts)
```

```python
# ------------------------- SCAN NETWORK -------------------------------------#
def scan(all_hosts: str):
    """Ping all Class C IP addresses 1-254"""
    for host_address in all_hosts:
        ip = str(host_address)
        try:
            result = ping(
                ip,  # Target IP address
                count=1,    # Number of pings
                timeout=2   # Timeout in seconds
            )

            if result.rtt_avg_ms < 1000:
                # If the response time is less than 1000ms,
                # there is a active target
                print(f" {ip} --> Alive RTT: {result.rtt_avg_ms:5}")
            else:
                # If greater than 1000ms, no response
                print(f" {ip} Inactive")

        except KeyboardInterrupt:
            # Catch the Keyboard Interrupt exception
            print("CTRL-C pressed. Exit program")
            sys.exit()

        except Exception as e:
            # Catch all other exceptions
            # Print out the exception error for debugging
            print("Sorry", e)
            sys.exit()


# --------------------- DISPLAY PROGRAM TITLE ------------------------------#
def display_program_title():
    """Print program title to console"""
    print(35 * "-")
    print("|   Python Network Ping Scanner   |")
    print(35 * "-")
    print(" Press CTRL C to exit")


# If a standalone program, call the main function
# Else, use as a module
if __name__ == "__main__":
    main()
```

1. Open a command prompt and navigate to the folder containing your **pythonping_scanner.py** file.

2. Type: **python pythonping_scanner.py** Press **Enter**.

3. If you have no errors, your program should begin pinging IP addresses, as shown below.

4. You can let the program run to completion (which will take a long time) or press **CTRL C** to terminate the script.

Example run in Windows:

```
-----------------------------------
|   Python Network Ping Scanner   |
-----------------------------------
 Press CTRL C to exit

 Enter your network address (ex. 192.168.9.0/24): 192.168.9.0/24
 192.168.9.1 --> Alive RTT:  0.53
 192.168.9.2 Inactive
 192.168.9.3 Inactive
 192.168.9.4 Inactive
 192.168.9.5 Inactive
 192.168.9.6 Inactive
 192.168.9.7 Inactive
 192.168.9.8 Inactive
 192.168.9.9 Inactive
 192.168.9.10 --> Alive RTT:  0.39
 192.168.9.11 Inactive
```

Tutorial 3: Scan Your Network from Linux

NOTE: If your class is using Linux for other assignments, complete this portion of the assignment.

This is a cross platform script. It will work on Windows or Linux or Mac. Copy and paste the code into Linux. Follow the directions in the program to install the **pythonping** library in Linux.

Your network in Linux should be the same as your network in Windows. If it isn't, set your VirtualBox network settings to Bridged Adapter.

PythonPing Scanner in Linux

This will work on most Linux systems include older distributions of Kali Linux. Try this first.

1. Open a terminal session.

2. Update software package lists: **sudo apt update**

3. Install pip3: **sudo apt install python3-pip**

4. Determine your version of Python: **python3**

5. Press **CTRL D** to exit the Python prompt.

6. Install the **pythonping** library

    a. **Python 3.10 and lower**: **sudo pip3 install pythonping**

    b. **Python 3.11: sudo pip3.11 install pythonping**

7. In a terminal → **sudo python3 pythonping_scanner.py**

8. Example run in Linux:

```
┌──(user㉿kali)-[~]
└─$ sudo python3 pythonping_scanner.py
[sudo] password for user:
+-------------------------------+
|   Python Network Ping Scanner |
+-------------------------------+
Press CTRL C to exit
Enter a class C network address (ex.192.168.1): 192.168.9
192.168.9.1 ──> Alive RTT: 0.75
192.168.9.2 Inactive
192.168.9.3 Inactive
192.168.9.4 Inactive
192.168.9.5 Inactive
192.168.9.6 Inactive
192.168.9.7 Inactive
192.168.9.8 Inactive
192.168.9.9 Inactive
192.168.9.10 ──> Alive RTT: 1.1
192.168.9.11 Inactive
192.168.9.12 Inactive
192.168.9.13 Inactive
192.168.9.14 Inactive
192.168.9.15 Inactive
192.168.9.16 Inactive
```

This scanner isn't very fast, but it works. To get faster results, we would use multithreading.

Assignment Submission

1. Attach all program files.

2. Attach a screenshot of each successful program run.

3. If you do not attach a screenshot of a successful program run on your correct network address, you will receive a 0 for this assignment.

4. Submit the assignment in Blackboard.