Week 10 Python Statistics Activities

Contents

Week 10 Python Statistics Activities 1
Descriptive Statistical Functions in Python 1
Basic Statistics Functions 1
Tutorial 1: Mean 2
Tutorial 2: Median 4
Tutorial 3: Mode 6
Tutorial 4: Standard Deviation 7
Tutorial 5: Variance 8
Tutorial 6: MIN and MAX 9
Assignment 1: Statistical Analysis of a Dataset 10
Assignment Submission 13

Time required: 60 minutes

1. Only create the Python tutorial code.
2. Save all code in a Google Colab Notebook.

Descriptive Statistical Functions in Python

This tutorial will guide you through using various descriptive statistical functions in Python. It covers basic functions like finding the mean, standard deviation, and median, as well as advanced functions like calculating percentiles and performing moving statistics.

Basic Statistics Functions

Python provides numerous functions for computing descriptive statistics. Here are some commonly used ones:

- **sum(x)**: Sums all elements in vector
- **min(x)**: Finds the minimum element in the vector `x`.
- **max(x)**: Finds the maximum element in the vector `x`.

- **mean(x)**: Calculates the average of all elements in `x`.
- **median(x)**: Finds the middle value of `x` when sorted in ascending order.
- **mode(x)**: Find the value that occurs the most.
- **std(x)**: Computes the standard deviation of `x`.
- **var(x)**: Calculates the variance of `x`, which is the square of the standard deviation.

Tutorial 1: Mean

Mean, also known as the average, is a measure of central tendency that represents the typical value of a set of numbers.

- It is calculated by summing up all the values in the dataset and dividing the sum by the total number of values.
- The mean is sensitive to extreme values, also known as outliers, as they can significantly influence its value.
- It is widely used in statistics, mathematics, and various fields of science and engineering to describe the central tendency of data.

These MATLAB program examples are from an earlier assignment. Let's see how to complete this program in Python using numpy.

MATLAB

```
% Mean (Average)

% Define a vector
vect = [2, 5, 1, 7, 3, 2];

% How many elements in the vector
n = length(vect);

% mean by definition
meanVal = sum(vect) / n;

% mean by function
meanVal = mean(vect);

fprintf("Vector: ");
fprintf("%d ", vect);
fprintf("\n");
fprintf("Mean: %.2f\n", meanVal);
```

Example run:

```
Vector: 2 5 1 7 3 2
Mean: 3.33
```

Python

NumPy is a Python library for numerical computing that provides support for large, multi-dimensional arrays and matrices, along with a collection of mathematical functions to operate on these arrays efficiently. It is widely used in scientific computing, data analysis, and machine learning due to its speed, versatility, and ease of use. NumPy's ndarray (N-dimensional array) data structure enables efficient computation and manipulation of large datasets, making it an essential tool for numerical tasks in Python.

A numpy array is the same as a MATLAB vector.

Add the following code to your Google Colab Notebook.

```python
# Mean (Average)
import statistics as st

# Define a Python list
vect = [2, 5, 1, 7, 3, 2]

# How many elements in the list
n = len(vect)

# mean by definition
mean_val = sum(vect) / n

# Calculate mean using Python's statistics mean functior
mean_val = st.mean(vect)

print(f"List: {vect}")
print(f"Mean: {mean_val:.2f}")
```

Example run:

```
List: [2, 5, 1, 7, 3, 2]
Mean: 3.33
```

Tutorial 2: Median

- The **median** is a statistical measure that represents the middle value of a dataset when it is ordered from smallest to largest.
- It is robust to outliers and extreme values, making it a useful measure of central tendency, particularly in skewed distributions.
- To compute the median, the dataset is arranged in ascending order, and the middle value is selected. If the dataset has an odd number of observations, the median is the middle value. If the dataset has an even number of observations, the median is the average of the two middle values.
- Unlike the mean, which can be influenced by extreme values, the median is less affected by outliers, making it a better representation of the central tendency in skewed distributions or datasets with extreme values.

MATLAB

```
%% Median (Mid point)
% Define a vector
vect = [2, 5, 1, 7, 3, 2];

% median by function
midVal = median(vect);

fprintf("Vector: ");
fprintf("%d ", vect);
fprintf("\n");
fprintf("Median: %.2f\n", midVal);
```

Example run:

```
Vector: 2 5 1 7 3 2
Median: 2.50
```

Python

To calculate the median with Python, let's again turn to numpy.

Add the following code to your Google Colab Notebook.

```
# Median (Mid point)
import statistics as st

# Define a Python List
vect = [2, 5, 1, 7, 3, 2]

# Calculate median using Python's statistics library
median_val = st.median(vect)

print(f"  List: {vect}")
print(f"Median: {median_val:.2f}")
```

Example run:

```
  List: [2, 5, 1, 7, 3, 2]
Median: 2.50
```

Tutorial 3: Mode

Mode: In statistics, the mode represents the value or values that occur most frequently in a dataset.

- It is one of the measures of central tendency, along with mean and median, providing insight into the central or typical value of a dataset.
- The mode can be particularly useful for categorical or discrete data, where it represents the most common category or value.
- Unlike mean and median, which require numerical data, the mode can be applied to any type of data, including categorical and ordinal data.
- A dataset may have one mode (unimodal), multiple modes (multimodal), or no mode if all values occur with equal frequency.
- Computing the mode involves identifying the value with the highest frequency or frequencies in the dataset.

The mode of a set of data is the most common data point.

MATLAB

```
%% Mode (Most common data point)
% Define a vector
vect = [2, 5, 1, 7, 3, 2];

% mode by function
modVal = mode(vect);

fprintf("Vector: ");
fprintf("%d ", vect);
fprintf("\n");
fprintf("Mode: %.2f\n", modVal);
```

Example run:

```
Vector: 2 5 1 7 3 2
Mode: 2.00
```

Python

Numpy does not have a mode function. We will use Python's built in statistics library, statistics.

```python
# Mode (Most common data point)
import statistics as st

# Define a Python list
vect = [2, 5, 1, 7, 3, 2]

# Calculate mode using Python's statistics library
mod_val = st.mode(vect)
print(f"List: {vect}")
print(f"Mode: {mod_val:.2f}")
```

Example run:

```
List: [2, 5, 1, 7, 3, 2]
Mode: 2.00
```

Tutorial 4: Standard Deviation

- **Standard Deviation**: Standard deviation is a measure of the dispersion or spread of a set of values from their mean (average) value.
- It quantifies the amount of variation or dispersion in a dataset, indicating how much individual data points deviate from the mean.
- A low standard deviation suggests that the data points tend to be close to the mean, while a high standard deviation indicates that the data points are spread out over a wider range of values.

MATLAB

```MATLAB
%% Standard Deviation (How spread out the data points are)
% Define a vector
vect = [2, 5, 1, 7, 3, 2];

% standard deviation by function
stdVal = std(vect);

fprintf("Vector: ");
fprintf("%d ", vect);
fprintf("\n");
fprintf("Standard Deviation: %.2f\n", stdVal);
```

Example run:

```
Vector: 2 5 1 7 3 2
Standard Deviation: 2.25
```

Python

```python
# Standard Deviation (How spread out the data points are)
import statistics as st

# Define a Python list
vect = [2, 5, 1, 7, 3, 2]

# Calculate standard deviation using Python's statistics library
std_val = st.stdev(vect)

print(f"              List: {vect}")
print(f"Standard Deviation: {std_val:.2f}")
```

Example run:

```
              List: [2, 5, 1, 7, 3, 2]
Standard Deviation: 2.25
```

Tutorial 5: Variance

MATLAB

```MATLAB
%% Variance (How spread out from average)
% Define a vector
vect = [2, 5, 1, 7, 3, 2];

% variance by function
varVal = var(vect);

fprintf("Vector: ");
fprintf("%d ", vect);
fprintf("\n");
fprintf("Variance: %.2f\n", varVal);
```

Example run:

```
Vector: 2 5 1 7 3 2
Variance: 5.07
```

Python

```python
# Variance (How spread out from average)
import statistics as st

# Define a Python list
vect = [2, 5, 1, 7, 3, 2]

# Calculate variance using Python's statistics library
var_val = st.variance(vect)

print(f"    List: {vect}")
print(f"Variance: {var_val:.2f}")
```

Example run:

```
    List: [2, 5, 1, 7, 3, 2]
Variance: 5.07
```

Tutorial 6: MIN and MAX

Pretty simple, the largest and smallest numbers of a dataset.

MATLAB

```MATLAB
%% MIN and MAX
% Define a vector
vect = [2, 5, 1, 7, 3, 2];

% Find minimum and maximum values
minVal = min(vect);
maxVal = max(vect);

fprintf("Vector: ");
fprintf("%d ", vect);
fprintf("\n");
fprintf("Min: %.2f Max: %.2f\n", minVal, maxVal);
```

Example run:

```
Vector: 2 5 1 7 3 2
Min: 1.00 Max: 7.00
```

Python

```python
# Min and Max
# Define a Python list
vect = [2, 5, 1, 7, 3, 2]

# Calculate min and max using Python
var_min = min(vect)
var_max = max(vect)

print(f"List: {vect}")
print(f" Min: {var_min:.2f} Max: {var_max:.2f}")
```

Example run:

```
List: [2, 5, 1, 7, 3, 2]
 Min: 1.00 Max: 7.00
```

Assignment 1: Statistical Analysis of a Dataset

Objective: Apply statistical techniques using Python to analyze and interpret data.

MATLAB

1. Import **students.csv** into MATLAB.

```MATLAB
% Import the dataset
data = readtable('students.csv','PreserveVariableNames',true);
```

2. Display the dataset to see the columns and rows.

```MATLAB
% Display the dataset
disp('Dataset:');
disp(data);
```

3. Extract the relevant columns.

```MATLAB
% Extract relevant columns
mathScores = data.MathScore;
englishScores = data.EnglishScore;
scienceScores = data.ScienceScore;
```

4. Calculate and display basic descriptive statistics (mean, median, mode, and standard deviation) for MathScore, EnglishScore, and ScienceScore. MathScore is shown here as an example of how to complete the others.

```
% Calculate and display statistics for MathScore
disp('Statistics for MathScore:');
fprintf("Mean: %.2f\n", mean(mathScores));
fprintf('Median: %.2f\n', median(mathScores));
fprintf('Mode: %.2f\n', mode(mathScores));
fprintf('Standard Deviation: %.2f\n', std(mathScores));
```

5. Calculate and display English Scores, and Science Scores.

Example run:

```
Dataset:
    StudentID       FirstName         LastName      MathScore    EnglishScore    ScienceScore
    _________    _______________    ____________    _________    ____________    ____________

        1        {'John'       }    {'Doe'     }       85            90              88
        2        {'Jane'       }    {'Smith'   }       78            85              92
        3        {'Michael'    }    {'Johnson' }       92            89              95
        4        {'Emily'      }    {'Williams'}       92            91              86
        5        {'Christopher'}    {'Brown'   }       76            80              78
        6        {'Amy'        }    {'Jones'   }       94            89              93
        7        {'Robert'     }    {'Davis'   }       83            87              93
        8        {'Olivia'     }    {'Miller'  }       79            82              85
        9        {'William'    }    {'Anderson'}       88            94              89
       10        {'Sophia'     }    {'Martin'  }       91            96              94

Statistics for MathScore:
Mean: 85.50
Median: 86.50
Mode: 92.00
Standard Deviation: 6.56
Statistics for EnglishScore:
Mean: 88.30
Median: 89.00
Mode: 89.00
Standard Deviation: 4.99
Statistics for ScienceScore:
Mean: 89.30
Median: 90.50
Mode: 93.00
Standard Deviation: 5.25
```

Python

1. Import **students.csv** into Python from GitHub

2. Right click the link below → Copy Link → Paste the link into the code as shown.

https://raw.githubusercontent.com/itinstructor/JupyterNotebooks/main/Datasets/students.csv

```
import pandas as pd
import statistics as st
# Import the dataset
data = pd.read_csv('https://raw.githubusercontent.com/itinstructor/JupyterNotebooks/main/Datasets/students.csv')
```

3. Display the dataset to see the columns and rows.

```
# Display the dataset
print('Dataset:')
print(data)
print('')
```

4. Extract the relevant columns.

```
# Extract relevant columns
math_scores = data['MathScore']
english_scores = data['EnglishScore']
science_scores = data['ScienceScore']
```

5. Calculate and display basic descriptive statistics (mean, median, mode, and standard deviation) for MathScore, EnglishScore, and ScienceScore. MathScore is shown here as an example of how to complete the others.

```
# Calculate and display statistics for MathScore
print('Statistics for MathScore:')
print(f"Mean: {st.mean(math_scores):.2f}")
print(f"Median: {st.median(math_scores):.2f}")
print(f"Mode: {st.mode(math_scores):.2f}")
print(f"Standard Deviation: {st.stdev(math_scores):.2f}")
print('')
```

6. To finish the program on your own, calculate and display English Scores, and Science Scores.

Example run:

```
Dataset:
   StudentID    FirstName  LastName  MathScore  EnglishScore  ScienceScore
0          1         John       Doe         85            90            88
1          2         Jane     Smith         78            85            92
2          3      Michael   Johnson         92            89            95
3          4        Emily  Williams         92            91            86
4          5  Christopher     Brown         76            80            78
5          6          Amy     Jones         94            89            93
6          7       Robert     Davis         83            87            93
7          8       Olivia    Miller         79            82            85
8          9      William  Anderson         88            94            89
9         10       Sophia    Martin         91            96            94

Statistics for MathScore:
Mean: 85.80
Median: 86.50
Mode: 92.00
Standard Deviation: 6.56

Statistics for EnglishScore:
Mean: 88.30
Median: 89.00
Mode: 89.00
Standard Deviation: 4.99

Statistics for ScienceScore:
Mean: 89.30
Median: 90.50
Mode: 93.00
Standard Deviation: 5.25
```

Assignment Submission

1. Insert a shared link to your Google Colab notebook that anyone can open.
2. Attach a screenshot of the Command Window showing the successful execution of each script.
3. Attach all to the assignment in Blackboard.