

# Deep Learning 182, HW #1

Roy Uziel	Irit Chelly
111111111111	021565510

April 23, 2018

## 1 Network architecture

In our graph we used convolutional layers. The input image is of size 28\*28.

```
1 new_input = tf.reshape(input_images, [-1, 28, 28, 1])
```

We defined the following hidden layers:

### 1. Convolutional Layer 1:

We used 32 filters, each filter is a kernel of size 5\*5. Each neuron in this layer is a result (scalar) of a convolution of each kernel centered on one neuron in the input layer. Thus, this layer consists of 28\*28\*32 neurons. We then compute the activation function relu on the result of each neuron:

```
1 conv1 = tf.layers.conv2d(  
2     inputs=new_input,  
3     filters=32,  
4     kernel_size=[5, 5],  
5     padding="same",  
6     activation=tf.nn.relu)
```

### 2. Pooling Layer 1:

Here we reduce the spatial size of the last layer by using a Max Pooling filter of size 2\*2 and apply the maximum value of each 2\*2 sized part of the image (Convolutional Layer 1):

```
1 pool2 = tf.layers.max_pooling2d(inputs=conv2, pool_size=[2,  
2], strides=2)
```

- 5.2 attach a short document describing the network architecture and any other architectures that you tested
- 5.3 Make sure to have your full name and ID on the top of the document
- 5.4 It is recommended to add tensorboard screenshots that describe the results (Optional)