

K-Nearest Neighbor Based Spoken Letter Recognition



Annika Shankwitz
Department of Linguistics

Spoken Letter Recognition

- Hearing a letter pronounced → Identifying the written letter

Spoken Letter Recognition

- Hearing a letter pronounced → Identifying the written letter



ISOLET – the Isolated Letter Speech Recognition Database

- Contains isolated spoken letters of the English alphabet
 - 150 speakers, 2 productions of the alphabet per speaker
 - 7,800 instances
 - 617 acoustical features

ISOLET – the Isolated Letter Speech Recognition Database

- Contains isolated spoken letters of the English alphabet
 - 150 speakers, 2 productions of the alphabet per speaker
 - 7,800 instances
 - 617 acoustical features
- Has 5 parts: ISOLET1-5
 - Each part contains 30 speakers, 15 male and 15 female
 - Training: ISOLET1-4 (80%)
 - Testing: ISOLET5 (20%)

ISOLET – Previous Work

- Neural network – 95.5% accuracy
- Hidden Markov Model – 96.6% accuracy

ISOLET – Previous Work

- Neural network – 95.5% accuracy
- Hidden Markov Model – 96.6% accuracy
- International Olympic Committee algorithm – KNN algorithm designed for high-dimensional, multi-class classification tasks
 - ↑ Only KNN approach applied to ISOLET

Research Questions

Q1: Does a KNN model perform well on ISOLET?

↑ with techniques to reduce data dimensionality and increase model efficiency

Q2: Which spoken letters are easiest for the KNN model to classify?

Q3: Which spoken letters are hardest for the KNN model to classify?

Methodology – Data Preprocessing


- Min-Max scaling

Methodology – Data Preprocessing

- Min-Max scaling
- PCA
 - 617 dimensions → 179 dimensions
(while capturing 95% of variance)

Methodology – Data Preprocessing

- Min-Max scaling
- PCA
 - 617 dimensions → 179 dimensions (while capturing 95% of variance)
 - Some classes form distinct clusters
 - H, R, O
 - Most classes don't form distinct clusters



Methodology – the KNN model

- Scikit-learn's KNeighborsClassifier()
 - gridSearchCV()
 - $k = [1, 3, 5, 7, 9, 11, 13, 15, 17, 19, 21]$
 - weights= uniform vs distance
 - algorithm = ball tree vs KD tree
 - 5-fold cross validation


Methodology – the KNN model

- Scikit-learn's KNeighborsClassifier()
 - gridSearchCV()
 - $k = [1, 3, 5, 7, 9, 11, 13, 15, 17, 19, 21]$
 - weights= uniform vs distance
 - algorithm = ball tree vs KD tree
 - 5-fold cross validation
- Best Parameters
 - $k = 9$
 - weights = distance
 - algorithm = ball tree

Q1: Does a KNN model perform well on ISOLET?

Yes!

- Macro-Precision: 0.93
- Macro-Recall: 0.93
- Macro-F1 score: 0.93
- Accuracy: 0.93




Q1: Does a KNN model perform well on ISOLET?

Yes!

- Macro-Precision: 0.93
- Macro-Recall: 0.93
- Macro-F1 score: 0.93
- Accuracy: 0.93

Compared to Previous Work:

- 2.5% less accurate than a neural network
- 3.6% less accurate than a Hidden Markov Model
 - ↑ both more complicated models



Q2: Which spoken letters are easiest for the KNN model to classify?

- H (F1 score 1.0)
- I (F1 score 0.99)
- O (F1 score 0.99)
- R (F1 score 0.99)
- W (F1 score 0.99)
- X (F1 score 0.99)
- Y (F1 score 1.0)

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	N	[ɛn]
B	[bi]	<u>O</u>	[ow]
C	[si]	P	[pi]
D	[di]	Q	[kju]
E	[i]	<u>R</u>	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
<u>H</u>	[eɪtʃ]	U	[ju]
<u>I</u>	[aɪ]	V	[vi]
J	[dʒeɪ]	<u>W</u>	[də.bɪ.ju]
K	[keɪ]	<u>X</u>	[ɛks]
L	[ɛl]	<u>Y</u>	[waɪ]
M	[ɛm]	Z	[zi]

Q2: Which spoken letters are easiest for the KNN model to classify?

- H (F1 score 1.0)
- I (F1 score 0.99)
- O (F1 score 0.99)
- R (F1 score 0.99)
- W (F1 score 0.99)
- X (F1 score 0.99)
- Y (F1 score 1.0)
- All have distinct pronunciations

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	N	[ɛn]
B	[bi]	<u>O</u>	[ow]
C	[si]	P	[pi]
D	[di]	Q	[kju]
E	[i]	<u>R</u>	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
<u>H</u>	[eɪtʃ]	U	[ju]
<u>I</u>	[aɪ]	V	[vi]
J	[dʒeɪ]	<u>W</u>	[də.bɪ.ju]
K	[keɪ]	<u>X</u>	[ɛks]
L	[ɛl]	<u>Y</u>	[waɪ]
M	[ɛm]	Z	[zi]

Q3: Which spoken letters are hardest for the KNN model to classify?

- B (F1 score 0.79)
- M (F1 score 0.84)
- N (F1 score 0.84)
- P (F1 score 0.84)
- V (F1 score 0.85)

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	<u>N</u>	[ɛn]
<u>B</u>	[bi]	O	[ow]
C	[si]	<u>P</u>	[pi]
D	[di]	Q	[kju]
E	[i]	R	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
H	[eɪtʃ]	U	[ju]
I	[aɪ]	<u>V</u>	[vi]
J	[dʒeɪ]	W	[də.bəl.ju]
K	[keɪ]	X	[ɛks]
L	[ɛl]	Y	[waɪ]
<u>M</u>	[ɛm]	Z	[zi]

Q3: Which spoken letters are hardest for the KNN model to classify?

- B (F1 score 0.79)
- M (F1 score 0.84)
- N (F1 score 0.84)
- P (F1 score 0.84)
- V (F1 score 0.85)
- All do not have distinct pronunciations

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	<u>N</u>	[ɛn]
<u>B</u>	[bi]	O	[ow]
C	[si]	<u>P</u>	[pi]
D	[di]	Q	[kju]
E	[i]	R	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
H	[eɪtʃ]	U	[ju]
I	[aɪ]	<u>V</u>	[vi]
J	[dʒeɪ]	W	[də.bɪ.ju]
K	[keɪ]	X	[ɛks]
L	[ɛl]	Y	[waɪ]
<u>M</u>	[ɛm]	Z	[zi]

Q3: Which spoken letters are hardest for the KNN model to classify?

- B (F1 score 0.79)
- M (F1 score 0.84)
- N (F1 score 0.84)
- P (F1 score 0.84)
- V (F1 score 0.85)
- All do not have distinct pronunciations
 - M is very similar to N

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	<u>N</u>	[ɛn]
<u>B</u>	[bi]	O	[ow]
C	[si]	<u>P</u>	[pi]
D	[di]	Q	[kju]
E	[i]	R	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
H	[eɪtʃ]	U	[ju]
I	[aɪ]	<u>V</u>	[vi]
J	[dʒeɪ]	W	[də.bɪ.ju]
K	[keɪ]	X	[ɛks]
L	[ɛl]	Y	[waɪ]
<u>M</u>	[ɛm]	Z	[zi]

Q3: Which spoken letters are hardest for the KNN model to classify?

- B (F1 score 0.79)
- M (F1 score 0.84)
- N (F1 score 0.84)
- P (F1 score 0.84)
- V (F1 score 0.85)
- All do not have distinct pronunciations
 - M is very similar to N
 - B, P, V are all similar to each other, and to D, E, T

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	<u>N</u>	[ɛn]
<u>B</u>	[bi]	O	[ow]
C	[si]	<u>P</u>	[pi]
D	[di]	Q	[kju]
E	[i]	R	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
H	[eɪtʃ]	U	[ju]
I	[aɪ]	<u>V</u>	[vi]
J	[dʒeɪ]	W	[də.bɪ.ju]
K	[keɪ]	X	[ɛks]
L	[ɛl]	Y	[waɪ]
<u>M</u>	[ɛm]	Z	[zi]

Q3: Which spoken letters are hardest for the KNN model to classify?

- B (F1 score 0.79)
- M (F1 score 0.84)
- N (F1 score 0.84)
- P (F1 score 0.84)
- V (F1 score 0.85)
- All do not have distinct pronunciations
 - M is very similar to N
 - B, P, V are all similar to each other, and to D, E, T
 - Next lowest letters: T (F1 score=0.86), D (F1 score=0.87), and E (F1 score=0.87)

IPA TRANSCRIPTIONS OF THE ENGLISH ALPHABET

Letter	IPA Transcription	Letter	IPA Transcription
A	[eɪ]	<u>N</u>	[ɛn]
<u>B</u>	[bi]	O	[ow]
C	[si]	<u>P</u>	[pi]
D	[di]	Q	[kju]
E	[i]	R	[aɪ]
F	[ɛf]	S	[ɛs]
G	[dʒi]	T	[ti]
H	[eɪtʃ]	U	[ju]
I	[aɪ]	<u>V</u>	[vi]
J	[dʒeɪ]	W	[də.bəl.ju]
K	[keɪ]	X	[ɛks]
L	[ɛl]	Y	[waɪ]
<u>M</u>	[ɛm]	Z	[zi]

Conclusion

Q1: Does a KNN model perform well on ISOLET?

↑ yes!

Q2: Which spoken letters are easiest for the KNN model to classify?

↑ letters with distinct pronunciations: H, I, O, R, W, X, Y

Q3: Which spoken letters are hardest for the KNN model to classify?

↑ letters without distinct pronunciations: B, M, N, P, V

References

- [1] R. Cole, Y. Muthusamy, and M. Fanty. “The ISOLET spoken letter database.” 1996.
- [2] M. Fanty and R. Cole. “ISOLET”. UCI Machine Learning Repository. Available: <https://archive.ics.uci.edu/dataset/54/isolet>.
- [3] M. Fanty and R. Cole. “Spoken letter recognition”. Advances in Neural Information Processing Systems (NIPS Conference). 1990. pp. 220-226.
- [4] T. Liu, K. Yang, and A. Moore. “The IOC algorithm: efficient many-class non-parametric classification for high-dimensional data”. Proceedings of the Tenth ACM SIGKDD International Conference on KnowledgeDiscovery and Data Mining. 2004.
- [5] F. Markus. “Why is speech recognition difficult?”. Semantic Scholar. 2003.
- [6] H. Nock and S. Young. “Loosely coupled HMMs for ASR”. Sixth International Conference on Spoken Language Processing (INTERSPEECH).2000.
- [7] Pedregosa et al., “Scikit-Learn: machine learning in Python”, Journal of Machine Learning Research, vol. 12. 2011. pp. 2825-2830.