

Use Case: Digital Petty Cash Ledger System

1. Introduction

A Petty Cash system is used by businesses to manage small, incidental expenditures (like tea, stationery, or taxi fares) using a "float" or "imprest" fund.¹ This use case requires the development of a **Digital Petty Cash Ledger** that allows a cashier to record income (replenishments) and expenses. The system must be built using C# and must demonstrate type-safe data handling without any external database.

2. Objective

The objective of this test is to verify the student's ability to:

- **Encapsulation & Abstraction:** Define clear data models for financial transactions.
- **Inheritance:** Differentiate between types of transactions (Income vs. Expense).
- **Generics:** Create a reusable Ledger or Repository to handle any transaction type while maintaining type safety.
- **Collections:** Efficiently store, retrieve, and filter transaction records using `List<T>` or `Dictionary<K,V>`.²

3. Requirements

The student must implement the following logic in C#:

A. The Data Model (OOP)

- **Abstract Class:** `Transaction` (Properties: `Id`, `Date`, `Amount`, `Description`).
- **Derived Classes:**
 - `ExpenseTransaction`: Adds a `Category` property (e.g., Office, Travel, Food).
 - `IncomeTransaction`: Adds a `Source` property (e.g., Main Cash, Bank Transfer).
- **Interface:** `IReportable` with a method `GetSummary()` to be implemented by all transaction types.

B. The Ledger Logic (Generics & Collections)

- **Generic Class:** `Ledger<T>` where `T : Transaction`.
- **Storage:** Internal `List<T>` to hold the transaction history.
- **Methods:**
 - `AddEntry(T entry)`: Adds a transaction.
 - `GetTransactionsByDate(DateTime date)`: Returns a filtered list.
 - `CalculateTotal()`: Uses LINQ or a loop to sum up the Amount.

C. Technical Restrictions

- **Storage:** In-memory only (no SQL, no File I/O).
- **Type Safety:** The generic `Ledger` must ensure that only `Transaction` objects can be processed.

4. Use Case Definition

Use Case ID	UC-FIN-01
Use Case Name	Record and Balance Petty Cash
Actor	Petty Cash Custodian
Pre-condition	The application is running; a ledger for Expenses and a ledger for Income are initialized.
Description	The custodian adds a fund replenishment (Income) and then records multiple minor expenses. The system then calculates the remaining balance.

Main Success Scenario (Steps)

1. The user creates a `Ledger<IncomeTransaction>` to track funds received from the main office.
2. The user records a \$500 replenishment from "Main Cash".
3. The user creates a `Ledger<ExpenseTransaction>` to track daily spends.
4. The user records an expense of \$20 for "Stationery" and \$15 for "Team Snacks".
5. The system uses a generic method to display the total from both ledgers.

6. The user calculates the **Net Balance** (Total Income - Total Expenses).

5. Expected Results

The student's solution should produce the following output:

- **Compile-time Check:** If a student tries to add an `IncomeTransaction` into a `Ledger<ExpenseTransaction>`, the code should fail to compile (proving Generic constraints).
- **Correct Calculations:** The console must show the total spent (\$35) and the total received (\$500) accurately.
- **Polymorphic Output:** A loop iterating through a `List<Transaction>` should be able to call `GetSummary()` and display unique details for both Income and Expenses.

6. Conclusion

By completing this use case, the student demonstrates a professional understanding of **Software Architecture**. Moving beyond simple variables to a Generic-based Ledger system shows that the developer can build scalable financial tools that are less prone to runtime errors and easy to maintain as business requirements grow.

Deliverables :

Algorithm, Class diagram using Draw.io

Tasks

Then code