

COL352: Assignment 1

Sachin 2019CS10722

January, 2022

1 Question 1

2 Question 2

An all-NFA M is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$ that accepts $x \in \Sigma^*$ if every possible state that M could be in after reading input x is a state from F . Note, in contrast, that an ordinary NFA accepts a string if some state among these possible states is an accept state. Prove that all-NFAs recognize the class of regular languages.

To prove that all-NFA's recognise the class of regular languages we need to show two things, firstly that the language accepted by all-NFA's is regular, and secondly given any regular language there exists an all-NFA which accepts it. Following are the proofs of these parts,

To Prove: Language accepted by all-NFA is regular.

Proof: Now by the definition, all-NFA M is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$ that accepts $x \in \Sigma^*$ if every possible state that M could be in after reading input x is a state from F . This would mean the all-NFA's are NFA because NFA accepts the string even if some of the states reached after reading an input x is in accept state F . Now we know that the language accepted by NFA is regular. Therefore the language accepted by all-NFA is also regular. Hence proved.

To Prove: For every regular language there exists an all-NFA that accepts it.

Proof: We know that for every regular language there exists a DFA which accepts it. Now the definition of a DFA M is that it is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$ that accepts $x \in \Sigma^*$ if the state that M could be in after reading input x is a state from F . Now we also know that the set of states DFA M would be in after reading the input x is a singleton set (Deterministic nature) and the state belongs to F if x is accepted by DFA. So every DFA is an all-NFA. Therefore for every regular language, there exists an all-NFA that accepts it. Hence proved.

Now above two facts would imply that the all-NFA's recognize the class of regular languages.

3 Question 3

4 Question 4

5 Question 5

For any string $w = w_1w_2...w_n$ the reverse of w written w^R is the string $w_n...w_2w_1$. For any language A , let $A^R = \{w^R \mid w \in A\}$. Show that if A is regular, then so is A^R . In other words, regular languages are closed under the reverse operation.

As every regular language has a DFA which accepts it, let D be $(Q, \Sigma, \delta, q_0, F)$ that accepts the language A . Now we will construct an NFA N from this DFA. The steps of the construction are given below. We will then show that the language accepted by NFA is indeed A^R .

Construction: To construct this NFA N we will have to reverse all the edges of the DFA D . Also make the start state of the D as the accepting state of the N . Add ϵ transitions from the accepting states of D to a new state s in NFA. Make s the start state of the NFA.

So N is $(Q_1, \Sigma, \delta', q_0', F')$ such that

$$\begin{aligned} Q_1 &= Q \cup \{s\} \\ F' &= q_0 \\ q_0' &= s \\ \delta'(q_1, a) &= (q_2 \mid \delta(q_2, a) = q_1 \text{ and } q_1, q_2 \in Q) \cup (s \mid q_1 \in F \text{ and } a = \epsilon) \end{aligned}$$

To Prove: The language accepted by N is A^R .

Proof: Now take any string $w_1w_2...w_n$ from the language A . The path (path is state then alphabet taken then next state reached) taken by this string to accept state in D would be $q_0, w_1, q_1, w_2, q_2, ..., q_n, w_n, f$ where $q_i \in Q$ and $f \in F$. Now take the reverse of the string $w_nw_{n-1}...w_1$. There exist a path from start to accept state in N as which is as follows $s, \epsilon, f, w_n, q_n, w_{n-1}, ..., q_1, w_1, q_0$. We know that q_0 is an accept state of N . Thus we have got an NFA that has an accepting path for any string w in A^R .

Now we have proved that for every string in A we have a accepting path in N . Now we can also similarly prove the reverse direction too i.e. for every string w in A^R we have accepting path in D for reverse of w . The proof of this goes as follows:

Take any string $w_1w_2...w_n$ from the language A^R . The path taken by this string to accept state in N would be $s, \epsilon, f, w_1, q_1, w_2, ..., q_n, w_n, q_0$ where $q_i \in Q$ and $f \in F$. Now take the reverse of the string $w_nw_{n-1}...w_1$. There exist a path from

start to accept state in D as which is as follows $q_0, w_n, q_1, w_{n-1}, q_2, \dots, q_n, w_1, f$. We know that f is an accept state of D. Thus we have got an DFA that has an accepting path for any string w in A . Hence we have proved that regular languages are closed under the reverse operation.

6 Question 6