**Tender No:** 2023-WP-ELECT-ANVT-WT-03 **Closing Date/Time:** 17/08/2023 13:00

CAO/WPO/Patna acting for and on behalf of The President of India invites E-Tenders against Tender No 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time 17/08/2023 13:00 Hrs. Bidders will be able to submit their original/revised bids upto closing date and time only. Manual offers are not allowed against this tender, and any such manual offer received shall be ignored.

### 1. NIT HEADER

Name of Work	11/0.433 KV power supply arr	stallation, erection, testing & commiss angement and associated electrical v or maintenance of Vande Bharat slee	vorks in connection with
Bidding type	Normal Tender		
Tender Type	Open	Bidding System	Single Packet System
Tender Closing Date Time	17/08/2023 13:00	Date Time Of Uploading Tender	20/07/2023 17:34
Pre-Bid Conference Required	No	Pre-Bid Conference Date Time	Not Applicable
Advertised Value	35646434.00	Tendering Section	MAINT
Bidding Style	Single Rate for Each Schedule	Bidding Unit	
Earnest Money (Rs.)	328200.00	Validity of Offer ( Days)	60
Tender Doc. Cost (Rs.)	0.00	Period of Completion	12 Months
Contract Type	Works	Contract Category	Expenditure
Bidding Start Date	03/08/2023	Are Joint Venture (JV) firms allowed to bid	No
Ranking Order For Bids	Lowest to Highest	Expenditure Type	Capital (Works)

### 2. SCHEDULE

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl.(%)	Amount	Bidding Unit
Schedu	le E 1-Elec	trical H.T Wo	rks				35646434.00	Above Below/Pa
	1	2.00	Numbers	3600000.00	7200000.00	AT Par	7200000.00	
1	Description:- Supply, erection (with foundation), testing and commissioning of copper wound power distribution transformer as per specification of 1600 KVA capacity as per following: Rated voltage (Line to line): 11/0.433 K Level: II (IS 1180 revision IV AMENDMENT NO. 4 MARCH 2021) Type: Oil immersed Method of cooling: ONA Number of phase: Three Rated frequency: 50 Hz Vector Group: DYN11 Service: Outdoor/Indoor installation Range of taps: +5% to -15% @ 2.5% Percentage impedance: 6.25% System earthing: solidly earthing Terminal arrangement: 11 KV side: 11 KV XLPE cable LT side: Bus duct flange/cable. The transformer shall be provided.							
1	with fitting & accessories along with marshalling box as listed in the technical specification.  2							
	3	1.00	Numbers	390515.00	390515.00	AT Par	390515.00	

Page 1 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

	ovtopoible		r mauntina	dust 9 vermin	proof floor mo	untad quitable	for ID 40 about	totaal alad
•			•				for IP-42 sheet ecification includ	
							No. Automatic P	
	Relay (API	FCR) with 4 Po	le suitable co	ontactor- copper	Bus Bar- 1 Set v	with auto manu	al switch and det	une reactor
			• •	•			MCB for switchi	•
							Contactor & 100 or both Status of	
	operation-		piete as rec	quired-4 Set, inc	ilcation Lamp i	OI ON/OFF IC	or botti Status C	л Сараско
	4	1.00	Set	4265414.00	4265414.00	AT Par	4265414.00	
	Description			<u>l</u>			ommissioning of	11KV switcl
							, protective relay.	
		•					n all respect as p	
	specification	on with power p	ack of suitab	ole rating for cont	trol circuit.			
	5	1.00	Numbers	4763930.00	4763930.00	AT Par	4763930.00	
	Description	on:- Supply, fix	xing, connec	ting and installa	ation of 500 KV	VA Water cool	ed DG set with	foundation
		, ,		\ I I /		•	VA 415V, 3PH 0	
		•					Base frame wit	
							tank, Sound prote: The sound pr	
			•				It should be we	
							ed and finally pov	
	for long las	sting finish and	aesthetic in I	looks.				
	6	1.00	Numbers	271206.00	271206.00	AT Par	271206.00	
1	Description	<b>on:-</b> Supply, er	ection, testin	ng and commissi	oning of emerge	ency LT panel	for DG complete	with 400 A
•		-		00 A 1nos. and	160 A MCCB 0	2 Nos., 100 A	MCCB-04 nos. a	and 63 Am
	MCCB-04	Nos for outgoir	ıg.					
	7	30.00	Metre	55716.00	1671480.00	AT Par	1671480.00	
	-	on:- Design, s	supply, erect		ort structure), te	-	mmissioning of	-
1	sandwich t IS8623 for	on:- Design, s type LT bus dur r connection be	supply, erect ct with Al bus etween LT pa	s bar suitable for anel and Transf	ort structure), to 415V, 50Hz, 3 p ormers complet	ohase, 4 wire, s e as required.	system as per IEC Bus duct is pre-	0 61439 and painted with
l	sandwich t IS8623 for RAL 7035	on:- Design, s type LT bus dur r connection be resin with high	supply, erect ct with Al bus etween LT pa n resistance t	s bar suitable for anel and Transf to chemical ager	ort structure), to 415V, 50Hz, 3 p ormers completents. Bus duct ho	phase, 4 wire, s e as required. using made of	system as per IEC Bus duct is pre- 1.5 mm thick ho	C 61439 and painted with t-galvanize
l	sandwich t IS8623 for RAL 7035	on:- Design, s type LT bus dur r connection be resin with high enclosure shal	supply, erect ct with Al bus etween LT pa n resistance t I provide a pr	s bar suitable for anel and Transf to chemical ager rotection not less	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hotel than IP- 55 & ir	phase, 4 wire, se as required. using made of asulation level is	system as per IEC Bus duct is pre- 1.5 mm thick ho s minimum B clas	61439 an painted wit t-galvanize
	sandwich t IS8623 for RAL 7035 steel. The	on:- Design, s type LT bus dur r connection be resin with high enclosure shal	supply, erect ct with Al bus etween LT pa n resistance t I provide a pr Numbers	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hos than IP- 55 & ir 279333.00	ohase, 4 wire, se as required. using made of asulation level is	system as per IEC Bus duct is pre- 1.5 mm thick ho s minimum B clas 279333.00	C 61439 and painted with t-galvanizeds
l 	sandwich t IS8623 for RAL 7035 steel. The	on:- Design, stype LT bus dured connection be resin with high enclosure shaled 1.00 cn:- Supply, ere	supply, erect ct with Al bus etween LT par resistance to provide a	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hose than IP- 55 & ir 279333.00 oning of Lead Ac	ohase, 4 wire, se as required. using made of insulation level is  AT Par	system as per IEC Bus duct is pre- 1.5 mm thick ho s minimum B clas 279333.00 e Free (VRLA) Sta	C 61439 an painted wit t-galvanize s
1	sandwich t IS8623 for RAL 7035 steel. The 8 Description	on:- Design, stype LT bus dured connection be resin with high enclosure shaled 1.00 cn:- Supply, ere	supply, erect ct with Al bus etween LT par resistance to I provide a provide	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hose than IP- 55 & ir 279333.00 oning of Lead Ac	ohase, 4 wire, se as required. using made of insulation level is  AT Par	system as per IEC Bus duct is pre- 1.5 mm thick ho s minimum B clas 279333.00	C 61439 and painted with t-galvanized is
1	sandwich t IS8623 for RAL 7035 steel. The 8 Description	on:- Design, stype LT bus durent connection be resin with high enclosure shales 1.00 cm:- Supply, erest with float Char	supply, erect ct with Al bus etween LT par resistance to I provide a provide	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hose than IP- 55 & ir 279333.00 oning of Lead Ac	ohase, 4 wire, se as required. using made of insulation level is  AT Par	system as per IEC Bus duct is pre- 1.5 mm thick ho s minimum B clas 279333.00 e Free (VRLA) Sta	C 61439 and painted with t-galvanized is
l I	sandwich t IS8623 for RAL 7035 steel. The 8 Description of 24V DC 15A as per	on:- Design, s type LT bus dur r connection be resin with high enclosure shal 1.00 on:- Supply, ere with float Char r requirement of	supply, erect ct with Al bus etween LT par resistance to a provide	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commissio Cell with Solid St	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hos than IP- 55 & ir 279333.00 oning of Lead Actate fully controll	ohase, 4 wire, see as required. using made of a sulation level is  AT Par id Maintenance ed 100AH capa	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B clas 279333.00 Free (VRLA) Statisticity having suital	C 61439 an painted wit t-galvanize s
l I	sandwich t IS8623 for RAL 7035 steel. The 8 Description of 24V DC 15A as per	on:- Design, stype LT bus dure connection be resin with high enclosure shales and the style on:- Supply, erest with float Char requirement control 3000.00 on:- Supplying	supply, erect ct with Al bus etween LT par resistance to a provide	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commissio Cell with Solid St	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hos than IP- 55 & ir 279333.00 oning of Lead Actate fully controll	ohase, 4 wire, see as required. using made of a sulation level is  AT Par id Maintenance ed 100AH capa	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B clas 279333.00 Free (VRLA) State acity having suital	C 61439 an painted wit t-galvanize s
1	sandwich t IS8623 for RAL 7035 steel. The 8 Description of 24V DC 15A as pe	on:- Design, stype LT bus dure connection be resin with high enclosure shales and the style on:- Supply, erest with float Char requirement control 3000.00 on:- Supplying	supply, erect ct with Al bus etween LT par resistance to a provide	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commissio Cell with Solid St	ort structure), to 415V, 50Hz, 3 pormers completents. Bus duct hos than IP- 55 & ir 279333.00 oning of Lead Actate fully controll	ohase, 4 wire, see as required. using made of a sulation level is  AT Par id Maintenance ed 100AH capa	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B clas 279333.00 Free (VRLA) State acity having suital	C 61439 an painted wit t-galvanize s
 	sandwich to IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as reference as refere	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charr requirement of 3000.00 on:- Supplying equired 12.00	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commissio Cell with Solid St 2348.00 0 Sq. mm 11kV	ort structure), to 415V, 50Hz, 3 p ormers completents. Bus duct hose than IP- 55 & ir 279333.00 oning of Lead Actate fully controll 7044000.00 Grade HT-XLPE	ohase, 4 wire, see as required. using made of a sulation level is  AT Par id Maintenance ed 100AH capa  AT Par is UG cable as particular in the capacity of th	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B clas 279333.00 Free (VRLA) State acity having suital 7044000.00 per IS: 7098 com	C 61439 an painted wit t-galvanize s ation Batter ble output of plete as pe
	sandwich to IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as results as results as per 10  Description description of 10	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charr requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply& mon:- Supply& m	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/ of the system Metre of 3 core 150 Each making of outcome.	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commissio Cell with Solid St 2348.00 0 Sq. mm 11kV	ort structure), to 415V, 50Hz, 3 p ormers complete ints. Bus duct ho than IP- 55 & ir 279333.00 ining of Lead Ac tate fully controll  7044000.00  Grade HT-XLPE  456996.00 ough Joints of 1	ohase, 4 wire, see as required. using made of insulation level is  AT Par id Maintenance and 100AH capa  AT Par id Cable as part of the	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Sta acity having suital 7044000.00 per IS: 7098 com 456996.00 core 150 Sq.mm	C 61439 an painted wit t-galvanize s ation Batter ble output of plete as pe
l I	sandwich to IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as results as results as per 10  Description description of 10	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charr requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply& mon:- Supply& m	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V//of the system Metre of 3 core 150 Each making of outcome.	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commissio Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight thr	ort structure), to 415V, 50Hz, 3 p ormers complete ints. Bus duct ho than IP- 55 & ir 279333.00 ining of Lead Ac tate fully controll  7044000.00  Grade HT-XLPE  456996.00 ough Joints of 1	ohase, 4 wire, see as required. using made of insulation level is  AT Par id Maintenance and 100AH capa  AT Par id Cable as part of the	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Sta acity having suital 7044000.00 per IS: 7098 com 456996.00 core 150 Sq.mm	C 61439 and painted with t-galvanize set on Batter ole output of plete as pe
l I	sandwich to IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spectral as reconstruction of 24V DC 15A as per 10  Description spectral for including a 11	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply& mall accessories at 8.00	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150 Each making of outcand making at Each	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight threa masonry enclose 16249.00	ort structure), to 415V, 50Hz, 3 pormers completed ints. Bus duct how than IP- 55 & ir 279333.00 or ining of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identification 129992.00	ohase, 4 wire, see as required. using made of insulation level is  AT Par id Maintenance is 100 AH capa  AT Par E UG cable as part of the capa is 100 AH capa  AT Par	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Statisty having suital 7044000.00 Per IS: 7098 com 456996.00 Core 150 Sq.mm as required.	C 61439 and painted with t-galvanize is ation Batter ble output complete as pe
	sandwich to IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as results including a 11  Description of 11	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charrequirement of 3000.00 on:- Supplying equired 12.00 on:- Supply& mall accessories at 8.00 on:- Supply & stype on one- supply & stype one- supply & stype on one- supply & stype on one- supply & stype on one- supply & stype one- supply & styp	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150  Each chaking of oute and making a Each chaking indo	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight threa masonry enclose 16249.00	ort structure), to 415V, 50Hz, 3 p ormers complete ints. Bus duct ho than IP- 55 & ir 279333.00 rining of Lead Ac tate fully controll  7044000.00  Grade HT-XLPE  456996.00  ough Joints of 1 sure for identifica 129992.00  of 11 KV grade	ohase, 4 wire, see as required. using made of insulation level is  AT Par id Maintenance ed 100AH capa  AT Par is UG cable as position complete  AT Par id A	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 erree (VRLA) State acity having suital 7044000.00 per IS: 7098 com 456996.00 core 150 Sq.mm as required. 129992.00 mm XLPE cable	C 61439 and painted with t-galvanize is ation Batter ble output complete as pe
I I	sandwich to IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as results including a 11  Description of 11	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charrequirement of 3000.00 on:- Supplying equired 12.00 on:- Supply& mall accessories at 8.00 on:- Supply & stype on one- supply & stype one- supply & stype on one- supply & stype on one- supply & stype on one- supply & stype one- supply & styp	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150  Each chaking of oute and making a Each chaking indo	s bar suitable for anel and Transf to chemical agerotection not less 279333.00 g and commission Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight three masonry enclose 16249.00 por termination of a mason of the straight three termination of the straight three terminations of the straight three terminati	ort structure), to 415V, 50Hz, 3 p ormers complete ints. Bus duct ho than IP- 55 & ir 279333.00 rining of Lead Ac tate fully controll  7044000.00  Grade HT-XLPE  456996.00  ough Joints of 1 sure for identifica 129992.00  of 11 KV grade	ohase, 4 wire, see as required. using made of insulation level is  AT Par id Maintenance ed 100AH capa  AT Par is UG cable as position complete  AT Par id A	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 erree (VRLA) State acity having suital 7044000.00 per IS: 7098 com 456996.00 core 150 Sq.mm as required. 129992.00 mm XLPE cable	C 61439 and painted with t-galvanize is ation Batter ble output complete as pe
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as result including a 11  Description accessories 12	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charrequirement of 3000.00 on:- Supplying equired 12.00 on:- Supply& mall accessories a 8.00 on:- Supply & es such as heat 2.00	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150 Each making of outcand making at Each making index shrinkable / Each	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight thra masonry enclose 16249.00 por termination of push on kits etc, 22795.00	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 ening of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00	ohase, 4 wire, se as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par it I KV grade 3 cation complete  AT Par id AT	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Statistically having suital 7044000.00 For IS: 7098 com 456996.00 For 150 Sq.mm as required. 129992.00 Final XLPE cable is required.	C 61439 and painted with t-galvanize is ation Batter ole output of the plete as per the cable including a
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as result including a 11  Description accessories 12  Description description accessories 12	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply & such as heat 2.00 on:- Supply & su	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150  Each making of outcand making a Each making index shrinkable / Each making outcand making index shrinkable / Each making outcand making outcand making outcand making index shrinkable / Each making outcand making outc	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight thra masonry enclose 16249.00 por termination of push on kits etc, 22795.00	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 or ining of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identification 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade of 11 KV grade of 11 KV grade complete include 11 KV grade of 11 KV grade	ohase, 4 wire, se as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par it IKV grade 3 cation complete  AT Par id AT P	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Statisty having suital 7044000.00 Per IS: 7098 com 456996.00 Per IS: 7098 com 129992.00 Per IS: 8 com 1299	C 61439 an painted wit t-galvanize s ation Batter ole output of plete as pe
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as result including a 11  Description accessories 12  Description description accessories 12	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply & such as heat 2.00 on:- Supply & su	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/of the system Metre of 3 core 150  Each making of outcand making a Each making index shrinkable / Each making outcand making index shrinkable / Each making outcand making outcand making outcand making index shrinkable / Each making outcand making outc	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight thra masonry enclose 16249.00 poor termination opush on kits etc, 22795.00 door termination	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 or ining of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identification 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade of 11 KV grade of 11 KV grade complete include 11 KV grade of 11 KV grade	ohase, 4 wire, se as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par it IKV grade 3 cation complete  AT Par id AT P	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Statisty having suital 7044000.00 Per IS: 7098 com 456996.00 Per IS: 7098 com 129992.00 Per IS: 8 com 1299	C 61439 and painted with t-galvanize is ation Batter ole output of the plete as per the cable including a
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as pereconstruction of 24V DC 15A as	on:- Design, stype LT bus dure connection be resin with high enclosure shall 1.00  on:- Supply, ere with float Char requirement of 3000.00  on:- Supplying equired 12.00  on:- Supply& mall accessories a 8.00  on:- Supply & es such as heat 2.00  on:- Supply & es such as heat 1200.00	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V//of the system Metre of 3 core 150 Each making of outcand making a Each making indotes thrinkable / Each making outcates shrinkable / Metre	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight three masonry enclose 16249.00 cor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00	ort structure), to 415V, 50Hz, 3 p ormers complete ints. Bus duct ho than IP- 55 & ir 279333.00 Ining of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00	ohase, 4 wire, see as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par it UG cable as position complete  AT Par id 3C 150 Sq in ding earthing as AT Par id as Garden as position complete and particular and particular and particular as AT Par ide 3C 150 sq. in ding earthing earth	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Sta acity having suital  7044000.00 Der IS: 7098 com  456996.00 Core 150 Sq.mm as required. 129992.00 Inm XLPE cable is required 45590.00 Inm XLPE cable is required	C 61439 an painted wit t-galvanize is ation Batter ole output of plete as pe
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as pereconsisting spec. as reconstruction including a 11  Description accessories 12  Description accessories 13  Description accessories 13	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, erowith float Charrequirement of 3000.00 on:- Supply and accessories at 8.00 on:- Supply & es such as heat 2.00 on:- Supply & es such as heat 1200.00 on:- Laying of on:- Laying of on:- Laying of on:- Design of the state of the supply and the such as heat 1200.00 on:- Laying of on:- Laying of on:- Design of the supply and the such as heat 1200.00 on:- Laying of on:- Laying of on:- Supply and the such as heat 1200.00 on:- Laying of on:- Laying of one-	supply, erect ct with Al bus etween LT provide a provide a provide at provide at 2.7V/of the system Metre of 3 core 150 Each making of oute and making a Each making index shrinkable / Each making oute shrinkable / Metre one number	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight three masonry enclose 16249.00 poor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00 PVC insulated a	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 oning of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00 ond PVC sheather than 150 or 150 o	ohase, 4 wire, see as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par if IKV grade 3 cation complete  AT Par if IKV grade 3 cation ca	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) Statisty having suital 7044000.00 For IS: 7098 com 456996.00 For IS: 7098 com 129992.00	C 61439 and painted with transparent trans
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as result including a 11  Description accessories 12  Description accessories 13  Description accessories 13	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supply & mall accessories at 8.00 on:- Supply & es such as heat 1200.00 on:- Laying of ear required.	supply, erect ct with Al bus etween LT provide a provide a provide at provide at 2.7V/of the system Metre of 3 core 150 Each making of oute and making a Each making index shrinkable / Each making oute shrinkable / Metre one number	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight threat masonry enclose 16249.00 poor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00 PVC insulated ad including excavers.	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 or ining of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identification 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00 ond PVC sheather vation, sand cus	AT Par  1 KV grade 3 cation complete AT Par  2 SC 150 Sq nding earthing as AT Par  2 SC 150 sq.nding earthing as AT Par  2 SC 150 sq.nding earthing as AT Par  2 SC 150 sq.nding earthing as AT Par  3 C 150 sq.nding earthing as AT Par  4 SC 150 sq.nding earthing as AT Par  5 Sq.nding earthing as AT Par  6 SC 150 sq.nding earthing as AT Par  7 Sq.nding earthing as AT Par  8 SC 150 sq.nding earthing as AT Par  8 SC 150 sq.nding earthing as AT Par	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 erree (VRLA) State that having suital 7044000.00 err IS: 7098 com 456996.00 errequired 45590.00 errequired 45590.00 erreable of 11 KV tive covering and suital formula to the second suital formula t	C 61439 an painted wit t-galvanize is ation Batter ole output of plete as per XLPE cable including a including a formula of grade of a formula of the plete as per the plete as
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as per 9  Description spec. as result including a 11  Description accessories 12  Description accessories 13  Description accessories 13	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply & es such as heat 2.00 on:- Supply & es such as heat 1200.00 on:- Laying of Sq. mm size directions of the stype of the styp	supply, erect ct with Al bus etween LT provide a provide a provide at provide at 2.7V/of the system Metre of 3 core 150 Each making of oute and making a Each making index shrinkable / Each making oute shrinkable / Metre one number	s bar suitable for anel and Transf to chemical ager rotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight three masonry enclose 16249.00 poor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00 PVC insulated a	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 oning of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00 ond PVC sheather than 150 or 150 o	ohase, 4 wire, see as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par if IKV grade 3 cation complete  AT Par if IKV grade 3 cation ca	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 Free (VRLA) State acity having suital  7044000.00 Foer IS: 7098 com 456996.00 Foer IS: 7098 com 456996.00 Fore 150 Sq.mm as required 129992.00 Final XLPE cable as required 45590.00 Final RVLPE cable as required 692400.00 Fore cable of 11 KV	C 61439 an painted wit t-galvanize is ation Batter ole output of plete as per XLPE cable including a including a formula of grade of
1 1 1 1 1 1 1 1	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as pereconstruction of 24V DC 15A as	on:- Design, stype LT bus dure connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Charr requirement of 3000.00 on:- Supplying equired 12.00 on:- Supply & es such as heat 1200.00 on:- Laying of Sq. mm size direct as required. 1200.00 on:- Laying of sq. mm size direct as required. 1200.00 on:- Laying of sq. mm size direct as required. 1200.00 on:- Laying of sq. mm:- Laying sq	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V/ of the system Metre of 3 core 150 Each making of oute and making a Each making index shrinkable / Each making oute a shrinkable / Metre one number rect in ground metre one number one number	s bar suitable for anel and Transf to chemical agerotection not less 279333.00 g and commission Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight three masonry enclose 16249.00 cor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00 PVC insulated a dincluding excaval	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct how than IP- 55 & ir 279333.00 oning of Lead Actate fully controll 7044000.00 or 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00 ond PVC sheather vation, sand cus 498000.00 insulated and Picture of the structure of the stru	ohase, 4 wire, see as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par it UG cable as position complete  AT Par id 3C 150 Sq in ding earthing as AT Par idea of 150 sq. in ding earthing as AT Par idea of XLPE power hioning, protective of AT Par idea of XLPE power hioning, protective of AT Par idea of XLPE power and the second of the second	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 erece (VRLA) State that the second	C 61439 and painted with transpainted with transpainted with transpainted services. Attended to the plete as permitted as permitted as permitted to the plete as permitted as permitted to the plete as permitted as permitted as permitted as permitted to the plete as permitted as
	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as pereconstruction of 24V DC 15A as	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supply & such as heat 1200.00 on:- Supply & such as heat 1200.00 on:- Laying of Sq. mm size direct as required.	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V//of the system Metre of 3 core 150 Each making of oute and making a Each making index shrinkable / Each making oute shrinkable / Metre one number ect in ground Metre one number mm size dir	s bar suitable for anel and Transf to chemical agerotection not less 279333.00 g and commission Cell with Solid St.  2348.00 0 Sq. mm 11kV  38083.00 door Straight thra masonry enclose 16249.00 cor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00 PVC insulated a dincluding excave 415.00 additional PVC rect in ground in	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct hos than IP- 55 & ir 279333.00 oning of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00 ond PVC sheather ation, sand cus 498000.00 insulated and P the same trend	ohase, 4 wire, see as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par if It W grade 3 cation complete  AT Par if It W grade 3	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 erree (VRLA) Statisty having suital 7044000.00 err IS: 7098 com 456996.00 erres 150 Sq.mm as required. 129992.00 erres 150 Sq.mm XLPE cable required 45590.00 erres 150 Sq.mm XLPE cable required 692400.00 erres 150 Sq.mm Attive covering and 150 Sq.mm and	C 61439 an painted wit t-galvanize is ation Batter ole output of the plete as perior of the
1	sandwich is IS8623 for RAL 7035 steel. The 8  Description of 24V DC 15A as pereconstruction of 24V DC 15A as	on:- Design, stype LT bus durent connection be resin with high enclosure shall 1.00 on:- Supply, ere with float Char requirement of 3000.00 on:- Supply & such as heat 1200.00 on:- Supply & such as heat 1200.00 on:- Laying of Sq. mm size direct as required.	supply, erect ct with Al bus etween LT provide a provide a provide a provide at 2.7V//of the system Metre of 3 core 150 Each making of oute and making a Each making index shrinkable / Each making oute shrinkable / Metre one number ect in ground Metre one number mm size dir	s bar suitable for anel and Transf to chemical agerotection not less 279333.00 g and commission Cell with Solid St. 2348.00 0 Sq. mm 11kV 38083.00 door Straight three masonry enclose 16249.00 cor termination opush on kits etc, 22795.00 door termination push on kits etc, 577.00 PVC insulated a dincluding excaval	ort structure), to 415V, 50Hz, 3 pormers complete ints. Bus duct hos than IP- 55 & ir 279333.00 oning of Lead Actate fully controll 7044000.00 Grade HT-XLPE 456996.00 ough Joints of 1 sure for identifica 129992.00 of 11 KV grade complete include 45590.00 of 11 KV grade complete include 692400.00 ond PVC sheather ation, sand cus 498000.00 insulated and P the same trend	ohase, 4 wire, see as required. using made of isulation level is  AT Par id Maintenance and 100AH capa  AT Par if It W grade 3 cation complete  AT Par if It W grade 3	system as per IEC Bus duct is pre- 1.5 mm thick ho is minimum B class 279333.00 erree (VRLA) Statisty having suital 7044000.00 err IS: 7098 com 456996.00 erres 150 Sq.mm as required. 129992.00 erres 150 Sq.mm XLPE cable required 45590.00 erres 150 Sq.mm XLPE cable required 692400.00 erres 150 Sq.mm Attive covering and 150 Sq.mm and	c 61439 and painted with t-galvanizers ation Batter ole output of plete as per XLPE cable including a including a line of 11 KV ole of 11 KV ole of 11 KV ole of 11 KV

Page 2 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

I	Description:- Supply, laying, testing and commissioning of XLPE insulated PVC sheathed armoured underground
	aluminium cable of graded 1.1KV for working voltage upto 1100 volts conforming to IS 7098 with upto da amendment as detailed given below (with making end termination with brass compression gland and lug
	required) Inner and outer sheat PVC extruded: a) 4CX400 Sq. mm  15 b 200.00 Metre 1016.00 203200.00 AT Par 203200.00
	Description:- Supply, laying, testing and commissioning of XLPE insulated PVC sheathed armoured underground
	aluminium cable of graded 1.1KV for working voltage upto 1100 volts conforming to IS 7098 with upto da amendment as detailed given below (with making end termination with brass compression gland and lug required) Inner and outer sheat PVC extruded: b) 2CX150 Sq.mm
	16 100.00 Metre 740.00 74000.00 AT Par 74000.00
	<b>Description:-</b> Supply, erection, testing and commissioning of PVC insulated copper conductor 10 core 2.5 Sq.m armored control cabling/ wiring in open duct/ pipes/ on surface/in ground etc. as required for complete control audio visual annunciation/ trip system / watering system etc. for above.
	17 1000.00 Kg 123.00 123000.00 AT Par 123000.00
	Description:- Supply & fixing of 6 mm thick MS chequered plate including the MS angle support on the trench the sub-station equipment complete as required
	18 10.00 Numbers 15464.00 154640.00 AT Par 154640.00
I	<b>Description:-</b> Supply, erection, testing & commissioning of maintenance free earthing arrangement (Chemic earthing with low impedance, corrosion resistant & long life). Earth electrode is made up of high tensile low carbon steel circular rods bonded with copper on outer surface and interconnection of earth electrode with suitable six copper strip. The earth electrode shall be of minimum 17.0 mm diameter and 3.66-meter length as per detail given technical specification connected with all required accessories.
	19 5.00 Set 13838.00 69190.00 AT Par 69190.00
	<b>Description:-</b> Earthing with copper earth plate 600 mm X 600 mm X 3 mm thick including accessories, as providing masonry enclosure with cover plate having locking arrangement and watering pipe of 2.7 meter long exwith charcoal/ coke and salt as required.
	20 10.00 Set 6855.00 68550.00 AT Par 68550.00
	Description:- Earthing with G.I earth pipe 4.5 mtr. long 40mm dia. including accessories and providing mason enclosure with cover plate having locking arrangement and watering pipe etc. including providing salt at charcoal for pipe earth electrode as required.  21 50.00 Metre 1162.00 58100.00 AT Par 58100.00  Description:- Providing and fixing 25 mm X 5 mm copper strip on surface or in recess for connections etc.
	required.
	22 1.00 Numbers 376398.00 376398.00 AT Par 376398.00
l	<b>Description:-</b> Design, Supply, Installation, testing and commissioning of Fire detection System for unit substation each set consisting of Smoke detectors 4 nos, Normal Beam Heat detectors 4 nos, Manual call point response no, Audio visual alarm 1 no, Control Module 1 no, Fire Alarm Control Panel with Display- 1 no, Loop interface board(signaling line Circuit) - 1 no, Fire Alarm Repeater/ annunciator panel - 1 no, Response Indicator - 1 no Ethernet bridge (If the PLC Panel's ethernet bridge can be utilized, it need not be separate) with all connected accessories like wiring, cabling, clamping etc.
	23 1.00 Set 24480.00 24480.00 AT Par 24480.00
	<b>Description:-</b> Providing & laying insulating rubber mat Nonskid type 1 No for each HT panel, transformers of size 25mm and for all the LT panels in sub stations of thickness 12mm Rubber mat shall be of size 910mm wide as p IS complete as required.
	24 4.00 Numbers 3690.00 14760.00 AT Par 14760.00
	<b>Description:-</b> Supply & erection of Fire Extinguisher (4 Liter) for B Class Fire in sub-stations as per IE Rules at conformity to Fire regulations as required.
	25 1.00 Set 109443.00 109443.00 AT Par 109443.00
	Description:- H-Pole assembly Supply, erection (with foundation), testing & commissioning of DP structure by
	nos. of RSJ poles 100X116-11 meters long with nut, bolt, washer, insulator, all connected works, pit, accessorietc., 11 KV isolating arrangement with 1250 A capacity AB switch vertical mounting type, lighting arresters approved make fixed on DP structure with gang operated rod including all connected accessories etc. & 11 kdrop out fuse of approved make and operated rod on DP structure including all connected accessories for the GOS.
	26 2500.00 Metre 285.00 712500.00 AT Par 712500.00
	<b>Description:-</b> Excavation of cable trench in all kind soil (450mmX1250mm) and making of original arrangement etc.
	27 100.00 Metre 365.00 36500.00 AT Par 36500.00

Page 3 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

_	28	200.00	Metre	2766.00	553200.00	AT Par	553200.00			
1	Description	on:- Horizont	al drilling of b	ores for cables i	including HDPE P	ipe and layin	g of cable.			
	29	50.00	Numbers	585.00	29250.00	AT Par	29250.00			
1	Description	n:- Supply 8	Installation	of cable route ma	arker with cement	t concrete for	undation 1:2:4 of si	ze 60X60 cm		
	at the bottom and 50X50 cm at top with a thickness of 10 cm including inscription duly engraved as required									
	30	1.00	Set	48951.00	48951.00	AT Par	48951.00			
	Description:- Providing & fixing of i. shock treatment chart duly framed Bilingual Hindi & English ii. Tool Box:1Set									
		•	•				s. 6/7, 8/9,10/11,			
	16/17, 18	/19, 20/22, 2	21/23, 24/27,	25/28, 30/32)	b. ring spanner-	12 nos.6/7, 8	8/9,10/11, 12/13, 1	14/15, 16/17,		
1	18/19, 20/	22, 21/23, 24	4/27, 25/28, 3	30/32) c. Ball Ha	ammer-01 nos. d.	. Hexa frame	- 01 nos. e. C. Plie	er 210mm-01		
	nos. f. Chiesel 22 x 200mm-01 nos. g. Screw driver 200mm-01 nos. h. Round File 200mm-01 nos. i. Flat file									
	150mm-0	1 nos. j. Racl	net socket sp	anner (Rachet-	01 Nos., Handle-	-03, Socket-0	01 Nos)-01 set} iii.	Key Board: 1		
	Set iv. Firs	st Aid Box: 1	Set v. Fire /S	and Bucket: 1Se	t vi Pair of Insulat	ted gloves: 1	Set vii. Set Earthin	g rods: 1 Set		
	viii. HT an	d LT Danger	Board: 1 Set			-		-		

### 3. ITEM BREAKUP

- 6	
	No item break up added
	No item break up added

### 4. ELIGIBILITY CONDITIONS

### **Special Financial Criteria**

S.No.	Description	Confirmation Required		Documents Uploading
1	The tenderer must have minimum average annual contractual turnover of V/N or 'V' whichever is less; where V= Advertised value of the tender in crores of Rupees N= Number of years prescribed for completion of work for which bids have been invited. The average annual contractual turnover shall be calculated as an average of "total contractual payments" in the previous three financial years, as per the audited balance sheet. However, in case balance sheet of the previous year is yet to be prepared/audited, the audited balance sheet of the fourth previous year shall be considered for calculating average annual contractual turnover. The tenderers shall submit requisite information as per Annexure-VIB, along with copies of Audited Balance Sheets duly certified by the Chartered Accountant/ Certificate from Chartered Accountant duly supported by Audited Balance Sheet.	No	INo	Allowed (Mandatory)

### **Special Technical Criteria**

S.No.	•	Confirmation Required		Documents Uploading
1	(a) The tenderer must have successfully completed or substantially completed any one of the following categories of work(s) during last 07 (seven) years, ending last day of month previous to the one in which tender is invited:(i) Three similar works each costing not less than the amount equal to 30% of advertised value of the tender, or (ii) Two similar works each costing not less than the amount equal to 40% of advertised value of the tender, or (iii) One similar work costing not less than the amount equal to 60% of advertised value of the tender.	No	IN∩	Allowed (Mandatory)

### **Special Technical Criteria**

S.N	Description	Confirmation	Remarks	Documents
		Required	Allowed	Uploading

Page 4 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

(b) (1) In case of tenders for composite works (e.g. works involving more than one distinct component, such as Civil Engineering works, S&T works, Electrical works, OHE works etc. and in the case of major bridges - substructure, superstructure etc.), tenderer must have successfully completed or substantially completed any one of the following categories of work(s) during last 07 (seven) years, ending last day of month previous to the one in which tender is invited: (i) Three similar works each costing not less than the amount equal to 30% of advertised value of each component of tender, or (ii) Two similar works each costing not less than the amount equal to 40% of advertised value of each component of tender, or (iii) One similar work each costing not less than the amount equal to 60% of advertised value of each component of tender. Note for b(1): Separate completed works of minimum required values shall also be considered for fulfillment of technical eligibility criteria for different components. (b)(2)In such cases, what constitutes a component in a composite work shall be clearly pre-defined with estimated tender cost of it, as part of the tender documents without any ambiguity. (b) (3) To evaluate the technical eligibility of tenderer, only components of work as stipulated in Allowed tender documents for evaluation of technical eligibility, shall be considered. The scope of No No (Mandatory) work covered in other remaining components shall be either executed by tenderer himself if he has work experience as mentioned in clause 7 of the Standard General Conditions of Contractor through subcontractor fulfilling the requirements as per clause 7 of the Standard General Conditions of Contract or jointly i.e., partly himself and remaining through subcontractor, with prior approval of Chief Engineer in writing. However, if required in tender documents by way of Special Conditions, a formal agreement duly notarised, legally enforceable in the court of law, shall be executed by the main contractor with the subcontractor for the component(s) of work proposed to be executed by the subcontractor(s), and shall be submitted along with the offer for considering subletting of that scope of work towards fulfilment of technical eligibility. Such subcontractor must fulfill technical eligibility criteria as follows: The subcontractor shall have successfully completed at least one work similar to work proposed for subcontract, costing not less than 35% value of work to be subletted, in last 5 years, ending last day of month previous to the one in which tender is invited through a works contract.

#### **Special Technical Criteria**

S.No.	Description	Confirmation Required		Documents Uploading
1	In case after award of contract or during execution of work it becomes necessary for contractor to change subcontractor, the same shall be done with subcontractor(s) fulfilling the requirements as per clause 7 of the Standard General Conditions of Contract, with prior approval of Chief Engineer in writing. Note for Item 10.1: Work experience certificate from private individual shall not be considered. However, in addition to work experience certificates issued by any Govt. Organisation, work experience certificate issued by Public listed company having average annual turnover of Rs 500 crore and above in last 3 financial years excluding the current financial year, listed on National Stock Exchange or Bombay Stock Exchange, incorporated/registered at least 5 years prior to the date of closing of tender, shall also be considered provided the work experience certificate has been issued by a person authorized by the Public listed company to issue such certificates. In case tenderer submits work experience certificate issued by public listed company, the tenderer shall also submit along with work experience certificate, the relevant copy of work order, bill of quantities, bill wise details of payment received duly certified by Chartered Accountant, TDS certificates for all payments received and copy of final/last bill paid by company in support of above work experience certificate.	No	No	Allowed (Mandatory)

### **Special Technical Criteria**

I	S.No.	•	Confirmation Required		Documents Uploading
	1	Scanned copies of documents in support of formation/registration of the company/firm/legal authorization of the person to deal with the tender/notarized/registered copies of the documents wherever required as per tender conditions are to be submitted along with offer.	No	Nο	Allowed (Mandatory)

#### Special Technical Criteria

S.No.	'	Confirmation Required		Documents Uploading
1	Regarding technical and financial eligibility criteria, scanned copies of supportive documents/certificates from competent officials are to be submitted along with their offer.		INO	Allowed (Mandatory)

Page 5 of 9 Run Date/Time: 20/07/2023 17:34:24

**Tender No:** 2023-WP-ELECT-ANVT-WT-03 **Closing Date/Time:** 17/08/2023 13:00

### **Special Technical Criteria**

S	•			Documents Uploading
1	Similar nature of work: "Electrical works involving supply, erection and commissioning of 11 KV or above voltage level substation"	No	INo	Allowed (Mandatory)

### **Special Technical Criteria**

S.No.		Confirmation Required		Documents Uploading
1	Bid Capacity: Not Applicable	No	INo	Allowed (Mandatory)

### **Special Technical Criteria**

S.No.	· ·	Confirmation Required		Documents Uploading
	ELECTRICAL CONTRACTOR LICENSE The tenderer should have a valid (on tender closing date) Electrical Contractor license and Electrical supervisory license for the required voltage level i.e. 11 KV or above issued from any state/Central Government licensing board. Failing which the tender shall be summarily rejected.	No	INO	Allowed (Mandatory)

### **Submission of Document Verification Certificate**

S.No.	•	Confirmation Required		Documents Uploading
1	Please submit a certificate in the prescribed format (please download the format from the link given below) for verification / confirmation of the documents submitted for compliance of eligibility / qualifying criteria. Non submission of the certificate, or submission of certificate either not properly filled in, or in a format other than the prescribed format shall lead to summary rejection of your offer.  ( Click here to download the Format of Self Certificatio)	No	IN∩	Allowed (Mandatory)

### 5. COMPLIANCE

### Commercial-Compliance

S.No.	Description	Confirmation Required		Documents Uploading
	Please enter the percentage of local content in the material being offered. Please enter 0 for fully imported items, and 100 for fully indigenous items. The definition and calculation of local content shall be in accordance with the Make in India policy as incorporated in the tender conditions.		Yes	Allowed (Mandatory)
	Please enter the percentage of local content in the material being offered. Please enter 0 for fully imported items, and 100 for fully indigenous items. The definition and calculation of local content shall be in accordance with the Make in India policy as incorporated in the tender conditions.		Yes	Allowed (Optional)
	Please enter the percentage of local content in the material being offered. Please enter 0 for fully imported items, and 100 for fully indigenous items. The definition and calculation of local content shall be in accordance with the Make in India policy as incorporated in the tender conditions.		Vac	Allowed (Optional)

### **General Instructions**

S.No.	Description	Confirmation Required		Documents Uploading
1	All documents in support of fulfilment of eligibility criteria with respect to completion of Similar nature of work for Technical Eligibility Criteria and Total contract value for Financial Eligibility Criteria should be furnished along with the tender and should be submitted online at the time of tender bidding. Tenders not accompanied by documentary evidence in support of eligibility criteria will be summarily rejected. No post tender communication, in any form will be made or entertained, after opening of tenders, in this regard. Railways may however call for the originals of the credentials for verification or any clarifications/confirmations on the contents of the documents submitted.	No	No	Not Allowed

Page 6 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

2	Tenderers shall note that the submission of other supporting documents namely- Constitution of firm, Work in hand, Arbitration/Court cases,Tools & Plants, Technical Personnel/Man Power and Association of railway Officers, at the time of on line bidding of tender, is important and they shall ensure the same. However Railways may seek clarifications/details/documents in this regard.	No	No	Not Allowed
	The tenderer(s) should not put any unusual condition from their side contradicting terms and conditions in the e-tender. Such unusual/contradictory conditions may not be considered.		No	Not Allowed
4	PLEASE FILL IN REQUIRED INFORMATION ASKED FOR IN THE SPECIFIED SPACE IN THE E-TENDER. TENDER WILL BE OTHER WISE TREATED INCOMPLETE AND HENCE WILL BE LIABLE FOR REJECTION.		No	Not Allowed
5	THE QUANTITY SHOWN IN THE SCHEDULES ARE APPROXIMATE AND ARE LIKELY TO VARY ON EITHER SIDE (+/-) AS PER CLAUSE-2 OF SPECIAL CONDITIONS OF CONTRAC.		No	Not Allowed

## **Technical-Compliances**

S.No.	Description	Confirmation Required	Remarks Allowed	Documents Uploading
1	Scanned copy [in PDF format] of the details regarding the Association of Railway Officer/s with the tender [for details please refer Annexure-H]	Yes	Yes	Allowed (Mandatory)
2	Scanned copy [in PDF format] of the details of the List of the Arbitration & Court cases during the last 3 years [for details please refer Annexure-J and I of Tender document]		Yes	Allowed (Mandatory)
3	Scanned copy [in PDF format] of the details of agency and own equipments proposed to be included [for details please refer Annexure- D of Tender document].		Yes	Allowed (Mandatory)
4	Scanned copy [in PDF format] of the details of technical personals of the Agency, available in hand [for details please refer Annexure-E of Tender document].		Yes	Allowed (Mandatory)
5	Scanned copy [in PDF format] of the complete address of the firm in PDF format, to which the all correspondences shall be made by the railway.[for details please refer Annexure-A of Tender document].		Yes	Allowed (Mandatory)
6	Scanned copy [in PDF format] of the eligibility cateria by the tenderer regarding contractual payments recived. [for details please refer Annexure-C of Tender document].	Yes	Yes	Allowed (Mandatory)
7	Scanned copy [in PDF format] of details the works on hand by the tenderer(s) [for details please refer Annexure-G of Tender document].	Yes	Yes	Allowed (Mandatory)
8	Scanned copy [in PDF format] of broad plan of execution of this work within the stipulated completion period [for details please refer Annexure-K of Tender document].		Yes	Allowed (Mandatory)
9	Scanned copy [in PDF format] of other credientials/facilities available with the firm/contractor/tenderer[for details please refer Annexure-L of Tender document].		Yes	Allowed (Mandatory)
10	Scan COPY OF THE PROGRAMME IN THE FORM OF BAR CHART FOR COMPLETION OF WORK, MACHINERY DEPLOYMENT FOR ACHIEVING THE PROGRAMMED PROGRESS MUST BE UPLOADED ALONG WITH THE TENDER		Yes	Allowed (Mandatory)
11	Scanned copy [in PDF format] of Deviation [for details please refer Annexure-M of Tender document].	Yes	Yes	Allowed (Mandatory)
12	Scanned copy [in PDF format] of the undertaking by Bidders towards compliance of office memorandum F. No. 6/18/2019-PPD dated 23rd July, 2020 (Public Procurement no.1) issued by Department of Expenditure, Ministry of Finance, Govt. of India. [for details please refer Annexure-N of Tender Document].	Yes	Yes	Allowed (Mandatory)
13	Scanned copy [in PDF format] of the Eligibility Criteria by the tenderer regarding execution of similar work (as per tender condition) [for details please refer Annexure- B of Tender document].		Yes	Allowed (Mandatory)
14	Scanned copy [in PDF format] of the details of the works completed during previous seven financial years and current year by the tenderer [for details please refer Annexure-F of Tender document]		Yes	Allowed (Mandatory)

Page 7 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

### Undertakings

S.No.	Description			Documents Uploading
1	$\ensuremath{I}/\ensuremath{We}$ have visited the works site and $\ensuremath{I}$ / $\ensuremath{We}$ am / are aware of the site conditions.	No	No	Not Allowed
2	I/We also hereby agree to abide by the Indian Railways Standard General Conditions of Contract April'2022 [GCC], with all correction slips up-to-date and to carry out the work according to the Special Conditions of Contract and specifications of materials and works as laid down by Railway as mentioned in the Special Conditions/ Specifications.	No	No	Not Allowed
3	It is certified that I am the authorised person to represent the firm and I am authorised to sign the tender and all the documents on behalf of the firm.		No	Not Allowed
4	It is certified that all the statement and document submitted with the offer are true and correct.	No	No	Not Allowed
5	It is certified that we are aware of the fact that this tender offer is made in the full understanding that our offer will be subjected to verification of all the information submitted with this tender.		No	Not Allowed
6	We have read the tender Notice [NIT] in detail, Tender document along with all the conditions attached/referred to, in this tender document, and agree to abide by the said conditions.		No	Not Allowed
7	We are aware of the fact that the railway reserve the rights to amend the scope and value of the contract and to reject [or accept] this offer without assigning any financial liability.		No	Not Allowed

### 6. Documents attached with tender

S.No.	Document Name	Document Description
1	Annexure1.pdf	Annexure 1
2	Annexure2.pdf	Annexure 2
3	Annexure3.pdf	Annexure 3
4	Annexure4.pdf	Annexure 4
5	AnnexureA.pdf	Annexure A
6	AnnexureBB1.pdf	Annexure B B1
7	AnnexureC.pdf	Annexure C
8	AnnexureD.pdf	Annexure D
9	AnnexureE.pdf	Annexure E
10	AnnexureF.pdf	Annexure F
11	AnnexureG.pdf	Annexure G
12	AnnexureH.pdf	Annexure H
13	Annexurel.pdf	Annexure I
14	AnnexureJ.pdf	Annexure J
15	AnnexureK.pdf	Annexure K
16	AnnexureL.pdf	Annexure L
17	AnnexureM.pdf	Annexure M
18	AnnexureN.pdf	Annexure N
19	AnnexureV.pdf	Annexure V
20	AnnexureVA.pdf	Annexure V A
21	GCCApril-2022.pdf	GCC April 2022
22	AdvanceCorrectionSlip-1GCC- 2022.pdf	Advance Correction Slip 1
23	AdvanceCorrectionSlip-2GCC- 2022.pdf	Advance Correction Slip 2
24	AdvanceCorrectionSlip-3GCC- 2022.pdf	Advance Correction Slip 3
25	TenderFormFirstSheet.pdf	Tender Form First Sheet

Page 8 of 9 Run Date/Time: 20/07/2023 17:34:24

Tender No: 2023-WP-ELECT-ANVT-WT-03 Closing Date/Time: 17/08/2023 13:00

26	TenderDocument.pdf	Tender Document

This tender complies with Public Procurement Policy (Make in India) Order 2017, dated 15/06/2017, issued by Department of Industrial Promotion and Policy, Ministry of Commerce, circulated vide Railway Board letter no. 2015/RS(G)/779/5 dated 03/08/2017 and 27/12/2017 and amendments/ revisions thereof.

As a Tender Inviting Authority, the undersigned has ensured that the issue of this tender does not violate provisions of GFR regarding procurement through GeM.

Signed By: KUMAR VINAY KRISHNA

Designation: Dy.CEE/WP

Page 9 of 9 Run Date/Time: 20/07/2023 17:34:24