

Navigating The Future of Online Shopping

Ecommerce Analysis Using Python and SQL

- SQL (MySQL) – Data Extraction, Querying
- Python (Pandas, Matplotlib) – Data Analysis, Visualization
- VsCode – Implementation
- Workflow – Data Cleaning > Analysis > Visualization > Insights

-Shreyash Kale



About Company

This dataset captures transactional data from a multi-category e-commerce platform that connects customers and sellers across diverse regions. The platform supports a broad product catalog and flexible payment options, including installment plans.

As competition in the e-commerce landscape intensifies, analyzing customer behavior, sales performance, and seller contributions becomes essential for driving sustainable business growth.

Insights - Basics

Objective: Extract fundamental insights from the dataset.

- Unique cities where customers are located – 4119 cities
- Number of orders placed in 2017 – 45,101 orders
- Total sales per category – health & Beauty Rs 1.25m
- Percentage of orders paid in installments – 51.46%
- Number of customers from each state – SP leads with 41,746

Q1. LIST ALL UNIQUE CITIES WHERE CUSTOMERS ARE LOCATED

Code: python

```
customers['customer_city'].unique()
```

Output

```
array(['franca', 'sao bernardo do campo', 'sao paulo', ...,  
      'monte bonito', 'sao rafael', 'eugenio de castro'], dtype=object)
```

Query: Sql

```
-- =====  
-- Q1. LIST ALL UNIQUE CITIES WHERE CUSTOMERS ARE LOCATED  
-- =====  
SELECT DISTINCT customer_city  
FROM customers;
```

Output

```
=====  
Q1. UNIQUE CITIES WHERE CUSTOMERS ARE LOCATED  
=====  
customer_city  
-----  
franca  
sao bernardo do campo  
sao paulo  
mogi das cruces  
campinas  
jaragua do sul  
timoteo
```

Q2. COUNT THE NUMBER OF ORDERS PLACED IN 2017

Code: python

```
-- Q2: Count the number of orders placed in 2017
SELECT COUNT(*) AS total_orders_2017
FROM orders
WHERE year(order_purchase_timestamp) = '2017';
```

Output

45101

Query: Sql

```
-- =====
-- Q2. COUNT THE NUMBER OF ORDERS PLACED IN 2017
-- =====
SELECT COUNT(DISTINCT order_id) AS total_orders_2017
FROM orders
WHERE STRFTIME('%Y', order_purchase_timestamp) = '2017';
```

Output

```
=====
Q2. COUNT OF ORDERS PLACED IN 2017
=====
total_orders_2017
-----
45101
```

Q3. FIND THE TOTAL SALES PER CATEGORY

Code: python

```
temp = order_items.merge(
    products[['product_id', 'product_category']],
    on='product_id',
    how='inner'
)
temp['product_category'] = temp['product_category'].fillna('Unknown')
category_sales = temp.groupby('product_category')['price'].sum().reset_index()
category_sales.rename(columns={
    'product_category': 'product_category_name',
    'price': 'total_sales'
}, inplace=True)

category_sales = category_sales.sort_values(
    by=['total_sales', 'product_category_name'],
    ascending=[False, True]
)
top9 = category_sales.head(9)
top9 = top9.reset_index(drop=True)
top9
```

Output

	product_category_name	# total_sales
0	HEALTH BEAUTY	1258681.34
1	Watches present	1205005.68
2	bed table bath	1036988.68
3	sport leisure	988048.97
4	computer accessories	911954.32
5	Furniture Decoration	729762.49
6	Cool Stuff	635290.85
7	housewares	632248.66
8	automotive	592720.11

Query: Sql

```
-- =====
-- Q3. FIND THE TOTAL SALES PER CATEGORY
-- =====

SELECT p.product_category_name,
       ROUND(SUM(oi.price), 2) AS total_sales
FROM order_items oi
JOIN products p ON oi.product_id = p.product_id
GROUP BY p.product_category_name
ORDER BY total_sales DESC,
         p.product_category_name ASC;
```

Output

```
=====
Q3: Total sales per category
=====
product_category  total_sales
HEALTH BEAUTY    1258681.34
Watches present  1205005.68
bed table bath   1036988.68
sport leisure    988048.97
computer accessories  911954.32
Furniture Decoration  729762.49
Cool Stuff       635290.85
housewares       632248.66
automotive       592720.11
Garden tools     485256.46
toys             483946.60
babies          411764.89
perfumery        399124.87
```

Q4. CALCULATE THE PERCENTAGE OF ORDERS THAT WERE PAID IN INSTALLMENTS

Code: python

```
installment_orders = payments[payments['payment_installments'] > 1]['order_id'].nunique()

total_orders = payments['order_id'].nunique()

percentage = (installment_orders / total_orders) * 100

percentage
```

Output

51.46

Query: Sql

```
-- =====
-- Q4. CALCULATE THE PERCENTAGE OF ORDERS THAT WERE PAID IN INSTALLMENTS
-- =====

SELECT
    ROUND(
        COUNT(DISTINCT CASE WHEN payment_installments > 1 THEN order_id END) * 100.0
        / COUNT(DISTINCT order_id),
        2
    ) AS installment_percentage
FROM payments;
```

Output

```
=====
Q4. PERCENTAGE OF ORDERS PAID IN INSTALLMENTS
=====
installment_percentage
-----
51.46
```

Q5. COUNT THE NUMBER OF CUSTOMERS FROM EACH STATE

Code: python

```
customers_state = customers['customer_state'].value_counts()

customers_state
```

Output

customer_state	# count
SP	41746
RJ	12852
MG	11635
RS	5466
PR	5045
SC	3637
BA	3380
DF	2140
ES	2033
GO	2020

Query: Sql

```
-- =====
-- Q5. COUNT THE NUMBER OF CUSTOMERS FROM EACH STATE
-- =====

SELECT customer_state,
       COUNT(*) AS total_customers
FROM customers
GROUP BY customer_state
ORDER BY total_customers DESC;
```

Output

Q5. NUMBER OF CUSTOMERS FROM EACH STATE	
=====	
customer_state	total_customers

SP	41746
RJ	12852
MG	11635
RS	5466
PR	5045
SC	3637
BA	3380
DF	2140
ES	2033
GO	2020
PE	1652

Insights - Intermediate

Objective: Dive deeper into sales and order trends.

- Orders per month in 2018 – January peak 7269 orders
- Avg products per order by city – Padre Carvalho, 7 products/orders
- Revenue % by product category – Health & Beauty 9.26%
- Price vs purchase frequency – Most purchased products, 527 times
- Total revenue by seller ranked – Top seller, Rs 2,29,472

Q6. CALCULATE THE NUMBER OF ORDERS PER MONTH IN 2018

Code: python

```
orders['order_purchase_timestamp'] = pd.to_datetime(orders['order_purchase_timestamp'])

orders['year_month'] = orders['order_purchase_timestamp'].dt.to_period('M').astype(str)

orders_2018 = orders[orders['order_purchase_timestamp'].dt.year == 2018]

orders_count = orders_2018.groupby('year_month')['order_id'].count().reset_index()
orders_count.rename(columns={'order_id': 'no_of_orders'}, inplace=True)

orders_count = orders_count.sort_values('year_month')

orders_count = orders_count.reset_index(drop=True)

orders_count
```

Output

	year_month	# no_of_orders
0	2018-01	7269
1	2018-02	6728
2	2018-03	7211
3	2018-04	6939
4	2018-05	6873
5	2018-06	6167
6	2018-07	6292
7	2018-08	6512
8	2018-09	16
9	2018-10	4

Query: Sql

```
-- =====
-- Q6. CALCULATE THE NUMBER OF ORDERS PER MONTH IN 2018
-- =====

SELECT
    STRFTIME('%Y-%m', order_purchase_timestamp) AS month,
    COUNT(*) AS total_orders
FROM orders
WHERE STRFTIME('%Y', order_purchase_timestamp) = '2018'
GROUP BY month
ORDER BY month;
```

Output

Q6. NUMBER OF ORDERS PER MONTH IN 2018	
month	total_orders
2018-01	7269
2018-02	6728
2018-03	7211
2018-04	6939
2018-05	6873
2018-06	6167
2018-07	6292
2018-08	6512

Q7. FIND THE AVERAGE NUMBER OF PRODUCTS PER ORDER, GROUPED BY CUSTOMER CITY

Code: python

```
products_per_order = order_items.groupby('order_id').size().reset_index(name='product_count')
merged = products_per_order.merge(
    orders[['order_id', 'customer_id']],
    on='order_id'
).merge(
    customers[['customer_id', 'customer_city']],
    on='customer_id'
)

result = merged.groupby('customer_city')['product_count'].mean().reset_index()

result['avg_products_per_order'] = result['product_count'].round(2)

result = result[['customer_city', 'avg_products_per_order']]
result = result.sort_values(
    by=['avg_products_per_order', 'customer_city'],
    ascending=[False, True]
)
result.head(10)
```

Output

	customer_city	# avg_products_per_order
2619	padre carvalho	7.0
907	celso ramos	6.5
756	candido godoi	6.0
1154	datas	6.0
2264	matias olimpiao	5.0
955	cidelandia	4.0
1146	curralinho	4.0
2395	morro de sao paulo	4.0
2817	picarra	4.0
3821	teixeira soares	4.0

Query: Sql

```
-- =====
-- Q7. FIND THE AVERAGE NUMBER OF PRODUCTS PER ORDER, GROUPED BY CUSTOMER CITY
-- =====

SELECT
    c.customer_city,
    ROUND(AVG(t.product_count), 2) AS avg_products_per_order
FROM (
    SELECT
        oi.order_id,
        COUNT(*) AS product_count
    FROM order_items oi
    GROUP BY oi.order_id
) t
JOIN orders o ON t.order_id = o.order_id
JOIN customers c ON o.customer_id = c.customer_id
GROUP BY c.customer_city
ORDER BY avg_products_per_order DESC,
         c.customer_city ASC;
```

Output

Q7. AVG PRODUCTS PER ORDER BY CUSTOMER CITY	
customer_city	avg_products_per_order
padre carvalho	7.0
celso ramos	6.5
candido godoi	6.0
datas	6.0
matias olimpiao	5.0
cidelandia	4.0
curralinho	4.0

Q8. CALCULATE THE PERCENTAGE OF TOTAL REVENUE CONTRIBUTED BY EACH PRODUCT CATEGORY

Code: python

```
temp = order_items.merge(
    products[['product_id', 'product_category']],
    on='product_id',
    how='inner'
)
category_revenue = temp.groupby('product_category')['price'].sum().reset_index()
category_revenue.rename(columns={
    'product_category': 'product_category_name',
    'price': 'revenue_category'
}, inplace=True)
total_revenue = category_revenue['revenue_category'].sum()

category_revenue['revenue_percentage'] = (
    category_revenue['revenue_category'] / total_revenue
) * 100

category_revenue['revenue_category'] = category_revenue['revenue_category'].round(6)
category_revenue['revenue_percentage'] = category_revenue['revenue_percentage'].round(2)

category_revenue = category_revenue.sort_values(
    by=['revenue_category', 'product_category_name'],
    ascending=[False, True]
)
category_revenue = category_revenue.reset_index(drop=True)
category_revenue
```

Output

	product_category_name	# revenue_category	# revenue_percentage
0	HEALTH BEAUTY	1258681.34	9.38
1	Watches present	1205005.68	8.98
2	bed table bath	1036988.68	7.73
3	sport leisure	988048.97	7.37
4	computer accessories	911954.32	6.8
5	Furniture Decoration	729762.49	5.44
6	Cool Stuff	635290.85	4.74
7	housewares	632248.66	4.71
8	automotive	592720.11	4.42
9	Garden tools	485256.46	3.62

Query: Sql

```
-- =====
-- Q8. CALCULATE THE PERCENTAGE OF TOTAL REVENUE CONTRIBUTED BY EACH PRODUCT CATEGORY
-- =====

SELECT
    p.product_category_name,
    ROUND(SUM(oi.price), 6) AS category_revenue,
    ROUND(
        SUM(oi.price) * 100.0 /
        (SELECT SUM(price) FROM order_items),
        2
    ) AS revenue_percentage
FROM order_items oi
JOIN products p ON oi.product_id = p.product_id
GROUP BY p.product_category_name
ORDER BY category_revenue DESC;
```

Output

```
=====
Q8. REVENUE CONTRIBUTION BY PRODUCT CATEGORY
=====
```

product_category	category_revenue	revenue_percentage
HEALTH BEAUTY	1258681.34	9.38
Watches present	1205005.68	8.98
bed table bath	1036988.68	7.73
sport leisure	988048.97	7.37

Q9. IDENTIFY THE CORRELATION BETWEEN PRODUCT PRICE AND THE NUMBER OF TIMES A PRODUCT HAS BEEN PURCHASED

Code: python

```
# Frequency
product_freq = order_items.groupby('product_id').size().reset_index(name='purchase_count')

# Avg price
product_price = order_items.groupby('product_id')['price'].mean().reset_index()

# Merge
merged = product_freq.merge(product_price, on='product_id')

# Correlation
correlation = merged['price'].corr(merged['purchase_count'])

correlation
```

Output

```
np.float64(-0.032139862680945167)
```

Query: Sql

```
-- =====
-- Q9. CORRELATION BETWEEN PRODUCT PRICE AND PURCHASE FREQUENCY
-- =====
SELECT
(
COUNT(*) * SUM(avg_price * purchase_count)
- SUM(avg_price) * SUM(purchase_count)
)
/
SQRT(
(COUNT(*) * SUM(avg_price * avg_price) - (SUM(avg_price) * SUM(avg_price))) *
(COUNT(*) * SUM(purchase_count * purchase_count) - (SUM(purchase_count) * SUM(purchase_count)))
) AS correlation
FROM (
SELECT
product_id,
COUNT(*) AS purchase_count,
AVG(price) AS avg_price
FROM order_items
GROUP BY product_id
) t;
```

Output

```
=====
Q9. CORRELATION: PRODUCT PRICE VS PURCHASE FREQUENCY
=====
correlation
-----
-0.03213986268094519
```

Q10. CALCULATE THE TOTAL REVENUE GENERATED BY EACH SELLER, AND RANK THEM BY REVENUE

Code: python

```
seller_revenue = order_items.groupby('seller_id')['price'].sum().reset_index()
seller_revenue.rename(columns={'price': 'revenue'}, inplace=True)
seller_revenue['revenue'] = seller_revenue['revenue'].round(6)

seller_revenue = seller_revenue.sort_values(
    by=['revenue', 'seller_id'],
    ascending=[False, True]
)

seller_revenue['rnk'] = seller_revenue['revenue'].rank(
    method='dense',
    ascending=False
).astype(int)

seller_revenue = seller_revenue.reset_index(drop=True)
seller_revenue.head(10)
```

Output

...	seller_id	# revenue	# rnk
0	4869f7a5dfa277a7dca6462dcf3b52b	229472.63	1
1	53243585a1d6dc2643021fd1853d89	222776.05	2
2	4a3ca9315b744ce9f8e937436149388	200472.92	3
3	fa1c13f2614d7b5c4749cbc52fecda94	194042.03	4
4	7c67e1448b00f6e969d365cea6b010a	187923.89	5
5	7e93a43ef30c4f03f38b393420bc753a	176431.87	6
6	da8622b14eb17ae2831f4ac5b9dab84a	160236.57	7
7	7a67c85e85bb2ce8582c35f2203ad73	141745.53	8
8	1025f0e2d44d7041d6cf58b6550e0b1	138968.55	9
9	955fee9216a65b617aa5c0531780ce6	135171.7	10

Query: Sql

```
-- =====
-- Q10. TOTAL REVENUE BY SELLER AND RANK
-- =====

SELECT
    oi.seller_id,
    ROUND(SUM(oi.price), 6) AS revenue,
    RANK() OVER (ORDER BY SUM(oi.price) DESC) AS rnk
FROM order_items oi
GROUP BY oi.seller_id
ORDER BY revenue DESC;
-- Top seller: 4869f7a5dfa... revenue ~229472.63, rank 1
```

Output

Q10. REVENUE BY SELLER AND RANKING		
seller_id	revenue	rnk
4869f7a5dfa277a7dca6462dcf3b52b2	229472.63	1
53243585a1d6dc2643021fd1853d8905	222776.05	2
4a3ca9315b744ce9f8e9374361493884	200472.92	3
fa1c13f2614d7b5c4749cbc52fecda94	194042.03	4
7c67e1448b00f6e969d365cea6b010ab	187923.89	5
7e93a43ef30c4f03f38b393420bc753a	176431.87	6
da8622b14eb17ae2831f4ac5b9dab84a	160236.57	7

Insights - Advanced

Objective: Generate strategic and customer-centric insights.

- Moving average of order values – Tracks customer spending trends
- Cumulative sales per month – 2018 hit, Rs 6.35 by August
- Year-over-year growth rate – 2017 grew 12,745% vs 2016
- Customer retention rate – 0% most buy only once
- Top 3 customers per year – 2017 top spender, Rs 13,440

Q11. CALCULATE THE MOVING AVERAGE OF ORDER VALUES FOR EACH CUSTOMER OVER THEIR ORDER HISTORY

Code: python

```
orders['order_purchase_timestamp'] = pd.to_datetime(orders['order_purchase_timestamp'])

order_value = order_items.groupby('order_id')['price'].sum().reset_index()
order_value.rename(columns={'price': 'order_value'}, inplace=True)

order_value = order_value.merge(
    orders[['order_id', 'customer_id', 'order_purchase_timestamp']],
    on='order_id',
    how='inner'
)

order_value = order_value.sort_values(['customer_id', 'order_purchase_timestamp'])

order_value['moving_avg'] = order_value.groupby('customer_id')['order_value'] \
    .transform(lambda x: x.rolling(window=3, min_periods=1).mean())

order_value = order_value[['customer_id', 'order_id', 'order_purchase_timestamp', 'order_value', 'moving_avg']]

order_value = order_value.reset_index(drop=True)
order_value.head(10)
```

Output

	customer_id	order_id	order_purchase_timestamp	order_value	moving_avg
0	00012a2ce6f8dcda20d059ce9849170	5f79b5b0931d63f1a42989eb65b9da6e	2017-11-14 16:08:26	89.8	89.8
1	000161a058600d5901f007fab4c2714	a44895d095d7e0702b6a162fa2dbec	2017-07-16 09:40:32	54.9	54.9
2	0001fd6190edaaf884bcaf3d49edf079	316a104623542e4d75189bb372bc5f8d	2017-02-28 11:06:43	179.99	179.99
3	0002414f95344307404f0ace7a26f1d5	5825ce2e88d5346438686b0bba99e5ee	2017-08-16 13:09:20	149.9	149.9
4	000379cdec625522490c315e70c7a9fb	0ab7fb08086d4af9141453c91878ed7a	2018-04-02 13:42:17	93.0	93.0
5	0004164d20a9e969af783496f3408652	cd3558a10d854487b4f907e9b326a4fc	2017-04-12 08:35:12	59.99	59.99
6	000419c5494106c306a97b5635748086	07f6c3baf9ac86865b60f640c4f923c6	2018-03-02 17:47:40	34.3	34.3
7	00046a560d4407e99b969756eb0b10f2	8c3d752c5c02227878fae49aeaddbf1d	2017-12-18 11:08:30	120.9	120.9
8	00050b6e01e69d5cd0612f1bcb69fa	fa906f338cee30e994d0945b3832e43	2017-09-17 16:04:44	69.99	69.99
9	000598ca2e4117407665ac3327513	9b961b0894e797f63622137f7eb1c1a	2018-08-11 12:14:35	1107.0	1107.0

Query: Sql

```
-- *****
-- Q11. MOVING AVERAGE OF ORDER VALUES FOR EACH CUSTOMER
-- (3-row window: current + 2 preceding)
-- *****

WITH order_value AS (
    SELECT
        c.customer_id,
        o.order_id,
        o.order_purchase_timestamp,
        SUM(oi.price) AS order_value
    FROM orders o
    JOIN order_items oi ON o.order_id = oi.order_id
    JOIN customers c ON o.customer_id = c.customer_id
    GROUP BY c.customer_id, o.order_id, o.order_purchase_timestamp
)
SELECT
    customer_id,
    order_id,
    order_purchase_timestamp,
    order_value,
    AVG(order_value) OVER (
        PARTITION BY customer_id
        ORDER BY order_purchase_timestamp
        ROWS BETWEEN 2 PRECEDING AND CURRENT ROW
    ) AS moving_avg
FROM order_value
ORDER BY customer_id, order_purchase_timestamp;
```

Output

Q11. MOVING AVERAGE OF ORDER VALUES PER CUSTOMER				
customer_id	order_id	order_purchase_timestamp	order_value	moving_avg
00012a2ce6f8dcda20d059ce98491703	5f79b5b0931d63f1a42989eb65b9da6e	2017-11-14 16:08:26	89.8	89.8
000161a058600d5901f007fab4c27140	a44895d095d7e0702b6a162fa2dbec	2017-07-16 09:40:32	54.9	54.9
0001fd6190edaaf884bcaf3d49edf079	316a104623542e4d75189bb372bc5f8d	2017-02-28 11:06:43	179.99	179.99
0002414f95344307404f0ace7a26f1d5	5825ce2e88d5346438686b0bba99e5ee	2017-08-16 13:09:20	149.9	149.9
000379cdec625522490c315e70c7a9fb	0ab7fb08086d4af9141453c91878ed7a	2018-04-02 13:42:17	93.0	93.0
0004164d20a9e969af783496f3408652	cd3558a10d854487b4f907e9b326a4fc	2017-04-12 08:35:12	59.99	59.99
000419c5494106c306a97b5635748086	07f6c3baf9ac86865b60f640c4f923c6	2018-03-02 17:47:40	34.3	34.3

Q12. CALCULATE THE CUMULATIVE SALES PER MONTH FOR EACH YEAR

Code: python

```
temp = orders.merge(order_items, on='order_id', how='inner')

temp['order_purchase_timestamp'] = pd.to_datetime(temp['order_purchase_timestamp'])

temp['year'] = temp['order_purchase_timestamp'].dt.year
temp['month'] = temp['order_purchase_timestamp'].dt.month
temp['month_name'] = temp['order_purchase_timestamp'].dt.month_name()
monthly_sales = temp.groupby(['year', 'month', 'month_name'])['price'].sum().reset_index()
monthly_sales = monthly_sales.sort_values(['year', 'month'])

monthly_sales['cumulative_sales'] = monthly_sales.groupby('year')['price'].cumsum()

monthly_sales.rename(columns={'price': 'monthly_sales'}, inplace=True)

monthly_sales = monthly_sales[
    ['year', 'month', 'month_name', 'monthly_sales', 'cumulative_sales']
]
monthly_sales = monthly_sales.reset_index(drop=True)

monthly_sales['monthly_sales'] = monthly_sales['monthly_sales'].round(6)
monthly_sales['cumulative_sales'] = monthly_sales['cumulative_sales'].round(6)
monthly_sales.head(10)
```

Output

...	# year	# month	month_name	# monthly_sales	# cumulative_sales
0	2016	9	September	267.36	267.36
1	2016	10	October	49507.66	49775.02
2	2016	12	December	10.9	49785.92
3	2017	1	January	120312.87	120312.87
4	2017	2	February	247303.02	367615.89
5	2017	3	March	374344.3	741960.19
6	2017	4	April	359927.23	1101887.42
7	2017	5	May	506071.14	1607958.56
8	2017	6	June	433038.6	2040997.16
9	2017	7	July	498031.48	2539028.64

Query: Sql

```
-- =====
-- Q12. CUMULATIVE SALES PER MONTH FOR EACH YEAR
-- =====

SELECT
    year,
    month,
    month_name,
    ROUND(monthly_sales, 6) AS monthly_sales,
    ROUND(cumulative_sales, 6) AS cumulative_sales
FROM (
    SELECT
        STRFTIME('%Y', o.order_purchase_timestamp) AS year,
        STRFTIME('%m', o.order_purchase_timestamp) AS month,
        CASE STRFTIME('%m', o.order_purchase_timestamp)
            WHEN '01' THEN 'January'
            WHEN '02' THEN 'February'
            WHEN '03' THEN 'March'
            WHEN '04' THEN 'April'
            WHEN '05' THEN 'May'
            WHEN '06' THEN 'June'
            WHEN '07' THEN 'July'
            WHEN '08' THEN 'August'
            WHEN '09' THEN 'September'
            WHEN '10' THEN 'October'
            WHEN '11' THEN 'November'
            WHEN '12' THEN 'December'
        END AS month_name,
        SUM(o.price) AS monthly_sales,
        SUM(SUM(o.price) OVER (
            PARTITION BY STRFTIME('%Y', o.order_purchase_timestamp)
            ORDER BY STRFTIME('%m', o.order_purchase_timestamp)
        )) AS cumulative_sales
    FROM orders o
    JOIN order_items oi ON o.order_id = oi.order_id
    GROUP BY year, month, month_name
) t
ORDER BY year, month;
```

Output

Q12. CUMULATIVE SALES PER MONTH FOR EACH YEAR				
year	month	month_name	monthly_sales	cumulative_sales
2016	09	September	267.36	267.36
2016	10	October	49507.66	49775.02
2016	12	December	10.9	49785.92
2017	01	January	120312.87	120312.87
2017	02	February	247303.02	367615.89
2017	03	March	374344.3	741960.19
2017	04	April	359927.23	1101887.42

Q13. CALCULATE THE YEAR OVER YEAR GROWTH RATE OF TOTAL SALES

Query: Sql

Code: python

```
temp = orders.merge(order_items, on='order_id', how='inner')
temp['order_purchase_timestamp'] = pd.to_datetime(temp['order_purchase_timestamp'])
temp['year'] = temp['order_purchase_timestamp'].dt.year
yearly_sales = temp.groupby('year')['price'].sum().reset_index()
yearly_sales.rename(columns={'price': 'total_sales'}, inplace=True)

yearly_sales = yearly_sales.sort_values('year')

yearly_sales['previous_year_sales'] = yearly_sales['total_sales'].shift(1)

yearly_sales['yoy_growth_percentage'] = (
    (yearly_sales['total_sales'] - yearly_sales['previous_year_sales']) /
    yearly_sales['previous_year_sales']
) * 100

yearly_sales['total_sales'] = yearly_sales['total_sales'].round(6)
yearly_sales['previous_year_sales'] = yearly_sales['previous_year_sales'].round(6)
yearly_sales['yoy_growth_percentage'] = yearly_sales['yoy_growth_percentage'].round(2)

yearly_sales = yearly_sales.reset_index(drop=True)
yearly_sales
```

Output

#	year	#	total_sales	#	previous_year_sales	#	yoy_growth_percentage
0	2016		49785.92		Missing value		Missing value
1	2017		6155806.98		49785.92		12264.55
2	2018		7386050.8		6155806.98		19.99

```
-- =====
-- Q13. YEAR OVER YEAR GROWTH RATE OF TOTAL SALES
-- =====

SELECT
    year,
    ROUND(total_sales, 6) AS total_sales,
    ROUND(LAG(total_sales) OVER (ORDER BY year), 6) AS previous_year_sales,
    ROUND(
        (total_sales - LAG(total_sales) OVER (ORDER BY year))
        / LAG(total_sales) OVER (ORDER BY year) * 100,
        2
    ) AS yoy_growth_percentage
FROM (
    SELECT
        STRFTIME('%Y', o.order_purchase_timestamp) AS year,
        SUM(oi.price) AS total_sales
    FROM orders o
    JOIN order_items oi ON o.order_id = oi.order_id
    GROUP BY year
) t
ORDER BY year;
```

Output

Q13. YEAR OVER YEAR GROWTH RATE			
year	total_sales	previous_year_sales	yoy_growth_percentage
2016	49785.92	None	None
2017	6155806.98	49785.92	12264.55
2018	7386050.8	6155806.98	19.99

Q14. CALCULATE THE RETENSION RATE OF CUSTOMERS, DEFINED AS THE PERCENTAGE OF CUSTOMERS WHO MAKE ANOTHER PURCHASE WITHIN 6 MONTHS OF THEIR FIRST PURCHASE

Code: python

```
# Ensure datetime
orders['order_purchase_timestamp'] = pd.to_datetime(orders['order_purchase_timestamp'])

# Sort orders
orders_sorted = orders.sort_values(['customer_id', 'order_purchase_timestamp'])

# First purchase
first_order = orders_sorted.groupby('customer_id')['order_purchase_timestamp'].first().reset_index()

# Merge
orders_merged = orders_sorted.merge(first_order, on='customer_id', suffixes=('', '_first'))

# Days difference
orders_merged['diff_days'] = (orders_merged['order_purchase_timestamp'] -
                              orders_merged['order_purchase_timestamp_first']).dt.days

# Retained customers (within 180 days)
retained_customers = orders_merged[
    (orders_merged['diff_days'] > 0) & (orders_merged['diff_days'] <= 180)
]['customer_id'].nunique()

total_customers = orders['customer_id'].nunique()

retention_rate = (retained_customers / total_customers) * 100

retention_rate
```

Output

```
0.0
```

Query: Sql

```
-- =====
-- Q14. CUSTOMER RETENTION RATE (within 6 months of first purchase)
-- =====

WITH first_orders AS (
    SELECT
        customer_id,
        MIN(order_purchase_timestamp) AS first_order
    FROM orders
    GROUP BY customer_id
),
repeat_customers AS (
    SELECT DISTINCT o.customer_id
    FROM orders o
    JOIN first_orders f ON o.customer_id = f.customer_id
    WHERE o.order_purchase_timestamp > f.first_order
    AND JULIANDAY(o.order_purchase_timestamp) <= JULIANDAY(f.first_order) + 180
)
SELECT
    ROUND(
        COUNT(DISTINCT r.customer_id) * 100.0 /
        COUNT(DISTINCT f.customer_id),
        2
    ) AS retention_rate
FROM first_orders f
LEFT JOIN repeat_customers r ON f.customer_id = r.customer_id;
```

Output

```
=====
Q14. CUSTOMER RETENTION RATE (within 6 months)
=====
retention_rate
-----
0.0
```

Q15. IDENTIFY THE TOP 3 CUSTOMERS WHO SPENT THE MOST MONEY IN EACH YEAR

Code: python

```
temp = orders.merge(order_items, on='order_id', how='inner')

temp['order_purchase_timestamp'] = pd.to_datetime(temp['order_purchase_timestamp'])

temp['year'] = temp['order_purchase_timestamp'].dt.year

cust_year_spend = temp.groupby(['year', 'customer_id'])['price'].sum().reset_index()
cust_year_spend.rename(columns={'price': 'total_spent'}, inplace=True)

cust_year_spend['rnk'] = cust_year_spend.groupby('year')['total_spent'] \
    .rank(method='min', ascending=False).astype(int)
top3 = cust_year_spend[cust_year_spend['rnk'] <= 3]
top3 = top3.sort_values(['year', 'rnk', 'customer_id'])
top3['total_spent'] = top3['total_spent'].round(6)
top3 = top3.reset_index(drop=True)
top3
```

Output

#	year	customer_id	total_spent	rnk
0	2016	a9dc96b027d1252bbac0a9b72d837f	1399.0	1
1	2016	1d34ed25963d5aae4cf3d7f3a4cda17	1299.99	2
2	2016	4a06381959b6670756de02e07b8381	1199.0	3
3	2017	1617b1357756262bfa56ab541c47bc	13440.0	1
4	2017	c6e2731c5b391845f6800c97401a43a	6735.0	2
5	2017	3fd6777bbce08a352fddd04e4a7cc8f	6499.0	3
6	2018	ec5b2ba62e574342386871631fafd3f	7160.0	1
7	2018	f48d464a0baaea338cb25f816991ab1	6729.0	2
8	2018	e0a2412720e9ea4f26c1ac985f6a735	4599.9	3

Query: Sql

```
-- =====
-- Q15. TOP 3 CUSTOMERS WHO SPENT THE MOST MONEY IN EACH YEAR
-- =====

SELECT *
FROM (
    SELECT
        STRFTIME('%Y', o.order_purchase_timestamp) AS year,
        o.customer_id,
        SUM(oi.price) AS total_spent,
        RANK() OVER (
            PARTITION BY STRFTIME('%Y', o.order_purchase_timestamp)
            ORDER BY SUM(oi.price) DESC
        ) AS rnk
    FROM orders o
    JOIN order_items oi ON o.order_id = oi.order_id
    GROUP BY year, o.customer_id
) t
WHERE rnk <= 3
ORDER BY year, rnk;
```

Output

Q15. TOP 3 CUSTOMERS BY SPENDING PER YEAR			
year	customer_id	total_spent	rnk
2016	a9dc96b027d1252bbac0a9b72d837fc6	1399.0	1
2016	1d34ed25963d5aae4cf3d7f3a4cda173	1299.99	2
2016	4a06381959b6670756de02e07b83815f	1199.0	3
2017	1617b1357756262bfa56ab541c47bc16	13440.0	1
2017	c6e2731c5b391845f6800c97401a43a9	6735.0	2

Key Business Insight

- 1. São Paulo dominates — SP state has 42% of all customers
- 2. Health & Beauty is top category — Rs1.25M in total sales
- 3. Half of customers pay in installments — 49.42% use installment plans
- 4. Massive growth in 2017 — Business grew 12,745% compared to 2016
- 5. Low retention rate — Most customers purchase only once, suggesting need for loyalty programs
- 6. Seasonal peaks — November 2017 had highest monthly sales (Rs863K) likely due to Black Friday



Thank You

Github: <https://github.com/itsShreyashkale/ecommerce-sql-python-project.git>

Linkedin: <https://www.linkedin.com/in/shreyash-kale-204b0a228/>