



Battery Sizing PPT

USA · India

Innovate. Integrate. Build.



1

Load Determination

2

Voltage Finalization

3

Current Details

4

Environment Condition

5

Battery Sizing



Load Determination

- ★ EV
- ★ Solar
- ★ UPS





Voltage Finalization

- ★ Motor Rating
- ★ Controller rating
- ★ System Rating (Voltage Window)





Current Details

- ★ Peak Current (time)
- ★ Continuous Current (time)
- ★ Backup time requirement; Mileage





Environment Condition

- ★ Operating temperature
- ★ Discharge time (day or night)
- ★ Availability of AC





Battery Sizing



Battery Sizing

- ❑ Battery sizing depend on points discussed above like load, voltage, current, temperature
- ❑ Lithium battery is measured in kilo watt hr(KWH)
- ❑ For determining kwh we need to know voltage and ampere hour i.e for eg. 48V 24AH ($48 \times 24 = 1152$) which is 1.152kwh
- ❑ Now for sizing depth of discharge (DOD) is important i.e for eg a 100Ah if discharge up to 80Ah then it said 80%DOD for that pack
- ❑ As we already know DOD is important for life cycle of pack it is decided as per longevity required by customer by as per theory 80% DOD is ideal.
- ❑ If we are aware of voltage, current and back up time just multiply current and back up time eg (10A load * 10Hrs back up = 100AH) is minimum required, Just add 20% capacity as DOD is only 80% , that means u need 120AH battery pack.
- ❑ In case of high operating temp like 50 degree and above add another 20% for long life, other wise battery will degrade faster.

Thank You!

Innolia Energy 2020



US:
405 Boulder Court
Pleasanton, CA 94566
(925) 398-8466, (925) 954-4770
team@innoliaenergy.com



India:
16-11-741/c/3 Moosarambagh
Dilsukhnagar, Hyderabad 500060
040-40274296, +91-7799992037
+91-9010752755, info@innoliaenergy.com



Factory:
284-2-88/1 Lingotam
Kuntlagudem, Telangana 508252
+91-9182543576, +91-9825969807
+91-9866586771, sales@innoliaenergy.com