ChromIQ

Measurement Report - Verification of Profile - Demo-Report-Matrix-verify

Created: 2026-08-11 11:21:10

Report Scope

The following profile verification runs are included:

- Demo-Report-Matrix-verify, Instrument: X-Rite ColorMunki · 1 verification run

No. of Measurements:
1

Date range:
2026-07-10 – 2026-07-10

How to read this report

This report compares what your instrument measured against the chart's design colours (the reference values the chart was built from). Every number is a colour difference (ΔE00): 0 is a perfect match, 1–2 is barely visible, and 10 or more is clearly different.

- Colour accuracy — the ΔE00 across the patches, split so you can see the bulk of the chart (all patches and the best 95%) apart from the few hardest patches (the worst 5%). Each metric is judged against your Pass thresholds.
- Paper white & darkest black — the brightest and deepest patches (L*), a quick health check of your paper and maximum ink.
- Cube corners — paper white, composite black and the six primary and secondary inks. These say as much about your inks as about the instrument.

What the numbers mean depends on how the chart was printed:

- A profiling chart is printed WITHOUT colour management (the raw print you measure to build a profile). It is not expected to match the design closely, so the ΔE can look large — that's normal. Here it is the CHANGE between dated reports that matters, not a single value.
- A verification chart is printed THROUGH your finished profile — ChromIQ converts the sheet itself and prints it with the printer's colour management off. It SHOULD match the design closely, so low ΔE and passes mean the profile is still accurate; rising numbers over time tell you when it's worth re-profiling. (Printed raw instead, the same sheet is a printer drift check — the report says which way each sheet was printed.)

Some of a chart's design colours can be brighter or more saturated than this printer and paper can physically produce — no profile can print them, however good it is. Where the report can tell (it asks the run's profile), it splits the colour-accuracy figures into two groups: “Within the profile's gamut” — the colours that were genuinely printable, the fair measure of accuracy — and “Beyond it” — the unreachable ones, whose distance describes the limit of the gamut, not a mistake of the profile. Every patch stays counted and visible; the Pass/Fail verdict judges the within-gamut figures.

Because the design reference never changes, comparing dated reports of the same chart on the same printer is a clean, reliable signal of drift — ageing inks, a wandering printer, or an instrument going off. Save a report after each measurement to build that history. Screen and print colours here are approximate; the numbers come from your measurement file and are exact.

Report Results

The following results are extracted from the detailed Colour accuracy data shown below for each measurement run. Where a sheet's colours are split into within / beyond the profile's gamut, Pass and Fail judge the within-gamut figures — colours the profile could never print are not counted against it.

Metric	2026-07-10
Average ΔE, all patches	Fail
Average ΔE, lowest 95%	Fail
Average ΔE, highest 5%	Fail
Maximum ΔE, all patches	Fail
Maximum ΔE, lowest 95%	Fail

Detailed data per measurement run

Measurement run — 2026-07-10T10:00:00 — 105 patches

Profile name: Demo-Report-Matrix-verify

How this verification was produced

What this measured	your whole everyday printing chain — the application's colour engine, this profile and the printer together
Printed	in another application with colour management (your answer when the sheet was measured)
Readings belong to this chart	verified — every patch holds the colour the chart asked for
How the colours were judged	relative to this sheet's own paper white — the print mapped white to the paper, so the paper itself is not counted against the profile
Reference for the ΔE figures	the chart's design colours

Colour accuracy (ΔE00 vs the chart's design)

Metric	Within gamut	Beyond it	All patches	Threshold	Result
Average ΔE, all patches	**2.70**	1.87	2.63	2.00	**Fail**
Average ΔE, lowest 95%	**2.49**	1.76	2.44	2.00	**Fail**
Average ΔE, highest 5%	**6.53**	2.65	6.53	2.00	**Fail**
Maximum ΔE, all patches	**6.97**	2.65	6.97	3.00	**Fail**
Maximum ΔE, lowest 95%	**6.14**	2.13	6.14	3.00	**Fail**
Spread (std. dev.)	**1.65**	0.47	1.60	—	—

Within what the profile (Demo-Report-Matrix.icc) can print: 97 of this sheet's colours; beyond it: 8. The Result judges the within-gamut figures — a colour beyond the gamut was never printable, so its distance describes the gamut's limit, not a mistake of the profile. Those patches stay visible in their own column, and how steady they are from check to check is a drift signal.

Paper white & darkest black

White (1) — L* 100.0
Black (6) — L* 0.0

Cube corners (the eight ink extremes)

Corner	Expected	Measured	ΔE00
White (1)			**0.17**
Black (5)			**6.16**
Red (11)			**2.06**
Green (13)			**1.64**
Blue (10)			**6.08**
Cyan (12)			**1.84**
Magenta (14)			**1.23**
Yellow (9)			**2.65**

Worst patches

Patch	Expected	Measured	ΔE00	Patch	Expected	Measured	ΔE00
15			**6.97**	49			**5.85**
55			**6.83**	84			**5.37**
17			**6.56**	103			**5.24**
5			**6.16**	39			**4.88**
7			**6.14**	104			**4.78**
6			**6.14**	95			**4.64**
10			**6.08**	56			**4.48**
8			**5.99**	33			**4.40**