ESCAPE SEQUENCES

Contrary to popular belief, there is no issue in utilizing raw escape sequences. Using `tput` abstracts the same ANSI sequences as if printed manually. Worse still, `tput` is not actually portable. There are a number of `tput` variants each with different commands and syntaxes (*try `tput setaf 3` on a FreeBSD system*). Raw sequences are fine.

Text Colors

NOTE: Sequences requiring RGB values only work in True-Color Terminal Emulators.

Sequence	What does it do?	Value
`\e[38;5;<NUM>m`	Set text foreground color.	`0-255`
`\e[48;5;<NUM>m`	Set text background color.	`0-255`
`\e[38;2;<R>;<G>;<B>m`	Set text foreground color to RGB color.	`R, G, B`
`\e[48;2;<R>;<G>;<B>m`	Set text background color to RGB color.	`R, G, B`

Text Attributes

NOTE: Prepend 2 to any code below to turn it's effect off (examples: 21=bold text off, 22=faint text off, 23=italic text off).

Sequence	What does it do?
`\e[m`	Reset text formatting and colors.
`\e[1m`	Bold text.
`\e[2m`	Faint text.
`\e[3m`	Italic text.
`\e[4m`	Underline text.
`\e[5m`	Blinking text.
`\e[7m`	Highlighted text.
`\e[8m`	Hidden text.
`\e[9m`	Strike-through text.

Cursor Movement

Sequence	What does it do?	Value
`\e[<LINE>;<COLUMN>H`	Move cursor to absolute position.	`line, column`
`\e[H`	Move cursor to home position (`0,0`).	
`\e[<NUM>A`	Move cursor up N lines.	`num`
`\e[<NUM>B`	Move cursor down N lines.	`num`
`\e[<NUM>C`	Move cursor right N columns.	`num`
`\e[<NUM>D`	Move cursor left N columns.	`num`
`\e[s`	Save cursor position.	
`\e[u`	Restore cursor position.	

Erasing Text

Sequence	What does it do?
`\e[K`	Erase from cursor position to end of line.
`\e[1K`	Erase from cursor position to start of line.
`\e[2K`	Erase the entire current line.
`\e[J`	Erase from the current line to the bottom of the screen.
`\e[1J`	Erase from the current line to the top of the screen.
`\e[2J`	Clear the screen.
`\e[2J\e[H`	Clear the screen and move cursor to `0,0`.