

Atul Anurag
PES2UG19CS075
COMPUTER NETWORKS LAB
Week #1

Study and understand the basic networking tools - Wireshark, Tcpdump, Ping, Traceroute and Netcat.

Learn and Understand Network Tools

1. Wireshark

- Perform and analyze Ping PDU capture
- Examine HTTP packet capture
- Analyze HTTP packet capture using filter

2. Netcat

- Establish communication between client and server
- Transfer files

3. Tcpdump

- Capture packets

4. Ping

- Test the connectivity between 2 systems

5. Traceroute

- Perform traceroute checks

6. Nmap

- Explore an entire network

Task 1: Linux Interface Configuration (ifconfig / IP command)

Step 1: To display status of all active network interfaces.

ifconfig (or) ip addr show

```
itsatul@itsatul-VirtualBox:~$ ip addr show
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:34:8c:be brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute enp0s3
        valid_lft 86230sec preferred_lft 86230sec
    inet6 fe80::be83:960e:a6cf:b0ed/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
itsatul@itsatul-VirtualBox:~$
```

Analyze and fill the following table:

ip address table:

Interface name	IP address (IPv4 / IPv6)	MAC address
lo	IPv4: 127.0.0.1/8 IPv6: 1/128	00:00:00:00:00:00
enp0s3	IPv4: 10.0.2.15/24 IPv6: fe80::be83:960e:a6cf:b0ed/64	08:00:27:34:8c:be

Step 2: To assign an IP address to an interface, use the following command. **sudo**

ifconfig interface_name 10.0.your_section.your_sno netmask 255.255.255.0 (or) sudo

ip addr add 10.0.your_section.your_sno /24 dev interface_name

```
itsatul@itsatul-VirtualBox:~$ sudo ip addr add 10.0.2.9/24 dev enp0s3
[sudo] password for itsatul:
```

Step 3: To activate / deactivate a network interface,

type. **sudo ifconfig interface_name down**

sudo ifconfig interface_name up

```
itsatul@itsatul-VirtualBox:~$ sudo ip link set enp0s3 down
itsatul@itsatul-VirtualBox:~$ sudo ip link set enp0s3 up
```

Step 4: To show the current neighbor table in kernel, type

ip neigh

```
itsatul@itsatul-VirtualBox:~$ ip neigh
10.0.2.2 dev enp0s3 lladdr 52:54:00:12:35:02 REACHABLE
itsatul@itsatul-VirtualBox:~$
```

Task 2: Ping PDU (Packet Data Units or Packets) Capture


Step 1: Assign an IP address to the system (Host).

Note: IP address of your system should be 10.0.your_section.your_sno.

Step 2: Launch Wireshark and select 'any' interface

Step 3: In terminal, type **ping 10.0.your_section.your_sno**

```
itsatul@itsatul-VirtualBox:~$ ping 10.0.2.9
PING 10.0.2.9 (10.0.2.9) 56(84) bytes of data.
64 bytes from 10.0.2.9: icmp_seq=1 ttl=64 time=0.038 ms
64 bytes from 10.0.2.9: icmp_seq=2 ttl=64 time=0.053 ms
64 bytes from 10.0.2.9: icmp_seq=3 ttl=64 time=0.052 ms
64 bytes from 10.0.2.9: icmp_seq=4 ttl=64 time=0.050 ms
64 bytes from 10.0.2.9: icmp_seq=5 ttl=64 time=0.060 ms
^C
--- 10.0.2.9 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4112ms
rtt min/avg/max/mdev = 0.038/0.050/0.060/0.007 ms
itsatul@itsatul-VirtualBox:~$
```



Observations to be made

Step 4: Analyze the following in Terminal

- TTL - 64
- Protocol used by ping - ICMP
- Time – 4112 ms

Step 5: Analyze the following in Wireshark

On Packet List Pane, select the first echo packet on the list. On Packet Details Pane, click on each of the four “+” to expand the information. Analyze the frames with the first echo request and echo reply and complete the table below.

Details	First Echo Request	First Echo Reply
Frame Number	1	2
Source IP address	10.0.2.15	10.0.2.9
Destination IP address	10.0.2.9	10.0.2.15
ICMP Type Value	8	0
ICMP Code Value	0	0
Source Ethernet Address	00:00:00:00:00:00	00:00:00:00:00:00
Destination Ethernet Address	00:00:00:00:00:00	00:00:00:00:00:00
Internet Protocol Version	4	4
Time To Live (TTL) Value	64	64

Task 3: HTTP PDU Capture

Using Wireshark's Filter feature

Step 1: Launch Wireshark and select 'any' interface. On the Filter toolbar, type-in 'http' and press enter

Step 2: Open Firefox browser, and browse www.flipkart.com

Observations to be made

Step 3: Analyze the first (interaction of host to the web server) and second frame (response of server to the client). By analyzing the filtered frames, complete the table below:

Details	First Echo Request	First Echo Reply
Frame Number	39	41
Source Port	57846	80
Destination Port	80	57846
Source IP address	10.0.2.15	163.53.78.110
Destination IP address	163.53.78.110	10.0.2.15
Source Ethernet Address	PesCompu_34:8c:be (08:00:27:34:8c:be)	RealtekU_12:35:02 (52:54:00:12:35:02)
Destination Ethernet Address	RealtekU_12:35:02 (52:54:00:12:35:02)	PesCompu_34:8c:be (08:00:27:34:8c:be)

No.	Time	Source	Destination	Protocol	Length	Info
39	10.489828161	10.0.2.15	163.53.78.110	HTTP	391	GET / HTTP/1.1
41	10.572470522	163.53.78.110	10.0.2.15	HTTP	403	HTTP/1.1 301 Moved Permanently (text/html)
67	10.881950612	10.0.2.15	192.124.249.41	OCSP	427	Request
69	11.461283235	192.124.249.41	10.0.2.15	OCSP	2344	Response
1059	13.741496943	10.0.2.15	192.124.249.41	OCSP	426	Request
1075	13.852713213	192.124.249.41	10.0.2.15	OCSP	2343	Response
1077	13.855638757	10.0.2.15	192.124.249.41	OCSP	426	Request
1109	14.008057386	10.0.2.15	117.18.237.29	OCSP	435	[TCP Previous segment not captured] Request
1116	14.078725528	117.18.237.29	10.0.2.15	OCSP	855	Response
1120	14.082732209	10.0.2.15	117.18.237.29	OCSP	435	Request
1143	14.155850048	117.18.237.29	10.0.2.15	OCSP	854	Response
1276	14.434291236	192.124.249.41	10.0.2.15	OCSP	1043	Response
1297	14.531288321	10.0.2.15	192.124.249.41	OCSP	427	Request
1305	14.545504363	10.0.2.15	192.124.249.41	OCSP	427	Request
1318	14.632868602	192.124.249.41	10.0.2.15	OCSP	1044	Response
1378	15.013124849	192.124.249.41	10.0.2.15	OCSP	2344	Response
1425	15.728289477	163.53.78.110	10.0.2.15	HTTP	263	HTTP/1.1 400 Bad request (text/html)

Frame 39: 391 bytes on wire (3128 bits), 391 bytes captured (3128 bits) on interface any, id 0

Linux cooked capture

Internet Protocol Version 4, Src: 10.0.2.15, Dst: 163.53.78.110

Transmission Control Protocol, Src Port: 57846, Dst Port: 80, Seq: 1, Ack: 1, Len: 335

Hypertext Transfer Protocol

GET / HTTP/1.1\r\nHost: www.flipkart.com\r\nUser-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:75.0) Gecko/20100101 Firefox/75.0\r\nAccept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8\r\nAccept-Language: en-US,en;q=0.5\r\nAccept-Encoding: gzip, deflate\r\nConnection: keep-alive\r\nUpgrade-Insecure-Requests: 1\r\n\r\n[Full request URI: http://www.flipkart.com/]
[HTTP request 1/1]
[Response in frame: 41]

Step 4: Analyze the HTTP request and response and complete the table below.

HTTP Request		HTTP Response	
Get	GET/HTTP/1.1	Server	nginx
Host	www.flipkart.com	Content-Type	text/html
User-Agent	Mozilla/5.0	Date	Wed, 27 Jan 2021
Accept-Language	en-US	Location	https://www.flipkart.com/
Accept-Encoding	gzip	Content-Length	178
Connection	keep-alive	Connection	

Using Wireshark's Follow TCP Stream

Step 1: Make sure the filter is blank. Right-click any packet inside the Packet List Pane, then select 'Follow TCP Stream'. For demo purpose, a packet containing the HTTP GET request "GET / HTTP / 1.1" can be selected.

Step 2: Upon following a TCP stream, screenshot the whole window.



```
Wireshark · Follow TCP Stream (tcp.stream eq 12) · any

GET / HTTP/1.1
Host: www.flipkart.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:75.0) Gecko/20100101 Firefox/75.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Upgrade-Insecure-Requests: 1

HTTP/1.1 301 Moved Permanently
Server: nginx
Date: Wed, 27 Jan 2021 15:45:06 GMT
Content-Type: text/html
Content-Length: 178
Location: https://www.flipkart.com/

<html>
<head><title>301 Moved Permanently</title></head>
<body bgcolor="white">
<center><h1>301 Moved Permanently</h1></center>
<hr><center>nginx</center>
</body>
</html>
```

Task 4: Capturing packets with tcpdump

Step 1: Use the command **tcpdump -D** to see which interfaces are available for capture.

sudo tcpdump -D

```
itsatul@itsatul-VirtualBox:~$ sudo tcpdump -D
[sudo] password for itsatul:
1.enp0s3 [Up, Running]
2.lo [Up, Running, Loopback]
3.any (Pseudo-device that captures on all interfaces) [Up, Running]
4.bluetooth-monitor (Bluetooth Linux Monitor) [none]
5.nflog (Linux netfilter log (NFLOG) interface) [none]
6.nfqueue (Linux netfilter queue (NFQUEUE) interface) [none]
itsatul@itsatul-VirtualBox:~$
```

Step 2: Capture all packets in any interface by running this command:

sudo tcpdump -i any

Note: Perform some pinging operation while giving above command. Also type www.google.com in browser.

```
itsatul@itsatul-VirtualBox:~$ ping -c 3 google.com & sudo tcpdump -i any
[1] 3821
PING google.com (142.250.183.14) 56(84) bytes of data.
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on any, link-type LINUX_SLL (Linux cooked v1), capture size 262144 bytes
64 bytes from bom07s30-in-f14.1e100.net (142.250.183.14): icmp_seq=1 ttl=115 time=71.7 ms
22:06:52.232456 IP bom07s30-in-f14.1e100.net > itsatul-VirtualBox: ICMP echo reply, id 5, seq 1, length 64
22:06:52.232719 IP localhost.57410 > localhost.domain: 44833+ [1au] PTR? 14.183.250.142.in-addr.arpa. (56)
22:06:52.232941 IP localhost.domain > localhost.57410: 44833 1/0/1 PTR bom07s30-in-f14.1e100.net. (95)
22:06:52.233084 IP localhost.40848 > localhost.domain: 60763+ [1au] PTR? 15.2.0.10.in-addr.arpa. (51)
22:06:52.233302 IP itsatul-VirtualBox.42403 > 192.168.43.1.domain: 46404+ [1au] PTR? 15.2.0.10.in-addr.arpa. (51)
22:06:52.242439 IP localhost.55762 > localhost.domain: 60769+ [1au] PTR? 53.0.0.127.in-addr.arpa. (52)
22:06:52.242840 IP localhost.34878 > localhost.domain: 10303+ [1au] PTR? 1.43.168.192.in-addr.arpa. (54)
22:06:52.242977 IP itsatul-VirtualBox.38015 > 192.168.43.1.domain: 23220+ [1au] PTR? 1.43.168.192.in-addr.arpa. (54)
22:06:52.246541 IP 192.168.43.1.domain > itsatul-VirtualBox.38015: 23220 NXDomain 0/0/0 (43)
22:06:52.246723 IP itsatul-VirtualBox.38015 > 192.168.43.1.domain: 23220+ PTR? 1.43.168.192.in-addr.arpa. (43)
22:06:53.162728 IP itsatul-VirtualBox > bom07s30-in-f14.1e100.net: ICMP echo request, id 5, seq 2, length 64
22:06:53.230934 IP bom07s30-in-f14.1e100.net > itsatul-VirtualBox: ICMP echo reply, id 5, seq 2, length 64
64 bytes from bom07s30-in-f14.1e100.net (142.250.183.14): icmp_seq=2 ttl=115 time=68.2 ms
22:06:54.164802 IP itsatul-VirtualBox > bom07s30-in-f14.1e100.net: ICMP echo request, id 5, seq 3, length 64
22:06:54.250534 IP bom07s30-in-f14.1e100.net > itsatul-VirtualBox: ICMP echo reply, id 5, seq 3, length 64
64 bytes from bom07s30-in-f14.1e100.net (142.250.183.14): icmp_seq=3 ttl=115 time=86.6 ms

--- google.com ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2003ms
rtt min/avg/max/ndev = 68.234/75.498/86.562/7.950 ms
22:06:58.983658 IP itsatul-VirtualBox.56624 > bom12s07-in-f4.1e100.net.https: Flags [P.], seq 2650825436:2650825627, ack 400385163, win 64028, length 191
22:06:58.983878 IP localhost.58524 > localhost.domain: 10428+ [1au] PTR? 164.67.250.142.in-addr.arpa. (56)
22:06:58.983956 IP bom12s07-in-f4.1e100.net.https > itsatul-VirtualBox.56624: Flags [.], ack 191, win 65535, length 0
22:06:58.984133 IP localhost.domain > localhost.58524: 10428 1/0/1 PTR bom12s07-in-f4.1e100.net. (94)
22:06:58.984435 IP itsatul-VirtualBox.56624 > bom12s07-in-f4.1e100.net.https: Flags [P.], seq 191:222, ack 1, win 64028, length 31
22:06:58.984619 IP bom12s07-in-f4.1e100.net.https > itsatul-VirtualBox.56624: Flags [.], ack 222, win 65535, length 0
22:06:59.148846 IP bom12s07-in-f4.1e100.net.https > itsatul-VirtualBox.56624: Flags [P.], seq 1:95, ack 222, win 65535, length 94
22:06:59.149061 IP bom12s07-in-f4.1e100.net.https > itsatul-VirtualBox.56624: Flags [P.], seq 95:134, ack 222, win 65535, length 39
22:06:59.149427 IP itsatul-VirtualBox.56624 > bom12s07-in-f4.1e100.net.https: Flags [.], ack 134, win 64028, length 0
22:06:59.151402 IP itsatul-VirtualBox.56624 > bom12s07-in-f4.1e100.net.https: Flags [P.], seq 222:261, ack 134, win 64028, length 39
22:06:59.151759 IP bom12s07-in-f4.1e100.net.https > itsatul-VirtualBox.56624: Flags [.], ack 261, win 65535, length 0
```

Observation

Step 3: Understand the output format.

Step 4: To filter packets based on protocol, specifying the protocol in the command line. For example, capture ICMP packets only by using this command:

sudo tcpdump -i any -c5 icmp

```
itsatul@itsatul-VirtualBox:~$ sudo tcpdump -i any -c5 icmp
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on any, link-type LINUX_SLL (Linux cooked v1), capture size 262144 bytes
```

Step 5: Check the packet content. For example, inspect the HTTP content of a web request like this:

sudo tcpdump -i any -c10 -nn -A port 80

```
itsatul@itsatul-VirtualBox:~$ sudo tcpdump -i any -c10 -nn -A port 80
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on any, link-type LINUX_SLL (Linux cooked v1), capture size 262144 bytes
22:15:27.366390 IP 10.0.2.15.39522 > 172.217.166.35.80: Flags [.], ack 456256704, win 63882, length 0
E..(.1@.@.W.
.....#.b.Pm.:S.1..P..._&..
22:15:27.366625 IP 172.217.166.35.80 > 10.0.2.15.39522: Flags [.], ack 1, win 65535, length 0
E..(.;..@.....#
...P.b.1..m.:TP.....
22:15:30.727776 IP 10.0.2.15.39522 > 172.217.166.35.80: Flags [F.], seq 1, ack 1, win 63882, length 0
E..(.2@.@.W.
.....#.b.Pm.:T.1..P..._&..
22:15:30.728199 IP 172.217.166.35.80 > 10.0.2.15.39522: Flags [.], ack 2, win 65535, length 0
E..(.<..@.....#
...P.b.1..m.:UP.....
22:15:30.804984 IP 172.217.166.35.80 > 10.0.2.15.39522: Flags [F.], seq 1, ack 2, win 65535, length 0
E..(.=.@.....#
...P.b.1..m.:UP.....
22:15:30.805040 IP 10.0.2.15.39522 > 172.217.166.35.80: Flags [.], ack 2, win 63882, length 0
E..(..@.@...
.....#.b.Pm.:U.1..P....;..
^C
6 packets captured
6 packets received by filter
0 packets dropped by kernel
itsatul@itsatul-VirtualBox:~$
```

Step 6: To save packets to a file instead of displaying them on screen, use the option -w:

sudo tcpdump -i any -c10 -nn -w webserver.pcap port 80

```
itsatul@itsatul-VirtualBox:~$ sudo tcpdump -i any -c10 -nn -w webserver.pcap port 80
tcpdump: listening on any, link-type LINUX_SLL (Linux cooked v1), capture size 262144 bytes
10 packets captured
14 packets received by filter
0 packets dropped by kernel
```


Task 5: Perform Traceroute checks

Step 1: Run the traceroute using the following command.

sudo traceroute www.google.com

```
itsatul@itsatul-VirtualBox:~$ sudo traceroute www.google.com
traceroute to www.google.com (142.250.183.132), 30 hops max, 60 byte packets
 1  _gateway (10.0.2.2)  0.660 ms  0.645 ms  0.637 ms
 2  * * *
 3  * * *
```

Step 2: Analyze destination address of google.com and no. of hops

The destination address is **142.250.183.132** and there were **30 hops**.

Step 3: To speed up the process, you can disable the mapping of IP addresses with hostnames by using the **-n** option

sudo traceroute -n www.google.com

```
itsatul@itsatul-VirtualBox:~$ sudo traceroute -n www.google.com
traceroute to www.google.com (142.250.77.36), 30 hops max, 60 byte packets
 1  10.0.2.2  0.400 ms  0.381 ms  0.370 ms
 2  * * *
```

Step 4: The **-I** option is necessary so that the traceroute uses ICMP.

sudo traceroute -I www.google.com

```
itsatul@itsatul-VirtualBox:~$ sudo traceroute -I www.google.com
traceroute to www.google.com (142.250.77.36), 30 hops max, 60 byte packets
 1  _gateway (10.0.2.2)  0.578 ms  0.571 ms  0.566 ms
 2  192.168.43.1 (192.168.43.1)  4.714 ms  4.730 ms  4.727 ms
 3  * * *
 4  10.50.110.121 (10.50.110.121)  56.955 ms  58.225 ms  58.248 ms
 5  10.50.140.102 (10.50.140.102)  54.264 ms  54.232 ms  54.243 ms
 6  aes-static-102.109.144.59.airtel.in (59.144.109.102)  52.826 ms  41.165 ms  41.070 ms
 7  * * 182.79.189.55 (182.79.189.55)  67.115 ms
 8  72.14.212.48 (72.14.212.48)  68.124 ms  60.018 ms  79.014 ms
 9  209.85.246.11 (209.85.246.11)  183.445 ms  181.890 ms  183.116 ms
10  142.250.238.203 (142.250.238.203)  183.107 ms  180.456 ms  179.202 ms
11  bom07s26-in-f4.1e100.net (142.250.77.36)  179.167 ms  150.261 ms  149.221 ms
```

Step 5: By default, traceroute uses icmp (ping) packets. If you'd rather test a TCP connection to gather data more relevant to web server, you can use the **-T** flag.

sudo traceroute -T www.google.com

```
itsatul@itsatul-VirtualBox:~$ sudo traceroute -T www.google.com
traceroute to www.google.com (142.250.77.36), 30 hops max, 60 byte packets
 1  _gateway (10.0.2.2)  0.516 ms  0.409 ms  0.392 ms
 2  bom07s26-in-f4.1e100.net (142.250.77.36)  80.054 ms  76.355 ms  77.457 ms
```

Task 6: Explore an entire network for information (Nmap)

Step 1: You can scan a host using its host name or IP address, for instance.

nmap www.pes.edu

```
itsatul@itsatul-VirtualBox:~$ nmap www.pes.edu
Starting Nmap 7.80 ( https://nmap.org ) at 2021-01-27 22:30 IST
Nmap scan report for www.pes.edu (13.71.123.138)
Host is up (0.082s latency).
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https

Nmap done: 1 IP address (1 host up) scanned in 19.68 seconds
itsatul@itsatul-VirtualBox:~$
```

Step 2: Alternatively, use an IP address to scan.

nmap 163.53.78.128

```
itsatul@itsatul-VirtualBox:~$ nmap 163.53.78.128
Starting Nmap 7.80 ( https://nmap.org ) at 2021-01-27 22:31 IST
Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn
Nmap done: 1 IP address (0 hosts up) scanned in 3.04 seconds
```

Step 3: Scan multiple IP address or subnet (IPv4) **nmap 192.168.1.1 192.168.1.2**

192.168.1.3

```
itsatul@itsatul-VirtualBox:~$ nmap 192.168.1.1 192.168.1.2 192.168.1.3
Starting Nmap 7.80 ( https://nmap.org ) at 2021-01-27 22:32 IST
Nmap done: 3 IP addresses (0 hosts up) scanned in 3.11 seconds
itsatul@itsatul-VirtualBox:~$
```