


BLIND BOX

The PARVEEN Blind Box is used when heavy downward jarring is required to dislodge a fish or push down an obstruction encountered in the tubing string.

BLIND BOX						
O.D. Range (in) *	F/N O.D. (in)	Top Connection	Part No.			
1.187 - 1.250	1.187	15/16 - 10 UN	221211			
1.625 - 1.375	1.375	15/16 - 10 UN	222221			
2.625 - 2.750	1.750	1-1/16 - 10 UN	222732			
3.500 - 4.625	2.312	1-9/16 - 10 UN	224646			
5.250 - 5.750	2.312	1-9/16 - 10 UN	225746			




^{*} Blind Boxes are also available in MM. increments within the specified O.D. ranges.

TUBING END LOCATOR

The PARVEEN Tubing End Locator is used to locate the end of the tubing. With its spring loaded finger, it can be run in various sizes of tubing ranging from 2-3/8" to 4-1/2".

TUBING END LOCATOR							
Size	Max O.D.	F/N O.D.	Top Conn.	Bottom Conn.	Part No.		
(in)	(in)*	(in)	Pin	Box			
2, 2-1/2	1.750	1.375	15/16 - 10 UN	1 - 11.1/2 NPT	421721		
3	2.500	1.375	15/16 - 10 UN	1 - 11.1/2 NPT	422521		
4	3.750	2.312	1-9/16 - 10 UN	1 - 11.1/2 NPT	423746		

^{*} O.D. With Finger Sheared



TUBING END LOCATOR