


## **LUBRICATOR RISERS**


PARVEEN Lubricator Risers are used to allow the wireline tool string to be raised above the wellhead valve prior to and after wireline operations and enable the wellhead valve to be opened and closed allowing entry and exit of the toolstring from the well bore.

An 'O' ring on the pin section forms the seal when made up into the box. The internal thread on the collar matches the external thread on box and makes up quickly by hand.

PARVEEN Lubricator Risers are available in standard lengths from 4 feet through 12 feet, and 2-1/2" through 6.38" bores. Standard end connections include a union box up and union pin and collar (nut) down. Bleed off valves are available in all models upon request. Working pressure ranges for these risers are from 5,000 PSI through 15,000 PSI.

PARVEEN also supplies **Light Weight Risers** in low alloy steel and 28 chrome stainless steel. Integral designs are also available for high pressures up to 15,000 PSI.





LUBRICATOR RISERS						
			Part No.			
Service	I.D. in.	W.P. (PSI)	4 Feet	6 Feet	8 Feet	10 Feet
STD	2.50	5,000	042553X1	042555X1	042557X1	042559X1
STS	3.00	5,000	043553X1	043555X1	043557X11	0435591X1
STD	2.50	10,000	042152X1	042155X1	042157X1	042159X1
STD	3.00	10,000	043153X1	043155X1	043157X1	043159X1
H2S	2.50	5,000	042553X0	042555X0	042557X0	042559X0
H2S	3.00	5,000	0423553X0	043555X0	043557X0	043559X0
H2S	2.50	10,000	042153X0	042155X0	042157X0	042159X0
H2S	3.00	10,000	043153X0	043155X0	043157X0	043159X0
STD	2.50	15,000	042453X1	042455X1	042457X1	042459X1
H2S	2.50	15,000	042453X0	042455X0	042457X0	042459X0
H2S	3.00	15,000	043453X0	043455X0	043457X0	043459X0
STD	4.00	5,000	044553X1	044555X1	044557X1	044559X1
H2S	4.00	5,000	044553X0	044555X0	044557X0	044559X0
STD	4.00	10,000	044153X1	044153X1	044157X1	044159X1
H2S	4.00	10,000	044153X0	044155X0	044157X0	044159X0
H2S	4.00	15,000	044453X0	044455X0	044457X0	044459X0
STD	5.00	5,000	045553X1	045555X1	045557X1	045559X1
STD	5.00	10,000	045153X1	045155X1	045157X1	045159X1
H2S	5.00	5,000	045553X0	045555X0	045557X0	045559X0
H2S	5.00	10,000	045153X0	045155X0	045157X0	045159X0
STD	6.38	5,000	049553X1	049555X1	049557X1	049559X1
H2S	6.38	5,000	049553X0	049555X0	049557X0	049559X0
H2S	6.38	10,000	049153X0	049155X0	049157X0	049159X0

## Notes:

- \* Other sizes available on request
- \* Refer to the Quick Union identification chart on page no. 16 & 17 for end connections.