


FLANGED STUDDED CROSSES AND TEES (AS PER API-6A)

*All dimensions are in inches.


(1-1) PI	(1-1) PRESSURE RATING:- 2000 PSI			
NOMINAL S	IZE & BORE	CENTER TO FACE		
Ød1	Ød2	H2	H1	
(VERTICAL)	(OUTLET)	(VERTICAL)	(HORIZONTAL)	
2 1/16	2 1/16	3.50	3.50	
2 9/16	2 1/16	3.50	4.00	
2 9/16	2 9/16	4.50	4.50	
3 1/8	2 1/16	3.50	4.50	
3 1/8	2 9/16	4.50	4.50	
3 1/8	3 1/8	4.50	4.50	
4 1/16	2 1/16	4.50	5.50	
4 1/16	2 9/16	4.50	5.50	
4 1/16	3 1/8	4.50	5.50	
4 1/16	4 1/16	5.50	5.50	

(1-2) PRESSURE RATING:- 3000 PSI			
NOMINAL SIZE & BORE		CENTER TO FACE	
Ød1	Ød2	H2 H1	
(VERTICAL)	(OUTLET)	(VERTICAL)	(HORIZONTAL)
3 1/8	2 1/16	4.50	5.00
3 1/8	2 9/16	5.00	5.00
3 1/8	3 1/8	5.00	5.00
4 1/16	2 1/16	4.50	6.12
4 1/16	2 9/16	5.00	6.12
4 1/16	3 1/8	5.00	6.12
4 1/16	4 1/16	6.12	6.12

(4.2) DDESSUDE DATING: 5000 DSI				
(1-3) PRESSURE RATING:- 5000 PSI				
NOMINAL SIZE & BORE		CENTER TO FACE		
Ød1	Ød2	H2	H1	
(VERTICAL)	(OUTLET)	(VERTICAL)	(HORIZONTAL)	
2 1/16	2 1/16	4.50	4.50	
2 9/16	2 1/16	4.50	5.00	
2 9/16	2 9/16	5.00	5.00	
3 1/8	2 1/16	4.50	5.50	
3 1/8	2 9/16	5.50	5.50	
3 1/8	3 1/8	5.50	5.50	
4 1/16	2 1/16	4.50	6.50	
4 1/16	2 9/16	5.00	6.50	
4 1/16	3 1/8	5.50	6.50	
4 1/16	4 1/16	6.50	6.50	



API Studded Tee



API Studded Cross

(1-4) PRESSURE RATING:- 10000 PSI				
NOMINAL SIZE & BORE		CENTER TO FACE		
Ød1	Ød2	H2	H1	
(VERTICAL)	(OUTLET)	(VERTICAL)	(HORIZONTAL)	
1 13/16	1 13/16	4.38	4.38	
2 1/16	1 13/16	4.38	4.38	
2 1/16	2 1/16	4.38	4.38	
2 9/16	1 13/16	4.50	5.12	
2 9/16	2 1/16	4.50	5.12	
2 9/16	2 9/16	5.12	5.12	
3 1/16	1 13/16	4.50	5.88	
3 1/16	2 1/16	4.50	5.88	
3 1/16	2 9/16	5.12	5.88	
3 1/16	3 1/16	5.88	5.88	
4 1/16	1 13/16	4.50	6.88	
4 1/16	2 1/16	4.50	6.88	
4 1/16	2 9/16	5.12	6.88	
4 1/16	3 1/16	5.88	6.88	
4 1/16	4 1/16	6.88	6.88	

(1-5) PRESSURE RATING:- 15000 PSI				
NOMINAL SIZE & BORE		CENTER TO FACE		
Ød1	Ød2	H2	H1	
(VERTICAL)	(OUTLET)	(VERTICAL)	(HORIZONTAL)	
1 13/16	1 13/16	5.00	5.00	
2 1/16	1 13/16	5.00	5.00	
2 1/16	2 1/16	5.00	5.00	
2 9/16	1 13/16	5.50	5.50	
2 9/16	2 1/16	5.50	5.50	
2 9/16	2 9/16	5.50	5.50	
3 1/16	1 13/16	6.31	6.31	
3 1/16	2 1/16	6.31	6.31	
3 1/16	2 9/16	6.31	6.31	
3 1/16	3 1/16	6.31	6.31	
4 1/16	1 13/16	7.62	7.62	
4 1/16	2 1/16	7.62	7.62	
4 1/16	2 9/16	7.62	7.62	
4 1/16	3 1/16	7.62	7.62	
4 1/16	4 1/16	7.62	7.62	

(1-6) PRESSURE RATING:- 20000 PSI			
NOMINAL SIZE & BORE		CENTER TO FACE	
Ød1	Ød2	H2	H1
(VERTICAL)	(OUTLET)	(VERTICAL)	(HORIZONTAL)
1 13/16	1 13/16	6.47	6.47
2 1/16	1 13/16	6.47	6.47
2 1/16	2 1/16	6.47	6.47
2 9/16	1 13/16	7.28	7.28
2 9/16	2 1/16	7.28	7.28
2 9/16	2 9/16	7.28	7.28
3 1/16	1 13/16	7.97	7.97
3 1/16	2 1/16	7.97	7.97
3 1/16	2 9/16	7.97	7.97
3 1/16	3 1/16	7.97	7.97
4 1/16	1 13/16	9.97	9.91
4 1/16	2 1/16	9.91	9.91
4 1/16	2 9/16	9.91	9.91
4 1/16	3 1/16	9.91	9.91
4 1/16	4 1/16	9.91	9.91