

# Notebook que incluye interact

## Preprocesamiento

```
In [1]: import os
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

from pathlib import Path

from tensorflow.keras.models import load_model, Model
from tensorflow.keras import layers
from matplotlib.lines import Line2D
from sklearn.decomposition import PCA, KernelPCA
from sklearn.manifold import TSNE
from sklearn.preprocessing import StandardScaler
from sklearn.cluster import KMeans, DBSCAN, SpectralClustering
from sklearn.metrics import silhouette_score

from ipywidgets import interact, widgets

import seaborn as sns
from sklearn.metrics.cluster import contingency_matrix
```

```
In [2]: project_dir = Path().resolve().parent

model_path = os.path.join(project_dir, r"models\model_4C_3FC.h5")
data_path = os.path.join(project_dir, r"data\raw\sdss_dat_files")
labels_path = os.path.join(project_dir, r"data\raw\label_data")

print(project_dir)
print(model_path)
print(data_path)
print(labels_path)
```

```
C:\Users\javip\OneDrive - Universidad Técnica Federico Santa María\6to año\elo308\ML_NPF
C:\Users\javip\OneDrive - Universidad Técnica Federico Santa María\6to año\elo308\ML_NPF\models\model_4C_3FC.h5
C:\Users\javip\OneDrive - Universidad Técnica Federico Santa María\6to año\elo308\ML_NPF\data\raw\sdss_dat_files
C:\Users\javip\OneDrive - Universidad Técnica Federico Santa María\6to año\elo308\ML_NPF\data\raw\label_data
```

## Función process\_spectrum

```
In [3]: def process_spectrum(file_path):
        try:
```

```

sed = np.loadtxt(file_path, unpack=True)
flux = sed[1, 48:-400] # 4200 puntos

# Ajuste a 3750 puntos, como espera la red
if len(flux) > 3750:
    diff = len(flux) - 3750
    start = diff // 2
    flux = flux[start:start + 3750]
elif len(flux) < 3750:
    flux = np.pad(flux, (0, 3750 - len(flux)), mode='constant')

norm_val = flux[2100]
if norm_val == 0 or np.isnan(norm_val):
    norm_val = np.mean(flux)

if norm_val == 0 or np.isnan(norm_val):
    return None

flux = flux / norm_val

if np.isnan(flux).any():
    return None

return flux.astype(np.float32)

except Exception:
    return None

```

```

In [4]: fields = ['File Name', 'MJD', 'Target ID', 'DB ID', 'Classification', 'Data Quality']
raw_labels_df = pd.DataFrame()

for filename in os.listdir(labels_path):
    if filename.endswith('.csv'):
        file_path = os.path.join(labels_path, filename)
        df = pd.read_csv(file_path, usecols=fields)
        raw_labels_df = pd.concat([raw_labels_df, df], ignore_index=True)

print(raw_labels_df.shape)
print(raw_labels_df['Classification'].value_counts().head(20))

```

```
(35253, 6)
Classification
WDA      13748
STAR     8749
WD+MS    2555
DUNNO    2086
UNCLASS  1441
WDC      1353
WDB      1186
WDELM    1069
sdX      744
WD        743
WDZ      383
CV        356
EXGAL    301
WDH      272
WDO      184
WDQ       81
WELM      1
DA        1
Name: count, dtype: int64
```

```
In [5]: raw_labels_df
```

Out[5]:

|              | Classification | DB ID | Data Quality | File Name                              | MJD   | Target ID  |
|--------------|----------------|-------|--------------|----------------------------------------|-------|------------|
| <b>0</b>     | WDA            | 21899 | NaN          | spec-15249-59265-04601916346-21899.png | 59265 | 4601916346 |
| <b>1</b>     | sdX            | 23360 | BLEND        | spec-15301-59338-04602344336-23360.png | 59338 | 4602344336 |
| <b>2</b>     | WDA            | 18900 | SNR          | spec-15113-59217-04538755416-18900.png | 59217 | 4538755416 |
| <b>3</b>     | WDA            | 18575 | NaN          | spec-15086-59267-04474143209-18575.png | 59267 | 4474143209 |
| <b>4</b>     | WD             | 20528 | SNR          | spec-15198-59269-04351438385-20528.png | 59269 | 4351438385 |
| ...          | ...            | ...   | ...          | ...                                    | ...   | ...        |
| <b>35248</b> | WDA            | 15895 | SNR          | spec-15011-59222-04399876473-15895.png | 59222 | 4399876473 |
| <b>35249</b> | WDA            | 20605 | NaN          | spec-15200-59324-04589320996-20605.png | 59324 | 4589320996 |
| <b>35250</b> | WDA            | 19388 | NaN          | spec-15193-59243-04594923329-19388.png | 59243 | 4594923329 |
| <b>35251</b> | DUNNO          | 19161 | SNR          | spec-15121-59212-04342114705-19161.png | 59212 | 4342114705 |
| <b>35252</b> | WDB            | 24506 | FC           | spec-15336-59294-04524328661-24506.png | 59294 | 4524328661 |

35253 rows × 6 columns

```
In [6]: file_dict = {}

for folder in os.listdir(data_path):
    folder_full_path = os.path.join(data_path, folder)
    if os.path.isdir(folder_full_path):
        for filename in os.listdir(folder_full_path):
            if filename.endswith('.dat'):
                key = filename.split('-')[-2] + '_' + filename.split('_')[-1]
                file_dict[key] = os.path.join(folder, filename)

print(f"Archivos .dat indexados: {len(file_dict)}")
```

Archivos .dat indexados: 33698

```
In [7]: full_model = load_model(model_path)

dummy_input = np.zeros((1, 3750, 1), dtype=np.float32)
_ = full_model.predict(dummy_input, verbose=0)

full_model.summary()
```



```
c:\Users\javip\OneDrive - Universidad Técnica Federico Santa María\6to año\elo308\ML_NPF\.venv\lib\site-packages\keras\src\layers\convolutional\base_conv.py:113: UserWarning: Do not pass an `input_shape`/`input_dim` argument to a layer. When using Sequential models, prefer using an `Input(shape)` object as the first layer in the model instead.
```

```
super().__init__(activity_regularizer=activity_regularizer, **kwargs)
c:\Users\javip\OneDrive - Universidad Técnica Federico Santa María\6to año\elo308\ML_NPF\.venv\lib\site-packages\keras\src\optimizers\base_optimizer.py:86: UserWarning: Argument `decay` is no longer supported and will be ignored.
```

```
warnings.warn(
WARNING:absl:Compiled the loaded model, but the compiled metrics have yet to be built. `model.compile_metrics` will be empty until you train or evaluate the model.
WARNING:absl>Error in loading the saved optimizer state. As a result, your model is starting with a freshly initialized optimizer.
```

Model: "sequential"

| Layer (type)                   | Output Shape      | Param # |
|--------------------------------|-------------------|---------|
| conv1d (Conv1D)                | (None, 1874, 128) | 640     |
| max_pooling1d (MaxPooling1D)   | (None, 937, 128)  | 0       |
| conv1d_1 (Conv1D)              | (None, 467, 64)   | 32,832  |
| max_pooling1d_1 (MaxPooling1D) | (None, 233, 64)   | 0       |
| conv1d_2 (Conv1D)              | (None, 115, 32)   | 8,224   |
| max_pooling1d_2 (MaxPooling1D) | (None, 57, 32)    | 0       |
| conv1d_3 (Conv1D)              | (None, 27, 16)    | 2,064   |
| max_pooling1d_3 (MaxPooling1D) | (None, 13, 16)    | 0       |
| flatten (Flatten)              | (None, 208)       | 0       |
| dense (Dense)                  | (None, 128)       | 26,752  |
| dropout (Dropout)              | (None, 128)       | 0       |
| dense_1 (Dense)                | (None, 64)        | 8,256   |
| dropout_1 (Dropout)            | (None, 64)        | 0       |
| dense_2 (Dense)                | (None, 32)        | 2,080   |
| dense_3 (Dense)                | (None, 12)        | 396     |

Total params: 81,246 (317.37 KB)

Trainable params: 81,244 (317.36 KB)

Non-trainable params: 0 (0.00 B)

Optimizer params: 2 (12.00 B)

## Construir extractores de capas

```
In [8]: def build_extractor_until(layer_name, full_model):
    input_layer = layers.Input(shape=(3750, 1))
    x = input_layer

    for layer in full_model.layers:
        x = layer(x)
        if layer.name == layer_name:
            break

    extractor = Model(inputs=input_layer, outputs=x)
    return extractor

flatten_extractor = build_extractor_until("flatten", full_model)
dense_extractor = build_extractor_until("dense", full_model)
dense1_extractor = build_extractor_until("dense_1", full_model)
dense2_extractor = build_extractor_until("dense_2", full_model)

print("extrat listos")
```

extrat listos

```
In [9]: def build_class_dataframe(class_name):
    star_df = raw_labels_df[raw_labels_df['Classification'] == class_name].copy()

    spectrum_list = []
    for _, row in star_df.iterrows():
        filekey = str(row['MJD']) + '_' + str(row['Target ID']) + '.dat'
        if filekey in file_dict:
            spectrum_list.append({
                'filename': file_dict[filekey],
                'classID': row['Classification']
            })

    spectrum_df = pd.DataFrame(spectrum_list)
    return spectrum_df
```

```
In [10]: # fc que carga espectros de una clase, los preprocesa y los deja listo para entrar
def load_class_spectra(class_name, n_samples=1100, random_state=42):
    spectrum_df = build_class_dataframe(class_name)
    print(f"{class_name}: disponibles con match a .dat = {len(spectrum_df)}")

    if len(spectrum_df) < n_samples:
        raise ValueError(f"No hay suficientes espectros para {class_name}. Disponib

    selected_df = spectrum_df.sample(n=n_samples, random_state=random_state).reset_

    X_list = []
    valid_rows = []

    for _, row in selected_df.iterrows():
        f_path = os.path.join(data_path, row['filename'])
        spec = process_spectrum(f_path)
```

```

        if spec is not None:
            X_list.append(spec)
            valid_rows.append(row)

X_final = np.array(X_list, dtype=np.float32)
X_input = X_final.reshape((X_final.shape[0], X_final.shape[1], 1))
valid_df = pd.DataFrame(valid_rows).reset_index(drop=True)

print(f"{class_name}: espectros válidos finales = {X_input.shape[0]}")
return X_input, valid_df

```

```

In [11]: # fc que carga los espectros y los conserva en formato 2D para poder graficarlos de
# retorna X_final, que son los espectros originales preprocesados, listos para graf
def load_class_spectra_DRACULA(class_name, n_samples=1100, random_state=42):
    spectrum_df = build_class_dataframe(class_name)
    print(f"{class_name}: disponibles con match a .dat = {len(spectrum_df)}")

    if len(spectrum_df) < n_samples:
        raise ValueError(f"No hay suficientes espectros para {class_name}. Disponib

    selected_df = spectrum_df.sample(n=n_samples, random_state=random_state).reset_

    X_list = []
    valid_rows = []

    for _, row in selected_df.iterrows():
        f_path = os.path.join(data_path, row['filename'])
        spec = process_spectrum(f_path)
        if spec is not None:
            X_list.append(spec)
            valid_rows.append(row)

    X_final = np.array(X_list, dtype=np.float32)
    X_input = X_final.reshape((X_final.shape[0], X_final.shape[1], 1))
    valid_df = pd.DataFrame(valid_rows).reset_index(drop=True)

    print(f"{class_name}: espectros válidos finales = {X_input.shape[0]}")
    return X_final, X_input, valid_df

```

```

In [12]: # fc que carga espectros, conserva el flujo (eje y) normalizado y conserva el eje r
def load_class_spectra_DRACULA_with_wavelength(class_name, n_samples=1100, random_s
    spectrum_df = build_class_dataframe(class_name)
    print(f"{class_name}: disponibles con match a .dat = {len(spectrum_df)}")

    if len(spectrum_df) < n_samples:
        raise ValueError(f"No hay suficientes espectros para {class_name}. Disponib

    selected_df = spectrum_df.sample(n=n_samples, random_state=random_state).reset_

    wave_list = []
    flux_list = []
    valid_rows = []

    for _, row in selected_df.iterrows():
        f_path = os.path.join(data_path, row['filename'])

```

```

    wave, flux = process_spectrum_with_wavelength(f_path)

    if wave is not None and flux is not None:
        wave_list.append(wave)
        flux_list.append(flux)
        valid_rows.append(row)

W_final = np.array(wave_list, dtype=np.float32)
X_final = np.array(flux_list, dtype=np.float32)

X_input = X_final.reshape((X_final.shape[0], X_final.shape[1], 1))
valid_df = pd.DataFrame(valid_rows).reset_index(drop=True)

print(f"{class_name}: espectros válidos finales = {X_input.shape[0]}")
print(f"{class_name}: shape wavelength = {W_final.shape}")
print(f"{class_name}: shape flux = {X_final.shape}")

return W_final, X_final, X_input, valid_df

'''
Uso de esta fc -> mostrar un espectro / muestra
W_wda, X_wda_spec, X_wda_input, df_wda_DRAC = load_class_spectra_DRACULA_with_wavel
    "WDA",
    n_samples=1100,
    random_state=42
)

sample_idx = 0

plt.figure(figsize=(10, 5))
plt.plot(W_wda[sample_idx], X_wda_spec[sample_idx])
plt.xlabel("Wavelength [Å]")
plt.ylabel("Normalized flux")
plt.title(f"WDA - sample {sample_idx}")
plt.tight_layout()
plt.show()
'''

'''
Uso de esta fc -> mostrar el promedio + lo anterior
mean_wave = np.nanmean(W_wda, axis=0)
mean_flux = np.nanmean(X_wda_spec, axis=0)

plt.figure(figsize=(10, 5))
plt.plot(mean_wave, mean_flux, label="Total mean spectrum")
plt.xlabel("Wavelength [Å]")
plt.ylabel("Normalized flux")
plt.title("WDA - Total mean spectrum")
plt.legend()
plt.tight_layout()
plt.show()
'''

```

```
Out[12]: '\nUsó de esta fc -> mostrar el promedio + lo anterior\nmean_wave = np.nanmean(W_w
da, axis=0)\nmean_flux = np.nanmean(X_wda_spec, axis=0)\n\nplt.figure(figsize=(10,
5))\nplt.plot(mean_wave, mean_flux, label="Total mean spectrum")\nplt.xlabel("Wave
length [Å])\nplt.ylabel("Normalized flux")\nplt.title("WDA - Total mean spectru
m")\nplt.legend()\nplt.tight_layout()\nplt.show()\n'
```

```
In [13]: def extract_layer_features(X_input): # fc que extrae representaciones internas de L
flatten_features = flatten_extractor.predict(X_input, batch_size=64, verbose=1)
dense_features = dense_extractor.predict(X_input, batch_size=64, verbose=1)
dense1_features = dense1_extractor.predict(X_input, batch_size=64, verbose=1)
dense2_features = dense2_extractor.predict(X_input, batch_size=64, verbose=1)

print("flatten:", flatten_features.shape)
print("dense:", dense_features.shape)
print("dense_1:", dense1_features.shape)
print("dense_2:", dense2_features.shape)

return flatten_features, dense_features, dense1_features, dense2_features
```

```
In [14]: def reduce_all_to_32(flatten_features, dense_features, dense1_features, dense2_feat
flatten_32 = PCA(n_components=32, random_state=42).fit_transform(flatten_features)
dense_32 = PCA(n_components=32, random_state=42).fit_transform(dense_features)
dense1_32 = PCA(n_components=32, random_state=42).fit_transform(dense1_features)
dense2_32 = dense2_features.copy() # ya está en 32

print("flatten_32:", flatten_32.shape)
print("dense_32:", dense_32.shape)
print("dense1_32:", dense1_32.shape)
print("dense2_32:", dense2_32.shape)

return {
    "flatten": flatten_32,
    "dense": dense_32,
    "dense_1": dense1_32,
    "dense_2": dense2_32
}
```

## Funciones para graficar

```
In [15]: # fc que grafica los features_nd en 2D
def plot_internal_structure_2d(
    features_nd,
    class_name,
    layer_name,
    method="pca",
    xlim=None,
    ylim=None,
    kpca_kernel="rbf",
    kpca_gamma=None,
    kpca_degree=3,
    kpca_coef0=1,
    scale_before_pca=False,
    scale_before_tsne=False,
```

```

scale_before_kpca=True
):
    method = method.lower()

    if method == "pca":
        X_plotPCA = features_nd.copy()

        if scale_before_pca:
            X_plotPCA = StandardScaler().fit_transform(X_plotPCA)

        emb_2d = PCA(n_components=2, random_state=42).fit_transform(X_plotPCA)

    elif method == "tsne":
        X_plotTSNE = features_nd.copy()

        if scale_before_tsne:
            X_plotTSNE = StandardScaler().fit_transform(X_plotTSNE)

        emb_2d = TSNE(
            n_components=2,
            random_state=42,
            perplexity=30,
            init='pca'
        ).fit_transform(X_plotTSNE)

    elif method == "kpca":
        X_kpca = features_nd.copy()

        if scale_before_kpca:
            X_kpca = StandardScaler().fit_transform(X_kpca)

        emb_2d = KernelPCA(
            n_components=2,
            kernel=kpca_kernel,
            gamma=kpca_gamma,
            degree=kpca_degree,
            coef0=kpca_coef0
        ).fit_transform(X_kpca)

    else:
        raise ValueError("method debe ser 'pca', 'tsne' o 'kpca'")

plt.figure(figsize=(6, 5))
plt.scatter(emb_2d[:, 0], emb_2d[:, 1], s=10, alpha=0.65)

if method == "kpca":
    extra = " + scaled" if scale_before_kpca else ""
    n_samples = features_nd.shape[0]
    plt.title(f"{class_name} - {layer_name} - estructura interna (KPCA-{kpca_ke

elif method == "pca":
    extra = " + scaled" if scale_before_pca else ""
    n_samples = features_nd.shape[0]
    plt.title(f"{class_name} - {layer_name} - estructura interna (PCA{extra}, n

elif method == "tsne":

```

```

        extra = " + scaled" if scale_before_tsne else ""
        n_samples = features_nd.shape[0]
        plt.title(f"{class_name} - {layer_name} - estructura interna (TSNE{extra},

plt.xlabel("Comp. 1")
plt.ylabel("Comp. 2")

if xlim is not None:
    plt.xlim(xlim)
if ylim is not None:
    plt.ylim(ylim)

plt.tight_layout()
plt.show()

```

```

In [16]: # funcion para graficar el espectro promedio total
def plot_total_mean_spectrum(
    spectra_2d,
    title="Total mean spectrum",
    wavelength=None,
    figsize=(10, 5),
    save_path=None
):
    """
    Grafica el espectro promedio total de todas las muestras.

    Parameters
    -----
    spectra_2d : np.ndarray
        Matriz shape (n_samples, n_wavelengths)
    title : str
        Título del gráfico
    wavelength : np.ndarray or None
        Eje x. Si None, usa índice espectral
    figsize : tuple
    save_path : str or None
        Si se entrega, guarda la figura
    """

    spectra_2d = np.asarray(spectra_2d)

    if spectra_2d.ndim != 2:
        raise ValueError(f"spectra_2d debe ser 2D. Shape actual: {spectra_2d.shape}")

    mean_spec = spectra_2d.mean(axis=0)

    if wavelength is None:
        wavelength = np.arange(spectra_2d.shape[1])

    plt.figure(figsize=figsize)
    plt.plot(wavelength, mean_spec, label="Total mean spectrum")
    plt.xlabel("Spectral index")
    plt.ylabel("Normalized flux")
    plt.title(title)
    plt.legend()
    plt.tight_layout()

```

```

if save_path is not None:
    plt.savefig(save_path, dpi=300, bbox_inches="tight")

plt.show()

```

```

In [17]: # función para graficar una muestra individual
def plot_single_spectrum(
    spectra_2d,
    sample_idx,
    valid_df=None,
    title=None,
    wavelength=None,
    figsize=(10, 5),
    save_path=None
):
    """
    Grafica un espectro individual a partir de su índice.

    Parameters
    -----
    spectra_2d : np.ndarray
        Matriz shape (n_samples, n_wavelengths)
    sample_idx : int
        Índice de la muestra a graficar
    valid_df : pd.DataFrame or None
        Metadata opcional para mostrar info adicional en el título
    title : str or None
        Si None, construye uno automático
    wavelength : np.ndarray or None
        Eje x. Si None, usa índice espectral
    figsize : tuple
    save_path : str or None
        Si se entrega, guarda la figura
    """

    spectra_2d = np.asarray(spectra_2d)

    if spectra_2d.ndim != 2:
        raise ValueError(f"spectra_2d debe ser 2D. Shape actual: {spectra_2d.shape}")

    if sample_idx < 0 or sample_idx >= spectra_2d.shape[0]:
        raise IndexError(f"sample_idx fuera de rango. Debe estar entre 0 y {spectra_2d.shape[0]}")

    spectrum = spectra_2d[sample_idx]

    if wavelength is None:
        wavelength = np.arange(spectra_2d.shape[1])

    if title is None:
        title = f"Single spectrum - sample {sample_idx}"

        if valid_df is not None and sample_idx < len(valid_df):
            row = valid_df.iloc[sample_idx]

            extra_parts = []

```



```

        if "filename" in row.index:
            extra_parts.append(f"file: {row['filename']}")
        if "classID" in row.index:
            extra_parts.append(f"class: {row['classID']}")

        if len(extra_parts) > 0:
            title += "\n" + " | ".join(extra_parts)

    plt.figure(figsize=figsize)
    plt.plot(wavelength, spectrum, label=f"Sample {sample_idx}")
    plt.xlabel("Spectral index")
    plt.ylabel("Normalized flux")
    plt.title(title)
    plt.legend()
    plt.tight_layout()

    if save_path is not None:
        plt.savefig(save_path, dpi=300, bbox_inches="tight")

plt.show()

```

```

In [18]: def plot_multiple_spectra(
    spectra_2d,
    sample_indices,
    valid_df=None,
    title="Selected spectra",
    wavelength=None,
    figsize=(10, 5),
    alpha=0.9,
    save_path=None
):
    """
    Grafica varias muestras individuales en la misma figura.

    Parameters
    -----
    spectra_2d : np.ndarray
        Matriz shape (n_samples, n_wavelengths)
    sample_indices : list or array-like
        Índices de las muestras a graficar
    valid_df : pd.DataFrame or None
    title : str
    wavelength : np.ndarray or None
    figsize : tuple
    alpha : float
    save_path : str or None
    """

    spectra_2d = np.asarray(spectra_2d)

    if spectra_2d.ndim != 2:
        raise ValueError(f"spectra_2d debe ser 2D. Shape actual: {spectra_2d.shape}")

    if wavelength is None:
        wavelength = np.arange(spectra_2d.shape[1])

```

```

plt.figure(figsize=figsize)

for idx in sample_indices:
    if idx < 0 or idx >= spectra_2d.shape[0]:
        raise IndexError(f"sample_idx {idx} fuera de rango.")

    label = f"sample {idx}"

    if valid_df is not None and idx < len(valid_df):
        row = valid_df.iloc[idx]
        if "filename" in row.index:
            label += f" | {row['filename']}"

    plt.plot(wavelength, spectra_2d[idx], alpha=alpha, label=label)

plt.xlabel("Spectral index")
plt.ylabel("Normalized flux")
plt.title(title)
plt.legend(fontsize=8)
plt.tight_layout()

if save_path is not None:
    plt.savefig(save_path, dpi=300, bbox_inches="tight")

plt.show()

```

## Función que agrega líneas de Balmer (mientras no tengo el paquete)

```

In [19]: def add_balmer_lines(ax, y_text=None, alpha=0.6, fontsize=9):
        """
        Agrega líneas verticales de Balmer al eje.
        """
        balmer_lines = {
            "Hε": 3970.1,
            "Hδ": 4101.7,
            "Hγ": 4340.5,
            "Hβ": 4861.3,
            "Hα": 6562.8
        }

        ymin, ymax = ax.get_ylim()

        if y_text is None:
            y_text = ymax - 0.03 * (ymax - ymin)

        for name, lam in balmer_lines.items():
            ax.axvline(lam, linestyle="--", alpha=alpha, linewidth=1.0)
            ax.text(
                lam,
                y_text,
                name,
                rotation=90,

```

```

        va="top",
        ha="right",
        fontsize=fontsize
    )

```

## Función que genera archivos de salida

```

In [20]: # =====
# FUNCIÓN PRINCIPAL PARA GENERAR OUTPUTS ESPECTRALES -> ESPECTROS POR CLUSTER
# =====
def generate_cluster_spectra_outputs(
    spectra_2d,          # shape (n_samples, n_wavelengths)
    cluster_labels,      # shape (n_samples,)
    valid_df,            # metadata alineada con spectra_2d
    class_name,
    layer_name,
    method_name,
    output_dir="dracula_outputs",
    ignore_noise=False,
    wavelength=None
):
    """
    Genera salidas para análisis espectral por cluster.

    Guarda:
    - sample_cluster_map.csv
    - cluster_summary.csv
    - spectra.dat general
    - clusters.dat general
    - wavelength.dat
    - spectra individuales por cluster
    - mean por cluster
    - std por cluster

    Parameters
    -----
    spectra_2d : np.ndarray
        Matriz de espectros originales, shape (n_samples, n_wavelengths)
    cluster_labels : np.ndarray
        Etiquetas de clustering, shape (n_samples,)
    valid_df : pd.DataFrame
        Metadata alineada con spectra_2d
    class_name : str
    layer_name : str
    method_name : str
    output_dir : str
    ignore_noise : bool
        Si True, elimina cluster -1 (útil para DBSCAN)
    wavelength : np.ndarray or None
        Vector de longitudes de onda. Si None, usa 0..n_wavelengths-1

    Returns
    -----
    dict con rutas y dataframes útiles
    """

```

```

"""

spectra_2d = np.asarray(spectra_2d)
cluster_labels = np.asarray(cluster_labels)

# -----
# Validaciones
# -----
if spectra_2d.ndim != 2:
    raise ValueError(f"spectra_2d debe ser 2D. Shape actual: {spectra_2d.shape}")

if len(cluster_labels) != spectra_2d.shape[0]:
    raise ValueError(
        f"cluster_labels y spectra_2d no coinciden: "
        f"{len(cluster_labels)} vs {spectra_2d.shape[0]}"
    )

if len(valid_df) != spectra_2d.shape[0]:
    raise ValueError(
        f"valid_df y spectra_2d no coinciden: "
        f"{len(valid_df)} vs {spectra_2d.shape[0]}"
    )

if wavelength is None:
    wavelength = np.arange(spectra_2d.shape[1], dtype=np.float32)

# -----
# Crear carpeta base
# -----
base_name = f"{class_name}_{layer_name}_{method_name}"
base_dir = os.path.join(output_dir, class_name, layer_name, method_name)
os.makedirs(base_dir, exist_ok=True)

# -----
# Crear dataframe muestra -> cluster
# -----
cluster_df = valid_df.copy().reset_index(drop=True)
cluster_df["sample_idx"] = np.arange(len(cluster_df))
cluster_df["cluster"] = cluster_labels

# -----
# Manejo de ruido DBSCAN (-1)
# -----
if ignore_noise:
    mask = cluster_df["cluster"] != -1
    cluster_df = cluster_df.loc[mask].reset_index(drop=True)
    spectra_used = spectra_2d[mask.to_numpy()]
    labels_used = cluster_df["cluster"].to_numpy()
else:
    spectra_used = spectra_2d
    labels_used = cluster_labels

unique_clusters = np.unique(labels_used)

# -----
# Guardar mapa muestra -> cluster

```

```

# -----
cluster_map_csv = os.path.join(base_dir, f"{base_name}_sample_cluster_map.csv")
cluster_df.to_csv(cluster_map_csv, index=False)

# -----
# Guardar archivos generales
# -----
spectra_dat = os.path.join(base_dir, f"{base_name}_spectra.dat")
labels_dat = os.path.join(base_dir, f"{base_name}_clusters.dat")
wavelength_dat = os.path.join(base_dir, f"{base_name}_wavelength.dat")

np.savetxt(spectra_dat, spectra_used, fmt="%.8e")
np.savetxt(labels_dat, labels_used.astype(int), fmt="%d")
np.savetxt(wavelength_dat, wavelength, fmt="%.8e")

# -----
# Guardar resumen y archivos por cluster
# -----
summary_rows = []

for c in unique_clusters:
    mask_c = labels_used == c
    cluster_spectra = spectra_used[mask_c]

    mean_spec = cluster_spectra.mean(axis=0)
    std_spec = cluster_spectra.std(axis=0)

    n_cluster = int(mask_c.sum())

    summary_rows.append({
        "cluster": int(c),
        "n_samples": n_cluster
    })

# metadata del cluster
cluster_meta = cluster_df.loc[cluster_df["cluster"] == c].copy()
cluster_meta_csv = os.path.join(base_dir, f"{base_name}_cluster_{c}_metadat
cluster_meta.to_csv(cluster_meta_csv, index=False)

# todos los espectros del cluster
cluster_specs_path = os.path.join(base_dir, f"{base_name}_cluster_{c}_spect
np.savetxt(cluster_specs_path, cluster_spectra, fmt="%.8e")

# media del cluster
mean_path = os.path.join(base_dir, f"{base_name}_cluster_{c}_mean.dat")
np.savetxt(mean_path, mean_spec, fmt="%.8e")

# std del cluster
std_path = os.path.join(base_dir, f"{base_name}_cluster_{c}_std.dat")
np.savetxt(std_path, std_spec, fmt="%.8e")

summary_df = pd.DataFrame(summary_rows).sort_values("cluster").reset_index(drop
summary_csv = os.path.join(base_dir, f"{base_name}_cluster_summary.csv")
summary_df.to_csv(summary_csv, index=False)

return {

```

```

    "base_dir": base_dir,
    "cluster_map_csv": cluster_map_csv,
    "spectra_dat": spectra_dat,
    "labels_dat": labels_dat,
    "wavelength_dat": wavelength_dat,
    "summary_csv": summary_csv,
    "summary_df": summary_df,
    "cluster_df": cluster_df
}

```

In [21]: *# fc que automatiza la generación de archivos de salida para todos los experimentos*

```

def generate_all_outputs_for_class(
    spectra_2d,
    valid_df,
    class_name,
    labels_dict_for_class,
    output_dir="dracula_outputs",
    ignore_noise_for_dbscan=False,
    wavelength=None
):
    """
    Recorre todas las capas y métodos de una clase y genera outputs espectrales.

    Parameters
    -----
    spectra_2d : np.ndarray
        Espectros originales shape (n_samples, n_wavelengths)
    valid_df : pd.DataFrame
    class_name : str
    labels_dict_for_class : dict
        Ejemplo:
        cluster_labels_all["WDA"]
    output_dir : str
    ignore_noise_for_dbscan : bool
    wavelength : np.ndarray or None

    Returns
    -----
    dict
    """

    all_outputs = {}

    for layer_name, methods_dict in labels_dict_for_class.items():
        all_outputs[layer_name] = {}

        for method_name, labels in methods_dict.items():
            ignore_noise = (method_name == "dbscan" and ignore_noise_for_dbscan)

            result = generate_cluster_spectra_outputs(
                spectra_2d=spectra_2d,
                cluster_labels=labels,
                valid_df=valid_df,
                class_name=class_name,
                layer_name=layer_name,
                method_name=method_name,

```

```

        output_dir=output_dir,
        ignore_noise=ignore_noise,
        wavelength=wavelength
    )

    all_outputs[layer_name][method_name] = result

    return all_outputs

```

**Contenedores -> diccionarios anidados que contienen array de enteros donde cada posición es una muestra y el valor es el cluster al que fue asignado.**

Tiene más o menos esta forma: cluster\_labels\_all -> "WDA" -> "flatten" -> "spectral" -> np.array([0,1,2,0,2,1,...]) shape (n\_muestras,)

```

In [22]: cluster_labels_all = {
        "WDA": {},
        "WDB": {}
    }

```

```

cluster_labels_all_n2 = {
    "WDA": {},
    "WDB": {}
}

```

```

In [23]: #guarda labels dentro del diccionario general cluster_labels_all.
def save_cluster_labels(container, class_name, layer_name, method_name, labels):
    """
    estructura final:
    cluster_labels_all["WDA"]["dense_1"]["spectral"] = labels
    """

    if class_name not in container:
        container[class_name] = {}

    if layer_name not in container[class_name]:
        container[class_name][layer_name] = {}

    container[class_name][layer_name][method_name] = np.asarray(labels).copy()

```

**Funciones que consideran las longitudes de onda**

```

In [24]: def process_spectrum_with_wavelength(file_path):
        try:
            sed = np.loadtxt(file_path, unpack=True)

```

```

wave = sed[0, 48:-400]
flux = sed[1, 48:-400]

# Ajuste a 3750 puntos, como espera la red
if len(flux) > 3750:
    diff = len(flux) - 3750
    start = diff // 2

    flux = flux[start:start + 3750]
    wave = wave[start:start + 3750]

elif len(flux) < 3750:
    pad_len = 3750 - len(flux)

    flux = np.pad(flux, (0, pad_len), mode='constant')

# Para wavelength, mejor evitar inventar demasiado.
# Extendemos linealmente usando el paso medio.
if len(wave) > 1:
    dw = np.nanmedian(np.diff(wave))
    extra_wave = wave[-1] + dw * np.arange(1, pad_len + 1)
    wave = np.concatenate([wave, extra_wave])
else:
    wave = np.pad(wave, (0, pad_len), mode='constant')

norm_val = flux[2100]

if norm_val == 0 or np.isnan(norm_val):
    norm_val = np.nanmean(flux)

if norm_val == 0 or np.isnan(norm_val):
    return None, None

flux = flux / norm_val

if np.isnan(flux).any() or np.isnan(wave).any():
    return None, None

return wave.astype(np.float32), flux.astype(np.float32)

except Exception:
    return None, None

```

```

In [25]: def load_class_spectra_DRACULA_with_wavelength(class_name, n_samples=1100, random_s
spectrum_df = build_class_dataframe(class_name)
print(f"{class_name}: disponibles con match a .dat = {len(spectrum_df)}")

if len(spectrum_df) < n_samples:
    raise ValueError(f"No hay suficientes espectros para {class_name}. Disponib

selected_df = spectrum_df.sample(n=n_samples, random_state=random_state).reset_

wave_list = []
flux_list = []
valid_rows = []

```



```

for _, row in selected_df.iterrows():
    f_path = os.path.join(data_path, row['filename'])

    wave, flux = process_spectrum_with_wavelength(f_path)

    if wave is not None and flux is not None:
        wave_list.append(wave)
        flux_list.append(flux)
        valid_rows.append(row)

W_final = np.array(wave_list, dtype=np.float32)
X_final = np.array(flux_list, dtype=np.float32)

X_input = X_final.reshape((X_final.shape[0], X_final.shape[1], 1))
valid_df = pd.DataFrame(valid_rows).reset_index(drop=True)

print(f"{class_name}: espectros válidos finales = {X_input.shape[0]}")
print(f"{class_name}: shape wavelength = {W_final.shape}")
print(f"{class_name}: shape flux = {X_final.shape}")

return W_final, X_final, X_input, valid_df

```

## Función para evaluación de K con Silhouette Score

```

In [26]: def evaluate_kmeans_k(features_32, class_name, layer_name, k_values=range(2, 9)):
        Xs = StandardScaler().fit_transform(features_32)

        #inertias = []
        silhouettes = []

        for k in k_values:
            km = KMeans(n_clusters=k, random_state=42, n_init=10)
            labels = km.fit_predict(Xs)

            #inertias.append(km.inertia_)
            silhouettes.append(silhouette_score(Xs, labels))

        plt.figure(figsize=(12,4))

        ...
        plt.subplot(1,2,1)
        plt.plot(list(k_values), inertias, marker='o')
        plt.title(f"{class_name} - {layer_name} - Elbow")
        plt.xlabel("k")
        plt.ylabel("Inercia")
        ...

        #plt.subplot(1,2,2)
        n_samples = features_32.shape[0]
        plt.plot(list(k_values), silhouettes, marker='o')
        plt.title(f"{class_name} - {layer_name} - Silhouette(n={n_samples})")
        #plt.legend([f"n={n_samples}"])

```

```
plt.xlabel("k")
plt.ylabel("Silhouette")

plt.tight_layout()
plt.show()
```

## Función para hacer matrices (de contingencia) y analizar cambios de k para Spectral Clustering

```
In [27]: def plot_migration_matrix(labels_a, labels_b, ka, kb, title=None, figsize=(6, 5)):
cm = contingency_matrix(labels_a, labels_b)

rows_labels = [f'C{i}' for i in range(cm.shape[0])]
cols_labels = [f'C{j}' for j in range(cm.shape[1])]

fig, ax = plt.subplots(figsize=figsize)
sns.heatmap(
    cm,
    annot=True,
    fmt='d',
    cmap='Blues',
    xticklabels=cols_labels,
    yticklabels=rows_labels,
    ax=ax
)
ax.set_xlabel(f'Clústeres k={kb}', fontsize=11)
ax.set_ylabel(f'Clústeres k={ka}', fontsize=11)
_title = title if title else f'Migración k={ka} → k={kb} (Flatten, WDA)'
ax.set_title(_title, fontsize=12, fontweight='bold')
plt.tight_layout()
plt.show()
```

## Visualización de un espectro con la longitud de onda correcta

```
In [28]: W_wda, X_wda_spec, X_wda_input, df_wda_DRAC = load_class_spectra_DRACULA_with_wavel
"WDA",
n_samples=1100,
random_state=42
)

sample_idx = 0

plt.figure(figsize=(10, 5))
plt.plot(W_wda[sample_idx], X_wda_spec[sample_idx])
plt.xlabel("Wavelength [Å]")
plt.ylabel("Normalized flux")
plt.title(f"WDA - sample {sample_idx}")
```


```
plt.tight_layout()
plt.show()
```

WDA: disponibles con match a .dat = 13723

WDA: espectros válidos finales = 1100

WDA: shape wavelength = (1100, 3750)

WDA: shape flux = (1100, 3750)



Anteriormente se consideran  $n=1100$  muestras, ahora usaré  $n=13000$  muestras (casi el total de muestras de WDA, que son 13723) -> los espectros válidos finales pueden ser menos que el  $n$  seleccionado, debido a que si en la función `process_spectrum` un espectro falla al cargarse, contiene valores nulos o tiene un valor de normalización 0, esta función retorna `None` y el espectro es descartado (no se agrega al conjunto final `X_list`).

```
In [29]: W_wda_n2, X_wda_spec_n2, X_wda_input_n2, df_wda_DRAC_n2 = load_class_spectra_DRACUL
         "WDA",
         n_samples=13723,
         random_state=42
         )

sample_idx = 0


plt.figure(figsize=(10, 5))
plt.plot(W_wda_n2[sample_idx], X_wda_spec_n2[sample_idx])
plt.xlabel("Wavelength [Å]")
plt.ylabel("Normalized flux")
plt.title(f"WDA - sample {sample_idx}")
plt.tight_layout()
plt.show()
```

WDA: disponibles con match a .dat = 13723

WDA: espectros válidos finales = 13711

WDA: shape wavelength = (13711, 3750)

WDA: shape flux = (13711, 3750)



Funciones que hacen cluster y plot según método, y generan espectros a partir de los clusters encontrados en cada método. Se implementa interact

```
In [30]: def _add_cluster_legend(ax, labels, cmap=plt.cm.viridis):
    unique_labels = np.unique(labels)
    label_min, label_max = unique_labels.min(), unique_labels.max()
    handles = []
    for lab in unique_labels:
        count = int(np.sum(labels == lab))
        if lab == -1:
            color, text = "black", f"ruido (-1): n={count}"
        else:
            norm = 0.5 if label_max == label_min else (lab - label_min) / (label_max - label_min)
            color, text = cmap(norm), f"cluster {lab}: n={count}"
        handles.append(Line2D([0], [0], marker='o', color='w',
                              markerfacecolor=color, markersize=8, label=text))
    ax.legend(handles=handles, title="Clusters", loc="best", fontsize=9)
```

```
In [31]: def _print_metrics_box(class_name, layer_name, method, param_str, metrics, dbcv=None):
    k = metrics['n_clusters']
    noise = metrics['n_noise']
    sil = f"{metrics['silhouette']:.4f}" if metrics['silhouette'] else "N/A"
    db = f"{metrics['davies_bouldin']:.4f}" if metrics['davies_bouldin'] else "N/A"
    ch = f"{metrics['calinski_harabasz']:.2f}" if metrics['calinski_harabasz'] else "N/A"
    sep = chr(9472) * 64
    print(f'\n \u250c{sep}\u2510')
    print(f' \u2502 {class_name} | {layer_name} | {method} | {param_str} ')
    print(f' \u2502 clusters={k} noise={noise} sil={sil} DB={db} CH={ch} ')
    if dbcv is not None:
        dbcv_str = f'{dbcv:.4f}' if dbcv == dbcv else 'N/A'
        print(f' \u2502 DBCV = {dbcv_str} (rango [-1,1], específico DBSCAN) ')
    print(f' \u2514{sep}\u2518\n')
```

```

def cluster_plot_KMeans(features_32, class_name, layer_name,
                        kmeans_k=3, random_state=42,
                        vis_method="pca", xlim=None, ylim=None,
                        container=None):

    Xs = StandardScaler().fit_transform(features_32)

    if vis_method.lower() == "pca":
        emb_2d = PCA(n_components=2, random_state=42).fit_transform(Xs)
    elif vis_method.lower() == "tsne":
        emb_2d = TSNE(n_components=2, random_state=42,
                      perplexity=30, init='pca').fit_transform(Xs)
    else:
        raise ValueError("vis_method debe ser 'pca' o 'tsne'")

    km_labels = KMeans(n_clusters=kmeans_k, random_state=random_state,
                      n_init=10).fit_predict(Xs)

    if container is not None:
        save_cluster_labels(container, class_name, layer_name, "kmeans", km_labels)

    fig, ax = plt.subplots(figsize=(9, 6))
    ax.scatter(emb_2d[:, 0], emb_2d[:, 1], c=km_labels, s=30, alpha=0.6, cmap='viridis')
    ax.set_title(f"{class_name} \u2014 {layer_name} \u2014 KMeans "
                f"(k={kmeans_k}, n={features_32.shape[0]})", fontsize=15)
    _add_cluster_legend(ax, km_labels)
    ax.set_xlabel("Comp. 1"); ax.set_ylabel("Comp. 2")
    if xlim: ax.set_xlim(xlim)
    if ylim: ax.set_ylim(ylim)
    plt.tight_layout(); plt.show()

    metrics = compute_cluster_metrics(Xs, km_labels)
    _print_metrics_box(class_name, layer_name, "kmeans", f"k={kmeans_k}", metrics)
    return {"kmeans": km_labels, "metrics": metrics}

def cluster_plot_Spect(features_32, class_name, layer_name,
                        spectral_k=3, random_state=42,
                        vis_method="pca", xlim=None, ylim=None,
                        container=None):

    Xs = StandardScaler().fit_transform(features_32)

    if vis_method.lower() == "pca":
        emb_2d = PCA(n_components=2, random_state=42).fit_transform(Xs)
    elif vis_method.lower() == "tsne":
        emb_2d = TSNE(n_components=2, random_state=42,
                      perplexity=30, init='pca').fit_transform(Xs)
    else:
        raise ValueError("vis_method debe ser 'pca' o 'tsne'")

    sc_labels = SpectralClustering(n_clusters=spectral_k, random_state=random_state,
                                  affinity='nearest_neighbors').fit_predict(Xs)

```

```

if container is not None:
    save_cluster_labels(container, class_name, layer_name, "spectral", sc_labels)

fig, ax = plt.subplots(figsize=(9, 6))
ax.scatter(emb_2d[:, 0], emb_2d[:, 1], c=sc_labels, s=30, alpha=0.6, cmap='viridis')
ax.set_title(f"{class_name} \u2014 {layer_name} \u2014 Spectral "
             f"(k={spectral_k}, n={features_32.shape[0]})", fontsize=15)
_add_cluster_legend(ax, sc_labels)
ax.set_xlabel("Comp. 1"); ax.set_ylabel("Comp. 2")
if xlim: ax.set_xlim(xlim)
if ylim: ax.set_ylim(ylim)
plt.tight_layout(); plt.show()

metrics = compute_cluster_metrics(Xs, sc_labels)
_print_metrics_box(class_name, layer_name, "spectral", f"k={spectral_k}", metrics)
return {"spectral": sc_labels, "metrics": metrics}

def cluster_plot_DBSCAN(features_32, class_name, layer_name,
                        dbscan_eps=1.5, dbscan_min_samples=10,
                        vis_method="pca", xlim=None, ylim=None,
                        container=None):

    Xs = StandardScaler().fit_transform(features_32)

    if vis_method.lower() == "pca":
        emb_2d = PCA(n_components=2, random_state=42).fit_transform(Xs)
    elif vis_method.lower() == "tsne":
        emb_2d = TSNE(n_components=2, random_state=42,
                      perplexity=30, init='pca').fit_transform(Xs)
    else:
        raise ValueError("vis_method debe ser 'pca' o 'tsne'")

    db_labels = DBSCAN(eps=dbscan_eps,
                      min_samples=dbscan_min_samples).fit_predict(Xs)

    if container is not None:
        save_cluster_labels(container, class_name, layer_name, "dbscan", db_labels)

    fig, ax = plt.subplots(figsize=(9, 6))
    ax.scatter(emb_2d[:, 0], emb_2d[:, 1], c=db_labels, s=30, alpha=0.3, cmap='viridis')
    ax.set_title(f"{class_name} \u2014 {layer_name} \u2014 DBSCAN "
             f"(eps={dbscan_eps}, n={features_32.shape[0]})", fontsize=15)
    _add_cluster_legend(ax, db_labels)
    ax.set_xlabel("Comp. 1"); ax.set_ylabel("Comp. 2")
    if xlim: ax.set_xlim(xlim)
    if ylim: ax.set_ylim(ylim)
    plt.tight_layout(); plt.show()

    metrics = compute_cluster_metrics(Xs, db_labels)
    n_pts = int(np.sum(db_labels != -1))
    dbcv = dbcv_score(Xs, db_labels) if n_pts <= 5000 else None
    if n_pts > 5000:
        print(f' [DBCV omitido: {n_pts} puntos no-ruido > 5000]')
    _print_metrics_box(class_name, layer_name, "dbscan", f"eps={dbscan_eps}", metrics)
    return {"dbscan": db_labels, "metrics": metrics, "dbcv": dbcv}

```

```

In [32]: def _plot_cluster_spectra_base(
    spectra_2d, labels, wavelength,
    class_name, layer_name, method_name,
    linewidth_mean=2.4,
    figsize=(11, 5),
    mark_balmer=True,
    robust_ylim=True,
    ignore_noise=False,
    diff_percentiles=(1, 99),
    show_std=False,
    smooth_sigma=3          # suavizado Gaussian para el plot de diferencia (pix
):
    spectra_2d = np.asarray(spectra_2d)
    labels      = np.asarray(labels)
    wavelength  = np.asarray(wavelength)

    if ignore_noise:
        mask      = labels != -1
        spectra_2d = spectra_2d[mask]
        labels     = labels[mask]

    unique_clusters = np.sort(np.unique(labels))
    total_mean      = np.mean(spectra_2d, axis=0)
    group_means     = {int(c): np.mean(spectra_2d[labels == c], axis=0)
                       for c in unique_clusters}

    n_clusters = len(unique_clusters)
    cmap       = plt.cm.get_cmap("tab10", n_clusters)

    # promedio de cada cluster por separado
    for i, c in enumerate(unique_clusters):
        group_spectra = spectra_2d[labels == c]
        group_mean     = group_means[int(c)]
        n              = int(group_spectra.shape[0])
        #color          = cmap(i)

        if c == -1:
            color = "gray"
            label_mean = f"Ruido (-1) mean (n={n})"
            title_tag = f"Ruido (-1) (n={n})"
        else:
            color = cmap(i)
            label_mean = f"Cluster {c} mean (n={n})"
            title_tag = f"Cluster {c} (n={n})"

        fig, ax = plt.subplots(figsize=figsize)

        if show_std:
            std = np.std(group_spectra, axis=0)
            ax.fill_between(wavelength,
                           group_mean - std,
                           group_mean + std,
                           alpha=0.18, color=color, label="±1σ")

        ax.plot(wavelength, group_mean, linewidth=linewidth_mean,

```

```

        color=color, label=f"Cluster {c} mean (n={n})")

    ax.set_xlabel("Wavelength [Å]")
    ax.set_ylabel("Normalized flux")
    ax.set_title(f"{class_name} - {layer_name} - {method_name}\n{n{title_tag}}")

    if robust_ylim:
        p_low, p_high = np.percentile(group_mean, [1, 99])
        margin = 0.10 * (p_high - p_low)
        ax.set_ylim(p_low - margin, p_high + margin)

    if mark_balmer:
        add_balmer_lines(ax)

    ax.legend()
    plt.tight_layout()
    plt.show()

# promedio total —
fig, ax = plt.subplots(figsize=figsize)
ax.plot(wavelength, total_mean, linewidth=linewidth_mean,
        color="black", label=f"Total mean (n={spectra_2d.shape[0]})")

ax.set_xlabel("Wavelength [Å]")
ax.set_ylabel("Normalized flux")
ax.set_title(f"{class_name} - {layer_name} - {method_name}\n"
            f"Total mean spectrum")

if robust_ylim:
    p_low, p_high = np.percentile(total_mean, [1, 99])
    margin = 0.10 * (p_high - p_low)
    ax.set_ylim(p_low - margin, p_high + margin)

if mark_balmer:
    add_balmer_lines(ax)

ax.legend()
plt.tight_layout()
plt.show()

# diferencia: promedio cluster - promedio total
from scipy.ndimage import gaussian_filter1d
for i, c in enumerate(unique_clusters):
    diff = group_means[int(c)] - total_mean
    diff_smooth = gaussian_filter1d(diff, sigma=smooth_sigma)
# ruido dbscan
    if c == -1:
        color = "gray"
        diff_label = "Ruido (-1) - total mean"
        diff_title = "Diff: Ruido (-1) mean - total mean"
    else:
        color = cmap(i)
        diff_label = f"Cluster {c} - total mean"
        diff_title = f"Diff: Cluster {c} mean - total mean"

fig, ax = plt.subplots(figsize=figsize)

```



```

ax.plot(wavelength, diff, linewidth=0.8, color=color,
        alpha=0.25, label="raw")
ax.plot(wavelength, diff_smooth, linewidth=linewidth_mean, color=color,
        alpha=1.0, label=f"{diff_label} ( $\sigma$ ={{smooth_sigma}}px)")
ax.axhline(0.0, linestyle="--", linewidth=1.2, color="gray", alpha=0.7)

ax.set_xlabel("Wavelength [Å]")
ax.set_ylabel("Δ Normalized flux")
ax.set_title(f"{{class_name}} - {{layer_name}} - {{method_name}}\n{{diff_title}}")

if robust_ylim:
    p_low, p_high = np.percentile(diff_smooth, diff_percentiles)
    margin = 0.15 * (p_high - p_low + 1e-8)
    ax.set_ylim(p_low - margin, p_high + margin)

if mark_balmer:
    add_balmer_lines(ax)

ax.legend()
plt.tight_layout()
plt.show()

# todos los promedios juntos
fig, ax = plt.subplots(figsize=figsize)
all_curves = []

for i, c in enumerate(unique_clusters):
    group_spectra = spectra_2d[labels == c]
    mean_spec = group_means[int(c)]
    n_in_cluster = int(np.sum(labels == c))
    #color = cmap(i)
    if c == -1:
        color = "gray"
        leg = f"Ruido (-1) (n={{n_in_cluster}})"
    else:
        color = cmap(i)
        leg = f"Cluster {c} mean (n={{n_in_cluster}})"

    if show_std:
        std = np.std(spectra_2d[labels==c], axis=0)
        ax.fill_between(wavelength,
                        mean_spec - std,
                        mean_spec + std,
                        alpha=0.18, color=color)

    ax.plot(wavelength, mean_spec, linewidth=2.2,
            color=color, label=leg)
    all_curves.append(mean_spec)

ax.plot(wavelength, total_mean, linewidth=2.4, linestyle="--",
        color="black", label=f"Total mean (n={{spectra_2d.shape[0]}})")

ax.set_xlabel("Wavelength [Å]")
ax.set_ylabel("Normalized flux")
ax.set_title(f"{{class_name}} - {{layer_name}} - {{method_name}}\n"
            f"All cluster means")

```

```

if robust_ylim:
    stacked = np.vstack([*all_curves, total_mean])
    p_low, p_high = np.percentile(stacked, [1, 99])
    margin = 0.10 * (p_high - p_low + 1e-8)
    ax.set_ylim(p_low - margin, p_high + margin)

if mark_balmer:
    add_balmer_lines(ax)

ax.legend()
plt.tight_layout()
plt.show()

return {
    "total_mean"      : total_mean,
    "group_means"     : group_means,
    "unique_clusters": unique_clusters
}

```

```

In [33]: def plot_spectra_kmeans(spectra_2d, labels, wavelength, class_name, layer_name,
                                linewidth_mean=2.4, figsize=(11,5),
                                mark_balmer=True, robust_ylim=True, show_std=False,
                                smooth_sigma=3):
    return _plot_cluster_spectra_base(
        spectra_2d, labels, wavelength,
        class_name, layer_name, method_name="kmeans",
        linewidth_mean=linewidth_mean, figsize=figsize,
        mark_balmer=mark_balmer, robust_ylim=robust_ylim,
        ignore_noise=False, show_std=show_std, smooth_sigma=smooth_sigma
    )

def plot_spectra_spectral(spectra_2d, labels, wavelength, class_name, layer_name,
                          linewidth_mean=2.4, figsize=(11,5),
                          mark_balmer=True, robust_ylim=True, show_std=False,
                          smooth_sigma=3):
    return _plot_cluster_spectra_base(
        spectra_2d, labels, wavelength,
        class_name, layer_name, method_name="spectral",
        linewidth_mean=linewidth_mean, figsize=figsize,
        mark_balmer=mark_balmer, robust_ylim=robust_ylim,
        ignore_noise=False, show_std=show_std, smooth_sigma=smooth_sigma
    )

def plot_spectra_dbscan(spectra_2d, labels, wavelength, class_name, layer_name,
                        ignore_noise=False, linewidth_mean=2.4, figsize=(11,5),
                        mark_balmer=True, robust_ylim=True, show_std=False,
                        smooth_sigma=3):
    return _plot_cluster_spectra_base(
        spectra_2d, labels, wavelength,
        class_name, layer_name, method_name="dbscan",
        linewidth_mean=linewidth_mean, figsize=figsize,
        mark_balmer=mark_balmer, robust_ylim=robust_ylim,
        ignore_noise=ignore_noise, show_std=show_std, smooth_sigma=smooth_sigma
    )

```

```

In [34]: # Widget interactivo para explorar los espectros promedio por cluster
def interactive_plot_cluster_spectra(
    spectra_2d,
    wavelength,
    class_name,
    container,
    linewidth_mean=2.4,
    figsize=(13, 5),
    mark_balmer=True
):
    """
    Controles:
    - Capa      : flatten / dense / dense_1 / dense_2
    - Método    : kmeans / spectral / dbscan
    - Mostrar  $\pm 1\sigma$ : activa/desactiva la banda de desviación estándar
    """
    spectra_2d = np.asarray(spectra_2d)
    wavelength = np.asarray(wavelength)

    # Leer capas y métodos disponibles desde el container
    available_layers = list(container[class_name].keys())
    available_methods = list(next(iter(container[class_name].values())).keys())

    layer_dropdown = widgets.Dropdown(
        options=available_layers,
        value=available_layers[0],
        description="Capa:"
    )
    method_dropdown = widgets.Dropdown(
        options=available_methods,
        value=available_methods[0],
        description="Método:"
    )
    std_toggle = widgets.ToggleButtons(
        options=["No", "Sí"],
        value="No",
        description="Mostrar  $\pm 1\sigma$ :",
        button_style=""
    )

    def _plot(layer_name, method_name, mostrar_std):
        if method_name not in container[class_name].get(layer_name, {}):
            print(f"Sin labels para {class_name} - {layer_name} - {method_name}")
            return

        labels = np.asarray(container[class_name][layer_name][method_name])
        unique_clusters = np.sort(np.unique(labels))
        total_mean = np.mean(spectra_2d, axis=0)
        n_clusters = len(unique_clusters)
        cmap = plt.cm.get_cmap("tab10", n_clusters)
        show_std = mostrar_std == "Sí"

        fig, ax = plt.subplots(figsize=figsize)

        for i, c in enumerate(unique_clusters):

```

```

mask          = labels == c
group_spectra = spectra_2d[mask]
group_mean    = np.mean(group_spectra, axis=0)
n_in_cluster  = int(mask.sum())
color         = cmap(i)

if show_std:
    std = np.std(group_spectra, axis=0)
    ax.fill_between(wavelength,
                    group_mean - std,
                    group_mean + std,
                    alpha=0.18, color=color)

ax.plot(wavelength, group_mean, linewidth=linewidth_mean,
        color=color, label=f"Cluster {c} (n={n_in_cluster})")

ax.plot(wavelength, total_mean, linewidth=2.0, linestyle="--",
        color="black", label=f"Total mean (n={spectra_2d.shape[0]})")

ax.set_xlabel("Wavelength [Å]")
ax.set_ylabel("Normalized flux")
ax.set_title(f"{class_name} - {layer_name} - {method_name}"
            + (" [±1σ]" if show_std else ""))

if mark_balmer:
    add_balmer_lines(ax)

ax.legend()
plt.tight_layout()
plt.show()

interact(
    _plot,
    layer_name=layer_dropdown,
    method_name=method_dropdown,
    mostrar_std=std_toggle
)

```

## Función para el cálculo de métricas Davies Bouldin Score, Calinski-Harabasz Score y Silhouette Score para un clustering dado

```

In [35]: from sklearn.metrics import davies_bouldin_score, calinski_harabasz_score, silhouet

def compute_cluster_metrics(Xs, labels):
    """
    Calcula DB, CH y Silhouette sobre el espacio escalado.
    Excluye ruido (-1) automáticamente.
    Retorna dict con metricas, o None en cada metrica si hay menos de 2 clusters.
    """
    mask          = labels != -1

```

```

Xs_clean      = Xs[mask]
labels_clean   = labels[mask]

n_clusters    = len(np.unique(labels_clean))
n_noise       = int(np.sum(~mask))

if n_clusters < 2:
    return {
        "n_clusters"      : n_clusters,
        "n_noise"         : n_noise,
        "silhouette"      : None,
        "davies_bouldin"   : None,
        "calinski_harabasz" : None
    }

return {
    "n_clusters"      : n_clusters,
    "n_noise"         : n_noise,
    "silhouette"      : round(silhouette_score(Xs_clean, labels_clean), 6),
    "davies_bouldin"   : round(davies_bouldin_score(Xs_clean, labels_clean), 6),
    "calinski_harabasz" : round(calinski_harabasz_score(Xs_clean, labels_clean), 6)
}

```

```

In [36]: # censity based clustering validation (DBCV)
from scipy.spatial.distance import cdist
from scipy.sparse.csgraph import minimum_spanning_tree
from scipy.sparse import csr_matrix

def dbcv_score(X, labels, noise_id=-1):
    """
    rango [-1, 1]. Mas alto = mejor.
    los puntos de ruido (noise_id=-1) se excluyen automaticamente.
    complejidad O(n^2). Recomendado para n <= 5000.
    """
    X      = np.asarray(X, dtype=np.float64)
    labels = np.asarray(labels)

    mask   = labels != noise_id
    X      = X[mask]
    labels = labels[mask]

    unique = np.unique(labels)
    if len(unique) < 2:
        return np.nan

    n = X.shape[0]

    # matriz de distancias completa
    D = cdist(X, X)
    np.fill_diagonal(D, np.inf)

    # distancia core: media armonica de distancias dentro del cluster
    # d_core(x_i) = (|C|-1) / sum_{j in C, j!=i} (1/d(x_i,x_j))
    core_dists = np.full(n, np.inf)
    for label in unique:

```

```

idx = np.where(labels == label)[0]
if len(idx) <= 1:
    continue
D_sub = D[np.ix_(idx, idx)]
with np.errstate(divide='ignore'):
    inv_d = np.where(np.isinf(D_sub), 0.0, 1.0 / D_sub)
    harmonic_core = (len(idx) - 1) / inv_d.sum(axis=1)
    for k, i in enumerate(idx):
        core_dists[i] = harmonic_core[k]

# Mutual reachability distance: mrd(i,j) = max(core_i, core_j, d(i,j))
D_fin = np.where(np.isinf(D), 0.0, D)
mrd = np.maximum(
    np.maximum(core_dists[:, None], core_dists[None, :]),
    D_fin
)

# Arbol de expansion minima sobre mrd
mst = minimum_spanning_tree(csr_matrix(mrd)).toarray()
mst_sym = np.maximum(mst, mst.T)

# DSC: max arista interna del MST por cluster (dispersion interna)
dsc = {}
for label in unique:
    idx = np.where(labels == label)[0]
    internal = mst_sym[np.ix_(idx, idx)]
    dsc[label] = float(internal.max()) if internal.size > 0 else 0.0

# DSPC: min MRD entre clusters distintos (separacion entre clusters)
dspc = {}
for i, li in enumerate(unique):
    for j, lj in enumerate(unique):
        if i >= j:
            continue
        ix_i = np.where(labels == li)[0]
        ix_j = np.where(labels == lj)[0]
        val = float(mrd[np.ix_(ix_i, ix_j)].min())
        dspc[(li, lj)] = dspc[(lj, li)] = val

# Validez por cluster: (separacion - dispersion) / max(separacion, dispersion)
validity = {}
for label in unique:
    min_sep = min(dspc[(label, o)] for o in unique if o != label)
    denom = max(min_sep, dsc[label])
    validity[label] = 0.0 if denom == 0 else (min_sep - dsc[label]) / denom

# Score global: promedio ponderado por tamaño de cluster
score = sum(
    (np.sum(labels == label) / n) * validity[label]
    for label in unique
)
return round(float(score), 6)

```

```

In [37]: # tabla de métricas
def build_metrics_table(
    representations_32,

```

```

class_name,
spectral_k_values = [2, 3, 4, 5],
dbscan_eps_values = [0.5, 1.0, 1.5, 2.0, 2.5, 3.0],
dbscan_min_samples = 10,
random_state      = 42
):
    """
    Itera sobre todas las combinaciones capa × método × parámetro
    y devuelve una tabla con las métricas de clustering.

    Solo considera Spectral Clustering y DBSCAN.

    Parameters
    -----
    representations_32 : dict {layer_name: np.ndarray shape (n, 32)}
    class_name         : str
    spectral_k_values  : list de k a probar para Spectral
    dbscan_eps_values  : list de eps a probar para DBSCAN
    dbscan_min_samples : int

    Returns
    -----
    pd.DataFrame con columnas:
        class | layer | method | param | param_value |
        n_clusters | n_noise | silhouette | davies_bouldin | calinski_harabasz
    """
    rows = []

    for layer_name, feats in representations_32.items():
        Xs = StandardScaler().fit_transform(feats)

        # — Spectral Clustering: barre sobre k —
        for k in spectral_k_values:
            labels = SpectralClustering(
                n_clusters = k,
                affinity    = "nearest_neighbors",
                assign_labels = "kmeans",
                random_state = random_state
            ).fit_predict(Xs)

            metrics = compute_cluster_metrics(Xs, labels)

            rows.append({
                "class"       : class_name,
                "layer"       : layer_name,
                "method"      : "spectral",
                "param"       : "k",
                "param_value" : k,
                **metrics
            })

        # — DBSCAN: barre sobre eps —
        for eps in dbscan_eps_values:
            labels = DBSCAN(
                eps = eps,
                min_samples = dbscan_min_samples

```

```

        ).fit_predict(Xs)

    metrics = compute_cluster_metrics(Xs, labels)

    rows.append({
        "class"          : class_name,
        "layer"          : layer_name,
        "method"         : "dbscan",
        "param"          : "eps",
        "param_value"    : eps,
        **metrics
    })

df = pd.DataFrame(rows, columns=[
    "class", "layer", "method", "param", "param_value",
    "n_clusters", "n_noise",
    "silhouette", "davies_bouldin", "calinski_harabasz"
])

return df

```

```

In [38]: # identificar las mejores configuraciones
def get_best_configs(metrics_df, top_n=5, min_clusters=2):
    """
    Rankea las configuraciones usando las tres métricas combinadas.

    Criterios:
        silhouette      → mayor es mejor
        davies_bouldin → menor es mejor
        calinski_harabasz → mayor es mejor

    Se filtran filas con métricas None o n_clusters < min_clusters.

    Parameters
    -----
    metrics_df : output de build_metrics_table
    top_n      : cuántas configuraciones mostrar
    min_clusters: mínimo de clusters para considerar válida la fila

    Returns
    -----
    pd.DataFrame con las top_n configuraciones y su score_compuesto
    """
    df = metrics_df.dropna(subset=["silhouette", "davies_bouldin",
                                   "calinski_harabasz"]).copy()
    df = df[df["n_clusters"] >= min_clusters].reset_index(drop=True)

    # Ranking por cada métrica (1 = mejor)
    df["rank_sil"] = df["silhouette"].rank(ascending=False)
    df["rank_db"]  = df["davies_bouldin"].rank(ascending=True) # menor es mejor
    df["rank_ch"]  = df["calinski_harabasz"].rank(ascending=False)

    # Score compuesto: promedio de los tres rankings (menor = mejor)
    df["score_compuesto"] = (df["rank_sil"] + df["rank_db"] + df["rank_ch"]) / 3

    top = (df.sort_values("score_compuesto")

```



```

        .head(top_n)
        .reset_index(drop=True))

cols_show = [
    "class", "layer", "method", "param_value", "n_clusters", "n_noise",
    "silhouette", "davies_bouldin", "calinski_harabasz", "score_compuesto"
]

return top[cols_show]

```

```

In [39]: # visualización tabla
def plot_metrics_heatmap(metrics_df, metric="silhouette", class_name=None):
    """
    Heatmap de una métrica para todas las combinaciones capa × configuración.

    Parameters
    -----
    metric : "silhouette" | "davies_bouldin" | "calinski_harabasz"
    """
    if class_name:
        df = metrics_df[metrics_df["class"] == class_name].copy()
    else:
        df = metrics_df.copy()

    df["config"] = df["method"] + " " + df["param"] + "=" + df["param_value"].astype(str)

    pivot = df.pivot_table(index="layer", columns="config",
                            values=metric, aggfunc="first")

    # Para DB, invertir la escala visualmente (menor = mejor = más oscuro)
    ascending = metric != "davies_bouldin"

    fig, ax = plt.subplots(figsize=(max(10, len(pivot.columns)), 4))
    sns.heatmap(
        pivot,
        annot=True, fmt=".4f",
        cmap="RdYlGn" if ascending else "RdYlGn_r",
        ax=ax,
        linewidths=0.5,
        cbar_kws={"label": metric}
    )
    title_note = "(↑ mejor)" if ascending else "(↓ mejor)"
    ax.set_title(f"{class_name or ''} - {metric} {title_note}", fontsize=13)
    ax.set_xlabel("")
    ax.set_ylabel("Capa")
    plt.xticks(rotation=30, ha="right")
    plt.tight_layout()
    plt.show()

```

## Caracterización espectral — profundidad de líneas Balmer por cluster

```

In [40]: BALMER_LINES = {
    'He': 3970,
    'Hδ': 4101,
    'Hγ': 4340,
    'Hβ': 4861,
    'Hα': 6563,
}

def _measure_line(flux, wave, center,
                  line_hw=20, cont_offset=50, cont_hw=25):
    wave = np.asarray(wave)
    flux = np.asarray(flux)

    line_mask = np.abs(wave - center) <= line_hw
    cont_mask = (
        ((wave >= center - cont_offset - cont_hw) & (wave <= center - cont_offset))
        ((wave >= center + cont_offset) & (wave <= center + cont_offset +
    )

    if line_mask.sum() == 0 or cont_mask.sum() == 0:
        return np.nan, np.nan

    F_cont = np.mean(flux[cont_mask])
    if F_cont == 0:
        return np.nan, np.nan

    F_line = flux[line_mask]
    W_line = wave[line_mask]
    depth = F_cont - np.min(F_line)
    d_lam = np.abs(np.gradient(W_line)).mean()
    ew = np.sum(np.clip(1.0 - F_line / F_cont, 0, None)) * d_lam
    return round(float(depth), 6), round(float(ew), 4)

def compute_balmer_depths(group_means, wavelength,
                           class_name, layer_name, method_name,
                           label_counts=None):
    """
    Calcula profundidad y pseudo-EW de lineas Balmer para cada cluster.

    group_means : dict {cluster_id: array espectro medio} <- viene de _plot_clust
    label_counts : dict {cluster_id: n_muestras} (opcional)

    Retorna pd.DataFrame filas=clusters, columnas=profundidad/EW por linea
    """
    wavelength = np.asarray(wavelength)
    rows = []

    for cid in sorted(group_means.keys()):
        mean_spec = np.asarray(group_means[cid])
        row = {
            'class' : class_name,
            'layer' : layer_name,
            'method' : method_name,

```

```

        'cluster': cid,
    }
    if label_counts is not None:
        row['n'] = label_counts.get(cid, None)

    for line_name, center in BALMER_LINES.items():
        if center < wavelength.min() or center > wavelength.max():
            row[f'{line_name}_depth'] = np.nan
            row[f'{line_name}_ew'] = np.nan
            continue
        depth, ew = _measure_line(mean_spec, wavelength, center)
        row[f'{line_name}_depth'] = depth
        row[f'{line_name}_ew'] = ew

    rows.append(row)

    return pd.DataFrame(rows)

def plot_balmer_comparison(balmer_df, metric='depth', figsize=(10, 4)):
    """
    Barras agrupadas: profundidad (o EW) de cada linea Balmer por cluster.
    metric : 'depth' o 'ew'
    """
    cols = [f'{ln}_{metric}' for ln in BALMER_LINES if f'{ln}_{metric}' in balmer_df]
    n_clusters = len(balmer_df)
    x = np.arange(len(cols))
    width = 0.8 / n_clusters
    cmap = plt.cm.get_cmap('tab10', n_clusters)

    fig, ax = plt.subplots(figsize=figsize)
    for i, (_, row) in enumerate(balmer_df.iterrows()):
        vals = [row[c] for c in cols]
        label = f"Cluster {int(row['cluster'])}"
        if 'n' in row and row['n'] is not None:
            label += f" (n={int(row['n'])})"
        ax.bar(x + i * width, vals, width=width, color=cmap(i), alpha=0.85, label=label)

    ax.set_xticks(x + width * (n_clusters - 1) / 2)
    ax.set_xticklabels([c.replace(f'_{metric}', '') for c in cols], fontsize=11)
    ax.set_ylabel('Profundidad (flux units)' if metric == 'depth' else 'Pseudo-EW')
    row0 = balmer_df.iloc[0]
    ax.set_title(f"Balmer {metric} por cluster - {row0['class']} | {row0['layer']}")
    ax.legend()
    plt.tight_layout(); plt.show()

```

## Estabilidad de clusters — ARI entre múltiples corridas

```

In [41]: from sklearn.metrics import adjusted_rand_score
        from itertools import combinations as _combinations

```

```

def _pairwise_ari(all_labels):
    pairs = list(_combinations(range(len(all_labels)), 2))
    return [adjusted_rand_score(all_labels[i], all_labels[j]) for i, j in pairs]

def test_kmeans_stability(features_32, k, class_name, layer_name,
                          n_runs=30, random_state_base=0):
    """
    Corre KMeans n_runs veces con semillas distintas.
    ARI ~ 1.0 => muy estable. ARI < 0.6 => inestable.
    """
    Xs = StandardScaler().fit_transform(features_32)
    all_labels = [
        KMeans(n_clusters=k, n_init=10, random_state=seed).fit_predict(Xs)
        for seed in range(random_state_base, random_state_base + n_runs)
    ]
    aris = _pairwise_ari(all_labels)
    mu, sd = np.mean(aris), np.std(aris)
    print(f"[{class_name} | {layer_name} | KMeans k={k}] "
          f"ARI = {mu:.3f} +/- {sd:.3f} "
          f"(min={min(aris):.3f}, max={max(aris):.3f}) [{n_runs} corridas]")
    return {'mean_ari': mu, 'std_ari': sd, 'all_ari': aris}

def test_spectral_stability(features_32, k, class_name, layer_name,
                             n_runs=20, random_state_base=0):
    """
    Corre SpectralClustering n_runs veces con semillas distintas.
    """
    Xs = StandardScaler().fit_transform(features_32)
    all_labels = [
        SpectralClustering(
            n_clusters=k, affinity='nearest_neighbors',
            assign_labels='kmeans', random_state=seed
        ).fit_predict(Xs)
        for seed in range(random_state_base, random_state_base + n_runs)
    ]
    aris = _pairwise_ari(all_labels)
    mu, sd = np.mean(aris), np.std(aris)
    print(f"[{class_name} | {layer_name} | Spectral k={k}] "
          f"ARI = {mu:.3f} +/- {sd:.3f} "
          f"(min={min(aris):.3f}, max={max(aris):.3f}) [{n_runs} corridas]")
    return {'mean_ari': mu, 'std_ari': sd, 'all_ari': aris}

def test_subsample_stability(features_32, cluster_func, class_name, layer_name,
                              n_runs=30, subsample_frac=0.80, random_state=42):
    """
    Estabilidad por submuestreo sin reposicion (recomendado para DBSCAN).
    cluster_func(Xs) -> labels (Xs ya escalado).
    """
    rng = np.random.default_rng(random_state)
    Xs = StandardScaler().fit_transform(features_32)
    n = Xs.shape[0]
    n_sub = int(n * subsample_frac)

```

```

runs = []
for _ in range(n_runs):
    idx = np.sort(rng.choice(n, size=n_sub, replace=False))
    labels = cluster_func(Xs[idx])
    runs.append((idx, labels))

aris = []
for (idx_i, lbl_i), (idx_j, lbl_j) in combinations(runs[:20], 2):
    common = np.intersect1d(idx_i, idx_j)
    if len(common) < 20:
        continue
    pos_i = np.searchsorted(idx_i, common)
    pos_j = np.searchsorted(idx_j, common)
    aris.append(adjusted_rand_score(lbl_i[pos_i], lbl_j[pos_j]))

if not aris:
    print(f"[{class_name} | {layer_name}] Sin pares comparables.")
    return {}

mu, sd = np.mean(aris), np.std(aris)
print(f"[{class_name} | {layer_name} | subsample {subsample_frac*100:.0f}%] "
      f"ARI = {mu:.3f} +/- {sd:.3f} "
      f"(min={min(aris):.3f}, max={max(aris):.3f}) [{n_runs} corridas]")
return {'mean_ari': mu, 'std_ari': sd, 'all_aris': aris}

def plot_ari_distribution(stability_result, title='Distribucion ARI', figsize=(7, 3)):
    aris = stability_result.get('all_aris', [])
    if not aris:
        return
    fig, ax = plt.subplots(figsize=figsize)
    ax.hist(aris, bins=20, color='steelblue', edgecolor='white', alpha=0.85)
    ax.axvline(np.mean(aris), color='red', linestyle='--',
               label=f'Media = {np.mean(aris):.3f}')
    ax.set_xlabel('ARI'); ax.set_ylabel('Frecuencia')
    ax.set_title(title); ax.legend()
    plt.tight_layout(); plt.show()

```

## Experimentos WDA

Usar n = 1100 muestras

```

In [42]: # Datos para DRACULA
X_wda_spec, X_wda_input, df_wda_DRAC = load_class_spectra_DRACULA("WDA", n_samples=
flatten_wda_DRAC, dense_wda_DRAC, dense1_wda_DRAC, dense2_wda_DRAC = extract_layer_
repr_wda_32 = reduce_all_to_32(flatten_wda_DRAC, dense_wda_DRAC, dense1_wda_DRAC, d

```

```

WDA: disponibles con match a .dat = 13723
WDA: espectros válidos finales = 1100
18/18 ————— 1s 24ms/step
18/18 ————— 1s 25ms/step
18/18 ————— 1s 23ms/step
18/18 ————— 0s 23ms/step
flatten: (1100, 208)
dense: (1100, 128)
dense_1: (1100, 64)
dense_2: (1100, 32)
flatten_32: (1100, 32)
dense_32: (1100, 32)
dense1_32: (1100, 32)
dense2_32: (1100, 32)

```

## Usar n = 13723 muestras (el total)

```

In [43]: # Datos para DRACULA
X_wda_spec_n2, X_wda_input_n2, df_wda_DRAC_n2 = load_class_spectra_DRACULA("WDA", n
flatten_wda_DRAC_n2, dense_wda_DRAC_n2, dense1_wda_DRAC_n2, dense2_wda_DRAC_n2 = ex
repr_wda_32_n2 = reduce_all_to_32(flatten_wda_DRAC_n2, dense_wda_DRAC_n2, dense1_wd

```

```

WDA: disponibles con match a .dat = 13723
WDA: espectros válidos finales = 13711
215/215 ————— 4s 20ms/step
215/215 ————— 5s 21ms/step
215/215 ————— 4s 20ms/step
215/215 ————— 4s 20ms/step
flatten: (13711, 208)
dense: (13711, 128)
dense_1: (13711, 64)
dense_2: (13711, 32)
flatten_32: (13711, 32)
dense_32: (13711, 32)
dense1_32: (13711, 32)
dense2_32: (13711, 32)





```

## Evaluación con Silhouette (n=1100)

```

In [44]: evaluate_kmeans_k(repr_wda_32["flatten"], "WDA", "flatten")
evaluate_kmeans_k(repr_wda_32["dense"], "WDA", "dense")
evaluate_kmeans_k(repr_wda_32["dense_1"], "WDA", "dense_1")
evaluate_kmeans_k(repr_wda_32["dense_2"], "WDA", "dense_2")


```



## Evaluación con Silhouette (n=13723)

```
In [45]: evaluate_kmeans_k(repr_wda_32_n2["flatten"], "WDA", "flatten")
          evaluate_kmeans_k(repr_wda_32_n2["dense"], "WDA", "dense")
```

```
evaluate_kmeans_k(repr_wda_32_n2["dense_1"], "WDA", "dense_1")  
evaluate_kmeans_k(repr_wda_32_n2["dense_2"], "WDA", "dense_2")
```




Gráficos t-SNE y PCA -> para Spectral Clustering y DBSCAN




## Resultados capa flatten, con Spectral Clustering + tSNE y PCA para n=1100

```
In [46]: res_k3=cluster_plot_Spect(
    repr_wda_32["flatten"],
    "WDA",
    "flatten",
    spectral_k=3,
    vis_method="tsne",
    container=cluster_labels_all
)

labels_flatten_k3 = res_k3["spectral"]
cluster_plot_Spect(
    repr_wda_32["flatten"],
    "WDA",
    "flatten",
    spectral_k=3,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10)
)
```



|            |  |         |  |             |  |                    |
|------------|--|---------|--|-------------|--|--------------------|
| WDA        |  | flatten |  | spectral    |  | k=3                |
| clusters=3 |  | noise=0 |  | sil=-0.0472 |  | DB=2.6617 CH=20.24 |




```
WDA | flatten | spectral | k=3
clusters=3 noise=0 sil=-0.0472 DB=2.6617 CH=20.24
```


```
Out[46]: {'spectral': array([0, 1, 0, ..., 0, 0, 0]),
'metrics': {'n_clusters': 3,
'n_noise': 0,
'silhouette': -0.047206,
'davies_bouldin': 2.661654,
'calinski_harabasz': 20.2384}}
```

## Spectral Clustering k = 4

```
In [47]: res_k4 = cluster_plot_Spect(
    repr_wda_32["flatten"],
    "WDA",
    "flatten",
    spectral_k=4,
    vis_method="tsne",
    container=cluster_labels_all
)
labels_flatten_k4 = res_k4["spectral"]
cluster_plot_Spect(
    repr_wda_32["flatten"],
    "WDA",
    "flatten",
    spectral_k=4,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10)
)
```



```
WDA | flatten | spectral | k=4  
clusters=4 noise=0 sil=-0.0258 DB=3.3007 CH=18.87
```



|                                                                                     |
|-------------------------------------------------------------------------------------|
| WDA   flatten   spectral   k=4<br>clusters=4 noise=0 sil=-0.0258 DB=3.3007 CH=18.87 |
|-------------------------------------------------------------------------------------|


```
Out[47]: {'spectral': array([3, 1, 3, ..., 3, 3, 3]),
'metrics': {'n_clusters': 4,
'n_noise': 0,
'silhouette': -0.025797,
'davies_bouldin': 3.300675,
'calinski_harabasz': 18.8727}}
```

## Spectral Clustering k = 2


```
In [48]: res_k2 = cluster_plot_Spect(
    repr_wda_32["flatten"],
    "WDA",
    "flatten",
    spectral_k=2,
    vis_method="tsne",
    container=cluster_labels_all
)

labels_flatten_k2 = res_k2["spectral"]

cluster_plot_Spect(
    repr_wda_32["flatten"],
    "WDA",
    "flatten",
    spectral_k=2,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10)
)
```



```
WDA | flatten | spectral | k=2  
clusters=2 noise=0 sil=0.0668 DB=2.2879 CH=21.49
```



```
WDA | flatten | spectral | k=2
clusters=2 noise=0 sil=0.0668 DB=2.2879 CH=21.49
```

```
Out[48]: {'spectral': array([0, 0, 0, ..., 0, 0, 0]),
          'metrics': {'n_clusters': 2,
                      'n_noise': 0,
                      'silhouette': 0.066835,
                      'davies_bouldin': 2.287926,
                      'calinski_harabasz': 21.4947}}
```

## Análisis de migración de clústeres

Se compara cómo los datos migran entre las configuraciones  $k=2$ ,  $k=3$  y  $k=4$ .


La matriz cuenta cuántas muestras compartidas hay entre cada par de clústeres.


Comparaciones realizadas:  $k=2 \rightarrow k=3$ ,  $k=3 \rightarrow k=4$ , y  $k=2 \rightarrow k=4$ .

```
In [49]: print(f'Muestras en variables - k=2: {np.bincount(labels_flatten_k2)}')
          print(f'Muestras en variables - k=3: {np.bincount(labels_flatten_k3)}')
          print(f'Muestras en variables - k=4: {np.bincount(labels_flatten_k4)}')


          plot_migration_matrix(labels_flatten_k2, labels_flatten_k3, ka=2, kb=3)
          plot_migration_matrix(labels_flatten_k3, labels_flatten_k4, ka=3, kb=4)
          plot_migration_matrix(labels_flatten_k2, labels_flatten_k4, ka=2, kb=4)
```

```
Muestras en variables - k=2: [1028  72]
Muestras en variables - k=3: [908 140  52]
Muestras en variables - k=4: [ 97 249  51 703]
```













### Espectros obtenidos de Spectral Clustering para k=3 y n=1100


```
In [50]: result = plot_spectra_spectral(X_wda_spec, labels_flatten_k3, W_wda[0],
...                                     class_name="WDA", layer_name="flatten")
...
label_counts = {c: int(np.sum(labels_flatten_k3 == c))
                 for c in np.unique(labels_flatten_k3)}
balmer_df = compute_balmer_depths(result['group_means'], W_wda[0],
                                   'WDA', 'flatten', 'spectral',
                                   label_counts=label_counts)
print(balmer_df.to_string(index=False))
plot_balmer_comparison(balmer_df, metric='depth')
plot_balmer_comparison(balmer_df, metric='ew')
...
```

C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```









```
Out[50]: "\nlabel_counts = {c: int(np.sum(labels_flatten_k3 == c)) \n          for c
in np.unique(labels_flatten_k3)}\nbalmer_df = compute_balmer_depths(result['group_
means'], W_wda[0],\n          'WDA', 'flatten', 'spectra
1',\n          label_counts=label_counts)\nprint(balmer_d
f.to_string(index=False))\nplot_balmer_comparison(balmer_df, metric='depth')\nplot
_balmer_comparison(balmer_df, metric='ew')\n"
```




### Espectros obtenidos de Spectral Clustering para k=4 y n=1100


```
In [51]: plot_spectra_spectral(
            X_wda_spec,
            labels_flatten_k4,
            W_wda[0],
            class_name="WDA",
            layer_name="flatten"
        )
```

```
C:\Users\javip\AppData\Local\Temp\ipykernel_6108\531566132.py:28: MatplotlibDeprecationWarning: The get_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get_cmap()`` or ``pyplot.get_cmap()`` instead.
    cmap = plt.cm.get_cmap("tab10", n_clusters)
```









```
Out[51]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
      0.34358275], dtype=float32),
          'group_means': {0: array([1.1657348 , 1.1637619 , 1.0596358 , ..., 0.5476993 , 0.
5519154 ,
      0.58027047], dtype=float32),
      1: array([2.0275433 , 2.11929 , 2.0890515 , ..., 0.28720883, 0.27873743,
      0.4125563 ], dtype=float32),
      2: array([5.8058877 , 5.789854 , 5.8244348 , ..., 0.25032267, 0.23638035,
      0.31707752], dtype=float32),
      3: array([2.845378 , 2.7164657 , 2.743732 , ..., 0.34086254, 0.23727994,
      0.28841776], dtype=float32)},
          'unique_clusters': array([0, 1, 2, 3])}
```




## Espectros obtenidos de Spectral Clustering para k=2 y n=1100




```
In [52]: plot_spectra_spectral(
          X_wda_spec,
          labels_flatten_k2,
          W_wda[0],
          class_name="WDA",
          layer_name="flatten"
        )
```

C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```







```
Out[52]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
      805,
      0.34358275], dtype=float32),
      'group_means': {0: array([2.455049 , 2.385652 , 2.3867228 , ..., 0.34960037, 0.
      27687111,
      0.34664583], dtype=float32),
      1: array([5.424247 , 5.4596367 , 5.4902544 , ..., 0.24507414, 0.23862773,
      0.29984945], dtype=float32)},
      'unique_clusters': array([0, 1])}
```

## Interactive de espectros obtenidos para los 3 métodos y permite seleccionar si se aplica la varianza o no

```
In [53]: interactive_plot_cluster_spectra(
      spectra_2d=X_wda_spec,
      wavelength=W_wda[0],
      class_name="WDA",
      container=cluster_labels_all
    )
```

```
interactive(children=(Dropdown(description='Capa:', options=('flatten',), value='fla
tten'), Dropdown(descripti...
```


```
In [54]: '''
      stab = test_spectral_stability(repr_wda_32["flatten"], k=3,
                                   class_name="WDA", layer_name="flatten")
      plot_ari_distribution(stab, title="Spectral Clustering k=3 - flatten WDA")
      '''
```

```
Out[54]: '\nstab = test_spectral_stability(repr_wda_32["flatten"], k=3, \n
      class_name="WDA", layer_name="flatten")\nplot_ari_distribution(stab, title="Spectr
al Clustering k=3 - flatten WDA")\n'
```


## DBSCAN

```
In [55]: res_dbs_flatten = cluster_plot_DBSCAN(
      repr_wda_32["flatten"],
      "WDA",
      "flatten",
      dbscan_eps=1.5,
      dbscan_min_samples=10,
      vis_method="tsne",
      xlim=None,
      ylim=None,
      container=cluster_labels_all
    )
      labels_dbs_flatten = res_dbs_flatten["dbscan"]
      cluster_plot_DBSCAN(
      repr_wda_32["flatten"],
      "WDA",
      "flatten",
      dbscan_eps=1.5,
      dbscan_min_samples=10,
      vis_method="pca",
      xlim=None,
```

```
ylim=None,  
container=cluster_labels_all  
)
```



```
WDA | flatten | dbscan | eps=1.5  
clusters=1 noise=790 sil=N/A DB=N/A CH=N/A  
DBCV = N/A (rango [-1,1], específico DBSCAN)
```



```
WDA | flatten | dbscan | eps=1.5
clusters=1 noise=790 sil=N/A DB=N/A CH=N/A
DBCV = N/A (rango [-1,1], específico DBSCAN)
```


```
Out[55]: {'dbscan': array([ 0, -1, -1, ..., -1, -1, -1], dtype=int64),
'metrics': {'n_clusters': 1,
'n_noise': 790,
'silhouette': None,
'davies_bouldin': None,
'calinski_harabasz': None},
'dbcv': nan}
```




## Espectros obtenidos de DBSCAN n=1100

```
In [56]: plot_spectra_dbscan(
X_wda_spec,
labels_dbs_flatten,
W_wda[0],
class_name="WDA",
layer_name="flatten"
)
```

C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```





```
Out[56]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
      805,
      0.34358275], dtype=float32),
      'group_means': {-1: array([2.8365166 , 2.7472477 , 2.7545357 , ..., 0.34455824,
      0.25810513,
      0.3559137 ], dtype=float32),
      0: array([2.1725419 , 2.1781251 , 2.1702151 , ..., 0.3381723 , 0.31581163,
      0.31215957], dtype=float32)}},
      'unique_clusters': array([-1,  0], dtype=int64)}
```

```
In [57]: '''
stab = test_subsample_stability(repr_wda_32["flatten"], lambda Xs: DBSCAN(eps=1.5,
                                class_name="WDA", layer_name="flatten")
plot_ari_distribution(stab, title="DBSCAN - flatten WDA")
'''
```


```
Out[57]: '\nstab = test_subsample_stability(repr_wda_32["flatten"], lambda Xs: DBSCAN(eps=
1.5, min_samples=10).fit_predict(Xs), \n                                class_name
="WDA", layer_name="flatten")\nplot_ari_distribution(stab, title="DBSCAN - flatten
WDA")\n'
```

## Resultados capa flatten, con Spectral Clustering + tSNE y PCA para n=13723


### Spectral Clustering k = 3

```
In [58]: res_k3_n2=cluster_plot_Spect(
            repr_wda_32_n2["flatten"],
            "WDA",
            "flatten",
            spectral_k=3,
            vis_method="tsne",
            container=cluster_labels_all_n2
        )
labels_flatten_k3_n2 = res_k3_n2["spectral"]
cluster_plot_Spect(
            repr_wda_32_n2["flatten"],
            "WDA",
            "flatten",
            spectral_k=3,
            vis_method="pca",
            xlim=(-10,10), ylim=(-10,10),
            container=cluster_labels_all_n2
        )
```





```
WDA | flatten | spectral | k=3  
clusters=3 noise=0 sil=0.1009 DB=2.6087 CH=229.35
```




```
WDA | flatten | spectral | k=3
clusters=3 noise=0 sil=0.1009 DB=2.6087 CH=229.35
```


```
Out[58]: {'spectral': array([0, 2, 2, ..., 0, 0, 0]),
          'metrics': {'n_clusters': 3,
                      'n_noise': 0,
                      'silhouette': 0.100929,
                      'davies_bouldin': 2.608655,
                      'calinski_harabasz': 229.3457}}
```

## Spectral Clustering k = 4

```
In [59]: res_k4_n2=cluster_plot_Spect(
            repr_wda_32_n2["flatten"],
            "WDA",
            "flatten",
            spectral_k=4,
            vis_method="tsne",
            container=cluster_labels_all_n2
        )
labels_flatten_k4_n2 = res_k4_n2["spectral"]
cluster_plot_Spect(
    repr_wda_32_n2["flatten"],
    "WDA",
    "flatten",
    spectral_k=4,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all_n2
)
```



```
WDA | flatten | spectral | k=4  
clusters=4 noise=0 sil=0.0862 DB=2.3763 CH=205.06
```



|                                                                                     |
|-------------------------------------------------------------------------------------|
| WDA   flatten   spectral   k=4<br>clusters=4 noise=0 sil=0.0862 DB=2.3763 CH=205.06 |
|-------------------------------------------------------------------------------------|


```
Out[59]: {'spectral': array([1, 0, 0, ..., 1, 1, 1]),
          'metrics': {'n_clusters': 4,
                      'n_noise': 0,
                      'silhouette': 0.086196,
                      'davies_bouldin': 2.376256,
                      'calinski_harabasz': 205.0587}}
```

## Spectral Clustering k = 2


```
In [60]: res_k2_n2 = cluster_plot_Spect(
            repr_wda_32_n2["flatten"],
            "WDA",
            "flatten",
            spectral_k=2,
            vis_method="tsne",
            container=cluster_labels_all_n2
        )

labels_flatten_k2_n2 = res_k2_n2["spectral"]

cluster_plot_Spect(
    repr_wda_32_n2["flatten"],
    "WDA",
    "flatten",
    spectral_k=2,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all_n2
)
```



```
WDA | flatten | spectral | k=2  
clusters=2 noise=0 sil=0.1542 DB=2.1674 CH=203.45
```



```
WDA | flatten | spectral | k=2
clusters=2 noise=0 sil=0.1542 DB=2.1674 CH=203.45
```


```
Out[60]: {'spectral': array([0, 0, 0, ..., 0, 0, 0]),
'metrics': {'n_clusters': 2,
'n_noise': 0,
'silhouette': 0.15423,
'davies_bouldin': 2.167417,
'calinski_harabasz': 203.4486}}
```


## Análisis de migración


```
In [61]: print(f'Muestras en variables - k=2: {np.bincount(labels_flatten_k2_n2)}')
print(f'Muestras en variables - k=3: {np.bincount(labels_flatten_k3_n2)}')
print(f'Muestras en variables - k=4: {np.bincount(labels_flatten_k4_n2)}')

plot_migration_matrix(labels_flatten_k2_n2, labels_flatten_k3_n2, ka=2, kb=3)
plot_migration_matrix(labels_flatten_k3_n2, labels_flatten_k4_n2, ka=3, kb=4)
plot_migration_matrix(labels_flatten_k2_n2, labels_flatten_k4_n2, ka=2, kb=4)
```

```
Muestras en variables - k=2: [12778  933]
Muestras en variables - k=3: [10285  1008  2418]
Muestras en variables - k=4: [ 2411 10257  922  121]
```










### Espectros obtenidos de Spectral Clustering para k=3 y n=13723




```
In [62]: plot_spectra_spectral(
    X_wda_spec_n2,
    labels_flatten_k3_n2,
    W_wda_n2[0],
    class_name="WDA",
    layer_name="flatten"
)
```



C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```












```
Out[62]: {'total_mean': array([2.5934331 , 2.626327 , 2.659192 , ..., 0.33381772, 0.30658
45 ,
        0.30957362], dtype=float32),
        'group_means': {0: array([2.5592344 , 2.608826 , 2.6437016 , ..., 0.29355285, 0.
27487236,
        0.2800041 ], dtype=float32),
        1: array([5.6649585 , 5.576642 , 5.523734 , ..., 0.2813838 , 0.23965177,
        0.24696966], dtype=float32),
        2: array([1.4584777 , 1.4708396 , 1.5309051 , ..., 0.5269406 , 0.4693723 ,
        0.46144333], dtype=float32)},
        'unique_clusters': array([0, 1, 2])}
```




## Espectros obtenidos de Spectral Clustering para k=4 y n=13723




```
In [63]: plot_spectra_spectral(
        X_wda_spec_n2,
        labels_flatten_k4_n2,
        W_wda_n2[0],
        class_name="WDA",
        layer_name="flatten"
    )
```


C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```












```
Out[63]: {'total_mean': array([2.5934331 , 2.626327 , 2.659192 , ..., 0.33381772, 0.30658
45 ,
      0.30957362], dtype=float32),
          'group_means': {0: array([1.461678 , 1.4912118 , 1.5468113 , ..., 0.53083587, 0.
47639927,
      0.47161406], dtype=float32),
      1: array([2.5525174 , 2.5947871 , 2.6296654 , ..., 0.2927134 , 0.27382073,
      0.2773593 ], dtype=float32),
      2: array([5.3857694 , 5.3072686 , 5.3410916 , ..., 0.24822943, 0.22407 ,
      0.24253443], dtype=float32),
      3: array([7.335885 , 7.489136 , 6.8908415 , ..., 0.5445756 , 0.32893983,
      0.32234848], dtype=float32)},
          'unique_clusters': array([0, 1, 2, 3])}
```

## Espectros obtenidos de Spectral Clustering para k=2 y n=13723




```
In [64]: plot_spectra_spectral(
          X_wda_spec_n2,
          labels_flatten_k2_n2,
          W_wda_n2[0],
          class_name="WDA",
          layer_name="flatten"
        )
```

C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```








```
Out[64]: {'total_mean': array([2.5934331 , 2.626327 , 2.659192 , ..., 0.33381772, 0.30658
45 ,
      0.30957362], dtype=float32),
      'group_means': {0: array([2.366988 , 2.4095309 , 2.4493794 , ..., 0.33739284, 0.
31091052,
      0.31333855], dtype=float32),
      1: array([5.694797 , 5.5954156 , 5.5326786 , ..., 0.28484887, 0.24734011,
      0.25800306], dtype=float32)},
      'unique_clusters': array([0, 1])}
```


## DBSCAN n=13723

```
In [65]: res_dbs_flatten_n2 = cluster_plot_DBSCAN(
      repr_wda_32_n2["flatten"],
      "WDA",
      "flatten",
      dbscan_eps=1.5,
      dbscan_min_samples=10,
      vis_method="tsne",
      xlim=None,
      ylim=None,
      container=cluster_labels_all_n2
    )
labels_dbs_flatten_n2 = res_dbs_flatten_n2["dbscan"]
cluster_plot_DBSCAN(
      repr_wda_32_n2["flatten"],
      "WDA",
      "flatten",
      dbscan_eps=1.5,
      dbscan_min_samples=10,
      vis_method="pca",
      xlim=None,
      ylim=None,
      container=cluster_labels_all_n2
    )
```



[DBCV omitido: 8677 puntos no-ruido > 5000]

```
WDA | flatten | dbscan | eps=1.5  
clusters=2 noise=5034 sil=0.2228 DB=1.0393 CH=15.24
```



[DBCV omitido: 8677 puntos no-ruído > 5000]

```
WDA | flatten | dbscan | eps=1.5
clusters=2 noise=5034 sil=0.2228 DB=1.0393 CH=15.24
```


```
Out[65]: {'dbscan': array([ 0,  0,  0, ..., -1,  0,  0], dtype=int64),
          'metrics': {'n_clusters': 2,
                      'n_noise': 5034,
                      'silhouette': 0.222837,
                      'davies_bouldin': 1.039314,
                      'calinski_harabasz': 15.2426},
          'dbcv': None}
```


## Espectros obtenidos de DBSCAN n=1100




```
In [66]: plot_spectra_dbscan(
          X_wda_spec_n2,
          labels_dbs_flatten_n2,
          W_wda_n2[0],
          class_name="WDA",
          layer_name="flatten"
        )
```


C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```










```
Out[66]: {'total_mean': array([2.5934331 , 2.626327 , 2.659192 , ..., 0.33381772, 0.30658
45 ,
      0.30957362], dtype=float32),
          'group_means': {-1: array([2.7815535 , 2.8900955 , 2.9436584 , ..., 0.31576797,
0.28334725,
      0.3002083 ], dtype=float32),
      0: array([2.4849486 , 2.473893 , 2.495432 , ..., 0.34429717, 0.31994784,
      0.31486255], dtype=float32),
      1: array([1.7804801 , 1.8268033 , 1.1103698 , ..., 0.3349731 , 0.44740748,
      0.47129342], dtype=float32)},
          'unique_clusters': array([-1,  0,  1], dtype=int64)}
```

## Resultados capa dense con Spectral Clustering + tSNE y PCA


### Spectral Clustering k = 3

```
In [67]: res_dense_k3 = cluster_plot_Spect(
          repr_wda_32["dense"],
          "WDA",
          "dense",
          spectral_k=3,
          vis_method="tsne",
          container=cluster_labels_all
        )
labels_dense_k3 = res_dense_k3["spectral"]

cluster_plot_Spect(
    repr_wda_32["dense"],
    "WDA",
    "dense",
    spectral_k=3,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



```
WDA | dense | spectral | k=3  
clusters=3 noise=0 sil=-0.0692 DB=4.2574 CH=22.01
```





```
WDA | dense | spectral | k=3
clusters=3 noise=0 sil=-0.0692 DB=4.2574 CH=22.01
```


```
Out[67]: {'spectral': array([0, 1, 0, ..., 0, 0, 0]),
          'metrics': {'n_clusters': 3,
                      'n_noise': 0,
                      'silhouette': -0.069202,
                      'davies_bouldin': 4.257357,
                      'calinski_harabasz': 22.0086}}
```


## Espectros obtenidos para dense de Spectral Clustering k = 3 y n = 1100




```
In [68]: plot_spectra_spectral(
          X_wda_spec,
          labels_dense_k3,
          W_wda[0],
          class_name="WDA",
          layer_name="dense"
        )
```


C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```










```
Out[68]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
      0.34358275]), dtype=float32),
  'group_means': {0: array([2.4774532 , 2.3956044 , 2.4117315 , ..., 0.35623387, 0.
26840338,
      0.3001185 ], dtype=float32),
    1: array([2.5829918, 2.5118012, 2.4566152, ..., 0.3786638, 0.3261105,
      0.5187181], dtype=float32),
    2: array([3.530849 , 3.5693934 , 3.6146684 , ..., 0.2205062 , 0.21133548,
      0.23398872], dtype=float32)},
  'unique_clusters': array([0, 1, 2])}
```

## Spectral Clustering k = 2


```
In [69]: res_dense_k2 = cluster_plot_Spect(
    repr_wda_32["dense"],
    "WDA",
    "dense",
    spectral_k=2,
    vis_method="tsne",
    container=cluster_labels_all
)

labels_dense_k2 = res_dense_k2["spectral"]

cluster_plot_Spect(
    repr_wda_32["dense"],
    "WDA",
    "dense",
    spectral_k=2,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



```
WDA | dense | spectral | k=2  
clusters=2 noise=0 sil=0.0973 DB=5.0157 CH=23.59
```



```
WDA | dense | spectral | k=2
clusters=2 noise=0 sil=0.0973 DB=5.0157 CH=23.59
```


```
Out[69]: {'spectral': array([0, 1, 0, ..., 0, 0, 0]),
          'metrics': {'n_clusters': 2,
                      'n_noise': 0,
                      'silhouette': 0.097317,
                      'davies_bouldin': 5.01569,
                      'calinski_harabasz': 23.5887}}
```


## Espectros obtenidos para dense con Spectral Clustering k = 2 y n = 1100



```
In [70]: plot_spectra_spectral(
          X_wda_spec,
          labels_dense_k2,
          W_wda[0],
          class_name="WDA",
          layer_name="dense"
        )
```

C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```







```
Out[70]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
        0.34358275], dtype=float32),
        'group_means': {0: array([2.6778753 , 2.6653168 , 2.6782897 , ..., 0.30306715, 0.
24021257,
        0.2645366 ], dtype=float32),
        1: array([2.5857353 , 2.411487 , 2.3922002 , ..., 0.43148127, 0.35071507,
        0.52027524], dtype=float32)},
        'unique_clusters': array([0, 1])}
```


## Spectral Clustering k = 4

```
In [71]: res_dense_k4 = cluster_plot_Spect(
        repr_wda_32["dense"],
        "WDA",
        "dense",
        spectral_k=4,
        vis_method="tsne",
        container=cluster_labels_all
    )


labels_dense_k4 = res_dense_k4["spectral"]
```



```
cluster_plot_Spect(  
    repr_wda_32["dense"],  
    "WDA",  
    "dense",  
    spectral_k=4,  
    vis_method="pca",  
    xlim=(-10,10), ylim=(-10,10),  
    container=cluster_labels_all  
)
```



|            |         |             |                    |
|------------|---------|-------------|--------------------|
| WDA        | dense   | spectral    | k=4                |
| clusters=4 | noise=0 | sil=-0.0642 | DB=4.0526 CH=21.47 |



```
WDA | dense | spectral | k=4
clusters=4 noise=0 sil=-0.0642 DB=4.0526 CH=21.47
```


```
Out[71]: {'spectral': array([0, 1, 1, ..., 1, 0, 1]),
          'metrics': {'n_clusters': 4,
                      'n_noise': 0,
                      'silhouette': -0.064243,
                      'davies_bouldin': 4.052599,
                      'calinski_harabasz': 21.474}}
```


## Espectros obtenidos para dense con Spectral Clustering k = 4 y n = 1100




```
In [72]: plot_spectra_spectral(
          X_wda_spec,
          labels_dense_k4,
          W_wda[0],
          class_name="WDA",
          layer_name="dense"
        )
```


C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```










```
Out[72]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
      0.34358275], dtype=float32),
          'group_means': {0: array([2.2014093 , 2.158382 , 2.2005947 , ..., 0.2949068 , 0.
25243846,
      0.25418982], dtype=float32),
      1: array([3.0813384 , 2.9562492 , 2.8712096 , ..., 0.40471596, 0.28300285,
      0.42386907], dtype=float32),
      2: array([1.3363804 , 1.2859322 , 1.4931991 , ..., 0.45842224, 0.45111826,
      0.56841254], dtype=float32),
      3: array([3.5727167 , 3.638489 , 3.6614907 , ..., 0.2230357 , 0.20094702,
      0.22675993], dtype=float32)},
          'unique_clusters': array([0, 1, 2, 3])}
```

## Spectral Clustering k = 5


```
In [73]: res_dense_k5= cluster_plot_Spect(
          repr_wda_32["dense"],
          "WDA",
          "dense",
          spectral_k=5,
          vis_method="tsne",
          container=cluster_labels_all
        )

labels_dense_k5 = res_dense_k5["spectral"]
cluster_plot_Spect(
    repr_wda_32["dense"],
    "WDA",
    "dense",
    spectral_k=5,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



WDA | dense | spectral | k=5

clusters=5 noise=0 sil=-0.0577 DB=3.8201 CH=20.76



```
WDA | dense | spectral | k=5
clusters=5 noise=0 sil=-0.0577 DB=3.8201 CH=20.76
```


```
Out[73]: {'spectral': array([0, 1, 1, ..., 1, 4, 4]),
          'metrics': {'n_clusters': 5,
                      'n_noise': 0,
                      'silhouette': -0.057705,
                      'davies_bouldin': 3.820103,
                      'calinski_harabasz': 20.7556}}
```

## Espectros obtenidos para dense con Spectral Clustering k = 5 y n = 1100


```
In [74]: plot_spectra_spectral(
          X_wda_spec,
          labels_dense_k5,
          W_wda[0],
          class_name="WDA",
          layer_name="dense"
        )
```


C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.




```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```

















```
Out[74]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
      0.34358275], dtype=float32),
  'group_means': {0: array([2.2097285 , 2.2039099 , 2.2040193 , ..., 0.31043428, 0.
3021945 ,
      0.31198978], dtype=float32),
    1: array([3.0544236 , 2.8907533 , 2.8173532 , ..., 0.4029806 , 0.316814 ,
      0.46407264], dtype=float32),
    2: array([1.3363804 , 1.2859322 , 1.4931991 , ..., 0.45842224, 0.45111826,
      0.56841254], dtype=float32),
    3: array([3.6623926 , 3.7046065 , 3.7464252 , ..., 0.22301494, 0.20047829,
      0.21942586], dtype=float32),
    4: array([2.4171212 , 2.394776 , 2.417792 , ..., 0.30506536, 0.181159 ,
      0.20035149], dtype=float32)},
  'unique_clusters': array([0, 1, 2, 3, 4])}
```


## Análisis de migración

```
In [75]: plot_migration_matrix(labels_dense_k2, labels_dense_k3, ka=2, kb=3, title='Migració
plot_migration_matrix(labels_dense_k3, labels_dense_k4, ka=3, kb=4, title='Migració
plot_migration_matrix(labels_dense_k2, labels_dense_k4, ka=2, kb=4, title='Migració
plot_migration_matrix(labels_dense_k4, labels_dense_k5, ka=4, kb=5, title='Migració
```











## DBSCAN

```
In [76]: res_dbs_dense = cluster_plot_DBSCAN(
    repr_wda_32["dense"],
    "WDA",
    "dense",
    dbscan_eps=1.5,
    dbscan_min_samples=10,
    vis_method="tsne",
    xlim=None,
    ylim=None,
    container=cluster_labels_all
)
labels_dbs_dense = res_dbs_dense["dbscan"]
cluster_plot_DBSCAN(
    repr_wda_32["dense"],
    "WDA",
    "dense",
    dbscan_eps=1.5,
    dbscan_min_samples=10,
    vis_method="pca",
    xlim=None,
    ylim=None,
    container=cluster_labels_all
)
```












```
WDA | dense | dbscan | eps=1.5  
clusters=3 noise=1030 sil=0.2891 DB=1.2437 CH=25.64  
DBCV = -0.2465 (rango [-1,1], específico DBSCAN)
```











```
Out[77]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
      805,
      0.34358275], dtype=float32),
      'group_means': {-1: array([2.6932576 , 2.6272886 , 2.636244 , ..., 0.34091115,
      0.2691639 ,
      0.34351528], dtype=float32),
      0: array([1.746611 , 1.7625626 , 1.6311738 , ..., 0.4074069 , 0.39039117,
      0.3910139 ], dtype=float32),
      1: array([1.9773873 , 1.9530846 , 1.9307591 , ..., 0.3325621 , 0.3242443 ,
      0.30534068], dtype=float32),
      2: array([3.1846838 , 3.0811136 , 3.047346 , ..., 0.29898563, 0.24524586,
      0.23926459], dtype=float32)},
      'unique_clusters': array([-1,  0,  1,  2], dtype=int64)}
```


## Espectros de cada grupo

## Resultados capa dense\\_1 con Spectral Clustering + tSNE y PCA


### Spectral Clustering k = 3

```
In [78]: cluster_plot_Spect(
      repr_wda_32["dense_1"],
      "WDA",
      "dense_1",
      spectral_k=3,
      vis_method="tsne",
      container=cluster_labels_all
    )

cluster_plot_Spect(
      repr_wda_32["dense_1"],
      "WDA",
      "dense_1",
      spectral_k=3,
      vis_method="pca",
      xlim=(-10,10), ylim=(-10,10),
      container=cluster_labels_all
    )
```



```
WDA | dense_1 | spectral | k=3  
clusters=3 noise=0 sil=0.0238 DB=4.4005 CH=24.49
```




```
WDA | dense_1 | spectral | k=3  
clusters=3 noise=0 sil=0.0238 DB=4.4005 CH=24.49
```

```
Out[78]: {'spectral': array([0, 1, 2, ..., 1, 2, 2]),  
         'metrics': {'n_clusters': 3,  
                    'n_noise': 0,  
                    'silhouette': 0.023817,  
                    'davies_bouldin': 4.400539,  
                    'calinski_harabasz': 24.4928}}
```


## Spectral Clustering k = 2

```
In [79]: cluster_plot_Spect(  
         repr_wda_32["dense_1"],  
         "WDA",  
         "dense_1",  
         spectral_k=2,  
         vis_method="tsne",  
         container=cluster_labels_all  
       )  
  
cluster_plot_Spect(  
         repr_wda_32["dense_1"],  
         "WDA",  
         "dense_1",  
         spectral_k=2,  
         vis_method="pca",  
         xlim=(-10,10), ylim=(-10,10),  
         container=cluster_labels_all  
       )
```





```
WDA | dense_1 | spectral | k=2  
clusters=2 noise=0 sil=0.0831 DB=5.1219 CH=25.13
```




```
WDA | dense_1 | spectral | k=2
clusters=2 noise=0 sil=0.0831 DB=5.1219 CH=25.13
```

```
Out[79]: {'spectral': array([0, 1, 1, ..., 1, 0, 0]),
          'metrics': {'n_clusters': 2,
                      'n_noise': 0,
                      'silhouette': 0.083096,
                      'davies_bouldin': 5.12186,
                      'calinski_harabasz': 25.1293}}
```


## Spectral Clustering k = 4

```
In [80]: cluster_plot_Spect(
          repr_wda_32["dense_1"],
          "WDA",
          "dense_1",
          spectral_k=4,
          vis_method="tsne",
          container=cluster_labels_all
        )

cluster_plot_Spect(
    repr_wda_32["dense_1"],
    "WDA",
    "dense_1",
    spectral_k=4,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



```
WDA | dense_1 | spectral | k=4  
clusters=4 noise=0 sil=-0.0056 DB=4.1062 CH=22.98
```




|                                                   |
|---------------------------------------------------|
| WDA   dense_1   spectral   k=4                    |
| clusters=4 noise=0 sil=-0.0056 DB=4.1062 CH=22.98 |


```
Out[80]: {'spectral': array([1, 2, 3, ..., 0, 3, 0]),
'metrics': {'n_clusters': 4,
'n_noise': 0,
'silhouette': -0.005627,
'davies_bouldin': 4.106197,
'calinski_harabasz': 22.9831}}
```

## DBSCAN n = 1100




```
In [81]: res_dbs_dense1 = cluster_plot_DBSCAN(
    repr_wda_32["dense_1"],
    "WDA",
    "dense_1",
    dbscan_eps=1.5,
    dbscan_min_samples=10,
    vis_method="tsne",
    xlim=None,
    ylim=None,
    container=cluster_labels_all
)
labels_dbs_dense1 = res_dbs_dense1["dbscan"]
cluster_plot_DBSCAN(
    repr_wda_32["dense_1"],
    "WDA",
    "dense_1",
    dbscan_eps=1.5,
    dbscan_min_samples=10,
    vis_method="pca",
    xlim=None,
    ylim=None,
    container=cluster_labels_all
)
```






```
WDA | dense_1 | dbscan | eps=1.5  
clusters=2 noise=1005 sil=0.1462 DB=1.5471 CH=10.44  
DBCV = -0.3294 (rango [-1,1], específico DBSCAN)
```















```
Out[82]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
        0.34358275], dtype=float32),
        'group_means': {-1: array([2.6698792 , 2.60546   , 2.6123645 , ..., 0.3421869 ,
0.26810586,
        0.34514776], dtype=float32),
        0: array([2.0704565 , 2.0117824 , 1.9967024 , ..., 0.3664882 , 0.35433948,
        0.33573303], dtype=float32),
        1: array([5.512115 , 5.605645 , 5.370374 , ..., 0.19852325, 0.22394557,
        0.2530301 ], dtype=float32)},
        'unique_clusters': array([-1,  0,  1], dtype=int64)}
```


## DBSCAN n = 13723

```
In [83]: cluster_plot_DBSCAN(
        repr_wda_32_n2["dense_1"],
        "WDA",
        "dense_1",
        dbscan_eps=1.5,
        dbscan_min_samples=10,
        vis_method="tsne",
        xlim=None,
        ylim=None,
        container=cluster_labels_all_n2
    )
cluster_plot_DBSCAN(
    repr_wda_32_n2["dense_1"],
    "WDA",
    "dense_1",
    dbscan_eps=1.5,
    dbscan_min_samples=10,
    vis_method="pca",
    xlim=None,
    ylim=None,
    container=cluster_labels_all_n2
)
```



[DBCV omitido: 9410 puntos no-ruido > 5000]

```
WDA | dense_1 | dbscan | eps=1.5
clusters=3 noise=4301 sil=0.2002 DB=0.9446 CH=31.18
```



[DBCV omitido: 9410 puntos no-ruido > 5000]


|            |            |            |                    |
|------------|------------|------------|--------------------|
| WDA        | dense_1    | dbscan     | eps=1.5            |
| clusters=3 | noise=4301 | sil=0.2002 | DB=0.9446 CH=31.18 |

```
Out[83]: {'dbscan': array([ 0,  0,  0, ..., -1,  0,  0], dtype=int64),
'metrics': {'n_clusters': 3,
'n_noise': 4301,
'silhouette': 0.200239,
'davies_bouldin': 0.944591,
'calinski_harabasz': 31.1797},
'dbcv': None}
```


## Resultados capa dense\\_2 con Spectral Clustering + tSNE y PCA

### Spectral Clustering k=3

```
In [84]: res_spectral_dense2 = cluster_plot_Spect(
    repr_wda_32["dense_2"],
    "WDA",
    "dense_2",
    spectral_k=3,
    vis_method="tsne",
    container=cluster_labels_all
)
labels_spectral_dense2 = res_spectral_dense2["spectral"]
cluster_plot_Spect(
    repr_wda_32["dense_2"],
    "WDA",
    "dense_2",
    spectral_k=3,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



```
WDA | dense_2 | spectral | k=3  
clusters=3 noise=0 sil=0.2710 DB=1.2327 CH=175.88
```




|                                                   |
|---------------------------------------------------|
| WDA   dense_2   spectral   k=3                    |
| clusters=3 noise=0 sil=0.2710 DB=1.2327 CH=175.88 |


```
Out[84]: {'spectral': array([0, 1, 2, ..., 2, 0, 2]),
'metrics': {'n_clusters': 3,
'n_noise': 0,
'silhouette': 0.271038,
'davies_bouldin': 1.232705,
'calinski_harabasz': 175.8825}}
```

## Spectral k = 2

```
In [85]: res_spectral2_dense2 = cluster_plot_Spect(
    repr_wda_32["dense_2"],
    "WDA",
    "dense_2",
    spectral_k=2,
    vis_method="tsne",
    container=cluster_labels_all
)
labels_spectral2_dense2 = res_spectral2_dense2["spectral"]
cluster_plot_Spect(
    repr_wda_32["dense_2"],
    "WDA",
    "dense_2",
    spectral_k=2,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



```
WDA | dense_2 | spectral | k=2  
clusters=2 noise=0 sil=0.3845 DB=1.0462 CH=242.63
```




|                                                   |
|---------------------------------------------------|
| WDA   dense_2   spectral   k=2                    |
| clusters=2 noise=0 sil=0.3845 DB=1.0462 CH=242.63 |


```
Out[85]: {'spectral': array([0, 1, 1, ..., 1, 0, 0]),
          'metrics': {'n_clusters': 2,
                      'n_noise': 0,
                      'silhouette': 0.384526,
                      'davies_bouldin': 1.046158,
                      'calinski_harabasz': 242.6344}}
```

## Spectral k = 4

```
In [86]: res_spectral4_dense2 = cluster_plot_Spect(
            repr_wda_32["dense_2"],
            "WDA",
            "dense_2",
            spectral_k=4,
            vis_method="tsne",
            container=cluster_labels_all
        )
labels_spectral4_dense2 = res_spectral2_dense2["spectral"]
cluster_plot_Spect(
    repr_wda_32["dense_2"],
    "WDA",
    "dense_2",
    spectral_k=4,
    vis_method="pca",
    xlim=(-10,10), ylim=(-10,10),
    container=cluster_labels_all
)
```



```
WDA | dense_2 | spectral | k=4  
clusters=4 noise=0 sil=0.2007 DB=1.5040 CH=144.10
```






|                                                   |
|---------------------------------------------------|
| WDA   dense_2   spectral   k=4                    |
| clusters=4 noise=0 sil=0.2007 DB=1.5040 CH=144.10 |


```
Out[86]: {'spectral': array([1, 0, 3, ..., 3, 1, 2]),
          'metrics': {'n_clusters': 4,
                      'n_noise': 0,
                      'silhouette': 0.200664,
                      'davies_bouldin': 1.503974,
                      'calinski_harabasz': 144.1003}}
```

## DBSCAN n=1100

```
In [87]: res_dbs_dense2 = cluster_plot_DBSCAN(
            repr_wda_32["dense_2"],
            "WDA",
            "dense_2",
            dbscan_eps=1.5,
            dbscan_min_samples=10,
            vis_method="tsne",
            xlim=None,
            ylim=None,
            container=cluster_labels_all
        )
labels_dbs_dense2 = res_dbs_dense2["dbscan"]
cluster_plot_DBSCAN(
    repr_wda_32["dense_2"],
    "WDA",
    "dense_2",
    dbscan_eps=1.5,
    dbscan_min_samples=10,
    vis_method="pca",
    xlim=None,
    ylim=None,
    container=cluster_labels_all
)
```



```
WDA | dense_2 | dbscan | eps=1.5  
clusters=1 noise=115 sil=N/A DB=N/A CH=N/A  
DBCV = N/A (rango [-1,1], específico DBSCAN)
```



```
WDA | dense_2 | dbscan | eps=1.5
clusters=1 noise=115 sil=N/A DB=N/A CH=N/A
DBCv = N/A (rango [-1,1], específico DBSCAN)
```


```
Out[87]: {'dbscan': array([0, 0, 0, ..., 0, 0, 0], dtype=int64),
'metrics': {'n_clusters': 1,
'n_noise': 115,
'silhouette': None,
'davies_bouldin': None,
'calinski_harabasz': None},
'dbcv': nan}
```




## Espectros obtenidos para dense\_2 con Spectral Clustering k = 3 y n = 1100




```
In [88]: plot_spectra_spectral(
    X_wda_spec,
    labels_spectral_dense2,
    W_wda[0],
    class_name="WDA",
    layer_name="dense_2"
)
```


C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```












```
Out[88]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
805,
      0.34358275], dtype=float32),
      'group_means': {0: array([2.9904964 , 2.91507   , 2.8665686 , ..., 0.26025265, 0.
15318817,
      0.33724385], dtype=float32),
      1: array([2.1885817 , 2.1160998 , 2.1143215 , ..., 0.43111524, 0.41862655,
      0.47746158], dtype=float32),
      2: array([2.6184115 , 2.5705345 , 2.6148593 , ..., 0.3616406 , 0.2949612 ,
      0.28239837], dtype=float32)},
      'unique_clusters': array([0, 1, 2])}
```




### Espectros obtenidos para dense\_2 con DBSCAN y n = 1100

```
In [89]: plot_spectra_dbscan(
      X_wda_spec,
      labels_dbs_dense2,
      W_wda[0],
      class_name="WDA",
      layer_name="dense_2"
    )
```

C:\Users\javip\AppData\Local\Temp\ipykernel\_6108\531566132.py:28: MatplotlibDeprecationWarning: The get\_cmap function was deprecated in Matplotlib 3.7 and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get\_cmap()`` or ``pyplot.get\_cmap()`` instead.

```
cmap = plt.cm.get_cmap("tab10", n_clusters)
```







```
Out[89]: {'total_mean': array([2.6493979 , 2.5868607 , 2.5898647 , ..., 0.34275877, 0.27436
      805,
      0.34358275], dtype=float32),
      'group_means': {-1: array([3.3574717 , 2.9026318 , 3.032409 , ..., 0.26793537,
      0.01046038,
      0.6476452 ], dtype=float32),
      0: array([2.5667284 , 2.5499933 , 2.5381944 , ..., 0.35149452, 0.3051795 ,
      0.3080834 ], dtype=float32)},
      'unique_clusters': array([-1,  0], dtype=int64)}
```

## Tabla de evaluación con métricas

```
In [90]: # construir tabla para WDA con n=1100
metrics_wda = build_metrics_table(
    representations_32 = repr_wda_32,
    class_name         = "WDA",
    spectral_k_values  = [2, 3, 4, 5],
    dbscan_eps_values  = [0.5, 1.0, 1.5, 2.0, 2.5, 3.0],
    dbscan_min_samples = 10
)

print(metrics_wda.to_string(index=False))

# vr las 5 mejores configuraciones
top_configs = get_best_configs(metrics_wda, top_n=5)
print(top_configs.to_string(index=False))


# heatmaps de cada métrica —
plot_metrics_heatmap(metrics_wda, metric="silhouette",      class_name="WDA")
plot_metrics_heatmap(metrics_wda, metric="davies_bouldin",  class_name="WDA")
plot_metrics_heatmap(metrics_wda, metric="calinski_harabasz", class_name="WDA")


...

# — Repetir para n=13723 si quieres comparar —
metrics_wda_n2 = build_metrics_table(
    representations_32 = repr_wda_32_n2,
    class_name         = "WDA",
    spectral_k_values  = [2, 3, 4, 5],
    dbscan_eps_values  = [0.5, 1.0, 1.5, 2.0, 2.5, 3.0]
)
top_configs_n2 = get_best_configs(metrics_wda_n2, top_n=5)
...
```

| class  | layer             | method   | param | param_value | n_clusters | n_noise | silhouette | davies_b |
|--------|-------------------|----------|-------|-------------|------------|---------|------------|----------|
| ouldin | calinski_harabasz |          |       |             |            |         |            |          |
| 287926 | WDA flatten       | spectral | k     | 2.0         | 2          | 0       | 0.066835   | 2.       |
| 661654 |                   |          |       | 21.4947     |            |         |            |          |
| 300675 | WDA flatten       | spectral | k     | 3.0         | 3          | 0       | -0.047206  | 2.       |
| 475563 |                   |          |       | 20.2384     |            |         |            |          |
|        | WDA flatten       | spectral | k     | 4.0         | 4          | 0       | -0.025797  | 3.       |
|        |                   |          |       | 18.8727     |            |         |            |          |
|        | WDA flatten       | spectral | k     | 5.0         | 5          | 0       | -0.041037  | 3.       |
|        |                   |          |       | 18.2195     |            |         |            |          |
| NaN    | WDA flatten       | dbscan   | eps   | 0.5         | 0          | 1100    | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA flatten       | dbscan   | eps   | 1.0         | 1          | 1084    | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA flatten       | dbscan   | eps   | 1.5         | 1          | 790     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA flatten       | dbscan   | eps   | 2.0         | 1          | 581     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA flatten       | dbscan   | eps   | 2.5         | 1          | 426     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA flatten       | dbscan   | eps   | 3.0         | 1          | 302     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| 015690 | WDA dense         | spectral | k     | 2.0         | 2          | 0       | 0.097317   | 5.       |
| 257357 |                   |          |       | 23.5887     |            |         |            |          |
| 052599 | WDA dense         | spectral | k     | 3.0         | 3          | 0       | -0.069202  | 4.       |
| 820103 |                   |          |       | 22.0086     |            |         |            |          |
|        | WDA dense         | spectral | k     | 4.0         | 4          | 0       | -0.064243  | 4.       |
|        |                   |          |       | 21.4740     |            |         |            |          |
|        | WDA dense         | spectral | k     | 5.0         | 5          | 0       | -0.057705  | 3.       |
|        |                   |          |       | 20.7556     |            |         |            |          |
| NaN    | WDA dense         | dbscan   | eps   | 0.5         | 0          | 1100    | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA dense         | dbscan   | eps   | 1.0         | 0          | 1100    | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| 243667 | WDA dense         | dbscan   | eps   | 1.5         | 3          | 1030    | 0.289126   | 1.       |
|        |                   |          |       | 25.6442     |            |         |            |          |
| NaN    | WDA dense         | dbscan   | eps   | 2.0         | 1          | 737     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA dense         | dbscan   | eps   | 2.5         | 1          | 501     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA dense         | dbscan   | eps   | 3.0         | 1          | 352     | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| 121860 | WDA dense_1       | spectral | k     | 2.0         | 2          | 0       | 0.083096   | 5.       |
| 400539 |                   |          |       | 25.1293     |            |         |            |          |
| 106197 | WDA dense_1       | spectral | k     | 3.0         | 3          | 0       | 0.023817   | 4.       |
| 779365 |                   |          |       | 24.4928     |            |         |            |          |
|        | WDA dense_1       | spectral | k     | 4.0         | 4          | 0       | -0.005627  | 4.       |
|        |                   |          |       | 22.9831     |            |         |            |          |
|        | WDA dense_1       | spectral | k     | 5.0         | 5          | 0       | -0.022790  | 3.       |
|        |                   |          |       | 21.2630     |            |         |            |          |
| NaN    | WDA dense_1       | dbscan   | eps   | 0.5         | 0          | 1100    | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| NaN    | WDA dense_1       | dbscan   | eps   | 1.0         | 0          | 1100    | NaN        |          |
| NaN    |                   |          |       | NaN         |            |         |            |          |
| 547066 | WDA dense_1       | dbscan   | eps   | 1.5         | 2          | 1005    | 0.146244   | 1.       |
|        |                   |          |       | 10.4406     |            |         |            |          |

|                   |         |                 |             |            |         |            |                |          |
|-------------------|---------|-----------------|-------------|------------|---------|------------|----------------|----------|
| WDA               | dense_1 | dbscan          | eps         | 2.0        | 1       | 639        | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_1 | dbscan          | eps         | 2.5        | 1       | 460        | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_1 | dbscan          | eps         | 3.0        | 1       | 313        | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | k           | 2.0        | 2       | 0          | 0.384526       | 1.046158 |
| 242.6344          |         | 242.6344        |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | k           | 3.0        | 3       | 0          | 0.271038       | 1.232705 |
| 175.8825          |         | 175.8825        |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | k           | 4.0        | 4       | 0          | 0.200664       | 1.503974 |
| 144.1003          |         | 144.1003        |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | k           | 5.0        | 5       | 0          | 0.220754       | 1.687113 |
| 107.4361          |         | 107.4361        |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | eps         | 0.5        | 3       | 720        | 0.483226       | 0.638550 |
| 856.0933          |         | 856.0933        |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | eps         | 1.0        | 1       | 221        | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | eps         | 1.5        | 1       | 115        | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | eps         | 2.0        | 1       | 82         | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | eps         | 2.5        | 1       | 62         | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | eps         | 3.0        | 1       | 52         | NaN            |          |
| NaN               |         | NaN             |             |            |         |            |                |          |
| class             | layer   | method          | param_value | n_clusters | n_noise | silhouette | davies_bouldin |          |
| calinski_harabasz |         | score_compuesto |             |            |         |            |                |          |
| WDA               | dense_2 | dbscan          | 0.5         | 3          | 720     | 0.483226   | 0.638550       |          |
| 856.0933          |         | 1.000000        |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | 2.0         | 2          | 0       | 0.384526   | 1.046158       |          |
| 242.6344          |         | 2.000000        |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | 3.0         | 3          | 0       | 0.271038   | 1.232705       |          |
| 175.8825          |         | 3.333333        |             |            |         |            |                |          |
| WDA               | dense   | dbscan          | 1.5         | 3          | 1030    | 0.289126   | 1.243667       |          |
| 25.6442           |         | 4.333333        |             |            |         |            |                |          |
| WDA               | dense_2 | spectral        | 4.0         | 4          | 0       | 0.200664   | 1.503974       |          |
| 144.1003          |         | 5.000000        |             |            |         |            |                |          |





```
Out[90]: '\n# — Repetir para n=13723 si quieres comparar —\nmetrics_wda_n2 = build_metric
s_table(\n    representations_32 = repr_wda_32_n2,\n    class_name      = "WD
A",\n    spectral_k_values = [2, 3, 4, 5],\n    dbscan_eps_values = [0.5, 1.0,
1.5, 2.0, 2.5, 3.0]\n)\ntop_configs_n2 = get_best_configs(metrics_wda_n2, top_n=5)
\n'
```

## Experimentos WDB

```
In [91]: # Experimento WDB para n=1100
X_wdb, df_wdb = load_class_spectra("WDB", n_samples=1100, random_state=42)

flatten_wdb, dense_wdb, dense1_wdb, dense2_wdb = extract_layer_features(X_wdb)

repr_wdb_32 = reduce_all_to_32(flatten_wdb, dense_wdb, dense1_wdb, dense2_wdb)
```

```

WDB: disponibles con match a .dat = 1184
WDB: espectros válidos finales = 1099
18/18 _____ 0s 19ms/step
18/18 _____ 0s 18ms/step
18/18 _____ 0s 19ms/step
18/18 _____ 0s 19ms/step
flatten: (1099, 208)
dense: (1099, 128)
dense_1: (1099, 64)
dense_2: (1099, 32)
flatten_32: (1099, 32)
dense_32: (1099, 32)
dense1_32: (1099, 32)
dense2_32: (1099, 32)

```

```

In [92]: # Experimento WDB para n=1184
X_wdb_n2, df_wdb_n2 = load_class_spectra("WDB", n_samples=1184, random_state=42)

flatten_wdb_n2, dense_wdb_n2, dense1_wdb_n2, dense2_wdb_n2 = extract_layer_features

repr_wdb_32_n2 = reduce_all_to_32(flatten_wdb_n2, dense_wdb_n2, dense1_wdb_n2, dens

```

```

WDB: disponibles con match a .dat = 1184
WDB: espectros válidos finales = 1183
19/19 _____ 0s 19ms/step
19/19 _____ 0s 20ms/step
19/19 _____ 0s 20ms/step
19/19 _____ 0s 20ms/step
flatten: (1183, 208)
dense: (1183, 128)
dense_1: (1183, 64)
dense_2: (1183, 32)
flatten_32: (1183, 32)
dense_32: (1183, 32)
dense1_32: (1183, 32)
dense2_32: (1183, 32)


```


## Evaluación K para n = 1100

```

In [93]: evaluate_kmeans_k(repr_wdb_32["flatten"], "WDB", "flatten")
evaluate_kmeans_k(repr_wdb_32["dense"], "WDB", "dense")
evaluate_kmeans_k(repr_wdb_32["dense_1"], "WDB", "dense_1")
evaluate_kmeans_k(repr_wdb_32["dense_2"], "WDB", "dense_2")

```





## Gráficos t-SNE y PCA + clustering