

### Critical

**Type mismatch FK** — `parking_slots.building_id` is `varchar(50)` but `buildings.id` is `int(11)` — same for `parking_requests.building_id`. The FK cannot be declared (MariaDB silently omits it). Referential integrity is completely absent on all parking-to-building relationships.

### Critical

**Wrong FK target** — `service_providers.building_id` references `users` — the constraint reads `FOREIGN KEY (building_id) REFERENCES users (id)`. A column named `building_id` should reference `buildings(id)`. This is almost certainly a copy-paste error and breaks all provider-to-building queries.

### High

**Derived column `user_profiles.age`** — age is computable from `dob` (also present in same table). Storing it creates a staleness problem: the stored age never increments automatically and will be wrong every year after insert.

### High

**Redundant `building_id` in `community_posts`, `community_comments`, and `cctv_captures`** — all three are already linked to an `apt_id` or `camera_id` which transitively identifies the building. Storing `building_id` directly violates 3NF and risks desync.

### High

**Three separate subscription table schemas with no unified plan reference** — `owner_subscriptions`, `building_subscriptions`, and `provider_subscriptions` all have near-identical columns (`status`, `started_at`, `expires_at`, `tran_id`, `payment_key`) but different plan FK targets. This is a missed opportunity for a polymorphic subscription design.

### High

**`bills.total_amount` is a derived value** — it is `subtotal - discount + tax`, all of which are already columns in the same row. Storing the total risks arithmetic inconsistency if any component is updated without recomputing the total.

### Medium

**`service_providers.rating` is a stored aggregate** — initialized to 5.00, presumably updated by application logic when a review is added. Should be a computed view over `provider_reviews` or updated via trigger, not hand-maintained.

### Medium

**Address decomposition inconsistency in `user_profiles`** — contains `address`, `permanent_address`, `latitude`, and `longitude` — four overlapping address representations without a clear semantic boundary between them.