SoK: FUZZCHECK.AI: On the Limitations of DNN Fuzzing to Discover Security Failures

***Abstract*—Deep neural networks (DNNs) are widely deployed in safety- and security-critical applications and remain vulnerable to adversarial manipulation. DNN fuzzing has emerged as a practical approach for systematically discovering model failures. However, existing DNN fuzzing research remains fragmented across goals, designs, and evaluation practices, making it unclear whether current fuzzers satisfy core security testing requirements, whose omission may lead to a misleading sense of security. To address this gap, we present FUZZCHECK.AI, a structured evaluation framework with six DNN security testing metrics (failure severity, targeted attack discovery, input plausibility, failure reproducibility, failure diagnostics, and attack transferability) and a codebook-guided, semi-automated assessment workflow combining LLM-based evidence extraction with expert review. Applying FUZZCHECK.AI to 32 representative DNN fuzzing papers, we uncover systematic blind spots in current fuzzing designs. Most fuzzers focus on low-severity robustness errors, rarely support targeted or transferable attacks, and provide limited failure diagnostics. A substantial fraction overlook cumulative mutation effects on input plausibility or serialization effects, leading to implausible or non-reproducible failures. No evaluated fuzzer achieves high compliance across all metrics, and 59.4% (19/32) exhibit low compliance on three or more. Based on these findings, we derive actionable recommendations to guide the design of DNN fuzzers for comprehensive security testing.**

I. INTRODUCTION

Deep neural networks (DNNs) are increasingly deployed in safety- and security-critical settings, including autonomous driving, speech interfaces, and large language model–based systems [1], [2], [3]. Despite impressive benchmark performance, these systems remain vulnerable to adversarial manipulations. Small, often imperceptible perturbations, such as pixel-level noise in images, waveform distortions in audio, or subtle token manipulations in text, can induce mispredictions, unsafe actions, or violations of safety and security policies [4], [5], [6], [7], [8], [9]. This gap between benchmark performance and model behavior under adversarial or uncommon yet valid inputs has motivated substantial work on automated DNN testing [10], [11], [12], [13], [14], [15], [16], highlighting the need for systematic approaches that go beyond static benchmark evaluation.

DNN fuzzing has emerged as a practical approach for probing model behavior under diverse, systematically mutated inputs. Inspired by traditional software fuzzing [17], [18], [19], recent DNN testing frameworks adapt fuzzing principles to deep learning models [20], [21], [22], [23]. At a high level, DNN fuzzers iteratively mutate seed inputs and leverage feedback signals from the target model to guide exploration toward previously underexplored or failure-prone behaviors [10], [11], [24]. Existing fuzzers differ substantially in their design choices. They vary in how test inputs are mutated, ranging from metamorphic transformations and gradient-guided perturbations to generative input synthesis [10], [21], [25]. They also differ in how exploration is guided, for example by selecting inputs for subsequent mutation that have previously triggered faults or expanded internal model activation coverage [21], [23]. In addition, fuzzers differ in their oracle designs, which specify failure conditions. Fuzzers also differ in their access assumptions, including whitebox, greybox, and blackbox settings [20], [11], [26]. Together, these design choices shape how effectively a fuzzer can discover DNN security failures such as jailbreaks, data leakage, bypassing model defenses, targeted attacks, and cross-model transferable attacks.

DNN fuzzing approaches often report high failure discovery efficiency, yet provide limited evidence on whether the discovered failures satisfy essential but under-examined security testing requirements. It is often unclear whether fuzzers discover targeted or cross-model transferable attacks, whether discovered failures bypass deployed defense mechanisms, or whether they expose underlying model vulnerabilities, such as reliance on spurious features or dataset bias. Moreover, discovered failures are meaningful only when the corresponding fault-inducing inputs remain plausible under realistic threat models and when they remain reproducible. Fuzzers that overlook any of these requirements may discover numerous failures, giving the impression of thorough testing, while leaving critical aspects of DNN security insufficiently examined and thereby providing a misleading sense of security.

As a rapidly emerging area, DNN fuzzing research remains fragmented, with substantial variation in mutation strategies, exploration mechanisms, and oracle designs. Consequently, it remains unclear how specific design choices shape a fuzzer's ability to satisfy different security testing requirements. Without a systematic analysis of fuzzing approaches, this fragmented landscape risks duplicated effort and blind spots in critical security testing dimensions. A systematization at this stage is therefore essential to clarify the capabilities and limitations of existing DNN fuzzing approaches in discovering security failures and to guide the design of frameworks for comprehensive security testing. To the best of our knowledge, no prior work has systematically examined how different DNN fuzzing approaches satisfy these security testing requirements.

To address this gap, we distill six DNN security testing metrics (failure severity, targeted attack discovery, input plausibility, failure reproducibility, failure diagnostics, and attack transferability) from prior work on machine learning security and develop a qualitative evaluation framework to assess DNN

TABLE I
SUMMARY OF KEY FINDINGS AND RECOMMENDATIONS.

Key Finding	Recommendation
Only 18.8% discover high-severity failures, while 65.6% focus on low-severity robustness errors.	Incorporate feedback from model defense mechanisms and encode security and policy violations in the oracle to discover high-severity failures.
Only 9.4% support targeted attack discovery, while 68.8% focus on untargeted failures.	Use target-aware exploration and directional mutation mechanisms to guide fuzzing toward attacker-chosen outputs.
37.5% overlook cumulative effect of mutation across iterations, leading to implausible failures.	Enforce plausibility relative to the original seed, or use auxiliary models to filter implausible mutations.
Over half of fuzzers ignore serialization effects (e.g., clipping, rounding), resulting in fragile, non-reproducible failures.	Design reproducibility-aware mutation strategies that explicitly account for serialization effects (e.g., clipping, rounding).
Most DNN fuzzing papers (96.8%) provide only partial or no failure diagnostics.	Evaluate fuzzers on models with known vulnerabilities and analyze whether discovered failures correlate with them.
Transferable attack discovery is largely unsupported, with only one fuzzer explicitly designed for it.	Incorporate multi-model feedback to guide mutation and exploration toward transferable failure discovery.
No fuzzer achieves full compliance; 59.4% fail on three or more metrics.	Integrate fuzzing components with complementary strengths to satisfy all core security testing requirements.

fuzzing papers/techniques along these dimensions. In doing so, we make several key contributions, and offer critical findings and recommendations to design better DNN fuzzers in the future, as outlined below:

1) We present FUZZCHECK.AI, a structured evaluation framework that defines six metrics capturing core DNN security testing requirements and provides a codebook with concrete evaluation guidelines for assessing DNN fuzzing papers.
2) We design a semi-automated, two-stage assessment workflow in which LLMs extract metric-relevant evidence and propose preliminary assessments guided by the FUZZCHECK.AI codebook, which experts validate and finalize to ensure reliable evaluation of DNN fuzzing papers.
3) We propose a taxonomy that categorizes DNN fuzzing approaches along multiple design dimensions (oracle design, mutation strategy, exploration strategy, and access level), enabling systematic analysis of how design choices influence security testing metrics.
4) Applying FUZZCHECK.AI to 32 representative DNN fuzzing papers, we identify recurring blind spots and derive actionable research directions, summarized in Table I, to guide the design of fuzzers for comprehensive DNN security testing.

II. BACKGROUND

A. DNN Fuzzing

DNN fuzzing is an automated testing paradigm that systematically probes the behavior of deep neural networks by iteratively generating and evaluating test inputs. Inspired by traditional software fuzzing [17], [18], [19], DNN fuzzers typically operate in a loop that starts from a set of seed inputs, applies mutations to produce new candidate inputs, executes the target model on these inputs, and uses feedback signals to guide subsequent exploration toward underexplored or failure-prone behaviors. Unlike benchmark-based evaluation, which measures performance on a fixed dataset, DNN fuzzing focuses on adaptive exploration of the input space [10], [20], [21].

At a high level, DNN fuzzers consist of three core components: mutation, exploration, and oracle. **Mutation** determines how new test inputs are generated from existing seeds or synthesized from scratch. **Exploration** governs how candidate inputs are prioritized during fuzzing based on feedback signals obtained from model execution. **Oracle** specifies how a fuzzer infers whether a generated input exposes incorrect, unsafe, or security-violating behavior in the DNN model. Depending on the level of access to the target model, DNN fuzzing can operate in white-box, grey-box, or black-box settings, each providing different degrees of visibility into internal model information [27].

DNN fuzzing is closely related to, but distinct from, other DNN testing approaches. Metamorphic testing (MT) applies predefined, semantics-preserving transformations and tests DNN models by checking prediction-level consistency between an input and its transformed variants, but does not perform iterative, feedback-guided exploration [13], [14], [28], [29]. Optimization-based adversarial attacks optimize small, semantics-preserving perturbations to induce targeted or untargeted mispredictions, emphasizing worst-case evasion objectives rather than systematic exploration of the model behavior space [30], [31], [8], [32], [33], [34], [35]. Coverage-based DNN testing measures test adequacy by quantifying how thoroughly a dataset exercises a model's internal behavior using coverage metrics defined over neuron activation states [36], [37], [15], [38].

B. DNN Fuzzing vs. Software Fuzzing

While inspired by traditional software fuzzing, DNN fuzzing differs in several fundamental ways. Unlike traditional software, where execution paths and code coverage provide a clear notion of exploration progress, DNNs operate in continuous, high-dimensional activation spaces in which each input induces a distinct pattern of internal activations [10], [21]. As a result, DNN fuzzers approximate exploration progress using heuristic feedback signals derived from model internals or outputs [10], [15], [39].

Another distinction lies in how fuzzers define an oracle to determine whether a test input exposes incorrect, unsafe, or security-violating behavior. In traditional software fuzzing, program crashes, assertion violations, or memory errors provide an unambiguous indication of such behavior. In contrast, DNN fuzzing lacks reliable ground-truth labels for mutated or synthesized inputs, making it difficult to directly determine whether a model's behavior violates security

or safety properties [21]. Consequently, DNN fuzzers infer failures using alternative oracle definitions, such as violations of safety or security policies [23], [24], inducing attacker-chosen outputs, inconsistencies across semantically equivalent inputs [12], [39], or divergence among models performing the same task [40], [41].

A further distinction arises in mutation strategy. In DNN fuzzing, mutation is designed to discover inputs that can fool the learned model into exhibiting safety- or security-violating behavior, whereas traditional software fuzzing uses mutation primarily to exercise execution paths that lead to program failures. As a result, the semantic plausibility of mutated inputs is largely irrelevant in traditional fuzzing but central to DNN fuzzing [42], [43], [20]. The security relevance of a discovered failure depends on whether it is triggered by inputs that preserve perceptual or semantic plausibility. Implausible or semantically invalid inputs may induce arbitrary model behavior but do not necessarily reflect exploitable weaknesses under realistic threat models, as practical adversarial manipulations are typically constrained to be imperceptible in order to evade detection [30], [21], [44].

III. Related Work

Several comprehensive surveys have explored the testing and evaluation of machine learning (ML) systems, each emphasizing different perspectives on robustness, safety, and security. Riccio et al. [45] and Zhang et al. [27] conducted systematic surveys of ML testing, outlining major techniques and challenges in test input generation, oracle design, adequacy criteria, and evaluation of testing effectiveness. Braiek and Khomh [46] and Huang et al. [47] reviewed how classical software-testing principles, such as coverage metrics, metamorphic testing, and formal verification, have been adapted to assess the reliability and safety of deep models. More recently, Guo et al. [16] surveyed coverage-guided testing for deep learning, systematically categorizing 89 studies by coverage criteria, test input generation, and optimization strategies. They also review evaluation practices and highlight open challenges in correlating coverage with fault detection, improving generalizability, and standardizing benchmarks.

While prior surveys primarily focus on categorizing DNN testing techniques and analyzing design and evaluation challenges, they do not systematically examine how existing DNN fuzzing designs satisfy core security testing requirements. To address this gap, we introduce a structured evaluation framework with six metrics and apply it to 32 representative DNN fuzzing papers, revealing systematic blind spots and design limitations that are not visible through conventional survey perspectives. Based on these findings, we distill actionable recommendations to guide the design of DNN fuzzers for comprehensive security testing.

IV. Our FuzzCheck.AI Framework

We introduce FuzzCheck.AI, a structured evaluation framework for assessing how different DNN fuzzing designs satisfy core security testing requirements. The framework consists of six security testing metrics that capture core requirements in DNN security testing. The framework also includes a codebook that specifies concrete evaluation guidelines for assessing DNN fuzzing papers on these metrics, enabling consistent and transparent evaluation. As illustrated in Figure 1, the codebook is applied to assess each paper against all six metrics based on its described fuzzing design and reported empirical results. These assessments are then aggregated to analyze trade-offs and blind spots across fuzzing designs, examine how different design choices support or constrain security testing requirements, and distill actionable insights to guide the development of future DNN fuzzing approaches.

A. Development of FuzzCheck.AI

We distilled the six FuzzCheck.AI metrics by analyzing evaluation practices and security testing goals in prior work on DNN testing and machine learning security. In particular, we examined how existing studies define DNN model security failures, attack surfaces, and threat models, and how they reason about the causes of discovered failures, to identify core DNN security testing requirements. These requirements include uncovering high-severity security failures [23], [8], supporting targeted attack discovery [8], [9], ensuring the plausibility of fault-inducing inputs [44], [12], maintaining failure reproducibility [48], providing explanations for discovered failures [39], [49], and discovering cross-model transferable failures [26], [42]. These requirements capture core attack surfaces and realistic threat assumptions, and DNN fuzzing methods that overlook any of them may provide a misleading sense of security. We formalize these requirements into a unified set of evaluation metrics for assessing DNN fuzzing papers.

We then developed and refined a set of concrete evaluation guidelines to assess DNN fuzzing papers on these metrics, which together form the FuzzCheck.AI codebook (Table II). To initialize the codebook, one author drafted an initial version based on pilot assessments of representative DNN fuzzing papers. For independent validation, a second author applied this initial codebook to the same paper set following established open-coding practices from qualitative research [50]. The two authors iteratively compared assessments, discussed disagreements, refined metric definitions and decision criteria, and re-evaluated papers across multiple rounds. All authors reviewed the revisions, provided feedback, and confirmed consensus before finalizing the codebook.

B. FuzzCheck.AI Metrics and Codebook

1) Failure Severity: DNN fuzzers differ in the class of failures they are designed to uncover. Some reveal only robustness-related errors, such as mispredictions or prediction inconsistencies under semantically preserving input mutations [20], [12]. Others uncover unsafe or otherwise undesirable model behaviors, such as toxic, biased, or harmful outputs [51], [9]. Some fuzzers target models equipped with



Fig. 1. Overview of FUZZCHECK.AI framework.

TABLE II
FUZZCHECK.AI CODEBOOK WITH EVALUATION CRITERIA FOR HIGH, MEDIUM, AND LOW FULFILLMENT LEVELS (**C.** = CODE).

C.	Metric	High (●)	Medium (◑)	Low (○)
FS	Failure Severity	Targets a model equipped with explicit safety or security safeguards, and discovers failures that bypass those safeguards to induce prohibited behavior.	Discovers unsafe, harmful, or otherwise undesirable behavior, without bypassing explicit safety or security safeguards.	Discovers only robustness-related errors (e.g., mispredictions), without unsafe/harmful behavior or safeguard bypass.
TA	Targeted Attack Discovery	Supports targeted attack discovery by steering exploration toward specific, predefined target outcomes (e.g., inducing a classifier to predict a target label).	Supports discovery of broader classes of security-violating behaviors (e.g., jailbreaks, toxicity, bias, or other unsafe behaviors), rather than a specific model output.	Performs untargeted exploration, revealing generic failures such as misclassifications, inaccuracies, or inconsistent predictions.
IP	Input Plausibility	Enforces input plausibility throughout fuzzing iterations by ensuring that mutated inputs remain within a plausible input distribution.	Enforces plausibility between successive mutation steps through bounded or rule-based constraints but overlooks cumulative effects across fuzzing iterations.	Does not enforce input plausibility, allowing unrealistic or semantically invalid inputs to induce failures.
FR	Failure Reproducibility	Enforces input representation constraints during mutation (e.g., clipping to valid ranges, rounding to appropriate precision) or generates inputs directly in valid serialized formats.	Partially accounts for input representation constraints (e.g., enforces some constraints or uses transformations that are less sensitive to numerical precision), but does not explicitly ensure reproducibility under serialization.	Does not account for input representation constraints, allowing perturbations to be altered or lost after serialization, leading to non-reproducible failures.
FD	Failure Diagnostics	Provides diagnostic analysis that explains why failures occur by linking discovered failures to underlying model vulnerabilities (e.g., reliance on spurious features, dataset bias, or overfitting).	Provides diagnostic insight through analysis of correlation between failures and observable model internals, or through statistical analysis of failure patterns.	Reports discovered failures but does not analyze model internals or failure patterns to provide diagnostic insight.
AT	Attack Transferability	Evaluates whether failures discovered on one model transfer to other models on the same task, and incorporates mechanisms to support discovering transferable security failures.	Evaluates whether failures discovered on one model transfer to other models on the same task, but the fuzzing design is not explicitly aimed at discovering transferable failures.	Does not demonstrate whether fault-inducing inputs discovered on one model also trigger failures in other models.

explicit safety or security safeguards and aim to discover failures that bypass those safeguards. Because modern DNNs are often deployed with mechanisms intended to prevent, detect, or mitigate adversarial and safety-violating behavior [52], [53], [54], [55], [56], [57], [58], failures that bypass such safeguards are particularly important in security testing.

To evaluate papers on this metric, we examine the strongest class of failure the fuzzer is designed and evaluated to uncover, based on the target model, oracle definition, and reported evaluation setting. In particular, we check whether the target model is equipped with explicit safety or security safeguards, and whether the failures correspond to safeguard bypass, unsafe or undesirable behavior, or only robustness-related errors.

2) Targeted Attack Discovery: Many adversarial threat models define the attacker's goal as modifying inputs to induce specific attacker-chosen outputs (e.g., unsafe content labeled as safe or speech transcribed to chosen commands) [30], [8], [9]. In this context, targeted attack discovery captures whether and how a DNN fuzzer steers its exploration toward predefined target outcomes, as opposed to discovering faults without an explicit output objective. We therefore include the targeted attack discovery metric to assess whether DNN fuzzers pursue this security testing objective, and to examine which fuzzing design choices enable or limit the discovery of such targeted attacks.

To evaluate DNN fuzzing papers on this metric, we examine whether the fuzzing design supports targeted attack discovery and how it steers exploration toward targeted failures. Specifically, we assess whether the fuzzer aims to discover fault-triggering inputs that induce attacker-chosen outputs (e.g., specific labels, phrases, or prohibited responses), broader classes of security-violating behavior (e.g., jailbreaks, toxicity, unsafe behaviors), or performs untargeted exploration that

discovers generic faults such as misclassifications or prediction inconsistencies. To support consistent evaluation under this metric, we examine how the fuzzer's mutation, exploration, and oracle components contribute to or constrain its ability to steer exploration toward targeted outcomes.

3) Input Plausibility: Input plausibility is critical for two reasons. First, when mutations do not preserve semantics, ground-truth labels become uncertain. To address this, many DNN fuzzers rely on semantic-preserving mutations and oracles that assume semantic equivalence between mutated inputs and their seed inputs [12], [21], [26]. If mutations produce unrealistic or semantically invalid inputs, a changed model output may no longer indicate a meaningful failure, but rather reflect a breakdown of the oracle assumption itself. Second, in realistic threat models, the security relevance of a discovered failure depends on whether it is induced by inputs that remain plausible within the task domain [7], [59], [60], [21]. For instance, a stop sign that is slightly brightened or rotated remains plausible within the driving domain, whereas one corrupted by heavy random noise or visually incoherent textures does not [12]. Similarly, speech containing mild background hiss remains intelligible and natural, while severely distorted or robotic utterances fall outside realistic speech conditions [8], [61]. Failures induced by unrealistic inputs may still trigger incorrect model behavior, but they are less meaningful for practical security evaluation.

DNN fuzzers typically generate fault-inducing inputs through iterative mutation of seed inputs. During fuzzing, promising mutated inputs, such as those that trigger failures or expand coverage, are added to the seed pool and selected for further mutation in later iterations [21]. As a result, distortions can accumulate across repeated rounds of mutation. While a single mutation with conservative parameters may preserve semantics, the cumulative effect of repeated mutations can progressively degrade semantic validity, eventually yielding inputs that are no longer realistic or recognizable.

Using this metric, we evaluate how DNN fuzzers control such cumulative distortion throughout fuzzing iterations when the fuzzer assumes semantic-preserving or realistic inputs. Specifically, we examine whether the mutation design ensures that final fault-inducing inputs remain semantically valid and within a plausible task-specific input distribution throughout the fuzzing process. If a DNN fuzzer intentionally generates unrealistic or semantically invalid inputs to stress-test model robustness or uncover extreme behaviors, then it falls outside the scope of this metric.

4) Failure Reproducibility: Small numerical perturbations introduced during mutation may induce failures that appear only in memory but disappear after saving the mutated input to disk [48]. Due to rounding or quantization during serialization, such perturbations may be lost, rendering these failures non-reproducible and therefore false positives rather than genuine model defects. Such failures do not represent exploitable vulnerabilities, as they arise outside the valid input space and cannot be reliably stored and transmitted.

In DNN fuzzing, mutations are often applied to floating-point tensor representations of inputs. If the mutations do not enforce the constraints of the target input format such as image pixels to be integer in the range $[0, 255]$, audio waveform within the amplitude range $[-1, 1]$, or discrete token IDs for text, the mutated inputs may violate representation requirements. When such inputs are saved to disk, standard serialization enforces these constraints (e.g., through rounding, clipping), which can alter or remove the fault-inducing perturbations. For example, an image pixel value may change from 155.0 to 155.4 after mutation; when serialized as an 8-bit image, this value is rounded to 155, eliminating the perturbation that triggered the failure. Similarly, if a mutation changes a pixel value from 254 to 256, it will be clipped to 255 during serialization, potentially altering the perturbation responsible for the observed failure. This issue becomes more severe when mutations are performed on normalized inputs (e.g., pixel values scaled to [0,1] or standardized using dataset-specific statistics). Perturbations introduced in this space may not be preserved when inputs are converted back to standard representations (e.g., $[0, 255]$ pixel values) for storage, leading to additional loss or distortion.

Using this metric, we evaluate how DNN fuzzers account for these input representation constraints in their design to ensure failure reproducibility. We assess whether mutation operations constrain perturbations so that serialization does not remove or alter fault-inducing perturbations. We also consider fuzzing approaches that generate inputs directly in serialized formats (e.g., synthesized speech, rendered images, or generated text) as reproducible under this metric, since such inputs are inherently stable with respect to serialization.

5) Failure Diagnostics: Understanding why a model fails is an important objective in security testing. We include this metric to assess whether and how DNN fuzzing papers provide diagnostic analysis of discovered failures, beyond merely reporting failure cases.

To evaluate DNN fuzzing papers on this metric, we examine whether a fuzzing paper provides diagnostic insight through analysis of observable model internals (e.g., model coverage or neuron characteristics such as activation frequency, layer type, and position). Such signals are widely used in DNN fuzzing to characterize model behavior and have been empirically associated with the discovery of erroneous behaviors [62], [39]. We also examine whether failures are analyzed through statistical failure patterns (e.g., class-level error concentration, distributional proximity to other classes, or correlations between failures and input structure), and whether such analysis connects discovered failures to broader sources of model vulnerability, such as non-robust or spurious features, dataset bias, or overfitting [6], [49], [63].

6) Attack Transferability: Fault-inducing inputs crafted on a surrogate model often transfer across other models performing the same task, enabling substitute-model attacks against unseen targets without internal access [64], [65], [26]. Such transferable attacks reveal shared vulnerability patterns across model implementations, rather than failures specific to a single model.

We include the attack transferability metric to assess whether DNN fuzzing papers enable the discovery of failures that transfer across models. To evaluate DNN fuzzing papers on this metric, we examine whether fault-inducing inputs generated through fuzzing on one model are reused to test other models performing the same task, and whether the fuzzing design incorporates mechanisms that support the discovery of transferable security failures across models.

C. Assessment Methodology

To ensure consistent, scalable, and transparent application of the codebook across papers, we design a semi-automated, two-stage assessment workflow that combines LLM-assisted evidence extraction with expert review. This methodology is motivated by prior work showing substantial overlap between LLM-generated and human reviewer feedback on scientific papers [66], as well as the ICLR 2025 LLM-assisted review feedback study, which highlights the potential of carefully designed LLM-based systems to enhance peer review quality at scale [67].

LLM-assisted Evidence Extraction. In the first stage of our assessment workflow, we use an LLM-based preliminary assessment pipeline that we developed to extract metric-relevant supporting evidence and generate a preliminary assessment with accompanying rationale for each paper. The pipeline consists of two independent evaluator LLMs and an arbitrator LLM. Each LLM is instructed to extract and cite supporting evidence from the paper, a practice shown to improve factual accuracy and reduce hallucinations in LLM outputs [68], [69]. When the two evaluator LLMs produce differing preliminary assessments, the arbitrator re-examines the full paper, the codebook criteria, and the evidence extracted by the evaluators to produce an arbitrated assessment with its own rationale grounded in the extracted evidence. We use GPT-5 mini and Gemini 2.5 Pro as evaluator LLMs, and o4-mini as the arbitrator. These models represent two leading LLM families with documented capabilities for structured reasoning and long-context analysis [70], [71], [72]. All LLMs were invoked using default API parameters. Prompt templates and representative outputs, illustrating how the LLM extracts evidence to justify its assessments and how disagreements between evaluators are resolved by the arbitrator, are shown in Appendix Listings 1 and 2.

Expert Review. In the second stage, two authors independently review and verify all LLM-generated preliminary assessments. Using the supporting evidence extracted by the LLM pipeline, the authors locate and examine the corresponding design descriptions of the proposed fuzzing method (e.g., mutation strategy, exploration strategy, and oracle definition), as well as the reported experimental results. For each metric, they assess whether the extracted evidence is relevant, whether the LLM-generated rationale correctly interprets the paper, and whether the paper satisfies the corresponding codebook criteria. Based on this analysis, the authors assign a final compliance level for each metric. Any disagreements between the two authors are resolved through discussion until consensus is reached, reducing subjective interpretation.

Reliability of LLM-assisted Assessment. Using this assessment workflow, we evaluated 32 DNN fuzzing papers against the six FuzzCheck.AI security metrics. The two evaluator LLMs disagreed in 44 cases, which were resolved by the arbitrator. In these cases, the arbitrator LLM's assessment aligned with the GPT-5 evaluator in 54.5% of instances and with the Gemini evaluator in 45.5%, indicating no model-family bias. Overall, LLM-based preliminary assessments aligned with expert assessments in 87% of cases, demonstrating their reliability in accelerating reliable evaluation. Expert–LLM assessment comparisons and agreement rates per metric are provided in Appendix Tables IX and X, respectively.

V. Literature Selection and Taxonomy

A. Literature Selection

We conducted a systematic web search across major academic databases, including Google Scholar, IEEE Xplore, ACM Digital Library, USENIX, NDSS, OpenReview, and Semantic Scholar, using a set of relevant keywords. While some DNN fuzzing studies explicitly use the term "fuzzing", others adopt fuzzing-inspired principles under broader descriptions such as "DNN testing" or "deep learning testing". To capture both categories, we constructed search queries by pairing fuzzing/testing terms with various model architectures, tasks, and domains (e.g., machine learning, deep learning, large language models, speech recognition, image classification, and autonomous driving). This approach ensured broad and inclusive coverage of studies aligned with the core fuzzing paradigm, even when not explicitly labeled as such.

Initial search results were screened by title and abstract to exclude irrelevant studies, including those focused on traditional software fuzzing that use AI models as tools (e.g., for input generation) or on fuzzing of deep learning libraries and frameworks. The authors independently screened all retrieved papers for relevance, yielding 111 studies for in-depth full-text review. In the next phase, we examined each paper's methodology and experimental workflow to determine whether it implemented a systematic exploration of the input space, a defining property of fuzzing-based testing. We excluded those whose objectives and workflows differ fundamentally from fuzzing, such as coverage analyses that measure how thoroughly a fixed test dataset explores a model, metamorphic testing that checks semantic consistency under predefined transformations on fixed test dataset, and optimization-based adversarial attacks that aim to find evasive examples rather than systematically probe model behavior. Fifty-eight papers were excluded at this stage.

Finally, we filtered papers based on venue reputation and research impact. We included all papers published in CORE-ranked A* and A conferences [73], which represent the leading venues for AI, software testing, and security research. For journal and arXiv papers, we applied a citation threshold of 30 (as of October 2025) to ensure the inclusion of well-established and widely recognized studies. Twenty-one papers

were excluded during this step, resulting in a final corpus of 32 DNN fuzzing studies, which we systematically assessed using our FuzzCheck.AI framework.

B. Taxonomy of DNN Fuzzing Approaches

We categorize DNN fuzzing approaches along key design dimensions (oracle design, mutation strategy, exploration strategy, and access level) to enable systematic analysis of how design choices influence security testing metrics.

1) Oracle Design: The oracle determines whether a test input reveals a model fault. In DNN fuzzing, manually labeling ground truth for mutated or synthesized inputs is infeasible, so fuzzers infer correctness using alternative reference signals, such as consistency across semantically equivalent inputs, agreement across multiple models, or violations of explicit safety or task-specific properties. Based on these reference sources, oracle designs fall into three categories:

Metamorphic Oracle. A metamorphic oracle assumes that semantics-preserving input mutations should yield the same model prediction as the original input. Under this design, the fuzzer applies transformations (e.g., rotation, brightness changes, paraphrasing) that preserve input semantics and flags a failure when the model produces inconsistent outputs across these variants. This design is widely used in DNN fuzzing frameworks (e.g., *DLFuzz*, *DeepHunter*, *DeepCruiser*), where violations of such metamorphic relations are treated as model faults [20], [21], [12], [61], [39], [74]. Among the 32 evaluated DNN fuzzers, 14 adopt metamorphic oracles.

Differential Oracle. A differential oracle compares outputs across multiple models performing the same task and flags a failure when the models disagree on the same input. Under this design, the fuzzer executes multiple models on the same mutated input and treats disagreement as evidence of erroneous behavior, without requiring ground-truth labels [10], [40], [25]. However, this approach cannot determine which model is faulty. Among the 32 evaluated DNN fuzzers, 6 adopt differential oracles.

Property-based Oracle. A property-based oracle encodes the failure condition directly in terms of expected model behavior, defining explicit rules over model outputs (e.g., producing a specified output, generating unexpected values, or violating safety or security policies). Under this design, the fuzzer flags a failure when the model output satisfies a failure condition defined by these properties. Unlike metamorphic and differential oracles, which rely on relative comparisons, this approach directly specifies the desired or prohibited behavior. For example, *LLM-Fuzzer* [23] detects jailbreak attacks by checking whether model responses lack expected refusal patterns, while *TensorFuzz* [11] identifies failures by detecting numerical errors (e.g., NaNs/Infs) in model outputs or loss values. Among the 32 evaluated DNN fuzzers, 12 adopt property-based oracles.

2) Mutation Strategy: The mutation strategy defines how a fuzzer modifies existing inputs or generates new ones. We categorize mutation strategies based on how mutations are guided during input generation, resulting in three categories:

Feedback-informed Mutation. Applies perturbations to seed inputs whose magnitude and direction are determined by model feedback (e.g., loss, confidence, predictions, or coverage). This steers mutations toward regions more likely to induce failures. For example, *DeepXplore* [10] perturbs inputs along gradients of a joint objective that maximizes neuron coverage while inducing differential behaviors across models. Among the 32 evaluated DNN fuzzers, only 3 adopt this mutation strategy.

Rule-based Mutation. Modifies seed inputs using predefined rules, templates, or domain-specific heuristics without relying on model feedback. These mutations can be metamorphic, preserving the underlying semantics while changing their appearance or presentation; for example, adjusting brightness or rotation in images, altering playback speed or pitch in audio, or replacing words with synonyms in text [21], [75]. Others intentionally alter content to test robustness under plausible, semantically shifted conditions, such as inserting or removing objects in images or phrases in text [76]. Among the 32 evaluated DNN fuzzers, 20 use rule-based mutation.

Generative Input Synthesis. Synthesizes test inputs using auxiliary generative models rather than modifying seed inputs through perturbations or predefined rules. These inputs may be produced from scratch or conditioned on existing seeds through systems such as large language models (LLMs), generative adversarial networks (GANs), diffusion models, or text-to-speech (TTS) engines. By leveraging learned data distributions, generative synthesis produces diverse and realistic inputs that enable fuzzers to expose model behaviors beyond those reachable through traditional mutation. Among the 32 evaluated DNN fuzzers, 9 use generative synthesis to produce test inputs.

3) Exploration Strategy: The exploration strategy determines how a fuzzer searches and prioritizes candidate inputs in the fuzzing loop. An effective strategy guides the search toward under-explored or failure-prone regions of the input space. Exploration strategies use information from model internals, model outputs, oracles, or the input domain to guide this process and can be grouped into four categories:

Coverage-guided Exploration. Prioritizes inputs that expand model coverage using metrics that estimate how broadly the model's internal states have been explored. These feedback signals guide exploration toward previously unseen behaviors, and higher coverage often correlates with increased fault discovery [39]. Common metrics include neuron-activation coverage [10], [15], neuron-path coverage [77], layer-wise distributional divergence [39], [43], and surprise adequacy [78].

Prediction-guided Exploration. Selects and prioritizes inputs that drive the model's predictions toward low confidence, high loss, or other indicators of uncertainty. By steering exploration toward inputs that make the model less certain or more error-prone, this strategy effectively targets regions of the input space where failures are more likely to occur.

Data-driven Exploration. Selects inputs based on statistical or structural properties of the data rather than model feedback. Inputs may be chosen using predefined heuristics, domain-

specific priors, or random sampling from the underlying distribution. Offline analyses such as clustering, feature statistics, or error modeling guide the selection and prioritization of diverse or fault-prone inputs. Operating independently of model feedback, this approach provides a simple but broadly applicable baseline for exploring the input space.

4) Access Level: The access level defines how much internal visibility a fuzzer has within the target model. Whether it can inspect gradients, neuron activations, and model parameters, or instead operates solely on model outputs, determines the range of feasible mutation strategies and feedback mechanisms. This access level reflects the underlying threat model and dictates what information the fuzzer can leverage during testing.

- **Whitebox:** Full access to model parameters, gradients, and neuron activations. This enables precise, gradient-based input mutation and targeted exploration near decision boundaries.
- **Greybox:** Partial access to internal model behavior, typically limited to signals such as neuron activations or intermediate layer outputs. Without access to parameters or gradients, fuzzing uses these internal signals as feedback to guide input mutation toward diverse or fault-revealing behaviors.
- **Blackbox:** No access to internal signals or model structure; only the model's outputs in response to given inputs are observable. Fuzzing relies on these outputs, such as prediction probabilities or confidence scores, to guide mutation and exploration.

We classify each fuzzer along these four dimensions, capturing its oracle design, mutation and exploration strategies, and model access level. These design choices are summarized in Table III.

TABLE III
FULFILLMENT LEVELS AND DESIGN CHOICES OF 32 DNN FUZZERS. **M**, **E**, AND **O** DENOTE MUTATION, EXPLORATION, AND ORACLE, RESPECTIVELY. METRICS (FS, TA, IP, FR, FD, AT) ARE DEFINED IN TABLE II.

Method/Author	Year	Design			Security Metrics					
		M	E	O	FS	TA	IP	FR	FD	AT
Blackbox										
PAIR [22]	2025	G	P	Pr	●	◑	●	●	○	◑
PAPILLON [42]	2025	G	P	Pr	●	◑	●	●	◑	◑
AutoDAN [26]	2024	G	P	Pr	●	●	●	●	○	◑
LLM-Fuzzer [23]	2024	G	P	Pr	●	◑	●	●	○	●
CureFuzz [79]	2024	R	P	Pr	◑	◑	●	●	◑	○
DRFuzz [41]	2023	R	P	Df	○	○	●	◑	●	○
ASDF [80]	2023	R	P	Df	○	○	●	●	◑	○
MDPFuzz [81]	2022	R	P	Pr	◑	◑	●	●	◑	○
BET [48]	2022	R	P	Pr	○	●	●	●	○	○
QATest [82]	2022	R	D	M	○	○	◑	●	◑	○
semSensFuzz [76]	2022	R	D	M	◑	○	●	◑	◑	○
CrossASR++ [25]	2021	G	D	Df	○	○	●	●	○	○
Asyrofi et al. [83]	2021	G	D	Df	○	○	●	●	○	○
Sensei [84]	2020	R	P	Pr	○	○	●	◑	○	○
KuK [51]	2020	R	P	M	●	○	◑	○	◑	◑
CrossASR [40]	2020	G	P	Df	○	○	●	●	○	○
LipFuzzer [85]	2019	R	D	M	◑	○	●	●	◑	○
Greybox										
Zhou et al. [24]	2025	G	C	Pr	●	◑	●	●	◑	○
NLC [39]	2023	R	C	M	○	○	◑	◑	◑	○
DistXplore [43]	2023	R	C	Pr	○	●	◑	◑	◑	○
TESTRNN [86]	2021	R	C, P	M	○	○	◑	◑	◑	○
TACTIC [87]	2021	G	C, P	M	○	○	●	◑	◑	○
HDTest [88]	2021	R	P	M	○	○	◑	○	◑	○
DeepHunter [21]	2019	R	C	M	○	○	●	◑	◑	○
TensorFuzz [11]	2019	R	C	Pr	○	◑	●	◑	◑	○
DeepStellar [75]	2019	R	C	Pr	○	○	◑	◑	◑	○
DeepEvolution [89]	2019	R	C	M	○	○	●	◑	○	○
DeepTest [12]	2018	R	C	M	◑	○	◑	◑	◑	○
DeepCruiser [61]	2018	R	C	M	○	○	◑	◑	◑	○
Whitebox										
ADAPT [62]	2020	F	C	M	○	○	◑	○	◑	○
DLFuzz [20]	2018	F	C, P	M	○	○	●	○	○	○
DeepXplore [10]	2017	F	C, P	Df	○	○	◑	●	◑	○

Symbols: ●=High, ◑=Medium, ○=Low.
Mutation: **F**=Feedback-informed, **R**=Rule-based, **G**=Generative Synthesized.
Exploration: **C**=Coverage-guided, **P**=Prediction-guided, **D**=Data-driven.
Oracle: **M**=Metamorphic, **Df**=Differential, **Pr**=Property-based.

VI. ANALYSIS AND FINDINGS

Our findings, as detailed in Table III, show that none of the 32 DNN fuzzing papers satisfy all six security testing metrics, and 19 exhibit low compliance on at least three. We analyze these results across metrics, design choices, and publication year to identify systematic blind spots in existing fuzzing approaches.

A. Failure Severity

Only 18.8% of DNN fuzzers discover high-severity failures that bypass safety or security mechanisms, while 15.6% expose medium-severity violations of user intent or safety expectations. The remaining 65.6% focus on robustness errors, indicating that most fuzzers focus on functional robustness testing rather than security-relevant failure discovery (Table IV).

Fuzzers focusing on bypassing safety or security mechanisms apply fuzz testing to models equipped with explicit safeguards. PAIR [22], PAPILLON [42], AutoDAN [26], LLM-Fuzzer [23], and Zhou et al. [24] uncover jailbreaks in aligned LLMs such as GPT-4 and Gemini Pro. These fuzzers employ property-based oracles whose failure conditions explicitly encode security or policy violations (e.g., offensive or disallowed content generation). KuK [51] discovers failures that bypass adversarial attack detection techniques. In contrast, none of the fuzzers with whitebox access, feedback-informed mutation, or differential oracles have been applied to safeguarded models (Table V). Temporal trends (Table VI) show that fuzzers explicitly evaluating models with safety or security safeguards have emerged only recently, primarily during 2024–2025, indicating an emerging focus on discovering high-severity security failures.

Fuzzers rated medium in failure severity expose violations of user intent or safety expectations without breaching explicit

TABLE IV
DISTRIBUTION OF DNN FUZZING STUDIES BY COMPLIANCE LEVEL ACROSS FUZZCHECK.AI METRICS DEFINED IN TABLE II.

Level	FS	TA	IP	FR	FD	AT
High (●)	18.8%	9.4%	65.6%	46.9%	3.1%	3.1%
Medium (◑)	15.6%	21.9%	34.4%	40.6%	65.6%	12.5%
Low (○)	65.6%	68.8%	0.0%	12.5%	31.2%	84.4%

TABLE V
PERCENTAGE (%) OF STUDIES PER DESIGN CHOICE EXHIBITING DIFFERENT MATURITY LEVELS ACROSS FUZZCHECK.AI METRICS. SHADED CELLS INDICATE WHERE OVER 50% OF STUDIES FALL INTO THAT LEVEL. **L.**=FULFILLMENT LEVEL.

Metric	L.	Access			Mutation			Exploration			Oracle		
		W	G	B	F	R	G	C	P	D	M	Df	Pr
Failure Severity	●	0	8	29	0	5	56	7	29	0	7	0	42
	◑	0	8	24	0	25	0	7	12	40	21	0	17
	○	100	83	47	100	70	44	86	59	60	71	100	42
Targeted Attack Discovery	●	0	8	12	0	10	11	7	12	0	0	0	25
	◑	0	17	29	0	15	44	14	29	0	0	0	58
	○	100	75	59	100	75	44	79	59	100	100	100	17
Input Plausibility	●	33	42	88	33	55	100	43	76	80	43	83	83
	◑	67	58	12	67	45	0	57	24	20	57	17	17
	○	0	0	0	0	0	0	0	0	0	0	0	0
Failure Reproducibility	●	33	8	76	33	30	89	14	59	80	14	83	67
	◑	0	83	18	0	60	11	71	24	20	57	17	33
	○	67	8	6	67	10	0	14	18	0	29	0	0
Failure Diagnostics	●	0	0	6	0	5	0	0	6	0	0	17	0
	◑	67	92	47	67	80	33	86	53	60	86	33	58
	○	33	8	47	33	15	67	14	41	40	14	50	42
Attack Transferability	●	0	0	6	0	0	11	0	6	0	0	0	8
	◑	0	0	24	0	5	33	0	24	0	7	0	25
	○	100	100	71	100	95	56	100	71	100	93	100	67

Symbols: ●=High, ◑=Medium, ○=Low.
Abbreviations: **W**=Whitebox, **G**=Greybox, **B**=Blackbox, **F**=Feedback-informed, **R**=Rule-based, **G**=Generative Synthesized, **C**=Coverage-guided, **P**=Prediction-guided, **D**=Data-driven, **M**=Metamorphic, **Df**=Differential, **Pr**=Property-based.

safeguards. CureFuzz [79] and MDPFuzz [81], for instance, expose unsafe control behaviors in autonomous systems, such as sudden turns, off-route maneuvers, or collision-prone trajectories. LipFuzzer [85] triggers misinterpretations in voice assistants, causing benign commands to launch unintended apps or share data with untrusted recipients.

Fuzzers rated low in this metric primarily expose robustness errors such as misclassifications, inconsistent outputs for semantically equivalent inputs, or divergent predictions across models performing the same task (e.g., DLFuzz [20], DeepHunter [21], CrossASR [40]). The discovery of robustness errors has been extensively studied across diverse design configurations, with nearly all fuzzers with whitebox access (100%), feedback-informed mutation (100%), coverage-guided exploration (86%), and differential oracles (100%) falling into this category (Table V).

B. Targeted Attack Discovery

Only 9.4% (3 out of 32) of DNN fuzzers achieve high fulfillment on the *Targeted Attack Discovery* metric by steering exploration toward specific, attacker-chosen outputs, while the majority (68.8%) focus on untargeted failure discovery (Table IV). Fuzzers rated high on this metric most frequently use rule-based mutation (11%), prediction-guided exploration (12%), and rely on property-based oracles (25%) to encode targeted attack conditions (Table V). Untargeted fuzzing dominated the literature from 2017 through 2023, with targeted attack discovery emerging primarily in 2024–2025 (Table VI).

Targeted attack discovery depends on how a fuzzer steers its search toward target failures and how the oracle defines the failure condition. Property-based oracles can explicitly encode target conditions in the failure definition. For example, AutoDAN [26] checks whether LLM outputs contain predefined affirmative prefixes (e.g., "Sure, here is how to…"). In our evaluation, 25% of fuzzers using property-based oracles achieve high ratings on this metric (Table V). In contrast, metamorphic and differential oracles inherently limit targeted discovery. Metamorphic oracles check for prediction inconsistency across semantically equivalent inputs, while differential oracles detect disagreement across models; neither defines what constitutes a targeted failure. Consequently, fuzzers that rely primarily on these oracles fall into the low category in our evaluation.

Exploration strategy also plays a critical role in targeted attack discovery by determining which inputs are prioritized for further mutation. Prediction-guided and coverage-guided exploration leverage model feedback to prioritize inputs that move outputs closer to a target condition, thereby supporting targeted exploration. In contrast, data-driven exploration relies on input distribution characteristics without incorporating model feedback, limiting its ability to steer search toward target outputs.

Feedback-informed mutation is well-suited for targeted attack discovery because it can modify inputs in directions that move model outputs toward a target failure condition. However, mutation alone is insufficient. All fuzzers using this strategy (e.g., DeepXplore [10], DLFuzz [20], ADAPT [62]) do not support targeted attack discovery because their oracle design (metamorphic or differential) does not encode target conditions. In contrast, some fuzzers with rule-based mutation or generative synthesis support targeted attack discovery by combining a property-based oracle with feedback-guided targeted exploration. For example, *BET* [48] supports targeted attack discovery by defining a target label as the failure condition in the oracle and generating continuous perturbations whose structure (e.g., sign and shape) follows predefined patterns inspired by convolutional kernel properties. It then evaluates mutated inputs using a label-specific objective function and prioritizes those whose outputs exhibit higher confidence for the target label, iteratively refining inputs toward the desired failure condition.

Overall, these findings indicate that targeted attack discovery primarily depends on oracle design to encode target failure conditions, while prediction-guided exploration enables effective search toward targeted failures. Notably, feedback-informed mutation strategies have not been used for targeted attack discovery in existing fuzzers, despite their potential, highlighting an important gap.

TABLE VI
YEAR-WISE MATURITY TRENDS OF FUZZCHECK.AI METRICS IN DNN FUZZING STUDIES (2017–2025). CELLS SHOW THE PERCENTAGE (%) OF STUDIES AT EACH COMPLIANCE LEVEL; SHADED CELLS INDICATES DOMINANCE (>50%). **L.**=FULFILLMENT LEVEL.

Metric	L.	'17	'18	'19	'20	'21	'22	'23	'24	'25
Failure Severity	●	0	0	0	25	0	0	0	67	100
	◑	0	33	20	0	0	50	0	33	0
	○	100	67	80	75	100	50	100	0	0
Targeted Attack Discovery	●	0	0	0	0	0	25	25	33	0
	◑	0	0	20	0	0	25	0	67	100
	○	100	100	80	100	100	50	75	0	0
Input Plausibility	●	0	33	80	50	60	75	25	100	100
	◑	100	67	20	50	40	25	75	0	0
	○	0	0	0	0	0	0	0	0	0
Failure Reproducibility	●	100	0	20	25	40	75	25	100	100
	◑	0	67	80	25	40	25	75	0	0
	○	0	33	0	50	20	0	0	0	0
Failure Diagnostics	●	0	0	0	0	0	0	25	0	0
	◑	100	67	80	50	60	75	75	33	67
	○	0	33	20	50	40	25	0	67	33
Attack Transferability	●	0	0	0	0	0	0	0	33	0
	◑	0	0	0	25	0	0	0	33	67
	○	100	100	100	75	100	100	100	33	33

Symbols: ●=High, ◑=Medium, ○=Low.

C. Input Plausibility

Most DNN fuzzers explicitly focus on ensuring input plausibility during test generation. A majority (62.5%) of the 32 evaluated studies achieve high compliance by enforcing plausibility throughout the fuzzing process. The remaining 37.5% constrain perturbations only between successive mutation steps, but overlook the cumulative effect of perturbations across fuzzing iterations, which can render inputs implausible (Table IV).

Among fuzzers achieving high input plausibility, 91% adopt generative synthesis-based mutation to produce realistic test inputs using generative models such as LLMs, GANs, or text-to-speech systems (Table V). LLM fuzzers such as PAIR, AutoDAN, and LLM-Fuzzer achieve high input plausibility by generating jailbreak prompt templates via LLM-mediated rewriting or semantically guided prompt construction, keeping fault-inducing prompts coherent, human-readable, and semantically meaningful. CrossASR [**?**], CrossASR++ [**?**], and Asyrofi et al. [**?**] maintain high input plausibility by synthesizing test inputs as speech from natural corpus text and excluding indeterminable cases where the generated audio is likely invalid.

Among fuzzers achieving high input plausibility, 91% adopt generative synthesis-based mutation to produce realistic test inputs using generative models such as LLMs, GANs, or text-to-speech systems (Table V).

High-compliance rule-based mutation fuzzers preserve plausibility through explicit constraints on mutation chains. For example, DeepHunter [21] restricts affine transformations (e.g., rotation, translation, scaling) to at most once per mutation chain and enforces pixel-change bounds with respect to a reference image, while DeepEvolution [89] computes structural similarity (SSIM) with respect to the original seed and discards visually distorted inputs from the seed pool. Similarly, feedback-informed mutation fuzzers such as DLFuzz [20] and BET [48] enforce plausibility by bounding all perturbations with respect to the original seed, thereby preventing cumulative drift across fuzzing iterations.

Approximately half of the feedback-informed and rule-based mutation fuzzers exhibit medium compliance on this metric, primarily because they overlook the cumulative effect of perturbations across fuzzing iterations (Table V). For example, DeepXplore [10] applies domain-specific constraints and DeepTest [12] applies semantic-preserving transformations at individual mutation steps, but neither accounts for the effect of cumulative small changes on an input over multiple iterations. Similarly, NLC [39] discards mutated inputs when the number of changed pixels between a mutated input and its parent seed exceeds a threshold, but fails to consider how small, bounded changes can accumulate across iterations. QATest [82] checks quality drift between successive mutations, but overlooks drift introduced across longer mutation chains spanning multiple fuzzing iterations.

Input plausibility improves steadily over time. Early studies (2017–2018) are dominated by medium compliance, while from 2019 onward high compliance becomes dominant. By 2024–2025, all evaluated fuzzers achieve high compliance, reflecting a growing focus on maintaining plausibility across fuzzing iterations, rather than only between successive mutations (Table VI).

D. Failure Reproducibility

DNN fuzzing papers exhibit mixed compliance with the failure reproducibility metric: 46.9% achieve high compliance, 40.6% medium, and 12.5% low (Table IV).

Fuzzers with high failure reproducibility explicitly account for standard I/O effects by generating or mutating inputs in forms that persist after serialization. Most DNN fuzzers employing generative input synthesis–based mutation strategies (91%) demonstrate high reproducibility because they produce test inputs directly in serialized formats (Table V). Representative examples include LLM-generated text prompts (e.g., PAIR [22] and PAPILLON [42]) and speech synthesized via text-to-speech models (e.g., LipFuzzer [85] and CrossASR [40]). In contrast, only 22% of rule-based mutation fuzzers ensure failure reproducibility. Among these, CureFuzz [79] and MDPFuzz [81] achieve high reproducibility by constraining mutations within physically valid bounds and validating each mutated state through autonomous-agent simulation. Among feedback-informed mutation fuzzers, BET [48] and DeepXplore [10] achieve high compliance by applying integer-level perturbations to pixel values. Table VI indicates that failure reproducibility was recognized early as an important concern, but later works exhibit mixed compliance before recent fuzzers (2024–2025) consistently ensure high reproducibility of discovered failures.

Approximately 67% of rule-based mutation fuzzers exhibit medium reproducibility, primarily because they apply

semantic-preserving metamorphic transformations but overlook quantization effects such as clipping and rounding (e.g., DeepHunter [21], DeepCruiser [61], DeepTest [12]). The generative synthesis–based fuzzer TACTIC [87] synthesizes driving scenes using a GAN-based image-to-image translation model, but does not ensure that pixel-level changes introduced by the GAN remain stable under standard I/O operations.

Finally, a substantial fraction of feedback-informed mutation fuzzers (50%) exhibit low compliance with this metric. DLFuzz [20] and ADAPT [62] apply fine-grained perturbations to normalized floating-point tensors without rounding or clipping, limiting failure reproducibility.

E. Failure Diagnostics

Among the 32 DNN fuzzers evaluated using our FUZZCHECK.AI framework, only DRFuzz [62] achieves high compliance with the failure diagnostics metric by explaining discovered regression failures as evidence of bias or overfitting in the learning process. In contrast, 65.6% of fuzzers achieve only medium compliance by offering heuristic or correlational explanations, such as linking failures to model activation diversity or reporting statistical patterns in fault occurrence, without attributing them to underlying causes. The remaining 31.2% merely report failure cases without any diagnostic analysis, providing no insight into why the failures occur (Table IV). The temporal trend (Table VI) shows no sustained upward trend in failure diagnostics over time. Medium compliance consistently dominates across years, suggesting that most DNN fuzzing research remains limited to correlational analyses rather than advancing toward deeper explanations of underlying model vulnerabilities.

Most coverage-guided fuzzers (86%) achieve only medium compliance with this metric (Table V). These fuzzers typically correlate failures with observable model internals or report statistical patterns in fault occurrence. For example, ADAPT [62] correlates failures with neuron characteristics such as activation frequency, layer type, and position, suggesting instability in specific regions of the network. Others, including TESTRNN [86], DeepCruiser [61], NLC [39], and DeepStellar [75], correlate fault-triggering inputs with neuron coverage expansion. ASDF [80] performs phoneme-level analysis to associate specific sounds with transcription errors, while LipFuzzer [85] links semantic misinterpretations to linguistic ambiguity. However, these analyses remain correlational and do not explain how the observed failures arise from underlying model vulnerabilities, such as reliance on non-robust or spurious features, dataset bias, or overfitting.

F. Attack Transferability

Among the 32 DNN fuzzing papers, only LLM-Fuzzer [23] is explicitly designed to discover transferable attacks, integrating feedback from multiple models into the fuzzing loop and rewarding prompts that succeed across models. In contrast, only 12.5% of fuzzers evaluate whether discovered failures transfer across models, while 84.4% entirely overlook transferability as a DNN security testing objective (Table IV).

As shown in Table V, support for attack transferability is limited across all access levels and fuzzing design configurations, indicating that most DNN fuzzers focus on model-specific failure discovery rather than vulnerabilities shared across models. The temporal trends in Table VI further show that only recent works from 2024–2025 exhibit limited consideration of transferable attack discovery.

G. Key Findings

Limited support for high-severity failure discovery. Only 18.8% of evaluated fuzzers discover high-severity failures that bypass explicit safety or security mechanisms, while 65.6% focus exclusively on low-severity robustness errors (e.g., prediction inconsistencies under semantically equivalent inputs).

Limited support for targeted attack discovery. Only 9.4% of evaluated fuzzers support targeted attack discovery by steering exploration toward attacker-chosen outputs, while the majority (68.8%) prioritize untargeted failure discovery, leaving the discovery of targeted security-violating behaviors largely unexplored.

Overlooked cumulative mutation effects. Although the majority (62.5%) of evaluated DNN fuzzers achieve high input plausibility, largely by leveraging generative synthesis-based mutation to produce realistic test inputs (91%), a substantial fraction (37.5%) fail to account for cumulative mutation effects across iterations, leading to the discovery of failures induced by unrealistic or semantically invalid inputs.

A recurring blind spot in failure reproducibility. Over half (53.1%) of evaluated fuzzers overlook serialization effects (e.g., clipping, rounding), resulting in fragile in-memory failures that may not persist after standard I/O operations.

Near-absence of causal failure diagnostics. Most DNN fuzzing papers (96.8%) provide only partial or no failure diagnostics: 65.6% offer correlational insights based on model internals or failure statistics, while 31.2% provide no diagnostic analysis.

Rare support for transferable attack discovery. Only one DNN fuzzer is explicitly designed to discover transferable failures. Although a small fraction (12.5%) evaluates transferability after discovery, most fuzzers do not incorporate mechanisms to actively discover failures that transfer across models, limiting insight into shared model vulnerabilities.

Fragmented support for comprehensive security testing. No evaluated fuzzer achieves high compliance across all six metrics, and the majority (59.4%, 19/32) exhibit low compliance on three or more metrics, indicating that most fuzzers are designed to address isolated requirements rather than comprehensive security testing.

H. Research Outlook for DNN Fuzzing

Our analysis suggests that current DNN fuzzing designs are already effective for some testing objectives, but remain limited for comprehensive security testing. In particular, existing fuzzers are well suited to robustness-oriented testing, where the goal is to uncover mispredictions, inconsistent behaviors,

regression faults, or other erroneous outputs under systematic input mutation. This strength is reflected in the large body of work on coverage-guided exploration, metamorphic mutation, and differential testing, which has shown that fuzzing can efficiently expose a wide range of model errors without relying on fixed benchmark datasets. More broadly, fuzzing provides a flexible and automated framework for probing DNN behavior across different access levels, model families, and application domains.

At the same time, our results highlight several recurring limitations when DNN fuzzing is viewed from a security-testing perspective. First, most existing fuzzers remain oriented toward generic fault discovery rather than toward security-relevant failure objectives. As a result, they often lack mechanisms to target safeguarded models, attacker-chosen outcomes, or transferable failures across models. Second, many fuzzers optimize for failure discovery volume without ensuring that the resulting failures remain realistic, reproducible, or diagnostically informative. This creates a gap between finding many errors and exposing failures that are meaningful for security evaluation. Third, current evaluation practices are fragmented: fuzzers are often assessed using method-specific notions of effectiveness, making it difficult to determine whether discovered failures satisfy broader security testing requirements.

These observations point to several critical research challenges for the next stage of DNN fuzzing. A first challenge is *security-aware oracle design*. Robustness-oriented oracles based on misclassification or disagreement are often insufficient for security testing, which requires failure conditions tied to harmful behavior, safeguard bypass, attacker-chosen outputs, or transfer across models. A second challenge is *threat-model-aligned mutation and exploration*. Security-oriented fuzzing requires search strategies that preserve realistic inputs when appropriate, support directional progress toward attacker objectives, and avoid discovering failures that depend only on fragile artifacts. A third challenge is *diagnostic depth*. If DNN fuzzing is to contribute not only to failure discovery but also to model hardening, fuzzers must better explain why failures occur and how they relate to underlying vulnerabilities such as spurious features, dataset bias, or overfitting. A fourth challenge is *standardized security evaluation*. Without shared benchmarks, defended target models, and metric-aware evaluation protocols, it remains difficult to compare fuzzers in terms of the security properties they actually test.

Taken together, these findings suggest that the central opportunity for future work is not merely to make DNN fuzzers discover more failures, but to make them discover the *right kinds* of failures for security testing. In this sense, the next phase of DNN fuzzing research is likely to depend less on improving generic search efficiency alone, and more on designing fuzzers whose mutation, exploration, and oracle components are explicitly aligned with security testing objectives.

VII. Recommendations

Our analysis highlights several targeted opportunities to design DNN fuzzing methods .

We next distill concrete recommendations for designing DNN fuzzers that better support the six security testing requirements captured by FuzzCheck.AI. We then illustrate how these recommendations can be applied in practice through a small case study on NLC [39].

High-severity failure discovery.

To enable high-severity security failure discovery, we recommend using models equipped with defense mechanisms as fuzzing targets, such as adversarially trained or safety-aligned models, or models protected by external filtering or detection components. Mutation and exploration strategies in fuzzing design can incorporate feedback signals from the defense mechanisms. Security and policy violations (e.g., jailbreaks, hallucinations, data leakage, or backdoor trigger activation) should be explicitly encoded in the oracle design to discover high-severity security failures.

To enable high-severity security failure discovery, fuzzers should target models equipped with explicit safeguards, such as adversarial defenses, safety alignment, or external filters, and should define failure conditions in terms of security-relevant violations (e.g., jailbreaks, unsafe actions, data leakage, or backdoor activation). This requirement can be satisfied in different ways across fuzzing designs. Property-based oracles can directly encode prohibited behaviors, feedback-informed mutation can exploit signals exposed by defenses or rejection mechanisms, and rule-based or generative mutation can be combined with safeguarded targets and security-aware evaluation to search for failures that bypass deployed protections rather than only robustness errors on undefended models.

Targeted attack discovery. To support targeted attack discovery, fuzzers should make the target outcome explicit in the oracle and use search guidance that rewards progress toward that target. Feedback-informed mutation can provide directional updates toward attacker-chosen labels, phrases, or outputs, but targeted discovery is not limited to gradient-based designs. Rule-based mutation can also support targeted discovery when candidate mutations are scored by target closeness, and generative mutation can condition synthesis on attacker objectives or target prompts. Across these designs, the key requirement is that exploration is driven by a target-aware objective rather than by generic error discovery alone.

Input plausibility enforcement. To ensure the plausibility of discovered fault-inducing inputs, fuzzers should enforce plausibility on the final generated input rather than only on each local mutation step. For rule-based and feedback-informed mutation, this means constraining perturbations relative to the original reference seed, not only the current mutated input, so that cumulative drift remains bounded across iterations. Such drift can be quantified using task-specific similarity measures, including LPIPS [90] or SSIM [91] for images, PESQ [92] or STOI [93] for speech, and perplexity [94] for text. Generative-synthesis designs already provide stronger support for this metric when they generate inputs directly from plausible task-valid distributions; in such cases, plausibility can be further strengthened using domain validity checks or auxiliary filters that reject unrealistic generations.

Failure reproducibility enforcement. To address failure reproducibility, fuzzers should ensure that a discovered failure remains valid under the representation and I/O path through which the input would actually be used. Generative-synthesis approaches that produce serialized text, audio, or rendered artifacts already provide strong support for this metric, since the generated artifact is itself the executed test input. For rule-based and feedback-informed mutation on continuous tensors, reproducibility can be improved by enforcing clipping and rounding during mutation, constraining perturbations so that de-normalization yields valid discrete inputs, and re-validating failures after standard serialization and reloading. For image-domain fuzzers, this includes checking persistence after writing and re-reading pixel-valued inputs; for audio, this includes clipping amplitudes to valid ranges and rechecking failures on the serialized waveform.

Causal failure diagnostics. To improve failure diagnostics, fuzzers should move beyond reporting failure counts and examples to explain why failures occur. This can be done through different forms of analysis depending on the design. Greybox and whitebox fuzzers can leverage activations, coverage signals, saliency maps, or layer-level behaviors to localize where failures arise. Blackbox fuzzers can still provide diagnostics by analyzing statistical failure patterns, clustering discovered failures, or evaluating targets with known vulnerabilities such as spurious correlations, dataset bias, or overfitting. In all cases, the goal is to connect discovered failures to underlying model weaknesses rather than reporting them only as isolated incidents.

Transferable attack discovery. To enable transferable attack discovery, fuzzers should evaluate whether discovered failures generalize beyond the model used during search and should incorporate transfer-aware feedback whenever possible. One route is to reuse fault-inducing inputs on additional models after discovery, which at least measures transferability. Stronger support can be achieved by incorporating multiple models into the search loop and rewarding candidate inputs that satisfy the failure condition across models. This can be implemented in feedback-informed designs using cross-model confidence or prediction shifts, and in rule-based or generative designs using cross-model oracle agreement or transfer-aware ranking of candidate seeds. The key requirement is that transferability is treated as an explicit testing objective rather than as an incidental post-hoc observation.

Case Study: Improving NLC [39] with FUZZCHECK.AI Recommendations. To demonstrate the practical utility of our recommendations, we apply our failure reproducibility and input plausibility recommendations to NLC. This fuzzer only partially satisfies these metrics. For reproducibility, NLC clips mutated pixel values to the valid range $[0, 255]$ but does not apply integer rounding, which can leave fault-inducing inputs sensitive to saving and reloading. For plausibility, NLC constrains perturbation magnitude with respect to a reference input for affine and pixel-level transformations, but allows texture-level transformations to bypass this check. We therefore implement two lightweight refinements. We add integer rounding during mutation to improve failure reproducibility, and enforce the plausibility check for all mutation types to improve input plausibility. As shown in Table VII, these refinements directly address the corresponding limitations and lead to measurable improvements. Enforcing reproducibility increases the failure reproducibility rate from 68.95% to 99.72%. Enforcing plausibility improves input quality, measured using CLIP image-image similarity between mutated inputs and their seed images, raising mean similarity from 0.733 to 0.820 and reducing plausibility violations (similarity below 0.80) from 66.91% to 37.29%. Combining both refinements achieves a favorable balance, maintaining high reproducibility (99.75%) while retaining most of the plausibility gain (average similarity 0.811, violation rate 38.20%). Overall, this case study shows that FUZZCHECK.AI recommendations can be translated into concrete fuzzer refinements for specific security-testing metrics, here improving failure reproducibility and input plausibility without fundamentally altering the fuzzer design.

TABLE VII
EFFECT OF APPLYING FUZZCHECK.AI RECOMMENDATIONS TO NLC. **#F**: FAILURE COUNT, **FR**: FAILURE REPRODUCIBILITY, **CLIP-SIM.**: MEAN CLIP IMAGE-IMAGE SIMILARITY TO THE ORIGINAL SEED, **IPV**: INPUT PLAUSIBILITY VIOLATION RATE (CLIP SIMILARITY BELOW 0.80).

Variant	#F	FR (%)	CLIP-sim.	IPV (%)
NLC [39]	1594	68.95	0.733	69.57
NLC + FR	1442	99.72	0.766	59.50
NLC + IP	952	94.43	0.820	37.29
NLC + FR + IP	1178	99.75	0.811	38.20

VIII. REPRODUCIBILITY AND EXTENSIBILITY

Our evaluation framework is designed to facilitate transparent, reproducible, and scalable evaluation of DNN fuzzing approaches. Its clear definition of evaluation metrics and structured codebook enables researchers and stakeholders to accurately replicate our study. Importantly, the DNN security testing requirements captured by FUZZCHECK.AI extend to other DNN testing paradigms, including adversarial attack-based testing [95], metamorphic testing [13], and emerging evaluation methods. New dimensions can be incorporated by expanding the codebook without modifying the assessment workflow, enabling systematic adaptation to evolving security testing needs.

future fuzzing design - we can input the plan of fuzzing design components to FuzzCheck.AI to see how that supports these secuirty metrics.

IX. DISCUSSION

Limitations. Our evaluation is limited by the completeness and clarity of methodology descriptions and experimental results reported in DNN fuzzing papers. As the analyzed works are selected from peer-reviewed, reputable venues, we assume that their reported designs and results are accurate. Since the assessment of research papers is inherently subjective, we employ a structured codebook, LLM-assisted evidence extraction, and independent expert review to promote consistency and

reduce bias. LLMs support metric-related evidence extraction and preliminary assessment, but final assessments are based on independent expert review, with disagreements among experts resolved through discussion. These safeguards mitigate both LLM hallucinations and human subjectivity. Although LLM behavior may evolve with model updates, transparent evidence citation and expert verification help ensure reproducibility and interpretability.

Future Work. An important direction for future work is to translate FUZZCHECK.AI into a quantitative evaluation framework that enables standardized benchmarking of DNN fuzzing methods across all six metrics. Such a framework could include models deployed with explicit defense mechanisms, such as adversarially trained or safety-aligned systems, as fuzzing targets, enabling controlled evaluation of a fuzzer's ability to discover high-severity security failures. It could further assess targeted attack discovery capability by quantifying a fuzzer's ability to generate inputs that induce attacker-chosen outcomes, such as malware classified as benign, unsafe images labeled as safe, or benign speech transcribed as unauthorized commands. The framework could also quantify input plausibility by measuring the degree to which fault-inducing inputs preserve realism and semantic validity, using domain-specific metrics such as LPIPS or SSIM for images, PESQ or STOI for speech, and perplexity for text. Failure reproducibility could be evaluated by quantifying the proportion of discovered failures that persist after fault-inducing inputs are stored to disk and reloaded. Failure diagnostics could be assessed by incorporating target models with known vulnerabilities and measuring how discovered failures correlate with these weaknesses, for example by examining whether failures concentrate on classes affected by spurious correlations, dataset bias, or overfitting. Finally, attack transferability could be measured by quantifying the proportion of fault-inducing inputs that generalize to other models performing the same task across different architectures and implementations.

X. CONCLUSION

This study reveals systematic blind spots in current DNN fuzzing designs across core security testing requirements. Applying FUZZCHECK.AI to 32 representative DNN fuzzing papers, we find that no existing fuzzer achieves high compliance across all metrics, with limited support for security-relevant failure discovery (e.g., high-severity, targeted, and transferable attacks), blind spots in input plausibility and failure reproducibility, and a near absence of causal failure diagnostics. These findings highlight a central open challenge: designing DNN fuzzers that efficiently discover security failures while jointly satisfying all security testing requirements. Our recommendations outline concrete guidelines for achieving high compliance on each metric and for integrating fuzzing designs with complementary strengths to enable comprehensive DNN security testing.

ETHICAL CONSIDERATIONS

This work is a Systematization of Knowledge (SoK) that analyzes DNN fuzzing research based on publicly available, peer-reviewed academic papers. The study does not involve experimentation on live systems, interaction with deployed models, collection of user data, or use of proprietary datasets. All assessments are derived from evidence explicitly reported in the evaluated literature.

Stakeholder Analysis. This study involves four stakeholder groups. (1) *Authors of evaluated DNN fuzzing papers:* Their methods, design choices, and reported empirical results are interpreted and categorized using a structured evaluation framework. (2) *AI security research community:* Researchers and practitioners may rely on the synthesized findings to guide future fuzzing designs, evaluation practices, and research directions. (3) *Research team:* During the assessment process, the researchers of this work may be exposed to potentially harmful model inputs, such as adversarial examples or jailbreak prompts reported in the evaluated papers. (4) *Adversaries:* Although not direct participants, adversaries may gain insights into common limitations or under-explored testing dimensions across fuzzing approaches.

Impact of the Research. The publication of FUZZCHECK.AI has both positive and negative impacts on the identified stakeholders.

Positive Impacts. This work (1) provides the AI security research community with a structured and transparent evaluation framework for assessing the security testing capabilities and limitations of DNN fuzzing approaches; (2) reveals recurring blind spots and trade-offs trade-offs among fuzzing design choices and DNN security testing metrics; and (3) informs future DNN fuzzing design by distilling actionable recommendations to improve security failure discovery.

Negative Impacts. (1) Assessments may be inaccurate for some evaluated papers due to incomplete reporting, ambiguous descriptions, or subjective interpretation, potentially misrepresenting reported methods or empirical evidence. (2) The research team may encounter descriptions of potentially harmful model inputs, such as adversarial examples or jailbreak prompts, reported in the evaluated papers. (3) Aggregated insights may indirectly inform adversaries about under-explored testing dimensions or common limitations across classes of fuzzing approaches.

Mitigations. (1) We mitigate the risk of potential inaccurate assessments by grounding all evaluations in a transparent codebook with explicit criteria. Each assessment is supported by evidence from the evaluated paper. All LLM-extracted evidence and preliminary assessments are independently reviewed by two authors, with disagreements resolved through discussion and consensus. (2) Encounter to potentially harmful model inputs reported in the evaluated papers is mitigated by limiting analysis to descriptive content in the literature and avoiding the reproduction, replay, or execution of adversarial examples or jailbreak prompts. (3) Any potential adversarial misuse is limited by the scope of this work, which reports

aggregated observations derived from existing literature and does not introduce new attack methods or exploit strategies.

Justification for Research. This work addresses the lack of clarity in DNN fuzzing research regarding how different fuzzing approaches satisfy core security testing requirements. By systematically evaluating representative fuzzing approaches against a structured set of security-oriented metrics, the study reveals recurring blind spots and trade-offs in current practices and distills concrete recommendations for improving security failure discovery. We determined that the benefits of this work outweigh the risks identified above, which are mitigated through methodological safeguards.

Open Science

We provide the following artifacts to facilitate independent verification of our results. All materials are hosted in an anonymized repository: https://anonymous.4open.science/r/FuzzCheckAI-18A2/

- **FuzzCheck.AI Codebook.** The rubric defining criteria for the three compliance levels for each FuzzCheck.AI metric.
- **LLM-Assisted Preliminary Assessment Pipeline.** Implementation of the LLM-assisted assessment workflow, including evaluator and arbitrator stages.
- **LLM-Generated Preliminary Assessments.** Preliminary assessments generated by the LLM pipeline for all 32 DNN fuzzing papers, including extracted evidence and rationales.
- **Expert-Validated and Corrected Final Assessments.** Final assessments after expert review, including documented corrections and rationales where LLMs misinterpreted evidence or extracted incorrect evidence.
- **Analysis Scripts.** Scripts used to generate all summary tables in this paper from the final validated assessments.

Upon acceptance, we will replace the anonymized repository with a stable, non-anonymous repository to ensure continued public availability.

References

[1] B. Vidgen, A. Harris, D. Nguyen, R. Tromble, S. Hale, and H. Margetts, "Challenges and frontiers in abusive content detection," in *Proceedings of the third workshop on abusive language online*. Association for Computational Linguistics, 2019.

[2] M. B. Hoy, "Alexa, siri, cortana, and more: an introduction to voice assistants," *Medical reference services quarterly*, vol. 37, no. 1, pp. 81–88, 2018.

[3] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell *et al.*, "Language models are few-shot learners," *Advances in neural information processing systems*, vol. 33, pp. 1877–1901, 2020.

[4] D. Amodei, C. Olah, J. Steinhardt, P. Christiano, J. Schulman, and D. Mané, "Concrete problems in ai safety," *arXiv preprint arXiv:1606.06565*, 2016.

[5] D. Heaven *et al.*, "Why deep-learning ais are so easy to fool," *Nature*, vol. 574, no. 7777, pp. 163–166, 2019.

[6] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus, "Intriguing properties of neural networks," *arXiv preprint arXiv:1312.6199*, 2013.

[7] I. J. Goodfellow, J. Shlens, and C. Szegedy, "Explaining and harnessing adversarial examples," *arXiv preprint arXiv:1412.6572*, 2014.

[8] N. Carlini and D. Wagner, "Audio adversarial examples: Targeted attacks on speech-to-text," in *2018 IEEE security and privacy workshops (SPW)*. IEEE, 2018, pp. 1–7.

[9] A. Wei, N. Haghtalab, and J. Steinhardt, "Jailbroken: How does llm safety training fail?" *Advances in Neural Information Processing Systems*, vol. 36, pp. 80 079–80 110, 2023.

[10] K. Pei, Y. Cao, J. Yang, and S. Jana, "DeepXplore: Automated whitebox testing of deep learning systems," in *Proceedings of the 26th Symposium on Operating Systems Principles*, 2017, pp. 1–18.

[11] A. Odena, C. Olsson, D. Andersen, and I. Goodfellow, "TensorFuzz: Debugging neural networks with coverage-guided fuzzing," in *International Conference on Machine Learning*. PMLR, 2019, pp. 4901–4911.

[12] Y. Tian, K. Pei, S. Jana, and B. Ray, "DeepTest: Automated testing of deep-neural-network-driven autonomous cars," in *Proceedings of the 40th international conference on software engineering*, 2018, pp. 303–314.

[13] Y. Yuan, Q. Pang, and S. Wang, "Unveiling hidden dnn defects with decision-based metamorphic testing," in *Proceedings of the 37th IEEE/ACM international conference on automated software engineering*, 2022, pp. 1–13.

[14] Y. Yuan, S. Wang, M. Jiang, and T. Y. Chen, "Perception matters: Detecting perception failures of vqa models using metamorphic testing," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021, pp. 16 908–16 917.

[15] L. Ma, F. Juefei-Xu, F. Zhang, J. Sun, M. Xue, B. Li, C. Chen, T. Su, L. Li, Y. Liu *et al.*, "DeepGauge: Multi-granularity testing criteria for deep learning systems," in *Proceedings of the 33rd ACM/IEEE international conference on automated software engineering*, 2018, pp. 120–131.

[16] H. Guo, C. Tao, Z. Huang, and W. Zou, "Coverage-guided testing for deep learning models: A comprehensive survey," *arXiv preprint arXiv:2507.00496*, 2025.

[17] W. Luo, D. Chai, X. Ruan, J. Wang, C. Fang, and Z. Chen, "Graph-based fuzz testing for deep learning inference engines," in *2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE)*. IEEE, 2021, pp. 288–299.

[18] J. Lin, Q. Zhang, J. Li, C. Sun, H. Zhou, C. Luo, and C. Qian, "Automatic library fuzzing through api relation evolvement," in *Proceedings of the 2025 Network and Distributed System Security Symposium (NDSS 2025)*, 2025.

[19] C. S. Xia, M. Paltenghi, J. Le Tian, M. Pradel, and L. Zhang, "Fuzz4all: Universal fuzzing with large language models," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.

[20] J. Guo, Y. Jiang, Y. Zhao, Q. Chen, and J. Sun, "DLFuzz: Differential fuzzing testing of deep learning systems," in *Proceedings of the 2018 26th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2018, pp. 739–743.

[21] X. Xie, L. Ma, F. Juefei-Xu, M. Xue, H. Chen, Y. Liu, J. Zhao, B. Li, J. Yin, and S. See, "DeepHunter: a coverage-guided fuzz testing framework for deep neural networks," in *Proceedings of the 28th ACM SIGSOFT international symposium on software testing and analysis*, 2019, pp. 146–157.

[22] P. Chao, A. Robey, E. Dobriban, H. Hassani, G. J. Pappas, and E. Wong, "Jailbreaking black box large language models in twenty queries," in *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*. IEEE, 2025, pp. 23–42.

[23] J. Yu, X. Lin, Z. Yu, and X. Xing, "{LLM-Fuzzer}: Scaling assessment of large language model jailbreaks," in *33rd USENIX Security Symposium (USENIX Security 24)*, 2024, pp. 4657–4674.

[24] S. Zhou, T. Li, K. Wang, Y. Huang, L. Shi, Y. Liu, and H. Wang, "Understanding the effectiveness of coverage criteria for large language models: A special angle from jailbreak attacks," in *2025 IEEE/ACM 47th International Conference on Software Engineering (ICSE)*. IEEE Computer Society, 2025, pp. 745–745.

[25] M. H. Asyrofi, Z. Yang, and D. Lo, "CrossASR++: A modular differential testing framework for automatic speech recognition," in *Proceedings of the 29th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2021, pp. 1575–1579.

[26] X. Liu, N. Xu, M. Chen, and C. Xiao, "Autodan: Generating stealthy jailbreak prompts on aligned large language models," in *The Twelfth International Conference on Learning Representations*.

[27] J. M. Zhang, M. Harman, L. Ma, and Y. Liu, "Machine learning testing: Survey, landscapes and horizons," *IEEE Transactions on Software Engineering*, vol. 48, no. 1, pp. 1–36, 2020.

[28] F. Wang, K. Ben, and X. Zhang, "Sr-mt: a metamorphic method to test the robustness of speech recognition software," in *Proceedings of the 7th International Workshop on Metamorphic Testing*, 2022, pp. 15–22.

[29] Y. Tian, S. Ma, M. Wen, Y. Liu, S.-C. Cheung, and X. Zhang, "To what extent do dnn-based image classification models make unreliable inferences?" *Empirical Software Engineering*, vol. 26, no. 5, p. 84, 2021.

[30] N. Carlini and D. Wagner, "Towards evaluating the robustness of neural networks," in *2017 IEEE Symposium on Security and Privacy (SP)*, 2017, pp. 39–57.

[31] N. Carlini, P. Mishra, T. Vaidya, Y. Zhang, M. Sherr, C. Shields, D. Wagner, and W. Zhou, "Hidden voice commands," in *25th USENIX security symposium (USENIX security 16)*, 2016, pp. 513–530.

[32] S.-M. Moosavi-Dezfooli, A. Fawzi, and P. Frossard, "Deepfool: a simple and accurate method to fool deep neural networks," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 2574–2582.

[33] Z. Zhang, E. Yang, and S. Fang, "Commandergabble: A universal attack against asr systems leveraging fast speech," in *Proceedings of the 37th Annual Computer Security Applications Conference*, 2021, pp. 720–731.

[34] Y. Qin, N. Carlini, G. Cottrell, I. Goodfellow, and C. Raffel, "Imperceptible, robust, and targeted adversarial examples for automatic speech recognition," in *International conference on machine learning*. PMLR, 2019, pp. 5231–5240.

[35] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," *arXiv preprint arXiv:2307.15043*, 2023.

[36] S. Dola, M. B. Dwyer, and M. L. Soffa, "Input distribution coverage: Measuring feature interaction adequacy in neural network testing," *ACM Transactions on Software Engineering and Methodology*, vol. 32, no. 3, pp. 1–48, 2023.

[37] M. Usman, Y. Sun, D. Gopinath, R. Dange, L. Manolache, and C. S. Păsăreanu, "An overview of structural coverage metrics for testing neural networks," *International Journal on Software Tools for Technology Transfer*, vol. 25, no. 3, pp. 393–405, 2023.

[38] Z. Ji, P. Ma, Y. Yuan, and S. Wang, "Cc: Causality-aware coverage criterion for deep neural networks," in *2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE)*. IEEE, 2023, pp. 1788–1800.

[39] Y. Yuan, Q. Pang, and S. Wang, "Revisiting neuron coverage for dnn testing: A layer-wise and distribution-aware criterion," in *2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE)*. IEEE, 2023, pp. 1200–1212.

[40] M. H. Asyrofi, F. Thung, D. Lo, and L. Jiang, "CrossASR: Efficient differential testing of automatic speech recognition via text-to-speech," in *2020 IEEE International Conference on Software Maintenance and Evolution (ICSME)*. IEEE, 2020, pp. 640–650.

[41] H. You, Z. Wang, J. Chen, S. Liu, and S. Li, "Regression fuzzing for deep learning systems," in *2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE)*. IEEE, 2023, pp. 82–94.

[42] X. Gong, M. Li, Y. Zhang, F. Ran, C. Chen, Y. Chen, Q. Wang, and K. Lam, "PAPILLON: Efficient and stealthy fuzz testing-powered jailbreaks for llms," in *Proceedings of the 34th USENIX Security Symposium (USENIX Security '25)*. Seattle, WA, USA: USENIX Association, Aug. 2025. [Online]. Available: https://www.usenix.org/conference/usenixsecurity25/technical-sessions

[43] L. Wang, X. Xie, X. Du, M. Tian, Q. Guo, Z. Yang, and C. Shen, "DistXplore: Distribution-guided testing for evaluating and enhancing deep learning systems," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2023, pp. 68–80.

[44] X. Chen, X. Gao, J. Zhao, K. Ye, and C.-Z. Xu, "Advdiffuser: Natural adversarial example synthesis with diffusion models," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023, pp. 4562–4572.

[45] V. Riccio, G. Jahangirova, A. Stocco, N. Humbatova, M. Weiss, and P. Tonella, "Testing machine learning based systems: a systematic mapping," *Empirical Software Engineering*, vol. 25, no. 6, pp. 5193–5254, 2020.

[46] H. B. Braiek and F. Khomh, "On testing machine learning programs," *Journal of Systems and Software*, vol. 164, p. 110542, 2020.

[47] X. Huang, D. Kroening, W. Ruan, J. Sharp, Y. Sun, E. Thamo, M. Wu, and X. Yi, "A survey of safety and trustworthiness of deep neural networks: Verification, testing, adversarial attack and defence, and interpretability," *Computer Science Review*, vol. 37, p. 100270, 2020.

[48] J. Wang, H. Qiu, Y. Rong, H. Ye, Q. Li, Z. Li, and C. Zhang, "BET: black-box efficient testing for convolutional neural networks," in *Proceedings of the 31st ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2022, pp. 164–175.

[49] A. Ilyas, S. Santurkar, D. Tsipras, L. Engstrom, B. Tran, and A. Madry, "Adversarial examples are not bugs, they are features," *Advances in neural information processing systems*, vol. 32, 2019.

[50] Y. Chun Tie, M. Birks, and K. Francis, "Grounded theory research: A design framework for novice researchers," *SAGE open medicine*, vol. 7, p. 2050312118822927, 2019.

[51] X. Zhang, X. Xie, L. Ma, X. Du, Q. Hu, Y. Liu, J. Zhao, and M. Sun, "Towards characterizing adversarial defects of deep learning software from the lens of uncertainty," in *Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering*, 2020, pp. 739–751.

[52] C. Xie, J. Wang, Z. Zhang, Z. Ren, and A. Yuille, "Mitigating adversarial effects through randomization," in *International Conference on Learning Representations*, 2018. [Online]. Available: https://openreview.net/forum?id=Sk9yuql0Z

[53] N. Papernot, P. McDaniel, X. Wu, S. Jha, and A. Swami, "Distillation as a defense to adversarial perturbations against deep neural networks," in *2016 IEEE symposium on security and privacy (SP)*. IEEE, 2016, pp. 582–597.

[54] W. Xu, D. Evans, and Y. Qi, "Feature squeezing: Detecting adversarial examples in deep neural networks," *arXiv preprint arXiv:1704.01155*, 2017.

[55] T. Bai, J. Luo, J. Zhao, B. Wen, and Q. Wang, "Recent advances in adversarial training for adversarial robustness," *arXiv preprint arXiv:2102.01356*, 2021.

[56] B. Wu, S. Wei, M. Zhu, M. Zheng, Z. Zhu, M. Zhang, H. Chen, D. Yuan, L. Liu, and Q. Liu, "Defenses in adversarial machine learning: A survey," *arXiv preprint arXiv:2312.08890*, 2023.

[57] T. Shen, R. Jin, Y. Huang, C. Liu, W. Dong, Z. Guo, X. Wu, Y. Liu, and D. Xiong, "Large language model alignment: A survey," *arXiv preprint arXiv:2309.15025*, 2023.

[58] N. Das, M. Shanbhogue, S.-T. Chen, F. Hohman, S. Li, L. Chen, M. E. Kounavis, and D. H. Chau, "Shield: Fast, practical defense and vaccination for deep learning using jpeg compression," in *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2018, pp. 196–204.

[59] Z. Yu, Y. Chang, N. Zhang, and C. Xiao, "{SMACK}: Semantically meaningful adversarial audio attack," in *32nd USENIX security symposium (USENIX security 23)*, 2023, pp. 3799–3816.

[60] K. Eykholt, I. Evtimov, E. Fernandes, B. Li, A. Rahmati, C. Xiao, A. Prakash, T. Kohno, and D. Song, "Robust physical-world attacks on deep learning visual classification," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 1625–1634.

[61] X. Du, X. Xie, Y. Li, L. Ma, J. Zhao, and Y. Liu, "DeepCruiser: Automated guided testing for stateful deep learning systems," *arXiv preprint arXiv:1812.05339*, 2018.

[62] S. Lee, S. Cha, D. Lee, and H. Oh, "Effective white-box testing of deep neural networks with adaptive neuron-selection strategy," in *Proceedings of the 29th ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2020, pp. 165–176.

[63] A. Torralba and A. A. Efros, "Unbiased look at dataset bias," in *CVPR 2011*. IEEE, 2011, pp. 1521–1528.

[64] N. Papernot, P. McDaniel, and I. Goodfellow, "Transferability in machine learning: from phenomena to black-box attacks using adversarial samples," *arXiv preprint arXiv:1605.07277*, 2016.

[65] Y. Chen, X. Yuan, J. Zhang, Y. Zhao, S. Zhang, K. Chen, and X. Wang, "{Devil's} whisper: A general approach for physical adversarial attacks against commercial black-box speech recognition devices," in *29th USENIX Security Symposium (USENIX Security 20)*, 2020, pp. 2667–2684.

[66] W. Liang, Y. Zhang, H. Cao, B. Wang, D. Y. Ding, X. Yang, K. Vodrahalli, S. He, D. S. Smith, Y. Yin *et al.*, "Can large language models provide useful feedback on research papers? a large-scale empirical analysis," *NEJM AI*, vol. 1, no. 8, p. AIoa2400196, 2024.

[67] N. Thakkar, M. Yuksekgonul, J. Silberg, J. Zou, C. Vondrick, R. Yu, V. Peng, F. Sha, and A. Garg, "Leveraging llm

feedback to enhance review quality," 2025, iCLR Blog, April 15 2025. [Online]. Available: https://blog.iclr.cc/2025/04/15/leveraging-llm-feedback-to-enhance-review-quality/

[68] J. Lála, O. O'Donoghue, A. Shtedritski, S. Cox, S. G. Rodriques, and A. D. White, "Paperqa: Retrieval-augmented generative agent for scientific research," *arXiv preprint arXiv:2312.07559*, 2023.

[69] B. Bohnet, V. Q. Tran, P. Verga, R. Aharoni, D. Andor, L. B. Soares, M. Ciaramita, J. Eisenstein, K. Ganchev, J. Herzig *et al.*, "Attributed question answering: Evaluation and modeling for attributed large language models," *arXiv preprint arXiv:2212.08037*, 2022.

[70] G. Comanici, E. Bieber, M. Schaekermann, I. Pasupat, N. Sachdeva, I. Dhillon, M. Blistein, O. Ram, D. Zhang, E. Rosen *et al.*, "Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities," *arXiv preprint arXiv:2507.06261*, 2025.

[71] A. Singh, A. Fry, A. Perelman, A. Tart, A. Ganesh, A. El-Kishky, A. McLaughlin, A. Low, A. Ostrow, A. Ananthram *et al.*, "OpenAI GPT-5 System Card," *arXiv preprint arXiv:2601.03267*, 2025.

[72] OpenAI, "OpenAI o3 and o4-mini System Card," OpenAI, System Card, Apr. 2025. [Online]. Available: https://cdn.openai.com/pdf/2221c875-02dc-4789-800b-e7758f3722c1/o3-and-o4-mini-system-card.pdf

[73] Computing Research and Education Association of Australasia (CORE), "Core conference rankings portal," https://portal.core.edu.au/conf-ranks/, 2025, accessed: 2025-05-26.

[74] T. Y. Chen, S. C. Cheung, and S. M. Yiu, "Metamorphic testing: a new approach for generating next test cases," *arXiv preprint arXiv:2002.12543*, 2020.

[75] X. Du, X. Xie, Y. Li, L. Ma, Y. Liu, and J. Zhao, "DeepStellar: Model-based quantitative analysis of stateful deep learning systems," in *Proceedings of the 2019 27th ACM joint meeting on European software engineering conference and symposium on the foundations of software engineering*, 2019, pp. 477–487.

[76] T. Woodlief, S. Elbaum, and K. Sullivan, "Semantic image fuzzing of ai perception systems," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 1958–1969.

[77] X. Xie, T. Li, J. Wang, L. Ma, Q. Guo, F. Juefei-Xu, and Y. Liu, "Npc: Neuron path coverage via characterizing decision logic of deep neural networks," *ACM Transactions on Software Engineering and Methodology (TOSEM)*, vol. 31, no. 3, pp. 1–27, 2022.

[78] J. Kim, R. Feldt, and S. Yoo, "Guiding deep learning system testing using surprise adequacy," in *2019 IEEE/ACM 41st International Conference on Software Engineering (ICSE)*. IEEE, 2019, pp. 1039–1049.

[79] J. He, Z. Yang, J. Shi, C. Yang, K. Kim, B. Xu, X. Zhou, and D. Lo, "Curiosity-driven testing for sequential decision-making process," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–14.

[80] D. H. X. Yuen, A. Y. C. Pang, Z. Yang, C. Y. Chong, M. K. Lim, and D. Lo, "Asdf: A differential testing framework for automatic speech recognition systems," in *2023 IEEE Conference on Software Testing, Verification and Validation (ICST)*. IEEE, 2023, pp. 461–463.

[81] Q. Pang, Y. Yuan, and S. Wang, "Mdpfuzz: testing models solving markov decision processes," in *Proceedings of the 31st ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2022, pp. 378–390.

[82] Z. Liu, Y. Feng, Y. Yin, J. Sun, Z. Chen, and B. Xu, "QATest: A uniform fuzzing framework for question answering systems," in *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*, 2022, pp. 1–12.

[83] M. H. Asyrofi, Z. Yang, J. Shi, C. W. Quan, and D. Lo, "Can differential testing improve automatic speech recognition systems?" in *2021 IEEE International Conference on Software Maintenance and Evolution (ICSME)*. IEEE, 2021, pp. 674–678.

[84] X. Gao, R. K. Saha, M. R. Prasad, and A. Roychoudhury, "Fuzz testing based data augmentation to improve robustness of deep neural networks," ser. ICSE '20. New York, NY, USA: Association for Computing Machinery, 2020, p. 1147–1158. [Online]. Available: https://doi.org/10.1145/3377811.3380415

[85] Y. Zhang, L. Xu, A. Mendoza, G. Yang, P. Chinprutthiwong, and G. Gu, "Life after speech recognition: Fuzzing semantic misinterpretation for voice assistant applications," in *Proc. of the Network and Distributed System Security Symposium (NDSS'19)*, 2019.

[86] W. Huang, Y. Sun, X. Zhao, J. Sharp, W. Ruan, J. Meng, and X. Huang, "Coverage-guided testing for recurrent neural networks," *IEEE Transactions on Reliability*, vol. 71, no. 3, pp. 1191–1206, 2021.

[87] Z. Li, M. Pan, T. Zhang, and X. Li, "Testing DNN-based autonomous driving systems under critical environmental conditions," in *International conference on machine learning*. PMLR, 2021, pp. 6471–6482.

[88] D. Ma, J. Guo, Y. Jiang, and X. Jiao, "HDTest: Differential fuzz testing of brain-inspired hyperdimensional computing," in *2021 58th ACM/IEEE Design Automation Conference (DAC)*. IEEE, 2021, pp. 391–396.

[89] H. B. Braiek and F. Khomh, "DeepEvolution: A search-based testing approach for deep neural networks," in *2019 IEEE International Conference on Software Maintenance and Evolution (ICSME)*. IEEE, 2019, pp. 454–458.

[90] R. Zhang, P. Isola, A. A. Efros, E. Shechtman, and O. Wang, "The unreasonable effectiveness of deep features as a perceptual metric," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 586–595.

[91] Z. Wang, A. C. Bovik, H. R. Sheikh, and E. P. Simoncelli, "Image quality assessment: from error visibility to structural similarity," *IEEE transactions on image processing*, vol. 13, no. 4, pp. 600–612, 2004.

[92] A. W. Rix, J. G. Beerends, M. P. Hollier, and A. P. Hekstra, "Perceptual evaluation of speech quality (pesq)-a new method for speech quality assessment of telephone networks and codecs," in *2001 IEEE international conference on acoustics, speech, and signal processing. Proceedings (Cat. No. 01CH37221)*, vol. 2. IEEE, 2001, pp. 749–752.

[93] C. H. Taal, R. C. Hendriks, R. Heusdens, and J. Jensen, "An algorithm for intelligibility prediction of time–frequency weighted noisy speech," *IEEE Transactions on audio, speech, and language processing*, vol. 19, no. 7, pp. 2125–2136, 2011.

[94] S. F. Chen and J. Goodman, "An empirical study of smoothing techniques for language modeling," *Computer Speech & Language*, vol. 13, no. 4, pp. 359–394, 1999.

[95] X. Yuan, P. He, Q. Zhu, and X. Li, "Adversarial examples: Attacks and defenses for deep learning," *IEEE transactions on neural networks and learning systems*, vol. 30, no. 9, pp. 2805–2824, 2019.

APPENDIX

A. EMPIRICAL FINDING ON FAILURE REPRODUCIBILITY

We empirically examine failure reproducibility in semantic-preserving metamorphic mutation-based fuzzers by evaluating whether a representative fuzzer, NLC [39], produces reproducible failures. We run NLC on a ResNet-50 model pretrained on CIFAR-10. In a 10-minute fuzzing run, NLC generated 3,694 fault-inducing images. When the saved fault-inducing inputs were re-evaluated, 9.88% reverted to their original labels, and 17.00% were mapped to different incorrect outputs than those originally recorded (Table VIII). These inconsistencies indicate that a substantial fraction of reported failures are not reproducible, highlighting the impact of serialization effects and numerical instability.

TABLE VIII
EMPIRICAL EVALUATION OF FAILURE REPRODUCIBILITY METRIC ON NLC [39] FUZZER.

Outcome	**Count**	**Percentage (%)**
Reproducible failure	2,701	73.12
Reverted to original label	365	9.88
Changed to different incorrect label	628	17.00
Total adversarial inputs	**3,694**	**100.00**

B. LLM VS. EXPERT ASSESSMENT ANALYSIS

Tables IX and X summarize agreement between LLM-based preliminary assessments and expert-corrected final assessments across papers and metrics, respectively. Overall

TABLE IX
PER-PAPER AGREEMENT BETWEEN LLM-GENERATED LABELS AND EXPERT-CORRECTED LABELS ACROSS ALL METRICS. GRAY CELLS INDICATE A DISAGREEMENT. (**L**=LLM-BASED PRELIMINARY ASSESSMENT, **H**=HUMAN EXPERT FINAL ASSESSMENT)

Paper	FS		TA		IP		FR		FD		AT	
	L	H	L	H	L	H	L	H	L	H	L	H
PAIR [22]	●	●	◑	◑	●	●	●	●	◑	○	◑	◑
Zhou et al. [24]	●	●	◑	◑	○	●	●	●	◑	◑	○	○
PAPILLON [42]	●	●	◑	◑	◑	●	●	●	◑	◑	◑	◑
AutoDAN [26]	●	●	●	●	●	●	●	●	◑	○	◑	◑
LLM-Fuzzer [23]	●	●	◑	◑	●	●	●	●	○	○	●	●
CureFuzz [79]	◑	◑	◑	◑	◑	●	○	●	◑	◑	○	○
NLC [39]	○	○	○	○	◑	◑	◑	◑	◑	◑	○	○
DRFuzz [41]	○	○	○	○	●	●	◑	◑	●	●	○	○
DistXplore [43]	○	○	●	●	◑	◑	◑	◑	◑	◑	○	○
ASDF [80]	○	○	○	○	◑	◑	●	●	◑	◑	○	○
MDPFuzz [81]	◑	◑	◑	◑	●	●	◑	●	◑	◑	○	○
BET [48]	○	○	●	●	●	●	◑	●	○	○	●	○
QATest [82]	○	○	○	○	◑	◑	●	●	◑	◑	○	○
semSensFuzz [76]	◑	◑	○	○	◑	●	◑	◑	◑	◑	◑	○
TESTRNN [86]	○	○	○	○	◑	◑	◑	◑	◑	◑	○	○
TACTIC [87]	○	○	○	○	●	●	◑	◑	◑	◑	○	○
HDTest [88]	○	○	○	○	●	◑	○	○	◑	◑	○	○
CrossASR++ [25]	○	○	○	○	●	●	●	●	○	○	○	○
Asyrofi et al. [83]	○	○	○	○	●	●	●	●	○	○	○	○
Sensei [84]	○	○	○	○	●	●	◑	◑	○	○	○	○
KuK [51]	●	●	○	○	◑	◑	○	○	◑	◑	○	◑
ADAPT [62]	○	○	○	○	●	◑	○	○	◑	◑	○	○
CrossASR [40]	○	○	○	○	●	●	●	●	○	○	○	○
DeepHunter [21]	○	○	○	○	●	●	◑	◑	◑	◑	●	○
TensorFuzz [11]	○	○	◑	◑	●	●	○	◑	◑	◑	◑	○
DeepStellar [75]	○	○	○	○	◑	◑	◑	◑	◑	◑	○	○
LipFuzzer [85]	◑	◑	◑	○	●	●	●	●	●	◑	○	○
DeepEvolution [89]	○	○	○	○	●	●	◑	◑	◑	○	○	○
DeepTest [12]	◑	◑	◑	○	◑	◑	◑	◑	◑	◑	○	○
DLFuzz [20]	○	○	○	○	●	●	○	○	◑	○	○	○
DeepCruiser [61]	○	○	○	○	◑	◑	◑	◑	◑	◑	○	○
DeepXplore [10]	◑	○	○	○	◑	◑	◑	●	●	◑	○	○

●: High ◑: Medium ○: Low

agreement was high (87%), with remaining discrepancies mainly arising from evidence misinterpretation or selection from irrelevant sections.

In several cases, the LLM-assisted pipeline relied on contextual cues or implicit assumptions rather than the formal codebook criteria. For example, in *DeepTest*, it assigned a *medium* rating for targeted attack discovery because the target models belonged to a safety-critical domain (autonomous driving), even though the fuzzer performs untargeted exploration. In *AutoDAN*, it misinterpreted hypotheses about transferability as diagnostic insight into failure root causes. Similarly, it penalized *CureFuzz* for ignoring I/O serialization effects, overlooking that its validity checks keep feature vectors within legal bounds and do not require clipping or rounding.

In other cases, the pipeline extracted evidence from irrelevant sections, leading to incorrect interpretations despite internally consistent reasoning. For instance, in *Zhou et al.*, the LLM-assisted pipeline assigned a low rating on the input plausibility metric by relying on the jailbreak detection section, where prompts contain meaningless adversarial suffixes, instead of the fuzzing method description. In contrast, human experts corrected this by examining the fuzzing design section

TABLE X
LLM VS HUMAN AGREEMENT ON EVALUATION METRICS. EACH CELL REPORTS THE AGREEMENT AS COUNT / TOTAL (PERCENTAGE%) ACROSS 32 DNN FUZZING STUDIES.

Metric	Agreement
Failure Severity	31/32 (96.9%)
Targeted Attack Discovery	30/32 (93.8%)
Input Plausibility	26/32 (81.2%)
Failure Reproducibility	27/32 (84.4%)
Failure Diagnostics	26/32 (81.2%)
Attack Transferability	27/32 (84.4%)
Overall	**167/192 (87.0%)**

and assigning a high rating, as the fuzzer synthesizes natural, semantically coherent prompts using an LLM.

Overall, these findings demonstrate that while LLM assistance substantially accelerates metric-relevant evidence localization, expert oversight remains essential for ensuring contextual accuracy and metric-aligned interpretation.

Listing 1. LLM Prompt Templates

```
# Evaluator Prompt
You are an expert in DNN fuzzing research.
You are given:
1. Metric codebook (definition and evaluation guidance
   for each compliance level).
2. The full text of an DNN fuzzing research paper.
Your task is to evaluate the method proposed in the paper
against the specified metric.
Instructions:
- Base your reasoning strictly on the paper content.
- Focus on technical and methodological sections.
- Assign one of the allowed values from the codebook.
- Justify your choice with explanation.
- Support it with direct evidence from paper.
Output Format:
- Return a JSON object using this schema:
{
  "value": "<value>", "why": "<Explanation>",
  "evidence": "<page, section, supporting quote>"
}

# Arbitrator Prompt
You are expert resolving disagreement between assessments
You are given:
1. Metric codebook (definition and evaluation guidance
   for each compliance level).
2. The full text of a DNN fuzzing research paper.
3. Two assessments with conflicting verdicts.
Instructions:
- Review both assessments using the codebook and paper.
- Assign a value and provide rationale.
- Justify your conclusion with explanation.
- Support it with direct evidence from the paper.
Output Format:
- Return a JSON object using this schema:
{
  "value": "<value>", "why": "<Explanation>",
  "evidence": "<page, section, supporting quote>"
}
```

Listing 2. LLM Assessment Outputs

```
# Evaluator A (ChatGPT:gpt-5-mini)
{
 "value": "Low",
 "why": "The paper studies coverage criteria and
   jailbreak detection for LLMs using [truncated]",
 "evidence": "Page 731, Section II-A (Model Inference
   Process): \"The text is tokenized into discrete
   elements, each mapped to a dense [truncated]"
}

# Evaluator B (Gemini:gemini-2.5-pro)
```

```
{
 "value": "High",
 "why": "The paper's methodology for generating and
   selecting test cases for Large Language Models (LLMs)
   operates entirely within the text domain [truncated]",
 "evidence": "Page 4, Section III-A, 'Findings': 'Attack
   queries are generated by appending adversarial
   suffixes to rejected queries using [truncated]"
}
```


 # Arbitrator Output (ChatGPT:o4-mini)


```
{
  "value": "High",
  "why": "All of the paper's test generation and
    evaluation is performed in the textual domain: inputs
    are discrete text prompts that are [truncated]",
  "evidence": "Page 731, Section III-A: "Attack queries
    are generated by appending adversarial suffixes to
    rejected queries using GCG [7]. [truncated]"
}
```

M.	L.	Paper	Evidence
Failure Severity	●	PAIR [22]	Abstract and Sec. IV describe semantic jailbreaks against safety-aligned LLMs; Table III reports jailbreak success on GPT-3.5, GPT-4, Claude, and Gemini; Sec. IV-C evaluates PAIR against SmoothLLM and perplexity-filter defenses, showing failures that bypass safeguards on defended models.
	◑	CureFuzz [79]	Sec. 3.1 defines the goal as uncovering crash-triggering scenarios in sequential decision-making systems; Sec. 4.2 instantiates these failures as vehicle collisions, aircraft collisions, and robot falls. The paper targets catastrophic unsafe behavior, but not safeguard bypass on defended models.
	○	DeepHunter [21]	Sec. 3.2 defines erroneous behavior as a mutant that changes the model prediction under metamorphic mutation, and Sec. 5.4 highlights detection of quantization-related errors. The evaluation focuses on robustness-related mispredictions rather than unsafe behavior or safeguard bypass.
Targeted Attack Discovery	●	AutoDAN [26]	Sec. 3.1 specifies a target response prefix such as "Sure, here is how to [Qi]..."; Sec. 3.3 optimizes the conditional probability of that target sequence; Alg. 2 and Sec. 3.5 steer the search away from refusal outputs. The search is explicitly guided toward a predefined attacker-chosen output.
	◑	PAIR [22]	Sec. II defines each jailbreak by an objective O describing the harmful content to elicit, and Sec. IV evaluates prompts against behaviors from JailbreakBench. PAIR steers toward a class of unsafe outcomes tied to the behavior objective, rather than a single fixed output string.
	○	DeepXplore [10]	Sec. 3 and Sec. 4.2 maximize differential behaviors and neuron coverage so that one DNN predicts differently from others. The optimization seeks any disagreement-inducing input, not a predefined attacker-chosen output or unsafe outcome class.
Input Plausibility	●	AutoDAN [26]	Sec. 3.2 uses LLM-based revision to preserve the logical flow and meaning of handcrafted jailbreak prompts; Sec. 3.4 reuses LLM-based diversification as the mutation operator; Table 1 and Sec. 4.2 report lower perplexity and semantically meaningful prompts. The method explicitly preserves semantic plausibility during prompt generation.
	◑	NLC [39]	Sec. VI-B applies realistic image transformations and accepts a mutation only if `is_valid()` holds, using bounds on changed pixels and pixel magnitude; the same section reports naturalness via IS/FID. These are per-mutation plausibility checks, but the paper does not enforce plausibility relative to the original seed across the full fuzzing process.
	○	None	No evaluated paper received a **low** (○) label on this metric, indicating that all assessed DNN fuzzers include at least some mechanism intended to preserve input plausibility.
Failure Reproducibility	●	CrossASR++ [25]	Sec. 2.1 generates test cases directly as TTS audio files (`generateAudio(texts)`), and Sec. 2.4.2 states that the repository provides all generated audios for reuse. Because the fault-inducing inputs are produced and reused in serialized audio form, the discovered failures are reproducible under standard I/O.
	◑	NLC [39]	Sec. VI-B uses metamorphic image transformations such as contrast, brightness, translation, rotation, blurring, and stylizing, and bounds pixel changes with `is_valid()`. However, the paper does not discuss saving/reloading inputs or handling serialization effects such as rounding or quantization.
	○	DLFuzz [20]	Sec. 3.2 mutates inputs by adding gradient-derived perturbations in memory and keeps the l_2 distance small; Sec. 4 reports adversarial inputs with tiny perturbations. The paper never discusses clipping, rounding, quantization, or re-evaluating saved inputs, so reproducibility under standard I/O is not addressed.
Failure Diagnostics	●	DRFuzz [41]	Sec. IV-B1 analyzes which classes contain the most regression faults and links them to overfitting; Sec. V-B uses Grad-CAM to show that different faulty behaviors are associated with different salient features. The paper goes beyond reporting failures to explain why regression faults occur.
	◑	DeepXplore [10]	Sec. 4.1 defines neuron coverage and Sec. 7.1 analyzes how neuron activations differ across classes; Tables 3 and 4 identify concrete feature changes associated with misclassification; Sec. 7.3 connects discovered differences to poisoned training samples. The paper provides diagnostic insight through internal signals and failure-pattern analysis, but not a full causal account of all failure modes.
	○	PAIR [22]	Secs. IV-A to IV-E report jailbreak success rates across models, categories, defenses, and attacker variants, but the paper does not analyze model internals, failure patterns, or underlying vulnerabilities beyond high-level speculation. It reports failures effectively without diagnosing why they occur.
Attack Transferability	●	LLM-Fuzzer [23]	Experiment III explicitly optimizes for templates that succeed across multiple source LLMs by assigning zero reward to templates whose successful jailbreaks come from only one or two models; Sec. 4.3 then evaluates the resulting templates on additional downstream LLMs and reports strong transfer in Fig. 4. Transferability is both measured and built into the search objective.
	◑	PAIR [22]	Sec. IV-B reuses successful jailbreak prompts found on GPT-4 and Vicuna to attack other downstream LLMs, and Table VI reports the transferred jailbreak rates. The paper measures cross-model transfer, but the method itself is not explicitly designed around a transfer-focused objective.
	○	DeepXplore [10]	Sec. 3 and Algorithm 1 define DeepXplore over a fixed set of multiple DNNs used as cross-referencing oracles during search, and Sec. 8 notes that differential testing requires at least two DNNs with the same functionality. The paper evaluates disagreement among the models used in the search, but does not reuse discovered inputs to test transfer to unseen target models.

TABLE XI

WORKED EXAMPLES SHOWING HOW THE FINAL FUZZCHECK.AI CODEBOOK IS APPLIED TO REPRESENTATIVE PAPERS. EACH ENTRY REPORTS THE FINAL MANUAL LABEL TOGETHER WITH THE PAPER EVIDENCE USED TO JUSTIFY IT.