RC-QASyn: Auditable Evidence, Coverage-Aware Construction and Bounded Repair for Synthetic Tabular Data

Author 1 (to be supplied)
Department
Sardar Vallabhbhai National Institute of Technology
Surat, India
email

Author 2 (to be supplied)
Department
Sardar Vallabhbhai National Institute of Technology
Surat, India
email

***Abstract*—Among 601 historical synthetic tabular candidate occurrences from three imbalanced classification datasets, 75 (12.5%) violate source-declared structural requirements; page-blocks0 accounts for 64 violations among 200 candidates (32%). RC-QASyn makes these defects, statistical support and dataset contribution separately auditable through provenance, schema checks, local and global TRAIN evidence, descriptive admission, fixed-budget construction and bounded integer repair. All 54 eligible repairs become structurally compliant; 21 rejected records remain ineligible. At matched budgets, quality-coverage selection raises distinct-feature TRAIN coverage over source order from 0.622 to 0.948 on Abalone19 and from 0.416 to 0.506 on Ecoli4, with zero exact duplicates. Improved geometry does not ensure improved classification: expanding the repaired page-blocks0 pool lowers logistic pure-synthetic F1 from 0.446 to 0.342 (paired conditional 95% difference interval: $[-0.135, -0.074]$). A separate train-only offline study uses five fresh stratified splits per dataset. Curated augmentation yields mean F1 0.758 ± 0.166 on Ecoli4 versus 0.848 ± 0.119 for real-only training; gains on page-blocks0 are small and random curation remains competitive. Saved predictions support 2,000-resample paired intervals. These results establish reproducible structural and geometric effects with mixed utility outcomes, without independently establishing complete semantic validity.**

***Index Terms*—synthetic tabular data; curation; coverage; bounded repair; imbalanced learning**

I. Introduction

A generated record can be readable and numerically plausible while omitting its class, violating an integer declaration or duplicating another record. These failures occur in the studied population: 75 of 601 candidates violate authoritative structure, including 64 of 200 page-blocks0 records. These are rates for this historical generation campaign, not estimates for LLM outputs generally. They motivate checking what a record contains before interpreting distributional resemblance or downstream usefulness.

Three questions remain distinct. Does a candidate comply with justified source declarations? How well does it resemble TRAIN observations locally and globally? What does it contribute to a selected dataset and its classifier? A distant observation may be legitimate, a compliant record may be redundant, and a diverse subset may train a worse classifier. RC-QASyn addresses these distinctions with an auditable curation system.

We ask: to what extent do structural filtering, heterogeneous evidence, coverage-aware selection and bounded repair improve measurable synthetic-data characteristics and downstream classification utility compared with simple alternatives? The revision combines a controlled historical study with a separate offline replication. Annotation experiments and validity calibrators are outside the active scope.

The contributions are:

1) Auditable separation of source-schema compliance, local/global statistical support and dataset contribution, linked to immutable candidate identities.
2) Evidence-aware fixed-budget construction evaluated against random, source-order, farthest-first and coverage-greedy controls, with coverage and redundancy measurements.
3) Source-preserving bounded integer repair, controlled reevaluation and matched-budget measurement of structural, geometric and utility changes.
4) Empirical analysis of agreement and disagreement between geometry and classification, strengthened by paired prediction uncertainty and split-specific offline generation.

These are integration and empirical contributions. Distances, covariance regularization, greedy selection, oversampling and bootstrap methods are established components; no new optimality guarantee is claimed.

II. Related work

A. Tabular generation

CTGAN, TabDDPM and GReaT model tabular generation through conditional adversarial, diffusion and language-model approaches [1], [2], [3]. EPIC adapts LLM prompting specifically to imbalanced-class tabular synthesis [4]. These methods change how candidates are produced. RC-QASyn instead curates an existing candidate stream: the historical generator is

not retrained here, and the offline experiments do not reproduce its LLM behavior.

B. Curating generated tabular data

The closest prior work also filters or ranks generated records after generation. CLLM curates LLM-generated rows in low-data regimes using a classifier's learning dynamics, keeping samples with high confidence and low aleatoric uncertainty [5]. ReFine filters LLM output to suppress redundancy that concentrates in local regions while retaining rare records [6]. Team-then-Trim follows LLM generation with a three-stage plug-in quality-control pipeline [7]. RUBRIC ranks minority candidates from any oversampler by a learned density-ratio realism score combined with a boundary-utility score, then keeps a limited budget [8]. RC-QASyn differs in three respects. Its support evidence is model-free (TRAIN-scaled nearest-neighbour distance and shrinkage Mahalanobis distance) rather than learned. Its admission keeps reject, abstain and review outcomes explicit instead of a single keep/drop decision. It adds source-declared structural checks and bounded repair, which these methods do not address. We do not claim that this design outperforms learned curation; Section VII records the absence of a direct comparison.

C. Evaluation, coverage and subset selection

Synthetic-data evaluation can distinguish fidelity, diversity and generalization at sample level [9]. Density and coverage metrics define support through k-nearest-neighbour balls around real observations [10]; our TRAIN coverage within a fixed radius is closely related, and our duplication rates are narrower diagnostics without probabilistic or privacy interpretation. Greedy coverage and diversity-based subset selection have substantial prior literature [11], [12]. Adaptive maximum-coverage sampling has recently been applied to synthetic training data, where a well-chosen subset can outperform the full synthetic set [13]. We reuse these ideas with traceable admission, class quotas and duplicate suppression. Classical unconstrained greedy guarantees do not automatically extend to the combined lexicographic selector. Quality filtering can also remove modes and reduce diversity in synthetic tabular data [14], which motivates keeping coverage as an explicit objective rather than filtering on fidelity alone.

D. Validation, constraints and repair

Schema-based data validation is established practice in machine-learning pipelines [15]. Constraint-aware models enforce explicit constraints during or immediately after generation [16], and recent work discovers inter-column constraints and repairs the records of unchanged generators with a post-processor [17]. RC-QASyn checks only source-justified declarations and permits a deliberately narrow, integer-only correction with an explicit edit budget, so that repairs remain auditable and never fabricate labels or features.

E. Oversampling and imbalanced learning

SMOTE interpolates minority observations [18]. Cleaning steps such as Tomek links and edited nearest neighbours remove synthetic or real samples after oversampling [19], and SMOTE-IPF applies an ensemble noise filter after SMOTE [20]; both are close in spirit to support-based admission. We use established imbalanced-learn implementations, including mixed-type SMOTENC [21]. Oversampling is a generation/training baseline, random candidate selection is a curation control, and class weighting changes classifier training. They answer different questions.

F. Calibration and inference

Calibration concerns agreement between confidence and observed outcomes [22]; candidate percentiles lack that interpretation. Bootstrap inference depends on its resampling design [23], and supplementary Wilson recall intervals address small positive counts [24]. Synthetic-data surveys and LLM-judge studies motivate traceability while limiting what recorded critic decisions establish [25], [26].

III. Methodology

Let T denote REAL TRAIN, E REAL TEST and $G = \{(o_i, x_i, y_i)\}$ the candidate stream. Occurrence identity distinguishes physical records even when payloads are equal. Source files, ordinals, payload hashes, specifications and experiment identities link each selected record to its inputs. Missing class remains missing; generation conditioning never supplies an absent payload label.

A. Authoritative structure and statistical evidence

Specifications identify required features/class, numerical primitives, nominal values, integer declarations and permitted fields. Supported violations can reject. Observed ranges do not become universal physical bounds. Existing checks are reused without adding a validator family.

For p features, the TRAIN-scaled mixed distance is

$$d(x,t) = \frac{1}{p}\sum_j \delta_j(x_j,t_j), \quad \delta_j = \begin{cases} \min(|x_j - t_j|/R_j, 1), & \text{numeric}, R_j > \\ \mathbf{1}[x_j \neq t_j], & \text{nominal or } R \end{cases} \tag{1}$$

Here R_j is TRAIN span and class is excluded. Local support $L_k(x)$ averages distances to the nearest $\min(k, |T_s|)$ supported TRAIN observations, with row-identity tie breaking; primary $k = 5$.

Global consistency scales numerical features by TRAIN median/IQR, falling back to span then one, and one-hot encodes TRAIN categories. For encoded dimension D, covariance S and mean μ,

$$\Sigma = (1-\alpha)S + \alpha\,\mathrm{diag}(S) + \lambda I, \qquad Q(x) = \sqrt{\max(0, (z-\mu)^\top \Sigma^{-1}(z- \tag{2}$$

Primary $\alpha = .10$, $\lambda = 10^{-8}$. Unsupported evidence and unseen TRAIN categories remain explicit. Existing sensitivities vary k or shrinkage.




Fig. 1. RC-QASyn architecture. Structure and statistical support are separate. Optional repair creates derived versions and repeats checks. B1/B2/B3 remain frozen controls. REAL TEST enters only evaluation. Dashed arrows denote provenance or optional reevaluation.

B. Descriptive combination and admission

For dataset/family candidate-score reference A_f, use

$$u_f(s) = \big(\#\{a < s\} + \tfrac{1}{2}\#\{a = s\}\big)/|A_f|. \tag{3}$$

Larger ranks indicate weaker support. Combined concern is $\max(u_L, u_Q)$ with both components required, an uncalibrated index rather than a validity probability. No independence assumption or learned fusion weight is introduced.

Admission rejects authoritative defects, abstains when required evidence is unavailable, requests review for partial structure or concern at least $q = .90$, and otherwise provisionally passes. Structure/local/global policies form ablations; combined

TABLE I
FROZEN TASK DATASETS AND LITERAL POSITIVE COUNTS.

Dataset	Rows	TRAIN	TEST	TRAIN+	TEST+	Candidates
Abalone19	4174	3340	834	26	6	200
Ecoli4	336	269	67	16	4	201
page-blocks0	5472	4377	1095	447	112	200

$q = .80, .95$ are historical sensitivities. Track A preserves historical models and ranks, including for derived queries. Track B reconstructs scores and reference ranks separately for each new TRAIN-fitted candidate pool.

C. Coverage-aware construction

Let $\mathcal{R}$ be distinct TRAIN feature/class regions and $h_t(S) = \mathbf{1}[\min_{s\in S} d(s,t) \le .05]$. Uniform coverage averages h_t over regions; balanced coverage assigns each class-y region weight $1/(Kn_y)$. Distinct-feature TRAIN coverage is reported separately.

At budget b, source order selects earliest occurrences; farthest-first maximizes minimum selected-set separation; coverage-greedy maximizes uniform marginal coverage. Quality-coverage prohibits repeated feature payloads, fills a feasible minority quota $\lfloor .5b \rfloor$ first, and uses the unchanged lexicographic objective: balanced marginal coverage, fewer neighbors within .01, greater separation, lower concern, then stable source order. Exact redundancy is $1 - u/n$ for u unique full payloads among n selections. Near redundancy is the fraction with another selected record within .01, unavailable for $n < 2$.

D. Bounded structural repair

Only fractional finite values in source-declared integer fields can change. Decimal half-to-even rounding must satisfy

$$|J| \le 3, \quad |x'_j - x_j| \le .5 \ (j \in J), \qquad x'_j = x_j \ (j \notin J). \quad (4)$$

Missing targets/features, category substitutions and imputation are excluded. More than three required edits refuses the whole record. Derived identities bind parent, policy, specification and payload; originals remain immutable. Frozen evidence and admission rescore repairs, and parent exclusivity prevents counting versions twice. Expanded-pool comparisons measure repair plus subsequent reselection, rather than the isolated effect of a numerical edit.

IV. EXPERIMENTAL DESIGN

The protocol was committed before new scores (`91619f1`); the implementation starts from frozen main `244a9bf`. RQ1 concerns structural frequency, RQ2 evidence complementarity, RQ3 coverage/redundancy, RQ4 repair, RQ5 utility and RQ6 stability/uncertainty. Settings remain fixed after scoring.

A. Track A: historical fixed-split study

The source datasets, original TRAIN/TEST identities and 601 historical candidates remain unchanged. Candidates depended on original TRAIN and are never reassigned to new outer splits. Previously evaluated TEST is reused descriptively. Exact feature-value TRAIN/TEST overlap is recorded in population manifests.

Budgets are 56 (Abalone19), 70 (Ecoli4) and 49 (page-blocks0), inherited from original construction. Raw-labeled random controls retain evaluable integer defects but exclude absent labels and unsupported features. Schema random additionally requires complete structural compliance. Admitted random uses the same combined-admitted pool as the four deterministic selectors. Random controls use seeds $13, 29, 43, 61, 79$. Admission ablations apply the same quality-coverage selector after structure-only, local, global or combined eligibility; pool-size changes are part of the intervention.

All 138 historical utility comparisons are replayed with saved predictions. Recorded B1/B2/B3 remain frozen; utility controls explicitly intersect their acceptance with structural completeness. The archived raw scorer could interpret missing class as the string `nan`; those scores are not used as complete binary-record comparisons.

B. External training comparators

RandomOverSampler (ROS) and SMOTE append exactly b minority rows to real TRAIN; Abalone19 uses SMOTENC because sex is categorical. Interpolation uses TRAIN-fitted numerical standardization and inverse transformation. Fractional values in integer-declared page-blocks0 fields are measured rather than silently rounded. Balanced logistic loss supplies a non-generative comparator. These training alternatives are distinct from same-pool curation. Mixed-class historical subsets may add fewer than b minority rows in hybrid regimes, as disclosed by exported class counts.

C. Track B: fresh split-specific offline curation

Five deterministic stratified 80/20 splits per dataset use seeds $13, 29, 43, 61, 79$ and the repository's hash-based algorithm. Every split refits preprocessing, generation, evidence and geometry using its TRAIN alone. Fresh pools contain $4b$ minority records: SMOTENC for Abalone19, SMOTE for Ecoli4 and ROS for integer-declared page-blocks0. ROS preserves source integers but creates no new support. Interpolation uses $k = \min(5, n_+ - 1)$.

Six matched-budget curators compare schema random, admitted random, admitted source order, farthest-first, coverage-greedy and quality-coverage. Real-only, class-weighted and ROS/SMOTE training comparisons are separate. Minority-only pools support hybrid augmentation; pure TSTR is unavailable by design. This is an offline curation experiment, not replication of LLM candidate quality. Holdouts can overlap, so across-split SD describes variability rather than an independent-sample standard error.

D. Classifiers, metrics and uncertainty

Models remain logistic regression (liblinear, maximum 300 iterations) and random forest (50 trees), seed 42. Median imputation, standard scaling and one-hot encoding fit only actual training populations. TRTR trains on real TRAIN; pure

TSTR trains on synthetic rows only; hybrid appends synthetic positive-literal records to real TRAIN. One-class training and empty augmentation remain unavailable.

We report $F_1 = 2TP/(2TP+FP+FN)$, balanced accuracy $\frac{1}{2}[TP/(TP+FN)+TN/(TN+FP)]$, MCC, AP and AUROC. AP is the step integral $\sum_k (R_k - R_{k-1})P_k$; repository `pr_auc` is its alias, not trapezoidal area. Point MCC follows the frozen zero convention for degenerate predicted margins; undefined bootstrap margins are counted explicitly.

Historical intervals use saved paired predictions, 2,000 stratified resamples, seed 20261025 and 95% percentile bounds. Positive/negative indices are sampled independently within observed strata, identically across paired methods. Metrics are recomputed for each resampled population. Primary pairs compare original quality-coverage with schema/admitted random seed 13, hybrid quality-coverage with TRTR, and repaired with original quality-coverage. Valid/undefined replicate counts are saved. Intervals condition on fitted models, observed TEST and class counts, excluding generation/refitting uncertainty. Between-split mean $\pm$ sample SD is separate. No multiplicity-adjusted significance claim is made.

V. Results

A. RQ1–RQ2: structure and complementary support

There are 75 structural rejects (12.48%): five of 200 Abalone19, six of 201 Ecoli4 and 64 of 200 page-blocks0. Fifteen records lack class, one lacks features and 64 have fractional-integer fields; categories overlap. Twenty-six violate multiple fields. No unsupported nominal value or invalid numerical primitive appears in this population.

Local/global Spearman correlations are .908, .488 and .621 for Abalone19, Ecoli4 and page-blocks0, with respectively 14, 30 and two tail-disagreement cases. The scores are related but do not identify identical concerns. Combined admission yields 170, 162 and 119 provisional passes, versus 195, 195 and 136 with structure only. Existing local/global, k/shrinkage and cutoff sensitivities are reused unchanged. These results establish distinct statistical information and eligibility, not semantic-error detection performance.

B. RQ3: matched-budget ablations

Table II consolidates structure, local/global admission, selection and repair. Every construction reaches its declared budget. Random rows average all five seeds; individual results and variability accompany the paper. Raw-labeled controls remove class/feature-incomplete records explicitly.

Quality-coverage increases distinct-feature TRAIN coverage over source order from .6225 to .9479 on Abalone19 and .4164 to .5056 on Ecoli4, with zero exact/near redundancy on both. Farthest-first removes redundancy but has lower Ecoli4 coverage (.4684). Coverage-greedy reaches .5056 with exact duplication .1143. These metrics distinguish different selection behavior. Combined eligibility, quotas and coverage objectives prevent interpreting this comparison as the isolated causal effect of an evidence score. Structure-only admission




Fig. 2. Historical fixed-budget distinct-feature TRAIN coverage. Random bars average five selection seeds; admitted selectors share the same pool.

followed by the same quality selector slightly exceeds full-admission coverage on Abalone19 (.951 versus .948) and Ecoli4 (.509 versus .506). On page-blocks0, full admission instead improves logistic pure-TSTR F1 over structure only (.446 versus .202). Additional evidence therefore changes outcomes without producing monotonic gains across datasets or metrics.

C. RQ4: bounded repair

All 54 eligible repairs become structurally compliant; 21 rejected records are ineligible. Repairs edit 73 fields: 39 records require one edit, eleven two and four three. Absolute changes range .1–.5, mean .3119. Five fractional-integer records also lack class and five require over three edits; neither group is repaired. Eleven further ineligible records belong to Abalone19/Ecoli4.

Under unchanged admission, 49 derived versions provisionally pass and five require review. The page-blocks0 admitted pool grows 119 to 168. At budget 49, quality-coverage selects 16 derived records: distinct-feature coverage rises .9324 to .9370, near duplication falls .3265 to .1020 and exact duplication remains zero. Source-order coverage slightly declines; other datasets are unchanged. Expanded pools therefore have method-dependent effects.

D. RQ5: utility and external comparators

All 138 historical utility rows reproduce within 10^{-12}, including 24 unavailable cases. The expanded study contains 894 utility rows: 678 successful and 216 explicitly unavailable, without execution failures or budget shortfalls. Complete files retain both classifiers, regimes, class counts, confusion counts and metrics. Eighteen additional method/type incompatibilities are listed separately.

External training baselines retain actual training populations and generated structural-compliance counts. Standard SMOTE's page-blocks0 outputs are not integer-coerced. Class weighting changes the training objective without generating records. These interventions are not matched candidate-curation alternatives. In the historical page-blocks0 SMOTE baseline, 46 of 49 generated rows fail the integer structural contract; all remain computationally evaluable numerical augmentation records, and this incompatibility is explicit rather than repaired silently.

For historical page-blocks0 logistic pure TSTR, repair-pool expansion changes F1 from .4464 to .3421, while AP changes .5552 to .5716. Hybrid F1 stays .7150. This negative

TABLE II

CONSOLIDATED HISTORICAL ABLATIONS. Q DENOTES UNCHANGED QUALITY-COVERAGE SELECTION. RANDOM ROWS AVERAGE FIVE SEEDS; COMPLETE PER-SEED DATA ACCOMPANY THE PAPER. F1 IS LOGISTIC PURE TSTR; – MEANS UNAVAILABLE.

Dataset	Method	Pool	n	Coverage	Exact	Near	F1
Abalone19	Raw labeled random	195	56	0.799	0.171	0.443	0.029
	Schema random	195	56	0.799	0.171	0.443	0.029
	Admitted random	170	56	0.833	0.236	0.493	0.022
	Structure + Q selection	195	56	0.951	0.000	0.000	0.030
	Structure/local + Q	177	56	0.950	0.000	0.000	0.031
	Structure/global + Q	177	56	0.948	0.000	0.000	0.031
	Structure/local/global + Q	170	56	0.948	0.000	0.000	0.031
	Admitted source order	170	56	0.622	0.357	0.625	–
	Admitted farthest first	170	56	0.940	0.000	0.000	0.035
	Admitted coverage greedy	170	56	0.948	0.107	0.268	0.030
	Repair pool + Q	170	56	0.948	0.000	0.000	0.031
Ecoli4	Raw labeled random	195	70	0.422	0.097	0.180	0.253
	Schema random	195	70	0.422	0.097	0.180	0.253
	Admitted random	162	70	0.439	0.117	0.197	0.217
	Structure + Q selection	195	70	0.509	0.000	0.000	0.216
	Structure/local + Q	175	70	0.509	0.000	0.000	0.195
	Structure/global + Q	177	70	0.506	0.000	0.000	0.229
	Structure/local/global + Q	162	70	0.506	0.000	0.000	0.205
	Admitted source order	162	70	0.416	0.200	0.386	–
	Admitted farthest first	162	70	0.468	0.000	0.000	0.200
	Admitted coverage greedy	162	70	0.506	0.114	0.243	0.108
	Repair pool + Q	162	70	0.506	0.000	0.000	0.205
page-blocks0	Raw labeled random	195	49	0.905	0.061	0.559	0.390
	Schema random	136	49	0.889	0.069	0.559	0.477
	Admitted random	119	49	0.914	0.082	0.702	0.535
	Structure + Q selection	136	49	0.934	0.000	0.286	0.202
	Structure/local + Q	120	49	0.932	0.000	0.327	0.446
	Structure/global + Q	120	49	0.934	0.000	0.327	0.448
	Structure/local/global + Q	119	49	0.932	0.000	0.327	0.446
	Admitted source order	119	49	0.914	0.265	0.592	–
	Admitted farthest first	119	49	0.932	0.000	0.000	0.550
	Admitted coverage greedy	119	49	0.932	0.163	0.449	0.627
	Repair pool + Q	168	49	0.937	0.000	0.102	0.342

TABLE III

HISTORICAL EXTERNAL TRAINING BASELINES. ROS AND SMOTE/NC APPEND B MINORITY ROWS. LR: LOGISTIC REGRESSION; RF: RANDOM FOREST. THESE DIFFER FROM CANDIDATE CURATION.

Dataset / method	Model	$+n$	F1	AP	BA	MCC
Abalone19 / Real	LR	0	0.000	0.026	0.500	0.000
Abalone19 / Real	RF	0	0.000	0.023	0.500	0.000
Abalone19 / Weighted LR	LR	0	0.054	0.038	0.873	0.144
Abalone19 / ROS+b	LR	56	0.000	0.031	0.500	0.000
Abalone19 / ROS+b	RF	56	0.000	0.031	0.500	0.000
Abalone19 / SMOTENC+b	LR	56	0.000	0.014	0.499	-0.003
Abalone19 / SMOTENC+b	RF	56	0.000	0.020	0.499	-0.003
Ecoli4 / Real	LR	0	1.000	1.000	1.000	1.000
Ecoli4 / Real	RF	0	0.667	1.000	0.750	0.696
Ecoli4 / Weighted LR	LR	0	0.800	1.000	0.984	0.803
Ecoli4 / ROS+b	LR	70	1.000	1.000	1.000	1.000
Ecoli4 / ROS+b	RF	70	0.857	1.000	0.875	0.859
Ecoli4 / SMOTE+b	LR	70	1.000	1.000	1.000	1.000
Ecoli4 / SMOTE+b	RF	70	0.857	1.000	0.875	0.859
page-blocks0 / Real	LR	0	0.715	0.746	0.802	0.699
page-blocks0 / Real	RF	0	0.869	0.921	0.911	0.856
page-blocks0 / Weighted LR	LR	0	0.721	0.768	0.903	0.696
page-blocks0 / ROS+b	LR	49	0.728	0.746	0.811	0.712
page-blocks0 / ROS+b	RF	49	0.864	0.920	0.906	0.851
page-blocks0 / SMOTE+b	LR	49	0.728	0.758	0.811	0.712
page-blocks0 / SMOTE+b	RF	49	0.869	0.916	0.911	0.856

result accompanies improved coverage and near redundancy: geometric gains do not ensure utility gains.

TABLE IV
CONDITIONAL 95% BOOTSTRAP INTERVALS (2,000 STRATIFIED PAIRED RESAMPLES). Q: QUALITY-COVERAGE PURE TSTR; REAL: TRTR. DEGENERATE MCC INTERVALS ARE UNAVAILABLE; ALL VALID COUNTS ARE SAVED.

Dataset / method	Model	F1 [CI]	AP [CI]	BA [CI]	MCC [CI]
Abalone19 / Real	LR	0.000 [0.000, 0.000]	0.026 [0.022, 0.044]	0.500 [0.500, 0.500]	0.000 [–, –]
Abalone19 / Real	RF	0.000 [0.000, 0.000]	0.023 [0.012, 0.047]	0.500 [0.500, 0.500]	0.000 [–, –]
Abalone19 / Q	LR	0.031 [0.029, 0.034]	0.019 [0.012, 0.068]	0.775 [0.758, 0.791]	0.093 [0.087, 0.100]
Abalone19 / Q	RF	0.030 [0.018, 0.039]	0.021 [0.011, 0.046]	0.724 [0.553, 0.820]	0.078 [0.018, 0.112]
Abalone19 / Q repair	LR	0.031 [0.029, 0.034]	0.019 [0.012, 0.068]	0.775 [0.758, 0.791]	0.093 [0.087, 0.100]
Abalone19 / Q repair	RF	0.030 [0.018, 0.039]	0.021 [0.011, 0.046]	0.724 [0.553, 0.820]	0.078 [0.018, 0.112]
Ecoli4 / Real	LR	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
Ecoli4 / Real	RF	0.667 [0.000, 1.000]	1.000 [1.000, 1.000]	0.750 [0.500, 1.000]	0.696 [0.489, 1.000]
Ecoli4 / Q	LR	0.205 [0.170, 0.258]	0.135 [0.109, 0.267]	0.754 [0.690, 0.817]	0.241 [0.188, 0.307]
Ecoli4 / Q	RF	0.296 [0.235, 0.400]	0.633 [0.348, 1.000]	0.849 [0.794, 0.905]	0.349 [0.280, 0.450]
Ecoli4 / Q repair	LR	0.205 [0.170, 0.258]	0.135 [0.109, 0.267]	0.754 [0.690, 0.817]	0.241 [0.188, 0.307]
Ecoli4 / Q repair	RF	0.296 [0.235, 0.400]	0.633 [0.348, 1.000]	0.849 [0.794, 0.905]	0.349 [0.280, 0.450]
page-blocks0 / Real	LR	0.715 [0.637, 0.783]	0.746 [0.663, 0.832]	0.802 [0.754, 0.845]	0.699 [0.619, 0.769]
page-blocks0 / Real	RF	0.869 [0.819, 0.914]	0.921 [0.868, 0.965]	0.911 [0.872, 0.944]	0.856 [0.802, 0.904]
page-blocks0 / Q	LR	0.446 [0.395, 0.500]	0.555 [0.458, 0.656]	0.759 [0.715, 0.804]	0.389 [0.325, 0.456]
page-blocks0 / Q	RF	0.342 [0.308, 0.377]	0.447 [0.368, 0.534]	0.727 [0.685, 0.768]	0.288 [0.234, 0.342]
page-blocks0 / Q repair	LR	0.342 [0.303, 0.383]	0.572 [0.482, 0.676]	0.713 [0.669, 0.758]	0.278 [0.222, 0.337]
page-blocks0 / Q repair	RF	0.316 [0.283, 0.350]	0.474 [0.391, 0.572]	0.704 [0.661, 0.748]	0.254 [0.200, 0.309]

E. RQ6: conditional uncertainty and fresh-split stability

The 216 endpoint and 168 paired-difference intervals derive from saved predictions. Page-blocks0 logistic repair-minus-original F1 is approximately $-.1043$, with conditional interval $[-.1350, -.0739]$; AP difference is $.0165$, interval $[-.0071, .0493]$. F1 decreases consistently under this conditional resampling design, while AP direction is less stable. These remain descriptive intervals on reused historical TEST.

Ecoli4 logistic TRTR predicts perfectly on only four positive and 63 negative TEST records, yielding conditional F1 interval $[1, 1]$. Its Wilson positive-recall interval is approximately $[.510, 1]$. Resampling perfect observed predictions cannot establish universal performance. Abalone19 has only six positive TEST examples; resampling adds no independent positive observations.

All 15 split-specific runs complete. Ecoli4 logistic F1 is $.8476 \pm .1186$ for real-only training and $.7581 \pm .1659$ for quality-curated augmentation. Admitted random has the same mean F1 there, though ranking metrics differ. Abalone19 logistic F1 stays zero under real-only and the declared augmentation methods; balanced logistic loss reaches $.0506 \pm .0095$. On page-blocks0, real-only F1 is $.7284 \pm .0256$, quality-curated augmentation $.7383 \pm .0283$ and admitted random $.7409 \pm .0270$. These outcomes do not show a uniform augmentation benefit or superiority over simple curation.

Split-wise paired differences use identical evaluation records. Pure TSTR on offline minority-only pools is unavailable, never renamed hybrid augmentation.

F. Exploratory addendum

The experiments in this subsection were declared after the main study, in two settings files committed before any score was computed, and each was executed once. They test four gaps identified in review: the small number of datasets, the half-budget minority quota, the absence of an equal-budget B2 comparison and the absence of published curation and oversampling baselines. None of these results enters the preceding tables, and all tests are exploratory, without multiplicity adjustment or significance claims.




Fig. 3. Every fresh-split logistic F1 value; black bars show five-split means. Real-only and hybrid regimes are distinct. The page-blocks0 pool generator is ROS.

Six further KEEL datasets join the three original ones (Table VI). They follow the fresh-split design of RQ6: five stratified splits, train-only fitting, minority-only SMOTE or SMOTENC pools of size $4b$, and the budget $b = \min(70, \max(30, \mathrm{round}(0.5\, n_{\min})))$. A seventh candidate, winequality-red-4, is unavailable because its source archive is empty. vehicle0 declares all 18 features as integers; unrounded SMOTE interpolation violates that declaration in all 1,400 candidates across its five splits, and bounded repair recovers only six, because nearly every record needs more than three integer edits. No curator can therefore run on vehicle0, although training comparators still can. This is the first fresh-split case in this study where the structural checks change the outcome: interpolation oversamplers can break source declarations wholesale, and the deliberately narrow repair bound declines to rewrite such records.

Across the eight datasets with usable pools, quality-coverage does not outperform random selection from the same admitted pool (Table VII). The median dataset-level F1 difference is $+.001$ for logistic regression and $+.013$ for random forest;

TABLE V

OFFLINE REPLICATION: FIVE REPEATED STRATIFIED HOLDOUTS, LOGISTIC REGRESSION, MEAN ± SAMPLE SD. REAL AND WEIGHTED ARE TRTR; OTHER METHODS ARE HYBRID MINORITY AUGMENTATION. NO HISTORICAL CANDIDATES ARE REUSED.

Dataset / method	k	F1	AP	BA	MCC
Abalone19 / Weighted LR	5	0.051 ± 0.009	0.045 ± 0.014	0.779 ± 0.071	0.116 ± 0.028
Abalone19 / Real	5	0.000 ± 0.000	0.042 ± 0.015	0.500 ± 0.000	0.000 ± 0.000
Abalone19 / ROS+b	5	0.000 ± 0.000	0.040 ± 0.014	0.500 ± 0.001	-0.002 ± 0.002
Abalone19 / SMOTENC+b	5	0.000 ± 0.000	0.041 ± 0.013	0.500 ± 0.000	-0.002 ± 0.002
Abalone19 / Curated Q	5	0.000 ± 0.000	0.044 ± 0.011	0.500 ± 0.001	-0.002 ± 0.002
Abalone19 / Admitted random	5	0.000 ± 0.000	0.047 ± 0.016	0.500 ± 0.000	-0.001 ± 0.002
Abalone19 / Schema random	5	0.000 ± 0.000	0.041 ± 0.012	0.500 ± 0.000	-0.002 ± 0.002
Ecoli4 / Weighted LR	5	0.695 ± 0.117	0.923 ± 0.053	0.928 ± 0.074	0.692 ± 0.127
Ecoli4 / Real	5	0.848 ± 0.119	0.944 ± 0.058	0.875 ± 0.088	0.855 ± 0.108
Ecoli4 / ROS+b	5	0.745 ± 0.177	0.908 ± 0.055	0.865 ± 0.089	0.744 ± 0.182
Ecoli4 / SMOTE+b	5	0.758 ± 0.166	0.944 ± 0.058	0.867 ± 0.089	0.757 ± 0.170
Ecoli4 / Curated Q	5	0.758 ± 0.166	0.934 ± 0.050	0.867 ± 0.089	0.757 ± 0.170
Ecoli4 / Admitted random	5	0.758 ± 0.166	0.934 ± 0.050	0.867 ± 0.089	0.757 ± 0.170
Ecoli4 / Schema random	5	0.758 ± 0.166	0.944 ± 0.058	0.867 ± 0.089	0.757 ± 0.170
page-blocks0 / Weighted LR	5	0.708 ± 0.029	0.788 ± 0.024	0.913 ± 0.013	0.687 ± 0.031
page-blocks0 / Real	5	0.728 ± 0.026	0.800 ± 0.019	0.819 ± 0.025	0.709 ± 0.025
page-blocks0 / ROS+b	5	0.738 ± 0.028	0.800 ± 0.019	0.828 ± 0.028	0.718 ± 0.029
page-blocks0 / SMOTE+b	5	0.736 ± 0.033	0.800 ± 0.019	0.826 ± 0.031	0.715 ± 0.032
page-blocks0 / Curated Q	5	0.738 ± 0.028	0.800 ± 0.020	0.828 ± 0.029	0.718 ± 0.029
page-blocks0 / Admitted random	5	0.741 ± 0.027	0.799 ± 0.019	0.829 ± 0.030	0.721 ± 0.026
page-blocks0 / Schema random	5	0.736 ± 0.030	0.800 ± 0.019	0.826 ± 0.029	0.716 ± 0.029

TABLE VI

EXPLORATORY ADDENDUM, DECLARED AFTER THE MAIN STUDY. DATASETS. IR = MAJORITY/MINORITY; b = SELECTION BUDGET; TEST POSITIVES ARE PER SPLIT (FIVE STRATIFIED 80/20 SPLITS).

Dataset	Rows	Min.	IR	Nom.	b	TEST pos.	Pool gen.
Abalone19	4174	32	129.4	yes	56	6	SMOTENC
Ecoli4	336	20	15.8	no	70	4	SMOTE
page-blocks0	5472	559	8.8	no	49	112	RandomOverSampler
yeast3	1484	163	8.1	no	65	33	SMOTE
yeast4	1484	51	28.1	no	30	10	SMOTE
vehicle0	846	199	3.3	no	70	40	SMOTE
segment0	2308	329	6.0	no	70	66	SMOTE
ecoli1	336	77	3.4	no	31	15	SMOTE
abalone9-18	731	42	16.4	yes	30	8	SMOTENC
winequality-red-4	unavailable (empty source archive)						

TABLE VII

EXPLORATORY ADDENDUM, DECLARED AFTER THE MAIN STUDY. ADDENDUM V1 ACROSS-DATASET SUMMARY: DATASET-LEVEL MEAN DIFFERENCE AND SPLIT WINS/TIES/LOSSES OVER FIVE FRESH SPLITS.

Comparison	Clf	Metric	Datasets $+/-/0$	Splits W/T/L	Median diff.
QC − adm. random	LR	AP	3/4/1	17/7/16	-0.001
QC − adm. random	LR	F1	4/1/3	11/22/7	+0.001
QC − adm. random	RF	AP	5/3/0	19/6/15	+0.002
QC − adm. random	RF	F1	6/2/0	15/15/10	+0.013
QC − real only	LR	AP	3/5/0	18/6/16	-0.000
QC − real only	LR	F1	5/1/2	15/15/10	+0.006
QC − real only	RF	AP	5/3/0	17/5/18	+0.002
QC − real only	RF	F1	5/2/1	18/11/11	+0.027
Best aug. − real only*	LR	AP	6/2/1	25/9/11	+0.003
Best aug. − real only*	LR	F1	6/1/2	18/17/10	+0.006
Best aug. − real only*	RF	AP	8/1/0	23/6/16	+0.021
Best aug. − real only*	RF	F1	7/2/0	28/9/8	+0.035

*Best method chosen on the same TEST splits; optimistic by construction.

over 40 paired splits per classifier, wins, ties and losses are 11/22/7 and 15/15/10, and exploratory Wilcoxon p-values for F1 and AP range from .19 to 1.00. The geometric effect, in contrast, replicates: on all five new datasets with usable pools, quality-coverage covers more distinct TRAIN support at radius .05 and selects fewer near-duplicates than admitted random selection, for example .677 versus .461 coverage and .000 versus .327 near-duplication on abalone9-18. Choosing the best augmentation per dataset can appear to beat real-only training, but that choice uses the same TEST splits and is optimistic by construction.

On the historical split (Table VIII), setting the minority quota to $\lfloor b\times$ TRAIN minority fraction$\rfloor$ lowers it from 28, 35 and 24 to 0, 4 and 5 records. Coverage is unchanged on all three datasets. Pure TSTR F1 rises on page-blocks0 (.446 to .593 with logistic regression, .342 to .631 with random forest), where near-duplication also falls from .327 to zero, but it falls on Ecoli4 (.296 to .250 with random forest) and slightly on Abalone19. Hybrid F1 moves by at most .011. The half-budget quota therefore shapes synthetic-only results in both directions and is not the main determinant of hybrid utility. At an equal budget, quality-coverage covers more TRAIN support than random subsets of the B2-accepted, structurally complete pool on all three datasets (.948, .506 and .932 versus .853, .419 and .905), whereas F1 shows no consistent winner: B2 subsets are ahead on page-blocks0 random-forest TSTR (.438 versus .342) and behind on Ecoli4 (.271 versus .296).

The second addendum benchmarks quality-coverage inside the same pipeline, on the nine available datasets, the same splits, pools and classifiers. Two curators re-implement published principles rather than the authors' code: a learning-dynamics filter in the spirit of CLLM [5], which keeps low-aleatoric, high-confidence candidates under a gradient-boosting model fitted on real TRAIN, and a discriminator-realism filter following the realism component of RUBRIC [8] and sample-level auditing [9], which keeps the candidates a random forest finds hardest to tell apart from real minority rows. All 45 rebuilt pools

TABLE VIII

EXPLORATORY ADDENDUM, DECLARED AFTER THE MAIN STUDY. ADDENDUM V1 HISTORICAL-SPLIT DESIGNS AT FIXED BUDGETS: CANONICAL QUALITY-COVERAGE (QC, QUOTA $0.5b$), QC WITH THE REAL-RATIO QUOTA (E2), ADMITTED RANDOM (MEAN OF FIVE SEEDS) AND RANDOM SUBSETS OF THE B2-ACCEPTED POOL (E3, MEAN OF FIVE SEEDS).

Dataset	Design	Quota	Cov.	Near dup.	LR TSTR F1	LR Hyb. F1	RF TSTR F1	RF Hyb. F1	LR Hyb. AP
Abalone19	QC	28	.948	.000	.031	.000	.030	.000	.017
Abalone19	QC real ratio (E2)	0	.948	.000	.029	.000	.027	.000	.018
Abalone19	Adm. random	–	.833	.493	.022	.000	.030	.000	.021
Abalone19	B2 random (E3)	–	.853	.232	.026	.000	.030	.000	.015
Ecoli4	QC	35	.506	.000	.205	1.000	.296	1.000	1.000
Ecoli4	QC real ratio (E2)	4	.506	.000	.190	1.000	.250	1.000	1.000
Ecoli4	Adm. random	–	.439	.197	.217	.933	.231	1.000	1.000
Ecoli4	B2 random (E3)	–	.419	.049	.213	.933	.271	1.000	1.000
page-blocks0	QC	24	.932	.327	.446	.715	.342	.863	.744
page-blocks0	QC real ratio (E2)	5	.932	.000	.593	.722	.631	.873	.747
page-blocks0	Adm. random	–	.914	.702	.535	.715	.475	.869	.743
page-blocks0	B2 random (E3)	–	.905	.506	.421	.715	.438	.867	.744

match the content fingerprints recorded earlier, and the 930 overlapping rows reproduce exactly. Among the eight curators (Table IX), quality-coverage has the best average rank only for logistic-regression F1 (3.75 of 8); the CLLM-style filter ranks best for logistic-regression AP (2.44) and the discriminator for random-forest AP (2.88), and Friedman tests do not separate the curators ($p = .21$ to $.65$).

Four published oversamplers from imbalanced-learn [21] serve as training comparators: SMOTE-ENN and SMOTE-Tomek [19], Borderline-SMOTE [27] and ADASYN [28], each with full balancing and with b added rows (Table X). Full balancing helps random forest most on the hardest datasets, for example SMOTE-Tomek reaches F1 .433 on yeast4 against .268 for quality-coverage, but the same oversamplers often reduce logistic-regression F1, to .63–.68 on yeast3 against .78. Availability is itself a finding. Borderline-SMOTE and ADASYN offer no path for nominal features, the cleaning step of SMOTE-ENN and SMOTE-Tomek fails on nominal columns, and ADASYN with b added rows generates no samples on page-blocks0; with vehicle0 lacking curators, the complete-case comparison covers five datasets. As context only, our real-only and SMOTE AUROC values exceed those reported by Newaz and Haq [29] for six shared datasets under 10-fold cross-validation, and the sign of the SMOTE effect agrees with theirs in five of twelve dataset–classifier pairs.

Across all sixteen methods on those five datasets (Table XI), full-balancing SMOTE-Tomek and ADASYN have the best random-forest F1 ranks (3.70 and 4.50, against 7.60 for quality-coverage; Friedman $p = .031$), while no method dominates the other three classifier–metric combinations. No Wilcoxon comparison of quality-coverage with any method reaches $p < .05$ (smallest .06). Taken together, the addenda support the same reading as the main study on nine datasets: quality-coverage reliably improves the coverage and redundancy of the curated set, but it does not improve classifier utility over simple selection or published oversampling.

VI. DISCUSSION

The strongest empirical contribution is a measurable separation of compliance, support, geometry and utility. Structural defects occur often enough in this historical stream to motivate explicit checks, and narrow repair corrects an eligible subset without fabricating labels. Coverage-oriented construction can reduce redundancy, but its classifier consequences remain mixed. Geometric evidence should therefore accompany direct task evaluation.

Admission ablations estimate the effect of changing candidate availability under fixed downstream rules, not a score's isolated utility effect with selected identities held constant. Repair changes both pool and selection; its utility decrease cannot be assigned solely to rounding one field. Source order can exclude the minority entirely, making unavailable TSTR a meaningful result rather than justification for adding ineligible data.

Simple alternatives are informative. Farthest-first eliminates duplicates, random selection remains competitive offline, and balanced logistic loss gives nonzero Abalone19 F1 where fixed-budget augmentation does not. The contribution is auditable curation with explicit tradeoffs rather than universally superior classifier training.

VII. LIMITATIONS

The historical study uses three datasets, a previously evaluated TEST and recorded exact-feature TRAIN/TEST overlap. Full original TRAIN influenced generation, preventing independent split claims from that pool. The fresh study rebuilds all fitted objects and candidates, but holdouts overlap and generators differ from the LLM stream. ROS adds no new support, and minority-only pools preclude pure TSTR. Offline findings, including the nine-dataset addendum (Section V-F), do not establish LLM-generation replication.

Four and six historical TEST positives limit Ecoli4 and Abalone19 inference, and the addendum adds datasets with

TABLE IX
EXPLORATORY ADDENDUM, DECLARED AFTER THE MAIN STUDY. MEAN F1 AND AP OF THE EIGHT CURATORS (HYBRID TRAINING: REAL TRAIN PLUS b SELECTED CANDIDATES).

Dataset	Schema rand.	Adm. rand.	Source order	Farthest-first	Cov.-greedy	QC (ours)	CLLM-style†	Disc.-realism†
LR, mean F1 over five splits								
Abalone19	**.000**	**.000**	**.000**	**.000**	**.000**	**.000**	**.000**	**.000**
Ecoli4	.758	.758	.758	.758	.758	.758	**.826**	.758
page-blocks0	.736	**.741**	.738	.738	.740	.738	.736	.739
yeast3	.773	.769	.779	.773	**.782**	**.782**	.771	.779
yeast4	.152	.150	.154	**.203**	.158	.158	.180	.185
segment0	**.988**	**.988**	**.988**	**.988**	**.988**	**.988**	**.988**	**.988**
ecoli1	.760	.745	.749	.750	.762	.758	.742	**.762**
abalone9-18	.676	.677	**.684**	.670	.670	.679	.671	.659
LR, mean AP over five splits								
Abalone19	.041	.047	.046	.047	.045	.044	**.050**	.042
Ecoli4	**.944**	.934	.934	.934	.934	.934	**.944**	.937
page-blocks0	.800	.799	.799	.800	.799	.800	**.800**	.799
yeast3	.813	.809	.807	.809	.807	.808	**.813**	.813
yeast4	.311	.319	.311	.327	.306	.305	**.331**	.322
segment0	.977	.977	.977	.978	.977	**.978**	.974	.977
ecoli1	.861	.862	**.868**	.864	.867	.865	.864	.861
abalone9-18	.774	.780	.771	.780	.781	.775	**.783**	.780
RF, mean F1 over five splits								
Abalone19	.000	**.057**	.000	.000	.000	.000	.000	.000
Ecoli4	.786	.748	**.819**	.800	.762	.786	.743	.790
page-blocks0	.890	**.893**	.892	.891	.886	.885	.890	.885
yeast3	.775	.790	.787	.794	**.810**	.801	.781	.794
yeast4	.246	.245	.240	.238	.210	.268	**.335**	.199
segment0	.991	.989	.989	**.991**	**.991**	**.991**	.989	.989
ecoli1	.775	.736	.771	**.782**	.773	.754	.748	.762
abalone9-18	.348	.373	.402	.370	**.406**	.388	.313	.392
RF, mean AP over five splits								
Abalone19	.040	**.070**	.034	.030	.037	.033	.039	.041
Ecoli4	.884	.872	**.895**	.882	.870	.882	.811	.883
page-blocks0	.922	.922	.924	.925	.924	.926	**.929**	.924
yeast3	.859	.867	.855	.873	.858	.859	.875	**.875**
yeast4	.406	.379	.401	.415	.364	.407	.383	**.421**
segment0	1.000	1.000	**1.000**	1.000	1.000	1.000	1.000	1.000
ecoli1	.867	.862	.857	.860	.840	.820	.868	**.870**
abalone9-18	.480	.533	.511	.551	**.567**	.554	.497	.518

Bold: best in row. †Re-implementation of the published principle, not the authors' code. vehicle0 omitted: no structurally complete candidate.

only eight (abalone9-18) and ten (yeast4) positives per split. Stratified intervals condition on observed records and fixed models; they do not quantify generation/refitting uncertainty or discover unseen positive modes. Undefined MCC margins are excluded with counts reported, potentially changing the conditional target. Comparisons are exploratory, without multiplicity-adjusted significance or state-of-the-art claims.

Source declarations establish a limited contract. Physical constraints, original target meaning and cross-field semantics remain unresolved where sources cannot justify them. No human annotation experiment is conducted, so complete semantic validity is not independently established. Evidence remains uncalibrated and provisional admission is a selection policy, not verified validity. Distances depend on scaling, support and covariance assumptions; coverage establishes neither predictive accuracy nor privacy.

The utility evidence does not favour the proposed selector. Several gaps raised in review are now tested in the exploratory addendum, and none changes this reading. Across eight datasets with usable pools, quality-coverage improves coverage and redundancy but not F1 or AP relative to random selection from the same admitted pool. Setting the minority quota to the observed class ratio leaves coverage unchanged and moves synthetic-only F1 in both directions. At an equal budget, B2-accepted random subsets are neither consistently better nor worse. Published full-balancing oversamplers rank

TABLE X

EXPLORATORY ADDENDUM, DECLARED AFTER THE MAIN STUDY. MEAN F1 AND AP OF REAL-ONLY TRAINING, CLASS WEIGHTING, EXISTING OVERSAMPLERS, FOUR PUBLISHED OVERSAMPLERS (IMBALANCED-LEARN 0.14.2; FULL BALANCING AND $+b$ ROWS) AND QUALITY-COVERAGE.

Dataset	Real only	CW-LR	ROS+b	SMOTE(NC)+b	SMOTE-ENN full	SMOTE-ENN +b	SMOTE-Tomek full	SMOTE-Tomek +b	B-SMOTE full	B-SMOTE +b	ADASYN full	ADASYN +b	QC (ours)
LR, mean F1 over five splits													
Abalone19	.000	**.051**	.000	.000	–	–	–	–	–	–	–	–	.000
Ecoli4	**.848**	.695	.745	.758	.711	.758	.745	.758	.700	.723	.688	.740	.758
page-blocks0	.728	.708	.738	.736	.693	**.761**	.699	.743	.665	.738	.628	–	.738
yeast3	.776	.660	.770	.778	.648	.779	.676	.776	.634	**.782**	.641	.776	.782
yeast4	.101	.235	.147	.154	.209	.099	.231	.200	**.282**	.201	.217	.222	.158
vehicle0	.927	.923	.931	.929	.892	.907	.922	.931	.919	.930	.918	**.934**	–
segment0	.988	.965	.988	.988	**.991**	.988	**.991**	.988	.931	.986	.938	.989	.988
ecoli1	.751	.746	.754	.749	.749	.737	.749	.745	**.760**	.730	.757	.744	.758
abalone9-18	.672	.471	.666	.636	–	–	–	–	–	–	–	–	**.679**
LR, mean AP over five splits													
Abalone19	.042	**.045**	.040	.041	–	–	–	–	–	–	–	–	.044
Ecoli4	.944	.923	.908	.944	.896	**.947**	.901	.940	.897	.922	.903	.903	.934
page-blocks0	**.800**	.788	.800	.800	.789	.794	.790	.800	.752	.800	.748	–	.800
yeast3	.813	.809	.807	.809	.805	.811	.807	**.814**	.795	.810	.801	.808	.808
yeast4	.313	.251	.308	.309	.242	**.338**	.259	.329	.312	.323	.254	.307	.305
vehicle0	.982	.976	.980	.981	.927	.921	**.984**	.981	.981	.983	.980	.981	–
segment0	.976	.981	.977	.977	.985	.973	.986	.977	**.997**	.983	.996	.983	.978
ecoli1	.866	.870	**.874**	.870	.842	.842	.867	.867	.870	.872	.868	.865	.865
abalone9-18	.771	**.777**	.772	.766	–	–	–	–	–	–	–	–	.775
RF, mean F1 over five splits													
Abalone19	**.000**	–	**.000**	**.000**	–	–	–	–	–	–	–	–	**.000**
Ecoli4	.600	–	.743	.819	**.836**	.776	.800	.786	.724	.743	.798	.798	.786
page-blocks0	.893	–	.885	**.901**	.830	.856	.865	.895	.864	.896	.850	–	.885
yeast3	.775	–	.783	.777	.778	.771	.804	.786	.792	**.807**	.788	.795	.801
yeast4	.236	–	.243	.165	.329	.103	**.433**	.185	.425	.234	.405	.188	.268
vehicle0	.928	–	.927	.927	.877	.884	.920	.928	.924	**.931**	.907	.928	–
segment0	.992	–	.991	.991	.989	.989	.991	.992	.992	.994	.994	**.994**	.991
ecoli1	.726	–	.771	.738	.787	.772	**.820**	.760	.806	.789	.797	.776	.754
abalone9-18	.347	–	.373	.374	–	–	–	–	–	–	–	–	**.388**
RF, mean AP over five splits													
Abalone19	.029	–	.026	.028	–	–	–	–	–	–	–	–	**.033**
Ecoli4	.828	–	.866	.841	**.925**	.846	.880	.878	.884	.859	.910	.863	.882
page-blocks0	.925	–	.920	.924	.915	.902	.917	.921	.912	.925	.909	–	**.926**
yeast3	.868	–	.851	**.876**	.850	.836	.849	.858	.810	.860	.808	.849	.859
yeast4	.387	–	.364	.349	.352	.332	.421	.403	**.435**	.382	.368	.355	.407
vehicle0	**.984**	–	.982	.983	.931	.951	.974	.982	.980	.980	.975	.979	–
segment0	1.000	–	1.000	1.000	1.000	.992	1.000	1.000	1.000	1.000	1.000	**1.000**	1.000
ecoli1	.833	–	.864	.853	.738	**.875**	.848	.855	.800	.829	.846	.844	.820
abalone9-18	.545	–	**.557**	.522	–	–	–	–	–	–	–	–	.554

Bold: best in row. –: unavailable (no nominal path, library error or no structurally complete candidate; CW-LR is logistic only). SMOTE-ENN/Tomek may remove rows; final counts are in results.

above quality-coverage for random-forest F1. Equal-budget comparisons with B1 and B3 remain unreported; B3 would require new judge calls. The learned-curation baselines re-implement the principles of CLLM and the realism component of RUBRIC rather than the authors' code, and omit CLLM's LLM generation and RUBRIC's boundary-utility term.

The addendum has its own limits. It was designed after the main results and the review were known, so it tests declared questions rather than an independent replication. Several of its datasets derive from the same KEEL sources (yeast3 and yeast4, Ecoli4 and ecoli1, Abalone19 and abalone9-18); dataset-level tests treat them as independent, which overstates the effective sample. winequality-red-4 could not be obtained. Re-scoring the canonical comparators on a different platform changes some classifier metrics by up to .0097, and the comparison with published AUROC values uses a different protocol and is context only.

Structural checks and bounded repair are exercised mainly on the historical LLM stream. Among the fresh pools, only vehicle0 contains structural defects. There, unrounded SMOTE interpolation breaks its integer declarations in every candidate, and the repair bound of three integer edits recovers six of 1,400, so the current repair policy is not suited to interpolation output. An earlier project phase produced LLM-proposed validity labels for the 120-record audit sample (27 invalid, all structural; 93 indeterminate; none confirmed valid), but these are not human ground truth and are not used here.

A. Future work

Several directions remain open. First, independent datasets with more minority TEST records, drawn from sources beyond the KEEL derivatives used here, would allow utility differences to be resolved. Second, a second LLM generation campaign under fresh splits would test whether the structural and support evidence behaves as it does on the historical stream. Third, structural rules and repair bounds could be designed for interpolation output, where integer violations affect many fields at once. Fourth, B1 and B3 could be compared at an equal budget, together with full implementations of learned curation methods. Finally, blinded human validity labels for the audit sample remain to be completed.

VIII. CONCLUSION

RC-QASyn makes provenance, structural compliance, statistical support, fixed-budget construction and bounded repair inspectable within the existing six-phase system. The historical audit identifies 75 structural rejects, corrects all 54 eligible records and measures changes in coverage and redundancy. Paired uncertainty and fresh train-only offline experiments strengthen the evidence while revealing limited and sometimes negative utility effects. The contribution is an empirically bounded, reproducible account of curation tradeoffs.

DECLARATIONS

Authors/affiliations/CRediT: Human authors must supply accurate names, institutions, roles and contact information before submission.

Funding, conflicts and ethics: Human authors must complete institutional and venue declarations; no approval, exemption or absence of conflicts/funding is inferred. Human validity annotation is outside this study.

Data/code: Versioned local source, manifests, generated-pool provenance, paired predictions, metrics, unavailable reasons and editable manuscript accompany this revision. Public release and licensing require author review. No remote push or merge is implied.

AI assistance: An AI coding/drafting assistant supported implementation, orchestration, source checking and revision under researcher instructions. Human authors must verify the work, accept submission responsibility and adapt this declaration to institutional/venue requirements. AI is not an author.

REFERENCES

[1] L. Xu, M. Skoularidou, A. Cuesta-Infante, and K. Veeramachaneni, "Modeling tabular data using conditional GAN," in *Advances in Neural Information Processing Systems*, vol. 32, 2019. [Online]. Available: https://proceedings.neurips.cc/paper/2019/hash/254ed7d2de3b23ab10936522dd547b78-Abstract.html

[2] A. Kotelnikov, D. Baranchuk, I. Rubachev, and A. Babenko, "TabDDPM: Modelling tabular data with diffusion models," in *Proceedings of the 40th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 202. PMLR, 2023, pp. 17 564–17 579. [Online]. Available: https://proceedings.mlr.press/v202/kotelnikov23a.html

[3] V. Borisov, K. Seßler, T. Leemann, M. Pawelczyk, and G. Kasneci, "Language models are realistic tabular data generators," *arXiv preprint arXiv:2210.06280*, 2023. [Online]. Available: https://arxiv.org/abs/2210.06280

[4] J. Kim, T. Kim, and J. Choo, "EPIC: Effective prompting for imbalanced-class data synthesis in tabular data classification via large language models," in *Advances in Neural Information Processing Systems*, vol. 37, 2024.

[5] N. Seedat, N. Huynh, B. van Breugel, and M. van der Schaar, "Curated LLM: Synergy of LLMs and data curation for tabular augmentation in low-data regimes," in *Proceedings of the 41st International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 235, 2024, pp. 44 060–44 092.

[6] M. Jiang, K. Chen, Y. Wang, Y. Zhao, Z. Dai, Y. Liu, Z. Li, Q. Zhang, H. Nie, H. Zhu, S. Liu, G. Ye, and H. Chai, "Limited reference, reliable generation: A two-component framework for tabular data generation in low-data regimes," arXiv preprint arXiv:2509.09960, 2025.

[7] C. Zhang, R. F. Lin, R. Bao, and S. Huang, "Team, then trim: An assembly-line LLM framework for high-quality tabular data generation," arXiv preprint arXiv:2602.04785, 2026.

[8] Y. Yu, D. Liu, S. Wang, W. Zhao, E. Jiang, C. Liu, J. Yu, H. Pan, R. Borovica-Gajic, and B. Lengerich, "RUBRIC: Realism–utility balanced ranking for imbalanced classification," arXiv preprint arXiv:2607.09816, 2026.

[9] A. Alaa, B. V. Breugel, E. S. Saveliev, and M. van der Schaar, "How faithful is your synthetic data? sample-level metrics for evaluating and auditing generative models," in *Proceedings of the 39th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 162. PMLR, 2022, pp. 290–306. [Online]. Available: https://proceedings.mlr.press/v162/alaa22a.html

[10] M. F. Naeem, S. J. Oh, Y. Uh, Y. Choi, and J. Yoo, "Reliable fidelity and diversity metrics for generative models," in *Proceedings of the 37th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 119, 2020, pp. 7176–7185.

[11] G. L. Nemhauser, L. A. Wolsey, and M. L. Fisher, "An analysis of approximations for maximizing submodular set functions—i," *Mathematical Programming*, vol. 14, pp. 265–294, 1978. [Online]. Available: https://link.springer.com/article/10.1007/BF01588971

[12] O. Sener and S. Savarese, "Active learning for convolutional neural networks: A core-set approach," in *International Conference on Learning Representations*, 2018. [Online]. Available: https://openreview.net/forum?id=H1aIuk-RW

[13] S. Tavakkol, M. Springer, M. Bateni, N. Bulut, V. Cohen-Addad, and M. Hajiaghayi, "Less is more: Adaptive coverage for synthetic training data," arXiv preprint arXiv:2504.14508, 2025.

[14] W. M. Stevenson, A. Gerdes, L. Galke Poech, and A. D. Lautrup, "Curating the collapse: How sample-level auditing accelerates model collapse in synthesis of tabular data," in *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, vol. 9, no. 4, 2026, pp. 2450–2461.

[15] E. Breck, N. Polyzotis, S. Roy, S. E. Whang, and M. Zinkevich, "Data validation for machine learning," in *Proceedings of Machine Learning and Systems (MLSys)*, 2019.

[16] M. Stoian, S. Dyrmishi, M. Cordy, T. Lukasiewicz, and E. Giunchiglia, "How realistic is your synthetic data? constraining deep generative models for tabular data," in *The Twelfth International Conference on Learning Representations*, 2024. [Online]. Available: https://proceedings.iclr.cc/paper_files/paper/2024/hash/887932131fddf943e8fe3310b62c0147-Abstract-Conference.html

[17] J. Zhao, M. Guan, and D. Liu, "Constraint-aware synthetic tabular data generation via inter-column constraint discovery with LLM agents," arXiv preprint arXiv:2608.15109, 2026.

[18] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "SMOTE: Synthetic minority over-sampling technique," *Journal of Artificial Intelligence Research*, vol. 16, pp. 321–357, 2002. [Online]. Available: https://www.jair.org/index.php/jair/article/view/10302

[19] G. E. A. P. A. Batista, R. C. Prati, and M. C. Monard, "A study of the behavior of several methods for balancing machine learning training data," *ACM SIGKDD Explorations Newsletter*, vol. 6, no. 1, pp. 20–29, 2004.

[20] J. A. Sáez, J. Luengo, J. Stefanowski, and F. Herrera, "SMOTE-IPF: Addressing the noisy and borderline examples problem in imbalanced classification by a re-sampling method with filtering," *Information Sciences*, vol. 291, pp. 184–203, 2015.

[21] G. Lemaître, F. Nogueira, and C. K. Aridas, "Imbalanced-learn: A python toolbox to tackle the curse of imbalanced datasets in machine learning," *Journal of Machine Learning Research*, vol. 18, no. 17, pp. 1–5, 2017. [Online]. Available: https://www.jmlr.org/papers/v18/16-365.html

[22] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in *Proceedings of the 34th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 70. PMLR, 2017, pp. 1321–1330. [Online]. Available: https://proceedings.mlr.press/v70/guo17a.html

[23] B. Efron, "Bootstrap methods: Another look at the jackknife," *The Annals of Statistics*, vol. 7, no. 1, pp. 1–26, 1979. [Online]. Available: https://doi.org/10.1214/aos/1176344552

[24] L. D. Brown, T. T. Cai, and A. DasGupta, "Interval estimation for a binomial proportion," *Statistical Science*, vol. 16, no. 2, pp. 101–133, 2001. [Online]. Available: https://doi.org/10.1214/ss/1009213286

[25] L. Long, R. Wang, R. Xiao, J. Zhao, X. Ding, G. Chen, and H. Wang, "On LLMs-driven synthetic data generation, curation, and evaluation: A survey," in *Findings of the Association for Computational Linguistics: ACL 2024*. Association for Computational Linguistics, 2024, pp. 11 065–11 082. [Online]. Available: https://aclanthology.org/2024.findings-acl.658/

[26] L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. P. Xing, H. Zhang, J. E. Gonzalez, and I. Stoica, "Judging LLM-as-a-judge with MT-bench and chatbot arena," in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets_and_Benchmarks.html

[27] H. Han, W.-Y. Wang, and B.-H. Mao, "Borderline-SMOTE: A new over-sampling method in imbalanced data sets learning," in *Advances in Intelligent Computing*, ser. Lecture Notes in Computer Science. Berlin, Heidelberg: Springer, 2005, pp. 878–887.

[28] H. He, Y. Bai, E. A. Garcia, and S. Li, "ADASYN: Adaptive synthetic sampling approach for imbalanced learning," in *2008 IEEE International*

Joint Conference on Neural Networks (IEEE World Congress on Computational Intelligence). IEEE, 2008, pp. 1322–1328.

[29] A. Newaz and F. S. Haq, "A novel hybrid sampling framework for imbalanced learning," arXiv preprint arXiv:2208.09619, 2022.

APPENDIX A
CLASS DENOMINATORS AND CONFUSION COUNTS

APPENDIX B
PAIRED REPAIR INTERVALS

All primary pairs for both classifiers and available regimes are in `paired-differences.json`. Undefined counts remain per endpoint. `confusions.csv` retains confusion counts and Wilson recall bounds for every successful result.

APPENDIX C
EVIDENCE MAP AND REPRODUCTION

The protocol is `docs/empirical-v2/protocol.md`; machine settings are in `configs/empirical/protocol-v1.json`. Canonical evidence is `artifacts/reports/empirical-v2/run-v2`. The report includes consolidated ablations, split-wise paired differences and confusions. A development run is explicitly superseded for an interval-metadata naming defect; its scores never selected configurations.

With this revision's `src` on PYTHONPATH, run `scripts/run_empirical_study.py` using a fresh output directory and frozen checkout as `--source-root`. `scripts/report_empirical_study.py` reads saved evidence without refitting. Exact commands, pinned dependencies and verification are in `docs/empirical-v2/handoff.md`.

The manifest binds revisions, code hashes, protocol identity, dependencies, runtime and output hashes. Population records retain exact TRAIN/TEST identities, source/dataset fingerprints, class counts and overlap diagnostics. Generator files retain fitted TRAIN identities, scaler parameters, seeds and generated payloads. Existing M2/M7 use fresh split-specific populations. Predictions preserve actual/predicted classes, positive scores and row identity; compressed index arrays preserve paired resamples.

The cell ledger `notes/table-evidence.json` links rendered values to input fields, row fingerprints and aggregation rules. Original M2, M4 and M6/M7 sensitivities remain unchanged. Individual seeds, every split, both classifiers, unavailable cases and budget checks accompany the paper. Full regression/static checks, replay and historical integrity are reported separately; replay is not another independent split.

TABLE XI
EXPLORATORY ADDENDUM, DECLARED AFTER THE MAIN STUDY. AVERAGE RANKS (1 = BEST) OF MEAN F1 AND AP ACROSS DATASETS, WITH EXPLORATORY FRIEDMAN TESTS, AND WILCOXON SIGNED-RANK TESTS OF QUALITY-COVERAGE AGAINST EACH METHOD. NO MULTIPLICITY ADJUSTMENT OR SIGNIFICANCE CLAIM.

(a) Curators, 8 complete datasets

Method	LR F1	LR AP	RF F1	RF AP
Schema rand.	5.12	4.81	4.81	5.00
Adm. rand.	5.12	5.12	4.50	5.12
Source order	4.38	5.38	4.00	4.62
Farthest-first	4.69	3.50	3.62	4.25
Cov.-greedy	3.81	5.00	3.88	5.88
QC (ours)	3.75	4.88	4.06	4.25
CLLM-style†	5.12	2.44	5.88	4.00
Disc.-realism†	4.00	4.88	5.25	2.88
Friedman p	0.654	0.207	0.525	0.387

(b) All methods, 5 complete datasets

Method	LR F1	LR AP	RF F1	RF AP
QC (ours)	6.10	9.40	7.60	8.60
Adm. rand.	10.30	9.80	10.80	9.00
Farthest-first	7.30	7.60	6.60	6.80
CLLM-style†	8.90	6.80	11.20	7.80
Disc.-realism†	5.70	7.60	9.80	4.40
Real only	7.30	7.40	12.50	9.00
ROS+b	9.80	9.20	10.00	8.60
SMOTE(NC)+b	8.30	7.00	10.70	10.20
SMOTE-ENN full	8.50	13.20	7.20	10.40
SMOTE-ENN +b	9.70	7.60	13.00	12.00
SMOTE-Tomek full	7.20	10.20	3.70	7.80
SMOTE-Tomek +b	8.10	5.40	9.80	7.00
B-SMOTE full	10.00	9.00	6.00	7.60
B-SMOTE +b	10.20	5.60	6.50	8.80
ADASYN full	10.80	9.90	4.50	8.20
ADASYN +b	7.80	10.30	6.10	9.80
Friedman p	0.904	0.578	0.031	0.826

(c) Wilcoxon, QC minus method: datasets QC better/worse, p

Method	LR F1	LR AP	RF F1	RF AP
Schema rand.	4/1, 0.12	4/4, 0.64	4/2, 0.31	5/3, 0.95
Adm. rand.	4/1, 0.19	3/4, 0.58	6/2, 0.31	5/3, 1.00
Source order	4/1, 0.44	4/3, 0.81	3/4, 0.58	4/4, 0.84
Farthest-first	4/1, 0.62	3/4, 0.22	3/3, 0.84	5/3, 0.74
Cov.-greedy	1/2, 1.00	3/4, 0.58	2/4, 1.00	5/3, 0.95
CLLM-style†	4/2, 1.00	2/6, 0.08	5/2, 0.38	3/5, 0.84
Disc.-realism†	2/3, 0.81	4/4, 0.46	4/3, 0.94	3/5, 0.38
Real only	5/1, 0.44	3/5, 0.46	5/2, 0.08	5/3, 0.46
CW-LR	6/2, 0.31	3/5, 0.74	–	–
ROS+b	5/1, 0.06	6/2, 0.38	5/1, 0.16	5/3, 0.38
SMOTE(NC)+b	5/0, 0.06	3/5, 0.64	4/2, 0.56	6/2, 0.31
SMOTE-ENN full	4/2, 0.44	5/1, 0.09	3/3, 0.69	4/2, 0.31
SMOTE-ENN +b	3/1, 0.62	3/3, 1.00	5/1, 0.16	5/1, 0.31
SMOTE-Tomek full	4/2, 0.44	4/2, 0.31	2/4, 0.31	3/3, 0.84
SMOTE-Tomek +b	2/2, 1.00	2/4, 0.16	2/3, 0.81	4/2, 0.56
B-SMOTE full	4/2, 0.44	3/3, 0.56	3/3, 1.00	3/3, 0.69
B-SMOTE +b	4/2, 0.56	2/4, 0.44	2/4, 1.00	3/3, 0.69
ADASYN full	5/1, 0.16	4/2, 0.22	2/4, 0.56	3/3, 0.69
ADASYN +b	3/2, 0.81	3/2, 1.00	2/3, 1.00	3/2, 0.62

TABLE XII

HISTORICAL PRIMARY PREDICTIONS: CLASS DENOMINATORS AND CONFUSION COUNTS. Q AND Q REPAIR USE PURE TSTR; REAL USES TRTR.

Dataset / method	Model	n_+	n_-	TP	FP	TN	FN
Abalone19 / Real	LR	6	828	0	0	828	6
Abalone19 / Real	RF	6	828	0	0	828	6
Abalone19 / Q	LR	6	828	6	373	455	0
Abalone19 / Q	RF	6	828	5	319	509	1
Abalone19 / Q repair	LR	6	828	6	373	455	0
Abalone19 / Q repair	RF	6	828	5	319	509	1
Ecoli4 / Real	LR	4	63	4	0	63	0
Ecoli4 / Real	RF	4	63	2	0	63	2
Ecoli4 / Q	LR	4	63	4	31	32	0
Ecoli4 / Q	RF	4	63	4	19	44	0
Ecoli4 / Q repair	LR	4	63	4	31	32	0
Ecoli4 / Q repair	RF	4	63	4	19	44	0
page-blocks0 / Real	LR	112	983	69	12	971	43
page-blocks0 / Real	RF	112	983	93	9	974	19
page-blocks0 / Q	LR	112	983	75	149	834	37
page-blocks0 / Q	RF	112	983	85	300	683	27
page-blocks0 / Q repair	LR	112	983	78	266	717	34
page-blocks0 / Q repair	RF	112	983	84	336	647	28

TABLE XIII

REPAIR-POOL MINUS ORIGINAL Q, LOGISTIC PURE TSTR: CONDITIONAL PAIRED DIFFERENCE INTERVALS. THESE MEASURE POOL EXPANSION AND RESELECTION TOGETHER.

Dataset	Metric	Lower	Upper	Valid	Undefined
Abalone19	f1	0.000	0.000	2000	0
Abalone19	average_precision	0.000	0.000	2000	0
Abalone19	balanced_accuracy	0.000	0.000	2000	0
Abalone19	mcc	0.000	0.000	2000	0
Ecoli4	f1	0.000	0.000	2000	0
Ecoli4	average_precision	0.000	0.000	2000	0
Ecoli4	balanced_accuracy	0.000	0.000	2000	0
Ecoli4	mcc	0.000	0.000	2000	0
page-blocks0	f1	-0.135	-0.074	2000	0
page-blocks0	average_precision	-0.007	0.049	2000	0
page-blocks0	balanced_accuracy	-0.067	-0.024	2000	0
page-blocks0	mcc	-0.146	-0.075	2000	0