ASTRAQUANTUM TECH

SUMMER OF CYBERSECURITY 2026

WEEK 10 PRACTICAL ASSIGNMENT

AI SECURITY & LLM APPLICATION RISKS

Prompt Injection • Privacy • AI Threat Modelling • Defences

LEARN TO TEST AI SYSTEMS RESPONSIBLY — THEN EXPLAIN HOW TO SECURE THEM

Student Name: Mariam Fatima

Student ID: AQT-1372

Date: 18 October 2026

1. Executive Summary

This report presents an introductory AI security assessment completed as part of Week 10 of the Summer of Cybersecurity 2026 programme. Two online learning activities were completed: TryHackMe — The Building Blocks of AI, including the NEURON-1 challenge, and GenAI Security Lab — Prompt Injection 101.

The activities covered fundamental AI concepts, neural networks, prompt injection, and sensitive information disclosure. The hands-on prompt injection exercise demonstrated how a simulated translation assistant could disclose a confidential access code when prompted to reproduce its instructions. The lab's defensive phase demonstrated a mitigation that kept the secret outside the model's context and blocked the tested exploit during verification.

A threat model was also developed for the hypothetical Campus Helper AI scenario. The identified risks include direct prompt injection, indirect prompt injection, sensitive information disclosure, excessive agency, improper output handling, and unbounded consumption.

The report recommends layered security controls, including least privilege, application-enforced access control, human approval for sensitive actions, output validation, log protection, and resource limits. The Campus Helper AI analysis is scenario-based; no real university system was tested.

2. Scope and Tools

2.1 Scope

The assessment covered two authorized online training activities and a written threat-model exercise. The purpose was to understand AI fundamentals, explore prompt injection in a training environment, evaluate the lab's defensive control, and recommend safeguards for a hypothetical university AI application.

No real AI product, university service, or private system was tested.

2.2 Tools and Training Environments

Task A: TryHackMe — The Building Blocks of AI

This learning room covered machine learning, neural networks, deep learning, and the NEURON-1 interactive classification challenge.

Task B: GenAI Security Lab — Prompt Injection 101

This hands-on exercise used the simulated LinguaBridge translation assistant to demonstrate prompt injection, apply a defensive control, and verify the result.

Task C: Campus Helper AI Threat Model

A written analysis of the fictional scenario provided in the assignment.

Task D: Defence Recommendations

A written set of recommended security controls and corresponding OWASP mappings.

Tools used included a web browser and Microsoft Word for report preparation and screenshot insertion.

3. Task A — The Building Blocks of AI

The TryHackMe learning room introduced the main concepts behind artificial intelligence and machine learning.

Supervised learning uses labelled data to learn input-output relationships. Unsupervised learning identifies patterns in unlabelled data. Semi-supervised learning combines a small amount of labelled data with a larger amount of unlabelled data. Reinforcement learning allows an agent to learn through rewards and penalties received after taking actions.

The neural network material explained how the input layer receives raw data, hidden layers identify features and patterns, and the output layer produces a classification. In the NEURON-1 challenge, I worked through an interactive neural network exercise by supplying input, assigning feature-detection roles to hidden nodes, and selecting the final classification.

This activity helped me understand how AI systems process information and why their inputs, decisions, and outputs must be considered when assessing security.




Figure 1. Evidence of completion of the TryHackMe — The Building Blocks of AI learning room.




Figure 2. NEURON-1 chatbot interaction showing hidden-layer analysis and the final network classification.




Figure 3. NEURON-1 neural network visualiser showing the completed classification challenge.

4. Task B — Prompt Injection 101

4.1 Objective

The objective of this activity was to understand how prompt injection can cause an AI assistant to disclose confidential information stored in its instructions, and to observe a defensive mitigation in an authorized training environment.

4.2 Attack Phase

The training target, LinguaBridge, was presented as a translation assistant containing a confidential access code in its model instructions. Direct requests for the code were refused. However, a request to translate the complete instructions into Spanish caused the target to reproduce the protected information.

The lab confirmed the exploit as successful. This demonstrated that a rule instructing a model not to reveal a secret is not a reliable security boundary when the secret remains available in the model's context.

4.3 Defence and Verification

During the defence phase, I selected the control described as “Keep the Secret Out of the Model.” The defensive approach stored the secret outside the model's instructions and used a separate authenticated service to retrieve it when authorized.

During verification, the lab reported that the original exploit was blocked and displayed the result “Retest held.”

The exercise demonstrated the importance of protecting secrets through application-level authorization and secure storage instead of relying only on model instructions.




Figure 4. The authorized training environment confirmed successful prompt injection against LinguaBridge.




Figure 5. The lab's verification result showed that the tested exploit was blocked after applying the defensive control.

5. Task C — Mini AI Threat-Modelling Scenario

5.1 Scenario

Campus Helper AI is a hypothetical university assistant that answers student questions using internal policy documents. Students can ask questions and upload documents. The AI can search a shared document store and create draft support tickets. The application also stores conversation logs that may contain student details.

The system should answer questions without disclosing private records, following conflicting instructions embedded in uploaded documents, or creating tickets without appropriate checks.

5.2 Threat Model Worksheet

Threat	How it could occur	Potential impact	Risk level	Recommended control
Direct prompt injection	A student submits instructions intended to override the AI's intended role.	The assistant may ignore restrictions or attempt to provide unauthorized information.	High	Treat prompts as untrusted input and enforce security rules outside the model.
Indirect prompt injection	An uploaded document contains malicious instructions that conflict with the assistant's role.	The AI may follow untrusted instructions or generate misleading responses.	High	Treat uploaded documents as untrusted data and prevent them from overriding privileged instructions.
Sensitive information disclosure	Responses or conversation logs expose private student details.	Privacy violations and unauthorized disclosure of student information.	High	Enforce access control, minimize sensitive data, redact logs, and restrict log access.
Excessive agency	The AI creates or modifies a ticket without sufficient permission checks.	Unauthorized or incorrect records and actions.	High	Apply least privilege, validate requested actions, and require human approval where appropriate.
Improper output handling	Generated text is used by another application component without validation.	Unsafe or malformed content may be processed downstream.	Medium	Validate and constrain generated outputs before downstream use.
Unbounded consumption	Repeated or oversized requests consume excessive resources.	Increased costs, degraded performance, or service disruption.	Medium	Apply rate limits, request-size limits, cost limits, and monitoring.

Risk levels are preliminary assessments based on the hypothetical scenario and are not results of testing a deployed system.

5.3 Threat Model Conclusion

The main concerns are unauthorized disclosure of student information, prompt injection through user messages or uploaded documents, and actions performed without appropriate authorization. These risks can affect confidentiality, integrity, and availability.

Campus Helper AI should use layered controls. The application must enforce access permissions independently of the model, treat uploaded content as untrusted, restrict tool permissions, and validate actions before execution.

6. Findings — AI-01 Template

Finding AI-01

Finding ID: AI-01

Title / Risk: Prompt Injection Leading to Sensitive Information Disclosure

Affected component or trust boundary: LinguaBridge's model instructions and the boundary between user-supplied messages and confidential information.

Evidence or scenario detail: In the authorized Prompt Injection 101 lab, asking the assistant to translate its complete instructions into Spanish resulted in the lab confirming the exploit. After the defensive control was applied, the verification phase reported that the exploit was blocked.

Description — what could go wrong?

A confidential access code stored in model instructions could be reproduced when a user manipulates the assistant into quoting, translating, or summarizing those instructions. A rule refusing direct requests for a secret does not reliably prevent indirect disclosure.

Potential impact: Confidential information could be exposed. If the code grants access to a protected resource, disclosure could enable unauthorized access.

Severity: High in the training scenario because the protected value was disclosed. The severity in a real deployment would depend on the secret's sensitivity and privileges.

Recommended controls:

Keep confidential values out of model instructions and conversation context.

Store secrets in a protected secret-management service.

Enforce authorization through application code.

Provide only the minimum information required for an authorized task.

Test for prompt injection and sensitive information disclosure.

OWASP LLM Top 10 category: LLM01: Prompt Injection. LLM02: Sensitive Information Disclosure is also relevant to the disclosure impact.

Finding AI-02

Finding ID: AI-02

Title / Risk: Potential Unauthorized Disclosure of Student Information

Affected component or trust boundary: Campus Helper AI's shared document store, retrieval process, and conversation logs.

Evidence or scenario detail: The assignment scenario states that the assistant searches internal policy documents and stores conversation logs that may contain student details. These features create potential risks if appropriate access restrictions are not enforced.

Description — what could go wrong?

If the application retrieves records without checking the requesting user's permissions, or allows unauthorized access to logs containing sensitive details, the assistant could expose information that a user is not permitted to see.

Potential impact: Privacy violations, unauthorized disclosure of student information, loss of trust, and possible institutional or regulatory consequences.

Severity: High as a preliminary scenario-based assessment because student information may be sensitive. Actual severity would depend on the data involved and the controls in place.

Recommended controls:

Authenticate users and enforce authorization before retrieving records.

Minimize sensitive information in prompts and logs.

Redact unnecessary private details from troubleshooting logs.

Restrict log access and apply appropriate retention policies.

Monitor access to sensitive resources.

OWASP LLM Top 10 category: LLM02: Sensitive Information Disclosure.

Finding AI-01 is based on the completed training lab. Finding AI-02 is based on the Campus Helper AI scenario and was not tested against a real application.

7. Task D — Defence Recommendations

The following controls are recommended for Campus Helper AI.

7.1 Least Privilege for Tools and Data Access

The AI should receive only the permissions required to complete its intended task. Read-only access should be the default, while sensitive data and ticket-management functions should be restricted.

7.2 Human Approval for Sensitive Actions

Creating, modifying, or sending records should require appropriate validation and human approval where necessary. This reduces the risk of unintended actions caused by malicious instructions or incorrect generated responses.

7.3 Access Control Outside the Model

Normal application code should verify a user's identity and permissions before retrieving private records or performing an action. Security should not depend only on the model following its system prompt.

7.4 Treat Prompts and Uploaded Documents as Untrusted

User messages and uploaded documents must not be allowed to override privileged application instructions. The application should handle retrieved content as untrusted data and use safeguards against indirect prompt injection.

7.5 Validate AI-Generated Outputs

Generated text should be checked against expected formats, allowed values, and application rules before being passed to another system or used to prepare a support ticket.

7.6 Protect Conversation Logs

Collect only necessary troubleshooting information, redact sensitive details when appropriate, restrict log access to authorized personnel, and apply suitable retention and monitoring policies.

7.7 Apply Usage Limits and Monitoring

Rate limits, request-size limits, and cost limits can reduce excessive consumption and service disruption. Monitoring should identify unusual usage patterns and suspicious tool calls.

7.8 OWASP Mapping

Identified risk	OWASP LLM Top 10 category	Relevant defensive control
Direct prompt injection	LLM01: Prompt Injection	Treat prompts as untrusted and enforce application-level controls.
Indirect prompt injection	LLM01: Prompt Injection	Treat uploaded documents and retrieved content as untrusted.
Sensitive information disclosure	LLM02: Sensitive Information Disclosure	Enforce authorization, minimize data, and redact logs.
Excessive agency	LLM06: Excessive Agency	Apply least privilege and human approval.
Improper output handling	LLM05: Improper Output Handling	Validate and constrain outputs before downstream use.
Unbounded consumption	LLM10: Unbounded Consumption	Apply rate, size, and cost limits with monitoring.
System prompt leakage	LLM07: System Prompt Leakage	Do not store secrets in system prompts; enforce access control outside the model.

These mappings use the OWASP Top 10 for LLM and GenAI Applications (2025). More than one category may be relevant to a finding, depending on the underlying cause and impact.

8. Evidence Register

The following screenshots document the two completed online activities. Each screenshot must be an original capture of my own work.

Figure 1: TryHackMe — The Building Blocks of AI completion page.

Figure 2: NEURON-1 challenge showing the completed classification activity.

Figure 3: Prompt Injection 101 — successful exploit confirmation.

Figure 4: Prompt Injection 101 — defensive verification showing “Retest held.”

At least two screenshots are included for each completed online activity. At least one screenshot per platform must show the computer's date and time. If the existing screenshots do not show this information, an additional original screenshot must be included.

Screenshots must not expose passwords, personal information, confidential values, or private records. No screenshots, flags, or text from walkthroughs or other students should be used.

9. Assessment Questions

Question 1. What is the difference between an AI model and an AI application or agent?

An AI model is the trained component that processes input and produces predictions or generated content. An AI application combines a model with software, data sources, user interfaces, and security controls. An AI agent may also use tools and perform actions toward a goal. Security must therefore cover both the model and the surrounding application.

Question 2. What is prompt injection? How can an uploaded document introduce indirect prompt injection?

Prompt injection occurs when input attempts to manipulate an AI into ignoring its intended instructions or performing an unintended task. Indirect prompt injection occurs when malicious instructions are embedded in content such as an uploaded document. If the model treats that content as trusted instructions rather than untrusted data, it may follow those instructions.

Question 3. Why should a system prompt not be treated as the only security control for confidential data?

A system prompt is part of the model's context and cannot reliably enforce confidentiality. The model may reproduce information through an unexpected request or prompt injection. Confidential data should instead be protected through application-enforced authorization, secure secret storage, data minimization, and restricted access.

Question 4. What does excessive agency mean, and why should AI tools follow least privilege?

Excessive agency occurs when an AI system has more permission or autonomy than necessary for its intended task. Least privilege limits its tools, data, and actions to the minimum required. This reduces the potential impact of prompt injection, incorrect decisions, and unauthorized operations.

Question 5. Why should generated output be validated before it is used by another application?

AI-generated content may be incorrect, malformed, misleading, or unsafe for its destination. Validation checks that the output meets expected formats, permitted values, and application rules. This helps prevent unsafe downstream processing and unauthorized actions.

Question 6. Name two ways to protect sensitive information in AI prompts, outputs, and logs.

First, minimize sensitive information in prompts and model context, and enforce authorization before retrieving confidential records. Second, redact sensitive details from logs when appropriate and restrict log access to authorized personnel. Secrets should be stored in protected services rather than embedded in prompts.

Question 7. Which OWASP LLM Top 10 category best matches one risk in your threat model, and why?

LLM01: Prompt Injection matches the direct and indirect prompt-injection risks in the Campus Helper AI threat model. User messages or uploaded documents may attempt to override the assistant's intended behaviour. Treating these inputs as untrusted and enforcing security controls outside the model helps reduce the risk.

10. Conclusion

This assessment improved my understanding of AI fundamentals and the security risks that arise when language models interact with users, documents, confidential information, and external tools.

The TryHackMe learning room introduced machine learning and neural network concepts. The Prompt Injection 101 exercise demonstrated that confidential information stored in model instructions may be

disclosed through an instruction-reproduction request. The defensive verification highlighted the importance of keeping secrets outside the model's context and using a separate authenticated service.

The Campus Helper AI threat model identified potential risks involving prompt injection, sensitive information disclosure, excessive agency, output handling, and unbounded consumption. The recommended controls demonstrate why AI security requires layered technical safeguards rather than relying only on the model's instructions.

11. References

TryHackMe. *The Building Blocks of AI*. Training room completed as part of Week 10. https://tryhackme.com/
Exact room URL: [Insert the room URL used during the activity.]

GenAI Security Lab. *Prompt Injection 101*. https://genaisecuritylab.com/learn-ai-security

OWASP. *Top 10 for LLM and GenAI Applications (2025)*. https://genai.owasp.org/llm-top-10/

MITRE. *Adversarial Threat Landscape for Artificial-Intelligence Systems (ATLAS)*. https://atlas.mitre.org/