PASSANGER SAFTEY AND CONVENIENCE TRAIN ACCIDENT PREVENTION PROJECT

CI:- KRISHAN KUMAR

AJAY SAINI

INDEX

S.NO.	TOPIC	PG.NO.
1	Project Members	3
2	Introduction	4
3	Parts	6
4	Single channel relay	11
5	Dual channel relay	13
6	Battery	15
7	Infra red (IR) sensor	17
8	Male to Male jumper wires	20
9	Female to female jumper wires	22
10	Dual shaft gear motor	24
11	Buzzer	26
12	Circuits	28
13	Conclusion	31

PROJECT MEMBERS



Ayush Raj



Kunal



Neeraj Singh



Amit Kumar



Saalim

INTRODUCTION

The **Passenger Safety and Convenience Train Accident Prevention Project** is a safety system designed to prevent accidents at railway crossings by automatically detecting and responding to train presence. The system typically consists of:
a
1. Sensors (e.g., IR sensors) to detect trains approaching the crossing.
2. Control systems to analyze sensor data and activate warnings or barriers.
3. Warning devices (e.g., sirens, gates) to alert pedestrians and vehicles of an approaching train.
4. Barrier systems (e.g., bridge) to physically block access to the crossing.


The system's goals are to:-

- Prevent vehicles and pedestrians from entering the crossing when a train is approaching.
- Minimize the risk of accidents and fatalities.
- Automate the crossing management process.


Some advanced features of **Passenger Safety and Convenience Train Accident Prevention Project** include:-

- Real-time monitoring and control.
- Integration with train scheduling and signaling systems.
- Video analytics and object detection.
- Emergency response systems.


PARTS



Single channel relay




Dual channel relay



Battery

Infra Red (IR) Sensor





Male to Male jumper wires



Female to Female jumper wires



Dual shaft gear motor

Buzzer



Single channel relay :-

A single-channel relay is an electrically operated switch that allows a low-power signal to control a higher-power circuit. It has a single input (or control) circuit and a single output (or load) circuit.


The relay consists of:
1. Electromagnet (coil)
2. Switch (contact)
3. Output circuit (load)

When a voltage is applied to the input circuit:
1. The electromagnet is energized, attracting the switch.
2. The switch closes, connecting the output circuit to the power source.
3. The load is energized.

When the input voltage is removed:
1. The electromagnet de-energizes.
2. The switch returns to its open state.
3. The output circuit is disconnected from the power source.

Single-channel relays are commonly used for:-
- Power switching
- Motor control
- Lighting control
- Alarm systems
- Automation systems

They offer isolation between the control circuit and the load, making them useful for controlling high-voltage or high-current devices with a low-voltage signal.



Dual channel relay :-

A dual-channel relay is an electrically operated switch that allows a low-power signal to control two separate higher-power circuits. It has two independent input (or control) circuits and two independent output (or load) circuits.


The dual-channel relay consists of:
1. Two electromagnets (coils)
2. Two switches (contacts)
3. Two output circuits (loads)

When a voltage is applied to each input circuit:
1. The corresponding electromagnet is energized, attracting the switch.
2. The switch closes, connecting the output circuit to the power source.
3. The load is energized.

When the input voltage is removed:
1. The electromagnet de-energizes.
2. The switch returns to its open state.
3. The output circuit is disconnected from the power source.

Dual-channel relays are commonly used for:-
- Controlling two separate devices with a single control signal
- Power switching in industrial automation
- Motor control in robotics and CNC machines
- Lighting control in stage lighting and building automation
- Alarm systems and security panels

They offer isolation between the control circuit and the loads, making them useful for controlling high-voltage or high-current devices with a low-voltage signal



Battery:-

A battery is a device that stores electrical energy in the form of chemical energy. It consists of one or more cells that contain a positive electrode (cathode) and a negative electrode (anode) separated by an electrolyte. Batteries can be used to power devices, machines, and vehicles.


Types of batteries:

1. Primary batteries (non-rechargeable):
- Alkaline
- Zinc-carbon
2. Secondary batteries (rechargeable):
- Lead-acid
- Nickel-cadmium (NiCd)
3. Specialized batteries:
- Button cells
- Pencil cells

Battery characteristics:
1. Voltage
2. Cycle life
3. Self-discharge rate
4. Terminal voltage

Applications:
1. Portable devices (smartphones, laptops)
2. 2. Electric vehicles
3. 3. Renewable energy systems
4. 4. Backup power systems (UPS)
5. 5. Industrial power tools
6. 6. Medical devices
7. 7. Consumer electronics

In summary, batteries are an essential part of modern life, powering various devices and applications. Understanding battery types, characteristics, and applications is crucial for selecting the right battery for specific uses.



Infra Red (IR) Sensor:-

An infrared (IR) sensor is an electronic device that detects and measures the intensity of infrared radiation, which is emitted by all objects at temperatures above absolute zero (-273°C). IR sensors are widely used in various applications, including:

1. Object detection and tracking
2. Temperature measurement
3. Motion detection and alarm systems
4. Remote sensing and imaging
5. Spectroscopy and chemical identification
6. Heat and flame detection
7. Medical imaging and diagnostics
8. Automotive applications (e.g., obstacle detection, night vision)
9. Consumer electronics (e.g., remote controls, thermal imaging cameras)

Types of IR sensors:

1. Thermal detectors (e.g., thermopiles, bolometers)2.
2. Photonic detectors (e.g., photodiodes,
1. phototransistors)
2. Pyroelectric detectors
3. Quantum detectors (e.g., quantum well infrared photodetectors)


IR sensors offer various advantages, including:

1. Non-invasive and non-contact measurement
2. High accuracy and sensitivity
3. Fast response time
4. Low power consumption
5. Compact size and light weight

However, IR sensors also have some limitations and challenges, such as:

1. Interference from ambient light and temperature
2. Sensor calibration and drift
3. Limited range and resolution
4. Vulnerability to environmental factors (e.g., humidity, dust)

Overall, IR sensors play a vital role in various applications, offering valuable insights and measurements in fields like object detection, temperature measurement, and medical imaging.


Distance Adjust
IR Receiver
Power LED
Vcc
Gnd
Out
IR Emitter LED
Obstacle LED
MH-B
OUT GND VCC

Male to Male jumper wires:-

A male-to-male (M-M) jumper wire is an electrical wire with a male connector (pin or plug) on both ends, used to connect two male ports or pins together. It is commonly used for:

1. Prototyping and breadboarding
2. Electronic project development
3. Circuit testing and debugging
4. Connecting components or modules
5. Jumpstarting or trouble shooting circuits

Characteristics:
1. Wire material (e.g., copper, aluminum)
2. Wire gauge (thickness)
3. Insulation material (e.g., PVC, Teflon)
4. Connector type (e.g., pin, plug, socket)
5. Length (varies from a few inches to several feet)

Types of male-to-male jumper wires:
1. Solid core
2. Stranded core
3. Flexible (e.g., silicone or rubber insulated)
4. Rigid (e.g., PCB-mounted)
5. Color-coded (for easy identification)

When selecting a male-to-male jumper wire, consider factors like wire gauge, insulation, and connector type to ensure compatibility with your project's requirements.



Female to Female jumper wires:-

Female-to-female jumper wires are electrical wires with female connectors on both ends, used for:

- Connecting female header pins of Arduino or development boards to other boards
- Prototyping and breadboarding
- Interconnecting components of a breadboard or test circuit without soldering

These wires offer the following features :-

- No soldering required
- Reusable
- Inexpensive
- Easy to use



Dual shaft gear motor:-

Here are some details about dual shaft gear motors:

- Dual shaft gear motors are useful in robotics applications
- Shaft on both sides allows the user to use a wheel and an encoder simultaneously
- They can operate within a voltage range of 3V to 9V
- They have a torque of 0.8 Kg/cm with an RPM of 100
- Operating voltage: 3-12V
- Shaft length: 8.5 mm
- Shaft diameter: 5.5 mm
- No load current: 40-180 mA
- Rated speed after reduction: 100 RPM
- Rated torque: 0.35 Kg-Cm
- Weight: 30 g
- Dimensions: 70x35x22 mm
- Gearbox shape: Straight

Applications: robotics, automation, vehicles, toys and different gear movement related operations



Buzzer:-

A buzzer is an electronic device that produces a sound or alert when an electric current passes through it. It's commonly used in various applications, including:

1. Alarm systems
2. Timers and clocks
3. Warning devices (e.g., fire alarms, security systems)
4. Industrial control systems
5. Medical devices (e.g., heart rate monitors, ultrasound machines)
6. Consumer electronics (e.g., doorbells, microwaves)
7. Automotive systems (e.g., reversing sensors, seatbelt reminders)
8. Toys and games

Types of buzzers:

1. Piezoelectric buzzer (uses a piezoelectric element to generate sound)
2. 2. Electromagnetic buzzer (uses a coil and magnet to produce sound)
3. Ceramic buzzer (uses a ceramic element to generate sound)
4. Active buzzer (has a built-in oscillating circuit to produce sound)
5. Passive buzzer (requires an external oscillating circuit to produce sound)


Buzzer characteristics:


1. Operating voltage
2. Frequency (pitch)
3. Sound pressure level (loudness)
4. Current consumption
5. Size and shape
6. Material (e.g., plastic, metal)

When selecting a buzzer, consider factors like operating voltage, frequency, and sound compatibility with your projec



Circuit:-


10A 250VAC 10A
125VAC
10A 30VDC 10A
28VDC
10A 250VAC 10A
125VAC
10A 30VDC 10A
28VDC
2 Relay Module
D2
DS2
D1
DS1
GND IN1 IN2 VCC
JD-VCC VCC GND


DO GND VCC
TONGLING
12VDC
CQC
NO
COM
NO

Conclusion:-

The **Passenger Safety and Convenience Train Accident Prevention Project** is a vital safety feature designed to prevent accidents and ensure smooth traffic flow at railway crossings. The system's key components, including sensors, control systems, warning devices, and barrier systems, work together to detect trains and alert pedestrians and vehicles. The system's benefits include:

1. Enhanced safety: Reduced risk of accidents and fatalities.
2. Increased efficiency: Automated management of railway crossings.
3. Improved traffic flow: Minimized congestion and wait times.
4. Reduced maintenance: Automated systems require less manual intervention.
5. Cost-effective: Long-term savings on maintenance and accident reduction.

In conclusion, the **Passenger Safety and Convenience Train Accident Prevention Project** is a crucial innovation in railway safety, ensuring the protection of lives and promoting efficient traffic management. Its implementation is essential for modern railway systems, prioritizing safety and efficiency.