SPESIFIKASI - FREEGO STANDARD



Tipe Mesin Air Cooled 4-Stroke, SOHC

Susunan Silinder Silinder Tunggal 52,4 x 57,9 mm Diameter x Langkah :

9,5:1 Perbandingan Kompresi : **Volume Silinder** 125 cc

7,0 kW / 8000 rpm
9,5 Nm/ 5500 rpm
Electric Starter
Wet Sump
Total = 0,84 L; Berkala = 0,80 L
Fuel Injection
Dry, Centrifugal Automatic Daya Maksimum Torsi Maksimum Sistem Starter

Sistem Pelumasan

Kapasitas Oli Mesin

Sistem Bahan Bakar :

Tipe Kopling :

Tipe Transmisi V-belt Automatic

Rangka Rangka

Tipe Rangka **Underbone** Suspensi Depan **Telescopic Fork** Suspensi Belakang **Unit Swing**

100/90 - 12M/C 59J - Tubeless **Ban Depan** 110/90-12M/C 64L - Tubeless Ban Belakang

Cakram Rem Depan **Tromol** Rem Belakang



1905 x 690 x 1115 mm PxLxT

Jarak Sumbu Roda 1275 mm Tinggi Tempat Duduk 780 mm

101 Kg (FreeGo 125), 102 Kg (FreeGo 125 Connected) **Berat Isi** :

Kapasitas Tangki Bensin Jarak Terendah ke Tanah : 135 mm



Kelistrikan

NGK/ CR6HSA **Tipe Busi**

Sistem Pengapian **TCI**

YTZ4V, GTZ4V, NTZ4V (FreeGo 125), YTZ6V (FreeGo 125 **Battery**

Connected)

Smart Key Sistem (Freego 125 Connected), Anak Sistem Penguncian

Kunci (Freego 125)