## SPESIFIKASI - FREEGO CONNECTED



**Tipe Mesin** Air Cooled 4-Stroke, SOHC

Susunan Silinder Silinder Tunggal Diameter x Langkah 52,4 x 57,9 mm

Perbandingan Kompresi 9.5:1 125 cc **Volume Silinder** 

7,0 kW / 8000 rpm Daya Maksimum 9,5 Nm/ 5500 rpm Torsi Maksimum Sistem Starter **Electric Starter** 

Sistem Pelumasan **Wet Sump** 

Total = 0,84 L; Berkala = 0,80 L Kapasitas Oli Mesin

Sistem Bahan Bakar **Fuel Injection** 

**Dry, Centrifugal Automatic** Tipe Kopling

Tipe Transmisi **V-belt Automatic** 

## Rangka Rangka

Tipe Rangka **Underbone** Suspensi Depan **Telescopic Fork** 

**Unit Swing** Suspensi Belakang

100/90 - 12M/C 59J - Tubeless **Ban Depan** 110/90-12M/C 64L - Tubeless : Ban Belakang

: Cakram Rem Depan **Tromol** Rem Belakang



1905 x 690 x 1115 mm PXLXT

1275 mm Jarak Sumbu Roda Tinggi Tempat Duduk 780 mm

101 Kg (FreeGo 125), 102 Kg (FreeGo 125 Connected) **Berat Isi** :

Kapasitas Tangki Bensin Jarak Terendah ke Tanah : 135 mm



## Kelistrikan

NGK/ CR6HSA **Tipe Busi** 

Sistem Pengapian TCI

YTZ4V, GTZ4V, NTZ4V (FreeGo 125), YTZ6V (FreeGo 125 **Battery** 

Smart Key Sistem (Freego 125 Connected), Anak Sistem Penguncian

Kunci (Freego 125)