

ALKA FOAM

Use for smoke house, oven, conveyors, trays, crates, bottle fillers, and production equipment

Ingredient

Sodium Hydroxide
Sodium Metasilicate
Coco Amine Oxide

PAGE 10



General use instruction:

Foam Cleaning of processing area and equipment:

1. For better results, pre-wash surface with water to remove gross soil.
2. Prepare 1-5% solution of ALKAFOAM. Fill foamer equipment with water $\frac{3}{4}$ full to allow sufficient amount of air. Add approximately 1 – 2 liters of ALKAFOAM.
3. Add compressed air in the foaming equipment. Check pressure gauge if it reaches 20 TO 30 psi before applying solution
4. Open release valve and start foaming making sure that the entire surface is covered with foam.
5. Allow contact time of 2-5 minutes.
6. Rinse thoroughly with water. (Do not allow foam to dry).

*For specific dilution or application, please consult Kalinisan Chemicals representative.

PRODUCT KNOWLEDGE

Benefits

- Effective soil removal properties for smoke house, oven, conveyors, trays, crates, bottle fillers, and production equipment.
- ALKAFOAM can also be used in cleaning heavily soiled floors
- Quickly removes fatty soils and carbon deposits.

Target Market

meat food industries

styxperformakemika.indonetwork.co.id