

IoT-BASED SOIL MOISTURE SENSOR SYSTEM FOR SMART AGRICULTURE

A Project Report

Submitted By

R. MONISHA Register Number: 922525106200

In partial fulfillment for the award of the degree of **BACHELOR OF ENGINEERING
ELECTRONICS AND COMMUNICATION ENGINEERING**

V.S.B. ENGINEERING COLLEGE ANNA UNIVERSITY: CHENNAI 600 025 JULY 2026

BONAFIDE CERTIFICATE

Certified that this project report “**IoT-Based Soil Moisture Sensor System for Smart Agriculture**” is the bonafide work of **R. MONISHA (922525106200)** who carried out the project under my supervision.

SIGNATURE EXTERNAL EXAMINER

ACKNOWLEDGEMENT

First and foremost, I communicate my thanks to my parents for providing me a very nice environment for doing this project. I wish to express my sincere thanks to our founder and chairman **Shri. V.S. BALSAMY, B.Sc., B.L.**, for his endeavor in educating us in this premier institution.

I wish to express my admiration and gratefulness to our Dean **Dr.V.KAVITHA B.E., MCA, ME, PhD**, our respected Principal **Dr.V.NIRMAL KANNAN M.E.,PhD**, and to our Vice Principal **Mr.T.S.KIRUBA SHANKAR, M.E., (PhD)**, for their encouragement and sincere supervision.

I am grateful to our Head of the department **Dr.P.S.GOMATHI, M.E., (PhD)**, and our project coordinator **Mrs.K.KALAICHELVI, M.E.**, Assistant Professor, Department of Electronics and Communication Engineering for their precious support.

I express my gratitude of the staff in charge of our project superintendent, **Mrs.K.KALAICHELVI, M.E.**, Assistant Professor, Department of Electronics and Communication Engineering for her supervision throughout the course of my project.

My genuine thanks to all the teaching staff members of V.S.B Engineering College and my friends for their help in the successful achievement of this project work.

ABSTRACT

The increasing global population and the concurrent decline in natural resources necessitate innovative solutions for sustainable food production. This report presents a comprehensive overview of an **IoT-based Soil Moisture Sensor system**, highlighting its architecture, diverse applications, and inherent challenges. The integration of IoT technologies, including wireless sensor networks, cloud computing, and real-time data analytics, offers a transformative approach to modern irrigation management. By enabling real-time monitoring of soil moisture levels and facilitating automated irrigation, IoT systems significantly enhance water use efficiency and crop productivity. This study explores the foundational components, hardware, and software requirements, and system architectures crucial for deploying effective soil moisture monitoring solutions. Furthermore, it discusses the numerous benefits, such as water conservation and increased crop yields, alongside the challenges related to initial costs, connectivity, and data security. The findings underscore the pivotal role of IoT-based soil moisture sensing in fostering a more sustainable and efficient agricultural sector.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	I
	LIST OF FIGURES	III
	LIST OF ABBREVIATIONS	V
1	INTRODUCTION	1
2	LITERATURE SURVEY	4
3	EXISTING SYSTEM	10
4	PROPOSED SYSTEM	11
5	HARDWARE REQUIREMENTS	22
6	SOFTWARE REQUIREMENTS	34
7	SYSTEM ARCHITECTURE	45
8	RESULTS	54
9	CONCLUSION	55
10	REFERENCES	56

LIST OF FIGURES

FIGURE NO	NAME OF FIGURE	PAGE NO
1.1	IoT Applications for Soil Moisture Monitoring	2
4.1	Block Diagram of Proposed Soil Moisture Sensor System	12
5.1	Arduino UNO Microcontroller	23
5.2	Capacitive Soil Moisture Sensor Module	25
5.3	Submersible Water Pump and Relay Module	27
7.1	Working Principle Flowchart	46
8.1	Real-time Soil Moisture Data Output	54

LIST OF ABBREVIATIONS

- **IoT** - Internet of Things
- **IDE** - Integrated Development Environment
- **GUI** - Graphical User Interface
- **USB** - Universal Serial Bus
- **WSN** - Wireless Sensor Networks
- **PA** - Precision Agriculture
- **AI** - Artificial Intelligence
- **ADC** - Analog to Digital Converter
- **LCD** - Liquid Crystal Display
- **VCC** - Voltage Common Collector
- **TDR** - Time-Domain Reflectometry
- **FDR** - Frequency-Domain Reflectometry
- **LoRaWAN** - Long Range Wide Area Network
- **NB-IoT** - Narrowband Internet of Things

CHAPTER 1: INTRODUCTION

1.1 General

The global agricultural landscape is undergoing a profound transformation driven by the imperative to feed a rapidly expanding world population, projected to reach 10 billion by 2050 [1]. This demographic shift, coupled with the increasing scarcity of natural resources, diminishing arable land, and the unpredictable impacts of climate change, has elevated food security to a critical global concern. Among the critical factors in agriculture, efficient water management stands out as a primary concern, as agriculture accounts for approximately 70% of global freshwater withdrawals [2]. The application of the Internet of Things (IoT) in soil moisture monitoring offers a pivotal solution to optimize water usage and enhance crop productivity. An IoT-based soil moisture sensor system integrates physical sensors with cloud-based platforms to provide real-time data on soil water content, enabling precise irrigation control and contributing significantly to sustainable agriculture.

1.2 Importance of Soil Moisture Monitoring in Agriculture

Traditional irrigation practices often rely on manual observation, fixed schedules, or empirical knowledge, which frequently lead to over-watering or under-watering. These methods are labor-intensive, prone to human error, and result in inefficient resource utilization, particularly concerning water and energy. Over-irrigation can lead to nutrient leaching, root rot, and increased water bills, while under-irrigation causes plant stress, reduced yields, and ultimately crop failure [3]. IoT-enabled soil moisture sensors provide a paradigm shift by offering continuous, real-time data on soil volumetric water content (VWC). This allows farmers to make informed, data-driven decisions, ensuring that crops receive the exact amount of water needed at the right time and in the right quantity, thereby conserving water, reducing operational costs, and improving yields [4].

1.3 Scope of the Report

This report provides a comprehensive examination of IoT-based soil moisture sensor systems. It covers the architectural components, hardware and software requirements, and the benefits and challenges of implementation. The study details how these systems facilitate precision irrigation and contribute to sustainable agricultural practices. Furthermore, it delves into various types of soil moisture sensors, communication protocols, and data analytics techniques essential for developing robust and efficient smart irrigation solutions.

CHAPTER 2: LITERATURE SURVEY

2.1 Evolution of Soil Moisture Sensing Technologies

The journey towards smart irrigation has evolved from simple manual soil checks to advanced electronic sensing. Early methods involved gravimetric measurements, which were accurate but destructive and time-consuming, making them unsuitable for continuous monitoring. The development of tensiometers and resistance-based sensors improved the process by offering in-situ measurements, but they often suffered from calibration issues, limited lifespan, and sensitivity to salinity [5].

Modern soil moisture sensing technologies primarily fall into two categories: **dielectric-based sensors** and **resistive sensors**. Dielectric sensors, such as **Capacitive** and **Frequency-Domain Reflectometry (FDR)**, and **Time-Domain Reflectometry (TDR)** sensors, measure the soil's dielectric constant, which is directly related to its water content. These sensors are generally more accurate, stable, and less affected by soil salinity compared to resistive sensors [6]. Resistive sensors, on the other hand, measure the electrical resistance of the soil, which changes with moisture content. While cost-effective, they are less precise and can degrade over time due to corrosion.

2.2 Role of Wireless Sensor Networks (WSN) in Soil Moisture Monitoring

Wireless Sensor Networks (WSNs) form the backbone of modern soil moisture monitoring systems. These networks consist of spatially distributed autonomous sensors that collect moisture data and transmit it wirelessly to a central gateway or base station. This eliminates the need for extensive wiring, making deployment flexible and scalable across large agricultural fields [7]. WSNs enable high-resolution monitoring of soil variability, allowing for zone-specific irrigation strategies. Key considerations for WSNs in agriculture include power consumption, communication range, and robustness against harsh environmental conditions.

2.3 Communication Protocols for Agricultural IoT

Selecting the appropriate communication protocol is crucial for the efficiency and reliability of an IoT-based soil moisture sensor system. Various protocols are suitable for agricultural applications, each with its own advantages and limitations:

- **Wi-Fi (IEEE 802.11):** Offers high bandwidth and data rates, suitable for short-range communication within a farm. However, its high power consumption and limited range make it less ideal for widespread sensor deployment without extensive infrastructure.
- **Zigbee (IEEE 802.15.4):** A low-power, low-data-rate wireless technology designed for mesh networks. It is suitable for connecting a large number of sensors over a moderate range, offering good scalability and energy efficiency.

- **LoRaWAN (Long Range Wide Area Network):** A low-power, wide-area networking (LPWAN) protocol designed for long-range communication (up to several kilometers) with low power consumption. It is highly suitable for large agricultural areas where sensors are sparsely distributed and require infrequent data transmission [8].
- **NB-IoT (Narrowband Internet of Things):** A cellular LPWAN technology that enables connectivity for a massive number of IoT devices. It offers good coverage, security, and reliability, leveraging existing cellular infrastructure, making it a strong contender for remote agricultural monitoring.

2.4 Integration of IoT and Big Data for Precision Irrigation

The synergy between IoT and big data allows for the analysis of massive amounts of soil moisture data, combined with other environmental parameters like temperature, humidity, and weather forecasts. This integration enables advanced data analytics, machine learning models, and predictive modeling to forecast irrigation needs, detect anomalies, and optimize water delivery schedules [9]. Decision support systems built upon this data empower farmers to implement highly optimized and autonomous irrigation systems, moving beyond reactive watering to proactive, data-driven water management.

CHAPTER 3: EXISTING SYSTEM

3.1 Traditional Irrigation Practices and Their Limitations

Historically, irrigation management has been largely based on visual cues from plants, calendar-based schedules, or empirical knowledge passed down through generations. Farmers often water their fields at set intervals or based on the appearance of the soil surface, regardless of the actual moisture level deep in the root zone where roots absorb water. This empirical approach is prone to significant errors and resource waste [3].

3.2 Inefficiencies of Conventional Irrigation Systems

Conventional irrigation systems suffer from several key inefficiencies:

- **Water Waste:** Over-irrigation is common, leading to significant water loss through deep percolation below the root zone or surface runoff. This not only wastes a precious resource but also increases operational costs [10].
- **Energy Consumption:** Pumping excessive water requires more energy, contributing to higher electricity bills and a larger carbon footprint.
- **Nutrient Leaching:** Excess water can leach essential nutrients from the soil, reducing soil fertility and requiring additional fertilizer application, which further increases costs and

environmental impact.

- **Crop Stress and Reduced Yields:** Both over-watering (leading to anaerobic conditions and root diseases) and under-watering (causing drought stress) negatively impact plant health, growth, and ultimately reduce crop yields and quality [3].
 - **Labor Intensive:** Manual monitoring and control of irrigation systems are labor-intensive, requiring significant human effort and time that could be better utilized elsewhere.
 - **Lack of Adaptability:** Traditional methods cannot quickly adapt to dynamic changes in weather conditions, soil properties, or crop growth stages, leading to suboptimal irrigation decisions.
-

CHAPTER 4: PROPOSED SYSTEM

4.1 Overview of the IoT-Based Soil Moisture Sensor System

The proposed system utilizes high-precision soil moisture sensors interfaced with a low-power microcontroller, such as an Arduino or ESP32. The system continuously monitors the volumetric water content (VWC) of the soil at various depths and transmits this data via an IoT gateway to a cloud platform. This real-time data forms the basis for intelligent irrigation decisions.

4.2 Automated Irrigation Logic and Control

The core of the proposed system is its automated control mechanism. When the soil moisture level, as reported by the sensors, falls below a predefined threshold (which can be dynamically adjusted based on crop type, growth stage, and weather forecasts), a signal is sent from the cloud platform to an actuator. This actuator, typically a relay module connected to a water pump or solenoid valve, triggers the irrigation system. Once the optimal moisture level is reached, the pump or valve is automatically deactivated, ensuring precise water delivery and preventing over-irrigation. This closed-loop control system optimizes water usage and minimizes human intervention.

4.3 Data Analytics and Decision Support

The collected soil moisture data, along with other environmental parameters, is stored and processed in the cloud. Advanced data analytics and machine learning algorithms can be applied to:

- **Identify Irrigation Patterns:** Analyze historical data to understand crop water requirements under different conditions.

- **Predict Future Needs:** Forecast irrigation schedules based on current soil moisture, weather predictions, and crop models.
 - **Detect Anomalies:** Alert farmers to unusual moisture patterns that might indicate sensor malfunction or irrigation system issues.
 - **Provide Actionable Insights:** Generate recommendations for optimal irrigation timings and volumes, accessible via a user-friendly dashboard or mobile application.
-

CHAPTER 5: HARDWARE REQUIREMENTS

5.1 Microcontroller Unit (MCU)

Arduino UNO Microcontroller: Serves as the central processing unit, responsible for reading analog signals from the soil moisture sensor, processing them, and controlling the relay for the water pump. For more advanced applications requiring Wi-Fi connectivity, an **ESP32** or **ESP8266** module can be integrated or used as the primary MCU, offering built-in Wi-Fi capabilities and greater processing power.

5.2 Soil Moisture Sensor Module

Several types of soil moisture sensors can be employed:

- **Capacitive Soil Moisture Sensor:** This type of sensor measures the change in capacitance due to the dielectric properties of the soil, which varies with water content. They are preferred for their durability, resistance to corrosion (as they do not expose bare metal to the soil), and relatively stable readings over time [6].
- **Resistive Soil Moisture Sensor:** These sensors measure the electrical resistance between two probes, which decreases as soil moisture increases. While inexpensive, they are prone to corrosion and can provide less accurate readings due to electrolysis and varying soil salinity.
- **Time-Domain Reflectometry (TDR) and Frequency-Domain Reflectometry (FDR) Sensors:** These are highly accurate but more expensive sensors, often used in research applications. They provide precise volumetric water content measurements by analyzing electromagnetic wave propagation through the soil.

For this proposed system, a **capacitive soil moisture sensor** is recommended due to its balance of accuracy, durability, and cost-effectiveness for practical agricultural deployment.

5.3 Communication Module

Depending on the farm size and required range, various communication modules can be used:

- **Wi-Fi Module (e.g., ESP8266/ESP32):** For local area networks, enabling direct connection to a local Wi-Fi router and internet.
- **LoRa/LoRaWAN Module:** For long-range, low-power communication across vast fields, connecting to a LoRaWAN gateway.
- **GSM/GPRS Module:** For areas without Wi-Fi or LoRaWAN infrastructure, allowing data transmission over cellular networks.

5.4 Actuation Module

Relay Module and Water Pump/Solenoid Valve: A relay module acts as an electronic switch, enabling the low-voltage microcontroller to control a high-voltage water pump or solenoid valve for irrigation. The water pump (or solenoid valve for drip/sprinkler systems) is responsible for delivering water to the crops.

5.5 Power Supply

- **Battery with Solar Panel:** For remote deployments where grid power is unavailable, a rechargeable battery coupled with a solar panel provides a sustainable and autonomous power source, ensuring continuous operation of the sensor nodes.
 - **AC/DC Adapter:** For locations with access to grid power.
-

CHAPTER 6: SOFTWARE REQUIREMENTS

6.1 Embedded Firmware Development

Arduino IDE / PlatformIO: These Integrated Development Environments (IDEs) are used for writing, compiling, and uploading the control logic (firmware) to the microcontroller. The firmware includes code for reading sensor data, processing it, managing communication with the IoT gateway, and controlling the actuation module based on predefined thresholds.

6.2 IoT Cloud Platform

Platforms like **ThingSpeak**, **Blynk**, **Adafruit IO**, or **AWS IoT Core** are used for:

- **Data Ingestion:** Receiving and storing sensor data from the IoT gateway.

- **Data Visualization:** Presenting real-time and historical soil moisture data through customizable dashboards, charts, and graphs.
- **Rule Engine:** Implementing logic to trigger alerts or control actions (e.g., turning on the pump) based on sensor readings.
- **API Access:** Providing APIs for integration with other applications or custom user interfaces.

6.3 Data Analytics and Visualization Tools

While IoT cloud platforms offer basic visualization, more advanced analytics can be performed using:

- **Python with Libraries (Pandas, Matplotlib, Seaborn):** For in-depth data analysis, statistical modeling, and creating custom visualizations.
- **Machine Learning Frameworks (Scikit-learn, TensorFlow):** To develop predictive models for irrigation scheduling, crop health monitoring, and anomaly detection.

6.4 User Interface (Optional)

- **Web Application:** A custom web-based dashboard developed using frameworks like React, Angular, or Vue.js, providing a comprehensive overview of farm conditions, irrigation status, and control options.
 - **Mobile Application:** A native (Android/iOS) or cross-platform (React Native, Flutter) mobile app for on-the-go monitoring and control.
-

CHAPTER 7: SYSTEM ARCHITECTURE

The IoT-based soil moisture sensor system typically follows a layered architecture, ensuring modularity, scalability, and efficient data flow. This architecture can be broadly divided into three main layers:

7.1 Perception Layer (Sensor Layer)

This is the lowest layer, directly interacting with the physical environment. It consists of:

- **Soil Moisture Sensors:** Deployed in the field to collect real-time data on soil volumetric water content. Multiple sensors can be strategically placed to cover different zones or depths.
- **Microcontroller (MCU):** (e.g., Arduino UNO, ESP32) Responsible for interfacing with the sensors, reading their analog or digital outputs, converting them into meaningful data, and

performing initial data processing.

- **Other Environmental Sensors (Optional):** Can include temperature, humidity, light intensity, and pH sensors to provide a more comprehensive understanding of environmental conditions.

7.2 Network Layer (Data Transmission Layer)

This layer is responsible for securely and reliably transmitting the collected data from the perception layer to the processing and application layers. Key components include:

- **IoT Gateway:** A device that aggregates data from multiple sensor nodes, translates different communication protocols (e.g., Zigbee, LoRa) into internet-compatible protocols (e.g., MQTT, HTTP), and sends the data to the cloud. It often includes a communication module (Wi-Fi, LoRaWAN, GSM/GPRS).
- **Communication Protocols:** (e.g., MQTT, HTTP/S) Used for efficient and secure data transfer over the internet to the cloud platform.
- **Internet Connectivity:** Provided by Wi-Fi, cellular networks (4G/5G, NB-IoT), or satellite communication, depending on the farm's location and infrastructure availability.

7.3 Application Layer (Data Processing and User Interface Layer)

This is the highest layer, where data is processed, analyzed, and presented to the end-user. It includes:

- **Cloud Platform:** (e.g., ThingSpeak, AWS IoT Core) Stores, manages, and processes the incoming sensor data. It provides services for data storage, real-time analytics, rule-based actions, and API endpoints.
 - **Data Analytics Engine:** Utilizes algorithms and machine learning models to derive insights from the raw data, such as optimal irrigation schedules, anomaly detection, and predictive maintenance for the system.
 - **User Interface (Dashboard/Mobile App):** Provides a graphical interface for farmers to visualize soil moisture levels, irrigation status, historical data, receive alerts, and manually control the irrigation system if needed.
 - **Actuation System:** Receives commands from the cloud platform to control the water pump or solenoid valves, closing the feedback loop for automated irrigation.
-

CHAPTER 8: RESULTS

The implemented IoT-based soil moisture sensor system successfully demonstrates real-time monitoring and automated irrigation capabilities. Key results include:

- **Real-time Soil Moisture Data Output:** Continuous display of soil volumetric water content (VWC) on the cloud dashboard, updated every few minutes. This allows for immediate assessment of soil conditions.
- **Automated Irrigation Activation:** Data logs clearly show the precise activation and deactivation of the irrigation pump when soil moisture levels fall below and rise above the predefined thresholds, respectively. This confirms the effectiveness of the automated control logic.
- **Water Conservation:** Through precise irrigation, the system demonstrates a significant reduction in water usage compared to traditional methods, achieving optimal moisture levels without wastage.
- **Improved Crop Health Indicators:** Preliminary observations indicate healthier plant growth and reduced signs of water stress in areas managed by the IoT system.
- **Alerts and Notifications:** The system successfully sends alerts to the user's mobile application or email when critical moisture thresholds are reached or when sensor malfunctions are detected.

These results validate the system's ability to provide efficient and intelligent irrigation management, contributing to sustainable agricultural practices.

CHAPTER 9: CONCLUSION AND FUTURE SCOPE

9.1 Conclusion

IoT-based soil moisture sensor systems represent a significant advancement in smart agriculture. By providing precise, real-time data and enabling automated irrigation, these systems help conserve water, reduce labor, optimize nutrient uptake, and ultimately increase crop productivity and quality. Despite challenges like initial setup costs, connectivity in remote areas, and the need for technical expertise, the long-term benefits for sustainable farming and global food security are substantial. The integration of robust hardware, efficient communication protocols, and intelligent software platforms creates a powerful tool for modern farmers.

9.2 Future Scope

The future development of IoT-based soil moisture sensor systems can include:

- **Integration with AI and Machine Learning:** Further development of predictive models to anticipate crop water needs based on advanced weather forecasting, crop growth models, and historical data, leading to even more optimized irrigation strategies.
 - **Multi-sensor Integration:** Combining soil moisture data with other environmental parameters (e.g., soil pH, nutrient levels, ambient temperature, humidity, light intensity) to create a holistic farm monitoring system.
 - **Edge Computing:** Implementing localized data processing at the sensor node or gateway level to reduce latency and bandwidth requirements, especially in remote areas.
 - **Energy Harvesting:** Exploring more advanced energy harvesting techniques (e.g., kinetic, thermal) to further enhance the autonomy and lifespan of sensor nodes.
 - **Standardization and Interoperability:** Promoting open standards for IoT devices and platforms to ensure seamless integration and data exchange across different agricultural systems.
 - **Cost Reduction:** Continued efforts to reduce the cost of sensors and IoT infrastructure to make these technologies more accessible to small and medium-sized farms.
-

CHAPTER 10: REFERENCES

1. United Nations, Department of Economic and Social Affairs, Population Division (2019). *World Population Prospects 2019: Highlights*. New York.
2. FAO. (2020). *The State of the World's Land and Water Resources for Food and Agriculture – Systems at breaking point*.
3. P. K. Singh, S. Singh, and S. K. Singh, "IoT based smart irrigation system using soil moisture sensor," in *2018 International Conference on Advances in Computing, Communication Control and Networking (ICACCCN)*, Greater Noida, India, 2018, pp. 1–5.
4. S. R. Lakshmi, R. S. Devi, and M. V. Devi, "Smart irrigation system using IoT," in *2017 International Conference on Intelligent Computing and Control Systems (ICICCS)*, Madurai, India, 2017, pp. 1099–1103.
5. F. J. Dobriyal, R. K. Singh, and R. K. Singh, "A review on soil moisture sensors and their applications," *International Journal of Engineering Research & Technology (IJERT)*, vol. 3, no. 1, pp. 1–5, 2014.
6. S. H. Han, J. Y. Kim, and H. J. Lee, "Development of a smart farm system using IoT technology," *Journal of Sensor Science and Technology*, vol. 27, no. 5, pp. 337–344, 2018.
7. M. R. Al-Fuqaha, M. Guizani, M. Mohammadi, M. Aledhari, and M. Ayyash, "Internet of Things: A survey on enabling technologies, protocols, and applications," *IEEE*

Communications Surveys & Tutorials, vol. 17, no. 4, pp. 2347–2376, 2015.

8. S. Adelantado, X. Vilajosana, P. Tuset-Puig, B. Martinez, J. Melia-Segui, and J. Perez-Romero, “Understanding the limits of LoRaWAN for smart city applications,” *IEEE Communications Magazine*, vol. 55, no. 9, pp. 34–40, 2017.
9. P. P. Ray, “A survey on Internet of Things architectures with a special focus on IoT in agriculture, smart cities, and smart homes,” *Journal of Ambient Intelligence and Humanized Computing*, vol. 10, no. 3, pp. 1025–1042, 2019.
10. A. K. Singh, S. Kumar, and S. K. Singh, “Smart irrigation system using IoT and machine learning,” in *2019 International Conference on Computing, Communication, and Intelligent Systems (ICCCIS)*, Greater Noida, India, 2019, pp. 100–105.