

- Q.28 Explain the procedure for GSM measurement of fabric.
- Q.29 Calculate warp and weft cover factor of a fabric if EPI is 30, PPI is 45 and count of warp is 40^s Ne and weft is 30^s Ne.
- Q.30 How CSP is measured? Discuss in brief.
- Q.31 What are the precautions to be taken while taking fabric sample?
- Q.32 What do you mean by serviceability? Write the factors which affects serviceability.
- Q.33 Describe the working principle of crease recovery tester.
- Q.34 What is bending length? Write the formula for flexural rigidity.
- Q.35 Write principle of fabric thickness tester.

5th Sem / Text. Desgn
Subject:- Testing and Quality Control - II

Time : 3Hrs.

SECTION-A

Note: Multiple choice questions. All questions are compulsory (10x1=10)

- Q.1 In a diaphragm bursting strength tester_____ is used to burst the fabric.
- a) Liquid b) Gas
- c) Both A & B d) None
- Q.2 Hanging loop method is used to test
- a) Crimp b) Pilling
- c) Stiffness d) None
- Q.3 The length of the fabric requires to bend a fabric to a fixed angle under its own weight is known as
- a) Crimped length b) Bending length
- c) Fabric length d) None
- Q.4 Count strength Product is also known
- a) GSM b) MSP
- c) CSP d) None
- Q.5 The specimen size for testing pilling in ICI pilling box is

SECTION-D

Note: Long answer type questions. Attempt any two questions out of three questions. (2x10=20)

- Q.36 Explain bursting strength tester and its working with the help of a diagram.
- Q.37 Define fabric stiffness and flexural rigidity. Explain Shirley stiffness tester and its working.
- Q.38 Write common fabric defects with their causes and remedies.

- a) 9 inches x 9 inches b) 5 inches x 5 inches
c) 15 inches x 15 inches d) None
- Q.6 Anvil and pressure foot are parts of _____ instruments.
- a) Tensile strength tester
b) Tearing strength tester
c) Fabric thickness tester
d) None
- Q.7 Picks per Inch of a fabric is also called as
- a) TPI b) PPI
c) EPI d) CPI
- Q.8 Chances of pilling are more in fabrics which are made from
- a) Low twisted yarns b) High twisted yarns
c) Filament yarns d) None
- Q.9 Sizing is done to improve the
- a) Yarn fineness b) Yarn strength
c) Yarn length d) None
- Q.10 When there is a missing weft in a fabric it is called as
- a) Double Pick b) Missing end
c) Miss pick d) None

SECTION-B

Note: Objective type questions. All questions are compulsory. (10x1=10)

Q.11 Write full form of GSM.

- Q.12 Describe Crimp.
- Q.13 Define fabric Handle.
- Q.14 Write the name of instrument used to measure pilling of fabric.
- Q.15 Define tensile strength.
- Q.16 List any three fabric defects.
- Q.17 Revealed stripe test method is used to test _____ strength. (Fiber/Fabric)
- Q.18 Define fabric stiffness.
- Q.19 Write the full form of CRL and CRE.
- Q.20 Define elongation at break percentage.

SECTION-C

Note: Short answer type questions. Attempt any twelve questions out of fifteen questions. (12x5=60)

- Q.21 Differentiate between cut strip and revealed strip method of fabric strength testing.
- Q.22 Explain the working principle of ICI pill box tester.
- Q.23 Describe any five factors responsible for pilling.
- Q.24 Discuss the method to measure bursting strength of a fabric.
- Q.25 Explain the working principle of single yarn strength tester.
- Q.26 How the calibration of tearing Strength Tester is done before using it?
- Q.27 Describe the method to measure drape of a fabric.