Proceedings of the Third International Conference on Augmented Intelligence and Sustainable Systems (ICAISS-2025)
IEEE Xplore Part Number: CFP25CB2-ART; ISBN: 979-8-3315-0724-4

2025 Third International Conference on Augmented Intelligence and Sustainable Systems (ICAISS) | 979-8-3315-0724-4/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICAISS61471.2025.11042234

AI-Driven Health Monitoring using Wearable Devices for Physical and Mental Well-Being

1st Kwesha Shah
Dept. of Computer Engineering
Mukesh Patel School of Technology Management & Engineering, SVKM's NMIMS
Mumbai, India
kwesha9999@gmail.com

2nd Gargi Nikam
Dept. of Computer Engineering
Mukesh Patel School of Technology Management & Engineering, SVKM's NMIMS
Mumbai, India
nikamgargi2003@gmail.com

3rd Devin Shah
Dept. of Computer Engineering
Mukesh Patel School of Technology Management & Engineering, SVKM's NMIMS
Mumbai, India
dvs.college25@gmail.com

4th Srivaths Thorve
Dept. of Computer Engineering
Mukesh Patel School of Technology Management & Engineering, SVKM's NMIMS
Mumbai, India
sriclg209@gmail.com

5th Shakila Shaikh
Dept. of Computer Engineering
Mukesh Patel School of Technology Management & Engineering, SVKM's NMIMS
Mumbai, India
shakilashaikh48@gmail.com

***Abstract*—This research investigates a health monitoring system that will cater to the physical and mental well-being using wearable devices, Internet of Things (IoT), AI-driven analytics and machine learning. While traditional wearable health applications focus on individual health indicators (e.g., heart rate, step count), this study integrates those with other indicators of mental and physical wellness and provides a more expansive evaluation. Implementing multiple machine learning models including Random Forest and Long Short-Term Memory (LSTM) for predicting stress levels, calorie requirements, and blood pressures. The technology will inform lifestyle choices for the user through personalized health insights. The system allows tracking both mood and stress markers, as well as providing recommendations to the users based on their health metrics. This encourages users to grasp the dynamic connection between their mental and physical well-being by developing a proactive and comprehensive approach to health.**

***Index Terms*—Wearable Technology, Internet of Things, Machine Learning, Health Monitoring**

I. Introduction

The integration of wearable technology, the Internet of Things (IoT), and machine learning (ML) has significantly transformed health monitoring, offering new opportunities for personalized physical and mental well-being management. Traditional health applications primarily focus on tracking isolated metrics such as heart rate or step count, which often limits their capacity to provide personalized health insights [3, 6]. With increasing understanding of the interaction between mental and physical health, there seems to be an urgent necessity for systems that take a more effective approach towards health [2, 12].

This study proposes a wearable health monitoring system that integrates multiple physiological and psychological indicators, utilizing advanced machine learning models such as Long Short-Term Memory (LSTM) and Random Forest. By analyzing real-time data from wearable devices, the system predicts critical health parameters by correlating blood pressure, stress levels, caloric requirements, etc to eventually give recommendations to users suited to their needs [4, 7, 9].

Reliability in our system is achieved through the continuous monitoring [6, 10, 22]. of health parameters facilitated by wearable devices and IoT infrastructure. The use of advanced machine learning models like LSTM and Random Forest further enhances reliability by enabling the detection of anomalies and providing consistent analysis of temporal health data. We aim to reduce the gap in current health monitoring technologies by offering actionable insights into the dynamic relationship between mental and physical health [5, 13].

II. Background

The current developments in wearable health monitoring are chiefly powered by the introduction of the Internet of Things (IoT) and machine learning (ML), which enable what are basically fitness trackers and smartwatches to gather various physiological data such as heart rate, blood pressure, and activity levels to allow real-time insights [3, 6]. With the aid of IoT systems, these gadgets bring data aggregation in one place for remote health management and different alternatives to traditional healthcare, which is resource-intensive [11]. The ML techniques, including LSTM networks and Random Forest classifiers, serve to reinforce wearable systems by providing timely analysis of time-series data in medical diagnoses such as blood pressure estimation, stress detection, and caloric prediction [7, 9, 17]. At the same time, however, current systems seem unable to bring these features together in one

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

integrated software platform for physical or mental health [2, 15].

The mutual influence of mental and physical health is particularly imperative since stress as well as emotional states do in fact exercise an enormous influence over metrics such as heart rate and blood pressure [5, 12]. These parameters, separated from each other, contribute to a traditional way of thinking, whereas their low levels of relevance based on laboratory assessment alone do not position the real impact onto current action scenarios [13, 15]. Besides, the reliance of IoT networks upon cloud storage raises privacy concerns as it entails a risk for unauthorized access and limits usability for some clientele in view of a smartphone-centric interface [6, 10, 11, 22]. This work aims at proposing an effective approach for monitoring physical and mental health and addressing concerned issues of privacy, security, and accessibility in wearable IoT technologies integrated with state-of-the-art ML programming to satisfy their critical demands in health monitoring [9, 22].

A. Objectives

The objectives of this study are:

- Develop a system that collects and fuses data in real-time regarding physiological metrics like blood pressure [23] and heart rate [18], as well as indicators of mental health such as mood and stress levels [19] through wearable devices [3][5].
- Utilization of machine learning models, such as long short term memory (LSTM) and Random Forest, to predict health measures (e.g., BP, caloric needs, stress levels) that will enable users to know the early warnings of possible health risks [7][4].
- Provide personalized recommendations for each user regarding their health data so that healthy decision-making is encouraged and physical and mental health management is proactive [8][9].
- Address issues of privacy concerning data and reliance on specific devices in order to make wearable health monitoring systems more secure and accessible [10][6].
- Establishing the models of relationships and interactions between physical and mental factors like stress and BP will contribute to improving health knowledge in the view of the interconnectedness of body and mind [2][12].

B. Significance and Scope

This study is well-positioned to confront significant challenges that emerge in the development of wearable health monitoring, primarily with regard to extensive data collection and predictive modeling that is taken to another level. Such an approach provides an integrated platform for personal health monitoring with an emphasis on both aspects: the mental and the physical; with recognition of the influence of psychological well-being on physical conditions. One essential aspect of the whole approach is to enable users of wearable health monitoring devices, particularly with mental disorders like stress, anxiety, and mood, to receive real-time actionable insights and recommendations towards better health management [1][4][6].

Moreover, the integration of IoT and ML in the project makes health management easier, especially for the high-risk populations of population-wide-related ailments such as hypertension. The project includes development and assessment of a mobile health app that integrates data derived from wearable devices for real-time tracking of physiological (BP and heart rate) and psychological factors (mood and stress). Although the app handles a wide range of health monitoring needs, it focuses mainly on preventive health and mental wellness for users sensitive to proactive health care [2][3][5]. The study examines different limitations of data accuracy; device dependence; data privacy and provides recommendations for the advancement of reliability and security in wearable health technology [5][6].

III. Literature Review

A. Existing Research

Research in wearable health monitoring and machine learning has made strides in enhancing real-time health insights. Machine learning models for hypertension and blood pressure (BP) estimation provide insights into BP risk factors and use physiological data to model risks associated with high blood pressure [1]. Mental health monitoring is also prominent, as wearable devices detect stress [20] by tracking physiological responses to psychological stressors, addressing a key aspect of mental well-being [2].

IoT-based health systems, especially those on Android, show promise in providing accessible patient monitoring and real-time data management [3]. Wearable sensors are applied for tasks such as calorie tracking, emotion detection, and cardiovascular monitoring, with ML models that link physiological signals to health conditions [4][5]. Advanced algorithms like Long Short-Term Memory (LSTM) networks enhance reliability for continuous monitoring, supporting real-time patient tracking and critical anomaly detection [7]. Additionally, cloud-based IoT applications in health facilitate remote care and issue emergency alerts, beneficial for patient safety [8]. ML models are also useful for hypertension prediction using large datasets, and they tackle challenges like energy efficiency and data privacy in wearables [9][10][11].

B. Gaps in the Literature

Although all these strides in wearable health technologies exist, there are a few disadvantages. Most research on hypertension detection focuses on one of the two—either physiological or clinical data—but not both, which could yield better prediction and reliability across multiple populations [1]. Still, wearable devices have been applied for monitoring mental health, although most of the research regarding them focuses mainly on stress detection but not a general classification of mood states. These create gaps in comprehensive tracking of mental health.

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

TABLE I
SUMMARY OF LITERATURE REVIEW

Sr No.	Existing Research	Gap	How This Research Fills These Gaps
1	Focus on hypertension detection using clinical and physiological data [1].	Few studies combine clinical and physiological data for BP detection.	Combines both data types to improve BP monitoring.
2	Stress detection with wearable devices [2].	Lack of classification for signals and disorders.	Provides classifications and a comprehensive review of mental health monitoring.
3	IoT-based health systems with Android apps exist but lack modern microcontrollers [3].	Limited use of modern technology and data handling.	Introduces microcontrollers and Firebase for real-time data handling.
4	Calorie prediction models focus on specific activities or datasets [4].	Lack of generalizable models across activities and groups.	Develops a broader model applicable across activities and demographics.
5	Links stress with BP, but often under lab conditions [5].	Stress not evaluated in real-world scenarios.	Uses real-life data collection to refine BP predictions based on emotions.
6	IoT benefits in healthcare but with issues in security and interoperability [6].	Limited focus on managing security and monitoring.	Reviews IoT challenges and security solutions in healthcare systems.
7	ML and LSTM used for health monitoring in various contexts [7].	Limited use of LSTM for real-time patient monitoring.	Applies LSTM for real-time anomaly detection in health monitoring.
8	IoT systems monitor vital signs but lack predictive health measures [8].	Lack of early detection and emergency alerts.	Implements an IoT system with emergency alerts for real-time monitoring.
9	ML for hypertension prediction using clinical data [9].	Limited use of large, diverse datasets.	Uses large datasets and neural networks to improve prediction accuracy.
10	ML in wearables for health monitoring has privacy and security issues [10].	Sparse research on energy efficiency in wearables.	Discusses energy efficiency and reliability in wearable ML systems.
11	IoT systems rely on smartphones, affecting usability [11].	Limited solutions for direct cloud data transmission.	Proposes direct cloud transmission from wearables.
12	Links mental health with hypertension, but findings are mixed [12].	Contradictory results and lack of longitudinal analysis.	Resolves contradictions with a large cohort study.
13	AI-enhanced wearable sensors for health are emerging [13].	Few studies address AI for data accuracy and privacy.	Reviews AI for enhancing data accuracy and privacy in wearables.
14	Reviews step counting and its health implications [14].	Lack of standardization in step-counting devices.	Proposes protocols to improve step-counting accuracy.
15	ML for stress classification and vital signs forecasting [15].	Limited predictive frameworks integrating multiple vitals.	Implements ML models for real-time stress and vital sign prediction.

Some authors in the literature propose IoT-based healthcare monitoring systems with real-time data handling. Such technologies are built on past technologies like microcontroller design; therefore, they are not effectively applicable in the modern context. In addition, the techniques wearables use to quantify steps are not standardized and, therefore, not likely to offer similar validity and reliability for physical activity parameters between heterogeneous studies [14]. Furthermore, the prediction models of stress and BP tend to be developed for the challenges of the laboratory only and do not include characteristics that meet the criteria for rigorous scaling and real-world relevance in accurate monitoring at a population level [5]. The bottlenecks prevail in direct data transmission frameworks for wearables, particularly those which circumvent smartphone dependency, and the demand for scalable, reliable IoT health monitoring solutions answering to this limitation.

Another notable limitation is in predictive modeling: although LSTM and other ML models [26] are showing promising results, the integration of serial data for comprehensive health insights is still limited. However, most systems do not integrate multiple vitals in real time, which limits the predictive power of wearable devices in real-life settings [7]. Furthermore, some studies have actually come up with conflicting results as regards the link of mental health to hypertension, whereby long-term and full understanding of BP's relationship with mental well-being is under limited longitudinal data [12]. In addition, wearable sensors bring up privacy issues, as the processing of real-time health data in the context of artificial intelligence raises many users' data security concerns [13].

C. How This Research Fills These Gaps

The current research overcomes previous studies' shortcomings by incorporating clinical and physiological data in the better prediction of blood pressure and detection of hypertension [1][9]. Further, the proposed system maximizes the use of IoT-based, real-time monitoring systems with the most advanced microcontrollers and Firebase to rapidly handle data, building upon the wearables in health monitoring applications with further ease of access and more functionality [3][8]. It also presents a unified mental health monitoring framework through the adoption of classification techniques that monitor

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

different vital signs related to mental health, such as levels of stress and states of mood, which can yield a more fine-grained and actionable understanding of health status [2][5].

Furthermore, using advanced predictive models such as LSTM, the continuous monitoring of patients is supported with events of anomaly detection and timely alerts that are so valuable in real-world critical health scenarios [7]. This work also concerns data privacy and security, representing those wearable technologies enabled by AI, giving equal importance to data accuracy and security in order for users to build confidence in real-time health data tracking. With personalized recommendations on activity and lifestyle changes, this study goes beyond health monitoring to proactively guide users towards achieving well-being goals for managing conditions of stress and mental health. The capability to track, in real-time, emotion and blood pressure establishes a proactive approach for dealing with the management of health conditions, enabling preventive care for hypertension and mood-related health issues.

IV. Methodology

In this study, the methodology has been performed based on integrating machine learning models with wearable IoT devices for real-time health monitoring, considering estimated parameters of blood pressure, mood, and the level of stress, including metabolic rate estimation. Combining these physiological data with socio-demographic data, predictive models involved are LSTM networks used for sequential data analysis [7], which can enhance the accuracy of circadian rhythm-dependent BP predictions and stress monitoring in real-world settings as shown in [1]. The monitoring process is achieved through the continuous collection of physiological data by wearable devices and its transmission to a cloud-based back-end. This enables centralised data access and analysis without constant reliance on a mobile application. The principal aim of AI, especially machine learning, is to analyse this real-time data to spot patterns, predict health parameters, and identify anomalies. It also enables the delivery of personalised health insights as well as activity recommendations based on individual user data and predicted health status.

A. Research Design

The research design will be a multi-phase, observational study reviewing the effectiveness of machine learning models in wearable health applications. Physiological and socio-demographic data are first gathered through IoT-enabled wearable devices and an Android mobile application, developed specifically to capture health metrics such as BP, heart rate, and stress levels in real time [3]. After data collection, predictive models such as LSTM and Random Forest will be implemented to predict the estimation of BP and caloric needs. Historical health data improves the accuracy of predictions of these types of models [4][9].The study will determine abnormal health conditions as revealed through sequential patterns found in the data, which could then facilitate early detection and intervention as necessary [7]. The application will monitor much more than just physiological measures; one's mood and stress levels will be self-reported, thereby capturing a much broader spectrum of mental well-being [5].

B. Data Collection Techniques



Fig. 1. System Architecture and Implementation.

Wearable devices are used to monitor health conditions, with smartwatches and fitness wristbands serving as a source for data acquisition and transmission of relevant information including blood pressure, heart rate, and physical activity. This data is then securely transmitted to the cloud [1][3][8] via established IoT protocols. In the cloud, our AI algorithms process and analyse this real-time data, integrating it with any self-reported information on mood and stress levels. Based on this comprehensive analysis, the system generates timely insights and personalised recommendations that are made available to the user. Additionally, the users are expected to input self-reported variables like mood and perceived stress levels through periodic surveys via web or paper-based questionnaires. These responses can then be integrated as mental health information along with physiological data provided by wearables using standardized classifications to ensure consistent storage and intelligibility [2][5]. During on-boarding, participants complete surveys to gather demographic information (age, gender, and occupation) and lifestyle habits (e.g., sleep, nutrition, and physical activity) that may affect the physiological measures captured. Their information is sent to the cloud to refine accuracy in analyzing the data acquired from wearables, and subjects are also allowed to amend their lifestyle information from time to time, permitting analysis of behaviors and health in real-time [9][11]. To ensure security and privacy, end-to-end encryption is implemented

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

as a protocol whenever data is sent to the cloud from the wearable devices. Encryption establishes protection against data breaches and shields any incoming storage from unauthorized access [10]. In addition, the researchers obtain the user's consent prior to data collection so as to respect ethical transparency requirements. Any personal identifiers are to be anonymized, thus ensuring privacy and compliance with health data regulations [6].

C. Sampling Methods and Size

Publicly available datasets are used in the study to build and train machine learning models on different health parameters. These datasets consist of a combination of varying demographic and physiological information such as age, lifestyle habits, and wearable device metrics [11, 9]. The selected datasets allow flexible modeling of blood pressure trend prediction and mood-state observation [12, 15]. Accordingly, the range and demography must match the datasets to achieve consistent data quality.

D. Data Analysis Process

- Data Preprocessing: To improve the precision of our predictions, rigorous data preprocessing techniques were applied to the collected data. This included cleaning the data to remove noise and errors, and normalising self-reported metrics to ensure consistency across datasets. Furthermore, our machine learning models, including LSTM and Random Forest, were trained and validated on relevant datasets to optimise their parameters and enhance the accuracy of their predictions. Self-reported metrics like mood and stress levels get normalized onto a common scale so that they will remain compatible with ML models and consistent across datasets [2][12]. For the missing data points we employed imputation techniques like mean imputation or exclusion in order to preserve data integrity in analysis, especially in the case of time series datasets, where continuous availability of data carries a lot of value [5].
- Model Training and Validation: The selection of machine learning algorithms was crucial for our system's functionality. Long Short-Term Memory (LSTM) networks[7][15] were chosen for their ability to analyse sequential time-series data, making them ideal for predicting blood pressure trends and detecting patterns in stress levels. For the classification of mood states, we employed the Random Forest algorithm, known for its robustness and efficiency in handling complex datasets. These models are accountable to the test data on accuracy metrics, including Mean Absolute Error (MAE) and Root Mean Square Error (RMSE), to ascertain their performance reliability and optimize parameters [16].
- Correlation and Regression Analysis: The correlation analysis seeks to determine the relationships between independent and dependent variables, such as the effect of stress on BP or the relationship between mood and HR. This insight demonstrates how physiological and psychological variables interplay [5][12]. Simple multivariate regression models analyze complex interactions by considering the combined effects of demographics and lifestyle variables, such as sleep and diet, on health metrics, allowing one to understand more deeply and clearly the latent variables [9].
- Predictive Trend Analysis and Anomaly Detection: Predictive trend models offer to dynamically model the state of the user's health and other vital indicators, such as blood pressure and stress, which provide the needed foresight for preventive monitoring. The models are basically concerned with the unmasking of anomalous events where some risk is detected so that the right interventions can be channeled ahead [1][3]. Anomaly detectors also use thresholds to monitor deviations in the normal patterns of BP or heart rate, for instance, issuing real-time alerts that, when necessary, prompt the user to consult a medical practitioner [7].
- Longitudinal Analysis and Insights Generation: Longitudinal data analysis involved tracking the changes occurring in the health measurements across periods long enough for avoiding misleading inferences. Some examples in this realm include long-term effects of stress on BP that remain hidden when one analyzes shorter time periods [5][12]. Model retraining of regular intervals is another way in which user feedback and incorporation of the newest data could assure improvement of prediction accuracy and relevance over time [11].
- Reporting and Visualization: Data insights are presented to the user via intuitive visualizations, such as graphs illustrating changes in BP, mood state, and stress state over time, seeking to engage the user in providing an understanding for the health indicators involved [5]. For the researcher, an extended report is generated, summarizing the performance of the model, the statistical results, and the utilization patterns in constructing information back to improve the effectiveness further and other research initiatives [6].

V. Result and Analysis

The findings here prove the feasibility and efficacy of the proposed health monitoring application in providing correct health predictions, detection of stress, and personalized wellness recommendations. This analysis has been performed based on the performance testing of the models, evaluation of feedback from users, and comparison studies with conventionally adopted methods, pertaining to various physiological and psychological parameters mentioned in the literature.

- Blood Pressure Prediction Accuracy The achieved Mean Squared Error (MSE) of 122.95 and R-squared (R^2) score of 0.856 in our LSTM-based blood pressure prediction model indicate strong predictive capability. An R^2 of 0.856 suggests our model could explain approximately 85.6% of the variance in blood pressure, highlighting its effectiveness in capturing the underlying trends in this physiological data. Such accuracy underscores the

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

```
Classification Report for LSTM Model:
              precision    recall  f1-score   support

           0       0.86      0.89      0.87     10948
           1       0.88      0.86      0.87     10948

    accuracy                           0.87     21896
   macro avg       0.87      0.87      0.87     21896
weighted avg       0.87      0.87      0.87     21896
```

Fig. 2. Classification Report.

possibility of LSTM networks providing users with valuable insight into their blood pressure prediction, which surely is a step up for most presently available wearable technologies that give primarily reactive monitoring. The result concurs with previous studies' results, showing that LSTM models are an apt choice for sequential data (shown in Fig. 2), such as blood pressure time series, because they learn long-term dependencies [1, 2, 7]. This predictive capability allows users to take preventive measures against hypertension, tackling one of the key gaps found in most of the current wearable technologies that often do not avail their users of predictive insights [5, 9].

- Stress Detection and Mood Analysis The Random Forest classifier [17, 24] for stress detection [18, 25, 30] gave an accuracy of 99%, where real-time stressors were correctly identified from the wearable inputs given in [10]. In addition, mood detection using Gradient Boosting presented 91% accuracy, which also conformed well with user-dependent emotional states as per [3,11]. The results affirm the previous works when wearables give insights (shown in Fig 3) into mental health also aligned with various ML algorithms [4,15]. High accuracy of both models suggests that wearables are capable of being actively involved in mental health monitoring to satisfy identified gaps in integrating their mental health metrics within health applications [13, 16].

```
Enter your current Blood Pressure (BP) reading: 130
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 50ms/step
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 38ms/step
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 38ms/step
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 40ms/step
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 36ms/step
Forecasted BP for next 5 days: [142.57559814453126, 146.34073486328126, 147.4906494140625, 147.829638671875, 147.92984924316406]
Detected Stress Level: no stress
Detected Emotion: Happy, Relaxed, Motivated
Recommended Activity: Maintain a healthy lifestyle with regular activities.
```

Fig. 3. Forecasted BP, Stress Level, Emotion and recommended activity.

- Personalized Activity Recommendations Based on the user's mood and levels of stress, the application's recommendation system has suggested specialized activities that will enhance the mental well-being with an accuracy of 91% when identifying suitable activities [3, 8].

```
  blood_pressure  calories_burned  time cal_type  \
0            Low               49    25   Normal
1           High              501     7     High
2            Low              497    23     High
3            Low              334    15     High
4           High               78    19   Normal

                                 insights
0                       Intake more calories
1  Regulate and Modify Exercise accordingly
2     Overexertion, Replenish and cooldown
3     Overexertion, Replenish and cooldown
4                          Improper Exercise
```

Fig. 4. Insights based on calories burned and blood pressure.

- Caloric and Basal Metabolic Rate (BMR) Estimation While the estimation of caloric needs from the model has been a valid foundation of daily energy needs [27], results proved that room for improvement exists within the model to result in more accurate estimations. The estimations currently obtained give insights (shown in Fig. 4) on an overall basis but would be likely even more tailored to accommodate specific variances between metabolic rates among different individuals [3, 9]. This had been expected and has been recognized in similar studies related to models for the prediction of caloric needs [4, 5, 7, 28].
- Usability and Real-Time Monitoring User feedback appears to indicate that the incorporation of wearables into an easy-to-use interface effectively bridges the gap between complex health data and actionable insights, as discussed by [6, 10, 11]. The continuous monitoring capability [13] of the app enables users to track both physical and mental health parameters whereby a large number of users feel much better aware and proactive to handle their health accordingly [7,8,15].

LSTM is selected overall due to its competency in sequential data handling that makes it suitable for physiological health monitoring. Unlike random forest and gradient boosting, which excel in classification tasks while lacking temporal awareness, LSTM captures long-term dependencies in time-series data, such as blood pressure trends. It shows that LSTM achieved 85.6% accuracy for blood pressure prediction that is comparable to the GRU (85.5%) (shown in Fig.5) ; however, LSTM is generally preferred for its superior handling of vanishing gradients when dealing with longer sequences. While random forest and gradient boosting typically perform better in stress and emotion detection tasks, attaining accuracies of 99% and 91%, respectively, these models aren't inherently meant for continuous physiological data analysis. Further, SVM and MLP show relatively low accuracy for emotion recognition, 62% and 60%, respectively, which in turn makes them more unreliable for real-time applications. LSTM serves as a comprise between accuracy and adaptability, ensuring better generalization across different health monitoring tasks, hence becomes the preferred model for an integrated system therein. These results show that wearable technology com-

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

bined with machine learning [21][26] offers solid predictive health insights that have been proven to influence positive health outcomes and active self-care practices positively [2, 5, 11, 14].



Fig. 5. Comparison of Model Accuracies.

VI. Conclusion

The developed health monitoring system effectively bridges gaps in current wearable technology by offering comprehensive, personalized health insights, including blood pressure prediction, stress detection, mood analysis, and activity recommendations. Leveraging advanced machine learning models such as LSTM and Random Forest, the app achieves high accuracy in predicting physiological metrics and mental health indicators, aligning with previous research on the potential of wearables in proactive health management.

This system empowers users to take charge of their health by integrating physical and mental health metrics into a unified, user-friendly interface. In addition, the system's personalized recommendations contribute to mental well-being, promoting better lifestyle choices and self-awareness, which places due emphasis on effective health solutions. While promising, the current results exhibit certain limitations in data privacy, caloric estimation accuracy, and the system's reliance on wearable devices, which indicate points for refinement.

References

[1] Erick Martinez-Ríos, Luis Montesinos, Mariel Alfaro-Ponce, Leandro Pecchia, "A review of machine learning in hypertension detection and blood pressure estimation based on clinical and physiological data," Biomedical Signal Processing and Control, vol. 68, 2021, 102813, ISSN 1746-8094, https://doi.org/10.1016/j.bspc.2021.102813.

[2] Nannan Long, Yongxiang Lei, Lianhua Peng, Ping Xu, Ping Mao, "A scoping review on monitoring mental health using smart wearable devices," Mathematical Biosciences and Engineering, vol. 19, no. 8, pp. 7899-7919, 2022, doi: 10.3934/mbe.2022369.

[3] Alruwaili, Madallah & Siddiqi, Muhammad & Farid, Kamran & Azad, Muhammad & Alanazi, Saad & Khan, Asfandyar & Khan, Abdullah, "A Health Monitoring System Using IoT-Based Android Mobile Application," Computer Systems Science and Engineering, vol. 47, pp. 2293-2311, 2023, doi: 10.32604/csse.2023.040312.

[4] Tarek Aziz, Mohammad & R, Sudheesh & Pecho, Renzon & Khan, Nayeem & Hasna Era, Akba Ull & Chowdhury, MD, "Calories Burnt Prediction Using Machine Learning Approach," Current Integrative Engineering, vol. 1, pp. 29-36, 2023, doi: 10.59762/cie5703905411202310311303 23.

[5] Gordon AM, Mendes WB, "A large-scale study of stress, emotions, and blood pressure in daily life using a digital platform," Proc Natl Acad Sci U S A, vol. 118, no. 31, e2105573118, Aug 3, 2021, doi: 10.1073/pnas.2105573118, PMID: 34326265, PMCID: PMC8346904.

[6] Abdulmalek, S.; Nasir, A.; Jabbar, W.A.; Almuhaya, M.A.M.; Bairagi, A.K.; Khan, M.A.-M.; Kee, S.-H, "IoT-Based Healthcare-Monitoring System towards Improving Quality of Life: A Review," Healthcare, vol. 10, no. 1993, 2022, https://doi.org/10.3390/healthcare10101993.

[7] Pavithra, D & Parameswaran, T & Choudhry, Mani & Amrutha, S & Deepa, T & Kiruthiga, R, "Application of LSTM Networks for Continuous Patient Monitoring and Anomaly Detection in Wearable Health Devices," Indian Journal Of Science And Technology, vol. 17, pp. 3909-3921, 2024, doi: 10.17485/IJST/v17i37.2600.

[8] S, Jayakumar & R, Ranjith & R, Tejswini & S, Kavil, "IoT Based Health Monitoring System," 2021, 10.3233/APC210140.

[9] D. LaFreniere, F. Zulkernine, D. Barber and K. Martin, "Using machine learning to predict hypertension from a clinical dataset," 2016 IEEE Symposium Series on Computational Intelligence (SSCI), Athens, Greece, 2016, pp. 1-7, doi: 10.1109/SSCI.2016.7849886.

[10] Saad, H.S., Zaki, J.F.W. & Abdelsalam, M.M, "Employing of machine learning and wearable devices in healthcare system: tasks and challenges," Neural Comput & Applic, vol. 36, pp. 17829–17849, 2024, https://doi.org/10.1007/s00521-024-10197-z.

[11] Wan, J., A. A. H. Al-awlaqi, M., Li, M. et al., "Wearable IoT enabled real-time health monitoring system," J Wireless Com Network, vol. 298, 2018, https://doi.org/10.1186/s13638-018-1308-x.

[12] Schaare, H.L., Blöchl, M., Kumral, D. et al., "Associations between mental health, blood pressure and the development of hypertension," Nat Commun, vol. 14, 1953, 2023, https://doi.org/10.1038/s41467-023-37579-6.

[13] Shajari, S.; Kuruvinashetti, K.; Komeili, A.; Sundararaj, U, "The Emergence of AI-Based Wearable Sensors for Digital Health Technology: A Review," Sensors, vol. 23, no. 9498, 2023, https://doi.org/10.3390/s23239498.

[14] Bassett DR Jr, Toth LP, LaMunion SR, Crouter SE, "Step Counting: A Review of Measurement Considerations and Health-Related Applications," Sports Med, vol. 47, no. 7, pp. 1303-1315, Jul 2017, doi: 10.1007/s40279-016-0663-1, PMID: 28005190, PMCID: PMC5488109.

[15] Bhavani T, VamseeKrishna P, Chakraborty C, Dwivedi P, "Stress Classification and Vital Signs Forecasting for IoT-Health Monitoring," IEEE/ACM Trans Comput Biol Bioinform, vol. 21, no. 4, pp. 652-659, Jul-Aug 2024, doi: 10.1109/TCBB.2022.3196151, Epub 2024 Aug 8, PMID: 35921342.

[16] R. Zhao, J. Wang, R. Yan and K. Mao, "Machine health monitoring with LSTM networks," 2016 10th International Conference on Sensing Technology (ICST), Nanjing, China, 2016, pp. 1-6, doi: 10.1109/ICSensT.2016.7796266.

[17] Kaur, P., Kumar, R. & Kumar, M, "A healthcare monitoring system using random forest and internet of things (IoT)," Multimed Tools Appl, vol. 78, pp. 19905–19916, 2019, https://doi.org/10.1007/s11042-019-7327-8.

[18] P. Madhuri, N. Krishnaiah, P. Anandan, U. N. Nisha, A. K. Tamrakar and P. Dileep, "Machine Learning Approach to Patient Health and Stress Monitoring System," 2022 IEEE 2nd Mysore Sub Section International Conference (MysuruCon), Mysuru, India, 2022, pp. 1-4, doi: 10.1109/MysuruCon55714.2022.9972478.

[19] Gideon Vos, Kelly Trinh, Zoltan Sarnyai, Mostafa Rahimi Azghadi, "Generalizable machine learning for stress monitoring from wearable devices: A systematic literature review," International Journal of Medical Informatics, vol. 173, 2023, 105026, ISSN 1386-5056, https://doi.org/10.1016/j.ijmedinf.2023.105026.

[20] Fatma M. Talaat and Rana Mohamed El-Balka, "Stress monitoring using wearable sensors: IoT techniques in medical field," Neural Comput. Appl, vol. 35, no. 25, pp. 18571–18584, Sep 2023, https://doi.org/10.1007/s00521-023-08681-z.

[21] Alazzam, Malik Bader, Alassery, Fawaz, Almulihi, Ahmed, "[Retracted] A Novel Smart Healthcare Monitoring System Using Machine Learning and the Internet of Things," Wireless Communications and Mobile Computing, vol. 5078799, 7 pages, 2021, https://doi.org/10.1155/2021/5078799.

[22] Al-Atawi, A.A.; Alyahyan, S.; Alatawi, M.N.; Sadad, T.; Manzoor, T.; Farooq-i-Azam, M.; Khan, Z.H, "Stress Monitoring Using Machine Learning, IoT and Wearable Sensors," Sensors, vol. 23, no. 8875, 2023, https://doi.org/10.3390/s23218875.

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.

[23] Quadir, M.A., Bhardwaj, S., Verma, N., Sivaraman, A.K., Tee, K.F, "IoT-Based Mental Health Monitoring System Using Machine Learning Stress Prediction Algorithm in Real-Time Application," in Venkataraman, N., Wang, L., Fernando, X., Zobaa, A.F. (eds) Big Data and Cloud Computing. ICBCC 2022. Lecture Notes in Electrical Engineering, vol 1021, Springer, Singapore, 2023, https://doi.org/10.1007/978-981-99-1051-_16.

[24] Mohamed Abd Al-Alim, Roaa Mubarak, Nancy M. Salem, Ibrahim Sadek, "A machine-learning approach for stress detection using wearable sensors in free-living environments," Computers in Biology and Medicine, vol. 179, 108918, 2024, https://doi.org/10.1016/j.compbiomed.2024.108918.

[25] Moser, M.K.; Ehrhart, M.; Resch, B, "An Explainable Deep Learning Approach for Stress Detection in Wearable Sensor Measurements," Sensors, vol. 24, 5085, 2024, https://doi.org/10.3390/s24165085.

[26] Kwesha Shah, Gargi Nikam, Vaibhav Zambre, Soni Sweta; Aspect based sentiment analysis on student feedback using machine learning techniques. AIP Conf. Proc. 20 September 2024; 3242 (1): 060003. https://doi.org/10.1063/5.0234991

[27] Talaat, F.M., El-Balka, R.M. Stress monitoring using wearable sensors: IoT techniques in medical field. Neural Comput & Applic 35, 18571–18584 (2023). https://doi.org/10.1007/s00521-023-08681-z.

[28] Aziz, Mohammad Tarek, et al. "Calories burnt prediction using machine learning ap-proach." Current Integrative Engineering 1.1 (2023): 29-36.

[29] Mandal, A., Paradkar, M., Panindre, P., & Kumar, S. (2023). AI-based Detection of Stress using Heart Rate Data obtained from Wearable Devices. Procedia Computer Science, 230, 749-759. https://doi.org/10.1016/j.procs.2023.12.129.

[30] Han, H. J., Labbaf, S., Borelli, J. L., Dutt, N., & Rahmani, A. M. (2020). Objective stress monitoring based on wearable sensors in everyday settings. Journal of Medical Engineering & Technology, 44(4), 177–189. https://doi.org/10.1080/03091902.2020.1759707.

Authorized licensed use limited to: SRM Institute of Science and Technology Kattankulathur. Downloaded on January 23,2026 at 14:00:13 UTC from IEEE Xplore. Restrictions apply.